

INCH-POUND

MIL-F-48370A (AR)
 AMENDMENT 3
02 October 1999
 SUPERSEDING
 AMENDMENT 2
 19 January 1990

MILITARY SPECIFICATION

FUZE, M934E6, HYBRID MICROCIRCUIT FOR

This amendment forms a part of Military Specification MIL-F-48370A, dated 1 July 1985, and is approved for use by the U.S. Army Armaments, Research, Development, and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1.1 Specifications and standards:

Specifications, Military:

Delete "MIL-C-26074" in its entirety.

Delete "MIL-M-38510" and substitute "MIL-PRF-38534 – Hybrid Microcircuits, General Specification for"

PAGE 2

* 2.1.1:

Federal Specifications, delete "QQ-S-766" in its entirety.

Standards, delete "MIL-STD-202" in its entirety.

* 2.1.2 Other Government documents, add the following:

"SAEAMS2404 – Nickel, Electroless, Plating

ASTM A 240 – Steel, Stainless, Plate, Sheet, and Strip for
 Pressure Vessels, Heat-Resisting Chromium and Chromium-Nickel"

MIL-F-48370A (AR)
AMENDMENT 3

PAGE 3

3.1.4a:

Delete first sentence and substitute “Iron, Nickel, Cobalt alloy (KOVAR) per MIL-I-23011, Class I, ASTM F-15.”

* Delete “MIL-C-26074” in its entirety and substitute “SAEAMS2404”

* 3.1.4b, Delete “QQ-S-766, Class 304” in its entirety and substitute “ASTM A240, Type 304”

3.1.5, Delete first sentence and substitute “The lead material shall consist of Iron, Nickel, Cobalt alloy (KOVAR) per MIL-I-23011, Class I, ASTM F-15.”

PAGE 4

3.2.3, Add the following sentence at the end of the paragraph “Aluminum shall be used for wire bonding on substrate interconnects.”

* 3.2.4, Delete in its entirety and substitute the following:

“3.2.4 Preseal bake. The hybrids shall be baked at a minimum of 150 degrees C in a vacuum/nitrogen atmosphere, min 0.04 Torr., for 24 hours minimum immediately prior to sealing.”

PAGE 6

* 3.3.11, Delete in its entirety.

* 3.4e, Delete “code identification” and substitute “CAGE Code”.

* 3.4.2, Delete “MIL-STD-202, method 215” and substitute “MIL-STD-883,method, 2015”.

* 3.5, Delete “MIL-M-38510” and substitute “MIL-PRF-38534”.

PAGE 8

* 3.7, Delete “MIL-M-38510” and substitute “MIL-PRF-38534”.

MIL-F-48370A (AR)
AMENDMENT 3

TABLE I. First article inspection

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9297034/9297063
	Microcircuit, Digital – Firing Circuit Microcircuit, Digital – Safing & Arming				NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION/CHARACTERISTICS	NO. OF SAMPLE UNITS	VERIFICATION LEVEL	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE/INSPECTION METHOD
	<p style="text-align: center;"><u>GROUP III – 1/</u></p> <p>Mechanical shock Vibration Constant Acceleration Seal Final Electrical Internal Visual</p>	15		<p>3.3.6 3.3.7 3.3.14 3.3.4 3.3.16 3.3.17</p>	<p>MIL-STD-883 MIL-STD-883 MIL-STD-883 MIL-STD-883 Detailed drawing 4.5.3</p>
	<p style="text-align: center;"><u>GROUP IV – 1/</u></p> <p>End Point Electrical <u>4/</u> High Temperature Storage Final Electrical</p>	20		<p>3.3.15 3.3.1 3.3.16</p>	<p>Detailed drawing MIL-STD-883 Detailed drawing</p>
<p>NOTES:</p> <p><u>4/</u> Ten of the units shall be tested at high temperature; the other ten units shall be tested at low temperature.</p> <p><u>5/</u> Electrical rejects may be used provided their construction and processing through final seal is identical to that of the device.</p>					

PAGE 13

* 4.4.2.1, Classification of characteristics, delete major defect 102 in its entirety.

* 4.4.2.2, Classification of characteristics:

Delete minor defect 201 and 202 in their entirety and substitute the following:

Category	Exam	“No of	AQL	Req.	Para. Ref/
<u>Minor</u>	<u>or Test</u>	<u>Sample</u>	<u>or</u>	<u>Para.</u>	<u>Insp. Method</u>
201	Physical Dimensions	2	100%	3.1.1	Gage or Calipers
202	Marking permanence	4		3.4.2	MIL-STD-883”

MIL-F-48370A (AR)
AMENDMENT 3

Delete notes 3 and 4 and substitute the following:

“Note 3: A PDA of 7 per MIL-PRF-38534 (Appendix F) or 32 accept/0 reject applied to wirebounds shall be used for ACC/REJ limits. Equal number of wirebounds shall be tested of each hybrid. Sample size shall be 2 hybrids.

Note 4: Accept/Reject limits applied to the hybrid lead solderability shall be 46 accept/4 reject. Sample size shall be 2 hybrids.”

PAGE 18

* 4.5.2, Delete in its entirety.

* 6.2.1, Delete in its entirety and substitute the following:

“6.2.1 Contract data requirements. Data specified in 3.2.2 and 3.2.5 of this document and in paragraphs A.3.2.5 and A.3.3 of MIL-PRF-38534, Appendix A, will be required for data delivery as specified in section C of the contract.”

* 6.3, Delete in its entirety and substitute the following:

“6.3 Submission of designs for approval. See MIL-A-48078. Submit equipment designs, as required, to US Army Tank Automotive Command, Armament Research, Development, and Engineering Center, TACOM-ARDEC, ATTN: AMSTA-AR-QAA-R, Picatinny Arsenal, NJ 07806-5000.”

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1336-0035)