

MIL-F-5577B
 SUPPLEMENT 1
 27 MAY 1959

MILITARY SPECIFICATION

FITTINGS, TANK, POWERPLANT FLUID, REMOVABLE, GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-F-5577B, 27 May 1959, and has been approved by the Department of Defense and is mandatory for use by the Army, Navy Bureau of Aeronautics, and the Air Force.

2.01 SCOPE

This supplement lists the MS Standards which form a part of this specification.

MS MILITARY STANDARDS

MS29550-Flange, Attachment, Molded Tank, Flush, Full Molded, Oval, 6X10
 MS29551-Flange, Attachment, Molded Tank, Flush, Full Molded, Rectangular, 12 x 18
 MS29552-Flange, Attachment, Molded Tank, Flush and Recessed, Full Molded, Oval, 8 X 10
 MS29553-Cover, Access, Molded Tank, Oval, 8 x 10
 MS29551-Flange, Attachment, Molded Tank, Flush, Full Molded, Rectangular, 8.38 x 14.50
 MS29555-Cover, Access, Molded Tank, Rectangular, 8.38 x 14.50
 MS29556-Flange, Attachment, Molded Tank, Flush and Recessed, Full Molded, Oval, 10 x 16
 MS29557-Cover, Access, Molded Tank, Oval 10 x 16
 MS29558-Fitting, "O" Ring, Circular, Compression Type, Single Groove, Tank, Outward Pressure
 MS2955-Fitting, "O" Ring, Circular, Through Bolt Type, Single Grooves Tank, Outward Pressure
 MS29560-Fitting, "O" Ring, Circular, Threaded Insert Type, Single Groove, Tank, Outward Pressure
 MS29562-Flange, Attachment, Molded Tank, Thru Hole, Flush, "O" Ring, Rectangular, 10 x 16
 MS29563-Flange, Attachment, Molded Tank, Flush, "O" Ring, Rectangular, 10 x 16
 MS29561-Flange, Attachment, Molded Tank, Thru Hole, Flush, "O" Ring, Rectangular, 12 x 18
 MS29565-Flange, Attachment, Molded Tank, Flush, "O" Ring, Rectangular, 12 x 18
 MS29566-Flange, Attachment, Molded Tank, Thru Hole. Flush, "O" Ring, Oval, 8 x 12
 MS29567-Flange, Attachment, Molded Tank, Thru Hole, Flush "O" Ring, Oval, 10 x 16
 MS29568-Flange, Attachment, Molded Tank, Flush, "O" Ring, Oval
 MS29572-Cover, Access, Molded Tank, Rectangular 8.50 x 16.75
 MS29573-Flange, Attachment, Molded Tank, Two Plane, Flush, Full Molded, Circular

MIL-F-5577B

MS MILITARY STANDARDS-Continued

MS29574-Flange, Attachment, Molded Tank, Recessed, Full Molded, Oval, 6.00 X 10.00

MS29575-Flange, Attachment, Molded Tank Recessed, Full Molded, Rectangular, 8.50 x 16.75

MS29576-Flange, Attachment, Molded Tank, Flush and Recessed, Full Molded, Circular

MS29577-Cover, Access, Molded Tank, Oval, 6.00 x 10.00

MS29578-Cover, Access, Molded Tank, Rectangular, 12.00 x 18.00

MS29579-Flange, Attachment, Molded Tank, Recessed, Two Plane, Circular

MS29580-Cover, Access, Molded Tank, Circular, 5.12 DIA

MS29581-Flange, Attachment, Molded Tank, Flush and Recessed, Full Molded, Oval, 3.56 x 5.70 (Booster Pump)

MS29582-Flange, Attachment, Molded Tank, Recessed, Full Molded, Rectangular 12.00 x 18.00

MS33581-Fitting, Tank, "O" Ring, Configuration

MS33595-Cover, Access, Molded Tank, Full Molded, General Features of Construction

MS33596-Flange, Attachment, Molded Tank, Full Molded General Features of Construction