

MIL-F-85731
14 April 1986
SUPERSEDING
MS 14108
15 October 1982
MIL-C-172 (IN PART)
8 December 1958
(See 6.4)

MILITARY SPECIFICATION

FASTENER, POSITIVE LOCKING, ELECTRONIC EQUIPMENT, GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers positive locking fasteners intended for use in aircraft to secure electronic line replaceable units (LRUs).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments, (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Naval Air Engineering Center, Systems Engineering and Standardization Department (Code 93), Lakehurst, NJ 08733-5100, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 5340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MIL-F-85731

SPECIFICATIONS
FEDERAL

QQ-P-35	Passivation Treatments for Corrosion Resistant Steel
QQ-P-416	Plating, Cadmium (Electrodeposited)
PPP-B-566	Box, Folding, Paperboard
PPP-B-576	Box, Wood, Cleated, Veneer, Paper Overlaid
PPP-B-585	Box, Wood, Wirebound
PPP-B-591	Boxes, Shipping, Fiberboard, Wood-Cleated
PPP-B-601	Boxes, Wood, Cleated Plywood
PPP-B-621	Box, Wood, Nailed and Lock Corner
PPP-B-636	Box, Shipping, Fiberboard
PPP-B-665	Boxes, Paperboard, Metal Edge and Components
PPP-B-676	Boxes, Setup
PPP-H-1581	Hardware (Fasteners and Related Items), Packaging of
PPP-T-60	Tape, Packaging, Waterproof

MILITARY

MIL-P-116	Preservation, Methods of
MIL-H-6088	Heat Treatment of Aluminum Alloys
MIL-H-6875	Heat Treatment of Steels (Aircraft Practices), Process For
MIL-A-8625	Anodic Coatings, for Aluminum and Aluminum Alloys
MIL-L-8937	Lubricant, Solid Film, Heat Cured, Corrosion Inhibiting, NATO Code S-1738
MIL-L-10547	Liner, Case and Sheet, Overwrap, Water Vaporproof Or Waterproof, Flexible

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
-------------	---

MIL-F-85731

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U. S. Military Property
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
DOD-STD-1788	Avionics Interface Design Standard

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturer's in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B117 Method of Salt Spray (Fog) Testing

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Specification sheet. The individual item requirements shall be as specified herein and in accordance with the applicable specification sheet. In the event of any conflict between the requirements of this specification and the specification sheet, the latter shall govern.

3.2 Qualification. The fasteners furnished under this specification shall be products which are qualified for listing on the applicable Qualified Products List at the time set for opening of bids (see 4.3 and 6.3).

3.2.1 Requalification. Requalification will be required in the event any change is made in the product design, material, heat treatment, finish or lubrication.

3.2.2 Retention of qualification. To maintain status on the Qualified Product List, certification shall be submitted at two year intervals to indicate continued compliance with the requirements of this specification (see 4.3.1).

3.3 Material. The material shall be as specified herein in the applicable specification sheet.

MIL-F-85731

3.3.1 Heat treatment.

3.3.1.1 Aluminum alloy. Heat treatment of aluminum alloy components shall be in accordance with MIL-H-6088.

3.3.1.2 Corrosion resistant steel (CRES) and alloy steel. Heat treatment of CRES and alloy steel components shall be in accordance with MIL-H-6875.

3.3.2 Protective treatment. Fastener components shall be plated or treated as specified herein or in the applicable specification sheet or standard.

3.3.2.1 Passivation. Fastener components fabricated from corrosion resistant steel shall be passivated in accordance with QQ-P-35.

3.3.2.2 Surface oxide. After heat treatment of corrosion-resistant steel fastener components, all surface oxide shall be removed by a means that will produce no intergranular or surface corrosion.

3.3.2.3 Alloy steel. Fastener components fabricated from alloy steel shall be cadmium plated in accordance with QQ-P-416, Type II, Class 2.

3.3.2.4 Aluminum alloy. Fastener components fabricated from aluminum alloy shall be anodized in accordance with MIL-A-8625.

3.4 Design. The fastener is designed to secure line replaceable units (LRUs) in military aircraft. When used in conjunction with a mating holddown device, it will secure the LRU in a stable position in the aircraft (see 6.1).

3.5 Lubricant. When specified in the applicable specification sheet or standard, the lubricant used on the fastener shall be in accordance with MIL-L-8937.

3.6 Environmental requirements. The fasteners shall be capable of functioning without damage when subjected to the environmental conditions in 3.6.1 through 3.6.3.

3.6.1 Endurance. The fastener shall be capable of withstanding 2000 cycles (as described in 3.6.1.1) of locking and unlocking without degradation of performance (see 4.5.2).

3.6.1.1 Cycle. One complete performance of the fastener from zero pound to the preload poundage and then back to the initial zero poundage.

3.6.2 Corrosion. The fastener shall be capable of five (5) lock and unlock endurance cycles described in 3.6.1.1 after being subjected to the corrosion test (see 4.5.3).

3.6.3 Sand and dust. The fastener shall be capable of five (5) lock and unlock endurance cycles described in 4.5.2 after being subjected to the sand and dust test (see 4.5.4).

MIL-F-85731

3.6.4 Vibration and shock. The fastener shall not become loose or unlocked when subjected to the vibration and shock test (see 4.5.5).

3.6.5 Static load. The fastener shall meet the loads specified in the applicable specification sheet when subjected to the static load test (see 4.5.6).

3.6.6 Equipment interface. The unattached extractor front holddown assembly will not hang in a position that will interfere with the installation or removal of other equipment.

3.6.7 Thermal shock. The extractor front holddown shall maintain its functional characteristics during alternate exposure to extremities of high and low temperatures according to MIL-STD-202, Test Condition "B".

3.6.8 Fungus. The extractor shall demonstrate a resistance to fungus development according to MIL-STD-810, Method 508.1, Procedure I.

3.6.9 Fluid immersion. Clutch function, parts and spindle travel will not deteriorate after being immersed in MIL-N-5606 hydraulic fluid and MIL-L-7808 oil for eight hours.

3.6.10 Box lift during extraction. The fastener front holddown shall not allow more than 0.917 in. (5mm) of lift at the front end of the box.

3.7 Identification marking. The fasteners shall be marked for identification in accordance with the applicable specification sheet or standard and MIL-STD-130.

3.8 Workmanship. Workmanship shall be consistent with the type of product, finish and the class of thread fit specified. Sharp edges shall be broken; hanging burrs and slivers that might become dislodged during usage shall be removed

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Test equipment and inspection facilities. The manufacturer shall insure that test and inspection facilities of sufficient accuracy, quality and quantity are established and maintained to permit performance of required inspections.

MIL-F-85731

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

- a. Qualification inspection (4.3)
- b. Quality conformance inspection (4.4)

4.3 Qualification inspection. Qualification inspection shall be performed at a laboratory acceptable to the Government (see 6.3) on sample units produced with equipment and procedures normally used in production.

4.3.1 Sample. The qualification test samples shall consist of twenty units.

4.3.2 Inspection routine. Sample units shall be subjected to the qualification inspection specified in table I in the order shown.

TABLE I. Qualification inspection.

Inspection	Number of samples	Requirement paragraph	Test method paragraph
Visual and dimensional examination	3	--	4.5.1
Endurance	3	3.6.1	4.5.2
Corrosion	3	3.6.2	4.5.3
Sand and dust	3	3.6.3	4.5.4
Vibration and shock	4	3.6.4	4.5.5
Static load	4	3.6.5	4.5.6

4.3.3 Retention of qualification. To retain qualification, the contractor shall forward a report at two year intervals to the qualifying activity (see 6.3). The qualifying activity shall establish the initial reporting date. This qualification certification, signed by a responsible official of management shall attest that the manufacturer has the capability to produce fasteners under conditions equal to those existing at the time of the original approved listing.

4.3.4 Certified test report. The manufacturer shall furnish a certified test report showing that the manufacturer's product satisfactorily conforms to this specification. The test report shall include as a minimum actual results of the tests specified herein. When this report is submitted, it shall be

MIL-F-85731

accompanied by a dated drawing which describes the manufacturer's product by specifying all dimensions and tolerances, composition of materials selected, coating or plating applied, and the hardness. The manufacturer's part number for each size shall be included on the drawing.

4.4 Quality conformance inspections. Quality conformance inspections shall consist of the tests specified in table II.

TABLE II. Quality conformance inspections

Inspection	Requirement paragraph	Test method paragraph
Visual and dimensional examination	--	4.5.1
Endurance (5 cycles)	3.6.1	4.5.2
Corrosion (2 hours)	3.6.2	4.5.3

4.4.1 Inspection lot. The inspection lot shall be as defined in MIL-STD-105.

4.4.2 Sampling.

4.4.2.1 Sampling for quality conformance inspections. A random sample of each item shall be selected in accordance with MIL-STD-105, inspection level S-1, Acceptable Quality Level (AQL) of 1.5 percent defective. For visual examination, fasteners shall be selected in accordance with MIL-STD-105, inspection level 1, AQL of 2.5 percent defective.

4.4.3 Resubmitted inspection lots. Resubmitted inspection lots shall be in accordance with MIL-STD-105. A resubmitted inspection lot shall be inspected using a tightened inspection. Where the original acceptance number was zero, a sample size represented by the next higher sample size code letter shall be selected.

4.4.4 Manufacturer's inspection report. Each production lot of fasteners shall be accompanied by two copies of the manufacturer's inspection report signed by an authorized representative of the manufacturer. This report shall state that the fasteners are from a production lot(s) which was manufactured, inspected and accepted in accordance with requirements of this specification. The report shall identify the part number and the production lot number(s) and shall include all actual test results or certifications of conformance.

4.5 Test methods.

4.5.1 Visual and dimensional examination. The fasteners shall be examined for conformance to the requirements of this specification and the applicable specification sheet.

MIL-F-85731

4.5.2 Endurance. The fasteners shall be mounted in a suitable tray fixture, as defined in 3.6.1. During lock operation, a preload of 103 lbs to 126 lbs (460N to 560N) shall be exerted on each hook and maintain the reading as specified in DOD-STD-1788. During this test there shall be a check reading of the forces every 50 cycles. The force reading must be within the force tolerance range.

4.5.3 Corrosion. The fasteners shall be subjected to the salt spray (fog) test of ASTM B117 for 168 hours. Upon completion of this test, the samples shall be subjected to the endurance test of 4.5.2 for Five (5) cycles only.

4.5.4 Sand and dust. The fasteners shall be subjected to the sand and dust test of MIL-STD-810, Method 510.1. Upon completion of this test the samples shall then be subjected to the endurance test of 4.5.2 for five (5) cycles only.

4.5.5 Vibration and shock. The fasteners shall be subjected to the vibration and shock test of MIL-STD-810. For vibration, use Method 514.2, Procedure I, Curve E. For shock, use Method 516.2, Procedure I, Figure 516.2-2.

4.5.5.1 The test specimens shall be mounted in a fixture conforming to figure 1 using a 60 pound weight simulated "black box" (15.29 inches wide x 12.52 inches long x 7.64 inches high). Hooks shall be mounted as shown in figure 2.

4.5.6 Static load. The fastener shall be mounted to the tray containing the simulated black box as shown in figure 1. The fastener shall be subjected to the test specified in 4.5.5.1. Upon completion of the static load test the fastener shall be capable of one complete lock and unlock cycle as defined in 3.6.1.1.

4.6 Inspection and packaging. The sampling and inspection of the preservation, packing and container marking shall be in accordance with PPP-H-1581.

5. PACKAGING

5.1 Packaging.

5.1.1 Level A. The fasteners in a unit quantity of 1 each, of the same part number, shall be packaged in accordance with MIL-P-116, Method III.

5.1.2 Level C. The fasteners shall be packaged in accordance with commercial practice. When the quantity permits, twenty-five unit packages, or a multiple thereof, shall be packaged in intermediate containers conforming to PPP-B-566, PPP-B-676, or PPP-B-665. The gross weight of the intermediate containers conforming to PPP-B-665 shall not be greater than 20 pounds.

MIL-F-85731

5.2 Packing. Fasteners shall be packed level A or C, as specified (see 6.2).

5.2.1 Level A. Fasteners shall be packed in overseas wether resistant type boxes conforming to any of the following: PPP-B-585, Class 3; PPP-B-591; PPP-B-621; PPP-B-636. Gross weight of wood and wood-created boxes shall not be greater than 200 pounds; fiberboard boxes shall not be greater than the weight limitations of the box specification. Box closures shall be in accordance with the box specification and the appendix thereto. Boxes shall be provided with case liners conforming to MIL-L-10547, sealed in accordance with the appendix thereto. Case liners may be omitted when weather resistant fiberboard boxes conforming to PPP-B-636 are used, provided that all joints and seams are sealed with tape conforming to PPP-T-60, Type III, Class 1.

5.2.2 Level C. Fasteners shall be packed to ensure adequate protection against damage during direct shipment from the source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations and may be the supplier's commercial practice, if this practice meets the requirements of this level.

5.3 Marking. In addition to any special markings required by the contract, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.

6.1.1 Positive self-locking electronic equipment fastener. These fasteners are intended for general use in aircraft to secure electronic LRUs in their installed position. They are designed with knurled or fluted knobs for hand operation to:

- a. Eliminate the need to have hand tools available and
- b. Reduce the risk of overstressing the LRU, rack, tray or other fastener accessories. The fastener must be used in conjunction with rear holddown device with properly toleranced, dimensionally stable seating that positions the front fasteners so as to give proper load line angle (see applicable specification sheet).

6.1.2 Force limiting insertion, positive extraction electronic equipment fastener. These fasteners are intended for use in military aircraft. Their purpose is to secure electronic LRUs installed in compliance with DOD-STD-1788 Avionics Interface Design Standard, and for use with commercial avionics LRUs that are designed in compliance with ARINC specification 600. They are designed for hand operation through a calibrated, force-limiting clutch in the forward direction (insertion). When operated in the reverse direction (extraction) they withdraw the LRU from its mounting rack or tray, disengaging

MIL-F-85731




FIGURE 1. Equipment hook.




FIGURE 2. Equipment hook mounting.

MIL-F-85731

the rear-mounted connector with a controlled straight pull. In these applications, the connector shell is the rear holddown, with a properly toleranced, dimensionally stable, rack or tray to ensure that the front fasteners are correctly positioned.

6.1.3 Visual indicator. There shall be some form of clear visual indication that the extractor front holddown unit has been activated to its designated load (refer to MIL-F-85731/2).

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

- a. Title, number and date of this specification.
- b. Quantity.
- c. Level of packaging required (see 5.1).
- d. Lot sampling for quality conformance inspection (see 4.4).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for such products which are, at the time set for opening of bids, qualified for inclusion on the applicable Qualified Products List whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Naval Air Systems Command (AIR 5112), Department of the Navy, Code (AIR-530), Washington, DC 20361-5300 and information pertaining to qualification of products covered by this specification may be obtained from the Naval Avionics Center, 600 East 21st Street, Code B/714, Indianapolis, IN 46219-2189.

6.4 Supersession data. This specification, MIL-F-85731 and its associated slash sheets, supersedes MS14108 Fastener, Positive Self-Locking Case Mounting, Electronic Equipment, in its entirety. This specification also supersedes, in part, all paragraphs of MIL-C-172 Cases; Bases, Mounting; And Mounts, Vibration (For use with Electronic Equipment in Aircraft), which deal with locking devices.

Custodian:
Air Force - 11
Army - AV

Preparing activity:
Navy -AS
(Project No. 5340-1590)

Review activity:
DLA - IS

INSTRUCTIONS. In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (*DO NOT STAPLE*), and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer
Naval Air Engineering Center
Engineering Specifications and Standards Department
(ESSD), Code 93
Lakehurst, NJ 08733



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON, D.C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Air Engineering Center
Systems Engineering Standardization Department
(SESD), Code 93
Lakehurst, NJ 08733

ATTN: TJM (9322)



