

INCH-POUND

MIL-F-8815D  
AMENDMENT 1  
23 June 1995

MILITARY SPECIFICATION

FILTER AND FILTER ELEMENTS, FLUID PRESSURE, HYDRAULIC  
LINE, 15 MICRON ABSOLUTE AND 5 MICRON ABSOLUTE,  
TYPE II SYSTEMS; GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-F-8815D, dated 27 September 1976, and is approved for use by Departments and Agencies of the Department of Defense.

PAGE 29

4.7.2.6.2.1.1: Change last sentence to: "The flow test shall be performed using trichloroethylene as a test fluid using the following rates:"

PAGE 30

4.7.2.6.2.3.1(b): Delete in its entirety and substitute: "Degrease in trichloroethylene."

PAGE 31

4.7.2.6.2.3.1(d): Delete in its entirety and substitute: "Rinse the filter element in trichloroethylene."

4.7.2.6.2.3.1(e): Delete 1st and 2nd sentences and substitute:

"Ultrasonically clean the filter element in trichloroethylene for a period of 30 minutes. The trichloroethylene shall be filtered through a filter element have the filtration characteristics conforming to MIL-F-81836(AS)."

Custodians:

Army - AV  
Navy - AS  
Air Force -11

Preparing activity:

Navy - AS

(Project No. 1650-0521)

Review activities:

Army - MI  
Air Force - 71