

MIL-G-6032D  
08 April 1988  
AMENDMENT 1

# MILITARY SPECIFICATION

GREASE, PLUG VALVE, GASOLINE AND OIL RESISTANT,  
NATO CODE NUMBER G-363, METRIC

This amendment forms a part of military specification MIL-G-6032D, dated 29 June 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

Table I, sixth entry: Delete in its entirety and substitute the following:

<u>Characteristics</u>	<u>Limits</u>	<u>Test Paragraph</u>
"Unworked penetration (1/4 scale)		
Type I	20-72	4.6.2
Type II	16-24	4.6.2"

Table I, column 1, opposite "Storage stability: Unworked penetration":  
Delete ", maximum".

Table I, column 2, opposite "Storage stability. Unworked penetration":  
Delete "23" and substitute "16-24".

Custodians:  
    Army - ME  
    Navy - AS  
    Air Force - 68

Preparing Activity:  
    Navy -AS  
    (Project No. 9150-1012)

Review activities:  
    Army - AT  
    DLA - GS

User activities:  
    Army - AT  
    Navy - SH

International Interests:  
    NATO

AMSC N/A

FSC 9150

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.