





## MIL-G-6162/IC(AS)





## MIL-G-6162/IC(AS)

IDENTIFICATION OF ITEMS		
ITEM	MILITARY PART NUMBER	MAX. WEIGHT POUNDS
1/ STARTER-GENERATOR ASSY (CONSISTS OF ONE STARTER-GENERATOR, ONE MOUNTING PLATE, ONE MOUNTING CLAMP)	M6162/1-1	37.5
2/ STARTER-GENERATOR	M6162/1-2	36.0
MOUNTING PLATE	M6162/1-3	
MOUNTING CLAMP	M6162/1-4	

- 1/ M6162/1-1 IS REQUIRED FOR NEW AIRCRAFT PROCUREMENT  
 2/ FOR SPARES PROVISIONING M6162/1-2 SHALL BE PROVIDED

STARTER-GENERATOR DATA		
RATED VOLTAGE	30	VOLTS
RATED CURRENT	400	AMPERES
MINIMUM RATED SPEED	7,000	RPM
CONTINUOUS OPERATING SPEED	10,000	RPM
MAXIMUM SPEED FOR REGULATION	12,000	RPM
MINIMUM SPEED FOR REGULATION	7,470	RPM
OVERSPEED	14,000	RPM
REGULATED FIELD CURRENT (MAX)	8	AMPS
GENERATOR EFFICIENCY - 70 TO 100% LOAD-MIN	75	%
RATED STARTER TORQUE - 1100 TO 5500 RPM (SEE REQ 1 & FIG 2)		
STARTER NO LOAD SPEED MINIMUM	5700 ± 300	RPM
OVERHUNG MOMENT MAX	250	IN LB
SHEAR SECTION - SHAFT	1.750 ± .250	IN LB
DIRECTION OF ROTATION (VIEWED FROM FREE END)	CW	
MINIMUM NATURAL FREQUENCY	250	Hz
MAXIMUM STARTER INRUSH (5 SEC)	1,000	AMPERES

## REQUIREMENTS

- 1 FROM 1100 RPM TO 5500 RPM MOTOR TORQUE SHALL DECREASE
- 2 THE STARTER-GENERATOR SHALL INCLUDE A MAGNETIC SPEED SENSOR WHICH SHALL HAVE AN OUTPUT AS FOLLOWS
  - a 2.5 VOLT PEAK-TO-PEAK MINIMUM AT 6000 RPM INTO A 20K ± 10% OHM IMPEDANCE, WITH A FREQUENCY OF 1.2 KHZ
  - b 15 VOLTS PEAK-TO-PEAK MAXIMUM AT 12,000 RPM OPEN CIRCUIT, WITH A FREQUENCY OF 5.4 KHZ
  - c THE WAVE SHAPE OF THE SPEED SENSOR OUTPUT SHALL BE APPROXIMATELY SINUSOIDAL WITH A SMOOTH CROSS POINT AT ZERO VOLTS. THE WAVE SHAPE SHALL NOT BE FLAT AT THE CROSS OVER POINT
  - d SENSOR WIRES SHALL NOT INTERFERE WITH MOUNTING STUDS
- 3 COOLING - BLAST AIR FOR IN-FLIGHT OPERATION IS 6 INCHES H<sub>2</sub>O MIN. AND SELF-COOLED WITH FAN FOR GROUND OPERATION
- 4 EXTERNAL COLOR WHITE, CONFORMING TO FED-STD-595 COLOR NUMBER 17875
- 5 MOUNTING CLAMP TORQUE REQUIREMENTS - 70 IN LB
- 6 THE STARTER-GENERATOR SHALL MEET THE TEMPERATURE AND ALTITUDE REQUIREMENTS OF FIGURE 1 OF THIS SPECIFICATION SHEET
- 7 THE STARTER-GENERATOR SHALL INCLUDE A STANDARD SIZE TYPE A, B, OR H METAL NAMEPLATE IN ACCORDANCE WITH MIL-P-15074, SECURELY ATTACHED TO THE MACHINE. THE NAMEPLATE SHALL CONTAIN THE FOLLOWING INFORMATION:
 

DC STARTER-GENERATOR  
 RATED VOLTAGE - 30 VOLTS  
 RATED SPEED - 7000 TO 12000 RPM  
 RATED CURRENT - 400 AMPS  
 MILITARY PART NO - M6162/1-2  
 MANUFACTURER'S PART NO. OR MODEL NO.  
 MANUFACTURER'S NAME OR TRADEMARK  
 SERIAL NO -  
 FEDERAL STOCK NO -  
 DATE OF MANUFACTURE -  
 ACCEPTANCE STAMP -
- 8 STARTER-GENERATOR BEARINGS SHALL BE PACKED WITH KRYTOX 288AC LUBRICANT
- 9 THE STARTER-GENERATOR SHALL MEET ALL REQUIREMENTS FOR OPERATION WHEN CONNECTED WITH AN M23761/1-1 CONTROL PANEL AND TWO M23761/1-1 CURRENT TRANSFORMERS PER MIL-E-23761/1 OR AS MODIFIED HEREIN
- 10 THE STARTER-GENERATOR ASSEMBLIES M6162/1-1 AND -2 SHALL MEET THE VIBRATION AND SHOCK TESTS REQUIREMENTS OF MIL-E-81910
- 11 A NO LOAD SPEED OF 5700 ± 300 RPM SHALL BE ACHIEVED THROUGH SHUNT FIELD WEAKENING
- 12 THE STARTER-GENERATOR SHALL MEET THE EMI REQUIREMENTS OF MIL-E-81910, HOWEVER THE MAXIMUM ALLOWABLE CONDUCTED AND RADIATED EMISSION LIMITS ARE RELAXED BY 20dB
- 13 THE MILITARY PART NUMBER SHALL BE INDICATED ON THE MOUNTING PLATE AND CLAMP

## MIL-G-6162/IC (AS)

## TESTS:

1. FOR ALL TESTS WHICH REQUIRE MOUNTING THE STARTER-GENERATOR, THE STARTER-GENERATOR SHALL BE MOUNTED BY MEANS OF THE M6162/1-5 MOUNTING PLATE AND THE M6162/1-4 MOUNTING CLAMP.
2. THE MACHINE SHALL BE OPERATED AS A GENERATOR AT 30 VOLTS AND 400 AMPERES AT 7000, 7500, 10000, AND 12000 RPM. THE FIELD TEMPERATURE SHALL STABILIZE AT ALL CONDITIONS. TEMPERATURE STABILIZATION IS DEFINED AS NO MORE THAN A 2°C TEMPERATURE RISE IN A ONE HOUR PERIOD.
3. THE COMMUTATION OF THE MACHINE SHALL BE MEASURED UPON TEMPERATURE STABILIZATION. THERE SHALL BE NO MORE THAN NUMBER 1-1/2 SPARKING (FIGURE 5 MIL-G-6162) EXCEPT AT 400 AMPERE LOAD SPARKING UP TO NUMBER 3 WILL BE ALLOWED.
4. THE PEAK RIPPLE VOLTAGE APPEARING AT THE DC OUTPUT (STARTER-GENERATOR TERMINALS) SHALL NOT EXCEED 2.5 VOLTS ABOVE OR BELOW THE DIRECT CURRENT AVERAGE VOLTAGE FROM 0 TO RATED LOAD-CURRENT WHEN BEING CONTROLLED BY THE GCU.
5. THE STARTER SHALL DELIVER A CRANKING TORQUE WITHIN +5% OF FIGURE 2 VALUES.
6. THE STARTER-GENERATOR SHALL BE CAPABLE OF OPERATING AS A GENERATOR AND SUBJECTED TO THE FOLLOWING CONDITIONS DURING A 216 HOUR ENDURANCE TEST.

RUN	DURATION HOURS	CYCLES	GEN. LOAD (AMPS)	COOLING AIR SOURCE	TEMP °C	DEW POINT °C MAX	ALTITUDE (FT)
1	12	5	400	BLAST (6"H <sub>2</sub> O)	+40	-	SEA LEVEL
2	12	3	400	BLAST (1 4"H <sub>2</sub> O)	+40	-	SEA LEVEL
3	74	4	400	BLAST (6"H <sub>2</sub> O)	-55	-60	30000
4	12	2	200	BLAST (6"H <sub>2</sub> O)	-55	-60	30000

## NOTES


1. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES.
2. TOLERANCES ARE DECIMALS .XX ± .01 .XXX ± .005. ANGLES ± 0°30.
3. WHERE ONLY MAXIMUM DIMENSIONS ARE SHOWN THE PART NEED NOT HAVE THE SHAPE SHOWN BUT SHOULD BE CONTAINED WITHIN THE OUTLINE SHOWN.
4. REVISION LETTERS ARE NOT USED TO DENOTE CHANGES DUE TO THE EXTENSIVENESS OF THE CHANGES.

PREPARING ACTIVITY


NAVY - AS

PROJECT NO. 6115-N459

MIL-G-6162/1C(AS)

FIGURE 1. MAXIMUM AIR INLET TEMPERATURE

MIL-G-6162/1C(AS)

FIGURE 2. STARTER SPEED - TORQUE REQUIREMENT



STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL	
<p><b>INSTRUCTIONS:</b> This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.</p> <p><b>NOTE:</b> This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.</p>	
<p><b>DOCUMENT IDENTIFIER (number) AND TITLE</b></p> <p>MIL-G-6162/1C(AS) Starter-Generator</p>	
<p><b>NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER</b></p> <p> </p>	
<p> <input type="checkbox"/> VENDOR           <input type="checkbox"/> USER           <input type="checkbox"/> MANUFACTURER         </p>	
<p>1. <input type="checkbox"/> HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? <input type="checkbox"/> IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.</p> <p style="margin-left: 20px;">A. GIVE PARAGRAPH NUMBER AND WORDING</p> <p style="margin-left: 20px;">B. RECOMMENDED WORDING CHANGE</p> <p style="margin-left: 20px;">C. REASON FOR RECOMMENDED CHANGE(S)</p>	
<p>2. REMARKS</p> <p> </p>	
<p>SUBMITTED BY (Printed or typed name and address - Optional)</p>	<p>TELEPHONE NO.</p> <p>DATE</p>



OLD

DEPARTMENT OF THE NAVY  
Naval Air Engineering Center  
Lakehurst, New Jersey 08733

OFFICIAL BUSINESS  
PENALTY FOR PRIVATE USE \$300



NO POSTAGE  
NECESSARY  
IF MAILED  
IN THE  
UNITED STATES

**BUSINESS REPLY MAIL**

FIRST CLASS

PERMIT NO. 12503

WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Engineering Specifications and Standards  
Department (Code 93 )  
Naval Air Engineering Center  
Lakehurst, NJ 08733



OLD