

MIL-G-952(AS)  
AMENDMENT 1  
26 July 1985

MILITARY SPECIFICATION  
GUNS, SPRAY, OIL AND SOLVENT

This amendment forms a part of Military Specification MIL-G-952(AS) dated 18 October 1949, and is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

- \* Paragraph 3.2 Delete in its entirety and substitute:

"Corrosion resistance. Exposed metal and working surfaces, except when the parts involved are made of corrosion resistant material, shall be coated or covered with an electro-chemical or chemical finish. Exposed metal is defined as metal exposed to the atmosphere, compressed air, or the spraying fluid."

- \* Paragraph 3.3.16 Delete in its entirety and substitute:

"Connections. Air connection shall be a 1/4-18 National Pipe Specification (NPS) male fitting. Solvent hose connections shall be male and of suitable size for the hose furnished."

PAGE 3

- \* Paragraph 3.4.1.7 Delete in its entirety and substitute:

"Air connection. The air connection shall be a 1/4-18 NPS male fitting."

Insert: 3.9 Instruction manual. Each spray gun shall be supplied with an instruction manual showing a complete parts list, functional diagram, and operating instructions.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:  
Navy - AS

Preparing Activity:  
Navy - AS

Project No. 4930-N248

FSC 4930

DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED