

INCH-POUND

MIL-H-24136/1A(SH)
3 September 1993
SUPERSEDING
MIL-H-24136/1
18 JUNE 1984

MILITARY SPECIFICATION

HOSE, SYNTHETIC RUBBER, SYNTHETIC FIBER REINFORCED FOR FLEXIBLE HOSE ASSEMBLIES (LOW PRESSURE SIZES -80 THROUGH -192)

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers synthetic fiber reinforced hoses in sizes -80 through -192 for use in low pressure applications.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 03Q42, 2531 Jefferson Davis Hwy, Arlington, VA 22242-5160 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MIL-H-24136/1A(SH)

SPECIFICATIONS

MILITARY

MIL-H-24136 - Hose, Synthetic Rubber, Synthetic Fiber Reinforced
for Flexible Hose Assemblies, General Specification
For.

MIL-F-24787 - Fittings for Flexible Hose Assemblies.

(Unless otherwise indicated, copies of the federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Hose. Hose furnished under this specification shall conform to the requirements of MIL-H-24136 and as specified herein.

3.2 Dimensions, pressures and construction. Hose dimensions and pressures shall be in accordance with table I. Hose construction shall be in accordance with table II.

TABLE I. Hose dimensions and pressures.

Hose size (dash no.)	Pressure (psi)		Hose dimensions Inches			
			I.D.		O.D.	
	Working (max)	Burst (min)	Min.	Max.	Min.	Max.
-80	300	1200	5.050	5.116	5.690	5.878
-96	300	1200	6.036	6.110	6.750	6.938
-128	300	1200	8.054	8.130	8.781	8.969
-160	200	800	10.064	10.140	10.781	10.969
-192	150	600	12.111	12.187	12.925	13.249

MIL-H-24136/1A(SH)

TABLE II. Hose construction and minimum bend radius.

Hose size (dash no.)	Hose reinforcement		Minimum bend radius (inches)	Impulse peak pressure (psi)
	Construction	No. of layers		
-80	Spiral	6	36	375
-96	Spiral	6	42	375
-128	Spiral	8	54	375
-160	Spiral	8	66	250
-192	Spiral	10	78	188

3.3 Stability. When tested in accordance with MIL-H-24136, 4.6.2, the hose shall not change in length more than plus 5 percent or minus 2 percent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions shall be in accordance with MIL-H-24136 and as specified herein.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of the manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Sampling for qualification testing.

4.2.1 Hose. Qualification testing of hose shall consist of hose samples as specified in table III. Samples shall be not less than 15 inches in length and shall be fitted with end fittings qualified to MIL-F-24787.

4.2.1.1 Qualified end fittings. End fittings used for the qualification of hose to this associated detail specification shall be fittings qualified to Group IX, MIL-F-24787. Where there are no previously qualified end fittings, the prospective hose supplier shall work together with a prospective fitting supplier to qualify their respective products. (The fitting supplier and hose supplier may be a single source.)

4.2.1.2 End fitting quantity. The quantity of end fittings required shall be in accordance with table IV.

MIL-H-24136/1A(SH)

TABLE III. Hose samples required.

Hose size (dash size)	Number of hose samples to be provided
-80	3
-128	4
<u>1/</u>	3

1/ This sample shall represent the largest hose proposed for qualification.

TABLE IV. End fittings required.

End fitting size (hose dash no.)	Number of end fitting to be provided
-80	6
-128	8
<u>1/</u>	6

1/ This sample shall represent the largest size proposed for qualification.

4.2.2 End fitting mix. Where there are two or more qualified suppliers of end fittings to Group IX of MIL-F-24787, the sample end fitting mix shall be in accordance with table V. Where there is only one previously qualified supplier, the "previously qualified" samples shall come from that supplier.

MIL-H-24136/1A(SH)

TABLE V. Hose and fitting mix for combined qualification, or where there is more than one qualified fitting source.

One approved source					
Hose size (dash no.)	No. of hose samples to be provided		End fitting <u>4</u> / size (hose dash no.)	No. of end fittings <u>4</u> / to be provided	
	<u>2</u> / <u>3</u> / Qualifier	Appvd <u>1</u> / source		<u>2</u> / <u>3</u> / Qualifier	Appvd <u>1</u> / source
-80	2	1	-80	4	2
-128	2	2	-128	4	4
<u>1</u> /	2	1	<u>1</u> /	4	2

Two or more approved sources			
Hose size (dash no.)	Number or hose samples to be provided by		
	Qualifier <u>2</u> /	Approved <u>1</u> / source #1	Approved <u>1</u> / source #2
-80	2	1	0
-128	2	1	1
<u>3</u> / <u>4</u> /	2	1	0
End fitting size <u>4</u> / (dash no.)	Number of end fittings to be provided by <u>4</u> /		
	Qualifier <u>2</u> /	Approved <u>1</u> / source #1	Approved <u>1</u> / source #2
-80	4	2	0
-128	4	2	2
<u>3</u> / <u>4</u> /	4	2	1

Hose samples shall be not less than 15 inches in length and shall be coupled on one end with the fitting being submitted for qualification and on the other end with previously qualified end fittings.

- 1/ Approved source - Previously qualified hose and fitting, or hose or fitting.
- 2/ Qualifier - Offeror of hose and fittings, or hose to be qualified.
- 3/ Satisfactory completion of qualification testing of the samples selected in accordance with tables III, IV and V will qualify the manufacturer for all sizes between the largest tested and -80.
- 4/ If the largest size proposed is -128, then the number of hose samples shall equal 7 and fittings 14. If a size larger than -128 is proposed, the total number of hose samples shall be 10 and fittings 20.

MIL-H-24136/1A(SH)

4.2.3 Hose and end fittings combined. In the event that a supplier for hose and end fittings or a hose supplier and a fitting supplier desire to qualify hose to this associated detail specification and fittings to Group IX, MIL-F-24787 in a combined qualification test, the samples required for testing shall be in accordance with table V.

4.2.4 Sample requirements when there are less than two previously qualified suppliers. Where there is only one qualified source for qualified samples, all the "previously qualified" samples required shall come from that source. Where there are no previously qualified sources, all samples of hoses and fittings shall be submitted by the prospective qualifier(s).

4.2.5 Test sequence. The sequence of tests on sample hose assemblies shall be as specified in table VI.

TABLE VI. Sequence of qualification tests on sample assemblies.

Test sequence (see MIL-H-24136)	Sample numbers									
	Size -80			Size -128				Largest size over -128		
	1	2	3	4	5	6	7	8	9	10
Proof pressure (see 4.6.1)	X	X	X	X	X	X	X	X	X	X
Stability test (see 4.6.2)	X	X	X	X	X	X	X	X	X	X
Aging test (see 4.6.3)		X	X		X	X	X		X	X
Hydraulic fluid circulation test (see 4.6.4)		X			X				X	
Impulse test (see 4.6.5)			X				X			X
Burst test (see 4.6.6)	X			X				X		
Vacuum test (see 4.6.7)			X				X			
Cold temperature flexing (see 4.6.8)						X				X
Adhesion test (see 4.6.9)			X				X			

5. PACKAGING

5.1 Packaging requirements. Packaging requirements shall be in accordance with MIL-H-24136.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Hose to this associated detail specification is intended for use in shipboard or shore to ship piping systems where pressures do not exceed the rated working pressure, and temperatures do not exceed minus 40°F or plus 200°F.

6.2 Acquisition requirements. Acquisition documents should specify the following:

- (a) Title, number and date of this specification.
- (b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1 and 2.1.1)
- (c) Size hose.
- (d) Quantity of hose (linear feet) per size.

6.3 Subject term (key word) listing.

Group IX
Spiral

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing activity:
Navy - SH
(Project 4730-N091-01)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the comment number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of this form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:

1. DOCUMENT NUMBER

MIL-H-24136/1A(SH)

2. DOCUMENT DATE (YYMMDD)

930903

3. DOCUMENT TITLE

HOSE, SYNTHETIC RUBBER, SYNTHETIC FIBER REINFORCED FOR FLEXIBLE HOSE ASSEMBLIES, (LOW PRESSURE SIZES -80 THROUGH -192)

4. NATURE OF CHANGE (identity paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

A. NAME (Last, First, Middle Initial)

b. ORGANIZATION

c. ADDRESS (Include Zip Code)

d. TELEPHONE (Include Area Code)

7. DATE SUBMITTED (YYMMDD)

(1) Commercial

(2) DSN

(if applicable)

8. PREPARING ACTIVITY

A. NAME Technical Point of Contact (TPOC)

MR. CARL BANKS, SEA 03Y23

ADDRESS ALL CORRESPONDENCE AS FOLLOWS:

b. TELEPHONE (Include Area Code)

(1) Commercial:

DSN:

TPOC: 703-602-0367

8-332-0367

c. ADDRESS (Include Zip Code)

COMMANDER, NAVAL SEA SYSTEMS COMMAND

ATTN: SEA 03Q42

1 JEFFERSON DAVIS HIGHWAY

INGTON, VA 22242-5160

IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:

Defense Quality and Standardization Office

5203 Leesburg Pike, Suite 1403

Falls Church, VA 22041-3466

Telephone 703-756-2340 DSN 289-2340