

INCH-POUND

MIL-H-85800(AS)  
AMENDMENT 1  
6 November 1995

MILITARY SPECIFICATION

HOSE ASSEMBLIES, POLYTETRAFLUOROETHYLENE, ARAMID FIBER REINFORCED,  
5000 AND 8000 PSI, GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-H-85800(AS), dated 16 January 1987, and is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1: Under "SPECIFICATIONS, FEDERAL," add the following:

"P-D-680 Dry Cleaning and Degreasing Solvent."

PAGE 19

4.6.3.10e: Delete and substitute:

"e. After the final two-hour pressurization period, the hose assemblies shall be drained and flushed with solvent conforming to type 1A of P-D-680."

4.6.3.10f: Delete and substitute:

"f. The hose assemblies shall be air dried and then subjected to a pneumatic effusion test in accordance with 4.6.3.12. To conduct this test, the hose shall be installed in an apparatus similar to that shown on Figure 4."

Preparing activity:  
Navy - AS

(Project 4720-N053)

AMSC N/A

1 of 1

FSC 4720

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.