

MIL-I-46838B(MI)
AMENDMENT 1
28 August 1987

MILITARY SPECIFICATION
INSULATING COMPOUND, ELECTRICAL, SILICONE RUBBER
ROOM TEMPERATURE VULCANIZING

This Amendment forms a part of MIL-I-46838B(MI), dated 27 February 1981, and is approved for use within the U.S. Army Missile Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Bottom of page in Beneficial comments - Delete DRSMI-RSDS and substitute AMSMI-RD-SE-TD-ST, third line, add -5270 after 35898, fourth line.

PAGE 3

Paragraph 2.2, Other publications, delete the year (-75 and -63) after ASTM D 149 and D 1084, respectively. Add the following ASTM:

ASTM D 3951

Packaging, Commercial

Add:

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

AMSC N/A

FSC 5970

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MIL-I-46838B(MI)

AMENDMENT 1

PAGE 10

5.1, delete and substitute:

5.1 Preservation, packing, unitization and marking. Level A, B or C.

PAGE 11

5.1.3, delete and substitute:

5.1.3 Level C. Unless otherwise specified, preservation and packaging shall be in accordance with ASTM D 3951.

5.2.3, delete and substitute:

5.2.3 Level C. The compound and curing agent packaged as specified in 5.1.1.1 shall be packed in accordance with ASTM D 3951.

PAGE 14

Add 6.10:

6.10 Metriation. Metric equivalents in accordance with FED-STD-376 are acceptable for use in this specification.

Custodian:
Army - MI

Preparing Activity:
Army - MI

Review Activities:
Army - AR
DLA - GS

Project No. 5970-A668

User Activity:
Army - ME