

MIL-I-7085B
 AMENDMENT 1
 10 APRIL 1987

MILITARY SPECIFICATION

INDICTOR, PRESSURE, ENGINE, 0-50 PSI

This amendment forms a part of MIL-I-7085B, dated 28 Jan 80, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Delete "firt sentence" and add: "Government documents."

Add: "2.1.1 Specifications standards, and handbooks. The following specifications, standard, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

Under SPECIFICATIONS, Federal, add: "PPP-B-601 Boxes, Wood, Cleated Plywood."

Under SPECIFICATIONS, Military, delete "title" to MIL-P-116 and add new title Preservation, Methods Of

Delete address on lines 3 and 4 of beneficial comments block and add: "Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990."

PAGE 2

Add: 2.2. Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM D3951 Packaging, Commercial

(Application for copies should addressed to: ASTM, 1916 Race St, Philadelphia PA 19103).

(Nongovernment standards and other publications are normally available from the organization which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

Add: 2.3. Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

MIL-I-7085B
AMENDMENT 1

PAGE 5

Add: "3.6 Recycled and reclaimed materials. The use of recycled and reclaimed materials shall be encouraged to the maximum extent possible without jeopardizing the intended end use of the item.

Add: "4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

PAGE 6

4.3 Delete "last sentence."

4.4 Delete "second sentence".

PAGE 9

Delete Section 5 in its entirety and add:

"5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1. Level A.

5.1.1.1. Cleaning. Indicators shall be cleaned in accordance with process C-1 or MIL-P-116.

5.1.1.2. Drying. Indicators shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3. Preservation application. Not applicable.

5.1.1.4. Unit packaging. Unless otherwise specified by the contracting activity, each indicator shall be packaged in quantity unit packs of one each in accordance with Method ICI of MIL-P-116. Overbox completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the indicator when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2. Level C. Each indicator shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

MIL-I-7085B
AMENDMENT 1

5.2.1. Level A. Indicators packaged as specified in 5.1.1. shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2. Level B. Indicators packaged as specified in 5.1.1. shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1. apply.

5.2.3. Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4. Industrial. The packaged indicators shall be packed in accordance with ASTM D3951.

5.3. Marking. In addition to any other markings required by the contract or order (see 6.2.), interior and exterior containers shall be marked in accordance with MIL-STD-129.

6.4. Line 12 delete "HQ AFLC CASO/LODS, Federal Center, Battle Creek, MI 49016" and add: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB, OK 73145-5990."

Delete "6.5" and "6.6"

Custodian:
Air Force - 99
Army - AV
Navy - AS

Preparing activity:
Air Force - 71

Project No.
6620-0422