METRIC

MIL-I-89014 AMENDMENT 1 11 April 1991

MILITARY SPECIFICATION

INTERIM TERRAIN DATA (ITD) / PLANNING INTERIM TERRAIN DATA (PITD)

This amendment forms a part of MIL-T-89304, dated 30 November 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

The attached insertable replacement pages listed below are replacements for stipulated pages. When new pages have been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page_replaced			
1	Reprinted without change			
2	2			
5	5			
6	6			
9	Reprinted without change			
10	10			
15	Reprinted without change			
16	16			
65	Reprinted without change			
66	66			
67	67			
68	Reprinted without change			
69	69			

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

AMSC N/A

AREA MCGT

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Custodian: an of all states and a residence of Review activities: Army - PO Air Force - 09 Navy - NO

Preparing activity: DMA MP

.

and an end of the second

(project MCGT-0070)

•

.

User activities:

Air Force: 09 Army: PO DMA: MP NSA: NSA-GIC-T5141 NO Navy: TVA: NSD-HB Canada: MECE

and the second second

ł





يرابع متمل متصبي

METRIC

MIL-I-89014 30 NOVEMBER 1990

MILITARY SPECIFICATION

INTERIM TERRAIN DATA (ITD) / PLANNING INTERIM TERRAIN DATA (PITD)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

- 1. SCOPE
- 1.1 Scope.

a. This specification establishes the first edition military specification requirements for the Defense Mapping Agency's (DMA) Interim Terrain Data (ITD) and Planning Interim Terrain Data (PITD). This document specifies the format, content, and product design of ITD and PITD, which are unsymbolized digital data sets. They are based on the level of detail represented, in the case of ITD, in the 1:50,000 scale Tactical Terrain Analysis Data Base (TTADB) or, in the case of PITD, in the 1:250,000 scale Planning Terrain Analysis Data Base (PTADB). Both ITD and PITD have an enhanced transportation network, and are provided in a standardized digital format. TTD and FITD are portrayals of analyzed attributes of terrain features (both natural and man-made) that are of significance to tactical (ITD) and planning (PITD) military operations.

b. The DMA Terrain Analysis Program is a dynamic program. This manual identifies specifications encountered in the production of the ITD and PITD thematic files. Supplementary instructions may need to be generated as this product evolves. Modifications will be handled through Configuration Management procedures.

Deneficial comments (recommendations, additions, delations) and any pertinent data which may be of use in improving this document should be addressed to : Director, Defense Mapping Agency, ATTN: PR, 8613 Lee Highway, Fairfax, VA. 22031-2137 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

ANSC N/A AREA MCGT

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

1.2 <u>Purpose</u>. Conformance to these specifications will assure uniformity of treatment among all mapping and charting elements engaged in a coordinated production and maintenance program for this product.

1.3 <u>Security</u>.

1.3.1 <u>Security classification</u>. The security classification of the products generated by the use of these specifications will be the lowest category practicable. When it is necessary to assign a security classification to the product, it will be accomplished in accordance with established national security procedures.

1.4 Applicability.

a. For the remainder of this document, the term ITD will be used
generically to describe both ITD and PITD. Where it is important to distinguish
between the two, this document will do so. Likewise, the term TADB will be used
generically to describe both TTADB and PTADB.

b. These specifications apply to all ITD produced by the Defense Mapping Agency and those produced for the Defense Mapping Agency as a result of either government contract or unit tasking.

c. These specifications apply to all activities involved in the preparation and maintenance of ITD.

1.5 ITD design.

a. ITD is a product developed to satisfy the armed services short-term and mid-term requirements for digital terrain analysis data.

* b. In the case where TADBs are used as the primary source, ITD will reflect the specification current at the time of TADB collection. In all other cases, the currently configured baselined TADB specification will be used.

 c. ITD is designed to use the Defense Mapping Agency Feature File (DMAFF) coding scheme (see 2.1.2.b.), and the DPS Standard Linear' Format (SLF) for Digital Cartographic Feature Data (see 2.1.2.a.), for data format and structure.

 d. ITD is independent of the method of its production. The production methods result in a standard product that meets the requirements of this specification.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

and the second second

2.1.1 <u>Specifications, standards, and handbooks</u>. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the current Department of Defense Index of Specifications and Standards (DODISS) and the supplement thereto, cited in the solicitation (see 6.2).

b. Features crossing file boundaries shall be continuous, i.e., a feature's geographic position which is located on a file boundary is common to all adjacent files. The only exceptions to this rule are when more current source is used and the feature on the ground has changed (e.g. new road), or when the mismatch is due to different TADB specifications. In these cases, there may be a discontinuity along a file boundary.

3.6 <u>Dimensions</u>.

3.6.1 Unit of measure. The Unit of Measure for the ITD/PITD is Metric.

3.6.2 <u>Minimum sizes</u>. The minimum and maximum sizes of features digitized in most of the thematic files are stated in the TADE specifications current at the time of collection. The features may be digitized as points, lines, or areas depending on the measured values from the source.

3.7 <u>Feature and attribute coding system</u>. ITD feature and attribute coding shall be in accordance with the DMAFF reference (see 2.1.2.b.).

3.8 <u>ITD file</u>. ITD will be produced in the DPS SLF format, which provides a standard format for digital cartographic feature data. Refer to the DPS SLF Specification (see 2.1.2.a.), for more detail on SLF format and structure. Appendix XVI to the SLF provides specific guidance for the implementation of ITD.

3.8.1 Magnetic tape media.

a. Physical characteristics - ITD will be distributed on 9 track, 1600 BPI unless requested at 6250 BPI, 1/2 inch magnetic tapes.

b. Magnetic tape label - The magnetic tape label shall be affixed to the side of the magnetic tape. At a minimum the label shall contain:

- (1) Name of the type of data (e.g., ITD).
- (2) Date and edition of data.
- (3) Area identifier.
- (4) Production center tape number
- (5) 'Tape density
- (6) Blocking of data
- (7) Number of records
- (8) Security classification of the tape contents

c. Refer to DPS SLF (see 2.1.2.a.); for further information.

3.9 Thematic file sequence.

a. The respective digital ITD files will be referred to as "thematic files".

b. The ITD shall be produced as a set of six segregated thematic files, duplicating the content of the six TADB thematic overlays, with the addition of enhanced transportation.

c. The six segregated thematic files are listed below and will be stored or written to tape in this order:

SURFACE CONFIGURATION (SLOPE) VEGETATION SURFACE MATERIALS SURFACE DRAINAGE TRANSPORTATION OBSTACLES

3.10 ITD/PITD features and attributes.

a. Except as noted in paragraphs 3.11 to 3.16, the features and attributes carried in the ITD thematic files, as per Appendix A, are the same as those required by the TTADB specifications (MIL-T-89303). See that specification for feature and attribute definitions, minimum sizes, usage limitations, placement rules, etc.

b. See Appendixes A and B for a listing of the features, feature codes, and their associated attributes, attribute codes, and attribute value meanings allowable for the ITD thematic files.

and the second second

c. All features in the ITD thematic files will carry an Overlay Category (OVC) attribute code value corresponding to the particular thematic on which it * appears. If a feature appears on more than one overlay, i.e., common open water, it will have that thematic's particular OVC code in each file in which it appears. OVC attribute values are shown in Appendix B.

3.11 <u>Surface Configuration (Slope)</u>. This section provides the basic guidance for the production of the Surface Configuration (Slope) thematic file for ITD.

3.11.1 General slope information.

*

a. Information contained in this file represents the maximum slope of the surface at each point on the ground, expressed as percent slope (tangent of the slope angle x 100), rather than in degrees. Slope is defined as (1) ground whose surface forms an angle with the plane of the horizon (a natural or artificial incline), or (2) the degree or extent of deviation from the horizontal. Although there are an infinite number of slope values at a given point, the maximum slope is the critical limiting value for tactical military operations.

b. See Appendix A for a listing of features and their attributes permitted.

c. Areal extent. Whereas surface configuration is represented by an areal file, all areas within the data set boundary must be labeled with a feature code. There will be no void areas in the file.

d. All features in the Surface Configuration thematic file will carry the OVC attribute code of "1".

3.13.4 Surface roughness classification and coding.

a. Surface roughness is synonymous with microrelief and covers the expression of the land surface or surface geomorphic features which are less than the contour interval of the base map in height. Surface roughness is that aspect of the microrelief on the land surface (boulder fields, hummocky ground, gullies, rugged bedrock, etc.) which reduces the rate of cross country movement for vehicles or foot troops.

b. Surface Roughness Qualifier (SRQ=0-98) (attribute/value numbers). Surface roughness is classified and coded in the surface materials thematic file by a project-tailored set of sequential numbers designating the surface roughness type. Each separate surface roughness type found in the project area is assigned a Surface Roughness Qualifier or type number. The only surface material types not assigned surface roughness type numbers are the Not-Evaluated and COW features.

c. Surface Roughness Qualifier (SRQ=0-98) (attribute value meaning descriptors).

(1) Each surface roughness type identified and number coded in the project is given a corresponding surface roughness descriptor.

(2) The surface roughness descriptors are a set of generalized statements about the small-scale differences in relief (natural and/or cultural) that are not normally shown or interpretable on a regular topographic map. These descriptors shall detail the surface roughness within specific mapping units sether than combining several different and separately occurring surface roughness descriptions together.

(3) The actual surface roughness descriptions associated with each Surface Roughness Qualifier are stored in the TTD SLF text record (Surface Roughness Table).

(4) The surface roughness type numbers 0, 1, and 2 are standardized. Refer to the T/PTADB specifications and the DPS SLF-A, Appendix XVI.

(5) The remaining surface roughness type numbers and descriptors (SRQ=03-98) are the analyst tailored types and are formatted as described in DPS SLF-A, Appendix XVI.

(6) General Roughness Categories 1-5 (GRL-GR5). Along with each surface roughness qualifier and description in the Surface Materials thematic file, there is an associated set of five surface or general roughness category (GRC) factor values. Each GRC factor value corresponds to one of the five categories of vehicle types or classes for which surface roughness is considered for the ITD (only GRLs are used for the PITD):

- - (b) GR2 Small Tracked Vehicles.

. ..

(c) GR3 - Large Wheeled Vehicles.

- (d) GR4 Small Wheeled Vehicles.
- (e) GR5 Foot Troops.
- NOTE: See Appendix B for possible GR1 GR5 values. ITD/PITD - for a SRQ = 1: GR1 through GR5 = 1.00 ITD - for a SRQ = 2: GR1 through GR5 = 0.00

(7) These factors are estimated numerical values reflecting the degradation of the rate of vehicular and foot troop movement due to travel over a particular surface roughness type on horizontal ground. The factors can be any numeric value from 0.00 to 1.00 in 0.05 increments.

3.14 <u>Surface Drainage</u>. This section provides the basic guidance for the production of the Surface Drainage thematic file for ITD.

3.14.1 General Surface Drainage information.

a. See Appendix A for a listing of features and their attributes permitted for the Surface Drainage thematic file. See TADB specifications for specific inclusion conditions.

b. Linear and areal extent. Whereas Surface Drainage is represented by a combination of feature types (mostly linear with some point and areal features) most of the area within the data set boundary of the covered area is not assigned a feature and/or attribute codes.

c. All features in the Surface Drainage thematic file will carry the OVC attribute code of "4".

3.14.2 <u>Miscellaneous</u> <u>Surface</u> <u>Drainage</u> <u>features</u>. Additional Surface Drainage features may be encountered which are of major significance to military operations, especially river and channel crossings and/or landings. In some environments, features such as intermittent lakes, washes/wadis, anastomosing streams, elevated aqueducts, tidal flats, weirs, features under construction, etc., may be of operational and landmark significance. Unique and significant Surface Drainage features not found in the specification will be shown as DMAFF Miscellaneous Graphic Features (9D010) and described (along with any new measurements made for the features) in the ITD SLF text record of the file.

3.15 <u>Transportation</u>. This section provides the basic guidance for the production of the Transportation thematic file for the ITD.

3.15.1 General Transportation Information.

and the factor of the

a. The features and attributes in this thematic file represent transportation features over which troops and supplies can be moved during a tactical military operation. The transportation thematic file consists of features required in TADB specifications in addition to the enhanced transportation guidelines as outlined in this section.

b. If associated attributes for a feature are unknown, guidelines presented in DMAFF specifications should be followed.

(4) The fourth column labeled "F Type" designates which feature types are allowable for this feature, that is: point, line, or area.

(5) The fifth column labeled "F At. No." is the field attribute number, which is the feature header field (location) in the digital data where this attribute is stored.

(6) The sixth column labeled "At. Code" contains the attribute code. This is the three character alphanumeric designation of the different attribute codes which the particular feature can have.

(7) In the seventh column labeled "Values" are the allowable values that the attribute code can have.

(8) In the eighth column labeled "Attribute" is the name of the attribute code designated in column six.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspections required (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his or any other facilities suitable for the performance of the inspection requirements specified herein; unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 <u>Responsibility for compliance</u>. All items shall meet all requirements of paragraphs 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

5. PACKAGING This section is not applicable to this specification.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 <u>Intended use</u>. ITD is a product developed to satisfy the armed services short-term and mid-term requirements for digital terrain analysis data.

and the second second

6.2 <u>Supersession</u>. This section is not applicable to this specification.

.

MIL-I-89014

AMENDMENT 1

6.3 Classification and special handling of ITD thematic files.

a. The classification of the final ITD files will be determined by the appropriate security section responsible for the final classification. The lowest possible classification of the final product is desired.

b. Even though the final thematic files might be unclassified, a handling caveat could be required. Some NATO and other countries have mapping and other agreements which dictate the handling of materials produced over their country. Security elements should check for caveat requirements at the beginning of each project.

وحيصة المعتا الأراك الم

6.4 <u>Acquisition requirement</u>. When this specification is used in
acquisition, the applicable issue of the DODISS must be cited in the solicition
(see 2.1.1).

MIL-I-89014 APPENDIX B AMENDMENT 1

ITD attribute code name and attribute values (Continued)

Attribute <u>Code</u>	Attribute <u>Values</u>	Value Meaning			
UBD	0	Clearance-Decimeters Unknown			
	1	l Decimeter			
	998	998 Decimeters			
UGD	Undergrowth	Density Category			
	0	Unknown			
-	1	None to sparse			
	2	Medium to Dense			
VEG		Vegetation Characteristics			
	0	Unknown			
	1	Dry Crops			
	2	Shifting (cultivation/usage)			
	3	Terraced			
	4	Rice Paddy			
	5	Agriculture With Scattered Forests Grassland			
	8 9	Grassland w/Scatt. Trees & Scrub Growth			
	13	Deciduous			
	14	Evergreen			
· .: .:	15	Mixed			
	17	Palm			
	19	Mangrove			
	24	Forest Clearing			
WDA	Water Depth				
	0	Unknown			
	1	<0.8 meters			
	2	>0.8 - 1.6 m			
	3	>1.6 - 2.4 m			
	4	>2.4 m			
	5	<1.2 m			
	6	>1.2 m - 2.4 m			
WDD	Width-Decim				
	0	Unknown			
	1	1 Decimeter			
	•	: · ·			
	•				
	•				

• •

.

and in the second second

.:

. .

MIL-I-89014 APPENDIX B AMENDMENT 1

ITD attribute code name and attribute values (Continued)

Attribute <u>Code</u>	Attribute <u>Values</u>	Value Meaning
WID	Width 0	Unknown
	1	1 Meter
	•	
	998	998 Meters
WTC	Weather Type Category	
	0	Unknown
-	1	All weather
	2	Fair/Dry Weather
WVA	Water Velocity Average	
	0	Unknown
	1	<=1.5 m/sec.
	2	>1.5 m/sec.

INDEX

•

*

	PARA	GRAPH PAGE
Accuracy	3.1	. 4
Acquisition requirements		16
Appendix A		14
Appendix A. ITD/PITD feature and feature attribute		
organization table		17
Appendix B. ITD attribute listing		57
Applicability	1.4	2
Applicable documents	2.	2
	20.	17
	20.	57
Bridges	3.12	.4 12
Classification and special handling of		
thematic overlays	6.3	16
Concluding material		· 69
Continuity (adjoining data set match)		4
Data density levels		4
Data set size		4
Datum		4
Deliverable data		
Dimensions		5
Feature and attribute coding system		5
"General obstacle information server serverses server		
General slope information		
"General surface"drainage information		10
General surface materials information		•
General transportation information		
General vegetation information		.i · 7
Government documents	2.1	- - 2
—		
Horizontal datum		—
		67 15
Intended use		57
ITD attribute code names and attribute values ITD attribute table		-
ITD design		2
ITD design		2 5
ITD set up of features and attributes		17
ITD/PITD features and attributes		_
Magnetic tape media		
Minimum sizes		
Miscellaneous Surface Configuration features		
Miscellaneous Vegetation features		• =
Miscellaneous Surface Materials features		
Miscellaneous Surface Drainage features		
Miscellaneous Transportation features		.2 10
Miscellaneous Obstacle features		.2 13
Names and labeling		14
Non-Government publications		. 3
Not-evaluated (9D010) areas		
Notes		15
Obstacles		13

•

.

. ... ,

.

••

.

MIL-I-89014 AMENDMENT 1

.

. . . .

. .

- - -

.

.

INDEX

	PARAGRAPH	PAGE	
Order of precedence	2.3	<u> </u>	
Organizational table	30.1	17	
Other Government documents, drawings, and publications	2.1.2	3	
Packaging	5.	15	
Purpose	1.2	2	
Quality	3.17	13	
Quality assurance provisions	4.	15	
Railroads	3.15.2	11	
Reproduction and storage	3.20	14	
Requirements	3.	4	
Responsibility for compliance	4.1.1	15	
Responsibility for inspection	4.1	15	
Roads	3.12.3	11	
Scope	1.	1	
•	1.1	1	
	10.	17	
	10.	57	
· · ·	10.1	17	
	10.1	57	
Security	1.3	2	
	1.3.1	2	
Specifications, standards, and handbooks	2.1.1		
Standardization document improvement proposal		70	
Supersession of the contraction of the second	•		
Surface Configuration (Slope)	3.11	6	
Surface Drainage	3.14	10	
Surface roughness classification and coding			
There is a second s	3.13.4 1914-9		antererererererererererererererererererer
Thematic file separation	3.9	5	
Transportation	3.15	10	
Tunnels	3.12.5	13	
Unit of measure	3.6.1	5	
Vegetation	3.12	7	
Vertical datum	3.2.2	4	

...* '.: • • • •

. . **.** -----.... . .

CONCLUDING MATERIAL

*. Custodian: DMA - MP Preparing activity: DMA - MP

(project MCGT-0017)

r

Review activities:
Army - PO
Air Force - 09
Navy - NO

User activities:

- Air Force: 09
- * Army: PO
- * DMA: MP
- NSA: NSA-GIC-T5141
- * Navy: NO
- TVA: NSD-HB
- Canada: M&CE