

INCH-POUND

MIL-M-48640(AR)
 AMENDMENT 1
 29 April 1991

MILITARY SPECIFICATION

MUZZLE BORESIGHT DEVICE: 9364909
 (M27 FOR 120MM GUN TUBE)

This amendment forms a part of MIL-M-48640(AR), dated 31 January 1986, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.5.1, delete in its entirety and substitute:

"3.5.1 Collimation. Collimation error, defined as the angular difference in the alignment of the optical axis with the mechanical axis, shall not exceed 20 seconds when the Muzzle Boresight Device is mounted in the test fixture."

3.5.3, delete in its entirety and substitute:

"3.5.3 Collimation repeatability. The collimation repeatability error shall not exceed 15 seconds. All measurements must meet the collimation requirements of 3.5.1."

PAGE 11

4.7.4.1, delete last sentence in its entirety and substitute:

"Collimation is met when collimation error is within 20 seconds as required by paragraph 3.5.1, when rotated through 360°, minimum of four readings 90° apart".

4.7.4.3.2, delete fourth sentence in its entirety and substitute:

"Repeatability within 15 seconds is acceptable."

Custodian
 Army-AR

Preparing Activity:
 Army-AR
 (Project 1240-AB15)

AMSC N/A 1 OF 1 FSC 1240
Distribution Statement A. Approved for public release; distribution is unlimited.