

INCH-POUND

MIL-N-8922B
AMENDMENT 1
23 NOVEMBER 1999

MILITARY SPECIFICATION

NUT, SELF-LOCKING, ALLOY STEEL, 220 KSI F_{TU} ,
450°F GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-N-8922B, dated 14 SEPTEMBER 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.2 Delete and Substitute: "3.2 Qualification. The nut manufacturer shall be responsible for conducting qualification tests and furnishing part drawings, certified qualification test reports (if required by the purchaser) and test samples. The nuts furnished under this specification shall be produced using the same manufacturing methods as those used to produce nuts that have passed qualification tests. The purchaser may apply any or all tests specified herein to any product represented as meeting this specification, at any time, to verify conformance."

3.3 Delete and Substitute: "3.3 Retention of Qualification. Requalification will be required in the event any change is made in the product design, construction, materials, method of manufacture, heat treatment, finish, lubricant, or manufacturer's part number or designation."

PAGE 8

4.3.1 Delete and Substitute: "4.3.1 Qualification Samples. Test samples shall be of the same material and manufactured by the same method as production parts. The number of nuts to be subjected to qualification tests shall be sufficient to perform the tests identified in Table V. All bolts, screws, or mandrels required for testing shall be in accordance with this specification."

MIL-N-8922B
AMENDMENT 1

4.3.3 Delete and Substitute: "4.3.3 Certified Test Report. The manufacturer shall maintain on file a certified test report showing that the manufacturer's product satisfactorily conforms to this specification. The test report shall include, as a minimum, actual results of the tests specified herein. A complete description and name of lubricating material used on the nuts shall be furnished. The manufacturer shall also maintain a dated drawing that completely describes the manufacturer's product. The drawing shall specify all dimensions and tolerances, material composition, coatings or platings applied, forming process, and heat treatment. The drawing shall also specify the manufacturer's part number for each size. Requalification will be required in the event any change is made in the product design, construction, materials, method of manufacture, heat treatment, finish, lubricant, or manufacturer's part number or designation."

4.3.4 Delete and Substitute: "4.3.4 Retention of Qualification. To maintain product qualification status, manufacturers shall maintain on file, a certified qualification test report (See 4.3.2) available for inspection by the procuring activity. The retention of a certified qualification test report by the manufacturer signifies that the manufacturer has demonstrated compliance to the qualification requirements of this specification. Products previously qualified via government-certified qualification tests and reports shall be considered qualified to this specification."

PAGE 17

6.3 Delete and Substitute: "6.3 Qualification. Awards will be made only for products that meet the qualification requirements of this document at the time set for opening of bids. Nuts that have not been previously qualified via government-certified qualification tests and reports may be acquired, provided that certified qualification test reports for these nuts are retained on file by the manufacturer along with the quality conformance inspection data, and they are made available to the buyer upon request."

6.3.1 Delete entire paragraph.

Custodians:
Army - AV
Navy - AS
Air Force - 99

Preparing Activity:
DLA-IS

(Project 5310-2525)