

: INCH-POUND :

MIL-P-642D
AMENDMENT 1
28 June 1990

MILITARY SPECIFICATION

PLUGS, TELEPHONE, AND ACCESSORY SCREWS,

GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-P-642D, dated 27 February 1979, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 9

4.6.8, delete and substitute:

"4.6.8 Vibration (see 3.6.7). Plugs shall be tested in accordance with method 2005 of MIL-STD-1344. The following details and exceptions shall apply:

- a. Method of mounting: Plugs shall be mounted with their longitudinal axis in a horizontal plane.
- b. Test condition: I.
- c. Direction of motion: Along the axis of the plug, and then perpendicular to the axis of the plug.
- d. Measurements during vibration: Each plug shall be monitored for electrical continuity, using a test current of 100 \pm 2 milli-amperes, dc. Loss of continuity for a period longer than 10 microseconds constitutes a failure.
- e. Measurements after vibration: Contact resistance shall be measured as specified in 4.6.4.
- f. The vibration test shall be performed on plugs, both unmated (without the mating jack) and mated (with the mating jack).
- g. Mating jack: The applicable mating jack (see table IV) shall have a 3 foot \pm 3 inch length of cord, of the type normally used with the jack, attached and hanging free. The plug shall be inserted into the mating jack and shall remain inserted throughout the mated portion of the test."

MIL-P-642D
AMENDMENT 1

CONCLUDING MATERIAL

Custodians:

Army - CR
Navy - EC
Air Force - 85

Review activities:

Army - AR, ME, MI
Navy - AS
Air Force - 11, 99
DLA - ES

User activities:

Army - AV, MI
Navy - MC, OS, SH, YD
Air Force - 17

Preparing activity:

Army - CR

Agent:

DLA - ES

(Project 5935-3788)