

INCH-POUND

MIL-P-71012A (AR)
AMENDMENT 1
17 SEPTEMBER 1999

MILITARY SPECIFICATION

PISTOL, SEMIAUTOMATIC, COMPACT, 9MM: M11

MIL-P-71012 was inactivated after 19 August 1997 For New Design

This Amendment forms a part of MIL- P-71012A (AR), dated 15 February 1994, and is approved for use by the US Army Armament Research, Development and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, Add under Military:

"MIL-P-3420 -Packaging Materials, Volatile Corrosion Inhibitor
 Treated, Opaque"

"MIL-B-22020 -Bags, Transparent, Flexible, Sealable, Volatile
 Corrosion Inhibitor Treated"

PAGE 4

Add new paragraph 2.2 as follows:

"2.2 Non-Government publications. The following documents of the exact revision listed below form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM D 1974 -Standard Practice for Methods of Closing, Sealing, and
 Reinforcing Fiberboard Boxes
ASTM D 5118 -Standard Practice for Fabrication of Fiberboard
 Shipping Boxes

(Application for copies should be addressed to American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)"

2.2, Renumber paragraph to 2.3.

MIL-C-71012A(AR)
AMENDMENT 1

PAGE 27

Delete paragraph 5.1.1.3 in its entirety and substitute:

"5.1.1.3 Preservation application. Apply P-9 by spraying or brushing. Turn the weapon at least once during draining process to allow excess preservatives to drain from all surfaces."

5.1.1.4, second line: Delete "method IC-1" and substitute "method I".

5.1.1.4c, second line: Delete "PPP-B-636, W5C" and substitute "ASTM D 5118, W5c/W6c".

5.1.1.4d, delete "PPP-B-636. Seal all seams and joints." and substitute "ASTM D 1974. Close with 2B7. Seal all seams and joints in accordance with method B or C."

5.1.1.4.1, End of paragraph: Add "The VCI should be received and stored (even during use) in a closed, sealed container protected from excessive heat, direct sun, moisture and excessive dust (see MIL-I-8574). Compatibility test requirements apply (see MIL-I-8574 paragraph 4.3.1)."

PAGE 28

Delete paragraph 5.1.1.4.3 in its entirety and substitute:

"5.1.1.4.3 Spare magazines. Spare magazines, if provided, shall be packaged method IC-1. Coat magazines with P-9 (VV-L-800). Wrap with MIL-P-3420 (Style C Class 1, form a). Heat seal closure. Alternate packaging: Coat magazine with P-9 and place in a bag made in accordance with MIL-B-22020 (Type II). Tape the bagged magazine to the interior of the weapon unit container (fiberboard box)."

Delete paragraph 5.1.4.4 in its entirety.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1005-0868)