

INCH-POUND

MIL-R-83536(USAF)
SUPPLEMENT 1
8 September 1992

MILITARY SPECIFICATION

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-R-83536, dated 22 June 1990.

SPECIFICATION SHEETS

- MIL-R-83536/1 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 5 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coils
- MIL-R-83536/2 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 5 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient suppressed DC Coils
- MIL-R-83536/3 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 5 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, DC Coils
- MIL-R-83536/4 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 5 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-R-83536/5 - Relays, Electromagnetic, Established Reliability, 4PDT, Low level to 5 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coils
- MIL-R-83536/6 - Relays, Electromagnetic, Established Reliability, 4PDT, Low level to 5 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-R-83536/7 - Relays, Electromagnetic, Established Reliability, 4PDT, Low level to 5 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, DC Coils
- MIL-R-83536/8 - Relays, Electromagnetic, Established Reliability, 4PDT, Low level to 5 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-R-83536/9 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coils
- MIL-R-83536/10 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-R-83536/11 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, AC Coils
- MIL-R-83536/12 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, DC Coils

MIL-R-83536(USAF)
SUPPLEMENT 1

- MIL-R-83536/13 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coils
- MIL-R-83536/14 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, AC Coils
- MIL-R-83536/15 - Relays, Electromagnetic, Established Reliability, 4PDT, Low level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coil
- MIL-R-83536/16 - Relays, Electromagnetic, Established Reliability, 4PDT, Low level to 10 Amperes, Permanent Magnet drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coil
- MIL-R-83536/17 - Relays, Electromagnetic, Established Reliability, 4PDT, 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, AC Coils
- MIL-R-83536/18 - Relays, Electromagnetic, Established Reliability, 4PDT, Low level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, DC Coils
- MIL-R-83536/19 - Relays, Electromagnetic, Established Reliability, 4PDT, Low level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coil
- MIL-R-83536/20 - Relays, Electromagnetic, Established Reliability, 4PDT, Low level to 10 Amperes, Magnetic Latch, Hermetically Sealed, All Welded, AC Coils
- MIL-R-83536/21 - Relays, Electromagnetic, Established Reliability, 3PDT, Low level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coil
- MIL-R-83536/22 - Relays, Electromagnetic, Established Reliability, 3PDT, Low level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coil
- MIL-R-83536/23 - Relays, Electromagnetic, Established Reliability, 3PDT, Low level to 10 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, DC Coil
- MIL-R-83536/24 - Relays, Electromagnetic, Established Reliability, 3PDT, Low level to 10 Amperes, Permanent Magnet Drive, Magnetic Latch, Hermetically Sealed, All Welded, Transient Suppressed DC Coil
- MIL-R-83536/25 - Relays, Electromagnetic, Established Reliability, 6PDT, Low level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, DC Coil
- MIL-R-83536/26 - Relays, Electromagnetic, Established Reliability, 6PDT, Low level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, Transient Suppressed DC Coil
- MIL-R-83536/27 - Relays, Electromagnetic, Established Reliability, 6PDT, Low level to 10 Amperes, Permanent Magnet Drive, Hermetically Sealed, All Welded, AC Coil

MIL-R-83536(USAF)
SUPPLEMENT 1

- MIL-R-83536/28 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Hermetically Sealed, All Welded, DC Coils (0.200 Inch Terminal Spacing, .050 Diameter Terminal Pins)
- MIL-R-83536/29 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Hermetically Sealed, All Welded, DC Coils (0.200 Inch Terminal Spacing, .050 Diameter Terminal Pins) With Internal Diodes For Transient Suppression And Polarity Reversal Protection
- MIL-R-83536/30 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Hermetically Sealed, All Welded, DC Coils (0.200 Inch Terminal Spacing, .062 Diameter Terminal Pins)
- MIL-R-83536/31 - Relays, Electromagnetic, Established Reliability, DPDT, Low level to 10 Amperes, Hermetically Sealed, All Welded, DC Coils (0.200 Inch Terminal Spacing, .062 Diameter Terminal Pins) With Internal Diodes For Transient Suppression and Polarity Reversal Protection

CONCLUDING MATERIAL -

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5945-0893)