

TYNCH-POUND

MIL-R-83726B
 SUPPLEMENT 1B
 9 December 1988
 SUPERSEDING
 SUPPLEMENT 1A
 28 July 1986

MILITARY SPECIFICATION
 RELAYS, HYBRID AND SOLID STATE, TIME DELAY,
 GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-R-83726B,
 dated 10 December 1984.

SPECIFICATION SHEETS

- MIL-R-83726/1 - Relays, Time Delay On Operate, Type I, Class B, 10 AMP, 2 PDT, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 7 SEP 84)
- MIL-R-83726/2 - Relays, Time Delay On Release, Separate Positive Control Type IIA, Class B, 10 AMP, 2 PDT, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 7 SEP 84)
- MIL-R-83726/3 - Relays, Time Delay On Operate Type I, Class B, 10 AMP, 2 PDT, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 7 SEP 84)
- MIL-R-83726/4 - Relays, Time Delay On Release, Separate Positive Control Type IIA, Class B, 10 AMP, 2 PDT, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 7 SEP 84)
- MIL-R-83726/7 - Relays, Hybrid, Time Delay, On Pickup, Type I, Class A, 2 Amperes, 2PDT, Fixed Time, 0.06 to 300 Seconds.
- MIL-R-83726/8 - Relays, Hybrid, Time Delay (On Release), Type IIA, Class A, 2 Amperes, 2PDT, Fixed Time, 0.100 to 300 Seconds.
- MIL-R-83726/12(USAF) - Relays, Hybrid, Time Delay (On Release), Type IIA, Class B, 10 Amperes, 4PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds.
- MIL-R-83726/13(USAF) - Relays, Solid State, Time Delay (On Operate), Type I, Class C, SPSTNO, 300 Milliamperes, Fixed Time, 0.05 to 600 Seconds, Hermetically Sealed.
- MIL-R-83726/14(USAF) - Relays, Hybrid, Time Delay (On Operate), Type I, Class B, 10 Amperes, 4PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds.
- MIL-R-83726/18(USAF) - Relays, Hybrid, Time Delay (On Release), Track Mounted, Type IIA, Class B, 10 Amperes, 2PDT, Hermetically Sealed, Fixed Time, 0.1 to 300 Seconds.
- MIL-R-83726/19(USAF) - Relays, Hybrid, Time Delay (On Operate), Track Mounted, Type I, Class B, 10 Amperes, 2PDT, Hermetically Sealed, Fixed Time, 0.1 to 300 Seconds.
- MIL-R-83726/20(USAF) - Relays, Solid State, Time Delay (On Operate), Type I, Class C, SPST, 250 Milliamperes, Fixed Time, .05 to 500 Seconds.
- MIL-R-83726/21(USAF) - Relays, Solid State, Time Delay (On Operate), Type I, Class C, SPST, 250 Milliamperes, Variable Time, .05 to 500 Seconds.
- MIL-R-83726/22(USAF) - Relays, Solid State, Repeat Cycle Time, Type IV, Class C, SPST, 250 Milliamperes.
- MIL-R-83726/23(USAF) - Relays, Hybrid, Time Delay (On Release), Type IIB, Class B, 10 Amperes, 4PDT, Hermetically Sealed.

AMSC N/A

1 of 2

FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MIL-R-83726B
SUPPLEMENT 1B

- MIL-R-83726/24(USAF) - Relays, Solid State, Time Delay (On Operate), Track Mounted, Type I, Class C, SPST, 150 Milliamperes, Fixed Time, 50 Milliseconds to 500 Seconds.
- MIL-R-83726/25(USAF) - Relays, Solid State, Track Mounted, Electronic Time Delay On Release, Type IIA, Class C, SPST, 150 Milliamperes, Fixed Time, 50 Milliseconds to 500 Seconds.
- MIL-R-83726/27(USAF) - Relays, Hybrid, Time Delay, Voltage Sensitive, Delay On Drop-Out, Class A, Type V, Hermetically Sealed, SPDT, 2 Ampere, Track Mounted.
- MIL-R-83726/28(USAF) - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 500 Seconds.
- MIL-R-83726/29(USAF) - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 500 Seconds.
- MIL-R-83726/30(USAF) - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Adjustable Time Delay (External Resistor), 0.1 to 500 Seconds.
- MIL-R-83726/31(USAF) - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, DPDT, 10 Amperes, Adjustable Time Delay (External Resistor), 0.1 to 500 seconds.
- MIL-R-83726/32(USAF) - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 600 Seconds, 1.718" X .530" X 1.520" Envelope Dimensions.
- MIL-R-83726/33(USAF) - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 600 Seconds, 1.718" X .530" X 1.520" Envelope Dimensions.
- MIL-R-83726/34(USAF) - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Adjustable Time Delay (External Resistor), 0.1 to 600 Seconds, 1.718" X .530" X 1.520" Envelope Dimensions.
- MIL-R-83726/35(USAF) - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, 4 PDT, 10 Amperes, Fixed Time Delay, 0.1 to 600 Seconds.
- MIL-R-83726/36(USAF) - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, 4 PDT, 10 Amperes, Fixed Time Delay, 0.1 to 600 Seconds.
- MIL-R-83726/37(USAF) - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, 4 PDT, 10 Amperes, Adjustable Time Delay (External Resistor), 0.1 to 600 Seconds.

CONCLUDING MATERIAL

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5945-0790-03)