

MILITARY SPECIFICATION

SHELTER, ELECTRICAL EQUIPMENT S-280()/G

This amendment forms a part of Military Specification MIL-S-55286E (CR), dated 11 October 1983 and is approved for use by the Communications and Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

PARA 3.4.10: Change subparagraphs a. and b. to read the following:

- "a. 1400 \pm 30 pounds without MK-1079()/G installed.
- b. 1410 \pm 30 pounds with MK-1079()/G installed."

PAGE 10

PARA 3.6.2: Delete the third sentence and replace with the following: "There shall be no permanent deformation, buckling, delamination (see 6.5.2), sealer separation or structural weakness to any part of the shelter; except that deformation in the skids and skid mounting brackets shall not exceed 1/4 inch and a quarter moon shaped (3" x 13") delamination (bulge) which appears on the interior front panel along the floor between the two center members shall not be considered cause for failure."

PAGE 20

PARA 4.5.2.3.1: Delete the second sentence and replace with the following: "In the event that the first delivery quantity is less than 50 units, the sample shall be selected from the first delivery quantity but shall be considered the sample for the first 50 units. Thereafter one sample shall be selected from each additional 150 shelters or fraction thereof (see 3.6.2, 4.6.22, Table VI)."

FSC 5411

MIL-S-55286E (CR)
Amendment 1

PAGE 29

PARA 4.6.13c: Change paragraph in its entirety to read: "c. Flatness: 106 measurements in accordance with SM-D-947181: 4 deviations are acceptable, 5 deviations are cause for rejection of the shelter."

PAGE 35

PARA 4.6.24.2: Fifth line; Change "5,000 kilogram load" to "500 kilogram load."

PAGE 43

FIGURE 4: In parts table; delete item no. "13 - 1 inch wide oak wedges."

CUSTODIAN
ARMY - CR

PREPARING ACTIVITY
ARMY-CR
PROJECT NO: 5411-A027