

| INCH-POUND |

| NOTICE OF INACTIVATION
FOR NEW DESIGN |

MIL-S-6049A
NOTICE 1
22 January 1991

MILITARY SPECIFICATION
STEEL, CHROME-NICKEL-MOLYBDENUM (8740) BARS
AND REFORGING STOCK (AIRCRAFT QUALITY)

This notice should be filed in front of MIL-S-6049A dated 28 June 1967.

MIL-S-6049A is inactive for new design and is no longer used by the Air Force except for replacement purposes.

For future acquisitions, use Society of Automotive Engineers (SAE) specifications.

AMS 6322K, Steel Bars, Forgings, and Rings 0.50Cr - 0.55Ni - 0.25Mo (0.38 - 0.43C)
(SAE 8740)

AMS 6325F, Steel Bars and Forgings, 0.50Cr - 0.55Ni - 0.25Mo(0.38 - 0.43C) (SAE
8740) Heat Treated, 105,000 psi (724 MPa) Tensile Strength

AMS 6327G, Steel Bars and Forgings, 0.50Cr - 0.55Ni - 0.25Mo (0.38 - 0.43C) (SAE
8740) Heat Treated, 125,000 psi (862 MPa) Tensile Strength.

(Application for copies of AMS publication should be addressed to the Society of
Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096).

Custodians:
Army - MR
Navy-AS
Air Force - 11

Preparing activity:
Air Force - 11

Reviewer activities:
Army - MI, AV, AR
Air Force - 84

Proj No. 9510-0809

User activities:
Army - AT, MU
Navy - OS

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is
unlimited

FSC 9510