

MIL-S-6904B
AMENDMENT-1
3 December 1969

MILITARY SPECIFICATION
SIGNALS, EMERGENCY WARNING,
GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-S-6904B, dated 19 April 1965, and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 7, paragraph 4.4.2.1: Delete, and substitute the following:

"4.4.2.1 Sampling plan A - A sample from each lot shall be selected in accordance with MIL-STD-105, Special Inspection Level S-2, acceptance number zero, and subjected to the following tests:

- (a) Temperature rise (see 4.6.3)
- (b) Low-voltage operation (see 4.6.4)
- (c) Dielectric strength (see 4.6.5)
- (d) Current consumption (see 4.6.6)
- (e) Sound intensity (see 4.6.7)
- (f) Endurance (see 4.6.8)
- (g) Sound frequency (see 4.6.9)"

Page 7, paragraph 4.4.2.2: Delete in its entirety.

Page 9, paragraph 4.6.11.7: Delete, and substitute the following:

"4.6.11.7 Vibration - The signal assembly shall be subjected to a vibration test in accordance with Procedure XII except that

- (1) the vibration amplitude (total excursion) shall be .060 inch,
- (2) the vibration frequency continually varying between 10 and 55 cps and (3) the signal shall be operated at intervals during the test. Upon the completion of the test the signal shall operate satisfactorily. It shall not operate inadvertently."

FSC 6340

MIL-S-6904B

Custodians:

Army - AV
Navy - AS
Air Force - 82

Preparing Activity:

Navy - AS
(Project No. 6340-0054)

Review Activities:

Army - AV
Navy - AS
Air Force - 82, 11

User Activities:

Army -
Navy - CG
Air Force -