

MIL-S-81824/3


15 June 1984

MILITARY SPECIFICATION SHEET

SPLICE, COAXIAL CABLE, ELECTRIC, PERMANENT, CRIMP STYLE
COPPER, INSULATED, ENVIRONMENT RESISTANT, CLASS 1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the splice, described herein shall consist of this specification sheet and the latest issue of MIL-S-81824.



NOTES:

1. Dimensions are in inches.
2. "B" Diameter shall not include color stripe.
3. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.

FIGURE 1. Splice assembly.


MIL-S-81824/3

TABLE I CONSTRUCTION DETAILS

| Military Part Number | Center Conductor Diameter Range | Color Code | A | B | C | D | Shield Splice E | | | Sealing Sleeve F | | Filler Sleeve G | | | H max. | J max. | MIL-C-17 Applicable Cables |
|----------------------|---------------------------------|------------|--------------|--------------|--------------|--------------|-----------------|---------|----------|------------------|---------|-----------------|---------|---------|--------|--------|------------------------------------|
| | | | | | | | (a) min | (d) min | (c) max. | (a) min | (b) max | (a) min | (e) max | (f) nom | | | |
| M81824/3-1 | .020 .010 | Yellow | .032 .022 | .080 .075 | .510 .490 | .245 .225 | 118 | .060 | .070 | 118 | .025 | NONE | | | .200 | 270 | /94 RG-179 /113 RG-316 /172 |
| M81824/3-2 | .020 .010 | Yellow | .032 .022 | .080 .075 | .510 .490 | .245 .225 | 157 | .075 | .080 | 157 | .051 | 157 | .070 | 105 | .250 | 315 | /95 RG-180 |
| M81824/3-3 | .040 .020 | Red | .053 .045 | .080 .075 | .510 .490 | .245 .225 | 236 | .118 | .137 | 236 | .075 | 236 | .070 | 118 | 300 | .350 | /110 RG-302 /111 RG-303 /170 |

| INCHES | mm | INCHES | mm | INCHES | mm |
|--------|------|--------|------|--------|-------|
| .010 | 0.25 | .075 | 1.91 | .225 | 5.72 |
| .020 | 0.51 | .080 | 2.03 | .230 | 5.84 |
| .022 | 0.56 | .105 | 2.67 | .236 | 5.99 |
| .025 | 0.64 | .110 | 2.79 | .245 | 6.22 |
| .026 | 0.66 | .118 | 3.00 | .250 | 6.35 |
| .032 | 0.81 | .135 | 3.43 | .270 | 6.86 |
| .040 | 1.02 | .137 | 3.48 | .300 | 7.62 |
| .045 | 1.14 | .155 | 3.94 | .315 | 8.00 |
| .050 | 1.27 | .157 | 3.99 | .350 | 8.89 |
| .053 | 1.35 | .200 | 5.08 | .490 | 12.45 |
| .060 | 1.52 | .210 | 5.33 | .510 | 12.95 |
| .070 | 1.78 | | | | |

MIL-S-81824/3

SELECTION GUIDE

- (a) As supplied. Cable jacket diameter must be less than this value.
- (b) Recovered I.D., through meltable inserts of sealing sleeve. Cable dielectric diameter must be greater than this value.
- (c) Recovered I.D., through shrinkable shield of shield splice sleeve. Cable shield diameter must be greater than this value. Shield may be folded back over cable jacket to increase its diameter.
- (d) Recovered I.D., through meltable inserts of shield splice sleeve. Cable jacket diameter must be greater than this value.
- (e) Recovered I.D.
- (f) Recovered O.D. measured when installed on metal crimp splice.

TABLE 11. CRIMP TOOLS

| Splice Part No. | Basic Crimp Tool No. | Die No. |
|----------------------------|-----------------------------------|--------------------------------------------------------------|
| M81824/3-1 /3-2 /3-3 | M22520/5-01 or M22520/10-01 | M22520/5-103 USE RED DIE or AWG 26-20 M22520/10-104 |

MATERIAL: METAL CRIMP SPLICE: Copper per ASTM B75-81a, Tin-plated.

SEALING SLEEVE:

Sleeve Material: Transparent blue poly(vinylidene fluoride) or equivalent. See 3.3.3.

Sealing Material: Fluorocarbon-based thermoplastic, or equivalent.

FILLER SLEEVE: Heat-shrinkable polyolefin based thermoplastic.

SHIELD SPLICE SLEEVE:

Sleeve Material: Transparent blue poly(vinylidene fluoride) or equivalent. See 3.3.3.

Sealing Material: Fluorocarbon-based thermoplastic, or equivalent.

Shield Splice: Copper-wire braid, coated with solder and flux. Type Sn63 RA (QQ-S-571) preferred.

MIL-S-81824/3

Qualification:

Test Specimens: Splice shall be installed in the center of a four foot length of the cables listed in Table I. The cable shall be the smallest diameter applicable for the splice tested. The Inner Conductor splice shall be installed using the crimp tool listed in Table II. The sealing sleeve, filler sleeve, and shield splice sleeve shall be installed using a standard forced air heat gun.

Requirements: All requirements shall be as specified except the following:

- (1) The Tensile Strength of the test specimen shall be not less than 75% of the unspliced cable. The unspliced cable shall be tested the same as the spliced cable.
- (2) Group IV: Not applicable.
- (3) Voltage Drop: Not applicable. Substitute Attenuation and Structural Return Loss. These tests shall be run per the applicable paragraphs of MIL-C-17. These tests shall be run initially on four foot lengths of cable and then the same pieces of cable shall be cut in half, spliced, and retested prior to conditioning.

| <u>Test</u> | <u>Requirement</u> |
|------------------------------|---------------------------------------------------------------------|
| Attenuation (Insertion Loss) | Not more than 1db increase over unspliced cable. Measured at 3 GHz. |
| Structural Return Loss | 2db maximum decrease over unspliced cable across band 0 to 3 GHz. |

REQUIREMENTS:

1. No etching or solvent treating of the associated cable insulation shall be permitted.
2. Operating frequency range: 50 MHz to 3 GHz.
3. Complete assembly instructions shall be furnished by the vendor with each splice assembly (Figure 1) acquired under this specification. The instruction sheet shall be approved by the qualification activity.

MIL-S-81824/3

Custodians:

Army - ER
Navy - AS
USAF - 85

Preparing Activity:

Navy - AS
(Project No. 5940-0963)

Review Activity:

Army - AV
Navy -
USAF - 11, 99
DSA - GS

User Activity:

Army - MI
Navy - EC, MC, SH, OS

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (*DO NOT STAPLE*), and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer
Naval Air Engineering Center
Engineering Specifications and Standards Department
(ESSD), Code 93
Lakehurst, NJ 08733




NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON, D.C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Air Engineering Center
Engineering Specifications and Standards Dept.
(ESSD), Code 93
Lakehurst, NJ 08733



STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

| | | | |
|--------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------|--|
| 1 DOCUMENT NUMBER MIL-S-81824/3 | | 2 DOCUMENT TITLE SPLICE, COAXIAL CABLE, ELECTRIC, PERMANENT, CRIMP STYLE COPPER, INSULATED, ENVIRONMENT RESISTANT, CLASS 1 | |
| 3a. NAME OF SUBMITTING ORGANIZATION | | 4 TYPE OF ORGANIZATION (Mark one) | |
| b ADDRESS (Street, City, State, ZIP Code) | | <input type="checkbox"/> VENDOR | |
| | | <input type="checkbox"/> USER | |
| 5 PROBLEM AREAS | | <input type="checkbox"/> MANUFACTURER | |
| | | <input type="checkbox"/> OTHER (Specify) _____ | |
| | | | |
| a. Paragraph Number and Wording | | | |
| b. Recommended Wording | | | |
| c. Reason/Rationale for Recommendation | | | |
| 6 REMARKS | | | |
| 7a. NAME OF SUBMITTER (Last, First, MI) - Optional | | b WORK TELEPHONE NUMBER (Include Area Code) - Optional | |
| c MAILING ADDRESS (Street, City, State, ZIP Code) - Optional | | 8 DATE OF SUBMISSION (YYMMDD) | |

(TO DETACH THIS FORM, CUT ALONG THIS LINE)