

PAGE 5

Table III: Delete present table and substitute the following table:

"Table III, Mechanical Properties

Nominal O.D. Inches	Nominal Wall Thickness Inch	Tensile Strength psi	Yield Strength at 0.2% Offset psi, min	Elongation	
				in 2 in., Strip	%, min Full Tube
Up to 0.188, incl	Up to 0.016, incl	75,000 - 120,000	30,000	--	33
	Over 0.016	75,000 - 105,000	30,000	--	35
Over 0.188 to 0.500, incl	Up to 0.010, incl	75,000 - 115,000	30,000	30	35
	Over 0.010	75,000 - 105,000	30,000	30	35
Over 0.500	Over 0.010	75,000 - 105,000	30,000	30	35

PAGE 6

3.10, lines 5, 6, 7 and 8, last two sentences: Delete and substitute:
"Centerless grinding of the O.D. surface or grit blasting of outer and inner surfaces are not acceptable. When tubing is fabricated by welding, it shall be so processed as to eliminate the bead reinforcement or any dimensional indication whatever of the presence or location of the weld."

add new paragraph to Section 3:

"3.11 Tolerances

3.11.1 Round tubing. Tolerances shall conform to MS 33531 or MS33533 as applicable."

PAGE 8

4.6.2, line 1: Delete "pieces" and substitute "piece".

PAGE 9

4.8.1, add new sentence to end of paragraph:

"A slight discoloration of the cloth of fibrous material shall not be a cause for rejection."

PAGE 10

6.2, line (c): Delete "(see 3.8 and 3.9)" and substitute "(see 3.7 and 3.8)".

Custodians:

Army - MR
Navy - AS
Air Force - 11

Preparing Activity:

Air Force - 11

Project No. 4710-0356

Review Activities:

Army - MI, ME, AR
Air Force - 13, 19, 99
DSA - CS

User Activities:

Army - AT
Navy - OS, YD