

MIL-STD-00415C(USAF)
21 October 1968

USED IN LIEU OF
MIL-STD-415B
8 February 1961

MILITARY STANDARD

TEST PROVISIONS

FOR ELECTRONIC SYSTEMS AND ASSOCIATED EQUIPMENT,

DESIGN CRITERIA FOR

MIL-STD-00415C(USAF)
21 October 1968

DEPARTMENT OF AIR FORCE

Test Provisions for Electronic Systems and Associated Equipment,
Design Criteria for

MIL-STD-00415C(USAF)

1. This standard has been approved by the Department of the Air Force and is mandatory for use, effective on date of issue, by that activity.
2. Recommended changes, additions, or deletions should be addressed to Commander, Aeronautical Systems Division, Attn: ASNPS-20, Wright-Patterson Air Force Base, Ohio 45433.

CONTENTS

SECTION		PAGE
1.	SCOPE	1
1.1	Coverage	1
1.2	Purpose	1
1.3	Classification of test provisions	1
2.	REFERENCED DOCUMENT	2
3.	DEFINITIONS	2
4.	GENERAL REQUIREMENTS	3
4.1	Applicability of standard	3
4.2	Analysis of end item	3
4.3	Quality assurance	3
5.	DETAIL REQUIREMENTS	3
5.1	Design	3
5.2	Test capabilities	4
5.2.1	General design considerations	4
5.2.1.1	Accuracy	4
5.2.1.2	Maintainability	4
5.2.1.3	Accessibility	4
5.2.1.4	Degradation and damage	4
5.2.1.5	Lead and wire lengths	4
5.2.1.6	Weight and space	5
5.2.2	Automatic checkout and automatic monitoring capabilities	5
5.2.2.1	Automatic checkout capability	5
5.2.2.2	On-board/on-site automatic monitoring capability	5
5.2.2.3	External receptacle(s)	5
5.2.3	BIT capability	6
5.2.3.1	Applicability of test provision classes	6
5.2.3.2	Self-test provisions	6
5.2.3.3	BIT provisions	6
5.2.4	Test points	6
5.2.4.1	Designation	6
5.2.4.2	Quantitative testing	6
5.2.4.3	External test points	7
5.2.4.4	Internal test points	7
5.2.4.5	Mechanical test points	7

MIL-STD-00415C(USAF)
21 October 1968

CONTENTS (CONT' D)

SECTION		PAGE
5.3	Human engineering requirements	7
5.3.1	High voltage hazard	7
5.3.2	Marking and color coding	7
5.3.2.1	Marking of test points	7
5.3.2.2	Marking of meters	8
5.3.2.3	Color coding of test points	8
6.	NOTES	8
6.1	Intended use	8
6.2	Ordering data	8

MIL-STD-00415C(USAF)
21 October 1968

This limited coordination Military standard has been prepared by the Department of the Air Force based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Standard MIL-STD-415B. It is subject to modification. However, pending its promulgation as a coordinated Military standard, it may be used in procurement.

1. SCOPE

1.1 Coverage. This standard establishes design criteria for test provisions that permit the functional and static parameters of electronic systems and associated equipment to be monitored, evaluated, or isolated. These test provisions consist of the following:

- a. An external test receptacle for connecting automatic, semi-automatic, or manual checkout equipment or automatic monitoring equipment (see 5.2.2).
- b. A built-in test capability (see 5.2.3).
- c. Test points (see 5.2.4).

1.2 Purpose. The purpose of this standard is to provide test provisions that will adequately support a defined maintenance concept.

1.3 Classification of test provisions. For the purpose of this standard test provisions are classified by the end item level of maintenance they are to support. Some provisions may support more than one maintenance level.

1.3.1 Class A test provisions. Class A test provisions evaluate end item performance. They provide the means to determine whether the end item is functioning within the performance limits specified in the end item specification.

1.3.2 Class B test provisions. Class B test provisions fault isolate end item malfunctions to a replaceable unit. (RU).

1.3.3 Class C test provisions. Class C test provisions fault isolate end item malfunctions to a replaceable item (RI).

1.3.4 Class D test provisions. Class D test provisions consist of test points (jacks, terminal boards, circuit junctions, etc.) that isolate malfunctions of items that have fixed circuitry (such as printed circuits, circuit cards, modules, etc.) to an individual circuit and piece part level.

MIL-STD-00415C(USAF),
21 October 1968

2. REFERENCED DOCUMENT

2.1 The following document, of the issue in effect on the date of invitation for bids or request for proposal, form a part of this standard to the extent specified herein.

MIL-STD-1472 Human Engineering Design Criteria For Military Systems,
Equipment and Facilities

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. DEFINITIONS

3.1 The terms used in this standard are defined as follows:

- a. Test provisions: The end item parts and circuitry which provide a capability for testing the end item or associated end items.
- b. End item: A system, subsystem, equipment, replaceable unit (RU), or replaceable item (RI).
- c. Automatic monitoring equipment (AME): An equipment that is designed to automatically conduct analysis of functional or static parameters, evaluate the degree of performance degradation, and perform fault isolation of end item malfunctions.
- d. Automatic checkout equipment (ACE): An equipment designed to check functional parameters and to perform fault isolation of end item malfunctions.
- e. Test point: A convenient and safe access to a single point in a circuit or mechanism used to measure or inject a significant quantity for the purpose of evaluating or troubleshooting the circuit mechanisms.
- f. Replaceable unit (RU): Any unit that is designed and packaged to be readily removed and replaced without unnecessary calibration or adjustment.
- g. Replaceable item (RI): An item that is designed and packaged in an RU for ready removal and replacement. In general, a plug-in module is considered a replaceable item.
- h. Go-no-go testing: Testing that presents results by visual display. Go-no-go testing is further divided into presence and comparative testing.
 - (1) Presence tests. Presence tests verify the presence, or absence, of end item signals or characteristics. Such signals or characteristics are those which are not tolerance critical to operation of the end item.

MIL-STD-00415C(USAF)

21 October 1968

(2) Comparative tests. Comparative tests compare end item signal or characteristic values with a specified tolerance band and present the operator with a go-no go readout; a "Go" for signals within tolerance, and a "No Go" for signals out of tolerance.

i. Marginal testing: Testing that presents results on an indicator that has tolerance zones for evaluating the signal or characteristic being tested. (For example: a green zone might indicate an acceptable tolerance range; a yellow zone, a tolerance range representing marginal operation; and a red zone, a tolerance that is unsatisfactory for operation of the end item.)

j. Quantitative testing: Testing that monitors or measures the specific quantity, level, or amplitude of a characteristic to evaluate the operation of an end item. The output of such tests are presented as finite or quantitative values of the associated characteristics.

4. GENERAL REQUIREMENTS

4.1 Applicability of standard. The requirements of this standard shall apply to the extent specified by the referencing specification or the contract. When this standard is referenced by the detail specification or the contract without additional limiting requirements, this standard shall apply in its entirety.

4.2 Analysis of end item. The contractor shall analyze the end item design to determine the test provisions that are required to support it. The type, amount, and configuration of test provisions shall be compatible with the end item maintenance concept approved by the procuring activity. When the contract requires a guidance meeting the analysis shall also be governed by the decisions made during the meeting.

4.2.1 The contractor shall consider all levels at which the end item is to be maintained such as organizational (flight line/on-board/on-site), field, or depot levels of maintenance. In determining the test provisions to be provided the contractor shall take into account the environments in which the item is to be maintained and the skill levels of the personnel who will use the provisions. He shall ensure that no area of end item maintenance is overlooked. Inherent self-test capabilities shall be considered. The contractor shall insure a minimum of duplication in the capabilities of test provisions ultimately decided upon.

4.3 Quality assurance. Test provisions shall meet as a minimum the same design requirements and quality assurance provisions specified in the applicable specification for the end item of which they are a part.

5. DETAIL REQUIREMENTS

5.1 Design. Test provisions shall be provided in end items to facilitate performance evaluation, malfunction detection, and maintenance. The specific test provisions to be designed as part of the end item shall depend, for the most part, upon the operational

MIL-STD-00415C(USAF)

21 October 1968

and maintenance demands placed on the end item by the maintenance concept, or the contract. The design of test provisions shall assure that their operation is simple, fool proof, and fail safe. Their complexity shall be minimized consistent with the achievement of the requirements specified in the end item specification and this standard.

5.2 Test capabilities. Test provisions shall include one or more of the test capabilities specified herein.

5.2.1 General design considerations

5.2.1.1 Accuracy. The design of test provisions shall permit accurate, decisive, and repeatable measurement of end item characteristics and parameters. The accuracy of testing or sensing circuitry shall exceed that of the characteristic or parameter being tested or sensed.

5.2.1.2 Maintainability. The design of test provisions shall be such that the provisions can be readily maintained with a minimum expenditure of manhours and with minimum downtime of the item in which they are contained.

5.2.1.2.1 The design shall utilize readily available and reliable parts. The number and type of parts used shall be held to a minimum consistent with providing the required capability. Parts and components requiring a minimum of adjustment, cleaning, and protection shall be used.

5.2.1.2.2 To the maximum extent practicable, modular construction shall be used. The arrangement and mounting of parts shall be such that test provision malfunctions can be readily isolated and the cause of the malfunction corrected by simple replacement of modules or plug-in components.

5.2.1.2.3 The design of test provisions shall include a capability for verifying that the end item is operational. Provisions requiring calibration shall be kept to a minimum. When calibration facilities are necessary, they shall be so designed that calibration can be easily performed and that the time between calibration is as great as possible.

5.2.1.3 Accessibility. Test provisions shall be so designed that they provide the optimum of accessibility to equipment and personnel.

5.2.1.4 Degradation and damage. The design or use of test provisions shall not degrade the performance of the end item in which they are contained. The provisions shall also be provided with adequate overload or decoupling protection to insure that the provisions are not damaged by end item signals or characteristics which may exceed specified tolerances.

5.2.1.5 Lead and wire lengths. Test provision wiring shall be routed to minimize possible EMI effects and to restrict wire lengths to a minimum.

MIL-STD-00415C(USAF)
21 October 1968

5.2.1.6 Weight and space

5.2.1.6.1 The selection of parts and design of test provisions shall be such that the provisions are incorporated in the end item with a minimum addition of weight and requiring a minimum of space. The contractor shall make maximum use of state-of-the-art miniaturized components and miniaturization techniques. When integrated circuit design is practical, it shall be employed to the maximum extent possible.

5.2.1.6.2 Unless a deviation is obtained from the procuring activity, the weight of test provisions incorporated in airborne equipment shall not exceed three percent of the weight of the item in which it is contained.

5.2.2 Automatic checkout and automatic monitoring capabilities

5.2.2.1 Automatic checkout capability. The automatic checkout capability shall permit automatic checkout equipment (ACE) to conduct analysis of functional parameters of an end item to evaluate performance and to determine location of a malfunction.

5.2.2.1.1 Applicability of test provision classes. Class A, B, and C test provisions shall be applicable to the automatic checkout capability.

5.2.2.2 On-board/on-site automatic monitoring capability. The on-board/on-site automatic monitoring capability shall permit automatic monitoring equipment (AME) to conduct analysis of functional or static parameters of an end item to evaluate the degree of performance degradation and to determine location of a malfunction.

5.2.2.2.1 Applicability of test provision classes. Class A, B, and C test provisions shall be applicable to the on-board/on-site automatic monitoring capability.

5.2.2.3 External receptacle(s). Automatic checkout or automatic monitoring of an end item shall be accomplished by the availability of an accessible electrical receptacle(s) that is flush mounted on the end item. The electrical receptacle(s) for automatic checkout and monitoring shall be readily accessible for connection to ACE and AME. When ACE receptacles are available on the end item, AME shall make maximum use of these receptacles.

5.2.2.3.1 The external receptacle(s) will be utilized by either automatic, semi-automatic, or manual checkout equipment.

5.2.2.3.2 The external receptacle(s) shall be provided to facilitate the automatic checkout capability or the automatic monitoring capability even though a built-in test capability or test points exist in the design of the end item.

5.2.2.3.3 The arrangement of receptacle(s) shall provide maximum utilization of the space available on the accessible surface of the end item. Where multiple receptacles are used, the space between such receptacles shall not be less than 1 inch. Receptacles shall be of the quick disconnect type.

MIL-STD-00415C(USAF)

21 October 1968

5.2.3 BIT capability. The built-in-test (BIT) capability shall evaluate end item malfunctions by means of self-test or BIT provisions. The built-in-test capability shall facilitate the following:

a. Go-no-go testing. Unless the contract or approved maintenance concept specifies otherwise, go-no-go testing as defined by this document shall be primarily used to satisfy the BIT capability.

b. Marginal testing. When critical end item parameters or characteristics are subject to change or drift and BIT capabilities must be used, these areas shall be tested by marginal testing techniques as defined in this standard.

5.2.3.1 Applicability of test provision classes. Class A and B test provisions shall be applicable to the BIT capability.

5.2.3.2 Self-test provisions. Self-test provisions shall be an inherent part of an end item. These provisions shall serve a dual function; end item performance evaluation, and complementing BIT provisions to provide end item testing.

5.2.3.2.1 When self-test provisions are practical, the contractor shall use them; however, their use shall not jeopardize the operation or performance of the end item.

5.2.3.3 BIT provisions. BIT provisions shall be added to an end item for the sole purpose of testing the item. They shall be simple in design and operation, accurate, easily maintained, preferably more reliable than the circuitry providing performance, and shall not degrade the performance of the end item in which they are incorporated.

5.2.3.3.1 Ease of operation. BIT provisions shall provide optimum convenience of use and operation. The design of controls and read-out devices shall be such that they can be easily used and interpreted by low skill personnel. To the maximum extent possible it shall be possible to operate the provisions with minimum reference to end item handbooks. The need for external equipment or tools to supplement this testing capability shall be minimized.

5.2.4 Test points

5.2.4.1 Designation. Test points shall be provided for end item parameters and characteristics which require testing and are not tested by other test provisions. Test point capabilities shall not duplicate the capabilities of the other test provisions unless specifically approved by the procuring activity. The number of test points shall be kept to a minimum but sufficient to provide the scope of maintenance required of them.

5.2.4.2 Quantitative testing. To the maximum extent practical, test points shall be used to perform quantitative testing as defined by this document.

MIL-STD-00415C(USAF)
21 October 1968

5.2.4.3 External test points. When the maintenance concept or contract directs external test points be provided, they will be limited to fulfilling the Class A and B test provision requirements of this document and shall be located at a readily accessible surface of the end item. The test points shall provide for the connection of electrical or mechanical external measuring or stimuli equipments. Unless otherwise specified by the procuring activity, electrical test points shall be of the jack type design.

5.2.4.4 Internal test points. Internal test points shall be limited to fulfilling the Class C and D test provision requirements of this document and shall be located within the end item. These test points shall provide for the connection of electrical or mechanical measuring or stimuli equipments. Class C electrical test points shall be of the "stand-off" terminal type. Class D electrical test points shall preferably be of the stand-off type, but when circuit junctions are readily accessible for connection of the above specified equipments, the junction may be considered as a test point.

5.2.4.5 Mechanical test points. When characteristics of the end item are to be tested by mechanical means or the item is to be provided with mechanical inputs, the associated mechanical test points shall be designed to utilize general purpose devices or tools to the maximum extent possible. In no case, however, shall the design of the required testing capability be degraded to utilize existing equipment.

5.3 Human engineering requirements. Human engineering design criteria and principles shall be so applied in the design of test provisions that safe, reliable, and effective performance by operator and maintenance personnel is achieved and personnel skill requirements and training time are minimized. The design of test provisions shall conform with the applicable detailed human engineering criteria established in MIL-STD-1472.

5.3.1 High voltage hazard. When operation or maintenance of an end item employing potentials in excess of 300 volts requires that these voltages be measured, the end item shall be provided with test provisions so that these voltages may be measured at potential levels of less than 300 volts relative to ground. The above voltages shall be construed as applying to direct current (dc), alternating current (ac), and dc plus ac voltages.

5.3.2 Marking and color coding

5.3.2.1 Marking of test points. All test points shall be permanently labeled to provide the clearest designation possible, both in terms of identification and legibility. Particular attention shall be given to the environmental conditions under which the test point must be identified in the equipment installation. Where space permits, a complete word description of the test point shall be provided. Otherwise, carefully chosen abbreviations or reference characters may be used. If possible, the within-tolerance range to be measured at the test point shall be included in the label. Water-proof ink shall not be considered as a permanent marking unless suitably protected against all environments to which it will be exposed.

MIL-STD-00415C(USAF)

21 October 1968

5.3.2.1.1 Multiple test points. When sequential testing is required, test points shall be grouped in a line or matrix reflecting the sequence of tests to be made. An outlined matrix array of test points shall also be used when multiple test points are associated with a single system. Each test point shall be assigned an alphanumeric designation and appropriately referenced in the applicable maintenance instructions.

5.3.2.2 Marking of meters. Meters shall be so marked that they may be read with ease, accuracy, and speed; and when a voltage or current is to be held within limits corresponding to a given sector of the meter scale, that sector shall be clearly marked for ease of observation. Meters used in conjunction with selector switch mechanisms shall be similarly labeled according to space limitations on the meter face. Otherwise, the subsystem or circuit designation and within-tolerance range shall be specified at each switch position.

5.3.2.3 Color coding of test points

5.3.2.3.1 All external test points shall be color coded to provide an indication of the type of signal to be obtained at that point. The following shall be the minimum color coding required:

- | | |
|---|---------------------------|
| a. Less than 120 volts ac | :White |
| b. 120 volts ac and above | :White encircled with red |
| c. Less than 28 volts dc | :Red |
| d. 28 volts dc and above | :Red encircled with red |
| e. Chassis ground | :Black |
| f. Reference ground other than chassis ground | :Gray. |

NOTE: Encirclement denotes danger.

5.3.2.3.2 Additional color coding of test points shall be as delineated in the applicable specification.

6. NOTES

6.1 Intended use. This document is intended for use by the project engineer and the procuring activity to establish test provision requirements for the end item.

6.2 Ordering data. To implement the requirements of this standard contractual documents should include the following:

- a. Test provision data requirements. The requirements for submission of test provision data.

MIL-STD-00415C(USAF)
21 October 1968

- b. Guidance meeting. A meeting between the contractor and the procuring activity to provide the contractor with system or equipment and AGE guidance relative to the end item maintenance philosophy and required test provisions.
- c. Identification of the specific test capability and class of test provisions required.

Custodian
Air Force - 11

Preparing activity
Air Force - 11

Reviewers
Air Force - 13, 17, 19, 82, 22

Proj No. MISC-6502