

MIL-STD-421B
11 March 1975

SUPERSEDING
MIL-STD-421A
4 December 1967

MILITARY STANDARD

CHAIN, ROLLER; POWER TRANSMISSION AND
CONVEYOR, FLAT LINK PLATES; BASE PITCH,
SINGLE AND MULTIPLE STRAND; CONNECTING
LINKS AND ATTACHMENT LINKS

FSC 3020

MIL-STD-421B
11 March 1975

DEPARTMENT OF DEFENSE

WASHINGTON, DC 20301

Chain, Roller; Power Transmission and Conveyor, Flat Link Plates; Base Pitch, Single and Multiple Strand; Connecting Links and Attachment Links.

MIL-STD-421B

1. This Military Standard is approved for use by all Departments and Agencies of the Department of Defense.
2. Recommended corrections, additions, or deletions should be addressed to Commander, U.S. Army Mobility Equipment Research and Development Center, ATTN: STSFB-DS, Fort Belvoir, VA 22060.

FOREWORD

The American Standards Association Sectional Committee B29, Transmission Chain, Sprockets and Cutters was organized in 1924, redesignated the United States of America Standards Institute in 1966, and again redesignated the American National Standards Institute in 1969. The ANSI Standard B29.1 "Transmission Roller Chains and Sprocket Teeth" and B29.5 "Attachments for Transmission Roller Chains" represent many years of study and research. Prior to organizing sectional committees, the original design of precision roller chains dates back to the 1890's, although various types of drive chains have been used for centuries.

Chain attachments have been in use for many years with numerous configurations and applications; however, the attachments were not interchangeable from one manufacturers chain to another, restricting the user to one source of supply. The need for standardization of dimensions and tolerances to accomplish interchangeability for attachments for roller chain was reviewed and a subcommittee of the Roller Chain Technical Committee of the Association was established in 1947 to propose standards that would obtain interchangeability. The result of this work was reviewed and approved by the Sectional Committee B29.

ANSI B29.1 is broad in scope, covering base pitch, single and multiple strand chains of straight link design, lending themselves to a great number of transmission-conveying usage.

ANSI B29.5 contains modifications of standard chain components to adapt chains for use in conveying, elevating and timing operations. The components most commonly modified are the pin link plate, roller link plate and chain pin.

The developed standards, ANSI B29.1 and ANSI B29.5, insure physical and functional interchangeability, with very few exceptions. The uses for industry and the Government are identical.

MIL-STD-421B

CONTENTS

	<u>Page</u>
Paragraph 1. SCOPE	1
1.1 Coverage	1
1.2 Application	1
2. REFERENCE DOCUMENTS	1
3. DEFINITIONS	1
4. GENERAL REQUIREMENTS (Not applicable)	2
5. DETAILED REQUIREMENTS	2

FIGURES

Figure	Type 1 RC, chain, roller:
	1. Single strand chain
	2. Multiple strand chain
	3. Side view of single and multiple strand chains
	Type 1 CL, link offset:
	4. Single strand link
	5. Multiple strand link
	Type 2 CL, link connecting, roller chain:
	6. Single strand link
	7. Multiple strand link
	Type 3 CL, link combination offset:
	8. Single strand link
	9. Multiple strand link
	10. Side view of single and multiple strand link
	Pin and roller attachment links:
	11. Attachment link, Type 1 PAL and 2 RAL
	12. Attachment link, Type 3 PAL and 4 RAL
	13. Attachment link, Type 5 PAL and 6 RAL
	14. Attachment link, Type 7 PAL and 8 RAL
	15. Attachment link, Type 9 PAL and 10 RAL

TABLES

Table	I. Type 1 RC, chain roller
	II. Type 1 CL, link offset
	III. Type 2 CL, link connecting
	IV. Type 3 CL, link combination offset
	V. Pin and roller attachment links for Type 1 roller chains
	VI. Pin and roller attachment links for Type 1 roller links

MIL-STD-421B

1. SCOPE

1.1 Coverage. This is a design standard covering Type 1 RC, Chain, Roller: Power Transmission and Conveyor, Flat Link Plates; Base Pitch, Single and Multiple Strand, and Connecting Links (CL) and Attachment Links.

1.2 Application. Chains and components covered by this standard with technical characteristics specified herein shall be installed on all new equipment where such types are applicable. This standard does not apply to equipment presently in the military supply system, except as technical characteristics will permit.

2. REFERENCED DOCUMENTS

2.1 The issues of the following documents in effect on the date of invitation for bids form a part of this standard to the extent specified herein:

GOVERNMENTAL

Military Specification:

MIL-C-52058

- Chains, Roller: Power Transmission and Conveyor, with Connecting Links and Attachment Links.

(Copies of specification required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

NONGOVERNMENTAL

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)

B29.1 - Transmission Roller Chains and Sprocket Teeth.

B29.5 - Attachments for Transmission Roller Chains.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

3. DEFINITIONS

3.1 All military and ANSI chain numbers referenced herein are based on chain numbers of ANSI B29.1 and attachment numbers from ANSI B29.5.

MIL-STD-421B

4. GENERAL REQUIREMENTS

(Not applicable.)

5. DETAILED REQUIREMENTS

5.1 Requirements and technical characteristics shall be as specified herein and in MIL-C-52058.

Custodians:

Army - ME
Navy - YD

Preparing activity:

Army - ME

Review activity:

DSA - CS

Project No. 3020-0083

User activities:

Army - AT, MI
Navy - SH

MIL-STD-4218




FIGURE 1. SINGLE STRAND CHAIN




FIGURE 2. MULTIPLE STRAND CHAIN




FIGURE 3. SIDE VIEW OF SINGLE AND MULTIPLE STRAND CHAINS

LEGEND:

- | | |
|---|---|
| A = Nominal distance from pin head to center line of chain. | G = Maximum width of roller link plates. |
| B = Nominal distance from pin end to center line of chain. | H = Nominal thickness of link plates. |
| C = Nominal diameter of pin. | I = Transverse pitch. |
| D = Nominal diameter of roller. | J = Maximum width of roller link. |
| E = Nominal chain width between roller link plates. | K = Minimum distance between pin link plates. |
| F = Maximum width of pin link plates. | L = Minimum hole in bushing. |

REQUIREMENTS:

- Tolerances:

Maximum A = A + 0.020	Nominal I = E + (4.22 x H)
Maximum B = B + 0.020	Maximum J = E + (2.12 x H)
Maximum C = C + 0.0005	Minimum K = J + 0.002
Maximum D = Nominal D	Minimum L = C + 0.0015
- Grade A, carbon and alloy steel chains.
- Grade B, Austenitic steel - corrosive resistant chains.
- Grade C, Martensitic steel - corrosive resistant - magnetic chains.
- Grade A, ANSI Chain numbers 25 through 50 shall be supplied with Class 1, riveted fastening.
- Grade A, ANSI Chain numbers 60 through 240 shall be supplied with Class 2, cottered fastening, unless otherwise specified.

NOTES:

- See Table I for dimensions.
- All dimensions are in inches.
- ANSI chain numbers 25 and 35 are rollerless.
- Dashed numbers (e.g., -2) affixed to ANSI chain numbers (e.g., 40-2) indicate numbers of strands.
- Class 2, cottered fastening may consist of a single cotter through pin holes, or double cutters as shown in figure 3 above, positioned at the option of the manufacturer.
- Material for cotter fasteners shall be compatible with the grade of chain.

TYPE 1RC, CHAIN, ROLLER: POWER TRANSMISSION AND CONVEYING,
FLAT LINK PLATES, BASE PITCH, SINGLE AND MULTIPLE STRAND

X971A

MIL-STD-421B

TABLE I

TYPE IRC, CHAIN ROLLER: POWER TRANSMISSION AND CONVEYING, FLAT LINK PLATES, BASE PITCH, SINGLE AND MULTIPLE STRAND

MIL-STD CHAIN NUMBER	ANSI CHAIN NUMBER	PITCH	MINIMUM ULTIMATE TENSILE STRENGTH POUNDS	APPROX WT/FT POUNDS	NOMINAL WIDTH		PIN DIA. C NOM.	ROLLER DIA. D NOM.	WIDTH E NOM.	LINK PLATES			GRADE
					A	B				WIDTH		THICK	
										F MAX.	G MAX.	H NOM.	
25-IRC-A	25	1/4	780	.085	0.16		.0905	.130	.125	.205	.238	.030	A
35-IRC-A	35	3/8	1,760	.22	0.24								A
35-IRC-B	35		1,450	.22									B
35-IRC-C	35		1,450	.22									C
35-2-IRC	35-2		3,520	.43									A
35-3-IRC	35-3		5,280	.64									A
35-4-IRC	35-4		7,040	.85	0.84		.141	.200	.187	.307	.356	.050	A
40-IRC-A	40	1/2	3,125	.41	0.33								A
40-IRC-B	40		2,600	.41	0.33								B
40-IRC-C	40		2,600	.41	0.33								C
40-2-IRC	40-2		6,250	.82	0.61								A
40-3-IRC	40-3		9,375	1.30	0.90								A
40-4-IRC	40-4		12,500	1.58	1.18								A
41-IRC-A	41	1/2	1,500	.28	0.28								A
41-IRC-B	41		1,450	.28	0.28								B
41-IRC-C	41		1,450	.28	0.28								C
50-IRC-A	50	5/8	4,880	.68	0.41								A
50-IRC-B	50		4,100	.68	0.41								B
50-IRC-C	50		4,100	.68	0.41								C
50-2-IRC	50-2		9,760	1.40	0.76								A
50-3-IRC	50-3		14,640	2.21	1.12								A
50-4-IRC	50-4		19,520	2.80	1.48								A
50-5-IRC	50-5		24,400	3.40	1.84								A
50-6-IRC	50-6		29,280	4.00	2.19								A
60-IRC-A	60	3/4	7,050	1.03	0.51								A
60-IRC-B	60		5,900	1.03	0.51								B
60-IRC-C	60		5,900	1.03	0.51								C
60-2-IRC	60-2		14,100	2.02	0.96								A
60-3-IRC	60-3		21,150	3.02	1.40								A
60-4-IRC	60-4		28,200	4.02	1.85								A
60-5-IRC	60-5		35,250	5.02	2.30								A
60-6-IRC	60-6		42,300	6.02	2.75								A
80-IRC-A	80	1----	12,500	1.69	0.64								A
80-IRC-B	80		10,500	1.69	0.64								B
80-IRC-C	80		10,500	1.69	0.64								C
80-2-IRC	80-2		25,000	3.32	1.23								A
80-3-IRC	80-3		37,500	4.95	1.81								A
80-4-IRC	80-4		50,000	6.70	2.39								A
80-5-IRC	80-5		62,500	8.23	2.96								A
80-6-IRC	80-6		75,000	9.84	3.54								A
100-IRC	100	1-1/4	19,500	2.70	0.79								A
100-2-IRC	100-2		39,000	5.20	1.50								A
100-3-IRC	100-3		58,500	7.80	2.20								A
100-4-IRC	100-4		78,000	10.40	2.91								A
120-IRC	120	1-1/2	28,100	4.00	0.98								A
120-2-IRC	120-2		56,200	7.90	1.88								A
120-3-IRC	120-3		84,300	11.05	2.78								A
120-4-IRC	120-4		112,400	14.70	3.68								A
140-IRC	140	1-3/4	38,300	5.20	1.06								A
140-2-IRC	140-2		76,600	10.10	2.03								A
140-3-IRC	140-3		114,900	13.75	3.00								A
140-4-IRC	140-4		153,200	20.00	3.96								A
160-IRC	160	2----	50,000	6.80	1.27								A
160-2-IRC	160-2		100,000	12.85	2.42								A
160-3-IRC	160-3		150,000	19.20	3.57								A
160-4-IRC	160-4		200,000	25.55	4.73								A
180-IRC	180	2-1/4	63,300	9.30	1.43								A
180-2-IRC	180-2		126,600	18.25	2.73								A
180-3-IRC	180-3		189,900	27.20	4.02								A
180-4-IRC	180-4		253,200	36.30	5.32								A
200-IRC	200	2-1/2	78,000	11.10	1.56								A
200-2-IRC	200-2		156,000	22.81	2.96								A
200-3-IRC	200-3		234,000	32.51	4.45								A
200-4-IRC	200-4		312,000	43.21	5.80								A
240-IRC	240	3----	112,500	16.70	1.85								A
240-2-IRC	240-2		225,000	33.04	3.58								A
240-3-IRC	240-3		337,500	49.37	5.31								A
240-4-IRC	240-4		450,000	65.70	7.04								A

X959A

MIL-STD-421B




FIGURE 4. SINGLE STRAND LINK




FIGURE 5. MULTIPLE STRAND LINK

LEGEND:

- A = Nominal distance from pin head to center line.
 B = Nominal distance from pin end to center line.
 C = Nominal diameter of pin.
 D = Nominal diameter of roller.
 E = Nominal chain width between offset link plates at end where bushing is installed.
 F = Maximum width of offset link plate at end of plate where pin is installed.
 G = Maximum width of offset link plate at end of plate where bushing is installed.
 H = Nominal thickness of link plates.
 I = Transverse pitch.
 J = Maximum width of offset link at end where bushing is installed.
 K = Minimum distance between offset link plates.
 L = Minimum hole in bushing.
 X = Distance from center of bushing to point of offset.
 Y = Distance from center of pin to point of offset.

REQUIREMENTS:

1. Tolerances:

Maximum A = A + 0.020	Maximum J = E + (2.12 x H)
Maximum B = B + 0.020	Minimum K = J + 0.002
Maximum C = C + 0.0005	Minimum L = C + 0.0015
Maximum D = Nominal D	Minimum X = 0.41 x pitch + 0.008
Nominal I = E + (4.22 x H)	Minimum Y = 0.475 x pitch + 0.008
2. Grade A, carbon and alloy steel - connecting links.
3. Grade B, Austenitic steel - corrosive resistant connecting links.
4. Type 1 offset links shall not be used with chains intended for use on military aircraft.

NOTES:

1. See Table II for dimensions.
2. All dimensions are in inches.
3. Offset links for ANSI Chain numbers 25 and 35 are roller-less.
4. Type 1 connecting links are for use with Type 1 RC, ANSI Chain numbers 60 through 240, see Tables I and II.
5. Where type 1 offset links are required for use with Grade C chains, use Grade B connecting links.
6. All type 1 offset links have Class 2, Cottered Fastening.
7. Dash numbers (e.g. -2) affixed to ANSI chain numbers (e.g. 40-2) indicate number of strands.

TYPE 1CL, LINK, OFFSET, ROLLER CHAIN, POWER TRANSMISSION
AND CONVEYOR, BASE PITCH, SINGLE AND MULTIPLE STRAND

X960A

MIL-STD-421B

TABLE II

TYPE ICL, LINK, OFFSET, ROLLER CHAIN TRANSMISSION AND CONVEYOR, BASE PITCH, SINGLE AND MULTIPLE STRAND

MIL-STD CONNECTING LINK NUMBER	ANSI CHAIN NUMBER	PITCH	MINIMUM ULTIMATE TENSILE STRENGTH POUNDS	APPROX WT/FT POUNDS	NOMINAL WIDTH		PIN DIA.	ROLLER DIA.	WIDTH	LINK PLATES			GRADE
					A	B				F MAX.	G MAX.	H NOM.	
60-1RC-1CL-A	60		7,050	0.06	0.64	0.64							A
60-1RC-1CL-B	60		5,300	0.06	0.64	0.64							B
60-2-1RC-1CL	60-2	3/4	14,100	0.13	1.07	1.07							A
60-3-1RC-1CL	60-3		21,150	0.19	1.52	1.52	.234	.469	.500	.615	.712	.094	A
60-4-1RC-1CL	60-4		28,200	0.25	1.97	1.97							A
60-5-1RC-1CL	60-5		35,250	0.32	2.42	2.42							A
60-6-1RC-1CL	60-6		42,300	0.38	2.89	2.89							A
80-1RC-1CL-A	80		12,500	0.14	0.79	0.79							A
80-1RC-1CL-B	80		9,500	0.14	0.79	0.79							B
80-2-1RC-1CL	80-2	1---	25,000	0.27	1.37	1.37							A
80-3-1RC-1CL	80-3		37,500	0.41	1.95	1.95	.312	.625	.625	.820	.950	.125	A
80-4-1RC-1CL	80-4		50,000	0.56	2.52	2.52							A
80-5-1RC-1CL	80-5		62,600	0.68	3.10	3.10							A
80-6-1RC-1CL	80-6		75,000	0.82	3.67	3.67							A
100-1RC-1CL	100		19,500	0.28	0.95	0.95							A
100-2-1RC-1CL	100-2	1-1/4	39,000	0.54	1.65	1.65		.750	.750	1.025	1.188	.156	A
100-3-1RC-1CL	100-3		58,500	0.81	2.36	2.36							A
100-4-1RC-1CL	100-4		78,000	1.08	3.06	3.06							A
120-1RC-1CL	120		28,100	0.50	1.15	1.15							A
120-2-1RC-1CL	120-2	1-1/2	56,200	0.99	2.05	2.05	.437	.875	1.000	1.230	1.425	.187	A
120-3-1RC-1CL	120-3		84,300	1.38	2.94	2.94							A
120-4-1RC-1CL	120-4		112,400	1.84	3.84	3.84							A
140-1RC-1CL	140		38,300	0.76	1.27	1.27							A
140-2-1RC-1CL	140-2	1-3/4	76,600	1.47	2.23	2.23	.500	1.000	1.000	1.435	1.662	.219	A
140-3-1RC-1CL	140-3		114,900	2.00	3.19	3.19							A
140-4-1RC-1CL	140-4		153,200	2.92	4.15	4.15							A
160-1RC-1CL	160		50,000	1.13	1.47	1.47							A
160-2-1RC-1CL	160-2	2---	100,000	2.14	2.63	2.63	.562	1.125	1.250	1.640	1.970	.250	A
160-3-1RC-1CL	160-3		150,000	3.20	3.78	3.78							A
160-4-1RC-1CL	160-4		200,000	4.26	4.93	4.93							A
180-1RC-1CL	180		63,300	1.74	1.77	1.77							A
180-2-1RC-1CL	180-2	2-1/4	126,600	3.42	3.00	3.00	.687	1.406	1.406	1.845	2.137	.281	A
180-3-1RC-1CL	180-3		189,900	5.10	4.30	4.30							A
180-4-1RC-1CL	180-4		253,200	6.81	5.59	5.59							A
200-1RC-1CL	200		78,000	2.31	1.91	1.91							A
200-2-1RC-1CL	200-2		156,000	4.55	3.31	3.31							A
200-3-1RC-1CL	200-3	2-1/2	234,000	6.77	4.80	4.80	.781	1.562	1.500	2.050	2.375	.312	A
200-4-1RC-1CL	200-4		312,000	9.00	6.15	6.15							A
240-1RC-1CL	240		112,500	4.46	2.01	2.01							A
240-2-1RC-1CL	240-2	3---	225,000	9.12	3.74	3.74	.937	1.875	1.875	2.40	2.85	.375	A
240-3-1RC-1CL	240-3		337,500	13.68	5.47	5.47							A
240-4-1RC-1CL	240-4		450,000	18.24	7.20	7.20							A

X961A

MIL-STD-421B




FIGURE 6. SINGLE STRAND LINK PLAN AND SIDE VIEWS




FIGURE 7. MULTIPLE STRAND LINK PLAN AND SIDE VIEWS

LEGEND:

- A = Nominal distance from pin head to center line.
- B = Nominal distance from pin end to center line.
- C = Nominal diameter of pin.
- E = Nominal chain width between roller link plates, dimension used here for determining distance between pin link plates and transverse pitch.
- F = Maximum width of pin link plates.
- H = Nominal thickness of link plates.
- I = Transverse pitch.
- K = Minimum distance between pin link plates.

REQUIREMENTS:

1. Tolerances:

- Maximum A = $A + 0.020$
- Maximum B = $B + 0.020$
- Maximum C = $C + 0.0005$
- Nominal I = $E + (4.22 \times H)$
- Minimum K = $E + (2.12 \times H) + 0.002$

- 2. Grade A, carbon and alloy steel-connecting links.
- 3. Grade B, Austenitic steel-corrosive resistant connecting links.
- 4. Grade C, Martensitic steel - corrosive resistant - magnetic - connecting links.
- 5. Type 2, connecting links, Grades B and C, for ANSI chain numbers 35 through 80 shall be provided with Class 2, cottered fastening, with two cotters as shown in figures 6 and 7 above.

NOTES:

- 1. See Table III for dimensions.
- 2. All dimensions are in inches.
- 3. Type 2 connecting links, Grade A, for ANSI chain number 25 through 50 supplied with Class 3, spring clip fastening.
- 4. Type 2 connecting links, Grade A, for ANSI chain numbers 60 through 240 supplied with Class 2, cottered fastening. Class 2, cottered fastening may consist of a single cotter through pin holes, or a double cotter as shown in figures 6 and 7 above, positioned at the option of the manufacturer.
- 5. Dash numbers (e.g. -2) affixed to ANSI Chain numbers (e.g. 40-2) indicate number of strands.

TYPE 2CL, LINK CONNECTING, ROLLER CHAIN: POWER TRANSMISSION AND CONVEYOR, FLAT LINK PLATES, BASE PITCH, SINGLE AND MULTIPLE STRANDS

X962A

MIL-STD-421B


TABLE III

TYPE 2CL, LINK CONNECTING, ROLLER CHAIN: POWER TRANSMISSION AND CONVEYOR.
FLAT LINK PLATES, BASE PITCH, SINGLE AND MULTIPLE STRANDS

MIL-STD CONNECTING LINK NUMBER	LINK FOR ANSI CHAIN NUMBER	PITCH	MINIMUM ULTIMATE TENSILE STRENGTH POUNDS	APPROX WT/FT POUNDS	NOMINAL WIDTH		PIN DIA	WIDTH	LINK PLATES		GRADE
					A	B			F MAX.	H NOM.	
25-1RC-2CL-A	25	1/4	780	0.01	0.16	0.19	.0905	.125	.205	.030	A
35-1RC-2CL-A	35	3/8	1,760	0.01	0.24	0.34	.141	.187	.307	.050	A
35-1RC-2CL-B	35		1,450	0.01	0.24	0.34					B
35-1RC-2CL-C	35		1,450	0.01	0.24	0.34					C
35-2-1RC-2CL	35-2		3,520	0.02	0.44	0.50					A
35-3-1RC-2CL	35-3		5,280	0.02	0.64	0.70					A
35-4-1RC-2CL	35-4		7,040	0.03	0.84	0.90					A
40-1RC-2CL-A	40	1/2	3,125	0.02	0.33	0.42	.156	.312	.410	.060	A
40-1RC-2CL-B	40		2,600	0.02	0.33	0.42					B
40-1RC-2CL-C	40		2,600	0.02	0.33	0.42					C
40-2-1RC-2CL	40-2		6,250	0.03	0.61	0.68					A
40-3-1RC-2CL	40-3		9,375	0.05	0.90	0.97					A
40-4-1RC-2CL	40-4		12,500	0.07	1.18	1.25					A
41-1RC-2CL-A	41	1/2	1,500	0.01	0.28	0.37	.141	.250	.340	.050	A
41-1RC-2CL-B	41		1,450	0.01	0.28	0.37					B
41-1RC-2CL-C	41		1,450	0.01	0.28	0.37					C
50-1RC-2CL-A	50	5/8	4,880	0.04	0.41	0.48	.200	.375	.512	.080	A
50-1RC-2CL-B	50		4,100	0.04	0.41	0.48					B
50-1RC-2CL-C	50		4,100	0.04	0.41	0.48					C
50-2-1RC-2CL	50-2		9,760	0.07	0.76	0.84					A
50-3-1RC-2CL	50-3		14,640	0.12	1.12	1.20					A
50-4-1RC-2CL	50-4		19,520	0.15	1.48	1.55					A
50-5-1RC-2CL	50-5		24,400	0.18	1.84	1.91					A
50-6-1RC-2CL	50-6		29,280	0.21	2.19	2.27					A
60-1RC-2CL-A	60	3/4	7,050	0.06	0.51	0.64	.234	.500	.615	.094	A
60-1RC-2CL-B	60		5,900	0.06	0.51	0.64					B
60-1RC-2CL-C	60		5,900	0.06	0.51	0.64					C
60-2-1RC-2CL	60-2		14,100	0.13	0.96	1.07					A
60-3-1RC-2CL	60-3		21,150	0.19	1.40	1.52					A
60-4-1RC-2CL	60-4		28,200	0.25	1.85	1.97					A
60-5-1RC-2CL	60-5		35,250	0.32	2.30	2.42					A
60-6-1RC-2CL	60-6		42,300	0.38	2.75	2.89					A
80-1RC-2CL-A	80	1--	12,500	0.14	0.64	0.79	.312	.625	.820	.125	A
80-1RC-2CL-B	80		10,500	0.14	0.64	0.79					B
80-1RC-2CL-C	80		10,500	0.14	0.64	0.79					C
80-2-1RC-2CL	80-2		25,000	0.27	1.23	1.37					A
80-3-1RC-2CL	80-3		37,500	0.41	1.81	1.95					A
80-4-1RC-2CL	80-4		50,000	0.56	2.39	2.52					A
80-5-1RC-2CL	80-5		62,500	0.68	2.96	3.10					A
80-6-1RC-2CL	80-6		75,000	0.82	3.54	3.67					A
100-1RC-2CL	100	1-1/4	19,500	0.28	0.79	0.95	.375	.750	1.025	.156	A
100-2-1RC-2CL	100-2		39,000	0.54	1.50	1.65					A
100-3-1RC-2CL	100-3		58,500	0.81	2.20	2.36					A
100-4-1RC-2CL	100-4		78,000	1.08	2.91	3.06					A
120-1RC-2CL	120	1-1/2	28,100	0.50	0.98	1.15	.437	1.000	1.230	.187	A
120-2-1RC-2CL	120-2		56,200	0.99	1.88	2.05					A
120-3-1RC-2CL	120-3		84,300	1.38	2.78	2.94					A
120-4-1RC-2CL	120-4		112,400	1.84	3.68	3.84					A
140-1RC-2CL	140	1-3/4	38,300	0.76	1.06	1.27	.500	1.000	1.435	.219	A
140-2-1RC-2CL	140-2		76,600	1.47	2.03	2.23					A
140-3-1RC-2CL	140-3		114,900	2.00	3.00	3.19					A
140-4-1RC-2CL	140-4		153,200	2.92	3.95	4.15					A
160-1RC-2CL	160	2--	50,000	1.13	1.27	1.47	.562	1.250	1.640	.250	A
160-2-1RC-2CL	160-2		100,000	2.14	2.42	2.63					A
160-3-1RC-2CL	160-3		150,000	3.20	3.57	3.78					A
160-4-1RC-2CL	160-4		200,000	4.26	4.73	4.93					A
180-1RC-2CL	180	2-1/4	63,300	1.74	1.43	1.77	.687	1.406	1.845	.281	A
180-2-1RC-2CL	180-2		126,600	3.42	2.73	3.00					A
180-3-1RC-2CL	180-3		189,900	5.10	4.02	4.30					A
180-4-1RC-2CL	180-4		253,200	6.81	5.32	5.59					A
200-1RC-2CL	200	2-1/2	78,000	2.31	1.56	1.91	.781	1.500	2.050	.312	A
200-2-1RC-2CL	200-2		156,000	4.55	2.96	3.31					A
200-3-1RC-2CL	200-3		234,000	6.77	4.45	4.80					A
200-4-1RC-2CL	200-4		312,000	9.00	5.80	6.15					A
240-1RC-2CL	240	3--	112,500	3.56	1.85	2.20	.937	1.875	2.46	.375	A
240-2-1RC-2CL	240-2		225,000	7.12	3.58	3.93					A
240-3-1RC-2CL	240-3		337,500	10.68	5.31	5.66					A
240-4-1RC-2CL	240-4		450,000	14.24	7.04	7.38					A

X963A

MIL-STD-421B



LEGEND:

- A = Nominal distance from pin head to center line of chain.
 C = Nominal diameter of pin.
 D = Nominal diameter of roller.
 E = Nominal chain width between offset link plates at end where bushing is installed and nominal width between roller link plates.
 F = Maximum width of offset link plate at end of plate where pin is installed.
 G = Maximum width of offset link plate at end of plate where bushing is installed.
 H = Nominal thickness of link plates.
 I = Transverse pitch.
 J = Maximum width of roller link and maximum width of offset link at end of link where bushing is installed.
 K = Minimum distance between offset link plates.
 L = Minimum hole in bushing.
 X = Distance from center of bushing to point of offset.
 Y = Distance from center of pin to point of offset.

REQUIREMENTS:

1. Tolerances;

Maximum A = $A + 0.020$
 Maximum C = $C + 0.0005$
 Maximum D = Nominal D
 Nominal I = $E + (4.22 \times H)$
 Maximum J = $E + (2.12 \times H)$

Minimum K = $J + 0.002$
 Minimum L = $C + 0.0015$
 Minimum X = $0.41 \times \text{pitch} + 0.008$
 Minimum Y = $0.475 \times \text{pitch} + 0.008$

2. Grade A, carbon and alloy steel - connecting links.

3. Grade B, Austenitic steel - corrosive resistant offset links.

NOTES:

- See Table IV for dimensions.
- All dimensions are in inches.
- Type 3 connecting links for ANSI chain numbers 25 and 35 are rollerless.
- Dash numbers (e.g. -2) affixed to ANSI chain numbers (e.g. 40-2) indicate number of strands.
- Where type 3 offset links are required for use with Grade C chains, Grade B offset links may be used.

TYPE 3CL, LINK COMBINATION OFFSET. ROLLER CHAIN: POWER TRANSMISSION AND CONVEYOR, BASE PITCH, SINGLE AND MULTIPLE STRAND

X964A

MIL-STD-421B

TABLE IV

TYPE 3CL, LINK COMBINATION OFFSET, ROLLER CHAIN: POWER TRANSMISSION
AND CONVEYOR BASE PITCH, SINGLE AND MULTIPLE STRAND

MIL-STD CONNECTING LINK NUMBER	LINK FOR ANSI CHAIN NUMBER	PITCH	MINIMUM ULTIMATE TENSILE STRENGTH POUNDS	APPROX WT/FT POUNDS	NOMINAL WIDTH A	PIN DIA. C NOM.	ROLLER DIA. D NOM.	WIDTH E NOM.	LINK PLATES			GRADE
									WIDTH F MAX.	THICK G MAX.	H NOM.	
25-1RC-3CL-A	25	1/4	780	0.01	0.16	.0905	.130	.125	.205	.238	.030	A
35-1RC-3CL-A	35	3/8	1,760	0.02	0.24	.141	.200	.187	.307	.356	.050	A
35-1RC-3CL-B	35		1,300	0.02	0.24							B
35-2-1RC-3CL	35-2		3,520	0.03	.435							A
35-3-1RC-3CL	35-3		5,280	0.04	.634							A
35-4-1RC-3CL	35-4		7,040	0.05	.834							A
40-1RC-3CL-A	40	1/2	3,125	0.04	0.33	.156	.312	.312	.410	.475	.060	A
40-1RC-3CL-B	40		2,350	0.04	0.33							B
40-2-1RC-3CL	40-2		6,250	0.06	0.61							A
40-3-1RC-3CL	40-3		9,375	0.10	0.90							A
40-4-1RC-3CL	40-4		12,500	0.14	1.18							A
41-1RC-3CL-A	41	1/2	1,500	0.02	0.28	.141	.306	.250	.340	.390	.050	A
41-1RC-3CL-B	41		1,300	0.02	0.28							B
50-1RC-3CL-A	50	5/8	4,880	0.08	0.41	.200	.400	.375	.512	.594	.080	A
50-1RC-3CL-B	50		2,350	0.08	0.41							B
50-2-1RC-3CL	50-2		9,760	0.14	0.76							A
50-3-1RC-3CL	50-3		14,640	0.24	1.12							A
50-4-1RC-3CL	50-4		19,520	0.30	1.48							A
50-5-1RC-3CL	50-5		24,400	0.36	1.84							A
50-6-1RC-3CL	50-6		29,280	0.42	2.19							A
60-1RC-3CL	60	3/4	7,050	0.12	0.51	.234	.469	.500	.615	.712	.094	A
60-2-1RC-3CL	60-2		14,100	0.26	0.96							A
60-3-1RC-3CL	60-3		21,150	0.38	1.40							A
60-4-1RC-3CL	60-4		28,200	0.50	1.85							A
60-5-1RC-3CL	60-5		35,250	0.64	2.30							A
60-6-1RC-3CL	60-6		42,300	0.76	2.75							A
80-1RC-3CL	80	1---	12,500	0.28	0.64	.312	.625	.625	.820	.950	.125	A
80-2-1RC-3CL	80-2		25,000	0.54	1.23							A
80-3-1RC-3CL	80-3		37,500	0.82	1.81							A
80-4-1RC-3CL	80-4		50,000	1.12	2.39							A
80-5-1RC-3CL	80-5		62,500	1.36	2.96							A
80-6-1RC-3CL	80-6		75,000	1.64	3.54							A
100-1RC-3CL	100	1-1/4	19,500	0.56	0.79	.375	.750	.750	1.025	1.188	.156	A
100-2-1RC-3CL	100-2		39,000	1.08	1.50							A
100-3-1RC-3CL	100-3		58,500	1.62	2.20							A
100-4-1RC-3CL	100-4		78,000	2.16	2.91							A
120-1RC-3CL	120	1-1/2	28,100	1.00	0.98	.437	.875	1.000	1.230	1.425	.187	A
120-2-1RC-3CL	120-2		56,200	1.98	1.88							A
120-3-1RC-3CL	120-3		84,300	2.76	2.78							A
120-4-1RC-3CL	120-4		112,400	3.68	3.68							A
140-1RC-3CL	140	1-3/4	38,300	1.52	1.06	.500	1.000	1.000	1.433	1.662	.219	A
140-2-1RC-3CL	140-2		76,600	2.94	2.03							A
140-3-1RC-3CL	140-3		114,900	4.00	3.00							A
140-4-1RC-3CL	140-4		153,200	5.84	3.96							A
160-1RC-3CL	160	2---	50,000	2.26	1.27	.562	1.125	1.250	1.640	1.900	.250	A
160-2-1RC-3CL	160-2		100,000	4.38	2.42							A
160-3-1RC-3CL	160-3		150,000	6.40	3.57							A
160-4-1RC-3CL	160-4		200,000	8.52	4.73							A
180-1RC-3CL	180	2-1/4	63,300	3.48	1.43	.687	1.406	1.406	1.845	2.137	.281	A
180-2-1RC-3CL	180-2		126,600	6.84	2.73							A
180-3-1RC-3CL	180-3		189,900	10.20	4.02							A
180-4-1RC-3CL	180-4		253,200	13.62	5.32							A
200-1RC-3CL	200	2-1/2	78,000	4.62	1.56	.781	1.562	1.500	2.050	2.375	.312	A
200-2-1RC-3CL	200-2		156,000	9.10	2.96							A
200-3-1RC-3CL	200-3		234,000	13.54	4.45							A
200-4-1RC-3CL	200-4		312,000	18.00	5.80							A
240-1RC-3CL	240	3---	112,500	8.12	1.85	.937	1.875	1.875	2.46	2.85	.375	A
240-2-1RC-3CL	240-2		225,000	16.24	3.58							A
240-3-1RC-3CL	240-3		337,500	24.36	5.31							A
240-4-1RC-3CL	240-4		450,000	32.48	7.04							A

X965A

MIL-STD-421B




FIGURE 11




FIGURE 12




FIGURE 13

PIN AND ROLLER ATTACHMENT LINKS
FOR
TYPE 1 ROLLER CHAINS

X966

MIL-STD-421B





FIGURE 14






FIGURE 15

TABLE V

ANSI CHAIN NUMBER	CHAIN PITCH	B MIN.	C NOM.	D	E MAX.	F MAX.	G NOM.	H MAX.	I	J NOM.	K NOM.
35	3/8	.102	.312	.375	.578	.178	.250	.547	.375	.375	.141
40	1/2	.131	.375	.500	.734	.237	.312	.703	.375	.500	.156
50	5/8	.200	.500	.625	1.031	.297	.406	.938	.468	.625	.200
60	3/4	.200	.625	.719	1.172	.356	.469	1.109	.562	.750	.234
80	1----	.261	.750	.969	1.516	.475	.625	1.500	.750	1.000	.312
100	1-1/4	.323	1.000	1.250	1.906	.594	.781	1.859	.938	1.250	.375
120	1-1/2	.386	1.125	1.438	2.141	.712	.906	2.172	1.125	1.500	.437
140	1-3/4	.448	1.375	1.750	2.750	.831	1.125	2.625	1.312	1.750	.500
160	2----	.516	1.500	2.000	3.219	.950	1.250	3.000	1.500	2.000	.562

REQUIREMENTS:

1. With the exception of dimensions shown in table V, dimensions of link plates, rollers, bushing, and pins for attachment links shall conform to dimensions shown in table 1 for Type 1 Roller Chains.
2. Tolerances for attachment links are the same as tolerances shown for Type 1 Roller Chains.
3. Attachment links shall be grade A, (carbon and alloy steels) unless otherwise specified.
4. Attachment links carried in stock as separate supply items for ANSI chain Nos. 35 through 50 shall be supplied with Class 3, spring clip fastening and shall be so specified.
5. Attachment links carried in stock as separate supply items for ANSI chain Nos. 60 through 160 shall be supplied with Class 2, cotter fastening and shall be so specified.

NOTES:

1. For MILITARY STANDARD ATTACHMENT LINK NUMBERS see TABLE VI
2. Attachment links for ANSI chain No. 35 are rollerless.

PIN AND ROLLER ATTACHMENT LINKS
FOR
TYPE 1 ROLLER CHAINS

X967A

MIL-STD-421B

TABLE VI

PIN AND ROLLER ATTACHMENT LINKS FOR TYPE 1 ROLLER LINKS

MIL-STD ATTACHMENT LINK NUMBER	TYPE	FOR ANSI CHAIN NUMBER	MIL-STD ATTACHMENT LINK NUMBER	TYPE	FOR ANSI CHAIN NUMBER
35-1RC-1PAL 35-1RC-2RAL 35-1RC-3PAL 35-1RC-4RAL 35-1RC-5PAL 35-1RC-6RAL 35-1RC-7PAL 35-1RC-8RAL 35-1RC-9PAL 35-1RC-10PAL	1 PAL 2 RAL 3 PAL 4 RAL 5 PAL 6 RAL 7 PAL 8 RAL 9 PAL 10 PAL	35	100-1RC-1PAL 100-1RC-2RAL 100-1RC-3PAL 100-1RC-4RAL 100-1RC-5PAL 100-1RC-6RAL 100-1RC-7PAL 100-1RC-8RAL 100-1RC-9PAL 100-1RC-10PAL	1 PAL 2 RAL 3 PAL 4 RAL 5 PAL 6 RAL 7 PAL 8 RAL 9 PAL 10 PAL	100
40-1RC-1PAL 40-1RC-2RAL 40-1RC-3PAL 40-1RC-4RAL 40-1RC-5PAL 40-1RC-6RAL 40-1RC-7PAL 40-1RC-8RAL 40-1RC-9PAL 40-1RC-10PAL	1 PAL 2 RAL 3 PAL 4 RAL 5 PAL 6 RAL 7 PAL 8 RAL 9 PAL 10 PAL	40	120-1RC-1PAL 120-1RC-2RAL 120-1RC-3PAL 120-1RC-4RAL 120-1RC-5PAL 120-1RC-6RAL 120-1RC-7PAL 120-1RC-8RAL 120-1RC-9PAL 120-1RC-10PAL	1 PAL 2 RAL 3 PAL 4 RAL 5 PAL 6 RAL 7 PAL 8 RAL 9 PAL 10 PAL	120
50-1RC-1PAL 50-1RC-2RAL 50-1RC-3PAL 50-1RC-4RAL 50-1RC-5PAL 50-1RC-6RAL 50-1RC-7PAL 50-1RC-8RAL 50-1RC-9PAL 50-1RC-10PAL	1 PAL 2 RAL 3 PAL 4 RAL 5 PAL 6 RAL 7 PAL 8 RAL 9 PAL 10 PAL	50	140-1RC-1PAL 140-1RC-2RAL 140-1RC-3PAL 140-1RC-4RAL 140-1RC-5PAL 140-1RC-6RAL 140-1RC-7PAL 140-1RC-8RAL 140-1RC-9PAL 140-1RC-10PAL	1 PAL 2 RAL 3 PAL 4 RAL 5 PAL 6 RAL 7 PAL 8 RAL 9 PAL 10 PAL	140
60-1RC-1PAL 60-1RC-2RAL 60-1RC-3PAL 60-1RC-4RAL 60-1RC-5PAL 60-1RC-6RAL 60-1RC-7PAL 60-1RC-8RAL 60-1RC-9PAL 60-1RC-10PAL	1 PAL 2 RAL 3 PAL 4 RAL 5 PAL 6 RAL 7 PAL 8 RAL 9 PAL 10 PAL	60	160-1RC-1PAL 160-1RC-2RAL 160-1RC-3PAL 160-1RC-4RAL 160-1RC-5PAL 160-1RC-6RAL 160-1RC-7PAL 160-1RC-8RAL 160-1RC-9PAL 160-1RC-10PAL	1 PAL 2 RAL 3 PAL 4 RAL 5 PAL 6 RAL 7 PAL 8 RAL 9 PAL 10 PAL	160
80-1RC-1PAL 80-1RC-2RAL 80-1RC-3PAL 80-1RC-4RAL 80-1RC-5PAL 80-1RC-6RAL 80-1RC-7PAL 80-1RC-8RAL 80-1RC-9PAL 80-1RC-10PAL	1 PAL 2 RAL 3 PAL 4 RAL 5 PAL 6 RAL 7 PAL 8 RAL 9 PAL 10 PAL	80			

X968A