

MIL-STD-651
 NOTICE 1
27 February 1970

MILITARY STANDARD
 VISUAL INSPECTION STANDARDS
 FOR
 20MM AMMUNITION AND
 COMPONENTS

TO ALL HOLDERS OF MIL-STD-651

1. The following pages of MIL-STD-651 have been revised and supersede the pages listed:

<u>New Page</u>	<u>Date</u>	<u>Superseded Page</u>	<u>Date</u>
127	27 February 1970	106	18 October 1962

2. The following pages are to be added:

<u>New Page</u>	<u>Date</u>
8a	27 February 1970
24a	27 February 1970
106-126	27 February 1970

3. The following pen-and-ink changes are to be made:

Page 13, delete item D.

4. RETAIN THIS NOTICE AND INSERT BEFORE THE TABLE OF CONTENTS.


5. Holders of MIL-STD-651 will verify that page changes and additions indicated above have been entered and will destroy the previous notice (notice page only). The latest notice (notice pages) will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Custodians:
 Army - MU
 Air Force - 70

Preparing Activity:
 Army - MU

Review Activities:
 Army - MU
 Air Force - 70

Project No. 1305-0331



(..... Acceptable.....)

Dent (Case)

Characteristic of delinked and relinked ammunition
(Added as additional acceptable "dent case," page 8)



(. Acceptable)

Dent in fuze nose cap

(Added as "Acceptable" dent, fuze nose cap, page 24)

LIST OF DEFECTS


FUZE, POINT DETONATING, M505A3, PARTS FOR

<u>No.</u>		<u>Page</u>
	Holder, Booster	
208.	Foreign matter	108
209.	Burr, sliver, sharp corner or edge	108
210.	Radii, external, max. (except spherical radius).	109
211.	Protective coating damaged or missing.	109
212.	Thickness of web	109
213.	Crack or split	110
214.	Damage	110
215.	Finish	110
216.	Thread undercut missing.	111
	Rotor	
217.	Foreign matter	111
218.	Damage	111
219.	Detent spring seat encroaches upon flash hole.	112
220.	Sharp corner or edge	112
221.	Finish	112
222.	Radius, base of detent spring seat	112
	Spring, Rotor Detent	
223.	Deformity (excluding out of flatness).	112
224.	Burr or sharp edge	112
225.	Foreign matter including corrosion	113
226.	Radii open end	113
227.	Radius opposite open end	113
228.	Finish	113
	Nose Cap	
229.	Burr or sliver, inside edge of crimping lip.	113
230.	Foreign matter	113
	Body	
231.	Finish, interior	113
232.	Foreign matter	114
233.	Internal thread relief missing	114
234.	Break, perimeter of firing pin hole, max.	114
235.	Sharp corner or edge	114


<u>No.</u>		<u>Page</u>
Metal Parts Assembly		
236.	Foreign matter	114
237.	Nose cap crimp missing or less than 360°	115
238.	Crack or split in body or nose cap	115
239.	Exterior protective coating damaged or missing	115
240.	Damage	116
241.	Firing pin missing or not "FREE"	116
242.	Finish exterior.	116
243.	Nose cap crimp below flush with body taper	116

Firing Pin

244.	Damage	117
245.	Foreign matter	117
246.	Finish	117
247.	Burr or sharp edge	117



(.Nonacceptable.)



(.Nonacceptable.)

- | | |
|--|-----------------------------|
| A. Oil or grease, presence
interior or exterior | G. Dirt and stain, exterior |
| B. Corrosion, interior | H. Chips, exterior |
| C. Corrosion, exterior | I. Dirt, exterior |
| D. Corrosion, spherical area | J. Stain, exterior |
| E. Dirt, interior | K. Stain, interior |
| F. Chips, interior | L. Stain, spherical surface |

No. 208. Foreign matter



(.Nonacceptable.)

No. 209. Burr, sliver, sharp corner or edge

No. 210. Radii, external, max. (except spherical radius) (not illustrated)
(Normally conformance of radii to specified dimensional limits will be judged visually. However, components having doubtful conformance to requirements shall be measured.)



A B C D E

(. Nonacceptable.)




F G H

(.Nonacceptable.)

- | | |
|------------------------|--|
| A. Missing | F. Cut, nick, scratch or score |
| B. Bare spot, exterior | G. Basis metal exposed |
| C. Bare spot, interior | H. Scratch, dent (basis metal not exposed) |
| D. Spotty | |
| E. Blistered | |

No. 211. Protective coating damaged or missing




(. .Nonacceptable. .)(Acceptable)

- A. Drill point in web (nonacceptable)*
B. Perforation (nonacceptable)
C. Normal

*A booster holder which complies with the specified dimensional requirements shall be classed defective if there is visual evidence of web rupture or perforation, as observed against an illuminated white background.

No. 212. Thickness of web

27 February 1970



(. . . . Nonacceptable. . . .)

No. 213. Crack or split



A


B

C

D

E

F



G

H

I

J

- A. Dent, crimping lip (nonacceptable)
- B. Dent or nick (nonacceptable)
- C. Dent, body (nonacceptable)
- D. Dent, nick or score on thread*
- E. Dent, crimping lip (acceptable)
- F. Cut or nick, flange (acceptable)
- G. Scratch, score, dent (basis metal not exposed) (acceptable)
- H. Scores, tool marks (nonacceptable)
- I. Scores, tool marks (acceptable)
- J. Thread damaged*

*Damaged threads shall be checked using the specified "Go" thread gage to determine the extent of damage. The component item shall be classed defective if the damaged thread is not accepted by the gage.


No. 214. Damage

No. 215. Finish (not illustrated - refer to drawing)



(Nonacceptable)

No. 216. Thread undercut missing




A B C D

(. Nonacceptable.)

- A. Oil or grease
- B. Chips

- C. Dirt (exterior)
- D. Dirt (interior)

No. 217. Foreign matter



A B C D


(. Nonacceptable.) (Acceptable)

- A. Deformity
- B. Gouge

- C. Score, dent or nick
- D. Dent or nick*

*Raised metal protruding above the spherical surface shall be classed as damaged if the maximum spherical diameter, measured across the raised metal, is exceeded.

No. 218. Damage



(Nonacceptable)

- No. 219. Detent spring seat encroaches upon flash hole
- No. 220. Sharp corner or edge (not illustrated - refer to drawing)
- No. 221. Finish (not illustrated - refer to drawing)
- No. 222. Radius, base of detent spring seat (not illustrated) (Components having doubtful compliance with the requirements shall be gaged.)



A B C D E
(. Nonacceptable.) (Normal)

- | | | |
|-------------------------|---------------|-----------|
| A. Twisted* | C. Crushed | E. Normal |
| B. Gouge, missing metal | D. Incomplete | |

*Shown for information only and is detected by gaging.


No. 223. Deformity (excluding out of flatness)



A B
(Nonacceptable) (Acceptable)

- | | |
|---------|---------|
| A. Burr | B. Burr |
|---------|---------|

No. 224. Burr or sharp edge (For sharp edge - refer to drawing)



A

B

C

(. Nonacceptable.)

A. Grease

B. Dirt

C. Slivers

No. 225. Foreign matter including corrosion (corrosion not illustrated)

No. 226. Radii open end (not illustrated) (Components having doubtful compliance with the requirements shall be gaged)

No. 227. Radius opposite open end (not illustrated) (Components having doubtful compliance with the requirements shall be gaged)

No. 228. Finish (not illustrated - refer to drawing)



(. Nonacceptable.) (Acceptable)

No. 229. Burr or sliver, inside edge of crimping lip



A

B

C

D

E

F

G

H

A. Corrosion (interior) (nonacceptable)

E. Stain (interior) (nonacceptable)

B. Corrosion (exterior) (nonacceptable)

F. Stain (exterior) (acceptable)

C. Dirt (interior) (nonacceptable)


G. Stain (interior) (acceptable)

D. Dirt (exterior) (nonacceptable)

H. Stain (exterior) (nonacceptable)

No. 230. Foreign matter

No. 231. Finish, interior (not illustrated) (Components having doubtful compliance with the requirements shall be gaged)



A B C D E F
(. Nonacceptable.)

- | | |
|-------------------------|-------------------------------|
| A. Dirt or corrosion | D. Chips, crimp groove |
| B. Chips, detent groove | E. Corrosion, firing pin hole |
| C. Chips, crimp groove | F. Oil or grease |


No. 232. Foreign matter

(Particular attention should be given to cleanliness of the rotor detent spring groove. The presence of foreign matter of any nature in the groove shall cause the body to be classed defective. Machining chips are especially objectionable. The use of a bent probe or other suitable inspection aid is suggested to detect the foreign matter in the groove area.)

No. 233. Internal thread relief missing (not illustrated - refer to drawing)

No. 234. Break, perimeter of firing pin hole, max. (not illustrated)(Components having doubtful compliance with the requirements shall be gaged.)


No. 235. Sharp corner or edge (not illustrated) (Components having doubtful compliance with requirements shall be gaged.)



A B C D E F
(. Nonacceptable.)(Acceptable)

- | | |
|------------------|------------------------------------|
| A. Oil or grease | D. Foreign material, crimping area |
| B. Corrosion | E. Dirt, body and threads |
| C. Dirt, threads | F. Dirt |

No. 236. Foreign matter



A B C D E F


(. Nonacceptable.) (Acceptable)

A. Crimp missing

F. Normal


B, C, D, E. Improper crimp

No. 237. Nose cap crimp missing or less than 360°



(. Nonacceptable.)

No. 238. Crack or split in body or nose cap



A B C D E

(. Nonacceptable.)

A. Missing


C. Corrosion, stain

E. Stain

B. Bare spot

D. Corrosion, stain

No. 239. Exterior protective coating damaged or missing




A B C D
(. Nonacceptable.)

- A. Damaged threads
- B. Nick on fuze body
- C. Nick on fuze body
- D. Nose cap dented

No. 240. Damage


(Thread deformity shall be classed as damaged only if the assembly is rejectable by the "Go" thread gage.)



No. 241. Firing pin missing or not "FREE"* (nonacceptable)


*A sample unit having no firing pin, as determined by visual inspection, or having a firing pin which does not move freely within the firing pin guide hole, as determined by shaking and audible sound (or other approved method), shall be classed defective.

No. 242. Finish, exterior (not illustrated - refer to drawing)



(. Nonacceptable.)

No. 243. Nose cap crimp below flush with body taper




A B C D

(. Nonacceptable.)

- | | |
|------------------------|-----------------------------|
| A. Flange missing | C. Firing pin point missing |
| B. Gouge or distortion | D. Firing pin point missing |

No. 244. Damage




(. Nonacceptable.)

- | | |
|------------------|-------------------|
| A. Oil or grease | C. Dirt |
| B. Dirt | D. Foreign matter |

No. 245. Foreign matter

No. 246. Finish (not illustrated - refer to drawing)



(. Nonacceptable.)

No. 247. Burr or sharp edge*


*Components having doubtful compliance with requirements shall be gaged.

LIST OF DEFECTS


FUZE, POINT DETONATING, M505A3


<u>No.</u>		<u>Page</u>
	Rotor and Detonator Assembly	
248.	Exposed explosive.	119
249.	Detonator stake missing.	119
250.	Spherical surface distorted.	119-120
251.	Detonator missing.	120
252.	Identification color incorrectly located or missing.	120
253.	Foreign matter.	121
	Rotor, Detonator and Rotor Detent Spring Assembly	
254.	Cracked, split or broken rotor detent spring.	121
	Booster Assembly	
255.	Exposed explosive.	122
256.	Charge missing.	122
257.	Low charge.	122
258.	Crack or split in booster holder.	123
259.	Thread damaged.	123
260.	Foreign matter.	123
	Assembly of Rotor-Detonator and Rotor Detent Spring Assembly in the Metal Parts Assembly	
261.	Rotor detent spring missing.	124
	Fuze Assembly	
262.	Thread damaged.	124
263.	Protective coating damaged.	124
264.	Nose cap damaged.	125
265.	Crack or split in body.	125
266.	Foreign matter.	126
267.	Sealant missing or faulty	126

No. 248. Exposed explosive (not illustrated)
(Explosive, exposed through a split, crack, rupture, or perforation in the disc or cup, or loose explosive (flake or cake) or any other visible surface of the assembly, shall be cause for classifying the assembly defective.)



No. 249. Detonator stake missing






. M N
(. . . .Acceptable. . . .)

- | | |
|-----------------------------|------------------|
| A. Symmetrical deformity | H. Scored |
| B. Symmetrical deformity | I. Chucking flat |
| C. Flat spot | J. Chucking flat |
| D. Burr, detent spring seat | K. Nick |
| E. Burr flash hole | L. Dent |
| F. Dent | M. Dent |
| G. Fold | N. Scratch |

No. 250. Spherical surface distorted




(Nonacceptable)

No. 251. Detonator missing

No. 252. Identification color incorrectly located or missing (not illustrated) (Green end of detonator must be adjacent to flash hole.)




A B C D E
(. Nonacceptable.)



F G H
(. . . . Nonacceptable. . . .) (Acceptable)

- | | |
|-----------------------------------|--|
| A. Oil, dirt or grease | E. Metal obstruction in flash hole |
| B. Foreign material, flash hole | F. Sealing compound in flash hole area |
| C. Dirt, flash hole | G. Dirt or grease, symmetrical surface |
| D. Dirt, rotor detent spring seat | H. Sealant, detonator crimp area |



No. 253. Foreign matter



A B
(. . . . Nonacceptable. . . .)

- | | |
|-----------|------------|
| A. Broken | B. Cracked |
|-----------|------------|

No. 254. Cracked, split or broken rotor detent spring



- | | |
|--------------------------------------|-----------------------------------|
| A. Closing disc crimped off center | D. Partial closing disc |
| B. Closing disc missing | E. Partially crimped closing disc |
| C. Exposed explosive on closing disc | F. Closing disc punctured |
| G. Closing disc damaged | |

No. 255. Exposed explosive


No. 256. Charge missing (not illustrated) (A booster holder found with the closing disc resting on the bottom of the cavity or any visual evidence of charge missing shall be cause for classifying the assembly defective.)



(. . . . Nonacceptable. . . .)

- | | |
|-----------------------------------|-------------------------------------|
| A. Concave disc resting on charge | B. Loose disc resting on low charge |
|-----------------------------------|-------------------------------------|

No. 257. Low charge



(.Nonacceptable.)

No. 258. Crack or split in booster holder

No. 259. Thread damaged (not illustrated) (The booster assembly shall be classed defective if the thread is crushed or otherwise distorted to a degree that prevents acceptance by the "Go" thread gage.)




A

B

C

(.Nonacceptable.)



D


E

(.Acceptable.)

A. Corrosion
B. Dirt

C. Oil and dirt
D, E. Stain, discoloration


No. 260. Foreign matter



A

(. Nonacceptable.)

A. Spring missing



B




(. Acceptable.)

B. Spring in position

No. 261. Rotor detent spring missing

(Visual inspection for "rotor detent spring missing" shall be performed on the rotor-detonator and rotor detent spring assembly prior to and after its insertion into the metal parts assembly.)


No. 262. Thread damaged (not illustrated) (The fuze assembly shall be classed defective if the thread is crushed or otherwise distorted to a degree that prevents acceptance by the "Go" thread gage.)



(. Nonacceptable.)

No. 263. Protective coating damaged


(The fuze assembly shall be classed defective if the plating film on the nose cap or body ogive is scored or otherwise broken to visibly expose basis metal.)



(.Nonacceptable.)


No. 264. Nose cap damaged

(The fuze assembly shall be classed defective if the nose cap is cracked, split, perforated, dented or otherwise deformed.)



(.Nonacceptable.)

No. 265. Crack or split in body




(. Nonacceptable.)

A, B, C, D. Stain

E. Grease

F, G, H. Dirty

No. 266. Foreign matter



(. Nonacceptable.)

A, B. Sealant on fuze body

C, D. Sealant not full 360° on base of fuze

No. 267. Sealant missing or faulty

(This characteristic applies only if base sealant is required. The assembly shall be classed defective, if the sealant does not seal crimp 360° and cover damaged plating on base of fuze, or if the sealant is present on fuze body.)

Notice. Copies of specifications, standards drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.

Custodians:

Army - MU
Air Force - 70

Preparing Activity:

Army - MU

Review Activities:

Army - MU
Air Force - 70

Project No. 1305-0331