

MIL-STD-810B
 NOTICE 4
 21 September 1970

MILITARY STANDARD
 ENVIRONMENTAL TEST METHODS

TO ALL HOLDERS OF MIL-STD-810B

1. The following pages of MIL-STD-810B have been revised and supersede the pages listed:

| <u>New page</u> | <u>Date</u> | <u>Superseded page</u> | <u>Date</u> |
|-----------------|-------------|------------------------|--------------|
| iii | 21 Sep 70 | iii | 15 June 1967 |
| iv | 21 Sep 70 | iv | 15 June 1967 |
| v thru vii | 21 Sep 70 | v | 15 June 1967 |

2. Make the following pen and ink changes:

a. Page ii, paragraph 3, and DD Form 1426: Change address to:

"Commander, Aeronautical Systems Division
 Attn: ASNPS-20
 Wright-Patterson AFB, Ohio 45433".

b. Page 8: Add the following new section and paragraph after 5.1:

"6. NOTES

6.1 International interest. Certain provisions of this standard are the subject of international standardization agreements (STANAG 3518 AE). When amendment, revision, or cancellation of this standard is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels, including departmental standardization offices, if required."

c. Page 8: Below reviewer activities listing add "International interest (see 6.1)".

d. Page 502-1, paragraph 4(b): Delete and substitute:

"(b) Storage temperature and duration (step 2)."

e. Page 504-3, paragraph 3.2, Procedure I, Step 7, line 4: Delete "step 1" and substitute "step 7".

FSC MISC

MIL-STB-810B
NOTICE 4 (USAF)

- f. Page 504-7, Figure 504-1, NOTE 2: Delete "PEQUIREMENTS" and substitute "REQUIREMENTS".
 - g. Page 506-1, paragraph 3.1, Procedure I, sixth sentence: Delete and substitute "The wind source shall be maintained at this velocity for 15 minutes afterwhich the wind source shall be turned off."
 - h. Page 507-5, step 7, line 1: Delete "4 through 6" and substitute "2, 4, 5, and 6".
 - i. Page 508-3, paragraph 3.7 Criteria for passing test: Delete "3.7" and substitute "3.1.7".
 - j. Page 510-1, paragraph 2.1, last sentence: Delete "Fenton Foundry Supply Company, Dayton, Ohio and".
3. The following is a cumulative list of earlier changes:

a. Superseded methods

| New method | Date | Superseded method | Date |
|------------|-------------------|-------------------|--------------|
| 513.1 | 20 October 1969 | 513 | 15 June 1967 |
| 514.1 | 20 October 1969 | 514 | 15 June 1967 |
| 515.1 | 20 October 1969 | 515 | 15 June 1967 |
| 516.1 | 20 October 1969 | 516 | 15 June 1967 |
| 517.1 | 20 October 1969 | 517 | 15 June 1967 |
| 519.1 | 18 September 1970 | T519 | 29 Sept 1969 |

b. New method

| Method | Date |
|----------------------------------|--------------------|
| T519 Gunfire Vibration, Aircraft | 29 September 1969. |

4. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

5. Holders of MIL-STD-810B will verify that pen and ink changes and page changes have been entered and will destroy the previous notices (notice pages only). This notice will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

MIL-STD-810B
NOTICE 4 (USAF)

Custodians:

Army - EL

Navy - AS

Air Force - 11

Preparing activity:

Air Force- 11

Review activities:

Army - EL, MI, MU, ME, AV, GL

Navy - AS, SH, OS, YD

Air Force - 11

CONTENTS

| Section | | Page |
|---------|------------------------------------------------------|------|
| 1. | Scope | 1 |
| 1.1 | Purpose | 1 |
| 1.2 | Application of test methods | 1 |
| 1.3 | Numbering system | 1 |
| 1.4 | Revision of standard | 1 |
| 1.5 | Revision of test methods | 1 |
| 1.6 | Method of reference | 1 |
| 2. | Referenced documents | 1 |
| 3. | General requirements | 2 |
| 3.1 | Test conditions | 2 |
| 3.1.1 | Measurements of test conditions | 3 |
| 3.1.2 | Tolerance of test conditions | 3 |
| 3.1.3 | Accuracy of test apparatus | 3 |
| 3.1.4 | Stabilization of test temperature | 3 |
| 3.1.5 | Reference conditions | 4 |
| 3.2 | Performance of test | 4 |
| 3.2.1 | Pretest performance record | 4 |
| 3.2.2 | Installation of test item in test facility | 4 |
| 3.2.3 | Performance check during test | 4 |
| 3.2.4 | Visual inspection and failure criteria | 4 |
| 3.3 | Test facilities apparatus | 4 |
| 3.3.1 | Test chamber | 4 |
| 3.3.1.1 | Volume of test chamber | 4 |
| 3.3.1.2 | Heat source | 4 |
| 3.3.1.3 | Location of temperature sensors | 4 |
| 3.4 | Test data | 5 |
| 4. | Test sequence | 5 |
| 5. | Test methods | 8 |
| 6. | Notes | 8 |
| 6.1 | International interest | 8 |

TEST METHODS

| Method No. | | |
|------------|----------------------------------|--------------|
| 500 | Altitude | 500-1-500-2 |
| 501 | High temperature | 501-1-501-2 |
| 502 | Low temperature | 502-1-502-1 |
| 503 | Temperature shock | 503-1-503-1 |
| 504 | Temperature - altitude | 504-1-504-10 |
| 505 | Sunshine | 505-1-505-2 |
| 506 | Rain | 506-1-506-2 |

MIL-STD-810B
15 June 1967

CONTENTS

TEST METHODS (Continued)

| Method No. | | Page |
|------------|----------------------------------------|------------------|
| 507 | Humidity | 507-1-507-5 |
| 508 | Fungus | 508-1-508-3 |
| 509 | Salt fog | 509-1-509-4 |
| 510 | Dust test | 510-1-510-2 |
| 511 | Explosive atmosphere | 511-1-511-5 |
| 512 | Leakage (immersion) | 512-1-512-2 |
| 513.1 | Acceleration | 513.1-1-513.1-6 |
| 514.1 | Vibration | 514.1-1-514.1-30 |
| 515.1 | Acoustical noise | 515.1-1-515.1-6 |
| 516.1 | Shock. | 516.1-1-516.1-10 |
| 517.1 | Space simulation | 517.1-1-517.1-11 |
| 518 | Temperature-humidity-altitude. | 518-1-518-3 |
| 519.1 | Gunfire vibration, aircraft. | 519.1-519.1-17 |

TABLES

| | | |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------|----------|
| Table I | Recommended test sequence | 6-7 |
| Table 504-I | Temperature range for various equipment classes . . | 504-5 |
| Table 504-II | Test chamber conditions for temperature-altitude tests. | 504-6 |
| Table 513.1-I | G levels for structural test (Procedure I) | 513.1-3 |
| Table 513.1-II | G levels for operational test (Procedure II) . . . | 513.1-4 |
| Table 514.1-I | Test procedure and time schedule chart for equipment installed in airplanes and helicopters - equipment category (a) | 514.1-14 |
| Table 514.1-II | Test procedure and time schedule chart for equipment installed in airplanes - equipment category (b) | 514.1-16 |
| Table 514.1-III | Test procedure and time schedule chart for equipment installed in helicopters - equipment category (c) | 514.1-18 |
| Table 514.1-IV | Test procedure and time schedule chart for equipment installed in air launched missiles - equipment category (d) | 514.1-20 |
| Table 514.1-V | Test procedure and time schedule chart for equipment installed in ground launched missiles - equipment category (e) | 514.1-22 |
| Table 514.1-VI | Test procedure and time schedule chart for equipment installed in ground vehicles - equipment category (f) | 514.1-24 |

21 September 1970

CONTENTS

TABLES (Continued)

| | Page |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------|
| Table 514.1-VII | Test procedure and time schedule chart for equipment transported by common carrier, land or air - equipment category (g) |
| | 514.1-26 |
| Table 514.1-IX | Linear cycling rates |
| | 514.1-28 |
| Table 515.1-I | Acoustical noise test category |
| | 515.1-2 |
| Table 516.1-I | Transit drop test (Procedure II) |
| | 516.1-3 |
| Table 517.1-I | Pressure levels for effects simulation |
| | 517.1-2 |
| Table 517.1-II | Average radiation characteristics of planets. |
| | 517.1-3 |
| Table 517.1-III | Solar simulator classification |
| | 517.1-3 |
| Table 517.1-IV | Solar electromagnetic energy distribution. |
| | 517.1-4 |
| Table 517.1-V | Solar simulator - instrumentation performance requirements |
| | 517.1-6 |
| Table 517.1-VI | Significant parameters for solar simulation |
| | 517.1-7 |
| Table 519.1-I | Ballistic table. |
| | 519.1-15 |
| Table 519.1-II | Random vibration test time |
| | 519.1-17 |

FIGURES

| | | |
|--------------|---------------------------------------------------------------------------------------------------------|--------|
| Figure 504-1 | Operational requirements for class 1, 1A, and 1B aerospace equipment. Temperature vs. altitude. | 504-7 |
| Figure 504-2 | Operational requirements for class 2 aerospace equipment. Temperature vs. altitude. | 504-8 |
| Figure 504-3 | Operational requirements for class 3 aerospace equipment. Temperature vs. altitude. | 504-9 |
| Figure 504-4 | Operational requirements for class 4 aerospace equipment. Temperature vs. altitude. | 504-10 |
| Figure 505-1 | Simulated solar radiation cycle - Procedure II | 505-3 |
| Figure 507-1 | Humidity cycle for procedure I | 507-6 |
| Figure 507-2 | Humidity cycle - Procedures II and III | 507-7 |
| Figure 507-3 | Humidity cycle - Procedure IV | 507-8 |
| Figure 509-1 | Variations of specific gravity of salt (NaCl) solution with temperature | 509-5 |
| Figure 509-2 | Salt solution filter. | 509-5 |

MIL-STD-810B
15 June 1967

CONTENTS

FIGURES (Continued)

| | Page |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Figure 509-3 | Location of salt solution filter 509-6 |
| Figure 511-1 | Weight of air (lbs). 511-6 |
| Figure 511-2 | Temperature of fuel (°F) 511-7 |
| Figure 511-3 | Correction of factor 511-8 |
| Figure 513.1-1 | Direction of vehicle acceleration 513.1-6 |
| Figure 514.1-1 | Vibration test curves for equipment installed in airplanes and helicopters - equipment category (a) 514.1-15 |
| Figure 514.1-2 | Vibration test curves for equipment installed in airplanes, excluding helicopters - equipment category (b) 514.1-17 |
| Figure 514.1-3 | Vibration test curves for equipment installed in helicopters - equipment category (c). 514.1-19 |
| Figure 514.1-4 | Vibration test curves for equipment installed in air launched missiles - equipment category (d) 514.1-21 |
| Figure 514.1-5 | Vibration test curves for equipment installed in ground launched missiles - equipment category (e) 514.1-23 |
| Figure 514.1-6 | Vibration test curves for equipment installed in ground vehicles - equipment category (f) 514.1-25 |
| Figure 514.1-7 | Vibration test curves for equipment transported by common carrier, land or air - equipment category (g) 514.1-27 |
| Figure 514.1-9 | Cut-off frequency vs. weight, equipment shipped by aircraft 514.1-29 |
| Figure 514.1-10 | Logarithmic sweep 514.1-30 |
| Figure 515.1-1 | Octave band spectrum for acoustical noise test 515.1-5 |
| Figure 515.1-2 | Octave band spectrum for acoustical noise test 515.1-6 |
| Figure 516.1-1 | Terminal-peak sawtooth shock pulse configuration and its tolerance limits 516.1-8 |
| Figure 516.1-2 | Half sine shock pulse configuration and its tolerance limits 516.1-9 |
| Figure 516.1-3 | System frequency response 516.1-10 |
| Figure 518-1 | Temperature-humidity-altitude cycle (Procedure I). 518-3 |
| Figure 519.1-1 | G_0/n_0r_0 vs. D 519.1-7 |

21 September 1970

vi

CONTENTS

FIGURES (Continued)

| | Page |
|----------------|----------------------------------------------------------------------------|
| Figure 519.1-2 | Reduction factor for mass loading 519.1-8 |
| Figure 519.1-3 | Determination of the D vector 519.1-9 |
| Figure 519.1-4 | Origin of the D vector for multigun, staggered array 519.1-10 |
| Figure 519.1-5 | Random vibration test curve 519.1-11 |
| Figure 519.1-6 | Peripherally mounted item 519.1-12 |
| Figure 519.1-7 | Swept random vibration test curve 519.1-13 |
| Figure 519.1-8 | Reduction of G_{\max} vs. distance parameter h/c 519.1-14 |

☆ U. S. GOVERNMENT PRINTING OFFICE: 1972 -714-163/5244