

MIL-STD-809B
1 December 1986
SUPERSEDING
MIL-STD-809A
3 April 1978

MILITARY STANDARD
ADAPTER, AIRCRAFT, JACKING POINT,
DESIGN AND INSTALLATION OF



AMSC N/A

FSC 1730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MIL-STD-809B

DEPARTMENT OF DEFENSE

Washington, DC 20350

Adapter, Aircraft, Jacking Point, Design and Installation of

1. This Military Standard is approved for use by all Departments and Agencies of the Department of Defense.
2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Air Engineering Center, Systems Engineering and Standardization Department, (Code 93), Lakehurst, NJ 08733-5100, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

MIL-STD-809B

CONTENTS

		<u>Page</u>
Paragraph	1	SCOPE 1
	1.1	Purpose 1
	1.2	Classification 1
	1.2.1	Types 1
	1.2.2	Classes 1
	2	REFERENCED DOCUMENTS 2
	2.1	Government Documents 2
	2.1.1	Specifications, standards & handbooks 2
	2.1.2	Other Government Documents & Publications 3
	2.3	Order of precedence 3
	2.4	Source of documents 3
	2.4.1	Military standards, specifications and associated documents 3
	3	DEFINITIONS 3
	3.1	Adapter 4
	3.2	Socket 4
	3.3	Turn-Around Time 4
	4	GENERAL REQUIREMENTS 5
	4.1	Materials 5
	4.1.1	Metals 5
	4.1.1.1	Dissimilar metals 5
	4.1.2	Protective finishes 5
	4.2	Interchangeability 5
	4.2.1	Drawings 5
	4.2.2	Jacking diagram 5
	4.3	Markings 6
	4.3.1	Location of adapters 6
	4.3.2	Identification of product 6
	4.4	Workmanship 6
	5	DETAILED REQUIREMENTS 7
	5.1	Design and installation 7
	5.1.1	Dimensions 7
	5.2	Arrangement 7
	5.2.1	Jacks to be used 7
	5.2.1.2	Government-Furnished Property 7
	5.2.1.3	Government-Loaned Property 7
	5.2.2	Operations to be performed 7
	5.2.3	Accessibility 8

MIL-STD-809B

CONTENTS (Cont'd)

		<u>Page</u>
Paragraph	5.2.4	Orientation 8
	5.2.5	Axle jack pads 8
	5.2.5.1	Steerable alighting gear 8
	5.2.5.2	Flat tires 8
	5.2.5.2.1	Single or tandem wheels 8
	5.2.5.2.2	Dual wheels 8
	5.3	Angle of installation 8
	5.3.1	Axle adapters 8
	5.3.2	Angular tolerances 9
	5.4	Class 1, Removable adapters 9
	5.4.1	Stowage provisions 9
	5.5	Class 2, Integral adapters 9
	5.5.1	Axle adapters 9
	5.6	Primary flight structure adapters 9
	5.7	Strength 9
	5.8	Screw threads 10
	5.9	Model Designations 10
	6	NOTES 11
	6.1	Intended use 11
	6.2	Data requirements 11
	6.3	Government-Furnished and Government-Loaned Property 11
	6.3.1	Government-furnished property 11
	6.3.2	Government-loaned property 11
	6.4	Subject Term (Key Word) Listing 11
	6.5	International Standardization Agreements 12
	6.6	Changes from previous issue 12

MIL-STD-809B

1. SCOPE

1.1 Purpose. This standard provides requirements for design and installation of aircraft jacking point adapters, as identified by ASCC AIR STD 25/7 Aircraft Jacking Pads, to permit use of standard jacking equipment.

1.2 Classification. Each adapter shall be classified by type and class.

1.2.1 Types. The design of the adapter shall be determined as to type by the loads imposed as follows:

Type I - Primary flight structure adapters for reactions of less than 10,000 pounds (4536 kg).

Type II - Primary flight structure adapters for reactions of 10,000 (4536 kg) to 112,000 pounds (50,803 kg).

Type III - Axle adapters for reactions of less than 10,000 pounds (4536 kg).

Type IV - Axle adapters for reactions of 10,000 (4536 kg) to 150,000 pounds (68,000 kg).

Type V - Axle or primary flight structure adapters for reactions of 150,000 (68,000 kg) to 300,000 pounds (136,080 kg).

1.2.2 Classes. All types of adapters shall be designed in accordance with one of the following classes;

Class 1 - Removable when the aircraft is flown.

Class 2 - Integral or permanently attached.

MIL-STD-809B

2. REFERENCED DOCUMENTS

2.1 Government Documents.

2.1.1 Specifications, standards and handbooks. Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this standard to the extent specified herein

SPECIFICATIONS

MILITARY

MIL-F-7179	Finishes, Coatings and Sealants for protection of Aerospace Weapons System
MIL-W-7327	Weighing Kit, Electronic, Aircraft and Missile A/S 37M-1 and A/S 37M-2
MIL-S-7742	Screw Threads, Standard, Optimum Selected Series, General Specifications for
MIL-A-8863	Airplane Strength and Rigidity Ground Loads for Navy Procured Airplanes
MIL-S-26149	Jack, Hydraulic, Hand Weapon and Support Systems, General Specification for
MIL-P-26191	Pumping Unit, Hydraulic AF/M27M-1 and AF/M27M-2

STANDARDS

MILITARY

DOD-STD-100	Engineering Drawing Practices
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-875	Type Designation System for Aeronautical and Support Equipment
MIL-STD-889	Dissimilar Metals
MIL-STD-1568	Materials and Processes for Corrosion Prevention and Control in Aerospace Weapon Systems
MIL-STD-1587	Materials and Process Requirements for Air Force Weapon Systems

MIL-STD-809B

MS26566 Jack, Aircraft Landing Gear
MS33559 Adapter, Aircraft, Jacking Points, Design and Installation of
MSS33589 Jack, Hydraulic, Tripod, Aircraft, Airframe

2.1.2 Other Government Documents and Publications. The following other Government documents and publications form a part of this standard to the extent specified herein.

PUBLICATION

AIR STANDARDIZATION COORDINATING COMMITTEE

AIR STD 25/7 Aircraft Jacking Pads

NAVAL AIR SYSTEMS COMMAND

NAVAIR 19-70-46 Index and Application Tables for Aircraft Jacks

(Copies of specifications, standards and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.3 Order of precedence. In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.

2.4 Source of Documents.

2.4.1 Military standards, specifications, and associated documents

Copies of listed military standards, specifications, and associated documents listed in the Department of Defense Index of Specifications and Standards, are available from the Department of Defense Single Stock Point, Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120. Copies of industry association documents should be obtained from the sponsoring industry association. Copies of all other listed documents should be obtained from the contracting activity or as directed by the contracting officer.

MIL-STD-809B

3. DEFINITIONS

3.1 Adapter. The Word Adapter as used herein is the piece/part that is the interface between the aircraft and the jack(s). The adapter shall be designed for a satisfactory fit and positive accommodation to bring or settle the aircraft into a proper position.

3.2 Socket. The word socket as used herein is the piece/part that is the interface between the adapter and the aircraft jack. The socket shall mate with the adapter to transmit the load to the jack,

3.3 Turn-Around Time. As used in this standard, Turn-Around Time (TAT) is that time required to complete an action which initially requires the use of an adapter as designed and installed in accordance with this standard and MS33559. The action will normally be a maintenance task such as a repair or replacement. The procuring activity shall define the Turn-Around Time(s) to be determined.

MIL-STD-809B

4. GENERAL REQUIREMENTS

4.1 Materials. Materials shall be of the best quality, of the lightest practicable weight suitable for the purpose intended and shall be approved by the procuring activity. Materials shall be selected in accordance with MIL-STD-1587 and in conjunction with MIL-STD-1568

4.1.1 Metals. The adapter shall be fabricated of metal only. Metals shall be suitably treated to resist corrosion in fuels, salt fog, or other atmospheric conditions to which the adapter will be subjected when in storage or during normal service use.

4.1.1.1 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in and shall be in accordance with MIL-STD-889.

4.1.2 Protective finishes. Adapters shall be finished in accordance with MIL-F-7179.

4.2 Interchangeability. All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other in respect to installation and performance. Changes in manufacturer's part numbers shall be governed by the drawing number requirements of DOD-STD-100.

4.2.1 Drawings. Contractor's drawings or each new adapter design shall be submitted to the procuring activity for examination to determine compliance with requirements specified herein and in MS33559. Drawing shall be provided in accordance with DOD-STD-100 and to the level established by the procuring activity.

4.2.2 Jacking diagram The contractor shall submit a jacking diagram containing the following information to the procuring activity for approval:

a. A three-view drawing showing the location of all jack points on all three views.

b. The load on each adapter under all probable load conditions, including fully and partially loaded, weight empty and weight empty with engines removed.

c. The height of each adapter in the static position, and with the struts fully compressed, completely deflated, and tire flat.

d. The clearance space to be provided for jacks at aircraft main jacking points will be represented by a right pyramid having an equilateral triangular base, limiting edges at 25° to the vertical and a truncated top such that a circle of 3.000 Inch (76.20mm) minimum diameter will fall within the truncated top.

MIL-STD-809B

4.3 Markings.

4.3.1 Location of adapters. Adapter locations on the aircraft shall be identified by stenciling letters 1-inch (25.4 mm) high reading (Jack Here) for Class 2 adapters and (Attach Jack Pad Here) for Class 1 adapters.

4.3.2 Identification of product. Class 1 adapters shall be durably and legibly marked in accordance with MIL-STD-130. The following information shall be contained:

Manufacturer's part number
Aircraft model number
Location on aircraft

When the size of the adapter precludes complete compliance with the foregoing requirement, the adapter shall carry the manufacturer's part number as a minimum requirement.

4.4 Workmanship. Workmanship shall be in accordance with high-grade aircraft-quality manufacturing practice covering this type of equipment, and of a quality control necessary to produce adapters free from all defects that affect proper functioning in service. The adapters shall be installed in a thoroughly workmanlike manner and the completed installation shall present a clean appearance suitable to accept the jack(s).

MIL-STD-809B

5. DETAILED REQUIREMENTS

5.1 Design and installation.

5.1.1 Dimensions. The dimensions and design of the adapters shall be in accordance with MS33559.

5.2 Arrangement. Adapters shall be arranged to preclude the possibility of the aircraft upsetting during any jacking operation, under all probable load conditions including fully and partially loaded, weight empty, and weight empty with engines removed. On aircraft having a total of more than three wing and fuselage jacking points manifold jacking shall be considered for the complete aircraft and the adapters shall be so arranged with respect to the aircraft center of gravity as to facilitate use of standard manifolding equipment in accordance with MIL-P-26191.

5.2.1 Jacks to be used. The jacks to be used in the design of jacking point adapter installations shall be in accordance with MS26566 and MS33589, and MIL-J-26149 except that the jacks to be used for carrier-based aircraft shall be as specified by the procuring activity per Technical Manual 19-70-46.

5.2.1.2 Government-Furnished Property. Standard suitable aircraft jacks from government inventory may be furnished by the procuring activity to verify the use of these jacks for the operational tests of 5.2.2 or any other test(s) which are pertinent to the use of jacks such as interchangeability or turn-around time.

5.2.1.3 Government-Loaned Property. The procuring activity may supply aircraft jacks for specific individual tests as required. These tests shall be scheduled and accomplished in accordance with the Test and Evaluation Master Plan (TEMP) and turn-around-time (TAT).

5.2.2 Operations to be performed. A sufficient number of jacking point adapters in accordance with MS33559 shall be provided on the aircraft to permit the aircraft to be jacked up for any of the following purposes:

a. Removal, replacement and servicing of alighting gear, wholly or in part including replacement of wheel, float or ski alighting gear with another type for convertible aircraft.

b. Checking the operation of retractable gear.

c. Checking the operation of steerable landing gear.

d. Servicing or replacing tires and wheels by jacking each alighting gear separately without the necessity of removing the struts or any part of the alighting gear structure.

e. Adjustment, maintenance and replacement of brakes.

f. As a precautionary measure to prevent tipping of the aircraft during normal maintenance operations, including replacement of engines, propellers or other equipment or structural components.

MIL-STD-809B

- g. Weighing the aircraft for determining location of center of gravity
- h. Positioning the aircraft for boresighting
- i. Placing the aircraft in jig position.
- j. Turn-around time (TAT) for all pertinent repairs or replacements.

5.2.3 Accessibility. Adapters shall be designed for ease of installation on the aircraft and shall be readily accessible. When adapters are recessed or otherwise enclosed in such manner that the jacking point is accessible only through a restricted opening, the access opening shall be large enough to permit use of standard weighing cells in accordance with MIL-W-7327.

5.2.4 Orientation. Primary flight structure adapters shall be so located that there will be no interference between adjacent jacks or between a jack and any component of the aircraft, including movable components, such as control surfaces, doors, etc; in any position in their normal operation range, regardless of orientation of the jack.

5.2.5 Axle jack pads. Axle jacking point adapters shall be so located that the shock absorber strut will remain compressed to the normal static position throughout the jacking operation except for quadricycle gears

5.2.5.1 Steerable alighting gear. Where adapters are provided on steerable alighting gear, the alighting gear shall be equipped with a means of preventing rotation around the vertical axis.

5.2.5.2 Flat tires. It shall be possible to jack each wheel, or set of wheels, with a single jack, even when a tire is flat.

5.2.5.2.1 Single or tandem wheels. The axle jacking point adapters, when located so that a flat tire will prevent the wheel from being jacked, may be extendible only if prior specific approval is obtained from the procuring activity. Sufficient clearance shall be provided between and around components to permit the use of one of the jacks specified in 5.2.1.

5.2.5.2.2 Dual wheels. For alighting gear with dual wheels, where design features prevent jacking of the wheels with a single jack when the tires are flat, the use of a jacking arrangement requiring the use of a special jack or adapter may be considered only if prior specific approval of the arrangement is obtained from the procuring activity.

5.3 Angle of installation. Eccentricities of loading shall be avoided in the design, position, or location of the adapters.

5.3.1 Axle adapters. Axle adapters shall be so installed that the axis of the adapter is vertical ± 1 degree when the aircraft is in its normal static position.

MIL-STD-8098

5.3.2 Angular tolerances. The axis of the primary flight structure adapters shall be vertical within ± 5 degrees, regardless of whether the longitudinal centerline of the aircraft is normally horizontal, vertical, or inclined, at any intermediate angular jacking attitude. Except for aircraft having a tail wheel type of landing gear, the axis of primary flight structure adapters shall be vertical ± 1 degree when the aircraft is midway between the normal static position and the position at which the longitudinal axis of the aircraft is horizontal.

5.4 Class 1, Removable adapters. Class 1 adapters shall be so designed that special tools will not be required for assembly, disassembly, or installation. Preferably, removable adapters shall be of single-piece or permanently assembled construction. The adapters shall be so installed that they will not work loose in service. They shall be built to withstand strains, jars, vibrations, and other conditions incident to storage, installation and service.

5.4.1 Stowage provisions. Provision shall be made to stow all Class 1 adapters within the aircraft. The adapters shall be fastened securely when stowed. If the adapters are stowed aboard the aircraft, their weight shall be included with the special equipment of the aircraft.

5.5 Class 2, Integral adapters. Class 2 adapter shall be constructed in a manner to complement the basic load-carrying structure of the aircraft. Wherever possible, Integral adapters shall form part of the primary flight structure of the aircraft.

5.5.1 Axle adapter. Axle adapters installed on main and nose alighting gear shall be integral with or permanently attached to the alighting gear, unless a deviation is specifically granted by the procuring activity.

5.6 Primary flight structure adapters. Where primary flight structure adapters protrude beyond the aircraft skin on aircraft other than rotary-wing, liaison, or low-speed trainer aircraft, they shall be Class 1. Where primary flight structure adapters do not protrude beyond the aircraft skin or are installed on rotary-wing, liaison, or low-speed trainers, they may be Class 1 or Class 2. Whenever practicable, all Class 1 adapters of one type shall be interchangeable throughout for each model of aircraft. When interchangeability is not practicable, adapters shall be marked for identification of the Intended location.

5.7 Strength. The strength of fastenings, adapters, and their attaching structure shall be in accordance with MIL-A--8863. All probable load conditions shall be considered, including fully and partially loaded, weight empty, weight empty with engines removed, or specific load conditions agreed upon between the contractor and the procuring activity. The vertical load shall act singly and in combination with the longitudinal load, the lateral load, and both longitudinal and lateral loads. At the jacking points the horizontal loads shall be reacted by Inertia forces which in turn will not essentially change the vertical loads at these points. The following table defines the jacking loads.

MIL-STD-809B

COMPONENT	LANDING GEAR 3 POINT ATTITUDE	OTHER JACK POINTS LEVEL ATTITUDE
Vertical	1.35 F	2.0 F
Longitudinal	0.4 F	0.5 F
Lateral	0.4 F	0.5 F

Where F is the static vertical reaction at the jacking point

5.8 Screw threads. Unless otherwise specified, threads on a Class 1 adapter, attached by a threaded end integral with itself, shall conform to MIL-S-7742. All threaded parts of the adapter shall be positively locked or safetied.

5.9 Model Designations. All aircraft, jack(s) used with the adapters as defined herein shall have their model designation established in accordance with the procedure of MIL-STD-875. Commercial jacks when used with military aircraft shall also be required to comply with MIL-STD-785 as to model designation. For currently existing aircraft jacks their present model designation may be revised or remain but all new equipment shall comply with MIL-STD-875.

MIL-STD-809B

6. NOTES

6.1 Intended use. The adapter defined herein shall be the key interface between the aircraft and the aircraft jack(s).

6.2 Data requirements. When this standard is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of the DoD FAR clause on data requirements (currently DoD FAR Supplement 52 227-7031) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this standard is cited in the following paragraphs.

Paragraph No.	Data Requirement Title	Applicable DID No.	Option
4.2.1	Drawings	DI-E-7431	AD-1350
4.2.2	Jacking Diagram	-----	---
5.2.1.2	GFE DD Form 610	DI-P-6161,	---
5.2.1.3	611 & 611-1	62, 63	---

(Data item descriptions related to this standard, and identified in section 6 will be approved and listed as such in DoD 5000. 19-L., Vol. II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.3 Government-Furnished and Government-Loaned Property.

6.3.1 Government-furnished property. The contracting officer should arrange to furnish the property listed in 5.2.1.2 and 5.2.2.

6.3.2 Government-loaned property. The contracting officer should arrange to loan the property listed in 5.2.1.3.

6.4 Subject Term (Key Word) listing.

Adapter, Aircraft, Jacking Point,
Aircraft, Adapter, Jacking Point
Boresighting, Aircraft, Positioning
Brake, Aircraft, Repair or Replacement
Jacking Point, Aircraft Adapter
Jig Positioning of Aircraft
Landing Gear Retraction, Operational Check
Landing Gear Steering, Operational Check
Removal Aircraft Landing Gear
Tire, Aircraft, Repair or Replacement

MIL-STD-809B

specification, 1.1 Adapter Ball-Shaped design and size, clearance dimensions and stowage provisions are the subject of international standardization agreement ASCC AIR STD 25/1, 25/7 and NATO STANAG 3098 ASP. When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations.

6.6 Changes from previous issue. Asterisks or vertical lines are not used in his revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians

ARMY - AV
AIR FORCE - 99
NAVY - AS

Preparing Activity:

NAVY AS

International Interest:

NATO

Reviewer

AIR FORCE - 11
AIR FORCE - 70

(Project No. 1730-0149)

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (*DO NOT STAPLE*), and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

Commanding Officer
Naval Air Engineering Center
Systems Engineering Standardization Department
SESD, Code 93
Lakehurst, N.J. 08733-5100

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Air Engineering Center
Systems Engineering Standardization Dept.
SESD, Code 93
Lakehurst, N.J. 08733-5100

ATTN: TJM(9322)



STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

1. DOCUMENT NUMBER

MIL-STD-809B

2. DOCUMENT TITLE

Adapter, Aircraft, Jacking Point, Design & Installation

3a. NAME OF SUBMITTING ORGANIZATION

4. TYPE OF ORGANIZATION (Mark one)

 VENDOR USER MANUFACTURER OTHER (Specify) _____

b. ADDRESS (Street, City, State, ZIP Code)

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER (Last, First, MI) - Optional

b. WORK TELEPHONE NUMBER (Include Area Code) - Optional

c. MAILING ADDRESS (Street, City, State, ZIP Code) - Optional

8. DATE OF SUBMISSION (YYMMDD)

DD FORM 1426
82 MAR

PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)