

NOTICE
OF CHANGE

INCH-POUND

MIL-STD-1179D
NOTICE 3
9 November 1992

MILITARY STANDARD
LAMPS, REFLECTORS AND ASSOCIATED SIGNALING
EQUIPMENT FOR MILITARY VEHICLES

To all Holders of MIL-STD-1179D:

1. The following pages of MIL-STD-1179D have been revised and supersede the page listed:

New Page	Date	Superseded Page	Date Reprinted Without Change
23	14 April 1986	23	17 June 1992
24	14 April 1986	24	

2. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

3. Holders of MIL-STD-1179D will verify that the changes indicated herein have been entered. This notice will be retained as a check sheet. This issuance is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Custodian:
Army - AT

Preparing Activity:
Army - AT

User Activities:
Navy - YD, MC
Air Force - 99

(Project 23GP-0019)

AMSC N/A
DISTRIBUTION STATEMENT A.
Distribution is unlimited.

1 of 1
Approved for public release;

FSC 23GP

MIL-STD-1179D
NOTICE 3TABLE IV. Lighting equipment location for tactical military trucks, trailers and truck tractors of 80 or more inches overall width (see 3.21).

Item	Trucks	Location on Trailers	Truck-tractors	Height above road surface measured from center of item on vehicle at curb weight
Head lamps	On the front, at the same height, 1 on each side of the vertical centerline; as far apart as practicable.		Same as trucks	Not less than 22 inches, nor more than 54 inches.
Tail lamps	On the rear - 1 on each side of the vertical centerline at the same level, as far apart as practicable (see 4.6.1.2).	Same as trucks	Same as trucks	Not less than 15 inches, nor more than 72 inches.
Stop lamps	On the rear - 1 on each side of the vertical centerline at the same level, and as far apart as practicable.	Same as trucks	Same as trucks	Not less than 15 inches, nor more than 72 inches.
Reflex reflectors	On the rear - 1 red on each side of the vertical centerline, at the same level, as far apart as practicable.	Same as trucks	Same as trucks	Not less than 15 inches, nor more than 60 inches.
	On each side - 1 red as far to the rear as practicable, and 1 amber as far to the front as practicable.	Same as trucks	On each side - 1 amber as far to the front as practicable.	Not less than 15 inches, nor more than 60 inches.

MIL-STD-1179D
NOTICE 3

TABLE IV. Lighting equipment location for tactical military trucks, trailers and truck tractors of 80 or more inches overall width (see 3.21) - Continued.

Item	Trucks	Trailers	Truck-tractors	Height above road surface measured from center of item on vehicle at curb weight
Side marker lamps	On each side - 1 red as far to the rear as practicable, and 1 amber as far to the front as practicable.	Not less than 15 inches and on the rear of trailers not more than 60 in (see 4.6.1.6).	On each side - 1 amber as far to the front as practicable.	Not less than 15 inches.
Back-up lamps	On the rear.			No requirement.
Turn signal lamps	At or near the front 1 amber on each side of the vehicle centerline, at the same level, as far apart as practicable. On the rear, 1 red or amber on each side of the vertical centerline at the same height and as far apart as practicable. The turn signal may be part of the stoplight assembly.		Same as trucks	On the front - not less than 15 inches, nor more than 83 inches. On the rear - not less than 15 inches, nor more than 83 inches.