

MIL-STD-1352F
24 April 1985
SUPERSEDING
MIL-STD-1352E
30 June 1979

MILITARY STANDARD

ATTENUATORS, FIXED AND VARIABLE, SELECTION OF



FSC 5985

MIL-STD-1352F

DEPARTMENT OF DEFENSE
Washington, DC 20301

Attenuators, Fixed and Variable, Selection of.

MIL-STD-1352F

1. This Military Standard is approved for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Electronic Systems Command, ATTN: ELEX 8111, Department of the Navy, Washington, DC 20363, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

MIL-STD-1352F

CONTENTS

	Page	
1.	SCOPE	1
1.1	Scope	1
1.2	Purpose	1
2.	REFERENCED DOCUMENTS	1
2.1	Government specifications	1
2.2	Order of precedence	1
3.	DEFINITIONS	1
3.1	Definitions	1
4.	GENERAL REQUIREMENTS	1
4.1	Selection of attenuators	1
4.2	Criteria for selection	2
4.3	Application and use	2
4.4	Detailed requirements for attenuators	2
5.	DETAILED REQUIREMENTS	2
6.	NOTES	2

TABLES

I.	Fixed attenuators with series TNC connectors (male and female)	3
II.	Fixed attenuators with series N connectors	3, 4
III.	Fixed attenuators with series N connectors (male and female)	4, 5
IV.	Fixed attenuators with type UG-45/U and UG-46/U connectors	6
V.	Fixed attenuators with series N connectors (male and female) and cooling fins	6
VI.	Fixed attenuators with SMA connectors (male and female)	7, 8, 9 and 10
VII.	Fixed attenuators, stripline	11
VIII.	Fixed attenuators, TO-5 configuration	12
IX.	Fixed attenuators with SMA connectors (male and female) bulkhead	13
X.	Fixed attenuators with BNC connectors (male and female)	13
XI.	Variable waveguide attenuators	14
XII.	Variable attenuators with series BNC connectors	14
XIII.	Variable attenuators with series SMA connectors	14
XIV.	Variable attenuators with banana plug connections	15
XV.	Variable attenuators with series N connectors	15
XVI.	Variable attenuators with series SMA connectors (coaxial, step)	15
XVII.	Variable attenuators with series TNC connectors (coaxial, step)	15
XVIII.	Cross-reference of AN nomenclature to part number	16

MIL-STD-1352F

1. SCOPE

1.1 Scope. This standard provides a list of standard fixed and variable attenuators for use in military applications.

1.2 Purpose. The purpose of this standard is to:

- a. Provide the equipment designer with a list of fixed and variable attenuators considered standard for use in military applications.
- b. Restrict the number of fixed and variable attenuators for use in military applications in order to provide effective logistic support of equipment.
- c. Establish criteria pertinent to choice and application of fixed and variable attenuators for use in military equipment.

2. REFERENCED DOCUMENTS

2.1 Government specifications. Unless otherwise specified, the following specifications of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation form a part of this standard to the extent specified herein.

SPECIFICATION

Military

MIL-A-3933	-	Attenuators, Fixed General Specification For.
MIL-A-24215	-	Attenuators, Variable (Coaxial and Waveguide), General Specification For.

(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence.

3. DEFINITIONS

3.1 Definitions. The terms used in this standard are those commonly encountered in attenuator engineering practice.

4. GENERAL REQUIREMENTS

4.1 Selection of attenuators. Fixed attenuators to be used in military applications shall be selected from those listed in tables I through X. Variable attenuators to be used in military applications shall be selected from those listed in tables XI through XVII. A cross reference is shown in table XVIII.

MIL-STD-1352F

4.2 Criteria for selection. The criteria for the selection of attenuators for inclusion in this standard are:

- a. The fixed and variable attenuators shall be considered by representatives of the military departments the best available type for current application.
- b. Availability of the fixed and variable attenuators shall be reasonably certain.
- c. The fixed and variable attenuators shall have an approved military specification.

4.3 Application and use. Fixed and variable attenuators used in military applications shall be representative of manufactured lots possessing acceptable material and physical and electrical characteristics and shall in no manner degrade the operational characteristics of the equipment in which used.

4.4 Detailed requirements for attenuators. The detailed requirements for attenuators listed in this standard are covered by the applicable MIL-A-3933 and MIL-A-24215 specification sheets.

5. DETAILED REQUIREMENTS. Not applicable.

6. NOTES. Not applicable.

1-11	"	6	"	"	"	"	"	"	"	"
1-12	"	7	"	"	"	1	"	"	"	"
1-13	"	8	"	"	"	"	"	"	"	"
1-14	"	9	"	"	"	"	"	"	"	"
1-15	"	10	"	"	"	"	"	"	"	"
1-16	"	12	"	"	"	"	"	"	"	"
1-17	"	15	"	"	"	"	"	"	"	"

See footnotes at end of table.

MIL-STD-1352F

TABLE II. Fixed attenuators with series N connectors - Continued.

Part number	Frequency range (GHz)	Attenuation		VSWR (max) (nom)	Impedance (ohms)	Power		Length ^{1/} (max)	Class _{2/}
		Nom (dB)	Devn (±dB)			Avg (V)	Peak (kW)		
M3933/ 1-18	DC to 3.0	20	0.2	1.20:1	50	1	1	4.375(111.13)	IIA
1-19	"	25	"	"	"	"	"	"	"
1-20	"	30	"	"	"	"	"	"	"
1-21	"	40	0.3	"	"	"	"	"	"
1-22	"	50	0.3	"	"	"	"	"	"

^{1/} The length is given in inches and metric equivalents (metric equivalents are in parentheses).

_{2/} A class IIA attenuator is for use as a secondary standard, and in laboratory and precision test equipment.

TABLE III. Fixed attenuators with series N connectors (male and female).

Part number	Frequency range (GHz)	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power		Length ^{1/} (max)	Class _{2/}
		Nom (dB)	Devn (±dB)			Avg (V)	Peak (kW)		
M3933/ 3-08	DC to 1.5	1	0.5	1.30:1	50	35	10	6.42(163.07)	III
3-09	"	2	"	"	"	18	"	"	"
3-10	"	3	"	"	"	15	"	"	"
3-11	"	4	"	"	"	12	"	"	"
3-12	"	5	"	"	"	10	"	"	"
3-13	"	6	"	"	"	"	"	"	"
3-14	"	10	"	"	"	"	"	"	"
3-15	"	20	"	"	"	"	"	6.85(163.07)	"
5-01	1 to 10.0	3	0.1	1.25:1	"	5	"	8.31(211.12)	IIB
5-02	"	6	"	1.25:1	"	3	6	"	"
5-03	"	10	"	1.30:1	"	1	2	"	"
5-04	"	7	"	1.30:1	"	3	6	"	"
5-08	"	1	"	1.25:1	"	5	10	"	"
5-09	"	2	"	"	5	5	10	"	"
5-10	"	4	"	"	50	4	8	"	"
5-11	"	5	"	"	"	3	6	"	"
5-12	"	8	"	1.30:1	"	2	2	"	"
5-13	"	9	"	"	"	"	"	"	"
5-14	2 to 10.0	20	0.2	"	"	"	"	"	"
6-01	DC to 1.5	10	0.1	1.15:1	"	1	1	3.25(82.55)	IIA
6-03	"	6	"	"	"	"	"	"	"
6-05	"	12	"	"	"	"	"	"	"
6-09	"	20	0.2	"	"	"	"	4.37(111.13)	"
6-10	"	30	0.3	"	"	"	"	4.37(111.13)	"
8-01	DC to 4.0	3	0.1	1.30:1	"	"	"	3.25(82.55)	IIB
8-02	"	6	"	"	"	"	"	"	"
8-03	"	10	"	"	"	"	"	"	"
9-04	DC to 4.5	1	0.2	1.35:1	"	4	2	2.75(69.85)	III
9-05	"	2	"	"	"	"	"	"	"
9-06	"	3	"	"	"	"	"	"	"
9-07	"	4	"	"	"	3	"	"	"

See footnotes at end of table.

MIL-STD-1352F

TABLE III. Fixed attenuators with series M connectors (male and female) - Continued.

Part number	Frequency range	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power		Length 1/ (max)	Class 2/
		Nom	Devn			Avg	Peak		
M3933/	(GHz)	(dB)	(±dB)			(W)	(kW)		
9-08	DC to 4.5	5	0.2	1.35:1	50	3	2	2.75(69.85)	III
9-09	"	6	0.3	1.35:1	"	3	"	"	"
9-10	"	8	"	1.25:1	"	2	"	"	"
9-11	"	10	"	"	"	"	"	"	"
9-12	"	12	0.4	"	"	"	"	"	"
9-13	"	15	"	"	"	"	"	"	"
9-14	"	20	"	"	"	"	"	"	"
9-15	"	25	0.6	"	"	"	"	"	"
9-16	"	30	0.6	"	"	"	"	"	"
9-17	"	50	1.0	"	"	"	"	4.0(101.6)	"
9-18	"	60	1.2	"	"	"	"	4.0(101.6)	"
18-01	DC to 12.4	3	0.2	"	"	"	1	2.70(68.58)	IV
18-02	"	6	0.2	"	"	"	"	"	"
18-03	"	10	0.4	"	"	"	"	"	"
18-04	"	20	0.4	"	"	"	"	"	"
18-05	"	30	0.8	"	"	"	"	"	"
18-06	"	40	0.8	"	"	"	"	"	"
18-07	"	50	1.25	"	"	"	"	"	"
18-08	"	60	1.25	"	"	"	"	"	"
18-09	"	1	0.4	"	"	5	"	"	"
18-10	"	2	0.4	"	"	"	"	"	"
18-11	"	3	0.3	"	"	"	"	"	"
18-12	"	5	"	"	"	"	"	"	"
18-13	"	6	"	"	"	"	"	"	"
18-14	"	10	0.4	"	"	"	"	"	"
18-15	"	13	0.5	"	"	"	"	"	"
18-16	"	20	0.5	"	"	"	"	"	"
18-17	"	30	0.8	"	"	"	"	"	"
18-18	"	40	0.8	"	"	"	"	"	"
18-19	"	50	1.0	"	"	"	"	"	"
18-20	"	60	1.0	"	"	"	"	"	"
18-21	DC to 18.0	3	0.3	1.20:1	"	2	0.2	"	"
18-22	"	6	0.3	"	"	"	"	"	"
18-23	"	10	0.5	"	"	"	"	"	"
18-24	"	20	0.5	"	"	"	"	"	"
26-01	0.4 to 18.0	1	0.1	1.50:1	"	5	10	8.31(211.12)	"
26-02	0.5 to 18.0	2	"	"	"	"	"	"	"
26-03	0.6 to 18.0	3	"	"	"	"	"	"	"
26-04	1.0 to 18.0	4	"	"	"	4	8	"	"
26-05	"	5	"	"	"	3	6	"	"
26-06	"	6	"	"	"	3	6	"	"
26-07	"	7	"	"	"	2.5	5	"	"
26-08	"	8	"	"	"	1	1	"	"
26-09	"	9	"	"	"	"	"	"	"
26-10	"	10	"	"	"	"	"	"	"
26-11	2.0 to 18.0	20	0.2	"	"	"	"	"	"

1/ The length is given in inches and metric equivalents (metric equivalents are in parentheses).

2/ A class IIA or IIB attenuator is for use as a secondary standard, and in laboratory and precision test equipment; a class III attenuator is for use in general field equipment; and a class IV attenuator is for use in equipment in which precision and stability are secondary considerations.

MIL-STD-1352F

TABLE IV. Fixed attenuators with type UG-45/U and UG-46/U connectors.

Part number	Frequency range (GHz)	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power		Length ^{1/} (max)	Class ^{2/}
		Nom (dB)	Devn (\pm dB)			Avg (W)	Peak (kW)		
M3933/									
2-02	1 to 4.0	3	0.1	1.30:1	46.5	10	20	14.312(363.52)	IIB
2-03	1 to 4.0	6	0.1	1.30:1	46.5	5	10	14.312(363.52)	IIB

^{1/} The length is given in inches and metric equivalents (metric equivalents are in parentheses).

^{2/} A class IIB attenuator is for use as a secondary standard, and in laboratory and precision test equipment.

TABLE V. Fixed attenuators with series N connectors (male and female) and cooling fins.

Part number	Frequency range (GHz)	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power		Length ^{1/} (max)	Class ^{2/}
		Nom (dB)	Devn (\pm dB)			Avg (W)	Peak (kW)		
M3933/									
10-1	DC to 4.0	6	0.2	1.30:1	50	15	3	5.25(133.35)	III
10-2	"	3	0.5	1.15:1	"	20	1	3.49(88.65)	"
10-3	"	10	"	"	"	"	"	"	"
10-4	"	20	"	"	"	"	"	"	"
10-5	"	30	0.75	"	"	"	"	"	"
10-6	DC to 8.0	3	0.6	1.30:1	"	25	5	"	"
10-7	"	6	"	"	"	"	"	"	"
10-8	"	10	"	"	"	"	"	"	"
10-9	"	20	"	"	"	"	"	"	"
10-10	"	30	1.0	"	"	"	"	"	"
10-11	DC to 11.0	3	0.75	"	"	20	1	"	"
10-12	"	6	"	"	"	"	"	"	"
10-13	"	10	"	"	"	"	"	"	"
10-14	"	20	"	"	"	"	"	"	"
10-15	"	30	"	"	"	"	"	"	"
10-16	DC to 18.0	3	0.3	1.40:1	"	"	"	"	"
10-17	"	6	0.3	"	"	10	"	"	"
10-18	"	10	0.5	"	"	"	2	"	"
10-19	"	20	0.5	"	"	"	"	"	"
10-20	"	30	1.0	"	"	"	"	"	"
10-21	"	40	1.0	"	"	"	"	"	"
10-22	"	50	1.35	"	"	"	"	"	"

^{1/} The length is given in inches and metric equivalents (metric equivalents are in parentheses).

^{2/} A class III attenuator is for use in general field equipment.

MIL-STD-1352F

TABLE VI. Fixed attenuators with SMA connectors (male and female).

Part number	Frequency range (GHz)	Attenuation		VSMR (max)	Impedance (nom) (ohms)	Power		Length 1/ (max)	Class
		Nom (dB)	Devn (±dB)			Avg (W)	Peak (kW)		
M3933/ 14-01	DC to 12.4	3	0.3	1.25:1	50	2	0.2	1.24(31.50)	IV
14-02	"	6	"	"	"	"	"	"	"
14-03	"	10	"	"	"	"	"	"	"
14-04	"	20	0.5	"	"	"	"	"	"
14-05	"	15	0.5	"	"	"	"	"	"
14-06	"	1	0.3	"	"	"	"	"	"
14-07	"	2	"	"	"	"	"	"	"
14-08	"	4	"	"	"	"	"	"	"
14-09	"	5	"	"	"	"	"	"	"
14-10	"	7	0.4	"	"	"	"	"	"
14-11	"	8	"	"	"	"	"	"	"
14-12	"	9	"	"	"	"	"	"	"
14-13	"	30	0.8	"	"	"	"	1.85(46.99)	"
14-14	"	40	0.8	"	"	"	"	"	"
14-15	"	60	2.0	"	"	"	"	"	"
14-16	"	50	2.0	"	"	"	"	"	"
14-17	"	28	0.9	"	"	"	"	"	"
14-18	"	16	0.5	"	"	"	"	1.24(31.50)	"
14-19	"	14	"	"	"	"	"	"	"
14-20	"	13	"	"	"	"	"	"	"
14-21	"	12	"	"	"	"	"	"	"
14-22	"	11	"	"	"	"	"	"	"
14-23	"	1.5	0.3	"	"	"	"	"	"
14-24	"	31	0.9	"	"	"	"	1.85(46.99)	"
16-01	DC to 18.0	3	0.3	1.35:1	"	"	0.5	1.24(31.50)	"
16-02	"	6	0.3	"	"	"	"	"	"
16-03	"	10	0.5	"	"	"	"	"	"
16-04	"	20	0.7	"	"	"	"	"	"
16-05	"	1	0.4	"	"	"	"	"	"
16-06	"	2	0.4	"	"	"	"	"	"
16-07	"	4	0.3	"	"	"	"	"	"
16-08	"	5	0.3	"	"	"	"	"	"
16-09	"	7	0.5	"	"	"	"	"	"
16-10	"	8	"	"	"	"	"	"	"
16-11	"	9	"	"	"	"	"	"	"
16-12	"	30	1.0	"	"	"	"	1.85(46.99)	"
16-13	"	40	1.0	"	"	"	"	"	"
16-14	"	50	2.0	"	"	"	"	"	"
16-15	"	60	2.0	"	"	"	"	"	"
16-16	"	0	0.4	"	"	"	"	1.24(31.50)	"
16-17	"	0.5	"	"	"	"	"	"	"
16-18	"	1.5	"	"	"	"	"	"	"
16-19	"	2.5	"	"	"	"	"	"	"
16-20	"	3.5	0.3	"	"	"	"	"	"
16-21	"	4.5	"	"	"	"	"	"	"
16-22	"	5.5	"	"	"	"	"	"	"
16-23	"	6.5	"	"	"	"	"	"	"
16-24	"	7.5	0.5	"	"	"	"	"	"
16-25	"	8.5	"	"	"	"	"	"	"
16-26	"	9.5	"	"	"	"	"	"	"
16-27	"	10.5	"	"	"	"	"	"	"
16-28	"	11	"	"	"	"	"	"	"
16-29	"	11.5	"	"	"	"	"	"	"
16-30	"	12	"	"	"	"	"	"	"
16-31	"	12.5	"	"	"	"	"	"	"

See footnote at end of table.

MIL-STD-1352F

TABLE VI. Fixed attenuators with SMA connectors (male and female) - Continued.

Part number	Frequency range (GHz)	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power		Length l_1 (max)	Class
		Nom (dB)	Devn (\pm dB)			Avg (W)	Peak (kW)		
M3933/ 16-32	DC to 18.0	13	0.5	1.35:1	50	2	0.5	1.24(31.50)	IV
16-33	"	13.5	"	"	"	"	"	"	"
16-34	"	14	"	"	"	"	"	"	"
16-35	"	14.5	"	"	"	"	"	"	"
16-36	"	15	"	"	"	"	"	"	"
16-37	"	15.5	"	"	"	"	"	"	"
16-38	"	16	0.7	"	"	"	"	"	"
16-39	"	16.5	"	"	"	"	"	"	"
16-40	"	17	"	"	"	"	"	"	"
16-41	"	17.5	"	"	"	"	"	"	"
16-42	"	18	"	"	"	"	"	"	"
16-43	"	18.5	"	"	"	"	"	"	"
16-44	"	19	"	"	"	"	"	"	"
16-45	"	19.5	"	"	"	"	"	"	"
16-46	"	20.5	"	"	"	"	"	"	"
16-47	"	21	"	"	"	"	"	"	"
16-48	"	21.5	"	"	"	"	"	"	"
16-49	"	22	"	"	"	"	"	"	"
16-50	"	22.5	"	"	"	"	"	"	"
16-51	"	23	"	"	"	"	"	"	"
16-52	"	23.5	"	"	"	"	"	"	"
16-53	"	24	"	"	"	"	"	"	"
16-54	"	24.5	"	"	"	"	"	"	"
16-55	"	25	"	"	"	"	"	"	"
16-56	"	28	"	"	"	"	"	"	"
16-57	"	32	1.0	"	"	"	"	1.85(46.99)	"
16-58	"	36	"	"	"	"	"	"	"
16-59	"	44	"	"	"	"	"	"	"
16-60	"	45	"	"	"	"	"	"	"
25-01	DC to 2.0	1	0.3	1.15:1	"	"	"	0.87(22.10)	"
25-02	"	2	"	"	"	"	"	"	"
25-03	"	3	"	"	"	"	"	"	"
25-04	"	4	"	"	"	"	"	"	"
25-05	"	5	"	"	"	"	"	"	"
25-06	"	6	"	"	"	"	"	"	"
25-07	"	7	"	"	"	"	"	"	"
25-08	"	9	"	"	"	"	"	"	"
25-09	"	9	"	"	"	"	"	"	"
25-10	"	10	"	"	"	"	"	"	"
25-11	"	11	"	"	"	"	"	"	"
25-12	"	12	"	"	"	"	"	"	"
25-13	"	13	"	"	"	"	"	1.03(26.16)	"
25-14	"	14	"	"	"	"	"	"	"
25-15	"	15	"	"	"	"	"	"	"
25-16	"	16	"	"	"	"	"	"	"
25-17	"	17	"	"	"	"	"	"	"
25-18	"	19	"	"	"	"	"	"	"
25-19	"	19	"	"	"	"	"	"	"
25-20	"	20	"	"	"	"	"	"	"
25-21	"	21	0.5	"	"	"	"	"	"
25-22	"	22	"	"	"	"	"	"	"
25-23	"	23	"	"	"	"	"	"	"
25-24	"	24	"	"	"	"	"	"	"
25-25	"	25	"	"	"	"	"	"	"
25-26	"	30	"	"	"	"	"	"	"

See footnote at end of table.

MIL-STD-1352F

TABLE VI. Fixed attenuators with SMA connectors (male and female) - Continued.

Part number	Frequency range (GHz)	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power		Length l / (max)	Class
		Nom (dB)	Devn (\pm dB)			Avg (W)	Peak (kW)		
M3933/ 25-27	DC to 12.4	1	0.3	1.25:1	50	2	0.5	0.97(22.10)	IV
25-28	"	2	"	"	"	"	"	"	"
25-29	"	3	"	"	"	"	"	"	"
25-30	"	4	"	"	"	"	"	"	"
25-31	"	5	"	"	"	"	"	"	"
25-32	"	6	"	"	"	"	"	"	"
25-33	"	7	0.4	"	"	"	"	"	"
25-34	"	8	"	"	"	"	"	"	"
25-35	"	9	"	"	"	"	"	"	"
25-36	"	10	"	"	"	"	"	"	"
25-37	"	11	"	"	"	"	"	"	"
25-38	"	12	"	"	"	"	"	"	"
25-39	"	13	"	"	"	"	"	0.94(23.88)	"
25-40	"	14	"	"	"	"	"	"	"
25-41	"	15	"	"	"	"	"	"	"
25-42	"	16	"	"	"	"	"	"	"
25-43	"	17	"	"	"	"	"	"	"
25-44	"	18	"	"	"	"	"	"	"
25-45	"	19	"	"	"	"	"	"	"
25-46	"	20	0.7	"	"	"	"	1.04(26.42)	"
25-47	"	21	"	"	"	"	"	"	"
25-48	"	22	"	"	"	"	"	"	"
25-49	"	23	"	"	"	"	"	"	"
25-50	"	24	"	"	"	"	"	"	"
25-51	"	25	"	"	"	"	"	"	"
25-52	"	30	1.0	"	"	"	"	"	"
25-53	"	35	"	"	"	"	"	1.35(34.29)	"
25-54	"	40	"	"	"	"	"	"	"
25-55	"	45	1.5	"	"	"	"	"	"
25-56	"	50	2.0	"	"	"	"	"	"
25-57	"	60	2.0	"	"	"	"	"	"
25-58	DC to 18.0	0	0.3	1.35:1	"	"	"	0.87(22.10)	"
25-59	"	0.5	"	"	"	"	"	"	"
25-60	"	1	"	"	"	"	"	"	"
25-61	"	1.5	"	"	"	"	"	"	"
25-62	"	2	"	"	"	"	"	"	"
25-63	"	2.5	"	"	"	"	"	"	"
25-64	"	3	"	"	"	"	"	"	"
25-65	"	3.5	"	"	"	"	"	"	"
25-66	"	4	"	"	"	"	"	"	"
25-67	"	4.5	"	"	"	"	"	"	"
25-68	"	5	"	"	"	"	"	"	"
25-69	"	5.5	"	"	"	"	"	"	"
25-70	"	6	"	"	"	"	"	"	"
25-71	"	6.5	"	"	"	"	"	"	"
25-72	"	7	0.4	"	"	"	"	"	"
25-73	"	7.5	"	"	"	"	"	"	"
25-74	"	8	"	"	"	"	"	"	"
25-75	"	8.5	"	"	"	"	"	"	"
25-76	"	9	0.5	"	"	"	"	"	"
25-77	"	9.5	"	"	"	"	"	"	"
25-78	"	10	"	"	"	"	"	"	"
25-79	"	11	"	"	"	"	"	"	"
25-80	"	12	"	"	"	"	"	"	"

See footnote at end of table.

MIL-STD-1352F

TABLE VI. Fixed attenuators with SMA connectors (male and female) - Continued.

Part number	Frequency range (GHz)	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power		Length 1/ (max)	Class
		Nom (dB)	Devn (±dB)			Avg (W)	Peak (kW)		
M3933/ 25-81	DC to 18.0	13	0.5	1.35:1	50	2	0.5	0.94(23.88)	IV
25-82	"	14	0.5	"	"	"	"	0.94(23.88)	"
25-83	"	15	0.6	"	"	"	"	1.04(26.42)	"
25-84	"	16	"	"	"	"	"	"	"
25-85	"	17	"	"	"	"	"	"	"
25-86	"	18	"	"	"	"	"	"	"
25-87	"	19	"	"	"	"	"	"	"
25-88	"	20	"	"	"	"	"	"	"
25-89	"	25	1.0	"	"	"	"	"	"
25-90	"	30	"	"	"	"	"	"	"
25-91	"	35	"	"	"	"	"	1.35(34.29)	"
25-92	"	40	"	"	"	"	"	"	"
25-93	"	45	"	"	"	"	"	"	"
25-94	"	50	2.0	"	"	"	"	"	"
25-95	"	60	2.0	"	"	"	"	"	"

1/ The length is given in inches and metric equivalents (metric equivalents are in parentheses).

MIL-STD-1352F

TABLE VII. Fixed attenuators, stripline.

Part number M3933/	Frequency range (GHz)	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power Peak (W)	Length ^{1/} (max)	Class
		Nom (dB)	Devn (±dB)					
22-01	DC to 12.4	3	0.6	1.50:1	50	100	0.125(3.18)	IV
22-02	"	6	"	"	"	100	"	"
22-03	"	10	"	"	"	50	"	"
22-04	"	20	1.5	"	"	50	0.250(6.35)	"
22-05	"	1	0.6	"	"	100	0.125(3.18)	"
22-06	"	5	"	"	"	100	"	"
22-07	"	7	"	"	"	50	"	"
22-08	"	8	0.6	"	"	"	"	"
22-09	"	12	0.7	"	"	"	"	"
22-10	"	15	1.0	"	"	"	"	"
22-11	"	17	1.2	"	"	"	"	"
22-13	"	2	0.6	"	"	100	"	"
22-15	"	4	0.6	"	"	"	"	"
22-23	DC to 18.0	1	0.7	1.80:1	"	"	"	"
22-24	"	2	"	"	"	"	"	"
22-25	"	3	"	"	"	"	"	"
22-26	"	4	"	"	"	"	"	"
22-27	"	5	"	"	"	"	"	"
22-28	"	6	"	"	"	"	"	"
22-29	"	7	"	"	"	"	"	"
22-30	"	8	"	"	"	"	"	"
22-31	"	9	"	"	"	"	"	"
22-32	"	10	0.5	"	"	"	"	"
22-33	"	11	0.5	"	"	"	"	"
22-34	"	12	1.0	"	"	"	"	"
22-35	"	13	1.0	"	"	"	"	"
22-36	"	14	+0.0 -1.7	"	"	"	"	"
22-37	"	15	+0.0 -2.0	"	"	"	"	"
22-38	"	16	+0.0 -2.3	"	"	"	"	"
22-39	"	17	+0.0 -2.5	"	"	"	"	"
22-40	"	18	+0.0 -3.0	"	"	"	"	"
22-41	"	19	+0.0 -3.5	"	"	"	"	"
22-42	"	20	+0.0 -3.5	"	"	"	"	"

^{1/} The length is given in inches and metric equivalents (metric equivalents are in parentheses).

MIL-STD-1352F

TABLE VIII. Fixed attenuators, T0-5 configuration.

Part number	Frequency range (GHz)	Attenuation		VSWR (max)	Impe- ance (nom) (ohms)	Power Avg mW	Class
		Nom (dB)	Devn (±dB/dB)				
M3933/ 23-01	DC to 1.0	3	0.1	1.35:1	50	100	IV
23-02	"	6	"	"	"	"	"
23-03	"	10	"	"	"	"	"
23-04	"	13	"	"	"	"	"
23-05	"	15	"	"	"	"	"
23-06	"	20	"	"	"	"	"
23-07	"	30	"	"	"	"	"
23-08	"	1	"	"	"	"	"
23-09	"	2	"	"	"	"	"
23-10	"	4	"	"	"	"	"
23-11	"	5	"	"	"	"	"
23-12	"	7	"	"	"	"	"
23-13	"	8	"	"	"	"	"
23-14	"	9	"	"	"	"	"
23-15	"	11	"	"	"	"	"
23-16	"	12	"	"	"	"	"
23-17	"	14	"	"	"	"	"
23-18	"	16	"	"	"	"	"
23-19	"	17	"	"	"	"	"
23-20	"	18	"	"	"	"	"
23-21	"	19	"	"	"	"	"
23-22	"	21	"	"	"	"	"
23-23	"	22	"	"	"	"	"
22-24	"	23	"	"	"	"	"
22-25	"	24	"	"	"	"	"
22-26	"	25	"	"	"	"	"
22-27	"	26	"	"	"	"	"
22-28	"	27	"	"	"	"	"
22-29	"	28	"	"	"	"	"
22-30	"	29	"	"	"	"	"
22-31	"	31	"	"	"	"	"
22-32	"	32	"	"	"	"	"
22-33	"	33	"	"	"	"	"
22-34	"	34	"	"	"	"	"
22-35	"	35	"	"	"	"	"
22-36	"	36	"	"	"	"	"
22-37	"	37	"	"	"	"	"
22-38	"	38	"	"	"	"	"
22-39	"	39	"	"	"	"	"
22-40	"	40	"	"	"	"	"
22-41	"	41	"	"	"	"	"

MIL-STD-1352F

TABLE IX. Fixed attenuators with SMA connectors (male and female), bulkhead.

Part number	Frequency range (GHz)	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power		Length ^{1/} (max)	Class _{2/}
		Nom (dB)	Devn (±dB)			Avg (W)	Peak (kW)		
M3933/ 24-01	2 to 12.4	10	0.3	1.25:1	50	2	0.1	1.03(26.2)	IV
24-02	"	15	0.5	"	"	"	"	"	"
24-03	"	20	0.5	"	"	"	"	"	"

^{1/} The length is given in inches and metric equivalents (metric equivalents are in parentheses).

_{2/} A class IV attenuator is for use in equipment in which precision and stability are secondary considerations.

TABLE X. Fixed attenuators with BNC connectors (male and female).

Part number	Frequency range (GHz)	Attenuation		VSWR (max)	Impedance (nom) (ohms)	Power		Length ^{1/} (max)	Class
		Nom (dB)	Devn (±dB)			Avg (W)	Peak (kW)		
M3933/ 19-01	DC to 4.5	1	0.3	1.25:1	50	4	0.5	2.7(68.6)	III
19-02	"	2	"	"	"	"	"	"	"
19-03	"	3	"	"	"	"	"	"	"
19-04	"	4	"	"	"	3	"	"	"
19-05	"	5	"	"	"	"	"	"	"
19-06	"	6	"	"	"	"	"	"	"
19-07	"	8	0.5	"	"	2	"	"	"
19-08	"	10	"	"	"	"	"	"	"
19-09	"	11	"	"	"	"	"	"	"
19-10	"	12	"	"	"	"	"	"	"
19-11	"	15	"	"	"	"	"	"	"
19-12	"	20	"	"	"	"	"	"	"
19-13	"	25	0.9	"	"	"	"	"	"
19-14	"	30	"	"	"	"	"	"	"
19-15	"	40	"	"	"	"	"	3.0(76.2)	"
19-16	"	50	1.2	"	"	"	"	"	"
19-17	"	60	1.4	"	"	"	"	"	"
19-18	"	13	0.5	"	"	"	"	2.7(68.6)	"

^{1/} The length is given in inches and metric equivalents (metric equivalents are in parentheses).

MIL-STD-1352F

TABLE XI. Variable waveguide attenuators.

Part number M24215/	Frequency range (GHz)	Attenuation range (dB)	Accu- racy (*dB)	Insertion loss (dB)	VSWR (max)	Imped- ance (ohms)	Power	
							Avg (W)	Peak (W)
4-001	8.5-9.6	0-60	--	1.0	1.15:1	-	1	--
4-002	7.0-11.0	0-20	--	0.3	1.25:1	-	5	100
4-003	10.8-18.0	0-20	--	0.3	1.25:1	-	5	"
4-004	11.0-17.0	0-30	--	0.5	1.40:1	-	1	"
4-005	12.4-18.0	"	--	"	1.15:1	-	"	"
4-006	12.4-18.0	"	--	"	"	-	"	"
5-001	3.95-5.85	0-50	0.1	1	"	-	15	--
5-002	5.3-8.2	"	"	"	"	-	10	--
5-003	8.2-12.4	"	"	"	"	-	10	--
5-004	12.4-18.0	"	"	"	"	-	5	--
5-005	2.6-3.95	0-60	"	"	"	-	10	--

TABLE XII. Variable attenuators with series BNC connectors.

Part number M24215/	Frequency range (GHz)	Attenuation range (dB)	Accu- racy (*dB)	Insertion loss (dB)	VSWR (max)	Imped- ance (ohms)	Power	
							Avg (W)	Peak (W)
6-001	DC to 1.0	0-12 (in 1 dB step)	0.35	1.5	1.50:1	50	0.5	--
6-002	"	0-120 (in 10 dB step)	3.0	1.5	1.50:1	"	0.5	--
10-001	"	0-101 (in 1 dB step)	2	0.6	1.40:1	"	1	--
10-002	DC to 0.5	0-101 (in 1 dB step)	2	0.2	1.40:1	75	0.5	--

TABLE XIII. Variable attenuators with series SMA connectors.

Part number M24215/	Frequency range (GHz)	Attenuation range (dB)	Accu- racy (*dB)	Insertion loss (dB)	VSWR (max)	Imped- ance (ohms)	Power	
							Avg (W)	Peak (W)
8-001	DC to 2.0	0-10 (in 1 dB step)	0.5	0.5	1.25:1	50	0.5	--
8-002	DC to 1.0	0-1 (in 0.1 dB step)	0.05	1.0	1.20:1	"	0.5	--
9-001	2-8.0	0-20	--	0.5	1.50:1	"	2	--
9-002	2-8.0	0-20	--	"	"	"	"	--
9-003	7.0-11.0	0-30	--	"	"	"	"	--
9-004	9.0-9.2	0-30	0.5	0.7	"	"	"	200
9-005	4.0-18.0	0-15	--	1.0	"	"	5	3000
9-006	11.0-17.0	0-20	--	0.5	1.60:1	"	5	3000

MIL-STD-1362F

TABLE XIV. Variable attenuators with banana plug connections.

Part number M24215/	Frequency range (MHz)	Attenuation range (dB)	Accu- racy (*dB)	Insertion loss (dB)	VSWR (max)	Imped- ance (ohms)	Power	
							Avg (W)	Peak (W)
11-001	DC to 1.0	0-100 (in 1 and 10 dB step)	.25 for 10 dB .75 for 100 section	--	--	600	5	--

TABLE XV. Variable attenuators with series N connectors.

Part number M24215/	Frequency range (MHz)	Attenuation range (dB)	Accu- racy (*dB)	Insertion loss (dB)	VSWR (max)	Imped- ance (ohms)	Power	
							Avg (W)	Peak (W)
12-001	DC - 1.0	0-10	0.2	0.8	1.50:1	50	2	60
12-002	0.5-1.0	0-10	0.2	0.5	"	"	2	60
12-003	0.8-2.5	0-30	--	0.2	"	"	10	5 kW
12-004	3.0-3.7	0-10	--	0.5	"	"	1	1 kW
12-005	2.0-5.0	0-20	--	0.5	"	"	2	2 kW
12-006	0.3-8.0	0-25	--	0.7	"	"	10	--
12-007	4.0-8.0	0-20	1.0	1.0	1.25:1	"	"	5 kW
12-008	4.0-8.0	0-40	1.5	1.5	"	"	"	"
12-009	7.0-11.0	0-40	1.5	1.5	"	"	"	5 "
12-010	DC-12.4	0-99	2.0	0.8	1.50:1	"	2	200
12-011	2.5-11.0	0-20	0.2	1.0	1.60:1	"	1	1 kW

TABLE XVI. Variable attenuators with series SMA connectors (coaxial, step).

Part number M24215/	Frequency range (MHz)	Attenuation range (dB)	Accu- racy (*dB)	Insertion loss (dB)	VSWR (max)	Imped- ance (ohms)	Power	
							Avg (W)	Peak (W)
13-01	DC-18.0	0-9	0.5	1.0	1.50:1	50	2	200
13-02	DC- 4.0	0-99	1.6	0.6	1.35:1	50	2	200

TABLE XVII. Variable attenuators with series TNC connectors (coaxial, step).

Part number M24215/	Frequency range (MHz)	Attenuation range (dB)	Accu- racy (*dB)	Insertion loss (dB)	VSWR (max)	Imped- ance (ohms)	Power	
							Avg (W)	Peak (W)
14-01	DC-12.4	0-69	1.8	0.8	1.50:1	50	2	200

MIL-STD-1352F

TABLE XVIII. Cross-reference of AN nomenclature to part number.

AN nomenclature	Part number M3933/	AN nomenclature	Part number
CN-30B/U	6-1	CN-330A/U	M3933/3-5
CN-32B/U	6-3	CN-796/U	M24215/10-001
CN-35B/U	6-5	CN-1128/U	M24215/6-002
CN-39B/U	6-9	CN-1138/U	M24215/4-001
CN-40B/U	6-10	CN-1139/U	M24215/5-001
CN-84B/U	5-1	CN-1140/U	M24215/6-001
CN-85B/U	5-2	CN-1295/U	M3933/8-1
CN-86B/U	5-3	CN-1296/U	M3933/8-2
CN-87B/U	4-1	CN-1297/U	M3933/8-3
CN-168B/U	2-2	CN-1298/U	M3933/9-1
CN-169B/U	2-3	CN-1299/U	M3933/9-2
CN-248A/U	1-4	CN-1300/U	M3933/9-3
CN-265A/U	5-4	CN-1301/U	M3933/10-1

Custodians:

Army - ER
Navy - EC
Air Force - 85

Preparing activity:

Navy - EC

(Project 5985-0991)

Review activities:

Army - AR, MI
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities:

Army - AV, ME
Navy - AS, MC, CG, SH
Air Force - 19

Agent:

DLA - ES

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (*DO NOT STAPLE*), and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY




NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND (ELEX 8111)
WASHINGTON, DC 20360



STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL*(See Instructions – Reverse Side)*

1 DOCUMENT NUMBER	2 DOCUMENT TITLE		
3a. NAME OF SUBMITTING ORGANIZATION		4 TYPE OF ORGANIZATION (Mark one)	
b. ADDRESS (Street, City, State, ZIP Code)		<input type="checkbox"/> VENDOR	
		<input type="checkbox"/> USER	
		<input type="checkbox"/> MANUFACTURER	
		<input type="checkbox"/> OTHER (Specify) _____	
5 PROBLEM AREAS			
a. Paragraph Number and Wording			
b. Recommended Wording			
c. Reason/Rationale for Recommendation			
6 REMARKS			
7a. NAME OF SUBMITTER (Last, First, MI) – Optional		b. WORK TELEPHONE NUMBER (Include Area Code) – Optional	
c. MAILING ADDRESS (Street, City, State, ZIP Code) – Optional		8 DATE OF SUBMISSION (YYMMDD)	