

MIL-STD-1554
NOTICE 2
28 Nov 1977

MILITARY STANDARD

INSERT ARRANGEMENTS FOR
MIL-C-83723 SERIES III AND MIL-C-26500
ENVIRONMENT RESISTING, CIRCULAR,
ELECTRICAL CONNECTORS

TO ALL HOLDERS OF MIL-STD-1554:

1. THE FOLLOWING PAGES OF MIL-STD-1554 HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

<u>NEW PAGE</u>	<u>DATE</u>	<u>SUPERSEDED PAGE</u>	<u>DATE</u>
1	15 January 1976	(Reprinted without change)	
2	28 November 1977	2	1 July 1975

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS..

3. Holders of MIL-STD-1554 will verify that page changes and additions indicated above have been entered. This notice page will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:

Army - EL
Navy - AS
Air Force - 85

Preparing activity:

Air Force - 85
(Project 5935-3007-8)

Review activities:

Army - AV, MI, MU
Air Force - 11, 15, 17, 99
DLA - ES

MIL-STD-1554
15 January 1976

1. SCOPE

1.1 This standard covers insert arrangements for use with MIL-C-83723 series III and MIL-C-26500 environment resisting, circular, electrical connectors.

2. REFERENCED DOCUMENTS

2.1 The issues of the following documents in effect on the date of invitation for bids form a part of this standard to the extent specified herein.

SPECIFICATIONS

MILITARY

- MIL-C-26500 - Connectors, General Purpose, Electrical, Miniature, Circular, Environment Resisting, General Specification for.
- MIL-C-83723 - Series III - Connectors, Electrical, (Circular, Environment Resisting), Receptacles and Plugs, General Specification for.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this standard to the extent specified herein.

ANSI Y14.5-1973 - Dimensioning and Tolerancing.

(Application for copies should be addressed to American Standards Institute, 1430 Broadway, New York, NY 10018.)

3. DEFINITIONS

3.1 The terms used in this standard are generally accepted by the electrical and electronics industries and commonly used in electrical connector engineering practice.

4. GENERAL REQUIREMENTS

Not applicable.

5. DETAIL REQUIREMENTS


5.1 Dimensions. Dimensions shall be in accordance with the applicable section of this standard and the following dimensional data:

- (a) Dimensioning and tolerancing in accordance with ANSI Y14.5-1973.
Dimensions are true position and in inches.
- (b) Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
- (c) Dimensions and markings shown are for engaging face of socket insert; pin insert is opposite.
- (d) The following tolerances apply to insert installed in shell:
 - 1. Center of each hole in insert shall be located at true position within .014 dia. $\oplus .014 \text{ dia.}$
 - 2. Center of engaging end of each contact shall be located at true position within .024 dia. $\oplus .024 \text{ dia.}$
- (e) Unless otherwise indicated, dimensions are symmetrical about centerline.

5.2 Main key or keyway polarization (see figure 1).

- (a) Each insert arrangement is shown in the "normal position" in the shell.
- (b) For alternate polarizing positions, the connector insert is rotated in respect to the shell.

MIL-STD-1554
28 November 1977



ALTERNATE SHELL KEY POSITIONS FOR CONNECTORS													INSERT POSITION E°
POSITION	SIZE 8				SIZE 10				SIZES 12 THRU 24				
	A°	B°	C°	D°	A°	B°	C°	D°	A°	B°	C°	D°	
N-NORMAL	105	140	215	265	105	140	215	265	105	140	215	265	0
1	-	-	-	-	↑	↑	↑	↑	↑	↑	↑	↑	10
2	-	-	-	-	↑	↑	↑	↑	↑	↑	↑	↑	20
3	-	-	-	-	↑	↑	↑	↑	↑	↑	↑	↑	30
4	-	-	-	-	↑	↑	↑	↑	↑	↑	↑	↑	40
5	-	-	-	-	↑	↑	↑	↑	↑	↑	↑	↑	50
6	102	132	248	320	102	132	248	320	18	149	192	259	0
7	80	118	230	312	80	118	230	312	92	152	222	342	0
8	35	140	205	275	35	140	205	275	84	152	204	334	0
9	64	155	234	304	64	155	234	304	24	135	199	240	0
Z 1/					25	115	220	270	98	152	268	338	0

1/ Alternate position '10' is cancelled and superseded by position Z.

INCHES	MM	INCHES	MM	INCHES	MM
.003	.08	.370	9.40	.696	17.68
.004	.10	.373	9.47	.700	17.78
.005	.13	.405	10.29	.708	17.98
.042	1.07	.408	10.36	.711	18.06
.052	1.32	.413	10.49	.765	19.43
.063	1.60	.424	10.77	.769	19.53
.072	1.83	.428	10.87	.892	22.66
.084	2.13	.468	11.89	.896	22.76
.094	2.39	.471	11.96	.998	25.35
.115	2.92	.521	13.23	1.002	25.45
.125	3.18	.524	13.31	1.123	28.52
.225	5.72	.526	13.36	1.127	28.63
.228	5.79	.530	13.46	1.248	31.70
.234	5.94	.583	14.81	1.252	31.80
.237	6.02	.586	14.88	1.373	34.87
.285	7.24	.646	16.41	1.377	34.98
.288	7.32	.649	16.48		

SHELL SIZE	F +.000 -.005	G +.003	H +.003	J +.000 -.003	K +.005 -.000	L +.003	M +.005 -.000	N +.005 -.000
8 1/	.424	.084	.042	.234	.428	.094	.063	.237
8 2/	.405	.084	.052	.225	.413	.094	.072	.228
10	.526	.084	.052	.285	.530	.094	.072	.288
12	.696	.084	.052	.370	.700	.094	.072	.373
14	.765	.084	.052	.405	.769	.094	.072	.408
16	.892	.115	.052	.468	.896	.125	.072	.471
18	.998	.115	.052	.521	1.002	.125	.072	.524
20	1.123	.115	.052	.583	1.127	.125	.072	.586
22	1.248	.115	.052	.646	1.252	.125	.072	.649
24	1.373	.115	.052	.708	1.377	.125	.072	.711

1/ Shell size 8 (bayonet and MIL-C-26500 threaded).
2/ Shell size 8 (MIL-C-83723, series III, threaded only).

Main key/keyway polarization.

FIGURE 1. Main key or keyway polarization.

Supersedes page 2 of 1 July 1975.