

This document has been approved
for public release and sale;
its distribution is unlimited.

MIL-STD-1658(OS)
NOTICE - 1
6 September 1974

MILITARY STANDARD
SHIPBOARD GUIDED MISSILE LAUNCHING SYSTEM
SAFETY REQUIREMENTS, MINIMUM

To all holders of MIL-STD-1658(OS):

1. Make the following pen and ink changes to MIL-STD-3658(OS) of 15 May 1974:

- a. Page 4, paragraph 5.5, line 2: Delete "be 1".
- b. Page 5, paragraph 5.11: Delete entirely and add the note "See Notice 1 of 6 September 1974 for revised paragraph 5.11" to reference the following revised paragraph 5.11:

5.11 A system shall be provided for the launcher which restricts pointing of the missile to only those "safe zones" within which the launched missile would safely clear ship superstructure and installations. The firing circuit shall be interrupted if the missile is pointing outside the "safe zones".

2. Retain this Notice page and insert before the Table of Contents of MIL-STD-1658(OS) of 15 May 1974.

3. Holders of MIL-STD-1658(OS) will verify that pages have been changed as indicated above. This Notice is a separate publication. Each Notice is to be retained by stocking points until MIL-STD-1658 is revised or cancelled, as Notices are not cumulative.

Custodian
NAVY - OS

★ U.S. GOVERNMENT PRINTING OFFICE: 1974-603-110/1848

Preparing Activity
NAVY - OS

Project Number 1440-N042

FSC 1440