

NOT MEASUREMENT SENSITIVE

MIL-STD-1691

15 FEBRUARY 2005

SUPERSEDING

MIL-STD-1691

16 JUNE 2004

MILITARY STANDARD

CONSTRUCTION AND MATERIAL SCHEDULE FOR
MILITARY MEDICAL AND DENTAL FACILITIES

AMSC N/A

FSC 6530

DISTRIBUTION STATEMENT A: APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS
UNLIMITED.

FOREWORD

1. This Military Standard is approved for use by all Departments and Agencies of the Department of Defense.
2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Facilities Engineering Command, Medical Facilities Design Office - Code 09MD, 901 M St SE, Building 212, Washington, DC 20374-5018 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.
3. The application information contained in this standard shall be applied in military construction budgets and may be used to identify equipment for construction and renovation planning not included in a military construction budget.
4. All built-in casework shall be fabricated and designated in accordance with Military Specification MIL-C-20709 (latest edition). All other casework shall be designated, specified, and installed in accordance with MILSPEC MIL-C-29240 Casework - Moveable and Modular for Hospital Laboratories and Pharmacies, MILSPEC MIL-C-2924I Material Handling Units for Medical Facilities, MILSPEC MIL-F-28687 Frame, Mobile, Hospital Laboratories and Pharmacies, Military Guide Spec II704, and other specifications as directed by the design agency.
5. The Joint Schedule Numbers (JSN) or the National Stock Numbers, within the MIL-STD-1691, shall not be used as substitutes for contract specifications and detail drawings. Citing JSN numbers and nomenclatures will not relieve the architect or design agency of the responsibility to verify and provide all necessary detail drawings and specifications showing actual dimensions, utility connections, accessories, quantity, quality, and performance required.

CONTENTS

PARAGRAPH	Page
1. SCOPE	1
1.1 Scope and purpose	1
1.2 Application	1
2. APPLICABLE DOCUMENTS (Not applicable)	1
3. DEFINITIONS	1
3.1 General	1
3.2 Schedule terms	1
3.3 Abbreviations	3
4. GENERAL REQUIREMENTS	11
4.1 Joint schedule numbers	11
4.2 Items not included	11
4.3 Additions, deletions, or changes	11
5. DETAILED REQUIREMENTS	11
5.1 Special instructions	11
5.2 Logistical responsibility	12
6. NOTES	17
6.1 Special considerations	17
6.2 Legend of utilities	17
6.3 Subject term (keyword) listing	19
6.4 Changes from previous issue	19
TABLES	
I. Item divisions and logistical responsibilities	13
APPENDIXES	
A. Medical/dental equipment catalog (by JSN)	21
Medical/dental equipment catalog alphabetical index	391

This page intentionally left blank.

1. SCOPE

- 1.1 Scope and purpose. This standard establishes a definite demarcation between the various elements involved in the planning, funding, construction, and funding of the medical and dental facilities of the Armed Services, the Department of Veterans Affairs, the United States Public Health Service (USPHS) and other using agencies. This standard provides a uniform basis upon which the Medical Services can identify items of construction and material and fix logistical and financial responsibility in an identical manner.
- 1.2 Application. This standard shall be applied to the architectural, financial and logistic planning, construction, and equipping of all medical and dental facilities included in the military and other using agency budgets for medical construction appropriation funds, other procurement (investment equipment) organizational maintenance funds, and departmental operation funds of the using service or agency.

2. APPLICABLE DOCUMENTS

This section is not applicable to this standard.

3. DEFINITIONS

- 3.1 General. As used in this standard for the schedule of items, the following definitions pertain to:
 - a. Fixed - fastened to walls, floors or ceiling, or to steam, gas, plumbing, electrical power, sensor lines in a permanent manner.
 - b. Portable - movable, including that equipment which is attached to utility lines by attachment plug, screw-on fitting, or quick disconnect fittings, and that which is of such size and use that special consideration must be given to its location.
 - c. Mobile - equipment on wheels or casters.
- 3.2 Schedule terms. Terms used in the column headings and body of the schedule are defined as follows:

JSN Joint Schedule Number. The number shall consist of an alpha character followed by four additional characters. The first alpha character shall denote the equipment groups as follows:

JSN	Equipment Groups
A	Architectural
C	Fixed Casework
D	Dental Equipment/and Dental Casework
E	Modular Casework
F	Furniture and Furnishing
K	Food Service Equipment
L	Laboratory Equipment
M	Miscellaneous
P	Plumbing Fixtures
R	Refrigeration
S	Sterilizers and Associated Equipment
T	Shop Equipment/Tools
U	User Specific Items
V	Veterinary
X	X-Ray Equipment and Accessories
W	War Readiness Materials

NSN National Stock Number as used in the Federal Supply System

Nomenclature Name of item.

CAT Category of Logistical Responsibility.

- A Contractor furnished and installed from construction funds (Construction Appropriations/Medical Construction Appropriations).
- B Government furnished from using service operating funds other than construction and installed by contractor from construction funds (Construction Appropriations/Medical Construction Appropriations).
- C Government furnished and installed from existing assets or from funds other than construction.
- D Other. Leased or rented equipment, or that obtained under special conditions as indicated. Fund source will be other than Construction Appropriation/Medical Construction Appropriations.
- E Government furnished and contractor installed from Construction Appropriation/Medical Construction Appropriations funds. (Procurement may be delayed until the latest date feasible that will not interfere with project completion. This will provide the latest model of equipment at the time it is needed.)
- F Government furnished and Government (vendor) installed from Construction Appropriation/Medical Construction Appropriations funds. (Procurement may be delayed until the latest date feasible that will not interfere with project completion. This will provide the latest model of equipment at the time it is

needed.)

- G Government furnished and installed equipment requiring special funding (not MILCON or project specific OM or OP dollars) and may require other justification and approvals.

3.3 Abbreviations. Abbreviations as used in this standard are defined as follows:

Abbreviation	Description
2RCSD	Two Wall Recessed
A	Angstrom
ABDOM	Abdominal/Abdomen
AC	Alternating Current
ADJ	Adjustable
AIDS	Acquired Immune Deficiency Syndrome
Al	Aluminum
AMPS	Amperes
ANES	Anesthesia
ANGIO	Angiography/angiographic
AR	As Required
ASSY	Assembly
ASTM	American Society for Testing and Materials
ATT	Attached/Attachment(s)
AUDIO	Audiometric/Audiometer
AUTO	Automatic
BAC	Bacteriological
BEV	Beverage
BIO	Biological
BKSPLSH	Backsplash
BNCH	Bench
BSE	Base
BTU	British Thermal Units
C	Centigrade/Celsius
C/	Central or Building Supplied
CAB	Cabinet
CAL	Calibration
CAP	Capacity
CARB	Carbonated
CATH	Catheterization

cc	Cubic Centimeter
CCTV	Closed Circuit Television
CCU	Coronary Care Unit
CEIL	Ceiling
CEPH	Cephalometric
CF	Complement Fixation
CFM	Cubic Feet Per Minute
CH	Channel
CHMBR	Chamber
CHOC	Chocolate
Cl	Chlorine
CMPT	Compartment
CMPTR	Computer
CMRA	Camera
CNR	Corner
CNTR	Center
Co	Cobalt
CO2	Carbon Dioxide
COLL	Collector
COMB	Combination
COMP	Compressor
COMPAT	Compatible
CONT	Continuous
CRM	Corrosion Resistant Metal
CRS	Corrosion Resistant Steel
CRT	Cathode Ray Tube
CS	Case
CSF	Cerebrospinal Fluid
CSH	Closed Shelf
CSTRS	Casters
CT	Computerized/Computed Tomography
CTR	Counter
CUFT	Cubic Foot
CUYD	Cubic Yard
CYL	Cylinder
D	Depth/Deep
DBL	Double
DC	Direct Current
DEPMEDS	Deployable Medical Systems

DIA	Diameter
DISINFECT	Disinfectant
DIV	Division
DNA	Deoxyribonucleic Acid
DO	Door
DPM	Drops Per Minute
DR	Drawer
DRNBD	Drainboard
E	Electron
EA	Each
EEG	Electroencephalogram
ECG	Electrocardiograph/Electrocardiogram
EIA	Enzyme Immunoassay
ELEC	Electrical/Electric
ENT	Ears, Nose and Throat
ETO	Ethylene Oxide
EX	Executive
EP	Explosion Proof
F	Fahrenheit
F/S	Free Standing
FDR	File Drawer
FED SPEC NO	Federal Specification Number
FG	Fiberglass
FGC	Fiberglass Cement
FLUOR	Fluorescent
FLR	Floor
FNT	Front
FPM	Feet Per Minute
FR-DTGS	Fast Recovery Deuterated Triglycerine Sulfate
FREQ	Frequency
FT	Foot/Feet
GAL	Gallon
GD	Garbage Disposal
GDO	Glazed Door
gm	Gram
GPH	Gallons Per Hour
GPM	Gallons Per Minute
GV	Gravity

H2SO4	Sulfuric Acid
HCl	Hydrochloric Acid
HCO	Hydrogen Ion Activity or Hemoglobin Measurements
HCT	Hematocrit
HD	Head
HDO	Half Door
HDR	Half Drawer
HEPA	High Efficiency Particulate Air
Hg	Mercury
Hgb	Hemoglobin
HORIZ	Horizontal
HP	Horsepower
HR	Hour
HT	Height/High
HTD	Heated
HTR	Heater
HVY DTY	Heavy Duty
HYD	Hydraulic
HZ	Hertz
ICU	Intensive Care Unit
ID	Inside Dimension
IN	Inch
INDIVL	Individual
INJ	Injector, Injection, Injected
INSTRU	Instrument
IPS	International Pipe Standard
ISE	Ion Selective Electrode
IV	Intravenous
K	Thousand/Potassium
KEYBD	Keyboard
KG	Kilogram
KV	Kilovolt
KVA	Kilovolt Ampere
KW	Kilowatt
L	Length
LAB	Laboratory
LAT	Lateral

LB	Pound
LC	Liquid Chromatography
LDG	Loading
LDO	Lower Door
LED	Light Emitting Diode
LFIL	Lateral File
LiTa	Lithium – Tantalate
LP	Lamp
LPM	Liters Per Minute
LT	Light
LVLS	Levels
mA	Milliampere
MACH	Machine
MAX	Maximum
MBL	Mobile
MCV	Mean Corpuscular Volume
MECH	Mechanical
MED	Medical
mEq	Milliequivalent
mEq/L	Milliequivalent Per Liter
MEV	Million Electron Volts
mg	Milligram
mg/dl	Milligrams Per Deciliter
min	minute, minimum
MKR BD	Marker Board
mL	milliliter
mm	millimeter
mmHg	Millimeters of Mercury
mmol/l	Millimol per Liter
MNFLDS	Manifolds
MNTD	Mounted
MNTRNG	Monitoring
MOD	Modular
MORT	Mortuary
MRI	Magnetic Resonance Imaging
MSN	Military Specification Number
MTR	Motor
MULT	Multiple
MV	Megavolt

Na	Sodium
Na/K/Li	Sodium Potassium Lithium
NARC	Narcotics
ng	Nanograms
nm	Nanometer
NOM	Nominal
NP	Neuropsychiatric
NPT	National Pipe Thread
OD	Outside Diameter/Optical Density
OH	Overhead
Ohm/cm	Ohm per Centimeter
OmmHg	Oxygen Millimeters of Mercury
ORTHO	Orthopedic
OT	Occupational Therapy
P	Phosphor, Phosphorus
P/H	Panel Hung
P/THRU	Pass Through
PANO	Panographic
PAR	Parallel
PBD	Pullboard
PC	Personal Computer
PCO2	Partial Pressure of Carbon Dioxide
PED	Pedestal
PER	Person
pH	The negative logarithm of the effective hydrogenion concentration or hydrogenion activity
PHARM	Pharmacy
PL	Place
PNL	Panel
PNT	Patient
PO2	Partial Pressure of Oxygen
PREFAB	Prefabricated
PREPN	Preparation
PREVAC	Prevacuum
PRIV	Privacy/Private
PSI	Pounds Per Square Inch
PSIG	Pounds Per Square Inch Gauge
PT	Physical Therapy
PTBL	Portable

PTT	Prothrombin Time Test
PWRD	Powered
R/F	Radiographic/Flu
RBC	Red Blood Coun
RCD	Record
RCSD	Recessed
REF	Refrigerated
REFR	Refrigerator
REQ	Require/d
RESP	Respiratory
RF	Radio Frequency
RIA	Radioimmunoass
RM	Room
ROT	Rotating
RPM	Revolutions/Rota
RR	Rear
SCRN	Screen
SDO	Sliding Door
Secs	Seconds
SECT	Section
SECY	Secretary/Secre
SENS	Sensitivity
SER	Service
SF	Square Foot
SGDO	Sliding Glass Door
SH	Shelf(ves)
SL	Slice
SLDG	Sliding
SMPLS	Samples
SNGL	Single
SPD	Speed
SPEC	Special
SQ	Square
SS	Stainless Steel
SSH	Sliding Shelf
STA	Station
STAT	Immediate
STK	Stack
STL	Stool

STM	Steam
STND	Stand
STOR	Storage
SUC	Suction
SUR	Surface
SURG	Surgical
SUSP	Suspension
SWG	Swing, Swinging
TBL	Table
TBLWR	Tableware
TEMP	Temperature
TLC	Thin Layer Chromatography
TOMO	Tomography/Tomographic
TPL	Triple
TRANS	Transportable
TREAT	Treatment
TRK	Track
TST	Test
TV	Television
U/C	Undercounter
UL	Underwriters Laboratories, Inc
UNHTD	Unheated
UPHD	Upholstery/Upholstered
UPRIGHT	Upright
UT	Utility/Utilities
UV	Ultraviolet
V	Volts
VAC	Vacuum/Volts AC
VAR	Variable
VDRL	Venereal Disease Research Laboratory
VERT	Vertical
VIS/UV	Visible/Ultraviolet
VOL	Volume
W	Width/Watts/Wide
W/	With
WBC	White Blood Count
WCP	Watercolor Pen

W/H	Wall Hung
W/H CTR	Wall Hung or Counter Mounted
W/O	Without
W/P/H	Wall or Panel Hung
WRK	Work
WKI	Walk In
WKSUR	Work Surface
WLL	Wall
WRST CNTRL	Wrist Control
WSH	Writing Shelf

O	Degrees
X	Powers of magnification
YD	Yard

4. GENERAL REQUIREMENTS

- 4.1 Joint Schedule Numbers. The Joint Schedule Numbers appearing in this standard shall be used to identify equipment on all architectural drawings, plans, and supporting documents for Military/Federal medical construction projects. The JSNs may be used to identify equipment for construction and renovation planning not included in a military construction budget, but, in those instances, the "CAT" column indicating logistical responsibility may be disregarded.
- 4.2 Items not included. Funds for items not included in this standard shall be included in the appropriate operating or supply budget estimates.
- 4.3 Additions, deletions, or changes. Additions, deletions, changes, and corrections to this standard shall be made as directed by the 1691 committee. Items can be added to the database by any using service or agency. Deletions or changes can be made only with the full committee's concurrence. The DMFO will maintain and promulgate these changes through revisions of this standard.

5. DETAILED REQUIREMENTS

5.1 Special instructions.

- a. Where reference to a specification is included in a JSN item description, items identified as "A" in the "CAT" column of Appendices A through C shall be procured against the latest authorized specification or purchase description. Design agents and contractors (Architect and Engineers) shall assure that current specifications and their latest amendments or purchase description shall be used in the procurement of equipment supplied by the construction contractor.
- b. The using service/agency shall be required to furnish information and participate in review of shop drawings and inspections prior to acceptance of technical equipment. Inquiries shall be addressed to the appropriate authority.

- c. Quality and type of equipment and furniture, e.g., stainless steel, steel, wood, gas fired, or electric, shall be determined by the using service/agency in each instance, based on the intended life and mission of the facility and the location and circumstance under which construction is to be accomplished.
- d. When design and space limitations necessitate substitution of equipment in the preparation of drawings, these substitutions shall be coordinated with and approved by the using service/agency.

5.2 Logistical responsibility. The items listed in Table I shall be included in construction cost estimates as appropriate.

TABLE I. Item divisions and logistical responsibilities

ITEM	Logistical Responsibility						
	A	B	C	D	E	F	G
Building and Grounds - To include:							
Hospital buildings (including administration)	X						
Medical clinic buildings	X						
Dental clinic buildings	X						
Clinical and medical research laboratory buildings	X						
Animal holding buildings	X						
Maintenance shop buildings	X						
Garages and automotive shelters	X						
Power plant buildings (steam and/or electrical)-	X						
Sewage disposal plant structures	X						
Medical helicopter landing pads	X						
Chapel	X						
Recreational building (including Red Cross, gymnasiums and swimming pools)	X						
Recreational fields (including tennis courts, diamonds, etc.,)	X						
Guard and sentry boxes, gatehouses	X						
Incinerator buildings	X						
Electrical Service - To include:							
Wiring (including material)	X						
Conduits	X						
Switches, panels, boxes, service outlets-	X						
Transformers (stepdown and distribution)	X						
Lighting, fixtures (including initial lamping)	X						
Generating equipment (including emergency)	X						
Explosion-proof fixtures	X						
Power Conditioning/Surge Protectors	X						
Heating, Air Conditioning, and Ventilation To include:							
Air conditioning (including packaged units)	X						
Boiler plants and water heaters	X						
Heat and steam distribution systems	X						
Central vacuum cleaning system	X						

TABLE I. Item divisions and logistical responsibilities - Continued

Plumbing - To include:							
Piping valves, fittings, and outlets	X						
Toilet, bath, and lavatory fixtures (including shower stalls, mirrors, towel racks, toilet paper dispensers, paper towel dispensers, soap dispensers, and bedpan washers)	X						
Sewer systems and plants	X						
Gas, air pressure and suction, and medical gas systems	X						
Automatic sprinkler systems	X						
Fire protection system (water)	X						
Refrigeration - To include:							
Refrigeration (walk-in)	X						
Deep freeze (walk-in)	X						
Built-in morgue refrigerators	X						
Communications - To include							
Telephone system, including- Conduits, outlet boxes,	X						
Telephone exchange, Key equipment instruments, and all necessary equipment	X						
Intercom systems, complete Conduits	X						
Instruments and equipment	X						
Public address system (fixed)	X						
Conduits-	X						
Instruments and equipment	X						
Television System (excluding security)	X						
Entertainment							
Conduits	X						
Antennas	X						
TV Brackets, wall and/or ceiling mounted		X					
TV Low voltage power supply		X					
Training							
Conduits	X						
TV cameras, TV receivers			X				

TABLE I. Item divisions and logistical responsibilities - Continued

ITEM	Logistical responsibility						
	A	B	C	D	E	F	G
Communications – Television System, continued							
Patient Monitoring							
TV cameras, receivers, cables and conduits	X						
Program distribution system, complete							
Conduits and equipment	X						
Paging systems for staff complete			X				
Radio equipment other than paging and program distribution			X				
Conduits and cables	X						
Instruments, equipment, and accessories			X				
Nurses' call systems							
Conduits	X						
Instruments and equipment	X						
Central dictating system							
Conduits	X						
Instruments and equipment			X				
Pneumatic tube systems	X						
Automatic data processing systems							
Conduits	X						
Cables and distribution			X				
Instruments and equipment			X				
Intrusion Detection System							
Conduits	X						
Cable and fittings						X	
Sensors and equipment						X	
TV equipment						X	

TABLE I. Item divisions and logistical responsibilities - Continued

ITEM	Logistical responsibility						
	A	B	C	D	E	F	G
Interior Intrusion Detection System (Local)	X						
Clocks							
Elapsed Time Clocks	X						
Battery clocks			X				
Audio-Visual equipment other than systems listed above			X				
Energy Monitoring and Control systems	X						
Fire Protection Alarm System	X						

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Special considerations.

- a. Not all items listed in this standard necessarily apply to all construction projects. It is improbable that any project will include all items. Items appearing on project equipment schedules that are not listed in this standard shall be assigned a number with a suffix code indicating a provisional or interim schedule number and shall be coordinated with and approved by the using service. It is not mandatory that every item that applies to a specific project be listed in this standard.
- b. Expendable supplies, hand tools, and accessories have not been included in the standard.
- c. Unless otherwise specifically noted, dimensions indicated mean:
 - Height - Outside dimensions bottom to top or floor to top, not including sloping tops or counter tops.
 - Width - Outside dimensions end to end across front.
 - Depth - Outside dimensions from front to back.
- d. All dimensions are approximate since they vary from manufacturer to manufacturer. Dimensions stated are the composite worst case reviewed during the MIL-STD-1691 update process.

6.2 Legend of utilities.

UTILITIES	CODE	EXPLANATION
WATER AND DRAIN	A	HOT AND COLD WATER
	B	COLD WATER AND DRAIN
	C	HOT WATER AND DRAIN
	D	COLD AND HOT WATER AND DRAIN
	E	TREATED WATER AND DRAIN
	F	COLD, HOT AND TREATED WATER AND DRAIN
	G	COLD AND TREATED WATER AND DRAIN
	H	HOT AND TREATED WATER AND DRAIN
	I	DRAIN ONLY
	J	COLD WATER ONLY

6.2 Legend of utilities, continued.

UTILITIES	CODE	EXPLANATION
ELECTRICITY	A	120 VOLT, CONVENTIONAL OUTLET
	B	120 VOLT, SPECIAL OUTLET
	C	208/220 VOLT
	D	120 AND 208/220 VOLT
	E	440 3 PHASE
	F	SPECIAL ELECTRICAL REQUIREMENTS
	G	208/220 VOLT 3 PHASE
MEDICAL GASES	A	OXYGEN
	B	VACUUM
	C	AIR, LOW PRESSURE (30 PSIG) MAX
	D	AIR, HIGH PRESSURE (85 PSIG) MIN
	E	OXYGEN AND VACUUM
	F	OXYGEN AND MEDICAL AIR (50 PSIG)
	G	OXYGEN, VACUUM AND MEDICAL AIR (50 PSIG)
	H	VACUUM AND HP AIR (85 PSIG) MINIMUM
	K	MEDICAL AIR (50 PSIG)
	L	VACUUM AND LP AIR (30 PSIG) MAX
MISCELLANEOUS GASES	A	STEAM
	B	NITROGEN GAS
	C	NITROUS OXIDE GAS
	D	NITROGEN AND NITROUS OXIDE GAS
	E	CARBON DIOXIDE GAS
	F	LIQUID CARBON DIOXIDE
	G	LIQUID NITROGEN
NON-MEDICAL GASES	A	NATURAL GAS
	B	LIQUID PROPANE GAS
	C	METHANE
	D	BUTANE
	E	PROPANE
	F	HYDROGEN GAS
	G	(Reserved)
	H	ACETYLENE GAS

6.2 Legend of utilities, continued

UTILITIES	CODE	EXPLANATION
MISCELLANEOUS	A	EARTH GROUND
	B	LEAD LINED WALLS
	C	REMOTE ALARM GROUND
	D	EMPTY CONDUIT WITH PULL CORD
	E	VENT TO ATMOSPHERE
	F	SPECIAL GAS REQUIREMENTS
	G	LIQUID GAS REQUIREMENTS
	H	RF/MAGNETIC SHIELDING
	J	WALL/CEILING SUPPORT REQUIRED
	K	EMPTY CONDUIT/PULLCORD & WALL/CEILING SUPPORT
	M	REQ
P	EARTH GROUND AND WALL/CEILING SUPPORT REQ	
		LEAD LINED WALLS AND WALL/CEILING SUPPORT REQ

6.3 Subject term (key word) listing.

- Hospitals
- Joint Schedule Numbers

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

This page intentionally left blank.

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
A0900		Relay Rack, Aluminum		C	C	C	.	--		--	--	--	--	--	--
Rack used to hold network components such as servers, switches, hubs, patch panels, router, etc. Racks are available in varying heights, channel depths, and channel width. The model numbers specified may be U.L. Listed version with 2 Top Angles, 7' height, 19" wide, blank Aluminum, with mounting holes on both sides (front and back) [Price difference verified.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	84	21	15	32 lb	1:	--	--	0	NO	--				
		213	53	38	15 kg	2:	--	--	NO	NO	--				
A0901		Cable Management, Horizontal Base Unit		C	C	C	.	--		--	--	--	--	--	
Horizontal cable management unit for a 19" rack with a channel approximately 2"x2". Provides for professional finish to hide cables in a switch rack. Various models are quoted with fingered type exits or brackets and/or rear access holes. [No other source(s) identifies with this description/specification.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	--	--	--	-- lb	1:	--	--	0	NO	--				
		--	--	--	-- kg	2:	--	--	NO	NO	--				
A0902		Rear Wire Frame		C	C	C	.	--		--	--	--	--	--	
For use with horizontal base unit for double sided management. This item is intended to be used with JSNs A0901 and/or A0903 model HC219 series from Hubbell only. [This item is a component of a Server/Networking system. No other source(s) identified with this description/specification]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	5	19	5	-- lb	1:	--	--	0	NO	--				
		13	48	13	-- kg	2:	--	--	NO	NO	--				
A0903		Rear Hinged Cover, for LAN Rack		C	C	C	.	--		--	--	--	--	--	
Use with the "rear frame" (JSN M1882). This item is intended to be used with JSNs A0901 and/or A0902 model HC219 series from Hubbell only [This item is a component of a Server/Networking system. No other source(s) identified with this description/specification]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	--	--	--	-- lb	1:	--	--	0	NO	--				
		--	--	--	-- kg	2:	--	--	NO	NO	--				
A0904		Fiber Optic Cabinet, 36 Port, Rack Mounted		C	C	C	.	--		--	--	--	--	--	
This cabinet is designed to accommodate up to 6 six-packs of adapters or blank panels. This cabinet is specifically designed to accommodate Hubbell adapter panels as reflected in JSNs A0905 and A0906. [This item is a component of a Server/Networking system. No other source(s) identified with this description/specification.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	4	17	12	11 lb	1:	--	--	0	NO	--				
		9	43	30	5 kg	2:	--	--	NO	NO	--				
A0905		Adapter Panel With Couplers, Blue, 6 Port, SM/MM		C	C	C	.	--		--	--	--	--	--	
Modular six-pack fiber adapter panel, designed to snap into Hubbell's enclosures such as JSN A0904. Loaded with 3 SM/MM SC duplex style blue adapters, standard density. [This item is a component of a Server/Networking system. No other source(s) identified with this description/specification]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	--	--	--	-- lb	1:	--	--	0	NO	--				
		--	--	--	-- kg	2:	--	--	NO	NO	--				
A0906		Adapter Panel With Couplers, Yellow, 6 Port, SM/MM		C	C	C	.	--		--	--	--	--	--	
Modular six-pack fiber adapter panel, designed to snap into Hubbell's enclosures such as JSN A0904. Loaded with 3 SM/MM SC duplex style Yellow adapters, standard density. [This item is a component of a Server/Networking system. No other source(s) identified with this description/specification]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	--	--	--	-- lb	1:	--	--	0	NO	--				
		--	--	--	-- kg	2:	--	--	NO	NO	--				

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A0907	5999	Patch Panel, Copper, UTP	C	C	C	.	--	--	--	--	--	--	--	--	--	--	--	--
This item is a patch panel, a component of a Computer Server/Networking Equipment Rack. The exact description and specification is directly dependent on the manufacturer and specific equipment rack used at the facility. [This JSN is maintained as an equipment/component place holder. Physical characteristics and utility data can not be determined until the end item is identified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO							
		CM:	--	--	--	-- kg	2:	--	--	DEPENDENT:	NO							
A0908		Patch Panel, 110 Block/RJ-45, Cat 5E, 48 Port,568A	C	C	C	.	--	--	--	--	--	--	--	--	--	--	--	--
This 48 Port/RJ45, Cat 5e (or better) patch panel is designed for the following applications. Gigabit 1000BASE-T, 100BASE-TX, ATM 155, TP-PMD (CDDI). [This item is a component of a Server/Networking system.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	4	19	5	-- lb	1:	--	--	0	NO							
		CM:	9	48	13	-- kg	2:	--	--	DEPENDENT:	NO							
A0909		Patch Panel, 110 Block/RJ-45, Cat 5E, 64 Port,568A	C	C	C	.	--	--	--	--	--	--	--	--	--	--	--	--
This 64 Port/RJ45, Cat 5e (or better) patch panel is designed for the following applications. Gigabit 1000BASE-T, 100BASE-TX, ATM 155, TP-PMD (CDDI). [Note: Leviton part number has changed to 5G584-U__ (number of ports 12-16-24-32-48-64-96) This item is a component of a Server/Networking system. No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	7	19	5	-- lb	1:	--	--	0	NO							
		CM:	18	48	13	-- kg	2:	--	--	DEPENDENT:	NO							
A0910		Patch Panel, 110 Block/RJ-45, Cat 5E, 96 Port,568A	C	C	C	.	--	--	--	--	--	--	--	--	--	--	--	--
This 96 Port/RJ45, Cat 5e (or better) patch panel is designed for the following applications. Gigabit 1000BASE-T, 100BASE-TX, ATM 155, TP-PMD (CDDI). [Note: Leviton part number has changed to 5G584-U__ (number of ports 12-16-24-32-48-64-96) This item is a component of a Server/Networking system.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO							
		CM:	--	--	--	-- kg	2:	--	--	DEPENDENT:	NO							
A0911		Power Supply, Uninterruptable, Rack Mounted	C	C	C	.	--	--	--	B	--	--	--	--	--	--	--	--
Uninterruptable Power Supply, Approximately 2200VA/1600W, Rack Mount with extendable Run Time. Unit must incorporate hot user swappable batteries and must have an overload indicator, replace battery indicator, audible alarm, automatic voltage regulation and include Smart Slot card and software. It must use RS232 DB-9 interface for communication. NEMA L5-30P power connector, and (8) NEMA 5-15R outlets. [This item is a component of a Server/Networking system to be used in conjunction with JSN A0912. No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	9	19	18	124 lb	1:	120	1	60	NO							
		CM:	23	48	46	57 kg	2:	--	--	DEPENDENT:	NO							
A0912		Battery Pack, Extended for use with UPS (A0911)	C	C	C	.	--	--	--	--	--	--	--	--	--	--	--	--
Battery Pack for use with JSN A0911 to extend backup power availability. Battery rated at approximately 1600 VA. Includes connector Part # SU031 for direct connect to SU2200XL series UPS. [This item is a component of a Server/Networking system to be used with JSN A0911. No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	7	19	18	136 lb	1:	--	--	0	NO							
		CM:	18	48	46	62 kg	2:	--	--	DEPENDENT:	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A0913		Switch, Local Area Network (LAN)	C	C	C	.	--	--	A	--	--	--	--	--	--	--	--	--
Omni switch router, 9 slot chassis, 725W AC power supply and rack mount brackets. Supports high speed frame switching fabric. Software and Manual included. Requires management module JSN A0914 and works with Power Supply A0915. [This item is a component of a Server/Networking system. Voltage range on Model 1 is 90-265 VAC. For Models 2 and 3 the voltage range is 100-240 VAC.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	25	18	19	154 lb	1:	125	1	6	60							
		CM:	64	46	48	70 kg	2:	--	--	--	NO							
									DEPENDENT:	NO								
A0914		Management Processor Module for LAN Switch	C	C	C	.	--	--	A	--	--	--	--	--	--	--	--	--
Management processor module with 10BaseT with layer-3 switching (HRE-X); 32 MB DRAM & 8 MB flash memory. Operates over the 22G distributed switching fabric. Works with Switch LAN JSN A0913 and Power Supply A0915 [This item is a component of a Server/Networking system. No other source(s) identified with this description/specification. Item Identified from 3Com is with corresponding components JSNs A0913 and A0915]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	--	--	--	-- lb	1:	--	--	--	0							
		CM:	--	--	--	-- kg	2:	--	--	--	NO							
									DEPENDENT:	NO								
A0915		Power Supply, 725 W, for LAN Switch	C	C	C	.	--	--	A	--	--	--	--	--	--	--	--	--
725 Watt powersupply, Redundant or spare power supply for the 9 slot Omni Switch Router. Works with Switch LAN JSN A0913 and Management Processor A0914 [This item is a component of a Server/Networking system. No other source(s) identified with this description/specification. Item Identified from 3Com is 930W and operates with corresponding components JSNs A0913 and A0914]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	--	--	--	-- lb	1:	--	--	--	0							
		CM:	--	--	--	-- kg	2:	--	--	--	NO							
									DEPENDENT:	NO								
A0916		Switching Module, Desktop, Fast Ethernet	C	C	C	.	--	--	--	--	--	--	--	--	--	--	--	--
High Density Fast Ethernet desktop switching module. Thirty-two 10/100Base TX switching ports, RJ-45 connectors. Supports Cat 5 twisted pair cable-100 ohm and CAM support for 1024 MAC addresses. [This item is a component of a Server/Networking system. Model 2 has 50 ports and Model 3 has 50 ports.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	2	18	16	14 lb	1:	--	--	--	0							
		CM:	5	46	41	7 kg	2:	--	--	--	NO							
									DEPENDENT:	NO								
A0917		Switching Module, MM Fiber,Gigabit Ethernet Server	C	C	C	.	--	--	--	--	--	--	--	--	--	--	--	--
Gigabit Ethernet server switching module. Four 1000 base SX switching ports, SC connectors. Supports multi-mode fiber optic cable and CAM support for 4096 MAC addresses. Must be used in the Omni Switch/Router product only. [This item is a component of a Server/Networking system. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	--	--	--	-- lb	1:	--	--	--	0							
		CM:	--	--	--	-- kg	2:	--	--	--	NO							
									DEPENDENT:	NO								
A0918		Switching Module, SM, Gigabit Ethernet Server	C	C	C	.	--	--	--	--	--	--	--	--	--	--	--	--
Gigabit Ethernet server switching module. Four 1000 Base LX switching ports, SC connectors. Supports single mode fiber optic cable and CAM support for 4096 MAC addresses. Must be used in the Omni Switch/Router product only. [This item is a component of a Server/Networking system. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	--	--	--	-- lb	1:	--	--	--	0							
		CM:	--	--	--	-- kg	2:	--	--	--	NO							
									DEPENDENT:	NO								

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES								
				R	A	F	A	H		1	2	3	4	5	6			
A1000	5805	Extinguisher, Fire	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
10 pound dry chemical fire extinguisher with charging gauge. Other types and sizes are available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	21	6	6	18 lb	1:	--	--	0	NO	--						
		CM:	53	15	15	9 kg	2:	--	--	NO	--	--						
A1010	5805	Telecommunication Outlet	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Telecommunication outlet location. [This JSN shows the location of a network outlet. The outlet is purchased as part of the overall information management system.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO	--						
		CM:	--	--	--	-- kg	2:	--	--	NO	--	--						
A1011	5805	Telephone, Desk, 1 Line	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Telephone, desk, 1 line. [This JSN is a place holder to indicate the placement of an instrument provided by a contractor as part of a total telephone system.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO	--						
		CM:	--	--	--	-- kg	2:	--	--	NO	--	--						
A1012	5805	Telephone, Wall Mounted, 1 Line	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Telephone, wall mounted, 1 line. [This JSN indicates the placement of an instrument provided by a contractor as part of a total telephone system package.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO	--						
		CM:	--	--	--	-- kg	2:	--	--	NO	--	--						
A1013	5805	Telephone, Wall Mounted, Multiple Line	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Telephone, wall mounted, multiple line. [This JSN indicates the placement of an instrument provided by a contractor as part of a total telephone system package.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO	--						
		CM:	--	--	--	-- kg	2:	--	--	NO	--	--						
A1014	5805	Telephone, Wall Mounted, 1 Line, With Speaker	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Telephone, wall mounted, 1 line, with speaker. [This JSN indicates the placement of an instrument provided by a contractor as part of a total telephone system package.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO	--						
		CM:	--	--	--	-- kg	2:	--	--	NO	--	--						
A1015	5805	Telephone, Desk, Multiple Line	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Telephone, desk, multiple line. [This JSN indicates the placement of an instrument provided by a contractor as part of a total telephone system package.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO	--						
		CM:	--	--	--	-- kg	2:	--	--	NO	--	--						
A1016	5805	Telephone, Desk, With Speaker	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Telephone, desk, with speaker. [This JSN indicates the placement of an instrument provided by a contractor as part of a total telephone system package.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO	--						
		CM:	--	--	--	-- kg	2:	--	--	NO	--	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A1017	5805	Telephone, Wall Mounted, Multi-Line, With Speaker	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Telephone, wall mounted, multi-line with speaker. [This JSN indicates the placement of an instrument provided by a contractor as part of a total telephone system package.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	--	--	--	-- kg	2:	--	--	--	DEPENDENT:	NO						
A1018	5805	Telephone, Wall Mounted, Waterproof	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Telephone, wall mounted, waterproof. [This JSN is maintained as an architectural placeholder and is intended to indicate the location(s) of the unit(s). The telephone is a component part of a total telephone system.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	--	--	--	-- kg	2:	--	--	--	DEPENDENT:	NO						
A1019	5805	Telephone, Wall Mounted, Multi-Line, Cordless	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall mounted, multi-line telephone with speaker including a cordless handset for use in operating room environments. Wall mounted base unit should be waterproof to permit easy decontamination. [This JSN indicates the placement of an instrument provided by a contractor as part of a total telephone system package.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	--	--	--	-- kg	2:	--	--	--	DEPENDENT:	NO						
A1030	7125	Locker, 2 Person, Over/Under	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available. [The dimensions have been removed from the Nomenclature and placed in the Description. The Description has also been changed to reflect the correct Locker width and depth. The "coat rod and hat shelf" were removed from the description as they are not normally found in over/under lockers. These are usually found in single personal lockers.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	BTUs / HR:							
EA		IN:	72	12	18	63 lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	183	30	46	29 kg	2:	--	--	--	DEPENDENT:	NO						
A1032	7125	Locker, Box, Personal Effects	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Personal effects locker box. Provides 6, one cubic foot spaces per locker with individually lockable doors. For use in staff lounges and patient areas where temporary storage of valuables and personal effects is required. Each box within the locker will be provided with a key lock that retains the key when open. [Nomenclature and Description have been corrected.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	BTUs / HR:							
EA		IN:	72	12	12	60 lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	183	30	30	27 kg	2:	--	--	--	DEPENDENT:	NO						
A1035	7125	Locker, Single Tier, 72x12x18	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Locker. Unit with coat hooks, hanger rod, and ventilating louvers. Door latch permits the use of a padlock. For storage of personal belongings.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	BTUs / HR:							
EA		IN:	72	12	18	68 lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	183	30	46	31 kg	2:	--	--	--	DEPENDENT:	NO						
A1040	7125	Locker, 2 Person, Side by Side, 72x15x18	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Two person side by side locker. Steel unit. It consists of side by side compartments for hanging clothes and over/under compartments for hats, etc. Used for personal belongings storage.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	BTUs / HR:							
EA		IN:	72	15	18	82 lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	183	38	46	38 kg	2:	--	--	--	DEPENDENT:	NO						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
A1055	7110	Mailbox, Horizontal, Rear Loading	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Horizontal, rear loading mail box. Consists of aluminum compartment doors with single dial reset-table combination lock, and zinc plated steel compartments. Used for mail distribution. Unit consists of 60 doors, (door sizes either 12" high and 5" wide or 12" wide and 5" high.) Size as required.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	42	34	16	180 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	107	86	41	82 kg	2:	--	--	--									
A1066	7105	Mirror, Float Glass, With SS Frame	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	36	18	1	22 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	91	46	3	10 kg	2:	--	--	--									
A1070	7105	Mirror, Float Glass, With SS Frame, 36 x Required	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A high quality 1/4" polished float glass mirror, framed in a one-piece, satin finished, stainless steel angle frame. All edges of the mirror are protected by absorbing filler strips. Back of mirror is protected by a protective coating. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hangers for concealed mounting. For use in restroom areas having a vanity with two or more countertop mounted lavatories. Pricing is based upon a 36" H X 36" W mirror. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
LF		IN:	36	36	1	20 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	91	91	1	9 kg	2:	--	--	--									
A1080	6530	Mirror, Posture, Wall Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	72	28	4	60 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	183	71	10	27 kg	2:	--	--	--									
A1085	6530	Mirror, SS, With SS Frame, 36x18	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A highly polished, stretcher leveled, stainless steel mirror, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For use in areas of a facility where a float glass mirror is not desired for reasons of patient and staff safety. This mirror is not intended for use in a maximum-security patient area. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	36	18	1	19 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	91	41	1	9 kg	2:	--	--	--									
A1090	6530	Mirror, Float Glass, With SS Frame & Shelf	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A high quality 1/4" polished float glass mirror, approximately 36" H X 18" W framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners and an integral stainless steel, stain finish, shelf. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in restroom areas, Doctor examination areas, offices, etc. May also be used above double lavatories, either wall or countertop mounted. [Other sizes are available.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	36	18	6	28 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	91	46	15	13 kg	2:	--	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A1095	9905	Message Board, Digital	C	C	C	C	--	--	A	--	--	--	--	D				
<p>Digital message display board. Electronic 80 character display with data memory enclosed in an aluminum frame. For use in areas like the pharmacy waiting room. [Several additional companies make customized electronic signs. These companies will not provide pricing without detailed specifications. The following is a partial list of custom manufacturers: American Signal, Chadmark, WUGS and Selectricsigns. No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN: 47	33	5	90 lb	1: 120	1	2	60		YES		--					
		CM: 119	84	13	41 kg	2: --	--	--	60		NO		--					
A1100	6530	Column, Service, Prefabricated, ICU	A	A	A	A	--	--	F	G	--	--	--	--				
<p>ICU prefabricated service column. Floor to ceiling freestanding column with medical gas outlets, lighting, electrical outlets, nurse call, vacuum regulators and bottle storage, monitor shelf, sphygmomanometer, and lapsed time indicator. To be used in ICU units. [Amperage and the resultant wattage will vary with number of electrical outlets selected.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN: 115	22	9	600 lb	1: 120	1	5	60		NO		--					
		CM: 292	56	23	273 kg	2: --	--	--	60		NO		--					
A1105	6530	Headwall, Prefabricated, ICU, With Equipment	A	A	A	A	--	--	F	G	--	--	A					
<p>ICU prefabricated headwall with equipment. Multi-wall surface mounted unit. Consists of: patient medical gases, and electrical module; and patient cabinet module. Includes examination lamp, elapsed time recorder, wall mounted sphygmomanometer, ceiling mounted intravenous arm assembly; Electro/safe hazard cardiac monitor shelf; vacuum bottle storage unit, medical gas/vacuum outlet and external grounding receptacles. [Prices may vary dependent on selected type and quantity of electrical and gas fixtures. Amperage and the resultant wattage will vary with number of electrical outlets selected.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN: 107	122	8	600 lb	1: 120	1	15	60		NO		--					
		CM: 272	310	20	273 kg	2: --	--	--	60		NO		--					
A1106	6530	Medical Gas Outlet Location - In OR Wall	A	A	A	A	--	--	F	G	--	--	A					
<p>Medical gas outlet location, installed within the finished wall, as defined by the architect. Operating room configuration. [Data sheets are provided to indicate application of modules and services.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
LT		IN: --	--	--	-- lb	1: --	--	--	0		NO		--					
		CM: --	--	--	-- kg	2: --	--	--	0		NO		--					
A1107	6530	Rail System , Utility, Gas and Electric	A	A	A	A	--	--	F	G	--	--	A					
<p>The headwall rail system shall consist of three horizontal rails mounted to the patient room headwall to provide utilities and patient services to support ancillary equipment to include gas and vacuum. The rail system must be capable of quickly adding or relocating medical gases services and be able to accept new equipment, provide physical support to equipment, brackets, shelves and other patient support items. [Pricing is based on a typical medical/ surgical single room, three rail system.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN: 96	120	10	-- lb	1: --	--	--	0		NO		--					
		CM: 244	305	25	-- kg	2: --	--	--	0		NO		--					
A1110	6530	Headwall, Prefabricated, General, 1-2 bed	A	A	A	A	--	--	F	G	--	--	--					
<p>1-2 bed, general, prefabricated headwall. Unit consists of a patient service module for general care, single or double bed type. It contains lighting, medical gases, electrical outlets, nurse call and bed bumper. Specify number and type of medical gas and electrical outlets. Size of module will vary by type and configuration of outlets. [Database dimensions and price are based on single bed configuration.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN: 96	94	8	215 lb	1: 120	1	15	60		NO		--					
		CM: 244	239	20	98 kg	2: --	--	--	60		NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A1115	6520	Console, Service, Infant, Prefabricated	A	A	A	A	--	--	F	G	--	--	A					
<p>Infant prefabricated service console. It consists of a cabinet service module. It contains all medical gases and electrical services for individual treatment. Specify number of electrical outlets and type of console (single or double). Size to be determined by nursery layout. For use in the neonatal ICU. [Prices will be sensitive to the options selected.</p> <p>No other source(s) identified with this description/specification.</p> <p>Hill Rom's (Cage Code 28713) model "Horizon 1001" is now obsolete. They do not offer any kind of replacement at this time.</p> <p>Electrical Requirements dependent on configuration.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	76	91	31	--	1b	1:	120	1	20	60	NO	--				
		CM:	193	231	79	--	kg	2:	--	--	--	DEPENDENT:	YES		--			
A1120	6530	Column, Service, Prefab, Surgical, Ceiling Mounted	A	A	A	A	--	--	F	G	D	--	--					
<p>Prefabricated surgical service column. Strong 18 gauge stainless steel shell ceiling mounted unit with the following services: oxygen, nitrous oxide, nitrogen, medical air, medical vacuum, gas evacuation, electrical outlets, monitoring connectors, and IV holders. Specify type of column (fixed or retractable) and number of outlets required for each service. Size will vary with number of service outlets required. Designed to be used in the operating room, recovery and ICU-CCU rooms. [Allied Health Care Products (Cage Code #11978), charges an additional \$200.00 per gas outlet added and \$100.00 per electrical outlet added to their service column.</p> <p>Price difference verified.</p> <p>No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	54	--	--	321	lb	1:	120	1	20	60	NO	--				
		CM:	137	--	--	146	kg	2:	--	--	--	DEPENDENT:	NO		--			
A1130	6530	Cabinet, Control, Nitrogen	A	A	A	A	--	--	B	--	--	--	--					
<p>Nitrogen control cabinet. Unit consists of supply cut-off valve, supply pressure gauge, pressure regulator (adjustable 0 to 200 PSI), outlet pressure gauge, nitrogen outlet and connection to surgical gas column. Specify recessed or surface mounting. Designed for powering surgical pneumatic tools. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	9	14	4	--	lb	1:	--	--	--	--	NO	--				
		CM:	23	36	10	--	kg	2:	--	--	--	DEPENDENT:	NO		--			
A1132	6530	Rail, Accessory Mounting, Length As Required	C	C	C	C	--	--	--	--	--	--	--					
<p>Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismounting of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismounting equipment without leaving or creating new holes in the finished surface of the wall. [Price will vary depending on the length , configurations and options added to the rail system. The weight capacity of the system is dependent on the wall structure, the method of attachment to the wall and the configuration of the item to be attached to the bracket.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
LF		IN:	2	24	2	1	lb	1:	--	--	--	--	NO	--				
		CM:	5	61	5	1	kg	2:	--	--	--	DEPENDENT:	NO		--			
A1145	7100	Shelving, Storage, Movable Aisle, Manual	C	C	C	C	--	--	--	--	--	--	--					
<p>Movable aisle, storage shelving unit. Unit is a manually operated, mobile aisle, high density, filing system. Total system includes tracks installed on carpet or floor, shelving carriage, and deck. Load capacity is 1000 pounds per linear foot. Designed for storage and filing of records. Starter unit consists of one end unit and one modular unit. Size as required with additional modular units. All units should be custom designed based on the available space and filing needs. System to be ADA (American's With Disability Act) compliant. [Pricing has been changed to reflect \$2.00 to \$2.50 per linear filing inch. This is the manner that manufacturers use to determine the cost of a system.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	--	--	--	--	lb	1:	--	--	--	--	NO	--				
		CM:	--	--	--	--	kg	2:	--	--	--	DEPENDENT:	NO		--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
A1150	7100	Shelving, File, Open, Patient Records	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Patient records open file shelving. Freestanding metal unit with 6 adjustable shelves, backstops, and dividers. Shelving assembly allows adding on of additional shelf units. For clinical and outpatient treatment records.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
			76	36	18	99 lb	1:	--	--	--	NO	--							
			193	91	46	45 kg	2:	--	--	--	NO	--							
A1155	7100	Shelving, Storage, Movable Aisle, Powered	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Movable aisle, powered, storage shelving system. Unit consists of 18-20 gauge steel shelving modular units with adjustable shelves, carriage, tracks, and is electrically powered. Each motor equipped with thermal overload protection. For storage applications with open access and high activity. Starter unit consists of one end unit and one modular unit. Size as required. These systems are custom designed to meet the individual requirements of each facility or application. System to be ADA (American's With Disability Act) compliant. [Pricing is based on a dollar amount per linear filing inch. This is the manner that manufacturers use to determine a cost estimate for a system considering the variables involved.]																			
UNIT OF ISSUE:		IN	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
			--	--	--	-- lb	1:	120	1	20	NO	--							
			--	--	--	-- kg	2:	--	--	--	NO	--							
A1160	6530	Track, IV, Oval, Ceiling Mounted, 4' x 7'	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Ceiling mounted, oval IV track. Fabricated with thick anodized aluminum. It includes a corrosion resistant trolley with self locking hinge, and a stainless steel spiral hook for attaching a bottle hanger. Designed for dispensing of IV solutions.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
			1	2	84	-- lb	1:	--	--	--	NO	--							
			3	5	213	-- kg	2:	--	--	--	NO	--							
A1165	6530	Track, IV, Ceiling Mounted, 7 Foot	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
7 ft. ceiling mounted IV track. Unit consists of a straight thick anodized aluminum track. It includes a carrier with self locking hinge, hook for attaching bottle hanger, and an adjustable pendant. Designed for dispensing IV solutions. [Price difference verified.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
			1	2	84	3 lb	1:	--	--	--	NO	--							
			3	5	213	2 kg	2:	--	--	--	NO	--							
A1170	6530	Track, IV, Ceiling Mounted, 4 Foot	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
4 ft. ceiling mounted IV track. Unit consists of an anodized aluminum track. Equipped with a carrier, with self locking hinge, hook and bottle pendant. Designed for dispensing IV solutions. [Price difference verified.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
			1	2	48	6 lb	1:	--	--	--	NO	--							
			3	5	122	3 kg	2:	--	--	--	NO	--							
A1175	7110	Vault, With Day Gate, Built In	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Built-in vault with day gate. Size as required. Consists of a fire resistant vault with a steel back-plate door that has a 2 hour fire rating. Equipped with locking mechanisms and full height locking bars, emergency ventilator, and alarm system. Designed for storage of cash, sensitive items, and important documents. Price dependent on size. [Price indicated is for the door and day gate only. Total cost for the vault is contingent on design and specifications determined by the architect. Model 1 NSN is 7110-00-935-1886 with Day Gate.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
			86	55	12	1,550 lb	1:	--	--	--	NO	--							
			218	140	30	704 kg	2:	--	--	--	NO	--							
A1180	6530	Scale, Roll On, Built In, 2000 Pound Capacity	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Built-in roll on scale with a 2000 pound capacity. Unit consists of a flush scale, floor mounted, and wall mounted display. The platform can be left exposed or covered with carpet. For use in food service or the laundry.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
			48	48	3	210 lb	1:	120	1	1	NO	--							
			122	122	8	96 kg	2:	--	--	--	NO	--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
A1195	6530	Counter, Cleanup, With 2 or 3 Sinks	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--		
Two or three sink cleanup counter. Unit is constructed of type 304 corrosion resistant stainless steel. It consists of three sinks 14"W X 16"H X 10"D, hot and cold water faucet, and pre-rinse spray hose. Equipped with channel reinforced drainboards, and backsplash, and supported by tubular stainless steel legs. Unit is designed for use in control sterile supply decontamination areas.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:							
EA		IN:	36	30	96	--	lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	91	76	244	--	kg	2:	--	--	--									
A4005	5830	Public Address System	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--		
Public address system. System features built-in speaker-microphone for hands-free operation, volume controls, battery backup for power failures, master clock programmer, group all call, and alert tone for emergency situations. Communications distribution system designed for facilities. [This JSN is maintained as an architectural placeholder. This type of system is uniquely configured to each individual facility and will generally consist of multiple components from various manufacturers. Pricing and model numbers can not be reasonably determined without defining the facility size and specified requirements of the system. Note: The "with tape input" was deleted from the Nomenclature and Description. Tape input is outdated as systems are now digital.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:							
EA		IN:	--	--	--	--	lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	--	--	--	--	kg	2:	--	--	--									
A4015	6645	Clock, Elapsed Time, Electric	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	D		
Elapsed time digital electric clock. Single display time that can be used either as a clock or elapsed time indicator. Clock consists of buttons to set minutes, and hours for the time. For use in operating and delivery room, and medical service columns. Analog or digital displays may be provided as specified by the user. [CAGE #1 (25415) , Gomco Division, Allied Healthcare Products, Incorporated, confirmed as a manufacturer/supplier for this item. Literature not available to verify model numbers or obtain price.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:							
EA		IN:	12	12	3	2	lb	1:	120	1	1	DEPENDENT:	YES	--						
		CM:	30	30	8	1	kg	2:	--	--	--									
A4995	7100	Table, Diaper Changing, Wall Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--		
Wall mounted diaper changing table for use in public restrooms. Unit is a fold down system that folds upward when not in use for minimal intrusion into the room. Changing surface is contoured and has safety belt to insure that an infant will not fall from the table. Table is designed to hold no less than 250 pounds static weight. Closed dimensions are approximately 21" H x 36" W x 5" D. Open dimensions vary according to style. One system's open dimensions are 15" high, 32" wide and 19" deep. [Dimensions are for the unit in a closed position mounted to a wall. For Model 3 must specify horizontal or vertical mounting. All models include liners.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:							
EA		IN:	21	36	5	26	lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	53	91	13	12	kg	2:	--	--	--									
A5020	7105	Bench, Locker Room, Floor Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--		
Locker room bench. Floor mounting -1-1/4" thick. Benches are sanded smooth with two coats of moisture-resistant sealer to ensure a protective, satin gloss surface, and mounted on strong steel pedestal anchored to the floor. Over all height of 18" includes pedestal. Size as required.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:							
EA		IN:	18	108	10	--	lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	46	274	25	--	kg	2:	--	--	--									
A5025	7105	Bench, Locker Room, Portable	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Portable locker room bench. Approximately 1-1/2" thick. Benches shall be laminated hardwood with a moisture resistant sealer or anodized aluminum Units are mounted on strong pedestals.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:							
EA		IN:	17	108	13	52	lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	43	274	33	24	kg	2:	--	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A5030	4510	Bench, Stall, Shower, Built In	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Shower bench; built-in. Eighteen (18) gauge stainless steel frame with anchors built-in into the wall. Size and shape as required.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:						
EA		IN:	11	35	22	20 lb	1:	--	--	--	NO	--						
		CM:	28	89	56	9 kg	2:	--	--	--	NO	--						
A5047	7110	Cabinet, Medicine	A	A	A	.	--	--	--	--	--	--	--	--	--	--	--	--
Medicine cabinet mounted in wall with a mirror front. Approximate size 15" W x 25" H x 3.5" D.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:						
EA		IN:	31	18	5	25 lb	1:	--	--	--	NO	--						
		CM:	79	46	13	12 kg	2:	--	--	--	NO	--						
A5065	7110	Cabinet, Narcotic, U/C or Ctr, With Safe, 24x24x12	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Under-counter narcotic cabinet with safe. Unit is a class 5 security cabinet with combination dial lock. Used for the storage of funds, narcotics, weapons, plans, etc.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:						
EA		IN:	32	25	25	1,150 lb	1:	--	--	--	NO	--						
		CM:	81	64	64	522 kg	2:	--	--	--	NO	--						
A5070	4510	Dispenser, Liquid Soap, SS, Surface Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
A surface mounted, satin finish stainless steel, top filling, liquid soap dispenser. Dispenser features: corrosion-resistant valve, push-in type and operable with one hand; heavy duty hinge and key lock lid; and vandal resistant concealed mounting. Minimum capacity 40 fluid ounces. For general purpose use throughout the facility. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:						
EA		IN:	8	7	6	2 lb	1:	--	--	--	NO	--						
		CM:	20	18	15	1 kg	2:	--	--	--	NO	--						
A5075	4510	Dispenser, Soap, Disposable	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve. [Based on infection control standards only soap dispensers refilled by means of a cartridge or replaceable bag are to be used.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:						
EA		IN:	11	5	4	3 lb	1:	--	--	--	NO	--						
		CM:	28	13	10	2 kg	2:	--	--	--	NO	--						
A5080	4510	Dispenser, Paper Towel, SS, Surface Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:						
EA		IN:	8	12	6	4 lb	1:	--	--	--	NO	--						
		CM:	20	30	15	2 kg	2:	--	--	--	NO	--						
A5085	4510	Dispenser, Paper Cup, SS, Surface Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
A surface mounted, satin finished stainless steel, 3 to 6-ounce paper or plastic flat-bottom cup dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 150 3-ounce cups. For general purpose use throughout the facility. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:						
EA		IN:	15	3	3	2 lb	1:	--	--	--	NO	--						
		CM:	38	8	8	1 kg	2:	--	--	--	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A5090	7240	Disposal, Sanitary Napkin, SS, Surface Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			CM:	12	8	5	3 lb	1:	--	--	--							
				30	20	13	2 kg	2:	--	--	--							
A5106	6530	Waste Disposal Unit, Sharps w/Glove Dispenser	C	A	C	C	--	--	--	--	--	--	--	--	--	--	--	--
The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			CM:	25	13	5	5 lb	1:	--	--	--							
				64	33	13	3 kg	2:	--	--	--							
A5107	4510	Dispenser, Glove, Surgical/Examination, Wall Mntd	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			CM:	6	11	4	2 lb	1:	--	--	--							
				15	28	10	1 kg	2:	--	--	--							
A5108	6530	Waste Disposal Unit, Sharps	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps. [Database price is for an 8 gallon container / 10 per case.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			CM:	18	17	11	2 lb	1:	--	--	--							
				46	43	28	1 kg	2:	--	--	--							
A5109	6530	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met. [These manufacturers provide numerous configurations of these grab bars.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			CM:	3	57	3	7 lb	1:	--	--	--							
				8	145	8	4 kg	2:	--	--	--							
A5110	6530	Grab Bar, 1-1/4" Dia., SS, 2 Wall, Shower Use	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall shower, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical applications in shower stalls where ADA (American's With Disabilities Act) requirements must be met. [These manufacturers provide numerous configurations of these grab bars.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			CM:	3	30	3	3 lb	1:	--	--	--							
				8	76	8	2 kg	2:	--	--	--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
A5120	6530	Window, Observation, One Way	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
One way observation window. Window frame mounted inside wall opening on an aluminum frame. Size as required. For use in pediatrics, occupational therapy and psychiatry. Typical size is 36" x 36". [This is a place holder as it would typically be provided by construction contractor/window contractor. Architecture note: Price will vary with the size of the window, which will be determined during design.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	--	--	--	--	--	--	1:	--	--	--	--						
		CM:	--	--	--	--	--	--	2:	--	--	--	--						
					-- lb								--						
					-- kg								--						
A5125	6530	Rack, Crutch, Wall Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Wall mounted crutch rack. Constructed of natural finished wood with chrome plated adjustable hangers. Designed for hanging crutches and accessories. [No other source(s) identified with this description/specification]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	17	60	16	25 lb	1:	--	--	--	--	--	--						
		CM:	43	152	41	12 kg	2:	--	--	--	--	--	--						
													--						
													--						
A5135	7125	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	6	36	10	12 lb	1:	--	--	--	--	--	--						
		CM:	15	91	25	6 kg	2:	--	--	--	--	--	--						
													--						
													--						
A5145	5340-00-754-1678	Hook, Garment, Double, SS, Surface Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	2	4	2	-- lb	1:	--	--	--	--	--	--						
		CM:	5	10	5	1 kg	2:	--	--	--	--	--	--						
													--						
													--						
A5150	5340	Hook, Garment, Triple, Surface Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A surface mounted, anodized aluminum or chrome bar or woodgrain finished panel with triple garment hooks. For general purpose use throughout the facility to hang various items of apparel.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	6	18	4	7 lb	1:	--	--	--	--	--	--						
		CM:	15	46	10	4 kg	2:	--	--	--	--	--	--						
													--						
													--						
A5155	5340	Costumer, Wall, Executive	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A contemporary solid hardwood or wood laminate panel with a minimum of 3 hooks and 2 matching solid wood hangers. At a minimum, panel and hangers shall be available in oak or walnut. For general purpose use in executive offices to hang various items of apparel.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	7	20	4	5 lb	1:	--	--	--	--	--	--						
		CM:	18	51	10	3 kg	2:	--	--	--	--	--	--						
													--						
													--						
A5160	7125	Shelf, 8" Depth, SS, Surface Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A surface mounted, satin finish stainless steel, shelf with a minimum depth of 8". Mounting brackets are welded to shelf. Shelf is available in various widths. For general purpose use in scrub areas/rooms or other areas of the facility where a SS shelf is required. Pricing based upon a 48" width. [No other source(s) identified with this description/specification]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	4	48	8	8 lb	1:	--	--	--	--	--	--						
		CM:	10	122	20	4 kg	2:	--	--	--	--	--	--						
													--						
													--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A5162	7125	Shelf, Fold Down, Stainless Steel	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Fold down utility shelf fabricated of stainless steel. The shelf is normally installed in female toilet compartments for the placement of a purse or package. The shelf is surfaced mounted and will automatically return to it's upright position when the object is removed.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	2	6	15	5 lb	1:	--	--	--	NO		--					
		CM:	5	15	38	3 kg	2:	--	--	--	NO		--					
A5165	7125	Shelf, 5" Depth, SS, Surface Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
A surface mounted, satin finish stainless steel, shelf with a maximum depth of 5". Mounting brackets are welded to shelf. Shelf is available in various widths. For general purpose use in scrub areas/rooms or other areas of the facility where a SS shelf is required. Pricing based upon a 48" width.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	5	48	5	8 lb	1:	--	--	--	NO		--					
		CM:	13	122	13	4 kg	2:	--	--	--	NO		--					
A5170	6530	Rod, Shower Curtain, 1"Diameter, W/Curtain & Hooks	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
A concealed mounted, 1" outside diameter, satin finish stainless steel, shower curtain rod with white vinyl shower curtain (72" H) and SS shower curtain hooks. Rod and curtain available in various widths. For general purpose use at shower stall or bathtub locations. Pricing based upon standard shower stall dimensions of 36" x 36" and a standard curtain height of 72".																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	74	36	3	3 lb	1:	--	--	--	NO		--					
		CM:	188	91	8	2 kg	2:	--	--	--	NO		--					
A5175	4510	Soap Dish, With Bar, SS, Recessed	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
A recessed mounted, satin finish stainless steel, soap dish with bar. Soap dish furnished with retaining lip and mounting clamp for installation in stud walls or countertop aprons. For general purpose use in shower stalls or at bathtub locations. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	6	6	4	1 lb	1:	--	--	--	NO		--					
		CM:	15	15	10	1 kg	2:	--	--	--	NO		--					
A5180	6530	Track, Cubicle, Surface Mounted, With Curtain	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote. [An interior designer will normally determine the curtain size, pattern, colors and fabric. Curtains although not sold by the foot average approximately \$7.00 per linear foot for a standard 6 foot length.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
FT		IN:	--	12	--	-- lb	1:	--	--	--	NO		--					
		CM:	--	30	--	-- kg	2:	--	--	--	NO		--					
A5181	6530	Screen, Privacy, Freestanding	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
The privacy screen shall consist of three panels, approximately 20 x 69 inches each and be freestanding. The panels shall be flame retardant bacteriostatic vinyl.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	69	66	4	12 lb	1:	--	--	--	NO		--					
		CM:	175	168	10	6 kg	2:	--	--	--	NO		--					
A5185	6530	Track, Drapery, Ceil/Wall Mntd, Sngl Channel Cord	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Ceiling or wall mounted single channel cord drapery track. Adjustable with mounted brackets and slides. Dimensions and shape as required. Unit consists of a thick extruded aluminum track. Equipped with self-lubricating carriers, beaded drop chain, hooks, removable end caps, and curtain. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote. [This is an architecture note. The variances between track systems are too great to make a reasonable assumption about size and cost. The style of curtain, i.e. size, patterns, colors and accessories are to be determined by the interior designer.]																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			FT	--	--	--	2 lb	--	--	--	--	NO	--		
			CM:	--	--	--	1 kg	2:	--	--	--	NO	--		
A5195	4510-00-702-6934	Dispenser, Toilet Tissue, SS, 1-Roll, Surface MNTD	A	A	A	A	--	--	--	--	--	--	--		
		A concealed surface mounted, single roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates one standard-core toilet tissue roll through 5" in diameter. Spindle is chrome plated plastic with a heavy-duty internal spring and turns freely for non-controlled delivery. For general purpose use in restrooms.													
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	2	8	4	1 lb	--	--	--	--	NO	--		
			CM:	5	20	10	1 kg	2:	--	--	--	NO	--		
A5200	4510-00-702-6934	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	A	A	A	A	--	--	--	--	--	--	--		
		A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms. [Price difference verified.]													
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	2	13	4	1 lb	--	--	--	--	NO	--		
			CM:	5	33	10	1 kg	2:	--	--	--	NO	--		
A5202	4510	Dispenser, Toilet Paper w/Utility Shelf, SS, 2-Roll	A	A	A	A	--	--	--	--	--	--	--		
		A concealed surface mounted, double roll, satin finish stainless steel, combination toilet tissue dispenser and utility shelf (minimum 5" depth). Unit accommodates two standard-core toilet tissue rolls through 6" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms. [No other source(s) identified with this description/specification]													
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	4	16	6	3 lb	--	--	--	--	NO	--		
			CM:	10	41	15	2 kg	2:	--	--	--	NO	--		
A5205	4510	Bar, Towel, 1" Diameter, SS, Surface Mounted	A	A	A	A	--	--	--	--	--	--	--		
		A surface mounted, satin finish stainless steel, 1" diameter, towel bar. Support posts and flanges are one piece, chrome-plated, cast heavy brass with satin finish. Towel bar shall not rotate within support posts. Available in 18", 24" and 30" widths. For general purpose use in shower or bathtub rooms. Pricing based upon a suggested standard width of 18".													
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	3	21	3	1 lb	--	--	--	0	NO	--		
			CM:	8	53	8	1 kg	2:	--	--	--	NO	--		
A5207	4510	Bar, Towel, 1" Diameter, SS, Surface Mntd, Psych	A	A	A	A	--	--	--	--	--	--	--		
		A surface mounted, satin finish stainless steel, 1" diameter, towel bar with concealed mounting flanges. Clearance between towel bar and wall shall be 1-1/2". Ends of towel bar pass through the flanges and are welded to form one structural unit. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Available in various widths. Recommended for use in shower or bathtub rooms on psychiatric and/or detention wards. Pricing based upon a suggested standard width of 18".													
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	3	18	3	2 lb	--	--	--	0	NO	--		
			CM:	8	46	8	1 kg	2:	--	--	--	NO	--		
A5210	7730	Bracket, Television, Wall Mounted, w/Adjust Arm	A	A	A	A	--	--	--	--	--	--	--		
		Wall mounted television bracket with adjustable arm. Consists of platform movable arm with full 120 degree swivel. Designed for holding wall mounted television units in patient rooms.													
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	27	30	15	28 lb	--	--	--	--	NO	--		
			CM:	69	76	38	13 kg	2:	--	--	--	NO	--		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A5215	7730	Bracket, Television, Ceiling Mounted	A	A	B	B	--	--	--	--	--	--	--	--	--	--	--	--
Ceiling mounted television bracket. The bracket shall be a yoke style mount with a load capacity of 300 pounds with adjustments of 0-15 degree tilt and 360 degree swivel. Width and height shall be capable of accommodating various size monitors.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	35	41	10	30 lb	1:	--	--	--	NO	--						
		CM:	89	104	25	14 kg	2:	--	--	--	NO	--						
A5220	6520	Bracket, Television, Wall Backing	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	13	18	1	11 lb	1:	--	--	--	NO	--						
		CM:	33	46	3	5 kg	2:	--	--	--	NO	--						
A5230	7125	Cabinet, Blanket, Fire, Wall Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Fire blanket cabinet with fire blanket, wall mounted cabinet. Finish is rust and acid resistant baked enamel and designed for storage of fire blankets. [The dimensions for the cabinet were removed to facilitate greater versatility and source selections.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	--	NO	--						
		CM:	--	--	--	-- kg	2:	--	--	--	NO	--						
A6010	6530	Bumper, Wall, Bed	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Protects the room walls while properly positioning the bed to vital services. Receptacles on both sides to be protected from accidental disconnection by some means such as angling. Utility connections may include normal power, emergency power, bed receptacle, telephone jack, low voltage controller and dedicated night light. [Price will be sensitive to the options selected. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	22	48	12	-- lb	1:	--	--	--	NO	--						
		CM:	56	122	30	-- kg	2:	--	--	--	NO	--						
A6025	7105	Mirror, Safety, Convex	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Shall be an 18 inch convex circular mirror. It shall provide a 160-degree wide-field viewing area. The mirror shall be made of shatterproof acrylic or unbreakable polycarbonate. Shall come with mounting bracket.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	18	18	12	12 lb	1:	--	--	--	NO	--						
		CM:	46	46	30	6 kg	2:	--	--	--	NO	--						
A6030	7100	Machine, Vending	D	D	D	D	--	--	A	--	--	--	--	--	--	--	--	--
This JSN is to be used for determining and defining the requirement for vending machines. Item is normally leased or supplied by Army & Air Force Exchange Service, (AAFES). [Architectural note: Information provided to indicate applications and styles of the units.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	84	37	41	800 lb	1:	120	1	15	NO	--						
		CM:	213	94	104	364 kg	2:	--	--	--	YES	--						
A6035	7100	Repository, Night, With Safe	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Constructed of high tensile steel body and jam designed to maximize protection against pry attack. Top or front load depository features a large hopper made of formed heavy duty steel, handle activated and designed for smooth money drop operation and large package capacity. Deposit drawer features a large fish-resistant pull out drawer deposit directly into standard interior locker.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	32	20	22	345 lb	1:	--	--	--	NO	--						
		CM:	81	51	56	157 kg	2:	--	--	--	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
A6045	7100	Artwork, Mural, Wall	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
This JSN is to be used for determining and defining locations of decorative artwork. [Interior Design note: Price based on an 8' X 13' wallpaper mural. Individually designed or created murals must be priced separately.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:									
EA		IN:	--	--	--	-- lb	1:	--	--	--	NO	--								
		CM:	--	--	--	-- kg	2:	--	--	--	NO	--								
A6046	6230	Artwork, Decorative, With Frame	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
This JSN is to be used for determining and defining location of decorative artwork. [Interior Design note: Price based on a 20" X 30" color print with decorative frame and glass. This is a place holder for artwork.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:									
EA		IN:	--	--	--	-- lb	1:	--	--	--	NO	--								
		CM:	--	--	--	-- kg	2:	--	--	--	NO	--								
A6090	6530	Exhaust System, Welding	A	A	A	A	--	--	A	--	--	A	--	--	--	--	--	E		
Welding fume exhaust system consisting of a 4" to 5" hose, connected to a heavy duty pressure blower assembly. For use in industrial shops for the evacuation of fumes caused by gas and arc welding. [The units identified come with 8 inch diameter vacuum hoses, per vendors recommendation.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:									
EA		IN:	73	36	29	340 lb	1:	120	1	13	60	NO	--							
		CM:	185	91	74	155 kg	2:	--	--	--	YES	--								
A6105	6530	Counter, Reception Control, Built-In	A	A	A	A	--	--	A	--	--	A	--	--	--	--	--	--		
Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth. [This is an architectural note. This is a millwork item and is custom built to meet the needs of the facility. Recommend this JSN be maintained as a placeholder for systems unique to each project. The price indicated does not reflect the price of any one manufacturer. This is a general price made up of individual items found in the MIL-STD-1691 data base.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:									
EA		IN:	30	30	114	-- lb	1:	--	--	--	NO	--								
		CM:	76	76	290	-- kg	2:	--	--	--	NO	--								
A6110	6530	Counter, Console, Communications	A	A	A	A	--	--	A	--	--	A	--	--	--	--	--	--		
Counter, console, communications. Consists of one 18" wide base cabinet with two drawers and file drawer, one 30" wide pencil drawer and one 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. [This is an architectural note. This is a millwork item and is custom built to meet the needs of the facility. Recommend this JSN be maintained as a placeholder for systems unique to each project. The price indicated does not reflect the price of any one manufacturer. This is a general price made up of individual items found in the MIL-STD-1691 data base.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:									
EA		IN:	30	30	66	-- lb	1:	--	--	--	NO	--								
		CM:	76	76	168	-- kg	2:	--	--	--	NO	--								
A6125	3990	Leveler, Dock	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--		
Unit attaches to the face of the dock for easy installation. It consists of a counterbalance lip that can be extended to rest on the bed of the trailer for loading and unloading of merchandise. When the trailer departs, the lip will automatically retract behind the bumper face. Size will vary depending on the application.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:									
EA		IN:	27	72	15	545 lb	1:	--	--	--	NO	--								
		CM:	69	183	38	248 kg	2:	--	--	--	NO	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
A6135	5670	Shutter, Roll, CRS, With Hood	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Coiling counter shutters require very little headroom and side room and can be easily concealed in the surrounding structure. These units are used for small openings or openings above counter tops. They are designed primarily for security and are available in aluminum, stainless steel or painted galvanized steel. Counter shutters can operated by manually (push-up), hand crank or motorized. Nominal size used for pricing, 48" high x 120" long. [Pricing was based on a manual operated, stainless steel counter shutter with frame, 48 inches high by 120 inches long for an 8 inch wall. Add an additional \$400.00 for an electrically operated unit with required modifications.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:				
EA		CM:	48	120	8	-- lb	1:	--	--	--	--	DEPENDENT:	NO	--				
			122	305	20	-- kg	2:	--	--	--	--							
A6155	7100	Cage, Security, Heavy Duty	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Modular woven wire security partition with doors creating a secure area or separate zones without blocking light or air. Easy surveillance of protective area. Durable 10 gauge, 1" diamond wire woven into a sturdy 1" x 1/2" x 1/8" channel frame. Size and shape of the security room will vary depending on the application. Price is per panel. Separate pricing of doors and windows. [Price is based on a single 5' x 10' panel. These manufacturers/vendors will custom fabricate security cages to specific requirements.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:				
EA		CM:	***	60	1	76 lb	1:	--	--	--	--	DEPENDENT:	NO	--				
			3048	152	3	35 kg	2:	--	--	--	--							
A6160	5680	Bumper, Dock	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Unit attaches to the face of the dock for easy installation by bolting or welding. The bumper block is constructed from the same material used in the manufacture of heavy tire cord. Used to protect vehicles and docks against impacts when positioning the vehicles to the dock for loading and unloading of merchandise. Size and shape of the bumper block will vary depending on the application.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:				
EA		CM:	12	36	5	100 lb	1:	--	--	--	--	DEPENDENT:	NO	--				
			30	91	13	46 kg	2:	--	--	--	--							
A6165	5680	Station, Pneumatic Tube System	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
The basic pneumatic tube system consists of a tube linking two or more different locations, a carrier to carry the payload and a power source to move the carrier from one location to another. The systems becomes more complex when the system is expanded to a network containing hundreds of locations and dozens of zones that need to transport the payload simultaneously. [This JSN is maintained as an architectural placeholder and is used for determining and defining the location of pneumatic tube stations. This type of system is uniquely engineered to each individual facility taking into consideration several factors to include; usage, number of stations, tube diameter and carrier size.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:				
EA		CM:	--	--	--	-- lb	1:	--	--	--	--	DEPENDENT:	NO	--				
			--	--	--	-- kg	2:	--	--	--	--							
A6200	5999	Uninterruptible Power Supply, Three Phase	A	A	A	A	--	--	G	--	--	--	--	--	--	--	--	
Uninterruptible power supply (UPS) available in 208, 480 or 600 VAC configuration. Used in areas where power protection is required for large computer systems, communication equipment, radiographic equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss. [This JSN is maintained as an architectural placeholder and is intended to indicate the location(s) of the unit. The variances between systems are too great to make a reasonable assumption about size, cost or electrical requirements. This type of equipment is uniquely configured to each individual facility based on the equipment it is to support. Pricing ranges from approximately \$5,000. To \$75,000. plus.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:				
EA		CM:	--	--	--	-- lb	1:	--	--	--	--	DEPENDENT:	NO	--				
			--	--	--	-- kg	2:	--	--	--	--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
A6210	5999	Uninterruptible Power Supply, Single Phase	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Stand alone uninterruptible power supply (UPS) available in 120, 208 or 240 VAC configuration. Power output can range from 200 VA to 3000 VA depending on the application. Used in areas where power protection is required for computer systems, communication equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss. [This JSN is maintained as an architectural placeholder and is intended to indicate the location(s) of the unit. The variances between systems are too great to make a reasonable assumption about size, cost or electrical requirements. This type of equipment is uniquely configured to each individual facility based on the equipment it is to support.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	--	--	--	--	1:	--	--	--	0	NO	--						
		CM:	--	--	--	--	2:	--	--	--	NO	NO	--						
A6305	7230	Drapes, Pair	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
This JSN is to be used for determining and defining the location of drapes. Fabric to be flame retardant, variable colors and patterns with backing. Price based on a pair of drapes for a window approximately 36" W X 60" H. [Design, color, fabric and size to be determined by interior designer. Prices are estimates only and do not include drapery hardware or installation. Actual price will depend on quality of fabric, type of lining and style of drape.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
PR		IN:	60	36	1	--	1:	--	--	--	0	NO	--						
		CM:	152	91	3	--	2:	--	--	--	NO	NO	--						
A6306	7230	Drapes, Blackout	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
This JSN is used for determining and defining the location of blackout drapes. The exact fabric used depends on the facility specific requirements for light transmission, flame retardancy, sound transmission, security and interior design color. The database pricing is by panel of light to medium duty blackout drapes approximately 96" W x 84" Long.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	84	98	1	3	1:	--	--	--	0	NO	--						
		CM:	213	249	3	2	2:	--	--	--	NO	NO	--						
A6311	7230	Blinds, Window, Mini w/Brackets	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Mini blinds for interior windows. Shall consist of 1-inch mini aluminum blinds with mounting bracket and child proof tassels. [Pricing based on 36" X 72" size blinds.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	72	36	2	--	1:	--	--	--	0	NO	--						
		CM:	183	91	5	--	2:	--	--	--	NO	NO	--						
A6330	6530	Intercom - Room To Room	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Intercom for local communication between rooms. May be used for areas such as a seclusion ante-room to the seclusion room or other areas such as the accelerator caves and the accelerator control area.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	3	8	10	4	1:	120	1	1	60	NO	--						
		CM:	8	20	25	2	2:	--	--	--	NO	NO	--						
C0023	6530	Cabinet, Wardrobe, 1 Door, 84x15x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Wardrobe cabinet with a fixed shelf, clothing rod, and a solid or louvered right or left-hinged door (appropriate door hinge configuration to be indicated on the equipment elevation drawings), an optional locking door is available. Also referred to as a wardrobe case, unit or storage unit. Used for storage of clothing and personal items.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	84	15	22	196	1:	--	--	--	--	NO	--						
		CM:	213	38	56	89	2:	--	--	--	NO	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
C0025	6530	Cabinet, Wardrobe, 1 Door, 84x24x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wardrobe cabinet with a fixed shelf, clothing rod, and a solid or louvered right or left-hinged door (appropriate door hinge configuration to be indicated on the equipment elevation drawings), an optional locking door is available. Also referred to as a wardrobe case, unit or storage unit. Used for storage of clothing and personal items.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			84	213	24	61	22	56	239 lb	109 kg	1: --	2: --	--	--	--	--	--	--
C0035	6530	Rail, Apron, 4x24x1	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			5	13	24	61	1	3	7 lb	4 kg	1: --	2: --	0	NO	NO	--	--	--
C0036	6530	Rail, Apron, 4x30x1	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. [Jamestown Metal Products (94881) pricing verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			4	10	30	76	1	3	9 lb	4 kg	1: --	2: --	--	NO	NO	--	--	--
C0037	6530	Rail, Apron, 4x36x1	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			4	10	36	91	1	3	10 lb	5 kg	1: --	2: --	--	NO	NO	--	--	--
C0038	6530	Rail, Apron, 4x42x1	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			4	10	42	107	1	3	12 lb	6 kg	1: --	2: --	0	NO	NO	--	--	--
C0039	6530	Rail, Apron, 4x48x1	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			4	10	48	122	1	3	14 lb	7 kg	1: --	2: --	0	NO	NO	--	--	--
C0040	6530	Rail, Apron, 4x54x1	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			5	13	54	137	1	3	16 lb	8 kg	1: --	2: --	--	NO	NO	--	--	--

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
C0041	6530	Rail, Apron, 4x60x1	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			4	10	4	60	1	18 lb	1:	--	--	--	--	NO	--	--	--	NO	--
								9 kg	2:	--	--	--	--	NO	--	--	--	NO	--
C0043	6530	Frame, Apron, 1 Drawer, 4x24x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	--
Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			4	10	4	24	22	30 lb	1:	--	--	--	--	NO	--	--	--	NO	--
								14 kg	2:	--	--	--	--	NO	--	--	--	NO	--
C0044	6530	Frame, Apron, 1 Drawer, 4x30x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	--
Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			4	10	4	30	22	32 lb	1:	--	--	--	--	NO	--	--	--	NO	--
								15 kg	2:	--	--	--	--	NO	--	--	--	NO	--
C0045	6530	Frame, Apron, 1 Drawer, 4x36x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	--
Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall. [Jamestown Metal Products (94881) pricing verified.]																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			4	10	4	36	22	37 lb	1:	--	--	--	--	NO	--	--	--	NO	--
								17 kg	2:	--	--	--	--	NO	--	--	--	NO	--
C0046	6530	Frame, Apron, 2 Drawer, 4x48x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	--
Apron frame with two standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			4	10	4	48	22	49 lb	1:	--	--	--	--	NO	--	--	--	NO	--
								23 kg	2:	--	--	--	--	NO	--	--	--	NO	--
C0047	6530	Frame, Apron, 3 Drawer, 4x60x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	--
Apron frame with three standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			4	10	4	60	22	66 lb	1:	--	--	--	--	NO	--	--	--	NO	--
								30 kg	2:	--	--	--	--	NO	--	--	--	NO	--
C0051	6530	Pegboard, Glassware, 30x30x6	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	--
Glassware pegboard with drip trough and pegs, suitable for holding a wide variety of lab glassware. The pegboard is available in various materials (epoxy resin, stainless steel, and wood) and with or without finished back. The pegs are generally made of polypropylene and are available in various lengths which determines the number of pegs that are provided. Pricing is based upon an epoxy resin construction without finished back, 6.5" length pegs, and a 5" depth drip trough.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO
			30	76	30	30	6	79 lb	1:	--	--	--	--	NO	--	--	--	NO	--
								36 kg	2:	--	--	--	--	NO	--	--	--	NO	--

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES															
				R	A	F	A	H		1	2	3	4	5	6										
C0052	6530	Pegboard, Glassware, 30x36x6	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--										
Glassware pegboard with drip trough and pegs, suitable for holding a wide variety of lab glassware. The pegboard is available in various materials (epoxy resin, stainless steel, and wood) and with or without finished back. The pegs are generally made of polypropylene and are available in various lengths which determines the number of pegs that are provided. Pricing is based upon an epoxy resin construction without finished back, 6.5" length pegs, and a 5" depth drip trough. [Jamestown Metal Products (94881) pricing verified.]																									
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO									
EA		IN:	30	36	6	95 lb	1:	--	--	--	NO	--	--	EA	CM:	76	92	15	44 kg	2:	--	--	--	NO	--
C01C0	6530	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x18x22	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--										
Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.																									
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO									
EA		IN:	36	18	22	95 lb	1:	--	--	--	NO	--	--	EA	CM:	91	46	55	44 kg	2:	--	--	--	NO	--
C01D0	6530	Cabinet, U/C/B, 4 Drawer, 36x18x22	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--										
Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.																									
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO									
EA		IN:	36	18	22	100 lb	1:	--	--	--	NO	--	--	EA	CM:	91	46	55	46 kg	2:	--	--	--	NO	--
C01Q0	6530	Cabinet, Sink, U/C/B, 1 Door, 36x18x22	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--										
Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.																									
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO									
EA		IN:	36	18	22	80 lb	1:	--	--	--	NO	--	--	EA	CM:	91	46	55	37 kg	2:	--	--	--	NO	--
C02B0	6530	Cabinet, U/C/B, 2 Shelves, 1 Door, 36x24x22	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--										
Standing height under counter base cabinet with two adjustable shelves and a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a cupboard cabinet. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]																									
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO									
EA		IN:	36	24	22	101 lb	1:	--	--	--	NO	--	--	EA	CM:	91	61	55	46 kg	2:	--	--	--	NO	--
C02C0	6530	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--										
Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.																									
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	NO									
EA		IN:	36	24	22	95 lb	1:	--	--	--	NO	--	--	EA	CM:	91	61	55	43 kg	2:	--	--	--	NO	--

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES											
				A	N	A	V	I							
				R	A	F	A	H	1	2	3	4	5	6	
C02D0	6530	Cabinet, U/C/B, 4 Drawer, 36x24x22	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--
Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	36	24	22	120 lb	1:	--	--	--	NO	--			
		CM:	91	61	55	55 kg	2:	--	--	--	NO	--			
C02Q0	6530	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	A A A A --	--	--	--	--	--	0	NO	BTUs / HR:				
Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	36	24	22	90 lb	1:	--	--	--	NO	--			
		CM:	91	61	55	41 kg	2:	--	--	--	NO	--			
C03A0	6530	Cabinet, U/C/B, Open, 2 Shelf, 36x30x22	A A A A --	--	--	--	--	--	--	NO	BTUs / HR:				
Standing height under counter base cabinet, open, with two adjustable shelves. Also referred to as an open cabinet. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	36	30	22	100 lb	1:	--	--	--	NO	--			
		CM:	91	76	55	46 kg	2:	--	--	--	NO	--			
C03E0	6530	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x30x22	A A A A --	--	--	--	--	--	--	NO	BTUs / HR:				
Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	36	30	22	130 lb	1:	--	--	--	NO	--			
		CM:	91	76	55	59 kg	2:	--	--	--	NO	--			
C03F0	6530	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x30x22	A A A A --	--	--	--	--	--	--	NO	BTUs / HR:				
Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	36	30	22	130 lb	1:	--	--	--	NO	--			
		CM:	91	76	55	59 kg	2:	--	--	--	NO	--			
C03G0	6530	Cabinet, U/C/B, 2 Shelf, 2 Door, 36x30x22	A A A A --	--	--	--	--	--	--	NO	BTUs / HR:				
Standing height under counter base cabinet with two adjustable shelves and two solid hinged doors. Also referred to as a cupboard cabinet. For general purpose use throughout the facility.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	36	30	22	131 lb	1:	--	--	--	NO	--			
		CM:	91	76	55	60 kg	2:	--	--	--	NO	--			
C03H0	6530	Cabinet, U/C/B, 2 Half Drawers, 3 DR, 36x30x22	A A A A --	--	--	--	--	--	--	NO	BTUs / HR:				
Standing height under counter base cabinet with two half width drawers side-by-side above three full width drawers. Also referred to as a drawer cabinet. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	36	30	22	150 lb	1:	--	--	--	NO	--			
		CM:	91	76	55	69 kg	2:	--	--	--	NO	--			

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES										
				A	N	A	V	I	1	2	3	4	5	6
C03J0	6530	Cabinet, U/C/B, 8 Half Drawers, 36x30x22	A A A A --	--	--	--	--	--	--	--	--	--	--	
Standing height under counter base cabinet with eight half width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:			
EA		IN:	36	30	22	165 lb	1:	--	--	--	NO		--	
CM:		91	76	55	75 kg	2:	--	--	--	NO		--		
C03L0	6530	Cabinet, U/C/B, 1 DR, 3 Half DR, 1 Door, 30" W	A A A A --	--	--	--	--	--	--	--	--	--	--	
Standing height under counter base cabinet, 34" H x 30" W x 22" D with a full width drawer above three half width drawers alongside a solid right or left door/cupboard (appropriate door/cupboard configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:			
EA		IN:	36	30	22	145 lb	1:	--	--	--	0		--	
CM:		91	76	55	66 kg	2:	--	--	--	NO		--		
C03P0	6530	Cabinet, Sink, U/C/B, 2 Door, 30" W	A A A A --	--	--	--	--	--	--	--	--	--	--	
Standing height under counter base sink cabinet. 36" H x 30" W x 22" D with two solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:			
EA		IN:	36	30	22	110 lb	1:	--	--	--	0		--	
CM:		91	76	55	50 kg	2:	--	--	--	NO		--		
C04A0	6530	Cabinet, U/C/B, Open, 2 Shelf, 36x36x22	A A A A --	--	--	--	--	--	--	--	--	--	--	
Standing height under counter base cabinet, open, with two adjustable shelves. Also referred to as an open cabinet. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:			
EA		IN:	36	36	22	105 lb	1:	--	--	--	--		--	
CM:		91	91	55	48 kg	2:	--	--	--	NO		--		
C04E0	6530	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	A A A A --	--	--	--	--	--	--	--	--	--	--	
Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:			
EA		IN:	36	36	22	140 lb	1:	--	--	--	--		--	
CM:		91	91	55	64 kg	2:	--	--	--	NO		--		
C04F0	6530	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x36x22	A A A A --	--	--	--	--	--	--	--	--	--	--	
Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:			
EA		IN:	36	36	22	135 lb	1:	--	--	--	--		--	
CM:		91	91	55	62 kg	2:	--	--	--	NO		--		
C04G0	6530	Cabinet, U/C/B, 2 Shelf, 2 Door, 36x36x22	A A A A --	--	--	--	--	--	--	--	--	--	--	
Standing height under counter base cabinet with two adjustable shelves and two solid hinged doors. Also referred to as a cupboard cabinet. For general purpose use throughout the facility. [Price difference verified.]														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:			
EA		IN:	36	36	22	141 lb	1:	--	--	--	0		--	
CM:		91	91	55	64 kg	2:	--	--	--	NO		--		

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES																																																							
				A	N	A	V	I	1 2 3 4 5 6																																																		
C04H0	6530	Cabinet, U/C/B, 2 Half Drawer, 3 Drawer, 36x36x22	A A A A --	--	--	--	--	--	--																																																		
Standing height under counter base cabinet with two half width drawers side-by-side above three full width drawers. Also referred to as a drawer cabinet. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]																																																											
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>36</td> <td>91</td> <td>22</td> <td>155 lb 71 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>55</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>HZ SWITCH: NO</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT: NO</td> <td></td> </tr> </tbody> </table>										UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	36	91	22	155 lb 71 kg	1:	--	--	--	--				55		2:	--	--	--	--									HZ SWITCH: NO										DEPENDENT: NO	
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																		
EA	36	91	22	155 lb 71 kg	1:	--	--	--	--																																																		
			55		2:	--	--	--	--																																																		
								HZ SWITCH: NO																																																			
								DEPENDENT: NO																																																			
C04J0	6530	Cabinet, U/C/B, 8 Half Drawer, 36x36x22	A A A A --	--	--	--	--	--	--																																																		
Standing height under counter base cabinet with eight half width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.																																																											
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>36</td> <td>91</td> <td>22</td> <td>185 lb 84 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>55</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>HZ SWITCH: NO</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT: NO</td> <td></td> </tr> </tbody> </table>										UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	36	91	22	185 lb 84 kg	1:	--	--	--	--				55		2:	--	--	--	--									HZ SWITCH: NO										DEPENDENT: NO	
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																		
EA	36	91	22	185 lb 84 kg	1:	--	--	--	--																																																		
			55		2:	--	--	--	--																																																		
								HZ SWITCH: NO																																																			
								DEPENDENT: NO																																																			
C04K0	6530	Cabinet, U/C/B, 1 Shelf, 6 Half DR, 1 DO, 36x36x22	A A A A --	--	--	--	--	--	--																																																		
Standing height under counter base cabinet with one adjustable shelf, two shallow half width drawers above a solid right or left door/cupboard (appropriate door/cupboard configuration to be indicated on equipment elevation drawings), and four half width drawers alongside. Also referred to as a combination cabinet or drawer and cupboard cabinet. For general purpose use throughout the facility.																																																											
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>36</td> <td>91</td> <td>22</td> <td>170 lb 78 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>0</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>55</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>0</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>HZ SWITCH: NO</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT: NO</td> <td></td> </tr> </tbody> </table>										UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	36	91	22	170 lb 78 kg	1:	--	--	0	--				55		2:	--	--	0	--									HZ SWITCH: NO										DEPENDENT: NO	
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																		
EA	36	91	22	170 lb 78 kg	1:	--	--	0	--																																																		
			55		2:	--	--	0	--																																																		
								HZ SWITCH: NO																																																			
								DEPENDENT: NO																																																			
C04L0	6530	Cabinet, U/C/B, 1 DR, 3 Half DR, 1 Door, 36" W	A A A A --	--	--	--	--	--	--																																																		
Standing height under counter base cabinet, 36" H x 36" W x 22" D with a full width drawer above three half width drawers alongside a solid right or left door/cupboard (appropriate door/cupboard configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.																																																											
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>36</td> <td>91</td> <td>22</td> <td>155 lb 71 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>0</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>55</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>0</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>HZ SWITCH: NO</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT: NO</td> <td></td> </tr> </tbody> </table>										UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	36	91	22	155 lb 71 kg	1:	--	--	0	--				55		2:	--	--	0	--									HZ SWITCH: NO										DEPENDENT: NO	
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																		
EA	36	91	22	155 lb 71 kg	1:	--	--	0	--																																																		
			55		2:	--	--	0	--																																																		
								HZ SWITCH: NO																																																			
								DEPENDENT: NO																																																			
C04P0	6530	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	A A A A --	--	--	--	--	--	--																																																		
Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible. [Jamestown Metal Products (94881) pricing verified.]																																																											
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>36</td> <td>91</td> <td>22</td> <td>115 lb 53 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>55</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>HZ SWITCH: NO</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT: NO</td> <td></td> </tr> </tbody> </table>										UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	36	91	22	115 lb 53 kg	1:	--	--	--	--				55		2:	--	--	--	--									HZ SWITCH: NO										DEPENDENT: NO	
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																		
EA	36	91	22	115 lb 53 kg	1:	--	--	--	--																																																		
			55		2:	--	--	--	--																																																		
								HZ SWITCH: NO																																																			
								DEPENDENT: NO																																																			
C05E0	6530	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x48x22	A A A A --	--	--	--	--	--	--																																																		
Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.																																																											
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>36</td> <td>91</td> <td>22</td> <td>165 lb 75 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>55</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>HZ SWITCH: NO</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT: NO</td> <td></td> </tr> </tbody> </table>										UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	36	91	22	165 lb 75 kg	1:	--	--	--	--				55		2:	--	--	--	--									HZ SWITCH: NO										DEPENDENT: NO	
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																		
EA	36	91	22	165 lb 75 kg	1:	--	--	--	--																																																		
			55		2:	--	--	--	--																																																		
								HZ SWITCH: NO																																																			
								DEPENDENT: NO																																																			
C05F0	6530	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x48x22	A A A A --	--	--	--	--	--	--																																																		
Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.																																																											
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>36</td> <td>91</td> <td>22</td> <td>165 lb 75 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>0</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>55</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>0</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>HZ SWITCH: NO</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT: NO</td> <td></td> </tr> </tbody> </table>										UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	36	91	22	165 lb 75 kg	1:	--	--	0	--				55		2:	--	--	0	--									HZ SWITCH: NO										DEPENDENT: NO	
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																		
EA	36	91	22	165 lb 75 kg	1:	--	--	0	--																																																		
			55		2:	--	--	0	--																																																		
								HZ SWITCH: NO																																																			
								DEPENDENT: NO																																																			

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1 2 3 4 5 6	
C05G0	6530	Cabinet, U/C/B, 2 Shelf, 2 Door, 36x48x22	A A A A --	--	--	--	--	--	--	
Standing height under counter base cabinet with two adjustable shelves and two solid hinged doors. Also referred to as a cupboard cabinet. For general purpose use throughout the facility. [Price difference verified.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	36	48	22	172 lb	1:	-- -- --	0	
EA		CM:	91	122	55	78 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
C05H0	6530	Cabinet, U/C/B, 2 Half Drawer, 3 Drawer, 36x48x22	A A A A --	--	--	--	--	--	--	
Standing height under counter base cabinet with two half width drawers side-by-side above three full width drawers. Also referred to as a drawer cabinet. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	36	48	22	190 lb	1:	-- -- --	--	
EA		CM:	91	122	55	87 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
C05J0	6530	Cabinet, U/C/B, 8 Half Drawer, 36x48x22	A A A A --	--	--	--	--	--	--	
Standing height under counter base cabinet with eight half width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	36	48	22	215 lb	1:	-- -- --	--	
EA		CM:	91	122	55	98 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
C05K0	6530	Cabinet, U/C/B, 1 Shelf, 6 Half DR, 1 DO, 36x48x22	A A A A --	--	--	--	--	--	--	
Standing height under counter base cabinet with one adjustable shelf, two shallow half width drawers above a solid right or left door/cupboard (appropriate door/cupboard configuration to be indicated on equipment elevation drawings), and four half width drawers alongside. Also referred to as a combination cabinet or drawer and cupboard cabinet. For general purpose use throughout the facility. [Price difference verified.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	36	48	22	200 lb	1:	-- -- --	--	
EA		CM:	91	122	55	91 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
C05L0	6530	Cabinet, U/C/B, 1 DR, 3 Half DR, 1 Door, 36x48x22	A A A A --	--	--	--	--	--	--	
Standing height under counter base cabinet with a full width drawer above three half width drawers alongside a solid right or left door/cupboard (appropriate door/cupboard configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility. [Price difference verified.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	36	48	22	190 lb	1:	-- -- --	--	
EA		CM:	91	122	55	87 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
C05P0	6530	Cabinet, Sink, U/C/B, 2 Door, 36x48x22	A A A A --	--	--	--	--	--	--	
Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible. [Jamestown Metal Products (94881) pricing verified.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	36	48	22	135 lb	1:	-- -- --	--	
EA		CM:	91	122	55	62 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
C06D0	6530	Cabinet, U/C/B, 4 Drawer, 30x18x22	A A A A --	--	--	--	--	--	--	
Sitting height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	30	18	22	95 lb	1:	-- -- --	--	
EA		CM:	76	46	55	43 kg	2:	-- -- --	NO	--
DEPENDENT: NO										

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
C06M0	6530	Cabinet, U/C/B, 1 PBD, 2 DR, 1 File DR, 30x18x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Sitting height under counter base cabinet with a pullboard above two drawers and file drawer. Also referred to as a drawer cabinet. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		CM:	30	18	22	105 lb	1:	--	--	--	NO							
			76	46	56	48 kg	2:	--	--	--	NO							
C09F0	6530	Cabinet, U/C/B, 2 Half Drawer, 2 Door, 30" W	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Sitting height under counter base cabinet, 30" H x 36" W x 22" D with two half width drawers above solid hinged doors. Also referred to as a combination cabinet or drawer and cupboard cabinet. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		CM:	30	36	22	115 lb	1:	--	--	--	0							
			76	91	55	53 kg	2:	--	--	--	NO							
C09G0	6530	Cabinet, U/C/B, 1 Shelf, 2 Door, 30x36x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Sitting height under counter base cabinet with one adjustable shelf and solid hinged doors. Also referred to as a cupboard or door cabinet. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		CM:	30	36	22	105 lb	1:	--	--	--	NO							
			76	91	55	48 kg	2:	--	--	--	NO							
C10G0	6530	Cabinet, U/C/B, 1 Shelf, 2 Door, 30x48x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Sitting height under counter base cabinet with one adjustable shelf and solid hinged doors. Also referred to as a cupboard or door cabinet. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		CM:	30	48	22	125 lb	1:	--	--	--	NO							
			76	122	55	57 kg	2:	--	--	--	NO							
CA020	6530	Cabinet, Open, W/H, 2 Shelf, Sloping Top, 38x24x13	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall hung open front cabinet with two adjustable shelves and sloping top. Also referred to as an open case. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		CM:	38	24	13	85 lb	1:	--	--	--	0							
			97	61	33	39 kg	2:	--	--	--	NO							
CA040	6530	Cabinet, Open, W/H, 2 Shelf, Sloping Top, 38x36x13	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall hung open front cabinet with two adjustable shelves and sloping top. Also referred to as an open case. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		CM:	38	36	13	107 lb	1:	--	--	--	NO							
			97	91	33	49 kg	2:	--	--	--	NO							
CA090	6530	Cabinet, Open, W/H, 2 Shelf, Sloping Top, 41x36x16	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall hung open front cabinet with two adjustable shelves and sloping top. Also referred to as an open case. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		CM:	41	36	16	121 lb	1:	--	--	--	NO							
			104	91	41	55 kg	2:	--	--	--	NO							
CA100	6530	Cabinet, Open, W/H, 2 Shelf, Sloping Top, 41x48x16	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall hung open front cabinet with two adjustable shelves and sloping top. Also referred to as an open case. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		CM:	41	48	16	152 lb	1:	--	--	--	NO							
			104	122	41	69 kg	2:	--	--	--	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES										
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5
CB020	6530	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		IN:	38	24	13	102 lb	1:	--	--	--	NO						
		CM:	97	61	33	47 kg	2:	--	--	--	NO						
CB060	6530	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 31x18x16	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility. [Price difference verified.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		IN:	31	18	16	104 lb	1:	--	--	--	0						
		CM:	79	46	41	48 kg	2:	--	--	--	NO						
CC010	6530	Cabinet, W/H, 2 SH, 1 GDO, Sloping Top, 38x18x13	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung cabinet with two adjustable shelves, framed-glass right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a framed-glass single hinged door case. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		IN:	38	18	13	80 lb	1:	--	--	--	NO						
		CM:	97	46	33	37 kg	2:	--	--	--	NO						
CD030	6530	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x30x13	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		IN:	38	30	13	113 lb	1:	--	--	--	NO						
		CM:	97	76	33	52 kg	2:	--	--	--	NO						
CD040	6530	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		IN:	38	36	13	112 lb	1:	--	--	--	0						
		CM:	97	91	33	51 kg	2:	--	--	--	NO						
CE030	6530	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility. [Price difference verified.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		IN:	38	30	13	105 lb	1:	--	--	--	NO						
		CM:	97	76	33	48 kg	2:	--	--	--	NO						
CE040	6530	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x36x13	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:						
EA		IN:	38	36	13	116 lb	1:	--	--	--	NO						
		CM:	97	91	33	53 kg	2:	--	--	--	NO						

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES										
				A	N	A	V	I						
				R	A	F	A	H	1	2	3	4	5	6
CE050	6530	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x48x13	A A A A --	--	--	--	--	--	--	--	--	--	--	--
Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:				
EA	CM:	IN: 38	48	13	139 lb	1: --	--	--	0	NO	--			
		CM: 97	122	33	64 kg	2: --	--	--	NO	NO	--			
CE080	6530	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 41x30x16	A A A A --	--	--	--	--	--	0	NO	--			
Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:				
EA	CM:	IN: 41	30	16	121 lb	1: --	--	--	0	NO	--			
		CM: 104	76	41	55 kg	2: --	--	--	NO	NO	--			
CE090	6530	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 41x36x16	A A A A --	--	--	--	--	--	0	NO	--			
Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:				
EA	CM:	IN: 41	36	16	135 lb	1: --	--	--	0	NO	--			
		CM: 104	91	41	62 kg	2: --	--	--	NO	NO	--			
CG040	6530	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x36x13	A A A A --	--	--	--	--	--	0	NO	--			
Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:				
EA	CM:	IN: 38	36	13	117 lb	1: --	--	--	0	NO	--			
		CM: 97	91	33	54 kg	2: --	--	--	NO	NO	--			
CG050	6530	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x48x13	A A A A --	--	--	--	--	--	--	NO	--			
Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:				
EA	CM:	IN: 38	48	13	142 lb	1: --	--	--	--	NO	--			
		CM: 97	122	33	65 kg	2: --	--	--	NO	NO	--			
CG090	6530	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 41x36x16	A A A A --	--	--	--	--	--	--	NO	--			
Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:				
EA	CM:	IN: 41	36	16	139 lb	1: --	--	--	--	NO	--			
		CM: 104	91	41	64 kg	2: --	--	--	NO	NO	--			
CR020	6530	Cabinet, F/S, 5 Shelf, 1 DO, Sloping Top, 92x24x13	A A A A --	--	--	--	--	--	0	NO	--			
Floor standing storage cabinet with five adjustable shelves, a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a tall case or a tall cabinet. For general purpose storage use throughout the facility.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:				
EA	CM:	IN: 92	24	13	249 lb	1: --	--	--	0	NO	--			
		CM: 234	61	33	113 kg	2: --	--	--	NO	NO	--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
CR070	6530	Cabinet, F/S, 5 Shelf, 1 DO, Sloping Top, 95x24x16	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
<p>Floor standing storage cabinet with five adjustable shelves, a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a tall case or a tall cabinet. For general purpose storage use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
EA	CM:	95	24	16	275 lb	1:	--	--	--	DEPENDENT:	NO	--						
		241	61	41	125 kg	2:	--	--	--									
CS010	6530	Sink, SS, Single Compartment, 7.5x12x12 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--
<p>Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
EA	CM:	20	15	18	19 lb	1:	--	--	--	DEPENDENT:	NO	--						
		51	38	46	9 kg	2:	--	--	--									
CS040	6530	Sink, SS, Single Compartment, 7.5x14x14 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--
<p>Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--				
EA	CM:	8	19	20	19 lb	1:	--	--	--	DEPENDENT:	NO	--						
		20	48	51	9 kg	2:	--	--	--									
CS070	6530	Sink, SS, Single Compartment, 7.5x16x16 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--
<p>Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--				
EA	CM:	8	20	22	27 lb	1:	--	--	--	DEPENDENT:	NO	--						
		19	50	56	13 kg	2:	--	--	--									
CS080	6530	Sink, SS, Single Compartment, 7.5x18x14 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--
<p>Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions. Third source with these dimensions could not be located.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--				
EA	CM:	8	22	20	20 lb	1:	--	--	--	DEPENDENT:	NO	--						
		19	56	50	9 kg	2:	--	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
CS090	6530	Sink, SS, Single Compartment, 7.5x19x16 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
<p>Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:					
EA		IN:	20	22	22	27 lb	1:	--	--	--	DEPENDENT:	NO	--					
		CM:	51	56	56	13 kg	2:	--	--	--								
CS140	6530	Sink, SS, Single Compartment, 10x14x16 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
<p>Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]</p> <p>No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:					
EA		IN:	11	17	22	23 lb	1:	--	--	--	DEPENDENT:	NO	--					
		CM:	27	43	56	11 kg	2:	--	--	--								
CS150	6530	Sink, SS, Single Compartment, 10x19x16 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
<p>Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:					
EA		IN:	10	22	22	32 lb	1:	--	--	--	DEPENDENT:	NO	--					
		CM:	27	56	56	15 kg	2:	--	--	--								
CS180	6530	Sink, SS, Single Compartment, 12x22x16 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
<p>Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:					
EA		IN:	12	25	22	32 lb	1:	--	--	--	DEPENDENT:	NO	--					
		CM:	30	64	56	15 kg	2:	--	--	--								
CS200	6530	Sink, SS, Single Compartment, 12x28x16 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
<p>Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]</p>																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES																	
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6						
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:											
			EA	CM:	24	31	22	36 lb	--	--	--	NO	--											
					61	79	56	17 kg	2:	--	--	NO	--											
CS220	6530	Cupsink												A	A	A	A	--	B	--	--	--	--	--
		A stationary basin, usually mounted in a laboratory counter top or ledge, connected with a drain and provided with a single-service cold water faucet, for drainage of various fluids. The cup-sink is manufactured in a variety of sizes, shapes (round, oval, rectangular), and materials (epoxy resin, stainless steel, polyolefin, and glass). For general purpose use in a lab area. [Dimensions indicated below are for outside dimensions of the cupsink..]																						
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:											
			EA	CM:	9	8	5	7 lb	--	--	--	NO	--											
					23	20	13	4 kg	2:	--	--	NO	--											
CS230	6530	Sink, SS, Double Compartment, 10x14x16 ID												A	A	A	A	--	D	--	--	--	--	--
		Double compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions for each compartment and the dimensions indicated below the description are overall outside dimensions.]																						
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:											
			EA	CM:	10	33	22	39 lb	--	--	--	NO	--											
					27	84	56	18 kg	2:	--	--	NO	--											
CS240	6530	Sink, SS, Single Compartment, 12x14x16 ID												A	A	A	A	--	D	--	--	--	--	--
		Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility. [Just Manufacturing (97483) is the only source found that offers this dimension. Elkay's offers a similar sink but is only 10 inches deep. Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]																						
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:											
			EA	CM:	14	17	22	23 lb	--	--	--	NO	--											
					36	43	56	11 kg	2:	--	--	NO	--											
CS250	6530	Sink, SS, Single Compartment, 6x12x9 ID												A	A	A	A	--	D	--	--	--	--	--
		Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]																						
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:											
			EA	CM:	18	15	15	19 lb	--	--	--	NO	--											
					46	38	38	9 kg	2:	--	--	NO	--											

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
CS260	4510	Sink, Epoxy Resin, 10x25x15 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
<p>One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions. LabTops faucets are provided through their master distributor Town & Country.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	11	26	16	70 lb	1:	--	--	--	NO							
		CM:	28	66	41	32 kg	2:	--	--	--	NO							
CS270	4510	Sink, Epoxy Resin, 11x18x15 ID	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
<p>One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area. [Dimensions indicated in the nomenclature are inside dimensions and the dimensions indicated below the description are outside dimensions.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	12	19	15	62 lb	1:	--	--	--	0							
		CM:	30	48	38	29 kg	2:	--	--	--	NO							
CS275	6525	Sink, Lead Lined, With Decay Storage	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
<p>Lead lined sink and storage module for processing radioactive material (hot-sink). The unit includes a goose neck faucet, a hot and cold water mixing valve, an anti-splash nozzle, a strainer and a drain and overflow system. Two chute openings to the side allow waste to drop into separate stainless steel storage trays (included). The lead shielding will be 1/2" thick on all six sides of the decay section (one of the sides is the divider between the sink and decay sections, another is the right door). The doors have key locks. The database height specification includes the extra height for the gooseneck faucet.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	47	31	31	1,800 lb	1:	--	--	--	0							
		CM:	119	79	79	818 kg	2:	--	--	--	NO							
CT030	6530	Countertop, High Pressure Laminate	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
<p>High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
LF		IN:	5	12	24	14 lb	1:	--	--	--	NO							
		CM:	13	30	61	7 kg	2:	--	--	--	NO							
CT050	6530	Countertop, Stainless Steel	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
<p>Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
LF		IN:	4	12	24	-- lb	1:	--	--	--	NO							
		CM:	10	30	61	-- kg	2:	--	--	--	NO							
CT060	6530	Countertop, Modified Epoxy Resin	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
<p>Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties. [Pricing based on a one linear foot by 30 inch deep countertop.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
LF		IN:	5	12	30	36 lb	1:	--	--	--	NO							
		CM:	13	30	76	17 kg	2:	--	--	--	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
CW030	6530	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 92"x30"	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Floor standing storage cabinet approximately 92" H x 30" W x 13" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility. [Cabinet depth for Model 3 is 16". Atlantic Medco no longer makes the 13" deep model with 92" H x 30" W.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	92	30	13	246 lb	1:	--	--	--	NO							
		CM:	234	76	33	112 kg	2:	--	--	--	NO							
CW040	6530	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 92"x36"	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Floor standing storage cabinet approximately 92" H x 36" W x 13" D, with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility. [Cabinet depth for Model 3 is 16".]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	92	36	13	268 lb	1:	--	--	--	NO							
		CM:	234	91	33	122 kg	2:	--	--	--	NO							
CW050	6530	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 92x48x13	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Floor standing storage cabinet with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	92	48	13	330 lb	1:	--	--	--	NO							
		CM:	234	122	33	150 kg	2:	--	--	--	NO							
CW080	6530	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95x30x16	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Floor standing storage cabinet with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	95	30	16	272 lb	1:	--	--	--	NO							
		CM:	241	76	41	124 kg	2:	--	--	--	NO							
CW090	6530	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95"x36"	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Floor standing storage cabinet approximately 95" H x 36" W x 16" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	95	36	16	293 lb	1:	--	--	--	NO							
		CM:	241	91	41	133 kg	2:	--	--	--	NO							
CW100	6530	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95x48x16	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Floor standing storage cabinet with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility. [Jamestown Metal Products (94881) pricing verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	95	48	16	372 lb	1:	--	--	--	NO							
		CM:	241	122	41	169 kg	2:	--	--	--	NO							
CW130	6530	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 98x30x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
Floor standing storage cabinet with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	98	30	22	312 lb	1:	--	--	--	NO							
		CM:	249	76	56	142 kg	2:	--	--	--	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
CW140	6530	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 98x36x22	A A A A --	--	--	--	--	--	--	--	--	--	--
Floor standing storage cabinet with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA		IN:	98	36	22	343 lb	1:	--	--	--	NO	--	
EA		CM:	249	91	56	156 kg	2:	--	--	--	NO	--	
CW150	6530	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 98"x48"	A A A A --	--	--	--	--	--	0	NO	NO	--	
Floor standing storage cabinet approximately 98" H x 48" W x 22" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA		IN:	98	48	22	422 lb	1:	--	--	--	NO	--	
EA		CM:	249	122	56	192 kg	2:	--	--	--	NO	--	
CX040	6530	Cabinet, Floor Standing, 5 SH, 2 SDO, ST, 92"x36"	A A A A --	--	--	--	--	--	--	NO	NO	--	
Floor standing storage cabinet approximately 92" H x 36" W x 13"D with five adjustable shelves, solid sliding doors, and sloping top. Also referred to as a tall case or full height storage cabinet. For general purpose use throughout the facility.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA		IN:	92	36	13	312 lb	1:	--	--	--	NO	--	
EA		CM:	234	91	33	142 kg	2:	--	--	--	NO	--	
CY090	6530	Cabinet, Floor Stand, 5 SH, 2 SGDO, ST, 95x36x16	A A A A --	--	--	--	--	--	--	NO	NO	--	
Floor standing storage cabinet with five adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a tall case or full height storage cabinet. For general purpose use throughout the facility.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA		IN:	95	36	16	300 lb	1:	--	--	--	NO	--	
EA		CM:	241	91	41	137 kg	2:	--	--	--	NO	--	
CY150	6530	Cabinet, Floor Stand, 5 SH, 2 SGDO, ST, 98x48x22	A A A A --	--	--	--	--	--	0	NO	NO	--	
Floor standing storage cabinet with five adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a tall case or full height storage cabinet. For general purpose use throughout the facility.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA		IN:	98	48	22	427 lb	1:	--	--	--	NO	--	
EA		CM:	249	122	56	194 kg	2:	--	--	--	NO	--	
D0100	6520	Analgesia Unit, Inhalation, Central Gases/Vacuum	C C C C --	B	--	E	C	--	0	NO	NO	--	
Analgesia machine for use in dental treatment areas equipped with centrally piped oxygen, nitrous oxide and oral evacuation (HVE) systems. The unit is used in dental operatories for conscious sedation administration and includes flowmeter heads; hoses with DISS (or other specified) connectors for attaching to house nitrous oxide, oxygen and vacuum systems; and gas scavenger rubber goods. The mobile stand is height adjustable. Electronically controlled flowmeter heads are also available.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA		IN:	53	24	24	35 lb	1:	--	--	--	NO	--	
EA		CM:	135	61	61	16 kg	2:	--	--	--	NO	--	
D0101	6520	Analgesia Unit, Inhalation, Central Vacuum Only	C C C C --	--	--	B	--	--	--	NO	NO	--	
Portable analgesia machine for use in dental treatment areas with central oral evacuation system (HVE), but without piped oxygen or nitrous oxide. The unit is used in dental operatories for conscious sedation administration and includes a manifold, flowmeter heads, hoses for connecting the tanks to regulators, a mobile stand and scavenger rubber goods. Electronic flowmeter heads are also available.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA		IN:	43	24	24	35 lb	1:	--	--	--	NO	--	
EA		CM:	110	61	61	16 kg	2:	--	--	--	NO	--	

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D0270	6520	Cabinet, Base, Sink, Angle Corner, 36x53x24	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
<p>Angle corner base cabinet unit. Used in dental laboratories to hold a casting machine, sink or for general storage. The cabinet has a 13-18" wide front face depending on the manufacturer and its sides will match adjacent cabinet units. The back walls of the cabinet may be shortened so the interior space does not reach all the way back to the wall corner. At its widest point, the largest cabinet found is approximately 53" from apex to apex. Depending on the manufacturer, the unit occupies the first 32-37.5" of wall space out from a room corner along both walls. Some manufacturers' pricing includes the cabinet top.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
			36	91	53	200 lb 91 kg	1:	--	--	--								
			24	61	24		2:	--	--	--								
D0370	6520	Cabinet, Base, Bin Drawer, 2 Drawer, 36x24x24	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
<p>Base unit with three drawers of equal or differing sizes. Top drawer section will accommodate a plaster bin. Used in dental laboratories. The database price and dimension information does not include the countertop.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
			36	91	24	150 lb 69 kg	1:	--	--	--								
			24	61	24		2:	--	--	--								
D0400	6520	Frame, Table, 2 Drawer, 36x40x24	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
<p>Table frame with two drawers. Used in dental laboratories to support work surfaces over open undercounter space. Undercounter drawer units are 4 to 6-1/2 inches high. Unit does not include the countertop. [Units 36" wide or less are normally available in a single drawer configuration. Manufacturers will provide a two draw unit upon request. Frames are also available in 17", 18" and 19" Depth.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
			36	91	40	130 lb 59 kg	1:	--	--	--								
			24	61	24		2:	--	--	--								
D0440	6520	Cabinet, Base, 4 Drawer, 32x20x18	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
<p>Base cabinet unit with four drawers. Unit is used in dental laboratories or surgery areas to store materials. Width and depth dimensions vary slightly by manufacturer.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
			32	81	20	80 lb 37 kg	1:	--	--	--								
			18	46	18		2:	--	--	--								
D0460	6520	Cabinet, Pedestal Base, W/Dust Collector, 25x42x20	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	
<p>Base cabinet for a pedestal workstation which contains a central dust collector serviced through large removable panels or access doors. The dust collector has a 1 HP blower with a minimum of 40 square foot of filter cloth and can supply an effective vacuum for up to four 3 inch diameter dust openings simultaneously. The unit is used in dental laboratories to remove particulate matter from grinding and polishing operations. [The manufacturers recommend this item be on a dedicated circuit. No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	YES	BTUs / HR:	--			
			25	63	42	150 lb 69 kg	1:	120	1	15								
			20	51	20		2:	--	--	--								
D0500	6520	Cabinet, Base, 4 Drawer, 36x18x24	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
<p>Base unit cabinet with four drawers used in dental laboratories. The drawers may be the same or different sizes depending on the manufacturer and the cabinet's use.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
			36	91	18	100 lb 46 kg	1:	--	--	--								
			24	61	24		2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
D0510	6520	Cabinet, Base, Drop Door, Door, 36x24x24	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Base unit storage cabinet. The cabinet has one drop door at the top and a single or double hinged door underneath. It is used in dental laboratories for general storage of equipment and supplies. Database price information is based on the closest standard cabinet plus a 25% surcharge for modification.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	38	24	24	95 lb	1:	--	--	--	0	NO	--						
		CM:	97	61	61	44 kg	2:	--	--	--	NO	NO	--						
D0520	6520	Cabinet, Base, Door, 36x24x24	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Base unit storage cabinet. Unit has a single or double hinged door. Used in dental laboratories for storage sinks or processing equipment.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	36	24	24	80 lb	1:	--	--	--	--	NO	--						
		CM:	91	61	61	37 kg	2:	--	--	--	NO	NO	--						
D0530	6520	Cabinet, Base, 2 Door, 36x36x24	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Base unit storage cabinet. Unit has two hinged doors. Used in dental laboratories for a sink, storage or processing equipment.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	36	36	24	1,050 lb	1:	--	--	--	--	NO	--						
		CM:	91	91	61	477 kg	2:	--	--	--	NO	NO	--						
D0550	6520	Cabinet, Base, Casting Machine, 36x24x24	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Dental laboratory base cabinet designed to hold a casting machine. The unit has a well for the casting machine and a single hinged door. The cabinet also has built-in vibration dampening.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	37	25	24	195 lb	1:	--	--	--	--	NO	--						
		CM:	94	64	61	89 kg	2:	--	--	--	NO	NO	--						
D0660	6520	Frame, Table, 2 Drawer, 1-2 Half Drawer, 36x42x24	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Table frame. The unit has two end full depth drawers and one or two half depth drawer(s) in the center. The table is used in dental laboratories to make a work bench with storage drawers. [All of the manufacturers products will require custom modification to accommodate drawer configuration.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	326	42	24	170 lb	1:	--	--	--	--	NO	--						
		CM:	828	107	61	78 kg	2:	--	--	--	NO	NO	--						
D0664	6530	Cabinet, Wall Hanging, Dental Laboratory, 30x24x12	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Heavy duty steel wall cabinet with adjustable shelves suitable for storage of dental laboratory case pans and dental laboratory equipment. Open front construction, no doors, with adjustable shelves. All components must be rust resistant due to the damp environment. Dimensions and shelf configuration vary by manufacturer. The supporting wall may require reinforcement for mounting this cabinet.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	30	24	13	50 lb	1:	--	--	--	--	NO	--						
		CM:	76	61	33	23 kg	2:	--	--	--	NO	NO	--						
D0666	6530	Cabinet, Wall Hanging, Dental Laboratory, 30x48x12	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Heavy duty steel wall cabinet with adjustable shelves suitable for storage of dental laboratory case pans and dental laboratory equipment. The unit has open front construction (no doors) and adjustable shelves. All components must be rust resistant due to the damp environment. Specific dimensions and shelf configuration vary by manufacturer. The supporting wall may require reinforcement for mounting this cabinet. [These units are painted steel. Stainless steel cabinets are also available.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	30	48	12	85 lb	1:	--	--	--	--	NO	--						
		CM:	76	122	30	39 kg	2:	--	--	--	NO	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
D0710	6520	Countertop, Epoxy Resin	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Modified epoxy resin 3/4" to 1-1/4" thick countertop (depending on vendor) with a back rail and shelf. The service ledge (back rail and shelf) is approximately 6 inches high and 6 inches front to back. The front face of the service ledge can be the base cabinet material (usually painted steel) or epoxy resin. The shelf section is removable to provide access to gas, electrical, and water connections. The database reflects 30" deep countertops priced by the linear foot. The height dimension is from the underside of the working surface to the top surface of the back service ledge. [Price difference verified.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	10	12	30	50 lb	1:	--	--	--	0		NO						
			25	30	76	23 kg	2:	--	--	--	DEPENDENT:		NO						
D0750	6520	Tank Assembly, Boilout	A	A	A	A	--	D	A	--	--	A	E						
Drop-in boil-out tank assembly. The unit consists of a stainless steel tank with cover, heat rectifier assembly, gas burner and adjustable thermostat and is used in dental laboratories. The bench top cut out size is approximately 10-7/8" wide x 16-7/8" deep. This unit requires a cabinet for mounting. [No other source(s) identified with this description/specification. When ordering Model 2 must specify natural or propane gas. Electric models are also available.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	24	14	18	175 lb	1:	120	1	5	60		NO						
			61	36	46	80 kg	2:	--	--	--	DEPENDENT:		YES						
D0753	6520	Tank Assembly, Curing	C	C	C	C	--	D	A	--	--	A	E						
Stainless steel sink unit for curing denture material. The sink is approximately 10" wide x 14" deep x 12" deep and uses gas heating elements. The unit requires an appropriate cabinet for mounting. [Double sink and electric models are also available depending on the manufacturer.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	24	14	18	175 lb	1:	120	1	5	60		NO						
			61	36	46	80 kg	2:	--	--	--	DEPENDENT:		YES						
D0755	6520	Assembly, Boilout/Curing, Double	A	A	A	A	--	D	A	--	--	A	E						
Two basin washout and boil-out tank assembly with stainless steel tanks and gas heating elements. The unit includes a recirculating pump, wax trap and drain valve. The assembly requires an appropriate cabinet for support. [No other source(s) identified with this description/specification. Electric models are available depending on the manufacturer.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	24	24	18	100 lb	1:	120	1	5	60		NO						
			61	61	46	46 kg	2:	--	--	--	DEPENDENT:		NO						
D0760	6520	Guard, Casting Machine	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Casting machine guard (well) and rim. The well is a minimum 13" deep and 19" in diameter. The well is stainless or heavy duty rust resistant steel with a rim to match the guard to the casting cabinet working surface. The unit is used in dental laboratories as an insert in a cabinet to preclude casting material from becoming a projectile if the casting equipment fails. Height and diameter dimensions vary slightly depending on the manufacturer. [Price variance verified.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	14	19	19	65 lb	1:	--	--	--	--		NO						
			36	48	48	30 kg	2:	--	--	--	DEPENDENT:		NO						
D0791	6520	Sink, SS, 18 Gauge, 11x14x14	A	A	A	A	--	D	--	--	--	--	--						
Stainless steel sink assembly. The sink is made of 18 gauge stainless steel and includes a mixing faucet and strainer or standpipe. The sink is used in dental laboratories.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	11	14	14	15 lb	1:	--	--	--	0		NO						
			28	36	36	7 kg	2:	--	--	--	DEPENDENT:		NO						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D0792	6520	Sink, SS, Without Faucet, 8x14x10	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
Stainless steel sink assembly. The sink is used in dental areas as a hand wash station. The sink depth varies slightly by manufacturer. The unit includes a strainer.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	9	17	12	10 lb	1:	--	--	--	NO		--					
		CM:	23	43	30	5 kg	2:	--	--	--	NO		--					
D0795	6520	Sink, CRS, 18 Gauge, With Faucet, 11x18x14	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
Corrosion resistant sink. The unit can mount from under the bench top or be a self-rimming drop-in unit. The faucet is ordered as a separate item from most manufacturers. Sink dimensions vary slightly by vendor.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	12	21	20	20 lb	1:	--	--	--	NO		--					
		CM:	30	53	51	9 kg	2:	--	--	--	NO		--					
D0800	6520	Sink, SS, With Faucet, Standpipe	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
Stainless steel sink assembly for use in dental laboratories. The sink is fitted with a mixing faucet and a standpipe or strainer. The inside sink dimensions are approximately 12" x 19" x 16". The outside sink dimensions vary slightly by manufacturer.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	12	19	16	28 lb	1:	--	--	--	NO		--					
		CM:	30	48	15	1 kg	2:	--	--	--	NO		--					
D0810	6520	Sink, SS, 10x14x10	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
Stainless steel sink used in dental laboratories. The unit includes a faucet and sink strainer. [Only one manufacturer was found that specifically made a 14" x 10" inch stainless steel sink compartment with a 10" inch basin depth.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	14	10	9 lb	1:	--	--	--	NO		--					
		CM:	25	36	25	4 kg	2:	--	--	--	NO		--					
D0811	6520	Valve, Water, Foot, With Faucet	A	A	A	A	--	A	--	--	--	--	--	--	--	--	--	
Foot operated water control valve for turning hot and cold water on and off in at a remote sink. Used in medical and dental laboratories for hands-free water control.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	12	12	6	10 lb	1:	--	--	--	NO		--					
		CM:	30	30	15	5 kg	2:	--	--	--	NO		--					
D0820	6520-01-173-2450	Cleaner, Ultrasonic, 6 Quart Capacity	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Dental instrument ultrasonic cleaner with a six quart capacity. The unit is used to clean dental instruments after use and before sterilizing. The cleaner includes an energy selection switch, drain system, drip tray and lower basket.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	11	13	7	14 lb	1:	120	1	4	NO		--					
		CM:	28	33	18	7 kg	2:	--	--	--	YES		--					
D0840	6520	Tank Assembly, Washout/Boilout	A	A	A	A	--	D	A	--	--	A	E					
Washout and boil-out tank assembly. The assembly has a single stainless steel tank and is used in dental laboratories to remove molding material from the casting. The unit is gas fired and includes four swing spouts, a pump, valves, a safety switch, a thermostat and a solenoid. The unit requires an appropriate cabinet for mounting. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	18	14	100 lb	1:	120	1	5	NO		--					
		CM:	26	46	36	46 kg	2:	--	--	--	YES		14,000					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
D0860	6520	Light, Bench, Dental	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Bench light. Used on dental prosthetic laboratory benches. The database physical dimensions refer to the reach of the lamp arm.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
EA		CM:	42	42	42	17 lb	1:	120	1	2	50/60	YES	NO	--					
			107	107	107	8 kg	2:	--	--	--				--					
D0870	6520	Hood, Collecting, Dust, 17x29x21	A	A	A	A	--	--	A	B	--	--	--	--	--	--	--	--	
Dust collecting hood for pumice polishing in dental laboratories. The hood is constructed of copper or heavy gauge sheet steel with a silver enamel finish. It has a light switch, incandescent lamp(s) and removable pumice pans. The hood removes between 200 and 365 cubic feet per minute of air volume with a velocity of approximately 4000 feet per minute through a 3 inch duct. [No other sources(s) identified with this description/specification. Grinding polishing stations are identified under JSNs D0970 and D0980. See JSN D0880 for the blast gate to connect this hood to a vacuum system.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
EA		CM:	13	29	21	54 lb	1:	120	1	10	60	NO	YES	--					
			33	74	53	25 kg	2:	--	--	--				--					
D0880	6520	Blast Gate, Vacuum System	A	A	A	A	--	--	--	B	--	--	--	--	--	--	--	--	
Blast gate for use with a bench or central vacuum system in a dental or other laboratory. The unit consists of a sliding panel in a frame which allows air to flow toward a vacuum source when the panel is opened. The gate is usually mounted in the vertical face of a laboratory bench service ledge. The front and back faces have flanges which adapt for the 3" hoses in the vacuum system. The gate is usually finished in baked enamel.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
EA		CM:	4	7	3	4 lb	1:	--	--	--	0	NO	NO	--					
			10	18	8	2 kg	2:	--	--	--				--					
D0881	6520	Hood, Fishmouth	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Fish-mouth shaped hood for attachment to a vacuum system in a dental laboratory. The hood is designed to fit around a grinding or polishing wheel mounted to an electric motor. The hood shapes the air flow around the wheel so the metal and dust particles spun from the wheel are sucked into the bench or central vacuum system.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
EA		CM:	15	8	15	5 lb	1:	--	--	--	0	NO	NO	--					
			38	20	38	3 kg	2:	--	--	--				--					
D0900	6520	Workstation, Dental Lab, Receiving	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Modular workstation for receiving supplies in a dental laboratory. The unit stands on the floor and consists of a 24" wide base cabinet unit with 4 drawers, a 24" wide single or double door base cabinet unit with an adjustable shelf and a 74" wide laminate counter supported by the two base cabinets. The working space between the two cabinets contains an undercounter single drawer unit. [Nevin includes the work surface as part of the cabinetry.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
EA		CM:	34	74	24	460 lb	1:	--	--	--	--	NO	NO	--					
			86	188	61	209 kg	2:	--	--	--				--					
D0904	6520	Workstation, Tech, Dental, Lab, Single Station	F	F	F	F	--	--	A	D	--	A	--	--	--	--	--	--	
Modular technician's workstation for the dental laboratory. The workstation features integrated gas, air, and electrical lines which all connect to building supplies from a single utility panel. The unit contains an overhead task lighting (approx. 3000 Lux) array. The workstation also includes a dust extraction system with filtration, a minimum of 4 drawers for storage, an air gun, a gas valve for a Bunsen burner and electrical outlets for accessory equipment. The desktop is made from a fiber/cement mixture or similar material to resist heat, abrasion, and chemical attack. This unit has a standard length work surface that varies among manufacturers but is nominally 43". Depending on the manufacturer, workstation package configurations may include seating and other minor accessories. The workstation may require more than one electrical connection to the facility power grid to run the equipment used on the bench. See JSN D0975 for an extended length workstation.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
EA		CM:	78	46	24	339 lb	1:	120	1	20	60	NO	YES	4,500					
			198	117	61	154 kg	2:	--	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D0905	6520	Workstation, Dental Lab, Four Station	A	A	A	A	--	--	A	D	--	A	--					
General purpose, modular dental laboratory workstation configuration which accommodates 4 technicians. The station of the unit includes a full-length, load-bearing steel frame on adjustable legs with end panels and supports, overhead task lighting (approx. 3000 lux, natural daylight), a storage cabinet with 4 drawers (each drawer with an insert), a stainless steel debris drawer, a Bunsen burner, an air gun and a bench mounted work tray holder. The dust extraction system has 4 units: 3 for dust and 1 for precious metal recovery. The working counter is made from a fiber/cement mixture or similar material to resist heat, abrasion, and chemical attack. Multiple connections to the hospital electrical system will be necessary to power the equipment used in this workstation.			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	78	87	48	1,500 lb	1:	120	1	80	60	NO	--			
			EA	CM:	198	221	122	681 kg	2:	--	--	--	60	YES	--			
D0910	6520	Workstation, Dental Lab, Metal Grinding	A	A	A	A	--	--	A	D	--	A	--					
Modular metal grinding workstation for a dental laboratory which includes a full-length load-bearing steel frame on adjustable legs with end panels and supports, a 3-drawer storage cabinet, a 4-drawer storage cabinet with instrument inserts, a cast cement/fiberglass countertop, overhead task lighting (3000 lux, natural daylight), an air gun and a dust extraction unit for a bench lathe (Beryllium filter). [Freuding Labors (CAGE SR113) was able to provide a quote from generic line drawings but not an exact illustration of their configuration.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	78	87	24	551 lb	1:	120	1	20	60	NO	--			
			EA	CM:	198	221	61	250 kg	2:	--	--	--	60	YES	--			
D0915	6520	Workstation, Dental Lab, Ceramic, Modular	A	A	A	A	--	--	A	D	--	A	--					
Modular dental laboratory ceramic workstation which includes a full-length load-bearing steel frame on adjustable legs with end panels and supports, an extension table, a 4-drawer storage cabinet with instrument inserts, a 4-drawer storage cabinet with inserts for ceramic powders and liquids, a cast cement/fiberglass countertop, overhead task lighting (3000 lux, natural daylight), an air gun and a micro-filter (ceramic) extraction unit for a stainless steel debris drawer. Some manufacturers' package configurations for this JSN include seating and other accessories. [Freuding Labors (CAGE SR113) was able to provide a quote from generic line drawings but not an exact illustration of their configuration.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	78	87	24	350 lb	1:	120	1	20	60	NO	--			
			EA	CM:	198	221	61	159 kg	2:	--	--	--	60	YES	--			
D0920	6520	Workstation, Dental Lab, Floor Standing	A	A	A	A	--	D	--	--	--	--	--	--				
Floor standing ceramic workstation which includes 2 floor standing cabinets with adjustable shelves, a floor standing cabinet with 4 drawers and inserts, a stainless steel sink (16"Lx16"Wx8"D) with faucet and a steel or plastic laminate counter top. [Freuding Labors (CAGE SR113) was able to provide a quote from generic line drawings but not an exact illustration of their configuration.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	36	87	24	475 lb	1:	--	--	--	--	NO	--			
			EA	CM:	91	221	61	216 kg	2:	--	--	--	--	NO	--			
D0925	6520	Hood, Fume, Dental Acrylic, Floor Standing	A	A	A	A	--	D	A	--	--	--	E					
Floor-standing fume hood workstation for processing acrylic dental resins. The fume hood is constructed of PVC plastic or other material resistant to acids and aggressive chemicals. The hood features built-in lighting, an extraction fan and a water channel for rinsing materials and containers. The hood has a counter-balanced vertically sliding front protective window. The database height dimension refers to the unit only. Add approximately 22" more to provide the clearance needed to open the window. [Freuding Labors (CAGE SR113) was able to provide a quote from generic line drawings but not an exact illustration of their configuration.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	73	48	27	370 lb	1:	120	1	7	60	NO	--			
			EA	CM:	185	122	69	168 kg	2:	--	--	--	60	YES	--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D0930	6520	Workstation, Dental Lab, Casting	A	A	A	A	--	--	A	--	--	--	--	E				
Modular casting workstation which includes a full-length load-bearing aluminum frame on adjustable legs with side panels and supports, an overhead stainless steel ventilation canopy hood (options include a start delay and 99 hour timer), a furnace shelf (48"Lx16"D), a pull-out casting ring cooling drawer with steel grid and a ceramic tile countertop. [Freuding Labors (CAGE SR113) was able to provide a quote from generic line drawings but not an exact illustration of their configuration.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	84	79	29	675 lb	1: 120	1	10	60	NO	YES	--					
			213	201	74	307 kg	2: --	--	--									
D0935	6520	Workstation, Dental Lab, Investment	A	A	A	A	--	D	A	C	--	--	--					
Modular investing workstation which includes a full-length load-bearing aluminum frame on adjustable legs with end panels and supports, 3 base cabinets with doors, a base cabinet with 3 drawers, an air gun, a stainless steel sink (7.5hx16wx16d) with a plaster trap and a mixing faucet (cold and warm), a waste disposal unit with scraper, and a corrosion resistant table top. [Model 3 is wall mounted.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	37	97	24	765 lb	1: --	--	--	0	NO	NO	--					
			94	246	61	348 kg	2: --	--	--									
D0940	6520	Workstation, Dental Lab, Equipment Bench	A	A	A	A	--	--	--	--	--	--	--					
Modular workstation for investment equipment which includes 2 floor-mounted single or double door storage cabinets with adjustable shelves and a cast cement/fiberglass counter top.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	36	47	24	250 lb	1: --	--	--	0	NO	NO	--					
			91	119	61	114 kg	2: --	--	--									
D0942	6520	Workstation, Dental Lab, Microblasting	F	F	F	F	--	--	A	D	--	--	--					
Complete micro-blaster and dust extraction device integrated into a 34" high x 24" wide x 24" deep (nominal) cabinet. The micro-blaster can use 25 to 250 micron aluminum oxide, sand, glass bead or walnut shell abrasives. The unit includes micro-blasting pencils, canisters for clean blasting, one recirculating nozzle for gross blasting, an air chisel, an air nozzle and a protective safety shield. The micro-blaster connects to a dust extraction system suitably sized for the micro-blaster. [Model 1 must sit on a workstation. Price difference verified.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	52	36	30	250 lb	1: 120	1	10	60	NO	NO	--					
			132	91	76	114 kg	2: --	--	--									
D0945	6520	Workstation, Dental Lab, Surveying / Milling	A	A	A	A	--	--	--	--	--	--	--					
Floor standing modular workstation for surveying and milling in a dental laboratory. The workstation includes three 24" wide single or double door floor cabinets with one adjustable shelf each, a 24" wide floor cabinet with 4 drawers, two undercounter single drawer units, end panels and a plastic laminate countertop. The countertop may be in two sections later joined at the site because of design, weight and handling restrictions.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	36	145	24	980 lb	1: --	--	--	--	NO	NO	--					
			91	368	61	445 kg	2: --	--	--									
D0950	6520	Workstation, Dental Lab, Acrylic Processing	A	A	A	A	--	--	--	--	--	--	--					
Modular workstation for acrylic processing in a dental laboratory. The unit is comprised of 2 single or double door base cabinets with an adjustable shelf each, a base cabinet with 5 drawers, a base cabinet with 3 drawers and a plastic laminate countertop. [Freuding Labors (CAGE SR113) was able to provide a quote from generic line drawings but not an exact illustration of their configuration.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	36	96	24	615 lb	1: --	--	--	--	NO	NO	--					
			91	244	61	280 kg	2: --	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES										
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5
D0955	6520	Workstation, Dental Lab, Acrylic Curing	A	A	A	A	--	--	A	--	--	--	--	--	--	--	E
Modular workstation for curing acrylic dental materials. The unit consists of a load-bearing metal frame on adjustable legs with end panels and supports, an overhead stainless steel extraction ventilation canopy with a built-in fan and a start delay timer. A plastic laminate countertop covers the top of the metal frame. The wall may require reinforcing to support the ventilation canopy. [Freuding Labors (CAGE SR113) was able to provide a quote from generic line drawings but not an exact illustration of their configuration.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	33	50	24	-- lb	1:	120	1	10	NO		--				
		CM:	84	127	61	-- kg	2:	--	--	--	YES		--				
D0960	6520	Workstation, Dental Lab, Plaster	A	A	A	A	--	D	A	D	--	--	--	--	--	--	--
Floor standing plaster workstation which includes 2 single door base cabinets with adjustable shelves, 2 base cabinets with 4 drawers each, a double wide base cabinet with a single door on one side and 2 drawers on the other, a stainless steel sink (16"Lx16"Wx8"D) with a mixing faucet and plaster trap, a stainless steel sink (32"Lx16"Wx8"D) with a model trimmer support shelf, a cold water valve for the trimmer, a mixing faucet and plaster trap, a stainless steel countertop with rolled edges and a waste disposal unit. The utility ledge contains electrical outlets as needed. [All models consist of multiple components. Only one manufacturer, Nevin Laboratories (Model 2) could be found with a stainless steel counter top. Model 2 and 3 do not come with a waste disposal unit that must be ordered separately.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	38	145	24	950 lb	1:	--	--	--	NO		--				
		CM:	97	368	61	432 kg	2:	--	--	--	NO		--				
D0965	6520	Plaster Dispensing System, Dental Lab, Power, W/M	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--
Wall mounted dispensing system for dental plasters, alginates and stone modeling powders. The unit consists of a wall rail, stainless steel or plastic holding bins and a hoist. The hoist lowers the individual bins to the floor for refilling and then lifts the filled bins back up for remounting on the wall rail. Each bin mount has an electric motor for agitating the plaster in the bins while its being dispensed. Multiple electrical outlets may be needed for this unit. The wall to which the unit is mounted will require reinforcing to support the unit's weight. The database information reflects the data for a three bin unit filled with plaster powder; two and four bin units are available. [This is the only manufacturer found for this item. See JSN D8620 for standard counter or wall mounted plaster bins filled by using a ladder or stepstool. Freuding Labors (SR113) has power agitated plaster bins filled from a service stairwell behind the wall.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	43	69	18	655 lb	1:	120	1	15	NO		--				
		CM:	109	175	46	298 kg	2:	--	--	--	YES		--				
D0970	6520	Workstation, Dental Lab, Polishing, 2 Station	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--
Modular 2 station polishing workstation which includes a full-length load-bearing table or cabinet on adjustable legs with end panels and supports, a stainless steel countertop with rolled edges, with integrated 2 speed motor, lighting, a dust extraction unit for wet and dry polishing and a removable waste tray. See JSN D0980 for a single station polishing unit. [No other source (s) identified with this description/specification.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	58	48	24	285 lb	1:	120	1	30	NO		--				
		CM:	147	122	61	130 kg	2:	--	--	--	YES		--				
D0975	6520	Workstation, Dental Lab, Die Trimming	A	A	A	A	--	--	A	D	--	A	--	--	--	--	--
Modular die trimming workstation which includes a full-length load bearing steel frame on adjustable legs with end panels and supports, overhead task lighting (3000 lux, natural daylight), 2 storage cabinets with 4 drawers and inserts, an adjustable air pressure and air gun, a dust extraction unit with particle filter, a collection hood and stainless steel debris drawer and a cast cement/fiberglass countertop. [No other source(s) identified with this description/specification.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	78	57	24	396 lb	1:	120	1	15	NO		--				
		CM:	198	145	61	180 kg	2:	--	--	--	YES		--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D0980	6520	Workstation, Dental Lab, Polishing, Single	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Modular polishing workstation with a full-length load-bearing table frame or cabinet on adjustable legs including end panels and supports, a stainless steel countertop with rolled edges, a built-in polishing unit with an integrated 2 speed motor, lighting, a dust extraction unit for wet and dry polishing and a removable waste tray. [Model 1 discontinued its cabinet model and now only provides the polishing unit. Model 3 comes only in a bench or table top model. Model 2 was the only manufacturer found that continues to make a cabinet/workstation model.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	56	37	24	325 lb	1:	120	1	15	60	NO	--			
			EA	CM:	142	94	61	148 kg	2:	--	--	--	DEPENDENT:	YES	--			
D2520	6520	Cabinet, Mobile, Storage/Assistant, Dental	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Mobile storage cabinet used in dental spaces. Multiple drawer and cupboard configurations are available. Specific configurations with sliding shelves or tops are often called Alabama and North Carolina.			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	34	22	18	150 lb	1:	--	--	--	--	NO	--			
			EA	CM:	86	56	46	69 kg	2:	--	--	--	DEPENDENT:	NO	--			
D2535	6520	Welder, Tack, Orthodontic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Orthodontic tack welder. Used in dental laboratories to repair and assemble orthodontic appliances.			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	8	12	10	14 lb	1:	120	1	15	60	NO	--			
			EA	CM:	20	30	25	7 kg	2:	--	--	--	DEPENDENT:	YES	--			
D2540	6520-00-511-6350	Casting Machine, Manual, Broken Arm	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Broken arm manual casting machine. The unit is used in dental laboratories to cast precious and non-precious type II/III metals. The unit must be enclosed in a guard well (JSN D0760) sized to accommodate the specific machine.			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	13	20	20	20 lb	1:	--	--	--	--	NO	--			
			EA	CM:	33	51	51	9 kg	2:	--	--	--	DEPENDENT:	NO	--			
D2550	6520	Casting Machine, Electric, Chrome/Cobalt	C	C	C	C	--	B	C	--	--	--	--	--	--	--	--	--
Chrome/cobalt casting machine. The unit employs electrical melting methods. The unit can be stand mounted or bench mounted. The database height dimension includes the clearance needed to open to cover. [Model 1 uses a gas torch melting technique with a vacuum.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	38	31	27	176 lb	1:	230	1	20	50/60	NO	--			
			EA	CM:	96	79	69	80 kg	2:	110	1	5	DEPENDENT:	YES	--			
D2560	6520	Casting Machine, Induction, Free Standing	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	--
Microprocessor controlled electronic induction casting machine. The unit is used in dental laboratories for casting all dental alloys and has an argon gas option to protect the alloys from oxidation. [Model 1 requires a dedicated circuit.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	41	31	27	364 lb	1:	230	1	20	60	NO	--			
			EA	CM:	104	79	69	166 kg	2:	--	--	--	DEPENDENT:	YES	--			
D2580	6520-01-234-0255	Casting Machine, Induction, Bench Mounted	C	C	C	C	--	--	D	--	--	--	--	--	--	--	--	--
Bench mounted, microprocessor controlled induction casting machine. The unit is designed for safe clean casting of precious and non-precious dental alloys. The machine features automatic temperature control through a range of 900 to 1800 degrees C (1652 to 3272 degrees F), a built-in optical pyrometer, a self-contained water cooling system and variable casting arm acceleration rate. The unit is designed for mounting on a low bench to bring it up to counter height for easy use. [The Jelenko CL-I-95, requires a space of 44 x 21 inches. No other source(s) identified with this description/specification. See JSN:D2560, Induction casting machines that are free standing/ floor models.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
			EA	IN:	44	22	29	375 lb	1:	208	1	17	50/60	YES	--			
			EA	CM:	112	56	74	171 kg	2:	120	1	26	DEPENDENT:	NO	--			

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
D3250	6520-00-110-5545	Chair, Operating, Dental, Without Unit Mount	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Dental operating chair. Used in dental operatories to position patients during dental procedures. This unit is as specified in the Federal Standard Supply Catalog. [See related chairs at JSNs D3300 and D3320.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:				
EA		IN:	63	27	78	380 lb	1:	120	1	15	HZ SWITCH: YES		--		
EA		CM:	160	69	198	172 kg	2:	--	--	--	DEPENDENT: NO		--		
D3290	6520	Soldering Unit, Precision	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Precision soldering unit. Used in dental laboratories for all types of soldering requirements.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:				
EA		IN:	10	10	10	25 lb	1:	120	1	8	HZ SWITCH: NO		3,500		
EA		CM:	25	25	25	12 kg	2:	--	--	--	DEPENDENT: YES		3,500		
D3295	6520	Chair, Rotary, Laboratory, Dental	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: --		BTUs / HR:				
EA		IN:	36	22	27	27 lb	1:	--	--	--	HZ SWITCH: NO		--		
EA		CM:	91	56	69	13 kg	2:	--	--	--	DEPENDENT: NO		--		
D3300	6520	Chair, Radiographic, Dental	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Dental x-ray chair. This chair is used in intraoral dental radiography and can be used as any dental chair, and is equipped with adjustable height capability. Standard dental operator chairs can be used for this purpose and may enhance clinical uniformity. Specify color at time of ordering.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:				
EA		IN:	64	28	75	350 lb	1:	120	1	12	HZ SWITCH: NO		--		
EA		CM:	163	71	58	159 kg	2:	--	--	--	DEPENDENT: YES		--		
D3310	6520	Chair, Procedure, Dental	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Dental procedure chair/table. Used in oral surgery to place the patient in any position between upright and prone. Unit comes in multiple colors and can be equipped with restraining straps, rails, IV pole and arm-boards. This unit does not have the connections needed to power a dental utility center from the chair base.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:				
EA		IN:	64	225	96	3,325 lb	1:	120	1	12	HZ SWITCH: NO		--		
EA		CM:	163	572	244	1,510 kg	2:	--	--	--	DEPENDENT: YES		--		
D3320	6520	Chair, Operating, Dental	C C C C --	B	A	H	--	--	--	--	--	--	--	--	--
Dental operating chair designed for the treatment and comfort of dental patients. The chair shall be capable of multiple positions, shall swivel, contain a adjustable headrest and arm rests that pivot up and down. The chair shall operate by means of electrohydraulics. The upholstery shall be seamless with no crevices to catch debris and be easy to clean.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:				
EA		IN:	68	27	80	280 lb	1:	120	1	12	HZ SWITCH: NO		--		
EA		CM:	173	69	203	128 kg	2:	--	--	--	DEPENDENT: NO		--		
D3380	6520	Stool, Operating, Dental, Doctor	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Dental operating stool. Used by the dentist in the care and treatment of patients. This chair has a gas cylinder to adjust the height of the chair. It also has backrest as an integral part of the unit. The unit is to be equipped with casters. Various color combinations of vinyl or fabric are available.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: --		BTUs / HR:				
EA		IN:	36	22	22	35 lb	1:	--	--	--	HZ SWITCH: NO		--		
EA		CM:	91	56	56	16 kg	2:	--	--	--	DEPENDENT: NO		--		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D3390	6520	Stool, Operating, Dental, Assistant	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Dental assistant's operating stool used in dental operatories during procedures. This chair has a body support arm or abdominal support that can be left or right hand adaptable. It is also gas cylinder operated for height adjustments. The chair is available in multiple vinyl or fabric color combinations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	33	22	22	44 lb	1:	--	--	--	NO							
		CM:	84	56	56	20 kg	2:	--	--	--	NO							
D3550	6520	Evacuation System, Laboratory, Dental	A	A	A	A	--	--	G	--	--	--	--	--	--	--	--	--
High vacuum laboratory evacuation station. The system is used in dental laboratories to provide a vacuum for up to twelve 3 inch suction inlets throughout the laboratory. The unit has a suction capacity of 1800 cubic feet per minute. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	80	46	36	1,000 lb	1:	220	3	30	NO							
		CM:	203	117	91	454 kg	2:	--	--	--	YES							
D3560	6520-00-597-7749	Curing Unit, Denture, 2 Stage	C	C	C	C	--	--	D	--	--	--	--	--	--	--	--	--
Two stage denture curing unit. The unit is used in dental laboratories to polymerize heat cured denture resins. The unit is a two stage, two flask capacity unit with a temperature range of 90 to 212 degrees Fahrenheit. The unit timer ranges from 15 minutes to 23 hours and automatically shuts the unit off at the completion of its cycle. The oven has a safety thermostat to preclude hazardous temperature levels. The unit also has removable covers and tanks. [KAVO's (CAGE 0PPY4) unit is 208V; Astron's unit is 120V. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	16	12	18	46 lb	1:	120	1	12	NO							
		CM:	41	30	46	21 kg	2:	208	1	12	YES							
D3565	7310	Resin Curing Unit, Visible Light	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Visible light resin curing unit which provides a high intensity, cold light source of visible blue light for the polymerization of all visible light cured materials. The unit provides for time selections between 10 and 60 seconds or continuous operation and beeps at ten or twenty second intervals during use.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	12	12	8	5 lb	1:	120	1	1	NO							
		CM:	30	30	20	3 kg	2:	--	--	--	NO							
D4001	6520	Compressor, Dental Air, System	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Dental air compressor system. Two or more equally sized compressors, with provisions for automatic, alternating and simultaneous operation shall be provided for dental air (DA). Each compressor is to be sized to operate at 65% duty cycle for maintenance of standard demand. Dental compressed air (DCA), 90 PSIG, is used for utility control in dental units, power for lifts, locks, rotary and other pneumatic dental instruments and equipment. DCA shall be oil-free air with the following air standards as maximums: Water - dry to a pressure dew point of 33 degrees F at not less than 90 PSIG; Condensed hydrocarbons - 0.1ppm by weight or 0.1 mg/L; Permanent particulates - 1.0 ppm by weight or 1.0 mg/L. Dental lab air (DLA), 30 PSIG, which is normally used for laboratory restorative and fabrication techniques may be combined with DCA. The system consists of, but not limited to, the following: compressor intake filters, compressors, after-coolers (air cooled), air receiver, pre-filter, dryer (refrigerated), after-filter. Pricing, electrical data and dimensions based upon 16-17 DTRs , each pump sized at approximately 17.5 cfm @ 100 PSIG. Other sizes and configurations are available to meet specified demands.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	61	90	57	2,575 lb	1:	230	3	22	NO							
		CM:	155	229	145	1,169 kg	2:	--	--	--	NO							
D4080	6520-00-519-8000	Curing Unit, Denture, 3 Stage	C	C	C	C	--	--	D	D	--	--	--	--	--	--	--	--
Three stage denture curing unit used in dental laboratories to polymerize heat-curing dental resins. The unit has a three stage, fifteen flask capacity unit with a temperature range of 105-212 degrees Fahrenheit. The controls provide for two time and temperature settings. The timer can be adjusted from 15 minutes to 23 hours. One unit requires an air supply to function properly. Depending on the manufacturer, the unit will operate on 120V or 220V power. The database height dimension includes the clearance necessary for opening one unit's attached cover. Mobile cabinet units are also available. [No other source(s) identified with this description/specification.]																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE: EA	HEIGHT IN: CM:	WIDTH 24 61	DEPTH 23 58	WEIGHT 100 lb 46 kg	VOLTS 1: 2:	PHASE 1 1	AMPS 12 20	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --			
D4100	6520	Cleaner, Steam, Dental	C	C	C	C	--	D	D	--	--	--	--		
Dental steam cleaner. The cleaner has a variable temperature control and is capable of generating up to 80 PSI of pressure. The unit is used for flushing out dirt, debris, wax and polishing compounds from models, dentures, impression trays and instruments. [Price difference verified. No other source (s) identified with this description/specification.]															
			UNIT OF ISSUE: EA	HEIGHT IN: CM:	WIDTH 21 54	DEPTH 16 41	WEIGHT 29 lb 13 kg	VOLTS 1: 2:	PHASE 1 1	AMPS 13 30	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --			
D4220	6520-00-582-5486	Suction Apparatus, Dental	C	C	C	C	--	--	A	--	--	--	--		
Mobile dental suction apparatus. Also called an aspirator. Used in dental clinics for aspirating blood, saliva and other fluids during surgery. Unit produces 635 millimeters of mercury of suction. [General purpose aspirators are also available at JSN M8755 and M8770.]															
			UNIT OF ISSUE: EA	HEIGHT IN: CM:	WIDTH 33 84	DEPTH 17 43	WEIGHT 72 lb 33 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 8 --	HZ: 60 HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --			
D4260	6520	Handpiece, Laboratory, Dental, Electric	C	C	C	C	--	--	A	--	--	--	--		
Portable dental laboratory handpiece. The unit has a straight handle and is electrically powered. The handpiece includes a controller and power cables. Unit is used to grind, polish or finish precious and non-precious metal alloys. [See the similar handpiece units at JSNs D4560 and D6550.]															
			UNIT OF ISSUE: EA	HEIGHT IN: CM:	WIDTH 4 10	DEPTH 6 16	WEIGHT 6 lb 3 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 2 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --			
D4261	6520	Handpiece, Laboratory, Dental	C	C	C	C	--	--	--	D	--	--	--		
Dental laboratory handpiece. Unit is a straight type and is air powered. It includes hoses, filter, a regulator, a hanging bracket and foot control. Unit is used to grind, polish or finish precious and non-precious metal alloys, chrome-cobalt alloys and porcelain surfaces.															
			UNIT OF ISSUE: EA	HEIGHT IN: CM:	WIDTH 4 10	DEPTH 6 15	WEIGHT 7 lb 4 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 24 --	HZ: -- HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --			
D4262	6515	Drill System, Surgical, Oral, Electric Drive	C	C	C	C	--	--	A	--	--	--	--		
Electrically powered surgical drill system. The system features stainless steel construction of handpieces, drills and reamers. The manufacturers offer a series of power units and cutting instruments. The database price reflects a control console, handpiece cable, footswitch and a selection of three handpieces. [Model 1 system is priced with one handpiece with others as options. Buffalo Supply (Cage Code AM252) is a distributor for Stryker Instruments who do not sell direct. Prices will vary based on handpieces selected.]															
			UNIT OF ISSUE: EA	HEIGHT IN: CM:	WIDTH 4 10	DEPTH 9 23	WEIGHT 5 lb 3 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 2 --	HZ: 60 HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --			
D4263	6515	Drill System, Surgical, Oral, Nitrogen Drive	C	C	C	C	--	--	--	B	--	--	--		
Nitrogen powered surgical drill system. The handpiece features stainless steel construction. The system has a variety of reciprocating or rotary saw and drill heads. The database price reflects a handpiece cable, footswitch and a selection of three handpieces. [No other source(s) identified with this description/specification. Stryker (CAGE 1CH83), who has a complete electrically powered system (see JSN D4262).]															
			UNIT OF ISSUE: EA	HEIGHT IN: CM:	WIDTH 2 5	DEPTH 2 5	WEIGHT 2 lb 1 kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	HZ: -- HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
D4310	6520	Press, Flask, Pneumatic	C	C	C	C	--	--	A	D	--	--	--	--	--	--	--	--	
Pneumatic press for a single denture molding flask. The unit applies 3000 or more pounds of pressure to the denture molding flask to obtain as hard a curing set of the denture material as possible. Depending on the manufacturer, a unit will operate directly from an air supply line or generate its own internal pneumatic pressure. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	22	14	9	65 lb	1:	120	1	5	0		NO		--				
EA		CM:	56	36	23	30 kg	2:	--	--	--	DEPENDENT:		YES		--				
D4320	6520-01-243-3283	Press, Flask, Hydraulic, Single Flask	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Single flask hydraulic press. The press is used in dental prosthodontic laboratories to load acrylic pressure packs for dentures and partials. The unit's self-contained hydraulics allow up to 3500 pounds of force with minimal physical effort by means of a hand lever.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	18	16	10	25 lb	1:	--	--	--	0		NO		--				
EA		CM:	46	41	25	12 kg	2:	--	--	--	DEPENDENT:		NO		--				
D4350	6520	Oven, Curing, Dental	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Vacuum dental curing oven. The unit is used in dental laboratories for vacuum staining and glazing of porcelain molds. The unit is used together with a vacuum pump (JSN D4360). The system is programmable by users for several firing programs.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	21	13	18	49 lb	1:	120	1	12	60		NO		--				
EA		CM:	53	33	46	23 kg	2:	--	--	--	DEPENDENT:		YES		--				
D4360	6520	Pump, Vacuum, Dental Oven	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Vacuum pump. The pump is used in dental laboratories to provide a vacuum source for the vacuum oven listed at JSN D4350.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	8	12	6	23 lb	1:	120	1	3	60		NO		--				
EA		CM:	20	30	15	11 kg	2:	--	--	--	DEPENDENT:		YES		--				
D4361	6520	Heater, Duplicating Colloid	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Heater for the duplicating colloid used in dental laboratories. The unit heats duplicating colloid to the correct temperature for use and maintains that temperature until the technician dispenses the colloid into a prosthetic mold or other dental model. The unit has approximately a 2 gallon capacity and the temperature control keeps the colloid within 5 degrees (above or below) of the temperature set by the technician.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	27	14	14	51 lb	1:	120	1	8	50/60		YES		--				
EA		CM:	69	36	36	24 kg	2:	--	--	--	DEPENDENT:		NO		--				
D4370	6520	Heater, Duplicating Colloid, Automatic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Automatic dental colloid heater and holding tank. The unit is used in dental laboratories to process, hold and dispense hydrocolloid for dental model duplicating work. The heater has adjustable temperature controls, automatic timing controls and a three gallon capacity. [Must specify voltage for Model 3 when ordering.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	29	18	19	90 lb	1:	120	1	15	50/60		YES		--				
EA		CM:	74	46	49	41 kg	2:	--	--	--	DEPENDENT:		NO		--				
D4500	6520-01-255-8162	Furnace, Laboratory, Dental, Burnout	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Dental burnout furnace. The unit is used in dental laboratories for burnout of dental alloy rings and flasks. The furnace is capable of automatic or manual operation and has a automatic self-calibration system as well as a digital readout. The unit can hold a minimum of fifteen 1-3/4" inlay rings. Some model lines are available with several sizes of heating elements and/or for other power configurations. [Jelrus International also provides a burnout furnace, model Infinity L30, part #15641 with a cost of \$1,375.00.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	20	18	19	50 lb	1:	120	1	12	60		NO		--				
EA		CM:	51	46	48	23 kg	2:	--	--	--	DEPENDENT:		YES		--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
D4510	6520	Furnace, Laboratory, Porcelain Glazing	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Dental laboratory furnace. The furnace is used for porcelain glazing and staining and is equipped with an automatic pyrometer and an alarm. [This is the only furnace found that is specifically designed for glazing and staining. The vacuum porcelain furnaces at JSN D4350 operate in the same temperature range and may fulfill the same function.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	15	11	10	19 lb	1:	120	1	5	0		YES		--				
		CM:	38	28	26	9 kg	2:	--	--	--	DEPENDENT:		NO		--				
D4560	6520-12-882-189	Engine, Dental, Bench, Electric	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
High speed bench mounted dental engine. The engine is used in prosthodontic laboratories for partial or complete denture repair and fabrication of surgical splints. The unit can be either directly electrically driven or have a remote motor connected to the drive unit by a belt and balancing arm. The unit includes a handpiece, footswitch and power control. The database physical dimensions refer to the belt/balancing arm style unit. [See the similar handpiece units at JSN D4260.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	24	13	11	8 lb	1:	120	1	2	60		NO		--				
		CM:	61	33	28	4 kg	2:	--	--	--	DEPENDENT:		YES		--				
D4590	6520	Chisel, Dental, Pneumatic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Pneumatic dental chisel. The chisel is used in a dental laboratory for prosthodontic appliance deflasking. Several different chisel tips are available. Some units require an oil atomizer for proper operation.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	5	5	2	1 lb	1:	--	--	--	0		NO		--				
		CM:	13	13	5	1 kg	2:	--	--	--	DEPENDENT:		NO		--				
D5520	6520	Module, Preventive Dentistry, 1 Station	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Single station preventive dentistry module, approximately 56"W x 36"H x 24"D. The unit includes a 12" diameter stainless steel sink with a single lever faucet, a duplex outlet mounted in the rear panel and a mirror with an overhead or integral light. The module is used for teaching proper dental cleaning techniques to patients. [This item of equipment as described, requires custom fabrication to include design costs. Most dental cabinets are now modular in configuration to provide flexibility. Manufacturers would not provide price estimates without detailed specifications. The listed vendors MILCARE, A-Dec and Dental-EZ provide similar off-the-shelf items at an estimated cost of \$6,000.00.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	36	56	24	310 lb	1:	120	1	3	60		NO		--				
		CM:	91	142	61	141 kg	2:	--	--	--	DEPENDENT:		NO		--				
D6000	6520-00-905-7894	Light, Dental Operating, Chair Mounted	B	B	B	B	--	--	--	--	--	--	--	--	--	--	--	--	
Chair mounted dental operating light used to illuminate the field of work for the dentist. The light is a reflector type with a three position switch. The facility must specify left or right hand delivery at the time of order. Database dimensions refer to the fully extended light.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	63	60	30	40 lb	1:	120	1	2	60		NO		--				
		CM:	160	152	76	19 kg	2:	--	--	--	DEPENDENT:		NO		--				
D6050	6520-00-890-2184	Light, Dental, Operating, Ceiling, Track	E	E	E	E	--	--	--	--	--	--	--	--	--	--	--	--	
Dental operating light used to illuminate the field of work. This is a single light unit on a cantilever arm mounted from a column which is suspended from a moving trolley in a ceiling track. The light can be used in installations where the ceiling height is between 8 and 10.5 feet; some units can mount to ceilings as high as 13 feet. Database physical dimensions refer to the light's maximum travel dimensions centered on the ceiling mounting track. The database weight includes the light, arm and trolley. Mounting this light may require reinforcing the ceiling or hanging the mount from the underside of the slab above a suspended ceiling.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	67	58	116	145 lb	1:	120	1	2	50/60		YES		--				
		CM:	170	147	295	66 kg	2:	--	--	--	DEPENDENT:		NO		--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D6100	6520-00-890-2184	Light, Dental, Operating, Dual, Ceiling, Track	E	E	E	E	--	--	F	--	--	--	--	--	--	--	--	
Dual lamp head, ceiling track mounted dental operating light used to illuminate the field of work. The light can be installed in rooms with a ceiling height between 8 and 10.5 feet; some units can accommodate a 13 foot ceiling height. Each head is on a cantilever arm mounted from a column which is suspended from a moving trolley in a ceiling track. The database physical dimensions refer to the light's maximum travel dimensions centered on the ceiling mounting track. The database weight includes the light, arm and trolley. Mounting this light may require reinforcing the ceiling or hanging the mount from the underside of the slab above a suspended ceiling. [A-Dec, Inc. discontinued its dual ceiling track light and now only provides a single ceiling track light (JSN D6050). No other source(s) found that provide a dual light.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	67	58	116	200 lb	1:	120	1	4	DEPENDENT: NO		--					
		CM:	170	147	295	91 kg	2:	--	--	--								
D6155	6520	Light, Dental, Operating, Ceiling, Column	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	
Dental operating light. The unit is a single head, ceiling column mounted with a variable intensity controller on the light head. The light illuminates the field of work for the dentist. Most units require the ceiling to be between 8 and 10.5 feet for installation. The database physical dimensions refer to the maximum extension of the light on its mount.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	60	50	50	44 lb	1:	120	1	2	DEPENDENT: YES		325					
		CM:	152	127	127	20 kg	2:	--	--	--								
D6250	6520-00-538-9150	Lathe, Dental, Bench Mounted	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Dental lathe which can perform grinding or polishing work depending on the attachments to the spindles. The unit is bench mounted and has two speeds, generally 1725 and 3450 rpm, or is variable across its entire operating range up to 3600 rpm. [Refer also to the integral bench mounted units at JSN D0970 and D0980.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	9	16	8	41 lb	1:	120	1	3	DEPENDENT: NO		--					
		CM:	23	41	20	19 kg	2:	--	--	--								
D6550	6520-00-889-7497	Grinder/Polisher, Bench Mounted, High Speed	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Bench mounted high speed grinding and polishing machine. The grinder/polisher is used in dental laboratories to finish gold and chrome appliances. The unit has 10,000 and 24,000 rpm spindle speeds. The unit can have a self-contained dust collection unit or be attached to a central vacuuming system. [See the similar handpiece units at JSNs D4260 and D4560.1R993]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	11	18	18	40 lb	1:	120	1	6	DEPENDENT: YES		--					
		CM:	28	46	46	19 kg	2:	--	--	--								
D6570	6520-01-004-2658	Bath, Water, Impression	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Dental impression water bath. The unit is used in dental laboratories to maintain the precise temperature of impression materials and for warming of carpules. The unit's temperature range is from 90 to 160 degrees Fahrenheit and is thermostatically controlled. [This is a small water bath. See any of the major scientific supply house catalogs (VWR, Allegiance, etc.) for standard size water baths starting at 1.5 L capacity.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	5	7	8	13 lb	1:	120	1	2	DEPENDENT: YES		--					
		CM:	13	18	20	6 kg	2:	--	--	--								
D6600	6520-00-890-1463	Mixer / Investor, With Vacuum	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Dental vacuum mixer-investor. Unit is used in dental laboratories to mix alginates and other materials as well as investing materials for inlays and crowns. Some units are equipped with a vibrating arm to assist in moving investments from the mixing chamber into the casting rings. Some models are microprocessor controlled. Units are mounted to a wall or bench for stability. Specify mounting when ordering.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	27	15	19	51 lb	1:	120	1	3	DEPENDENT: YES		--					
		CM:	69	39	48	23 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D6610	6520	Arthroscope, Dental, TMJ	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Direct view rigid arthroscope for TMJ surgery. The scope is available in different tube diameters and viewing angles depending on the manufacturer. The arthroscope is also available as a videoscope. See JSNs M8605 through M8607 for the support equipment for the direct vision scope. Use JSNs M8610 and M8611 for the support equipment for the video version of the arthroscope. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			1	3	1	1 lb	1:	--	--	--	NO	NO	--					
			3	8	3	1 kg	2:	--	--	--	NO	NO	--					
D6650	6520	Former, Vacuum, With Motor, Vacuum Pump, Heater	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Vacuum former. Used in dental laboratories for adaptation of thermoplastic resins. Unit has a self contained motor, vacuum pump and heater.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			12	10	16	22 lb	1:	120	1	10	60	NO	--					
			30	25	41	10 kg	2:	--	--	--	YES	YES	--					
D7090	6520	Utility Center, Dental, Wall or Floor Mounted	B	B	B	B	--	B	A	H	--	--	--	--	--	--	--	--
Utility center. The unit contains electrical and quick connect air, waste and water utility connections. The center accommodates one umbilical and includes shut-off valves and regulators for both the air and water supplies. [This JSN is often included as part of the dental operating unit. See the manufacturers' technical sheets for JSN D8250.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			6	15	18	10 lb	1:	--	--	--	0	NO	--					
			15	38	46	5 kg	2:	--	--	--	NO	NO	--					
D8060	6520	Furnace, Porcelain, Vacuum	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
Vacuum porcelain furnace. Used in dental laboratories to fire porcelain molds for dental appliances. Unit shall include a vacuum pump capable of producing 27 inches of mercury in thirty seconds. [Refer also to JSNs D4350 (Oven, Curing, Dental) and D4360 (Pump Vacuum, Dental Oven).]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			23	15	16	68 lb	1:	115	1	12	50/60	YES	--					
			58	38	41	31 kg	2:	--	--	--	NO	NO	--					
D8250	6520	Delivery System, Dental Operating	C	C	C	C	--	B	B	H	--	--	--	--	--	--	--	--
Dental operating unit. The dentist and/or dental hygienist uses the unit for treatment of dental patients. The unit contains the operating connections for handpieces, the water spray and the vacuum system. The unit can be wall, chair or cart mounted.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			48	75	42	170 lb	1:	120	1	15	60	NO	--					
			122	190	107	78 kg	2:	--	--	--	YES	YES	--					
D8255	6520	Chair, Operating, Dental, With Unit Mount, Light	B	B	B	B	--	B	A	H	--	--	--	--	--	--	--	--
Dental operating chair. The unit is equipped with a dental delivery system, an assistant's utility center, a cuspidor and an operating light. [DentalEZ Group (Cage Code 25692) also provides chairs, delivery systems, lights and other options.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			74	50	83	500 lb	1:	120	1	12	60	NO	--					
			188	127	211	227 kg	2:	--	--	--	YES	YES	--					
D8510	6520-01-213-2652	Oven, Drying, Dental	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Dental model drying oven. The oven is used to dehydrate refractory models prior to bee's wax dipping. The unit provides efficient circulation of air to eliminate moisture as it evaporates. The unit has an adjustable damper, two shelves, a built-in thermostat, a secondary temperature controller and a glass thermometer.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			28	18	20	69 lb	1:	120	1	8	50/60	YES	--					
			71	46	51	32 kg	2:	--	--	--	NO	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
D8530	6520	Polisher, Electrochemical	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Electrochemical dental appliance plater/polisher. The unit includes a controller, a tray, polishing bowls, a rinse bowl and top, an anode base and lead assembly, spare fuses and a cathode. The unit is used to plate and polish chrome frameworks prior to final finishing. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	14	14	15	26 lb	1:	120	1	5	60	YES	--						
			36	36	39	12 kg	2:	--	--	--	DEPENDENT:	YES	--						
D8540	4940-00-865-1733	Sandblaster, Complete	C	C	C	C	--	--	A	D	--	--	--	--	--	--	--	--	
Sandblaster. The unit is used in dental laboratories for abrasive blasting of restorations. The blaster comes with abrasive tanks, abrasive pencils, a pressure regulator and a filter system. The unit can be attached to a dust collection system. The blaster is available in different power configurations or in recycling workstations (see JSN D0942).																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	19	19	22	70 lb	1:	120	1	11	60	NO	--						
			48	48	56	32 kg	2:	--	--	--	DEPENDENT:	NO	--						
D8555	6520	Torch, Casting/Soldering, Dental	C	C	C	C	--	--	--	C	--	A	E						
Dental casting and soldering torch used in dental laboratories for soldering and casting crown and bridge alloys. The torch is assembled from a variety of handles, mixers, tubes and tips depending on the particular piece of work.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	1	9	1	1 lb	1:	--	--	--	--	NO	--						
			3	23	3	1 kg	2:	--	--	--	DEPENDENT:	NO	--						
D8560	6520	Oral Surgery System, Mobile	C	C	C	C	--	B	A	H	--	--	--	--	--	--	--	--	
Mobile oral surgical unit. The unit includes an air-drive for dental handpieces, a mobile stand, a variable foot control, a removable instrument holder, one high speed surgical handpiece, one surgical straight air turbine handpiece, an instrument tray, a three function syringe and 10 feet of electrically conductive tubing with fittings. The unit requires a utility mounting box, see JSN D7090, which is often included. The unit is also available in a doctor/assistant configuration with all the instruments for both. The unit is used in dental operatories where the delivery system is not part of the dental chair.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	30	19	15	60 lb	1:	120	1	10	50/60	YES	--						
			76	48	38	28 kg	2:	--	--	--	DEPENDENT:	NO	--						
D8620	6520	Bin, Plaster, 3 Compartment	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Above counter or wall mounted three compartment plaster bin. The bin can be made from stainless steel or heavy duty plastic and is used in dental laboratories to hold and gravity feed plaster materials. The bin has a total plaster capacity of 75 pounds. The overall bin size varies by manufacturer.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	30	36	10	40 lb	1:	--	--	--	--	NO	--						
			76	91	26	19 kg	2:	--	--	--	DEPENDENT:	NO	--						
D8650	6520	Chute, Waste, Plaster, Counter Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Counter mounted plaster waste chute. The chute is generally made of stainless steel and is available in either a round or square configuration. The chute is mounted over a waste receptacle and is used to dispose of waste material through the countertop. The chute is usually specified and purchased as part of the countertop rather than as a separate item.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	4	7	7	1 lb	1:	--	--	--	--	NO	--						
			10	18	18	1 kg	2:	--	--	--	DEPENDENT:	NO	--						
D8850	6520-00-149-0123	Amalgamator, Dental	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Dental amalgamator. The amalgamator is used in dental operatories to triturate alloys for restoration of teeth after removal of caries.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	6	12	9	10 lb	1:	120	1	1	60	NO	--						
			15	30	23	5 kg	2:	--	--	--	DEPENDENT:	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
D8950	6520-00-962-2106	Vibrator, Dental, Heavy Duty	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Dental molding vibrator. Used in dental laboratories to remove air from the mold material. [220V models are available from most manufacturers.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	7	11	8	20 lb	1:	120	1	3	60		NO		--				
EA		CM:	18	28	20	9 kg	2:	--	--	--	60		YES		--				
D8960	6520	Vibrator, Dental, Standard Duty	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Dental porcelain vibrator. Used in the dental laboratory for the packing of unfired porcelain slurry. [Some manufacturers offer 208V models.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	6	8	8	6 lb	1:	120	1	2	60		NO		--				
EA		CM:	15	20	20	3 kg	2:	--	--	--	60		YES		--				
D8990	6520-01-180-6964	Cleaner, Ultrasonic, 10-12 Quart Capacity	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Ultrasonic cleaner. Used in dental laboratories and operatories to clean dental instruments and tools either as a preliminary step to sterilization or to remove material. Cleaners are available in several sizes with or without timers and/or heat. The units used for the database have a 10-12 quart capacity and are equipped with a timer and heat. [See JSN D0820 for a smaller cleaner.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	12	13	13	23 lb	1:	120	1	4	60		NO		--				
EA		CM:	30	33	33	11 kg	2:	--	1	--	60		YES		--				
D9010	6520	Cabinet, Blast Cleaning, F/S	A	A	A	A	--	--	A	D	--	--	--	--	--	--	--	--	
Blast cleaning cabinet. Used in dental laboratories for removing investment and oxide film from metal castings. Unit has internal light, foot switch and a viewing window. Unit requires an air supply capable of 4 cubic feet per minute at 80 pounds per square inch.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	84	58	40	250 lb	1:	120	1	15	60		NO		--				
EA		CM:	213	147	102	114 kg	2:	--	--	--	60		NO		--				
D9015	6520	Microfinisher, Dental, Counter Mounted	A	A	A	A	--	--	A	D	--	--	--	--	--	--	--	--	
Dental air abrasive micro-finisher. Unit is dual system with individual micro-nozzles, individual controls and gauges for use with oxide abrasives or glass beads. It has view-port and sleeved arm holes. Used in dental laboratories for fine finish work on appliances. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	25	17	16	55 lb	1:	120	1	10	60		NO		--				
EA		CM:	64	43	41	25 kg	2:	--	--	--	60		YES		--				
D9035	6520	Driver, Model Indexing Pins	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Model indexing pin driver used to accurately place indexing pins in multiple piece dental models and multiple piece die sets. The bench top instrument provides a means to accurately align, drill and insert indexing pins.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	15	10	15	22 lb	1:	120	1	5	60		NO		--				
EA		CM:	38	25	38	10 kg	2:	--	--	--	60		NO		--				
D9050	6520-00-564-4050	Trimmer, Model, Dental, 1/4 HP	B	B	B	B	--	--	B	A	--	--	--	--	--	--	--	--	
Dental model trimmer with a 1/4 or 1/3 HP motor and a 10" abrasive wheel. The trimmer is used in dental laboratories for trimming plaster and stone dental impression models. This is a light duty unit and its commonly used accessories include floor switches, water valves, water spray heads and splash shields. The database pricing is for the basic unit only.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	14	14	16	50 lb	1:	120	1	8	60		NO		--				
EA		CM:	36	36	41	23 kg	2:	--	--	--	60		YES		--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D9051	6520	Trimmer, Model, Dental, Dual Wheel	C	C	C	C	--	B	A	--	--	--	--	--	--	--	--	
Dual wheel dental model trimmer including drain tray for use in dental laboratories for trimming models. [Only known source for a dual wheel trimmer.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:						
EA		CM:	20	24	23	84 lb	1:	110	1	12	60		NO					
			51	61	58	39 kg	2:	--	--	--	DEPENDENT:		YES					
D9055	6520	Valve, Control, Water	A	A	A	A	--	J	--	--	--	--	--	--	--	--	--	
Water control valve used to provide a water connection to model trimmers and other equipment. The valve generally has a wheel control, has an outlet at 90 degrees to the inlet, stops flow by compression against a seat and has a flange for surface mounting. The valve is commonly called an angle stop.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:						
EA		CM:	4	3	3	1 lb	1:	--	--	--	--		NO					
			10	8	8	1 kg	2:	--	--	--	DEPENDENT:		NO					
D9056	6520	Valve, Air, Needle Control	A	A	A	A	--	--	--	C	--	--	--	--	--	--	--	
Needle control air valve for a dental laboratory work bench. The unit is a right angle or straight serrated tip air needle control valve furnished with casting flange for the dental laboratory. It is chrome plated with a hose barb nozzle. The valve has a shank nipple for connection to the servicing air system.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:						
EA		CM:	4	3	5	1 lb	1:	--	--	--	0		NO					
			10	8	13	1 kg	2:	--	--	--	DEPENDENT:		NO					
D9057	6520	Valve, Gas, Needle Control	A	A	A	A	--	--	--	--	--	--	--	--	A	--	--	
Needle control gas valve. The unit is a right angle, handle indexed, gas control valve for the dental laboratory. It is chrome plated with a hose barb nozzle. Used in a dental laboratory as a bench gas supply valve. It should come with a shank nipple for plumbing connection. The valve normally uses a 3/8" female pipe thread.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:						
EA		CM:	--	--	--	-- lb	1:	--	--	--	0		NO					
			--	--	--	-- kg	2:	--	--	--	DEPENDENT:		NO					
D9058	6520-01-251-5400	Blowgun, Air, Lever Type, With 10 Foot Hose	C	C	C	C	--	--	--	C	--	--	--	--	--	--	--	
Air blowgun with a lever control for use in a dental laboratory. The blowgun comes with a 10 foot coiled rubber hose (usually 3/8" diameter) which includes a connection for or a quick disconnect fitting. Note: The NSN above is for the blowgun only. The hose assembly NSN is 6520012515401.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:						
EA		CM:	6	20	6	10 lb	1:	--	--	--	--		NO					
			15	51	15	5 kg	2:	--	--	--	DEPENDENT:		NO					
D9059	6520-01-216-4954	Coupler, Quick Disconnect	A	A	A	A	--	--	--	C	--	--	--	--	--	--	--	
Quick disconnect coupler for a low pressure air line on a dental laboratory work bench. The coupler uses a 3/8" NPT connection to the servicing air supply line.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:						
EA		CM:	1	1	3	1 lb	1:	--	--	--	--		NO					
			3	3	8	1 kg	2:	--	--	--	DEPENDENT:		NO					
D9060	6520-01-045-6407	Prophylaxis Unit, Ultrasonic	C	C	C	C	--	J	A	D	--	--	--	--	--	--	--	
Dental ultrasonic prophylaxis unit. Used in dental clinics for the removal of calculus. Unit requires water and air supplies.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:						
EA		CM:	4	9	10	13 lb	1:	120	1	2	60		YES					
			10	23	25	6 kg	2:	--	--	--	DEPENDENT:		NO					

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES											
				A	N	A	V	I	1	2	3	4	5	6	
D9250	6520	Rail, Apron, 4.5" H x W x 2" D	A A A A --	--	--	--	--	--	--	--	--	--	--	--	
Apron rails. Used to fill in spaces under counter tops between cabinets. The width is determined by requirements of project. The database pricing and physical dimensions reflect a 36" wide rail.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
EA		IN:	5	36	2	6 lb	1:	--	--	--	0	NO	--		
		CM:	13	91	5	3 kg	2:	--	--	--	NO	--			
D9280	6520	Legs, Rail, Apron	A A A A --	--	--	--	--	--	--	--	--	--	--	--	
Apron rail legs. Used to support countertops when there is no base cabinet to support D9940, height as required. Used in dental operations. Database pricing and dimensional information assumes a 24" deep counter, 36" above the floor.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
EA		IN:	36	2	24	20 lb	1:	--	--	--	--	NO	--		
		CM:	91	5	61	9 kg	2:	--	--	--	NO	--			
D9330	6520	Compressor, Air, Dental, 6 Operatories	A A A A --	I	C	--	--	--	--	--	--	--	--	--	
Dental air compressor. Unit is used in dental clinics to provide an air supply to operate the dental handpieces and other instruments used in the care and treatment of patients. Compressor can handle up to six operatories and is equipped with an air dryer system.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
EA		IN:	33	51	35	410 lb	1:	208	1	22	50/60	NO	--		
		CM:	84	130	89	187 kg	2:	--	--	--	NO	--			
D9420	6520	Cabinet, Wall Hung, 2 Sliding Doors, 30x36x12	A A A A --	--	--	--	--	--	--	--	--	--	--	--	
Wall hung double sliding door cabinet. Unit has 2 adjustable shelves. Unit is used in dental operations to hold instrument trays overhead. Cabinet depth and height dimensions vary slightly by manufacturer.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
EA		IN:	31	36	13	88 lb	1:	--	--	--	--	NO	--		
		CM:	79	91	33	40 kg	2:	--	--	--	NO	--			
D9450	6520-00-133-4857	Cabinet, Base, With Sink, 1 Door, 37x20x18	A A A A --	D	--	--	--	--	--	--	--	--	--	--	
Sink base cabinet. The cabinet has a single swing door with a towel drop access door to a waste receptacle. The requestor must specify if a sink and faucet are desired. Height and depth measurements vary slightly by manufacturer. The unit is used in dental operatories for a sink cabinet. [A-Dec (CAGE 51840) and Den-Tal-Ez (CAGE 25692) market complete workstations rather than individual cabinets.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
EA		IN:	37	20	18	75 lb	1:	--	--	--	0	NO	--		
		CM:	94	51	46	34 kg	2:	--	--	--	NO	--			
D9520	6520	Cabinet, Base, 5 Drawer	A A A A --	--	--	--	--	--	--	--	--	--	--	--	
Base cabinet unit approximately 37" x 20" x 19". The cabinet includes five drawers: one small depth, one large depth and three medium depth. The cabinet dimensions vary slightly by manufacturer and other drawer configurations are available. The cabinet is used in dental operatories to hold instruments and supplies. [A-Dec (CAGE 51840) and Den-Tal-Ez (CAGE 25692) market complete workstations rather than individual cabinets.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
EA		IN:	37	20	19	100 lb	1:	--	--	--	0	NO	--		
		CM:	94	51	48	45 kg	2:	--	--	--	NO	--			
D9540	6520	Cabinet, Base, 1-2 Door, 37x20x19	A A A A --	--	--	--	--	--	--	--	--	--	--	--	
Base cabinet unit. The cabinet has a single or double hinged door(s). The dimensions vary slightly by manufacturer. The cabinet is used in dental operatories to store materials. [A-Dec (CAGE 51840) and Den-Tal-Ez (CAGE 25692) market complete workstations rather than individual cabinets.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
EA		IN:	36	20	19	70 lb	1:	--	--	--	0	NO	--		
		CM:	92	51	48	32 kg	2:	--	--	--	NO	--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES										
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5
D9610	6520-00-890-1847	Cabinet, Base, With Sink, 2 Doors	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--
Base sink cabinet unit approximately 37hx24wx19d. The unit has double swing doors, a sink, a faucet and a drain. The cabinet is used in dental operatories as a sink for dentists and assistants to wash their hands and instruments.																	
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
					37	27	19	100 lb	1:	--	--	0	NO	NO	--		
					94	69	48	46 kg	2:	--	--				--		
D9660	6520	Cabinet, Desk, Wall Hung, 1-2 Drawers, 6.5x20x18	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung desk unit. The desk has one or two drawers. It is used in dental operatories to hold instruments and supplies as well as serve as a writing surface. The desk dimensions differ slightly by manufacturer.																	
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
					7	19	18	46 lb	1:	--	--	--	NO	NO	--		
					18	48	46	21 kg	2:	--	--	--	NO	NO	--		
D9662	6520	Cabinet, Desk, Wall Hung, 2 Drawers, 6.5x27x17	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung desk cabinet unit with two drawers. The cabinet is used in dental operatories to store instruments and supplies as well as a writing surface.																	
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
					7	27	17	85 lb	1:	--	--	--	NO	NO	--		
					18	69	43	39 kg	2:	--	--	--	NO	NO	--		
D9681	6520	Cabinet, Base, Wall Hung, 3 Drawers, 22x20x18	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung base cabinet unit with 3 drawers. The cabinet is used in dental operatories for storage of supplies and instruments. It includes a countertop. The cabinet dimensions vary slightly by manufacturer.																	
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
					22	20	18	66 lb	1:	--	--	--	NO	NO	--		
					56	51	46	30 kg	2:	--	--	--	NO	NO	--		
D9691	6520	Cabinet, Base, Wall Hung, 4 Drawers	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung base cabinet unit with four drawers approximately 22" H x 20" W x 18" D. The unit includes a countertop and is used in dental operatories to store instruments and supplies. [A-Dec (CAGE 51840) and Den-Tal-Ez (CAGE 25692) market complete workstations rather than individual cabinets. The wall hung unit for Model 3 requires a wall cleat. The unit is also priced with a top and two end panels not separately numbered.]																	
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
					25	20	18	79 lb	1:	--	--	0	NO	NO	--		
					64	51	46	36 kg	2:	--	--				--		
D9786	6520-00-133-4552	Cabinet, Base, Wall Hung, 2 Doors	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
Wall hung base cabinet, approximately 22"H x 20"W x 18"D. The unit has two hinged doors and an adjustable shelf. The cabinet is used in dental operations for storage. It is often called a half height cabinet. It includes a countertop. The cabinet dimensions vary slightly between vendors. [These are the only two manufacturers found. A-Dec (CAGE 51840) and Den-Tal-Ez (CAGE 25692) market complete workstations rather than individual cabinets.]																	
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
					22	20	18	61 lb	1:	--	--	0	NO	NO	--		
					56	51	46	28 kg	2:	--	--				--		
D9835	6520	Cabinet, Base, Sink, Wall Hung, 2 Doors, 18x27x17	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--
Wall hung base cabinet unit with a sink. The cabinet has double hinged doors and is set up to accept a sink. It is used, with a sink, by dentists and assistants in the operatory to wash hands and instruments.																	
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
					18	27	17	85 lb	1:	--	--	--	NO	NO	--		
					46	69	43	39 kg	2:	--	--	--	NO	NO	--		

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES																																						
				A	N	A	V	I	1 2 3 4 5 6																																	
D9861	6520	Cabinet, Wall Hung, 2 Sliding Doors, 23Hx38Wx8D	A A A A --	--	--	--	--	--	--																																	
Wall hung sliding door cabinet. The cabinet has double sliding doors and an adjustable shelf. The unit is used in dental operatories to store dental materials and supplies.																																										
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>23</td> <td>38</td> <td>8</td> <td>61 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>58</td> <td>97</td> <td>20</td> <td>28 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> </tbody> </table>										UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	23	38	8	61 lb	1:	--	--	--	NO			58	97	20	28 kg	2:	--	--	--	NO
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																
EA	CM:	23	38	8	61 lb	1:	--	--	--	NO																																
		58	97	20	28 kg	2:	--	--	--	NO																																
D9863	6520	Cabinet, Wall Hung, 2 Sliding Doors, 30Hx38Wx14D	A A A A --	--	--	--	--	--	--																																	
Wall hung sliding door cabinet. Unit is used in dental operations to store materials or supplies.																																										
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>30</td> <td>38</td> <td>14</td> <td>140 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>76</td> <td>97</td> <td>36</td> <td>64 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> </tbody> </table>										UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	30	38	14	140 lb	1:	--	--	--	NO			76	97	36	64 kg	2:	--	--	--	NO
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																
EA	CM:	30	38	14	140 lb	1:	--	--	--	NO																																
		76	97	36	64 kg	2:	--	--	--	NO																																
D9872	6520	Sink, CRS, 6x12x9	A A A A --	D	--	--	--	--	--																																	
Corrosion resistant steel sink. The sink comes with a strainer and a swing faucet. The sink interior dimensions vary slightly by manufacturer. The sink is used in dental operatories as a hand washing sink. [Dimensions shown below are outside measurements and are width from left to right, depth from front to back and height from top to bottom of bowl. Price differences verified.]																																										
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>7</td> <td>15</td> <td>15</td> <td>15 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>18</td> <td>38</td> <td>38</td> <td>7 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> </tbody> </table>										UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	7	15	15	15 lb	1:	--	--	--	NO			18	38	38	7 kg	2:	--	--	--	NO
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																
EA	CM:	7	15	15	15 lb	1:	--	--	--	NO																																
		18	38	38	7 kg	2:	--	--	--	NO																																
D9880	6520	Sink, CRS, Drop-In, 7.5hx16wx16d or 7.5hx18wx14d	A A A A --	D	--	--	--	--	--																																	
Drop-in corrosion resistant sink made from 18 gauge stainless steel with a 7.5h x 16w x 16d bowl (256 sq. in.), or an 7.5h x 18w x 14d bowl (252 sq. in.). The unit has a faucet, a drain, a back ledge with three precut fixture holes and requires mounting in a cabinet or counter. The sink's overall outer dimensions vary slightly by manufacturer. The sink is used in dental operatories and laboratories for dentists, assistants and technicians to wash hands, instruments or accessories.																																										
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>9</td> <td>22</td> <td>21</td> <td>27 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>23</td> <td>56</td> <td>53</td> <td>13 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> </tbody> </table>										UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	9	22	21	27 lb	1:	--	--	--	NO			23	56	53	13 kg	2:	--	--	--	NO
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																
EA	CM:	9	22	21	27 lb	1:	--	--	--	NO																																
		23	56	53	13 kg	2:	--	--	--	NO																																
D9900	6520	Bracket, Support	A A A A --	--	--	--	--	--	--																																	
Support bracket. The bracket is used in dental operatories to support a desk, table frame, work surface or other wall hung module. [Support Brackets as identified in the description are generally manufacturer unique and are designed specifically for that manufacturer's product such as apron legs or end panels. refer to JSNs D0400, D0660 and D9280. The Hamilton Mfr. Co. does offers a bracket that is considered universal and is therefore provided as a source.]																																										
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>12</td> <td>2</td> <td>12</td> <td>20 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>30</td> <td>5</td> <td>30</td> <td>9 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> </tbody> </table>										UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	12	2	12	20 lb	1:	--	--	--	NO			30	5	30	9 kg	2:	--	--	--	NO
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																
EA	CM:	12	2	12	20 lb	1:	--	--	--	NO																																
		30	5	30	9 kg	2:	--	--	--	NO																																
D9940	6520	Countertop, Laminated, 1" or 1-1/4"x W x D	A A A A --	--	--	--	--	--	--																																	
Laminated plastic countertop. The counter includes a molded splashback and is used as a work surface on dental operating cabinets. The user must specify a 1 or 1-1/4 inch thickness (depending on the manufacturer) when ordering as well as the counter's width and depth. The database price reflects the cost per linear foot at 30" depth.																																										
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>2</td> <td>12</td> <td>30</td> <td>21 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>5</td> <td>30</td> <td>76</td> <td>10 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> </tbody> </table>										UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	2	12	30	21 lb	1:	--	--	--	NO			5	30	76	10 kg	2:	--	--	--	NO
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																
EA	CM:	2	12	30	21 lb	1:	--	--	--	NO																																
		5	30	76	10 kg	2:	--	--	--	NO																																
D9941	6520	Countertop, Laminated, 3/4" Thick	A A A A --	--	--	--	--	--	--																																	
A 3/4" thick laminated countertop. The top is a high pressure laminated covered top with a splashback. The counter is used as a work surface on dental operatory cabinets. Priced per linear foot. [Must specify dimensions at time of order.]																																										
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>1</td> <td>12</td> <td>18</td> <td>7 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>3</td> <td>30</td> <td>46</td> <td>4 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> </tbody> </table>										UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	1	12	18	7 lb	1:	--	--	--	NO			3	30	46	4 kg	2:	--	--	--	NO
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																
EA	CM:	1	12	18	7 lb	1:	--	--	--	NO																																
		3	30	46	4 kg	2:	--	--	--	NO																																

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
D9960	6520	Cabinet, Wall Hung, 2 Sliding Door, 23x38x14	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall hung cabinet with two sliding doors and a removable shelf for use in dental operatories.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
EA		CM:	23	38	14	74 lb	1:	--	--	--								
			58	97	36	34 kg	2:	--	--	--								
D9980	6520-00-133-4500	Cabinet, Base, 7 Drawers, 37Hx20Wx18D	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Base cabinet unit with 7 drawers; four are shallow and three are deep. The unit is also called a full height cabinet. It is used in a dental operator to hold instruments and supplies. The database pricing and dimension information includes the countertop. The cabinet dimensions vary slightly by manufacturer. [No other source(s) identified with this description/specification. Although the two manufacturers listed will provide this product from standard stock several companies stated that given a detail specification they would custom make any cabinet. This should be considered an alternative to local areas. Cabinet shipments outside a local area of use will often increase cost by fifty percent.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
EA		CM:	37	20	18	105 lb	1:	--	--	--								
			94	51	46	48 kg	2:	--	--	--								
E0042	6530	Workcenter, Computer, Free Standing, 48" W	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 TOOL RAIL 2 PAPER TRAY 1 DIAGONAL TRAY 1 FREESTANDING WORK SURFACE 1 MOBILE PEDESTAL, BOX/FILE 1 ADJUSTABLE KEYBOARD TRAY																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
EA		CM:	42	48	23	150 lb	1:	--	--	--								
			107	122	58	69 kg	2:	--	--	--								
E0045	6530	Workcenter, Computer, Free Standing, 60" W	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 TOOL RAIL 2 PAPER TRAY 1 DIAGONAL TRAY 1 FREESTANDING WORK SURFACE 1 MOBILE PEDESTAL, BOX/FILE 1 ADJUSTABLE KEYBOARD TRAY																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
EA		CM:	42	60	23	175 lb	1:	--	--	--								
			107	152	58	80 kg	2:	--	--	--								
E0048	6530	Workcenter, Computer, Free Standing, 72" W	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 2 PAPER TRAY 1 DIAGONAL TRAY 1 TOOL RAIL 1 FREESTANDING WORK SURFACE 24D X 72W 1 MOBILE PEDESTAL, BOX/FILE 1 ADJUSTABLE KEYBOARD TRAY																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--			
EA		CM:	42	72	23	200 lb	1:	--	--	--								
			107	183	58	91 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
E0051	6530	Workstation, Corner Work Surface, Wall Mtd, 72x48	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES: 4 VERTICAL HANGING STRIPS 2 LOCKABLE FLIPPER UNITS 2 SHELF, STORAGE/DISPLAY 2 LIGHT 1 TACKBOARD 2 TOOL RAIL 2 PAPER TRAY 1 DIAGONAL TRAY 1 CANTILEVERED WORK SURFACE 1 ADJUSTABLE KEYBOARD TRAY 1 MOBILE PEDESTAL, BOX/FILE 1 CPU HOLDER																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	IN: 80 CM: 203	72 183	48 122	250 lb 114 kg	1: 2:	120 --	1 --	2 --	60 NO YES	NO YES	-- --					
E0054	6530	Workstation, L-Shaped, Wall Mounted, 72x60	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES: 6 VERTICAL HANGING STRIPS 3 LOCKABLE FLIPPER UNIT 3 SHELF, STORAGE/DISPLAY 3 LIGHT 2 TACKBOARD 2 TOOL RIAL 2 PAPER TRAY 1 DIAGONAL TRAY 2 CANTILEVERED WORK SURFACE 1 ADJUSTABLE KEYBOARD TRAY 1 MOBILE PEDESTAL, BOX/FILE 1 CPU HOLDER 1 PENCIL DRAWER																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	IN: 80 CM: 203	75 190	63 160	302 lb 137 kg	1: 2:	120 --	1 --	2 --	60 NO YES	NO YES	-- --					
E0057	6530	Workstation, L-Shaped w/Table, Wall Mounted, 72x60	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES: 3 VERTICAL HANGING STRIPS 2 LOCKABLE FLIPPER UNIT 2 SHELF, STORAGE/DISPLAY 2 LIGHT 1 TACKBOARD 2 TOOL RAIL 2 PAPER TRAY 1 DIAGONAL TRAY 1 CANTILEVERED WORK SURFACE 1 FREESTANDING WORK SURFACE 1 ADJUSTABLE KEYBOARD TRAY 1 MOBILE PEDESTAL, BOX/FILE [The database electrical requirement is only for the module's lights.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	IN: 80 CM: 203	75 190	62 157	225 lb 103 kg	1: 2:	120 --	1 --	2 --	0 NO YES	NO YES	-- --					

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I R A F A H						UTILITIES					
				1	2	3	4	5	6	1	2	3	4	5	6
E0060	6530	Workstation, L-Shaped, Wall Mounted, 72x72	C C C C --	--	A	--	--	--	--	--	--	--	--	--	
		THIS TYPICAL INCLUDES: 5 VERTICAL HANGING STRIPS 2 LOCKABLE FLIPPER UNITS 4 SHELF, STORAGE/DISPLAY 3 LIGHTS 2 TACKBOARDS 2 TOOL RAILS 2 PAPER TRAYS 1 DIAGONAL TRAY 2 CANTILEVERED WORK SURFACES 1 ADJUSTABLE KEYBOARD TRAY 1 MOBILE PEDESTAL, BOX/FILE 1 PENCIL DRAWER 1 CPU HOLDER													
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 80 190	DEPTH 75 190	WEIGHT 275 lb 125 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 2 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --		
E0063	6530	Workstation, L-Shaped w/Peninsula, Wall Mtd, 72x72	C C C C --	--	A	--	--	--	--	--	--	--	--	--	
		THIS TYPICAL INCLUDES: 3 VERTICAL HANGING STRIPS 2 LOCKABLE FLIPPER UNITS 2 SHELVES, STORAGE/DISPLAY 2 LIGHTS 1 TACKBOARD 2 TOOL RAILS 2 PAPER TRAYS 1 DIAGONAL TRAY 1 CANTILEVERED WORK SURFACE 1 PENINSULA WORK SURFACE 1 ADJUSTABLE KEYBOARD TRAY 1 MOBILE PEDESTAL, BOX/FILE 1 PENCIL DRAWER 1 CPU HOLDER													
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 80 190	DEPTH 73 185	WEIGHT 250 lb 114 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 2 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --		
E0066	6530	Workstation, Corner Work Surface, Wall Mtd, 72x72	C C C C --	--	A	--	--	--	--	--	--	--	--	--	
		THIS TYPICAL INCLUDES: 5 VERTICAL HANGING STRIPS 3 LOCKABLE FLIPPER UNITS 3 SHELVES, STORAGE/DISPLAY 3 LIGHTS 2 TACKBOARDS 2 TOOL RAILS 2 PAPER TRAYS 1 DIAGONAL TRAY 2 CANTILEVERED WORK SURFACES 1 CANTILEVERED CORNER WORK SURFACE 1 ADJUSTABLE KEYBOARD TRAY 1 STATIONARY PEDESTAL, BOX/BOX/FILE 1 PENCIL DRAWER 1 CPU HOLDER													

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I R A F A H	UTILITIES 1 2 3 4 5 6
-----	-----	--------------	-----------	------------------------	--------------------------

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE 1:	AMPS 1:	VOLTS 2:	PHASE 2:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:
EA	80	203	75	250 lb 114 kg	120	1	2	--	--	--	60	NO	YES	--

E0069	6530	Workstation, L-Shaped, Wall & Panel Mounted, 72x90	C C C C --	-- A -- -- -- --
-------	------	---	------------	------------------

THIS TYPICAL INCLUDES:

- 3 VERTICAL HANGING STRIPS
- 4 STANDARD SOLID PANELS
- 2 PANEL-TO-PANEL CONNECTORS
- 1 PANEL CONNECTOR, 2-WAY CORNER
- 1 FINISHED END HARDWARE
- 3 LOCKABLE FLIPPER UNITS
- 2 SHELVES, STORAGE/DISPLAY
- 3 LIGHTS
- 2 TACKBOARDS
- 2 TOOL RAILS
- 2 PAPER TRAYS
- 1 DIAGONAL TRAY
- 2 CANTILEVERED WORK SURFACES
- 1 ADJUSTABLE KEYBOARD TRAY
- 1 MOBILE PEDESTAL, BOX/FILE
- 1 PENCIL DRAWER
- 1 CPU HOLDER
- 1 SUPPORT PANEL

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE 1:	AMPS 1:	VOLTS 2:	PHASE 2:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:
EA	80	203	77	300 lb 137 kg	120	1	2	--	--	--	0	NO	YES	--

E0072	6530	Workstation, Corner Work Surface, Wall Mtd, 72x96	C C C C --	-- A -- -- -- --
-------	------	--	------------	------------------

THIS TYPICAL INCLUDES:

- 5 VERTICAL HANGING STRIPS
- 3 LOCKABLE FLIPPER UNITS
- 3 SHELVES, STORAGE/DISPLAY
- 3 LIGHTS
- 2 TACKBOARDS
- 2 TOOL RAILS
- 2 PAPER TRAYS
- 1 DIAGONAL TRAY
- 2 CANTILEVERED WORK SURFACES
- 1 CANTILEVERED CORNER WORK SURFACE
- 1 ADJUSTABLE KEYBOARD TRAY
- 1 MOBILE PEDESTAL, BOX/FILE
- 1 PENCIL DRAWER
- 1 CPU HOLDER

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE 1:	AMPS 1:	VOLTS 2:	PHASE 2:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:
EA	80	203	75	300 lb 137 kg	120	1	2	--	--	--	60	NO	YES	--

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
E0075	6530	Workstation, L-Shaped, Freestanding, 72x48	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 STANDARD SOLID PANELS 2 PANEL-TO-PANEL CONNECTORS 1 PANEL CONNECTOR, 2-WAY CORNER 2 FINISHED END HARDWARE KITS 2 LOCKABLE FLIPPER UNITS 2 SHELVES, STORAGE/DISPLAY 3 LIGHTS 2 TACKBOARDS 2 TOOL RAILS 2 PAPER TRAYS 1 DIAGONAL TRAY 2 CANTILEVERED WORK SURFACES 1 ADJUSTABLE KEYBOARD TRAY 1 HANGING PEDESTAL, BOX/FILE 1 PENCIL DRAWER 2 SUPPORT PANELS 																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:				
		EA	IN: 67	77	53	225 lb	1: 120	1	2	HZ SWITCH:	NO	DEPENDENT:	YES	--				
			CM: 170	196	135	103 kg	2: --	--	--	DEPENDENT:	YES		--					
E0078	6530	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		<p>This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 solid panel, 85"H (2159mm) x 48"W (1219mm); 1 solid panel, 85"H (2159mm) x 30"W (762mm); 2 solid panels, 47"H (1194mm) x 24"W (610mm); 2 panel connectors, 2-way corner, 85"H (2159mm); 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface, 48"W (1219mm); 1 peninsula work surface, 72"W (1829mm); 1 lockable flipper unit, 48"w (1219mm); 1 lockable flipper unit, 30" W (762 mm); 1 shelf, storage/display, 48"W (1219mm); 1 shelf, storage/display, 30"W (762 mm); 1 light, 48"W (1219mm); 1 light, 30"W (762mm); 1 tack board, 48"W (1219mm); 1 tool rail, 30"W (762mm); 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file. 																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:				
		EA	IN: 80	85	75	200 lb	1: 120	1	2	HZ SWITCH:	NO	DEPENDENT:	YES	--				
			CM: 203	216	190	91 kg	2: --	--	--	DEPENDENT:	YES		--					
E0081	6530	Workstation, L-Transaction 72, Free Std, 72x72	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		<p>This JSN provides a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 solid panel, 67"H (1702mm) x 48"W (1219mm); 1 solid panel, 47"H (1194mm) x 48"W (1219mm); 1 solid panel, 47"H (1194mm) x 24"W (610mm); 1 panel connector, 2-way corner, 67"H (1702mm); 2 panel-to-panel connectors; 																

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
		2 finished end hardware kits; 1 cantilevered corner work surface, 48"W (1219mm); 2 cantilevered work surfaces, 24"W (610mm); 1 transaction countertop, 72"W (1829mm); 1 lockable flipper unit, 48"w (1219mm); 1 lockable flipper unit, 24" W (610 mm); 1 light, 48"W (1219mm); 1 light, 24"W (610mm); 1 tack board, 48"W (1219mm); 1 tack board 24"W (610mm); 1 tool rail, 24"W (610mm); 2 paper trays; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal box/box/file and 2 support panels																	
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			EA	67	170	82	225 lb 103 kg	1: 120 2: --	1 --	2 --	0 NO YES	NO YES	--	--					

E0084	6530	Workstation, Corner Work Surf, Free Stand, 72x72																	
		THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware Kits 3 Lockable Flipper Units 3 Lights 2 Tackboards 2 Tool Rails 2 Paper Trays 1 Diagonal Tray 2 Cantilevered Work Surfaces 1 Cantilevered Corner Work Surface 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels																	
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			EA	67	170	77	200 lb 91 kg	1: 120 2: --	1 --	2 --	60 NO YES	NO YES	--	--					

E0087	6530	Workstation, Corner w/Peds, Free Standing, 72x72																	
		THIS TYPICAL INCLUDES: 4 Solid Panels, 67"H (1702mm) x 36"W (914mm) 2 Panel-to-Panel Connectors 2 Panel Connectors, 2-Way Corner, 67"H (1702mm) 2 Finished End Hardware Kits 1 Cantilevered Corner Work Surface, 36"W (914mm) 2 Cantilevered Work Surfaces, 36"W (914mm) 2 Lockable Flipper Units, 36"W (914mm) 2 Lights, 36"W (914mm) 2 Tackboards, 36"W (914mm) 1 Tool Rail, 36"W (914mm) 2 Paper Trays 1 Diagonal Tray 1 Adjustable Keyboard Tray																	

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I R A F A H	UTILITIES 1 2 3 4 5 6						
		2 Mobile Pedestal Box/Box/Files 1 Support Panel									
		UNIT OF ISSUE: EA	HEIGHT IN: 67 CM: 170	WIDTH: 79 DEPTH: 196	DEPTH: 77 WEIGHT: 200 lb 91 kg	WEIGHT: 200 lb 91 kg	VOLTS 1: 120 2: --	PHASE 1: 1 2: --	AMPS 1: 2 2: --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --
E0090	6530	Workstation, L-Shaped, Free Standing, 72x72	C C C C --	-- A -- -- -- --							
		THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware Kits 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels									
		UNIT OF ISSUE: EA	HEIGHT IN: 67 CM: 170	WIDTH: 77 DEPTH: 196	DEPTH: 77 WEIGHT: 250 lb 114 kg	WEIGHT: 250 lb 114 kg	VOLTS 1: 120 2: --	PHASE 1: 1 2: --	AMPS 1: 2 2: --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --
E0093	6530	Workstation, L-Transaction 48, Free Stand, 96x72	C C C C --	-- A -- -- -- --							
		THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 3 Finished End Hardware Kits 2 Lockable Flipper Units 2 Lights 1 Tack board 2 Tool Rails 2 Paper Trays 1 Diagonal Tray 2 Cantilevered Work Surfaces 1 Cantilevered Corner Work Surface 1 Transaction Countertop 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels [The database electrical requirement is only for the module's lights.]									
		UNIT OF ISSUE: EA	HEIGHT IN: 67 CM: 170	WIDTH: 101 DEPTH: 208	DEPTH: 82 WEIGHT: 275 lb 125 kg	WEIGHT: 275 lb 125 kg	VOLTS 1: 120 2: --	PHASE 1: 1 2: --	AMPS 1: 2 2: --	HZ: 0 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --
E0096	6530	Workstation, L-Transaction 72, Free Stand, 72x96	C C C C --	-- A -- -- -- --							
		THIS TYPICAL INCLUDES: 2 Solid Panels, 67"H (1702mm) x 48"W (1219mm) 1 Solid Panel, 47"H (1194mm) x 48"W(1219mm) 1 Solid Panel, 47"H (1194mm) x 24"W (610mm) 1 Panel Connector, 2-Way Corner, 67"H (1702mm) 2 Panel-to-Panel Connectors 2 Finished End Hardware 1 Cantilevered, Corner Work Surface, 48"W (1219mm)									

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

- 1 Cantilevered, Work Surface, 48"W (1219 mm)
- 1 Cantilevered, Work Surface, 24"W (610mm)
- 1 Transaction Countertop, 72"W (1829m)
- 2 Lockable Flipper Units, 48"W (1219mm)
- 2 Lights, 48W (1219mm)
- 1 Tack board, 48"W (1219mm)
- 1 Tack board, 24"W (610mm)
- 1 Tool Rail, 48"W (1219mm)
- 2 Paper Trays
- 2 Diagonal Trays
- 1 Adjustable Keyboard Tray
- 1 Mobile Pedestal, Box/File
- 2 Support Panels

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	67	77	106	106	250 lb	1:	120	1	2	60
	CM:	170	196	269	114 kg	2:	--	--	--	NO
										DEPENDENT: YES

E0099	6530	Workstation, Corner Work Surf, Free Stand, 72x96	C	C	C	C	--	--	A	--	--	--	--
-------	------	---	---	---	---	---	----	----	---	----	----	----	----

THIS TYPICAL INCLUDES:

- 3 Solid Panels, 67"H (1702mm) x 48"W (1219mm)
- 1 Solid Panel, 67"H (1702mm) x 24"W (610mm)
- 2 Panel-to-Panel Connectors
- 1 Panel Connector, 2-Way Corner, 67"H (1702mm)
- 2 Finished End Hardware Kits
- 1 Cantilevered Corner Work Surface, 48"W (1219mm)
- 1 Cantilevered Work Surface, 48"W (1219mm)
- 1 Cantilevered Work Surface, 24"W (610mm)
- 2 Lockable Flipper Units, 48"W (1219mm)
- 1 Lockable Flipper Unit, 24"W (610mm)
- 2 Lights, 48"W (1219mm)
- 1 Light, 24"W (610mm)
- 2 Tackboards, 48"W (1219mm)
- 2 Tool Rails, 24"W (610mm)
- 2 Paper Trays
- 1 Diagonal Tray
- 1 Adjustable Keyboard Tray
- 1 Mobile Pedestal, Box/Box/File
- 2 Support Panels

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	67	77	101	101	251 lb	1:	120	1	2	60
	CM:	170	196	257	114 kg	2:	--	--	--	NO
										DEPENDENT: YES

E0102	6530	Workstation, L-Shaped w/Files, Free Stand, 72x120	C	C	C	C	--	--	A	--	--	--	--
-------	------	--	---	---	---	---	----	----	---	----	----	----	----

This JSN will provide a whole work station typical to quickly plan work areas in administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:

- 3 solid panels, 85"H (2159mm) x 48"W (1219mm);
- 3 hanging file drawers, 48"W (1219mm);
- 2 solid panels, 85"H (2159mm) x 24"W (610mm);
- 2 tackboards, 48"W (1219mm);
- 2 soiled panels, 53"H (1346mm) x 24"W (610mm);
- 2 tool rails, 24"W (610mm);
- 3 panel connectors, 2-way corner, 85"H (2159mm);
- 2 paper trays;
- 3 panel-to-panel connectors;
- 2 diagonal trays;
- 2 finished end hardware;
- 1 adjustable keyboard tray;

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I					UTILITIES					
				R	A	F	A	H	1	2	3	4	5	6

1 cantilevered work surface, 72"W (1829mm);
 2 mobile pedestal box/files;
 1 cantilevered work surface, 48"W (1219mm);
 3 lockable flipper units, 48"W (1219mm);
 1 shelf, 24"W (610mm);
 1 shelf, storage/display, 24"W (610mm);
 2 shelves, storage/display, 48"W (1219mm);
 3 lights, 48"W (1219mm) and 1 pencil drawer. [The database electrical requirement is only for the module's lights.]

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:		
OF ISSUE:	IN:	80	79	127	350 lb	1:	120	1	2	HZ SWITCH: NO	
EA	CM:	203	201	323	159 kg	2:	--	--	--	DEPENDENT: YES	--

E0105	6530	Workstation, U-Transaction 72, Free Stand, 108x72	C	C	C	C	--	--	A	--	--	--	--
-------	------	--	---	---	---	---	----	----	---	----	----	----	----

THIS TYPICAL INCLUDES:

7 Standard Solid Panels
 4 Panel-to-Panel Connectors
 2 Panel Connectors, 2-Way Corner
 3 Finished End Hardware Kits
 2 Lockable Flipper Units
 4 Shelves, Storage/Display
 4 Lights
 3 Tackboards
 2 Tool Rails
 2 Paper Trays
 1 Diagonal Tray
 3 Cantilevered Work Surfaces
 1 Transaction Countertop
 1 Adjustable Keyboard Tray
 1 Hanging Pedestal, Box/File
 1 Pencil Drawer
 2 Support Panels

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:		
OF ISSUE:	IN:	67	121	77	300 lb	1:	120	1	3	HZ SWITCH: NO	
EA	CM:	170	307	196	137 kg	2:	--	--	--	DEPENDENT: YES	--

E0108	6530	Workstation, U-Shaped, Free Standing, 108x72	C	C	C	C	--	--	A	--	--	--	--
-------	------	---	---	---	---	---	----	----	---	----	----	----	----

THIS TYPICAL INCLUDES:

7 Standard Solid Panels
 4 Panel-to-Panel Connectors
 2 Panel Connectors, 2-Way Corner
 2 Finished End Hardware
 3 Lockable Flipper Units
 4 Shelves, Storage/Display
 5 Lights
 4 Tackboards
 2 Tool Rails
 2 Paper Trays
 1 Diagonal Tray
 3 Cantilevered Work Surfaces
 1 Adjustable Keyboard Tray
 1 Mobile Pedestal, Box/File
 1 Pencil Drawer
 2 Support Panels

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:		
OF ISSUE:	IN:	67	108	77	350 lb	1:	120	1	3	HZ SWITCH: NO	
EA	CM:	170	274	196	159 kg	2:	--	--	--	DEPENDENT: YES	--

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
E0111	6530	Workstation, U-Transact 72 w/Cab, Free Std, 72x84	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>This JSN will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES:</p> <p>1 Freestanding Cabinet, 67"H (1702mm) x 30"W (762mm) w/Lockable Flipper Unit and 2 Lateral File Drawers</p> <p>1 Freestanding Cabinet, 67"H (1702mm) x 30"W (762mm)</p> <p>2 Interior Shelves</p> <p>2 Organizers, Horizontal/Diagonal</p> <p>1 Organizer, Horizontal</p> <p>2 Solid Panels, 47"H (1194mm) X 48"W (1219mm)</p> <p>2 Solid Panels, 47"H (1194mm) x 24"W (610mm)</p> <p>2 Panel Connectors, 2-Way Corner, 47"H (1194mm)</p> <p>1 Finished End Hardware Kits</p> <p>1 Cantilevered Work Surface, 72"W (1829mm)</p> <p>1 Cantilevered Work Surface, 48"W (1219mm)</p> <p>1 Tack board, 48"W (1219mm)</p> <p>1 Adjustable Keyboard Tray</p> <p>1 Mobile Pedestal, Box/Box/File</p> <p>1 Support Panel</p> <p>1 Pencil Drawer</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--					
EA		IN:	67	83	97	300 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	170	211	246	137 kg	2:	--	--	--									
E0114	6530	Workstation, U-Shaped Peninsula, Free Stand, 72x96	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
<p>This JSN will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES:</p> <p>2 Solid Panels, 85"H (2159mm) x 48"W (1219mm)</p> <p>2 Solid Panels, 85"H (2159mm) x 24"W (610mm)</p> <p>1 Solid Panel, 85"H (2159mm) x 30"W (762mm)</p> <p>2 Solid Panels, 47"H (1194mm) x 24"W (762mm)</p> <p>3 Panel Connectors, 2-Way Corner, 85"H (2159mm)</p> <p>3 Panel-to-Panel Connectors</p> <p>2 Finished End Hardware</p> <p>1 Cantilevered Work Surface, 72"W (1829mm)</p> <p>1 Cantilevered Work Surface, 48"W (1219mm)</p> <p>1 Peninsula Work Surface, 72"W (1829mm)</p> <p>2 Lockable Flipper Units, 48"W (1219mm)</p> <p>1 Lockable Flipper Unit, 30"W (762mm)</p> <p>1 Shelf, 24"W (610mm)</p> <p>2 Shelves, Storage/Display, 48"W (1219mm)</p> <p>1 Shelf, Storage/Display, 30"W (762mm)</p> <p>1 Shelf, Storage/Display, 24"W (610mm)</p> <p>2 Lights, 48"W (1219mm)</p> <p>1 Light, 30"W (762mm)</p> <p>1 Light, 24"W (610mm)</p> <p>2 Tackboards, 48"W (1219mm)</p> <p>1 Tool Rail, 30"W (762mm)</p> <p>1 Tool Rail, 24"W (610mm)</p> <p>2 Paper Trays</p> <p>2 Diagonal Trays</p> <p>1 Adjustable Keyboard Tray</p> <p>2 Mobile Pedestal, Box/Files [The database electrical requirement is only for the module's lights.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--					
EA		IN:	80	80	110	300 lb	1:	120	1	3	DEPENDENT:	YES	--						
		CM:	203	203	279	137 kg	2:	--	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES														
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
E0117	6530	Workstation, Straight, Free Standing, 48" W	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--		
<p>This JSN will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 solid panel, 67"H (1702mm) x 48"W (1219mm); 1 solid panel, 47"H (1194mm) x 24"W (610mm); 1 panel connector, 2-way corner, 67"H (1702mm); 2 finished end hardware kits; 1 cantilevered work surface, 48"W (1219mm); 1 lockable flipper unit, 48"W (1219mm); 1 light, 48"W (1219mm); 1 tack board, 48"W (1219mm); 1 tool rail, 48"W (1219mm); 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file and 1 support panel. [The database electrical requirement is only for the module's lights.] 																				
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		CM:	67	43	24	152 lb	1:	120	1	1	60	NO	--							
			170	109	61	69 kg	2:	--	--	--	DEPENDENT:	YES	--							
E0120	6530	Workstation, Straight, Free Standing, 60" W	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--		
<p>This JSN will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 Solid Panels, 67"H (1702mm) x 30"W (762mm) 1 Solid Panel, 47"H (1194mm) x 24"W (610mm) 1 Panel - to Panel Connector 1 Panel Connector, 2-Way Corner, 67"H (1702mm) 2 Finished End Hardware Kits 1 Cantilevered, Work Surface, 60"W (1524mm) 2 Lockable Flipper Units, 30"W (762mm) 2 Lights, 30"W (762mm) 1 Tack board, 30"W (762mm) 1 Tool Rail, 30"W (762mm) 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/Box/File 1 Support Panel 																				
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		CM:	67	65	24	200 lb	1:	120	1	2	60	NO	--							
			170	165	61	91 kg	2:	--	--	--	DEPENDENT:	YES	--							
E0123	6530	Workstation, Straight, Free Standing, 72" W	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--		
<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Solid Panel, 85"H (2159mm) x 48"W (1219mm) 1 Solid Panel, 85"H (2159mm) x 24"W (610mm) 2 Solid Panels, 47"H (1194mm) x 24"W (610mm) 2 Panel Connectors, 2-Way Corner, 85"H (2159mm) 1 Panel-to-Panel Connector 2 Finished End Hardware Kits 1 Cantilevered, Work Surface, 72"W (1829mm) 1 Lockable Flipper Unit, 48"W (1219mm) 1 Lockable Flipper Unit, 24"W (610mm) 1 Shelf, Storage/Display, 48"W (1219mm) 1 Shelf, Storage/Display, 24"W (610mm) 1 Light, 48"W (1219mm) 1 Light, 24"W (610mm) 																				

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
		1 Tack board, 48"W (1219mm) 1 Tool Rail, 24"W (610mm) 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/Box/File																
			UNIT OF ISSUE: EA	HEIGHT IN: 85 CM: 216	WIDTH 80 DEPTH 61	DEPTH 24 WEIGHT 250 lb 114 kg	WEIGHT 250 lb 114 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 2 --	HZ: 0 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --						
E0126	6530	Workstation, Straight, Dbl Sided, Free Std, 75" W																
		This JSN will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES: 2 Freestanding Cabinets, 67"H (1702mm) x 36"W (914mm) w/Lockable Flipper Units 2 Organizers, Horizontal/Diagonal 2 Interior Shelves 2 Tackable Display Screens 2 Peninsulas with Cutouts, 75"W (1905mm) 2 Mobile Pedestal, Box/Box/Files 2 Marker Boards																
			UNIT OF ISSUE: EA	HEIGHT IN: 67 CM: 170	WIDTH 136 DEPTH 72 DEPTH 183	DEPTH 72 WEIGHT 300 lb 137 kg	WEIGHT 300 lb 137 kg	VOLTS 1: -- 2: --	PHASE -- --	AMPS -- --	HZ: -- HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --						
E0202	6530	Worksurface, w/Overhead Cab, Wall Mtd, 24" W																
		THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface																
			UNIT OF ISSUE: EA	HEIGHT IN: 80 CM: 203	WIDTH 24 DEPTH 61	DEPTH 24 WEIGHT 75 lb 34 kg	WEIGHT 75 lb 34 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 1 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --						
E0204	6530	Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 24" W																
		THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface 2 Storage Frames 2 Drawers, 3"H (76mm) 3 Drawers, 6"H (152mm)																
			UNIT OF ISSUE: EA	HEIGHT IN: 80 CM: 203	WIDTH 24 DEPTH 61	DEPTH 24 WEIGHT 101 lb 46 kg	WEIGHT 101 lb 46 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 1 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --						

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES										
				R	A	F	A	H							1	2	3	4	5	6
E0206	6530	Worksurface, w/Overhead Cab, Wall Mtd, 30" W	C C C C --	--	A	--	--	--	--											
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface																				
UNIT OF ISSUE: EA		HEIGHT IN: 80	WIDTH CM: 203	DEPTH 24	DEPTH 61	WEIGHT 100 lb 46 kg	VOLTS 1: 120 2: --	PHASE 1	AMPS 1	HZ: 0	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --							
E0208	6530	Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 30" W	C C C C --	--	A	--	--	--	--											
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface 2 Storage Frames 2 Drawers, 3"H (76mm) 3 Drawers, 6"H (152mm)																				
UNIT OF ISSUE: EA		HEIGHT IN: 80	WIDTH CM: 203	DEPTH 24	DEPTH 61	WEIGHT 125 lb 57 kg	VOLTS 1: 120 2: --	PHASE 1	AMPS 1	HZ: 0	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --							
E0210	6530	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	C C C C --	--	A	--	--	--	--											
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface																				
UNIT OF ISSUE: EA		HEIGHT IN: 80	WIDTH CM: 203	DEPTH 48	DEPTH 61	WEIGHT 100 lb 46 kg	VOLTS 1: 120 2: --	PHASE 1	AMPS 1	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --							
E0212	6530	Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 48" W	C C C C --	--	A	--	--	--	--											
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface 4 Storage Frames 4 Drawers, 3"H (76mm) 6 Drawers, 6"H (152mm)																				
UNIT OF ISSUE: EA		HEIGHT IN: 80	WIDTH CM: 203	DEPTH 48	DEPTH 61	WEIGHT 152 lb 69 kg	VOLTS 1: 120 2: --	PHASE 1	AMPS 1	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --							

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
E0214	6530	Worksurface, w/Overhead Cab, Wall Mtd, 60" W	C C C C --	--	A	--	--	--	--						
THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips 2 Lockable Flipper Units 2 Shelves, Storage/Display 2 Lights 1 Cantilevered Work Surface															
UNIT OF ISSUE: EA		HEIGHT IN: 80 CM: 203	WIDTH 60	DEPTH 24 61	WEIGHT 125 lb 57 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 1 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --			
E0216	6530	Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 60" W	C C C C --	--	A	--	--	--	--						
THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips 2 Lockable Flipper Units 2 Shelves, Storage/Display 2 Lights 1 Cantilevered Work Surface 4 Storage Frames 4 Drawers, 3"H (76mm) 6 Drawers, 6"H (152mm)															
UNIT OF ISSUE: EA		HEIGHT IN: 80 CM: 203	WIDTH 60	DEPTH 24 61	WEIGHT 175 lb 80 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 1 --	HZ: 0	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --			
E0218	6530	Worksurface, w/Overhead Cab, Wall Mtd, 72" W	C C C C --	--	A	--	--	--	--						
THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips 2 Lockable Flipper Units 2 Shelves, Storage/Display 2 Lights 1 Cantilevered Work Surface															
UNIT OF ISSUE: EA		HEIGHT IN: 80 CM: 203	WIDTH 72 183	DEPTH 24 61	WEIGHT 125 lb 57 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 2 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --			
E0220	6530	Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 72" W	C C C C --	--	A	--	--	--	--						
THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips 2 Lockable Flipper Units 2 Shelves, Storage/Display 2 Lights 1 Cantilevered Work Surface 4 Storage Frames 4 Drawers, 3"H (76mm) 6 Drawers, 6"H (152mm)															
UNIT OF ISSUE: EA		HEIGHT IN: 80 CM: 203	WIDTH 72 183	DEPTH 24 61	WEIGHT 176 lb 80 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 2 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
E0222	6530	Worksurface, Computer, O/H Cab, Wall Mtd, 48" W	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--		
THIS TYPICAL INCLUDES:																			
2 Vertical Hanging Strips																			
1 Lockable Flipper Unit																			
1 Shelf, Storage/Display																			
1 Light																			
1 Tack board																			
1 Cantilevered Work Surface																			
1 Adjustable Keyboard Tray																			
1 CPU Holder																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	80	48	24	130 lb	1:	120	1	1	0	NO	--						
			203	122	61	59 kg	2:	--	--	--	DEPENDENT:	YES	--						
E0224	6530	Worksurface, Computer, O/H Cab, Wall Mtd, 60" W	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--		
THIS TYPICAL INCLUDES:																			
3 Vertical Hanging Strips																			
2 Lockable Flipper Units																			
2 Shelves, Storage/Display																			
2 Lights																			
1 Tack board																			
2 Tool Rails																			
2 Paper Trays																			
1 Diagonal Tray																			
1 Cantilevered Work Surface																			
1 Adjustable Keyboard Tray																			
1 Stationary Pedestal, Box/Box/File																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	80	60	24	175 lb	1:	120	1	2	0	NO	--						
			203	152	61	80 kg	2:	--	--	--	DEPENDENT:	YES	--						
E0226	6530	Worksurface, Computer, O/H Cab, Wall Mtd, 72" W	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--		
THIS TYPICAL INCLUDES:																			
3 Vertical Hanging Strips																			
2 Lockable Flipper Units																			
2 Shelves, Storage/Display																			
2 Lights																			
1 Tack board																			
2 Tool Rails																			
2 Paper Trays																			
1 Diagonal Tray																			
1 Cantilevered Work Surface																			
1 Adjustable Keyboard Tray																			
1 Stationary Pedestal, Box/Box/File																			
1 Pencil Drawer																			
1 CPU Holder																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	80	72	24	200 lb	1:	120	1	2	60	NO	--						
			203	183	61	91 kg	2:	--	--	--	DEPENDENT:	YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES										
				R	A	F	A	H							1	2	3	4	5	6
E0233	6530	Office, Provider, L-Shaped, Wall Mtd, 102"W x 96"D	C C C C --	--	A	--	--	--	--											
THIS TYPICAL INCLUDES: 6 Vertical Hanging Strips 3 Lockable Flipper Units 6 Shelves, Storage/Display 3 Lights 2 Tackboards 2 Tool Rails 2 Paper Trays 1 Diagonal Tray 2 Cantilevered Work Surfaces 1 Cantilevered Corner Work Surface 1 Freestanding Work Surface 1 Pencil Drawer 2 Hanging File Drawers 1 Adjustable Keyboard Tray 1 Freestanding Pedestal, Box/Box/File 1 CPU Holder																				
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		CM:	80	105	99	302 lb	1:	120	1	2	60	NO	--							
			203	267	251	138 kg	2:	--	--	--	DEPENDENT:	YES	--							
E0236	6530	Office, Provider, L-Shaped, Wall Mtd, 110"W x 72"D	C C C C --	--	A	--	--	--	--											
THIS TYPICAL INCLUDES: 4 Vertical Hanging Strips 2 Lockable Flipper Units 5 Shelves, Storage/Display 2 Lights 1 Tack board 2 Tool Rails 2 Paper Trays 1 Diagonal Tray 1 Cantilevered Work Surface 1 Freestanding Work Surface 2 Hanging File Drawers 1 Adjustable Keyboard Tray 1 Freestanding Pedestal, Box/Box/File																				
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		CM:	80	123	75	300 lb	1:	120	1	1	60	NO	--							
			203	312	190	137 kg	2:	--	--	--	DEPENDENT:	YES	--							
E0239	6530	Office, Provider, L-Shaped, Wall Mtd, 120"W x 48"D	C C C C --	--	A	--	--	--	--											
THIS TYPICAL INCLUDES: 7 Vertical Hanging Strips 2 Lockable Flipper Units 7 Shelves, Storage/Display 2 Lights 2 Tackboards 4 Tool Rails 2 Paper Trays 1 Diagonal Tray 2 Cantilevered Work Surfaces 1 Pencil Drawer 1 Adjustable Keyboard Tray 1 Hanging Pedestal, Box/File																				

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I	UTILITIES
				R A F A H	1 2 3 4 5 6

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	80	203	51	300 lb	1:	120	1	60	
				137 kg	2:	--	--	NO	--
								DEPENDENT:	
								YES	--

E0251	6530	Exam, Workstation & Storage, Wall Mtd, 3 Walls	C C C C --	-- A -- -- -- --
-------	------	--	------------	------------------

THIS TYPICAL INCLUDES:

- 11 VERTICAL HANGING STRIPS
- 1 LOCKABLE FLIPPER UNIT
- 1 SHELF, STORAGE/DISPLAY
- 1 LIGHT
- 1 TACKBOARD
- 1 CANTILVERED WORK SURFACE
- 1 HANGING PEDESTAL, BOX/FILE
- 1 ADJUSTABLE KEYBOARD TRAY
- 4 SUPPORT RAIL
- 2 EQUIPMENT RAIL
- 5 DISPENSING BINS
- 3 STORAGE FRAME WITH DOOR
- 1 STORAGE FRAME
- 1 DRAWER, 3" H
- 1 DRAWER, 6" H
- 1 DRAWER, 9" H
- 3 TRAY/SHELF FOR STORAGE FRAME

DRAWER ORGANIZER BINS [The database width dimension (177" or 14' 9") is the minimum wall distance (three walls) necessary to install this configuration.]

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	80	203	24	200 lb	1:	120	1	60	
				91 kg	2:	--	--	NO	--
								DEPENDENT:	
								YES	--

E0254	6530	Exam, Workstation & Markerboard, Wall Mtd, 48" W	C C C C --	-- A -- -- -- --
-------	------	--	------------	------------------

THIS TYPICAL INCLUDES:

- 4 Vertical Hanging Strips
- 1 Lockable Flipper Unit
- 1 Shelf, Storage/Display
- 1 Light
- 2 Tackboards
- 1 Marker Board
- 1 Cantilevered Work Surface
- 1 Adjustable Keyboard Tray
- 1 CPU Holder [The database width dimension reflects the minimum wall distance needed to install this configuration.]

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	80	203	24	125 lb	1:	120	1	60	
				57 kg	2:	--	--	NO	--
								DEPENDENT:	
								YES	--

E0257	6530	Exam, Workstation & Sink, Wall Mtd, 48" W	C C C C --	D A -- -- -- --
-------	------	---	------------	-----------------

THIS TYPICAL INCLUDES;

- 1 FLIP DRAW UNIT W/LOCK 13D X 48W X 15-1/2H
- 3 WALL STRIP 84H
- 1 TASKLIGHT, WARM WHITE 3500K 24W
- 1 EQUIPMENT RAIL SYSTEM 48W
- 1 SINK UNIT, CANTILEVERED, FOR STORAGE 24D X 48W
- 1 C FRAME 22W X 17D
- 1 DRAW A-SIZE 3H
- 1 DRAW B-SIZE 6H
- 1 DRAW C-SIZE 9H
- 1 LABEL CLIP 19W 12/PACKAGE

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

- 1 ORGANIZER KIT A-SIZE
 1 ORGANIZER KIT B-SIZE
 2 RAIL CLAMP
 1 SINK AND FAUCET

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:		
OF ISSUE:	IN:	92	48	24	125 lb	1:	120	1	1	HZ SWITCH: NO	BTUs / HR:
EA	CM:	234	122	61	57 kg	2:	--	--	--	DEPENDENT: YES	--

E0260	6530	Exam, Workstation & Cart, Free Standing, 84" W	C	C	C	C	--	--	A	--	--	--	--
-------	------	--	---	---	---	---	----	----	---	----	----	----	----

THIS TYPICAL INCLUDES:

- 1 Vertical Hanging Strip
 1 Standard Solid Panel
 1 Standard Open Panel
 1 Panel Connector, 2-Way Corner
 1 Finished End Hardware Kit
 1 Lockable Flipper Unit
 1 Light
 1 Tack board
 1 Tool Rail
 2 Paper Trays
 1 Diagonal Tray
 1 Cantilevered Work Surface
 1 Freestanding Work Surface
 1 Adjustable Keyboard Tray
 1 Mobile Pedestal, Box/File
 1 Support Panel
 2 Storage Frames
 1 Mobile Cart w/Top Surface
 2 Drawers, 3"H (76mm)
 2 Drawers, 6"H (152mm)
 1 Drawer, 9"H (229mm)

Drawer Organizer Bins [The database width dimension reflects the minimum distance needed to install this configuration.]

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:		
OF ISSUE:	IN:	67	84	24	200 lb	1:	120	1	1	HZ SWITCH: NO	BTUs / HR:
EA	CM:	170	213	61	91 kg	2:	--	--	--	DEPENDENT: YES	--

E0272	6530	Treatment, Sink, Workcenter, Wall Mtd, 120" W	F	F	F	F	--	D	A	--	--	--	--
-------	------	---	---	---	---	---	----	---	---	----	----	----	----

THIS TYPICAL INCLUDES:

- 3 Vertical Hanging Strips
 1 Wall Mounted Rail
 1 Lockable Flipper Unit
 1 Shelf, Storage/Display
 1 Light
 1 Cantilevered Work Surface
 1 Cantilevered Sink Adaptable Work Surface
 4 Storage Frames
 1 Supply Locker
 6 Drawers, 3"H (76mm)
 10 Drawers, 6"H (152mm)
 1 Sink & Faucet
 1 Foot Pedal
 3 Tray/Shelf
 Drawer Organizer Bins

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:		
OF ISSUE:	IN:	80	129	24	275 lb	1:	120	1	1	HZ SWITCH: NO	BTUs / HR:
EA	CM:	203	328	61	125 kg	2:	--	--	--	DEPENDENT: YES	--

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
E0275	6530	Treatment, Sink, Workcenter, Cart, Wall Mtd, 105"W	F	F	F	F	--	D	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES: 3 vertical hanger strips; 2 lockable flipper units; 1 light; 1 tack board; 1 cantilevered, sink adaptable work surface w/attached backsplash; 1 cantilevered work surface w/attached backsplash; 4 storage frames; 4 drawers, 3"H (76mm); 5 drawers, 6"H (152mm); 2 drawers, 9"H (229mm); 1 mobile cart; 1 extended top surface; drawer organizer bins.																
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 88	DEPTH 107	WEIGHT 220 lb 100 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 1 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --					
E0281	6530	Workcenter, Trauma, w/Sink, Wall Mtd, 171" W	F	F	F	F	--	D	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES:: 3 vertical hanger strips; 1 lockable flipper unit; 1 light; 1 cantilevered, sink adaptable work surface w/attached backsplash and space for storage frame; 1 height adjustable table; 3 storage frames; 3 large storage containers; 1 support rail; 7 tray/shelves; 9 drawers, 3"H (76mm); 9 drawers, 6"H (152mm); 4 drawers, 9"H (229mm); 4 wire shelves; 1 tray/shelf divider; 1 chest tube rack; drawer organizer bins.																
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 88	DEPTH 183	WEIGHT 375 lb 171 kg	VOLTS 1: 2:	PHASE 1 --	AMPS 1 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --					
E0287	6530	Workcenter, Med Prep, w/Sink, Wall Mtd, 117"W	F	F	F	F	--	D	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES: 4 Vertical Hanger Strips 3 Lockable Flipper Units 3 Shelves, Storage/Display 2 Lights 16 Bins, 4-9/16"W (114mm) x 2-3/16"H (57mm) 1 Cantilevered, Sink Adaptable Work Surface w/Attached Backsplash 2 Cantilevered Work Surfaces w/Attached Backsplash 1 Large Storage Container 1 E1500 Wall Mounting Rail is required 2 Tray/Shelves 2 Locked Drawers w/Locked Lid, 6"H (152mm) 3 8-Bin Cassette Assemblies 2 Drawers, 3"H (76mm) 2 Drawers, 6"H (152mm) Drawer Organizer Bins																

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES									
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	88	117	24	300 lb	120	1	1	60	NO	--		
				CM:				2:			DEPENDENT:				
				224	297	61	137 kg	--	--	--	YES	--			
E0293	6530	Sink & Locker, Soiled Utility, Wall Mtd, 78"W	F	F	F	F	--	D	--	--	--	--			
THIS TYPICAL INCLUDES:															
1 E1500 Wall Mounting Rail is required															
1 Freestanding Sink Adaptable Cabinet w/Integral Backsplash															
1 Supply Locker															
1 Sink and Faucet															
2 Drawers, 9"H (229mm)															
4 Wire Shelves															
Consider the need for an E0921 to transport the locker from place to place.															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	78	78	24	275 lb	--	--	--	--	NO	--		
				CM:				2:			DEPENDENT:				
				198	198	61	125 kg	--	--	--	NO	--			
E0296	6530	Sink & Storage, Soiled Utility, Wall Mtd, 72" W	F	F	F	F	--	D	--	--	--	--			
THIS TYPICAL INCLUDES:															
3 Vertical Hanging Strips															
2 Shelves															
1 Cantilevered Sink Adaptable Work Surface															
1 Cantilevered Work Surface with Backsplash															
1 Support Rail															
1 Storage Cabinet with Door															
1 Drawer, 6"H (152mm)															
1 Foot Pedal for Sink Operation															
1 Sink and Faucet															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	80	72	24	110 lb	--	--	--	--	NO	--		
				CM:				2:			DEPENDENT:				
				203	183	61	50 kg	--	--	--	NO	--			
E0299	6530	Sink & Storage, Soiled Utility, Wall Mtd, 96" W	F	F	F	F	--	D	A	--	--	--			
THIS TYPICAL INCLUDES:															
3 vertical hanger strips;															
3 extra deep shelves;															
1 light;															
1 cantilevered, sink adaptable work surface w/attached backsplash;															
1 cantilevered work surface w/attached backsplash;															
2 drawers, 6"H (152mm) and 1 sink with faucet.															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	92	99	24	135 lb	120	1	1	60	NO	--		
				CM:				2:			DEPENDENT:				
				234	251	61	62 kg	--	--	--	YES	--			
E0305	6530	Sink & Storage, Clean Utility, Wall Mtd, 72" W	F	F	F	F	--	D	--	--	--	--			
THIS TYPICAL INCLUDES:															
3 Vertical Hanging Strips															
2 Shelves															
1 Cantilevered Sink Adaptable Work Surface															
1 Cantilevered Work Surface and Backsplash															
1 Storage Cabinet with Door															
1 Support Rail															
1 Drawer, 6"H (152mm)															
1 Sink and Faucet															
1 Foot Pedal for Sink Operation															

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I	UTILITIES					
				R A F A H	1	2	3	4	5	6

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
OF ISSUE:	IN: 80	72	24	110 lb	1: --	--	--	--	NO
EA	CM: 203	183	61	50 kg	2: --	--	--	DEPENDENT: NO	--

E0308	6530	Sink & Locker, Clean Utility, Wall Mtd, 121" W	F F F F --	D -- -- -- -- --
-------	------	---	------------	------------------

THIS TYPICAL INCLUDES:

- 2 vertical hanger strips;
- 1 lockable flipper unit;
- 1 cantilevered, sink adaptable work surface w/attached backsplash;
- 3 large storage containers;
- 1 E1500 Wall Mounting Rail is required
- 7 tray/shelves;
- 4 drawers, 3"H (76mm);
- 6 drawers, 6"H (152mm);
- 1 drawer, 9"H (229mm);
- 4 wire shelves;
- 1 tray/shelf divider;
- 1 sink with faucet and drawer organizer bins.

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
OF ISSUE:	IN: 88	135	24	175 lb	1: --	--	--	--	NO
EA	CM: 224	343	61	80 kg	2: --	--	--	DEPENDENT: NO	--

E0314	6530	Sink Area, Staff Lounge, Wall Mtd, 72" W	F F F F --	D A -- -- -- -- --
-------	------	---	------------	--------------------

THIS TYPICAL INCLUDES:

- 2 Vertical Hanging Strips
- 1 Lockable Flipper Unit
- 1 Shelf, Storage/Display
- 1 Light
- 1 Cantilevered Work Surface
- 1 Cantilevered Sink Adaptable Module
- 1 Storage Cabinet
- 1 Storage Cabinet with Door
- 2 Drawers, 4"H (102mm)
- 3 Drawers, 8"H (203mm)
- 1 Support Rail
- 1 Sink and Faucet

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
OF ISSUE:	IN: 80	75	24	176 lb	1: 120	1	1	60	NO
EA	CM: 203	190	61	80 kg	2: --	--	--	DEPENDENT: YES	--

E0403	6530	Nurse Station, Accessible w/Angle, Free Std, 96" W	F F F F --	-- A -- -- -- -- --
-------	------	---	------------	---------------------

Nurse Station typicals have non-powered steel frames with a pre-installed metal junction box for hard-wired electrical solutions configured to user specifications. Data modules and low voltage cabling can be routed freely within the frame. Electrical and/or data devices are not provided. The panel inserts are available in fabric, painted metal, tackable, acoustical, paper management, rail, glass, open and electrical/data accessible configurations. Typicals include panel inserts for both sides of steel frame. All electrical connections must be made by an electrical contractor. THIS TYPICAL INCLUDES:

- 1 steel frame w/low access;
- 2 steel frame;
- 1 cantilevered, low access work surface, 135 degree;
- 2 laminate panel inserts, 20"H (508mm);
- 1 panel insert, tackable, 16"H (406mm);
- 1 panel insert, paper mgmt. 16"H (406mm);
- 6 panel inserts, painted metal, 16"H (406mm);
- 2 countertops w/light support assembly, 16"D (406mm);
- 2 form trays, 6"W (152mm) and 1 form tray, 9"W (229mm).

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES																																																									
				R	A	F	A	H	1	2	3	4	5	6																																																					
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>107</td> <td>241</td> <td>112</td> <td>80 kg</td> <td>1: 120</td> <td>1</td> <td>15</td> <td>60</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2: --</td> <td>--</td> <td>--</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT:</td> <td>YES</td> </tr> </tbody> </table>													UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	107	241	112	80 kg	1: 120	1	15	60	--							2: --	--	--	NO	--										DEPENDENT:	YES											
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																									
EA	CM:	107	241	112	80 kg	1: 120	1	15	60	--																																																									
						2: --	--	--	NO	--																																																									
									DEPENDENT:	YES																																																									
E0406	6530	Nurse Station, Angle, Free Standing, 96" W		F	F	F	F	--	--	A	--	--	--	--																																																					
<p>Nurse Station typicals have non-powered steel frames with a pre-installed metal junction box for user defined hard-wired electrical solutions. Data modules and low voltage cabling can be routed freely within the frame. Electrical and/or data devices are not provided as part of the typical. Panel inserts are available in fabric, painted metal, tackable, acoustical, paper management, rail, glass, open and electrical/data accessible configurations. Typicals include panel inserts for both sides of the steel frame. All electrical connections must be made by an electrical contractor. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 3 steel frames; 1 cantilevered work surface, 135 Degrees; 1 panel insert, tackable, 16"H (406mm); 2 panel inserts, paper mgmt., 16"H (406mm); 9 panel inserts, painted metal; 1 countertop w/light support assembly, 16"D (406mm); 2 form trays, 9"W (229mm); 1 tape dispenser and 1 binder/file holder. 																																																																			
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>107</td> <td>241</td> <td>112</td> <td>91 kg</td> <td>1: 120</td> <td>1</td> <td>15</td> <td>0</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2: --</td> <td>--</td> <td>--</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT:</td> <td>YES</td> </tr> </tbody> </table>													UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	107	241	112	91 kg	1: 120	1	15	0	--							2: --	--	--	NO	--										DEPENDENT:	YES											
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																									
EA	CM:	107	241	112	91 kg	1: 120	1	15	0	--																																																									
						2: --	--	--	NO	--																																																									
									DEPENDENT:	YES																																																									
E0409	6530	Nurse Station, Admitting, Free Standing, 72" W		F	F	F	F	--	--	A	--	--	--	--																																																					
<p>Nurse Station typicals have non-powered steel frames with a pre-installed metal junction box for user defined hard-wired electrical solutions. Data modules and low voltage cabling can be routed freely within the frame. Electrical and/or data devices are not provided as part of the configuration. Panel inserts are available in fabric, painted metal, tackable, acoustical, paper management, rail, glass, open and electrical/data accessible styles. Typicals include panel inserts for both sides of the steel frame. All electrical connections must be made by an electrical contractor. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 steel frames, 54"H (1372mm) x 36"W (914mm); 3 steel frames, 38"H (965mm) x 24"W (610mm); 1 steel frame w/low access, 38"H (965mm) x 48"W (1219mm); 2 frame connectors, 3-way corner, 54"H (1372mm); 4 finished end hardware kits; 1 cantilevered work surface, 24"W (1219mm); 1 cantilevered, low access work surface, 48"W (1219mm); 1 pedestal, box/box/file; 2 laminate panel inserts, 20"H (508mm) x 48"W (1219mm); 1 panel insert, paper mgmt. 16"H (406mm) x 24"W (610mm); 11 panel inserts, painted metal, 16"H (406mm) x 24"W (610mm); 12 panel inserts, painted metal, 16"H (406mm) x 36"W (914mm); 1 diagonal tray and 2 paper trays. 																																																																			
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>165</td> <td>201</td> <td>152</td> <td>103 kg</td> <td>1: 120</td> <td>1</td> <td>15</td> <td>60</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2: --</td> <td>--</td> <td>--</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>DEPENDENT:</td> <td>YES</td> </tr> </tbody> </table>													UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	165	201	152	103 kg	1: 120	1	15	60	--							2: --	--	--	NO	--										DEPENDENT:	YES											
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																																									
EA	CM:	165	201	152	103 kg	1: 120	1	15	60	--																																																									
						2: --	--	--	NO	--																																																									
									DEPENDENT:	YES																																																									
E0412	6530	Nurse Station, Recept, Straight, Free Std, 96" W		F	F	F	F	--	--	A	--	--	--	--																																																					
<p>Nurse station typicals have non-powered steel frames with a pre-installed metal junction box for user defined hard-wired electrical solutions. Data modules and low-voltage cabling can be routed freely within the frame. Electrical and/or data devices are not provided with the nurse station. Panel inserts are available in fabric, painted metal, tackable, acoustical, paper management, rail, glass, open and electrical/data accessible styles. Typicals include panel inserts for both sides of the steel frame. All electrical connections must be made by an electrical contractor. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 steel frame w/low access, 38"H (965mm) x 48"W (1219mm); 1 steel frame, 38"H (965mm) x 48"W (1219mm); 2 steel frames, 38"H (965mm) x 24"W (610mm); 2 frame connectors, 2-way corner, 38"H (965mm); 																																																																			

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

2 finished end hardware kits;
 1 cantilevered work surface, 48"W (1219mm);
 1 cantilevered low access work surface, 48"W (1219mm);
 1 pedestal box/box/file;
 2 laminate panel inserts, 20"H (508mm) x 48"W (1219mm);
 1 panel insert, paper mgmt., 16"H (406mm) x 48"W (1219mm);
 3 panel inserts, painted metal, 16"H (406mm) x 48"W (1219mm);
 8 panel inserts, painted metal, 16"H (406mm) x 24"W (610mm);
 1 countertop w/light support assembly, 16"D (406mm) x 8'-0"L (1829mm);
 2 paper trays and
 1 mini-shelf.

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT LB:	WEIGHT KG:	VOLTS 1:	VOLTS 2:	PHASE	AMPS	HZ:	HZ SWITCH DEPENDENT:	BTUs / HR:
EA	38	97	116	91	251	114	120	--	1	15	60	NO	--

E0415	6530	Nurse Station, Recept, L-Shaped, Free Std, 96 x 96	F	F	F	F	--	--	A	--	--	--	--
-------	------	--	---	---	---	---	----	----	---	----	----	----	----

Nurse station typicals have non-powered steel frames with a pre-installed metal junction box for user defined hard-wired electrical solutions. Data modules and low voltage cabling can be routed freely within the frame. Electrical and/or data devices are not provided with the nurse station. Panel inserts are available in fabric, painted metal, tackable, acoustical, paper management, rail, glass, open and electrical/data accessible styles. Typicals include panel inserts for both sides of steel frame. All electrical connections must be made by an electrical contractor. THIS TYPICAL INCLUDES:

1 steel frame, 54"H (1372mm) x 48"W (1219mm);
 3 steel frames, 38"H (965mm) x 48"W (1219mm);
 2 steel frames, 38"H (965mm) x 24"W (610mm);
 1 frame connector, 2-way corner, 54"H (1372mm);
 2 frame connectors, 2-way corner, 38"H (965mm);
 2 finished end hardware kits;
 1 cantilevered corner work surface, 48"W (1219mm);
 2 cantilevered work surfaces, 48"W (1219mm); 2 pedestal box/box/files;
 1 fully adjustable keyboard tray;
 13 panel inserts, painted metal, 16"H (406mm) x 48"W (1219mm);
 8 panel inserts, painted metal, 16"H (406mm) x 24"W (610mm);
 3 panel inserts, paper mgmt., 16"H (406mm) x 24"W (1219mm);
 2 panel inserts, tackable, 16"H (406mm) x 48"W (1219mm);
 15 panel inserts, tackable, 16"H (406mm) x 48"W (1219mm);
 1 countertop w/light support assembly, 16"D (406mm) x 16'-0"L (4877mm);
 8 form trays, 9"W (229mm);
 4 form trays, 6"W (152mm) and
 6 form trays, 4"W (102mm).

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT LB:	WEIGHT KG:	VOLTS 1:	VOLTS 2:	PHASE	AMPS	HZ:	HZ SWITCH DEPENDENT:	BTUs / HR:
EA	54	137	110	279	300	137	120	--	1	15	60	NO	--

E0418	6530	Nurse Station, Medium, Free Standing	F	F	F	F	--	--	A	--	--	--	--
-------	------	--------------------------------------	---	---	---	---	----	----	---	----	----	----	----

Nurse station typicals have non-powered steel frames with a pre-installed metal junction box for user defined electrical solutions. Data modules and low voltage cabling can be routed freely within the frame. Electrical and/or data devices are not provided with the nurse station. Panel inserts are available in fabric, painted metal, tackable, acoustical, paper management, rail, glass, open and electrical/data accessible styles. Typicals include panel inserts for both sides of the steel frame. All electrical connections must be made by an electrical contractor. This JSN includes: 5 steel frames, 70"H (1778mm) x 24"W (610mm); 1 steel frame, 70"H (1778mm) x 48"W (1219mm); 2 steel frames, 38"W (965mm) x 48"W (1219mm); 4 steel frames, 38"H (965mm) x 24"W (610mm); 1 steel frame w/low access, 38"H (965mm) x 48"W (1219mm); 2 frame connectors, 3-way corner, 70"H (1778mm); 1 frame connector, 2-way corner, 38"H (965mm); 2 frame connectors, 135 degree, 2-way, 38"H (965mm); 4 finished end hardware kits; 1 cantilevered work surface, 96"W (2438mm); 2 cantilevered work surfaces, 72"W (1828mm); 1 cantilevered work surface, 48"W (1219mm); 1 cantilevered low access work surface, 135 degree, 48"W (1219mm); 2 pedestal box/box/files; 2 pass-thru chart shelves, 48"W (1219mm); 2 pass-thru chart shelves, 24"W (610mm); 2 laminate panel inserts, 20"H (508mm) x 48"W (1219mm); 10 panel inserts, painted metal, 16"H (406mm) x 48"W (1219mm); 2 panel inserts, tackable, 16"H (406mm) x 48"W (1219mm); 38 panel inserts, painted metal, 16"H (406mm) x 24"W (610mm); 6 panel inserts, tackable, 16"H (406mm) x 24"W (610mm); 4 panel

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
			<p>inserts, paper mgmt., 16"H (406mm) x 24"W (610mm); 4 panel inserts, electrical/data access, 16"H (406mm) x 24"W (610mm); 1 countertop w/light support assembly, 16"D (406mm) x 14'-0"L (4267mm); 6 form trays, 9"W (229mm); 6 form trays, 6"W (152mm) and 6 form trays, 4"W (102mm). [Multiple electrical connections may be needed to support the equipment likely to be placed in this work center.]</p>																
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
			EA	70	168	120	600 lb	120	1	15	60	NO	--						
				CM:				2:				DEPENDENT:							
				178	427	305	273 kg	--	--	--		YES	--						
E0421	6530	Nurse Station, Large, Free Standing																	
			<p>Nurse station typicals have non-powered steel frames with a pre-installed metal junction box for user defined electrical solutions. Data modules and low voltage cabling can be routed freely within the frame. Electrical and/or data devices are not provided with the nurse station typical. Panel inserts are available in fabric, painted metal, tackable, acoustical, paper management, rail, glass, open and electrical/data accessible styles. Typicals include panel inserts for both sides of the steel frame. All electrical connections must be made by an electrical contractor. This JSN includes: 3 steel frames, 70"H (1778mm) x 48"W (1219mm); 1 steel frame, 70"H (1778mm) x 24"W (610mm); 4 steel frames, 38"H (965mm) x 48"W (1219mm); 4 steel frames, 38"H (965mm) x 30"W (762mm); 18 steel frames, 38"H (965mm) x 24"W (610mm); 1 steel frame w/ low access, 38"H (965mm) x 48"W (1219mm); 2 frame connectors, 3-way corner, 70"H (1778mm); 4 frame connectors, 2-way corner, 38"H (965mm); 8 frame connectors, 135 degree, 2-way, 38"H (965mm); 8 finished end hardware kits; 2 cantilevered work surfaces, 72"W (1828mm); 4 cantilevered work surfaces, 30"W (762mm); 2 cantilevered work surfaces, 24"W (610mm); 2 cantilevered, angled work surfaces, 48"W (1219mm); 4 cantilevered, 135 degree work surfaces, 48"W (1219mm); 1 cantilevered, low access work surface, 48"W (1219mm); 4 equipment shelves, 48"W (1219mm); 2 lockable flipper units, 48"W (1219mm); 2 lockable flipper units, 24"W (610mm); 1 pass-thru chart shelf, 48"W (1219mm); 1 pass-thru chart shelf, 24"W (610mm); 2 laminate panel inserts, 20"H (508mm) x 48"W (1219mm); 4 equipment access tiles, 48"W (1219mm); 12 panel inserts, painted metal, 16"H (406mm) x 48"W (1219mm); 6 panel inserts, tackable, 16"H (406mm) x 48"W (1219mm); 2 panel inserts, paper mgmt., 16"H (406mm) x 48"W (1219mm); 16 panel inserts, painted metal, 16"H (406mm) x 30"W (762mm); 16 panel inserts, painted metal, 16"H (406mm) x 30"W (762mm); 56 panel inserts, painted metal, 16"H (406mm) x 24"W (610mm); 4 panel inserts, paper mgmt., 16"H (406mm) x 24"W (610mm); 4 panel inserts, electrical/data access, 16"H (406mm) x 24"W (610mm); 6 panel inserts, tackable, 16"H (406mm) x 24"W (610mm); 12 form trays, 9"W (229mm); 12 form trays, 6"W (152mm); 12 form trays, 4"W (102mm); 4 pencil drawers and 4 fully adjustable keyboard trays. [Multiple electrical connections will be needed to support the equipment likely to be placed in this work center.]</p>																
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
			EA	70	245	232	1,500 lb	120	1	15	60	NO	--						
				CM:				2:				DEPENDENT:							
				178	622	589	681 kg	--	--	--		YES	--						
E0503	6530	Module, Lab, Work Surface, O/H Cab, 24" W																	
			<p>THIS TYPICAL INCLUDES: 1 MODULE WITH 7-1/4" (184MM) UTILITY CHASE 1 SERVICE SHELF 2 ELECTRICAL ACCESS PANELS 2 MODULE CONNECTORS 1 LOCKABLE FLIPPER UNIT 1 SHELF, STORAGE/DISPLAY 1 LIGHT 1 WORK SURFACE [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]</p>																
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
			EA	80	24	36	125 lb	120	1	1	60	NO	--						
				CM:				2:				DEPENDENT:							
				203	61	91	57 kg	--	--	--		YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
E0506	6530	Module, Lab, Work Surface, O/H Cab, 30" W	F	F	F	F	--	--	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES: 1 MODULE WITH 7-1/4" (184MM) UTILITY CHASE 1 SERVICE SHELF 2 ELECTRICAL ACCESS PANELS 2 MODULE CONNECTORS 1 LOCKABLE FLIPPER UNIT 1 SHELF, STORAGE/DISPLAY 1 LIGHT 1 WORK SURFACE [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	80	203	36	160 lb 73 kg	1: 120	1	1	60	NO	YES	--					
E0509	6530	Module, Lab, Work Surface, O/H Cab, 48" W	F	F	F	F	--	--	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES: 1 MODULE WITH 7-1/4" (184MM) UTILITY CHASE 1 SERVICE SHELF 2 ELECTRICAL ACCESS PANELS 2 MODULE CONNECTORS 1 LOCKABLE FLIPPER UNIT 1 SHELF, STORAGE/DISPLAY 1 LIGHT 1 WORK SURFACE [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	80	203	36	250 lb 114 kg	1: 120	1	1	60	NO	YES	--					
E0512	6530	Module, Lab, Work Surface, O/H Cab, 60" W	F	F	F	F	--	--	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES: 2 MODULES WITH 7-1/4" (184mm) UTILITY CHASE 2 SERVICE SHELVES 4 ELECTRICAL ACCESS PANELS 4 MODULE CONNECTORS 2 LOCKABLE FLIPPER UNITS 2 SHELVES, STORAGE/DISPLAY 2 LIGHTS 1 WORK SURFACE [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	80	203	36	315 lb 143 kg	1: 120	1	1	60	NO	YES	--					
E0515	6530	Module, Lab, Work Surface, O/H Cab, 72" W	F	F	F	F	--	--	A	--	--	--	--	--	--	--	--	--
		THIS TYPICAL INCLUDES: 2 MODULES WITH 7-1/4" (184mm) UTILITY CHASES 2 SERVICE SHELVES 4 ELECTRICAL ACCESS PANELS 4 MODULE CONNECTORS 2 LOCKABLE FLIPPER UNITS 2 SHELVES, STORAGE/DISPLAY 2 LIGHTS 1 WORK SURFACE [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission																

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I	UTILITIES
				R A F A H	1 2 3 4 5 6

cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's lights.]

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:
EA	80	203	36	375 lb	120	1	1	60	
			91	171 kg	2:	--	--	NO	--
								DEPENDENT:	
								YES	--

E0518	6530	Module, Lab, Work Surface, O/H Cab, Drwrs, 24" W	F F F F --	-- A -- -- -- --
-------	------	--	------------	------------------

THIS TYPICAL INCLUDES:

- 1 MODULE WITH 7-1/4" (184mm) UTILITY CHASE
- 1 SERVICE SHELF
- 2 ELECTRICAL ACCESS PANELS
- 2 MODULE CONNECTORS
- 1 LOCKABLE FLIPPER UNIT
- 1 SHELF, STORAGE/DISPLAY
- 1 LIGHT
- 1 WORK SURFACE
- 2 STORAGE FRAMES
- 1 STORAGE FRAME RAIL
- 1 DRAWER, 3"H (76mm)
- 3 DRAWERS, 6"H (152mm)
- 1 DRAWER, 9"H (229mm)

DRAWER ORGANIZER BINS [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:
EA	80	203	36	150 lb	120	1	1	60	
			91	69 kg	2:	--	--	NO	--
								DEPENDENT:	
								YES	--

E0521	6530	Module, Lab, Work Surface, O/H Cab, Drwrs, 30" W	F F F F --	-- A -- -- -- --
-------	------	--	------------	------------------

THIS TYPICAL INCLUDES:

- 1 MODULE WITH 7-1/4" (184mm) UTILITY CHASE
- 1 SERVICE SHELF
- 2 ELECTRICAL ACCESS PANELS
- 2 MODULE CONNECTORS
- 1 LOCKABLE FLIPPER UNIT
- 1 SHELF, STORAGE/DISPLAY
- 1 LIGHT
- 1 WORK SURFACE
- 2 STORAGE FRAMES
- 1 STORAGE FRAME RAIL
- 1 DRAWER, 3"H (76mm)
- 3 DRAWERS, 6"H (152mm)
- 1 DRAWER, 9"H (229mm)

DRAWER ORGANIZER BINS [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:
EA	80	203	36	190 lb	120	1	1	60	
			91	87 kg	2:	--	--	NO	--
								DEPENDENT:	
								YES	--

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES																																																
				R	A	F	A	H							1	2	3	4	5	6																																						
E0524	6530	Module, Lab, Work Surface, O/H Cab, Drwrs, 48" W	F F F F --	--	A	--	--	--	--																																																	
<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 MODULE WITH 7-1/4" (184mm) UTILITY CHASE 1 SERVICE SHELF 2 ELECTRICAL ACCESS PANELS 2 MODULE CONNECTORS 1 LOCKABLE FLIPPER UNIT 1 SHELF, STORAGE/DISPLAY 1 LIGHT 1 WORK SURFACE 2 STORAGE FRAMES 1 STORAGE FRAME RAIL 1 DRAWER, 3"H (76mm) 3 DRAWERS, 6"H (152mm) 1 DRAWER, 9"H (229mm) <p>DRAWER ORGANIZER BINS [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]</p>																																																										
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>80</td> <td>203</td> <td>48</td> <td>36</td> <td>251 lb</td> <td>120</td> <td>1</td> <td>1</td> <td>60</td> <td>NO</td> <td>YES</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>122</td> <td>91</td> <td>114 kg</td> <td>--</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>																				UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	80	203	48	36	251 lb	120	1	1	60	NO	YES	--				122	91	114 kg	--	--	--				
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																																														
EA	80	203	48	36	251 lb	120	1	1	60	NO	YES	--																																														
			122	91	114 kg	--	--	--																																																		
E0527	6530	Module, Lab, Work Surface, O/H Cab, Drwrs, 60" W	F F F F --	--	A	--	--	--	--																																																	
<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 MODULES WITH 7-1/4" (184mm) UTILITY CHASE 2 SERVICE SHELVES 4 ELECTRICAL ACCESS PANELS 4 MODULE CONNECTORS 2 LOCKABLE FLIPPER UNITS 2 SHELVES, STORAGE/DISPLAY 2 LIGHTS 1 WORK SURFACE 2 STORAGE FRAMES 1 STORAGE FRAME RAIL 2 DRAWERS, 3"H (76mm) 3 DRAWERS, 6"H (152mm) 1 DRAWER, 9"H (229mm) [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's lights. Unit also includes Drawer Organizer Bins.] 																																																										
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>80</td> <td>203</td> <td>60</td> <td>36</td> <td>325 lb</td> <td>120</td> <td>1</td> <td>1</td> <td>60</td> <td>NO</td> <td>YES</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>152</td> <td>91</td> <td>148 kg</td> <td>--</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>																				UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	80	203	60	36	325 lb	120	1	1	60	NO	YES	--				152	91	148 kg	--	--	--				
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																																														
EA	80	203	60	36	325 lb	120	1	1	60	NO	YES	--																																														
			152	91	148 kg	--	--	--																																																		
E0530	6530	Module, Lab, Work Surface, O/H Cab, Drwrs, 72" W	F F F F --	--	A	--	--	--	--																																																	
<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 MODULES WITH 7-1/4" (184mm) UTILITY CHASES 2 SERVICE SHELVES 4 ELECTRICAL ACCESS PANELS 4 MODULE CONNECTORS 2 LOCKABLE FLIPPER UNITS 2 SHELVES, STORAGE/DISPLAY 2 LIGHTS 1 WORK SURFACE 2 STORAGE FRAMES 1 STORAGE FRAME RAIL 2 DRAWERS, 3"H (76mm) 3 DRAWERS, 6"H (152mm) 1 DRAWER, 9"H (229mm) 																																																										

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I	UTILITIES						
				R A F A H	1 2 3 4 5 6						
DRAWER ORGANIZER BINS [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's lights.]											
	UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:
	EA	80	72	36	400 lb	120	1	1	60	NO	--
		CM:				2:				DEPENDENT:	
		203	183	91	182 kg	--	--	--		YES	--
E0533	6530	Module, Lab, Work Surf, O/H Cab, Hvy Storage, 48"W			F F F F --	-- A -- -- -- --					
THIS TYPICAL INCLUDES:											
1 MODULE WITH 7-1/4" (184mm) UTILITY CHASE											
1 SERVICE SHELF											
2 ELECTRICAL ACCESS PANELS											
2 MODULE CONNECTORS											
1 LOCKABLE FLIPPER UNIT											
1 SHELF, STORAGE/DISPLAY											
1 LIGHT											
1 WORK SURFACE											
4 STORAGE FRAMES											
1 STORAGE FRAME RAIL											
2 DRAWERS, 3"H (76mm)											
6 DRAWERS, 6"H (152mm)											
2 DRAWERS, 9"H (229mm)											
DRAWER ORGANIZER BINS [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]											
	UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:
	EA	80	48	36	302 lb	120	1	1	60	NO	--
		CM:				2:				DEPENDENT:	
		203	122	91	137 kg	--	--	--		YES	--
E0536	6530	Module, Lab, Work Surf, O/H Cab, Hvy Storage, 72"W			F F F F --	-- A -- -- -- --					
THIS TYPICAL INCLUDES:											
2 MODULES WITH 7-1/4" (184mm) UTILITY CHASES											
2 SERVICE SHELVES											
4 ELECTRICAL ACCESS PANELS											
4 MODULE CONNECTORS											
2 LOCKABLE FLIPPER UNITS											
2 SHELVES, STORAGE/DISPLAY											
2 LIGHTS											
1 WORK SURFACE											
6 STORAGE FRAMES											
1 STORAGE FRAME RAIL											
3 DRAWERS, 3"H (76mm)											
9 DRAWERS, 6"H (152mm)											
3 DRAWERS, 9"H (229mm)											
DRAWER ORGANIZER BINS [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's lights.]											
	UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:
	EA	80	72	36	400 lb	120	1	1	60	NO	--
		CM:				2:				DEPENDENT:	
		203	183	91	182 kg	--	--	--		YES	--

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES						
				R	A	F	A	H		1	2	3	4	5	6	
E0539	6530	Module, Lab, Work Surf, O/H Cab, Cabinet, 30" W	F F F F --	--	A	--	--	--	--							
<p>THIS TYPICAL INCLUDES:</p> <p>1 MODULE WITH 7-1/4" (184mm) UTILITY CHASE</p> <p>1 SERVICE SHELF</p> <p>2 ELECTRICAL ACCESS PANELS</p> <p>2 MODULE CONNECTORS</p> <p>1 LOCKABLE FLIPPER UNIT</p> <p>1 SHELF, STORAGE/DISPLAY</p> <p>1 LIGHT</p> <p>1 WORK SURFACE</p> <p>1 STORAGE CABINET</p> <p>1 DRAWER, 6"H (152mm) [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]</p>																
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:					
EA		CM:	80	30	36	165 lb	1: 120	1	1	60	NO	--				
			203	76	91	75 kg	2: --	--	--	DEPENDENT:	YES	--				
E0542	6530	Module, Lab, Work Surf, O/H Cab, Cabinet, 48" W	F F F F --	--	A	--	--	--	--							
<p>THIS TYPICAL INCLUDES:</p> <p>1 MODULE WITH 7-1/4" (184mm) UTILITY CHASE</p> <p>1 SERVICE SHELF</p> <p>2 ELECTRICAL ACCESS PANELS</p> <p>2 MODULE CONNECTORS</p> <p>1 LOCKABLE FLIPPER UNIT</p> <p>1 SHELF, STORAGE/DISPLAY</p> <p>1 LIGHT</p> <p>1 WORK SURFACE</p> <p>1 STORAGE CABINET</p> <p>1 DRAWER, 3"H (76mm)</p> <p>1 DRAWER, 6"H (152mm) [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]</p>																
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:					
EA		CM:	80	48	36	260 lb	1: 120	1	1	60	NO	--				
			203	122	91	118 kg	2: --	--	--	DEPENDENT:	YES	--				
E0545	6530	Module, Lab, Work Surf, O/H Cab, Cabinets, 48" W	F F F F --	--	A	--	--	--	--							
<p>THIS TYPICAL INCLUDES:</p> <p>1 MODULE WITH 7-1/4" (184mm) UTILITY CHASE</p> <p>1 SERVICE SHELF</p> <p>2 ELECTRICAL ACCESS PANELS</p> <p>2 MODULE CONNECTORS</p> <p>1 LOCKABLE FLIPPER UNIT</p> <p>1 SHELF, STORAGE/DISPLAY</p> <p>1 LIGHT</p> <p>1 WORK SURFACE</p> <p>2 STORAGE CABINETS</p> <p>2 DRAWERS, 6"H (152mm) [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]</p>																
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:					
EA		CM:	80	48	36	271 lb	1: 120	1	1	60	NO	--				
			203	122	91	123 kg	2: --	--	--	DEPENDENT:	YES	--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
E0551	6530	Module, Lab, End Panel, 60" W	F	F	F	F	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 MODULE END SUPPORT FRAME 2 SUPPORT RAILS 2 MODULE CONNECTORS																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	80	60	4	75 lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	203	152	10	34 kg	2:	--	--	--	DEPENDENT:	NO						
E0554	6530	Cabinet, w/Sink, O/H Cab, Free Standing, 48"Wx24"D	F	F	F	F	--	D	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 Freestanding, sink adaptable cabinet w/integral backsplash 1 Lockable flipper unit 1 Sink and faucet 2 Vertical Hanging Strips																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	84	48	24	176 lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	213	122	61	80 kg	2:	--	--	--	DEPENDENT:	NO						
E0557	6530	Cabinet, w/Sink, O/H Cab, Free Standing, 60"Wx24"D	F	F	F	F	--	D	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 Freestanding, sink adaptable cabinet w/integral backsplash 2 Lockable flipper units 1 Sink and faucet 3 Vertical Hanging Strips																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	84	60	24	250 lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	213	152	61	114 kg	2:	--	--	--	DEPENDENT:	NO						
E0563	6530	Module, Lab, Dbl Side, w/Sink, Lockers, 192"Wx72"D	F	F	F	F	--	D	A	--	--	--	--	--	--	--	--	--
This JSN includes: 3 modules, 80"H (2032mm) x 48"W (1219mm) with 7-1/4"W utility chases; 2 module end support frames; 1 vertical utility chase cover; 8 module-to-module connectors; 1 cantilevered work surface, 60"W (1524mm); 5 cantilevered work surfaces, 48"W (1219mm); 1 cantilevered, sink adaptable work surface, 48"W (1219mm); 1 sink and faucet; 2 lockable flipper units, 48"W (1219mm); 5 lights, 48"W (1219mm); 2 glass front cabinets, 48"W (1219mm); 1 shelf, storage/display, 48"W (1219mm); 1 shelf, storage/display, 60"W (1524mm); 2 storage cabinets; 4 storage frames; 2 storage frame lids; 1 dispensing rail, 48" (1219mm); 2 supply lockers; 2 support rails, 60"W (1524mm); 1 mobile cart w/top surface; 1 transporter for supply lockers; 17 drawers, 3"H (76mm); 7 drawers, 6"H (152mm); 5 drawers, 9"H (229mm); 9 tray/shelves; 10 bins, 4-9/16"W (114mm) x 2-3/16"H (57mm); 3 service shelves, 48"W (1219mm); 1 tack board, 48" (1219mm); 1 paper mgmt. rail, 60"W (1524mm); 2 paper trays; 1 diagonal tray; 1 fully adjustable keyboard tray; 1 mobile pedestal, box/box/file and drawer organizer bins. [The utility chase will accommodate water, drain and gas piping as well as electrical and data transmission cabling. The final utility configuration depends on the exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	80	192	72	1,200 lb	1:	120	1	3	HZ SWITCH:	NO						
		CM:	203	488	183	545 kg	2:	--	--	--	DEPENDENT:	YES						
E0566	6530	Module, Lab, Dbl, w/End, Lockr, Shelf, 192"Wx60"D	F	F	F	F	--	D	A	--	--	--	--	--	--	--	--	--
This JSN includes: 1 clinical panel w/ceiling entry electrical/data channel, 80"H (2032mm) x 48"W (1219mm); 1 clinical panel, 80"H (2032mm) x 48"W (1219mm); 1 clinical panel, 48"H (1219mm) x 48"W (1219mm); 1 end support panel, 80"H (2032mm) x 60"W (1524mm); 1 clinical panel, 48"H (1219mm) x 24"W (610mm); 1 clinical panel, w/floor entry electrical/data channel, 48"H (1219mm) x 30"W (762mm); 1 panel connector, 3-way corner, 48"H (1219mm); 6 panel-to-panel connectors; 2 panel end caps, 48"H (1219mm); 6 cantilevered work surfaces, 48"W (1219mm); 1 cantilevered work surface, 30"W (762mm); 2 lockable flipper units, 48"W (1219mm); 1 glass front cabinet, 48"W (1219mm); 3 lights, 48"W (1219mm); 1 dispensing rail, 48"W (1219mm); 1 storage cabinet; 6 storage frames; 2 storage frame lids; 1 transaction shelf, 48"W (1219mm); 1 shelf, storage/display, 48"W (1219mm); 2 supply lockers; 1 transporter for supply lockers; 1 mobile cart w/top surface; 2 electrical/data channels, 8'-0" (2438mm); 3 electrical/data channels, 48"W (1219mm); 6 channel end caps; 20 drawers, 3"H (76mm); 11 Drawers, 6"H (152mm); 5 drawers, 9"H (229mm); 8 tray/shelves; 1 wire shelf; 1 mobile pedestal, box/box/file; 1 adjustable keyboard tray; 10 bins, 4-9/16"W (114mm) x 2-3/16"H (57mm); 2 diagonal trays; 3 paper trays and drawer organizer bins. [The utility chase for this JSN will accommodate electrical and data transmission cabling.; it is not designed for plumbing or gas lines. The final utility configuration depends on the																		

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES														
				A	N	A	V	I	1	2	3	4	5	6				
				R	A	F	A	H										

exact equipment to be placed on the module. The database electrical requirement is only for the module's light.]

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS 2:	HZ:	HZ SWITCH:	BTUs / HR:
EA	80	203	60	1,000 lb 454 kg	120	1	2	60	NO	--
								DEPENDENT:	YES	--

E0570	6530	Workstation, Chemistry Lab, Minimal	F	F	F	F	--	--	A	--	--	--	--
-------	------	--	---	---	---	---	----	----	---	----	----	----	----

THIS TYPICAL INCLUDES:

- 4 Vertical Hanger Strips
- 2 Light 48W (1219mm)
- 1 Cantilevered Work Surface 30D (762mm) x 48W (1219mm)
- 1 Cantilevered Corner Work Surface 30D (762mm) x 48W (1219mm) x 48W (1219)
- 1 DR, 3H (76mm)
- 1 DR, 9H (229mm)
- 1 Storage Frame
- 1 Mobile Cart w/Top Surface
- 2 Lockable Flipper Unit, 48W (1219mm)
- 1 Adjustable Keyboard Tray
- 2 Shelf, Storage/Display 48W (1219)
- 2 Extra Deep Shelf, 48W (1219mm)
- Drawer Organizer Bins
- * Hardware required to complete installation.

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS 2:	HZ:	HZ SWITCH:	BTUs / HR:
EA	84	213	48	454 lb 207 kg	--	--	--	--	NO	--
								DEPENDENT:	NO	--

E0571	6530	Workstation, Urinalysis Lab, Minimal	F	F	F	F	--	A	A	--	--	--	--
-------	------	---	---	---	---	---	----	---	---	----	----	----	----

THIS TYPICAL INCLUDES:

- 7 Vertical Hanger Strips
- 1 Equipment Rail, System-Mt, 48W (1219)
- 3 Light 48W (1219mm)
- 1 Light 24W (610)
- 1 Cantilevered Work Surface 30D (762mm) x 48W (1219mm)
- 1 Cantilevered Work Surface 30D (762mm) x 72W (1829mm)
- 1 Cantilevered Corner Work Surface 30D (762mm) x 48W (1219mm) x 48W (1219)
- 3 DR, 6H (152mm)
- 1 Lockable Flipper Unit, 24W (610mm)
- 3 Lockable Flipper Unit, 48W (1219mm)
- 3 Mobile Drawer Caddie with Drawers
- 1 Adjustable Keyboard Tray
- 3 Shelf, Storage/Display 48W (1219mm)
- 1 Shelf, Storage/Display 24W (610mm)
- 1 Cantilevered ADA Sink Cabinet, w/Backsplash, 30D (762mm) x 24W (610mm)
- 1 Swing-Away Eyewash
- 1 SS ADA Sink 19D (483mm) x 21D (533mm)
- 1 Gooseneck Mixing Faucet ASSY. With Wristbands
- 1 Strainer and Tailpiece
- Drawer Organizer Bins
- * Hardware required to complete installation.

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS 2:	HZ:	HZ SWITCH:	BTUs / HR:
EA	84	213	48	907 lb 412 kg	--	--	--	--	NO	--
								DEPENDENT:	NO	--

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES										
				A	N	A	V	I						
				R	A	F	A	H	1	2	3	4	5	6

E0572	6530	Workstation, Hematology Lab, Minimal	F F F F --	A	A	--	--	--	--	--	--	--	--	--
-------	------	--------------------------------------	------------	---	---	----	----	----	----	----	----	----	----	----

THIS TYPICAL INCLUDES:

- 6 Vertical Hanger Strips
 - 1 Equipment Rail, System-Mt, 48W (1219)
 - 2 Clinical Panel, 80H (2032mm) x 30W (762mm)
 - 1 Module, 80 H (2032mm) x 24W (610mm), w/ 7-1/4inch utility chase, w/ service shelf
 - 1 Module, 80 H (2032mm) x 48W (1219mm), w/ 7-1/4inch utility chase, w/ service shelf
 - 1 Vertical Chase Cover
 - 2 Service Shelf 48W (1219mm)
 - 2 Light 24W (610)
 - 1 Light 30W (762mm)
 - 2 Light 48W (1219mm)
 - 1 Cantilevered Work Surface 30D (762mm) x 60W (1524mm)
 - 2 Cantilevered Work Surface 30D (762mm) x 72W (1829mm)
 - 1 Height Adjustable Table, 30D (762mm) x 72W (1829mm)
 - 3 DR, 3H (76mm)
 - 5 DR, 6H (152mm)
 - 1 DR, 9H (229mm)
 - 1 Storage Frame
 - 1 Mobile Cart w/Top Surface
 - 2 Lockable Flipper Unit, 24W (610mm)
 - 2 Lockable Flipper Unit, 30W (762mm)
 - 2 Lockable Flipper Unit, 48W (1219mm)
 - 4 Mobile Drawer Caddie with Drawers
 - 1 Adjustable Keyboard Tray
 - 1 Shelf, Storage/Display 24W (610mm)
 - 2 Shelf, Storage/Display 30W (762mm)
 - 1 Shelf, Storage/Display 48W (1219mm)
 - 4 Extra Deep Shelf, 24W (610mm)
 - 2 Extra Deep Shelf, 48W (1219mm)
 - 1 Sink Base Cabinet, Dbl. Door, Backsplash, 30D (762mm) x 48W (1219mm)
 - 1 Swing-Away Eyewash
 - 1 SS ADA Sink 19D (483mm) x 33D (838mm)
 - 1 Gooseneck Mixing Faucet ASSY. With Wristbands
 - 1 Strainer and Tailpiece
 - 1 Coat Hook
 - Drawer Organizer Bins
- * Hardware required to complete installation.

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
OF ISSUE:	IN:	84	258	48	1,948 lb	1:	120	1	3
EA	CM:	213	655	122	885 kg	2:	--	--	--
								HZ SWITCH: NO	
								DEPENDENT: YES	--

E0573	6530	Workstation, Shipping/Receiving Lab, Minimal	F F F F --	A	A	--	--	--	--
-------	------	--	------------	---	---	----	----	----	----

THIS TYPICAL INCLUDES:

- 1 Equipment Rail, System-Mt, 48W (1219)
- 2 Clinical Panel, 80H (2032mm) x 30W (762mm)
- 1 Module, 80 H (2032mm) x 24W (610mm), w/ 7-1/4inch utility chase, w/ service shelf
- 2 Module, 80 H (2032mm) x 48W (1219mm), w/ 7-1/4inch utility chase, w/ service shelf
- 1 Vertical Chase Cover
- 2 Service Shelf 48W (1219mm)
- 2 Light 48W (1219mm)
- 2 Cantilevered Work Surface 30D (762mm) x 48W (1219mm)
- 2 Lockable Flipper Unit, 48W (1219mm)
- 2 Adjustable Keyboard Tray
- 1 Sink Base Cabinet, Dbl. Door, Backsplash, 30D (762mm) x 48W (1219mm)
- 1 Swing-Away Eyewash
- 1 SS ADA Sink 19D (483mm) x 33D (838mm)
- 1 Gooseneck Mixing Faucet ASSY. With Wristbands

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

1 Strainer and Tailpiece
 1 Coat Hook
 Drawer Organizer Bins
 * Hardware required to complete installation.

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	84	125	48	930 lb	1:	--	--	--	--	NO
	213	318	122	422 kg	2:	--	--	--	NO	--

E0574	6530	Workstation. Microbiology Lab, Minimal	F	F	F	F	--	A	A	--	--	--	--
-------	------	--	---	---	---	---	----	---	---	----	----	----	----

THIS TYPICAL INCLUDES:

9 Vertical Hanger Strips
 1 Equipment Rail, System-Mt, 24W (610)
 1 Light 24W (610)
 2 Light 30W (762mm)
 2 Light 48W (1219mm)
 1 Cantilevered Work Surface 30D (762mm) x 48W (1219mm)
 1 Cantilevered Work Surface 30D (762mm) x 60W (1524mm)
 1 Height Adjustable Table, 30D (762mm) x 72W (1829mm)
 1 DR, 6H (152mm)
 1 Lockable Flipper Unit, 24W (610mm)
 2 Lockable Flipper Unit, 30W (762mm)
 2 Lockable Flipper Unit, 48W (1219mm)
 2 Mobile Drawer Caddie with Drawers
 1 Adjustable Keyboard Tray
 1 Shelf, Storage/Display 24W (610mm)
 2 Shelf, Storage/Display 30W (762mm)
 2 Shelf, Storage/Display 48W (1219mm)
 2 Extra Deep Shelf, 24W (610mm)
 2 Extra Deep Shelf, 48W (1219mm)
 1 Cantilevered Sink Cabinet, 30D (762mm) x 24W (610mm)
 1 SS ADA Sink 19D (483mm) x 21D (533mm)
 1 Swing-Away Eyewash
 1 Gooseneck Mixing Faucet ASSY. With Wristbands
 1 Strainer and Tailpiece
 Drawer Organizer Bins
 * Hardware required to complete installation.

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	84	185	30	928 lb	1:	--	--	--	--	NO
	213	470	76	422 kg	2:	--	--	--	NO	--

E0579	6530	Workstation, Chemistry Lab, Small	F	F	F	F	--	D	A	--	--	--	--
-------	------	-----------------------------------	---	---	---	---	----	---	---	----	----	----	----

THIS TYPICAL INCLUDES:

1 Equip Rail. Wall-MT 48W (1219mm)
 1 Clinical Panel, Open 80H (2032mm) x 24W (610mm)
 3 Clinical Panel, Open 80H (2032mm) x 30W (762mm)
 3 Clinical Panel, Open 80H (2032mm) x 48W (1219mm)
 2 Clinical Panel with Ceiling Entry Elec./Data Channel, 80H (2032mm) x 48W (1219mm)
 1 Clinical Panel with Ceiling Entry Elec./Data Channel, 80H (2032mm) x 30W (762mm)
 2 Clinical Panel, 48H (1219mm) x 30W (762)
 2 Clinical Panel, 80H (2032mm) x 48W (1219mm)
 1 Light, 24W (610mm)
 2 Light, 30W (762mm)
 5 Light 48W (1219mm)
 1 Electrical/Data Channel 48W (1219mm)
 1 Electrical/Data Channel 60W (1524mm)
 1 Electrical/Data Channel 72W (1829mm)
 1 Electrical/Data Channel 96W (2438mm)

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES							
			A	N	A	V	I	1	2	3	4	5	6
		2 Electrical/ Data Channel, Corner 4 Cantilevered Work Surf, 30D (762mm) x 48W (1219mm) 1 Cantilevered Work Surf, 30D (762mm) x60W (1524mm) 1 Cantilevered Work Surf, 30 D (762mm) x 72W (1829mm) 1 DR., 3H (76mm) 3 DR, 6H (152mm) 1 Storage Frame 1 Mobile Cart w/ Top Surface 1 Lockable Flipper Unit, 24W (610mm) 2 Lockable Flipper Unit, 30W (762mm) 4 Lockable Flipper Unit, 48W (1219mm) 1 Mobile Drawer Caddie with Drawers 2 Adjustable Keyboard Tray 1 Shelf, Storage/Display 24 W (610mm) 2 Shelf, Storage/Display 30W (762mm) 4 Shelf, Storage/Display 48W (1219mm) 1 Shelf Unit with Door 48W (1219mm) 6 Extra Deep Shelf, 48W (1219mm) 4 Extra Deep Shelf, 30W (762mm) 6 Paper Tray 1 Sink Base Cab, w. Door, Backslash, 30D (762mm) x 24W (610mm) 1 Swing-Away Eyewash 1 SS Double Sink 19D (483mm) x 33D (838mm) 1 Gooseneck Mixing Faucet Assay, with Wristbands 1 Strainer and Tailpiece 1 Coat Hook Drawer organizer Bins * Connecting hardware required to complete installation. [Workstation requires interface between the modular furniture and building for both electrical and plumbing. There are three electrical ceiling entries and one sink.]											
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:
			EA	84	213	30	2,982 lb 1,354 kg	1: --	--	--	NO	--	
								2: --	--	--	NO	--	

E0580	6530	Workstation, Urinalysis Lab, Small	F	F	F	F	--	D	A	--	--	--	--
		THIS TYPICAL INCLUDES: 6 Vertical Hanging Strips 1 Equip Rail, Wall-Mt, 24W (610mm) 2 Light, 30W (762mm) 1 Light 48W (1219mm) 2 Tool Rail, 30W (762) 1 Tackboard, 30W (762mm) 1 Cantilevered Work Surf, 30D (762) x 48W (1219mm) 1 Cantilevered Work Surf, 30D (762mm) x 60W (1524mm) 1 DR., 3H (76mm) 3 DR., 6H (152mm) 2 Lockable Flipper Unit, 30W (762mm) 1 Lockable Flipper Unit, 48W (1219mm) 3 Mobile Drawer Caddie with Drawer 1 Adjustable Keyboard Tray 2 Shelf, Storage/Display 30W (762mm) 1 Shelf, Storage/Display 48W (1219mm) 1 Pedestal, Box, File 2 Height Adjustable Table, 24D (610mm)x 48W (1219mm) 2 Paper Tray 1 Diagonal Tray 8 Shelf Dividers 1 Cantilevered Sink Cab, 30D (762mm) x 24W (610mm)											

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
1 SS Sink 19D (483mm) x 21D (533mm) 1 Gooseneck Mixing Faucet Assay. With Wristbands 1 Strainer and Tailpiece Drawer Organizer * Hardware required to complete installation. [Workstation utilizes the architectural wall for electrical, but requires plumbing interface between the modular furniture and building.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
EA		CM:	84	180	30	908 lb	1:	--	--	--		DEPENDENT:	NO	--					
			213	457	76	413 kg	2:	--	--	--				--					

E0581	6530	Workstation, Hematology Lab, Small	F	F	F	F	--	D	A	--	--	--	--	--					
THIS TYPICAL INCLUDES 2 Equip Rail, Wall-Mt, 48W (1219mm) 4 Clinical Panel, Open 80H (2032mm) x 30W (762mm) 3 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80H (2032mm) x 48W (1219mm) 4 Clinical Panel, 48H (1219mm) x 30W (762mm) 1 Clinical Panel, 80W (2032mm) x 48W (1219mm) 8 Light 48W (1219mm) 4 Electrical/Data Channel 96W (2438mm) 8 Cantilevered Work Surf, 30D (762mm) x 48 (1219mm) 2 Height Adjustable Table, 30D (762mm x 48W (1219mm) 4 DR., 3H (76mm) 5 DR., 6H (152mm) 7 Lockable flipper Unit, 48W (1219mm) 3 Mobile Drawer Caddie with Drawers 2 Storage Cabinet w/Door 2 Adjustable Keyboard Tray 7 Shelf, Storage/Display 48W (1219mm) 1 3 Shelf Unit with Door, 48W (1219mm) 8 Extra Deep Shelf, 48W (1219mm) 4 Paper Tray 1 Sink Base Cab, w/Door, w/Backsplash, 30D (762mm) x24W (610mm) 1 Sink Base Cab, w/Door, w/Backsplash, 30D (762mm) x48W (1219mm) 1 Swing-Away Eyewash 1 SS Double Sink 19D (483mm) x 33D (838mm) 1 SS Double Sink 19D (483mm) x21D (533mm) 2 Gooseneck Mixing Faucet ASSY. With Wristbands 2 Strainer and Tailpiece 1 Coat Hook Drawer Organizer Bins * Connecting hardware required to complete installation. [Workstation requires interface between the modular furniture and building for both electrical and plumbing.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
EA		CM:	84	312	96	3,387 lb	1:	--	--	--		DEPENDENT:	NO	--					
			213	792	244	1,538 kg	2:	--	--	--				--					

E0582	6530	Workstation, Shipping/Receiving Lab, Small	F	F	F	F	--	D	A	--	--	--	--	--				
THIS TYPICAL INCLUDES: 1 Equip Rail, Wall-Mt, 48W (1219mm) 1 Clinical Panel, Open 80H (2032mm) x 24W (610mm) 1 Clinical Panel, 80H (2032mm) x 30W (762mm) 5 Clinical Panel, 80W (2032mm) x 48W (1219mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80H (2032mm) x 24W (610mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80H (2032mm) x 30W (762mm) 3 Clinical Panel, 48H (1219mm) x 30W (762mm) 2 Light, 24W (610mm) 5 Light 48W (1219mm)																		

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES										
				A	N	A	V	I						
				R	A	F	A	H	1	2	3	4	5	6

<p>4 Electric/Data Channel 48W (1219mm) 1 Electrical/Data Channel 72W (1829mm) 1 Electrical/Data Channel, Corner 3 Cantilevered Work Surf, 30D (762mm) x 48W (1219mm) 1 Cantilevered Work Surf, 30D (762mm) x 72W (1829mm) 2 DR., 3H (76mm) 2 DR., 6H (152mm) 1 Storage Cabinet w/Door 2 Lockable Flipper Unit, 24W (610mm) 3 Lockable Flipper Unit, 48W (1219mm) 1 Mobile Drawer Caddie with Drawers 2 Adjustable Keyboard Tray 2 Shelf, Storage/Display 24W (610mm) 2 3- Shelf, Storage/Display 48W (1219mm) 3 Shelf Unit with Door, 48W (1219mm) 2 Extra Deep Shelf, 48W (1219mm) 6 Paper Tray 1 Cantilevered ADA Sink Cab, 30D (762mm) x 24W (610mm) 1 Swing-Away Eyewash 1 SSADA Sink 19D (483mm) x 21D (533mm) 1 Gooseneck Mixing Faucet Assay. With Wristbands 1 Strainer and Tailpiece 1 Coat Hook Drawer Organizer Bins</p> <p>* Connecting hardware required to complete installation. [Workstation requires interface between the modular furniture and building for both electrical and plumbing. There are two electrical ceiling entries and two sinks.]</p>													
---	--	--	--	--	--	--	--	--	--	--	--	--	--

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
OF ISSUE:	IN: 84	240	30	2,463 lb	1: --	--	--	NO	
EA	CM: 213	610	76	1,119 kg	2: --	--	--	NO	--

E0583	6530	Workstation, Microbiology Lab, Small	F F F F --	D A -- -- -- --
-------	------	--------------------------------------	------------	-----------------

<p>THIS TYPICAL INCLUDES:</p> <p>1 Equip Rail, Wall-Mt, 48W (1219mm) 1 Clinical Panel, Open 80H (2032mm) x 24W (610mm) 3 Clinical Panel, 80H (2032mm) x 30W (762mm) 3 Clinical Panel, 80W (2032mm) x 48W (1219mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80H (2032mm) x 48W (1219mm) 3 Clinical Panel, 48H (1219mm) x 30W (762mm) 1 Clinical Panel, 48H (1219mm) x 48W (1219mm) 1 Light, 24W (610mm) 5 Light 48W (1219mm) 2 Electric/Data Channel 48W (1219mm) 1 Electrical/Data Channel 72W (1829mm) 1 Electrical/Data Channel 96W (2438mm) 2 Electrical/Data Channel, Corner 6 Cantilevered Work Surf, 30D (762mm) x 48W (1219mm) 1 Cantilevered Work Surf, 30D (762mm) x 72W (1829mm) 2 Height Adjustable Table, 30D (762mm) x48W (1219mm) 1 Height Adjustable Table, 30D (762mm) x60W (1219mm) 1 Transaction Countertop 48W (1219mm) 8 DR, 3H (76mm) 10 DR, 6H (152mm) 2 Storage Frame 2 Storage Cabinet w/Door 2 Mobile Cart w/Top Surface 1 Lockable Flipper Unit, 24W (610mm)</p>													
---	--	--	--	--	--	--	--	--	--	--	--	--	--

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
		4 Lockable Flipper Unit, 48W (1219mm) 4 Mobile Drawer Caddie with Drawers 1 Adjustable Keyboard Tray 1 Shelf, Storage/Display 24W (610mm) 4 Shelf, Storage/Display 48W (1219mm) 1 Shelf Unit with Door, 48W (1219mm) 6 Extra Deep Shelf, 48W (1219mm) 6 Paper Tray 1 Sink Base Cab, w/Door, Backsplash, 30D (762mm) x 48W (1219mm) 1 Swing-Away Eyewash 1 SS Sink 19D (483mm) x 33D (838mm) 1 Gooseneck Mixing Faucet Assay. with Wristbands 1 Strainer and Tailpiece 1 Coat Hook Drawer Organizer Bins * Connecting hardware required to complete installation. [Workstation requires interface between the modular furniture and building for both electrical and plumbing.]																	
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			EA	84	213	96	244	2,991 lb 1,358 kg	1: --	--	--	--	NO	NO	--				

E0584	6530	Workstation Blood Bank/Serology Lab, Small	F	F	F	F	--	D	A	--	--	--	--	--				
		THIS TYPICAL INCLUDES: 1 Equip Rail, Wall-Mt, 48W (1219mm) 1 Clinical Panel, Open 80H (2032mm) x 24W (610mm) 2 Clinical Panel, 80H (2032mm) x 30W (762mm) 3 Clinical Panel, 80W (2032mm) x 48W (1219mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80H (2032mm) x 48W (1219mm) 2 Clinical Panel, 48H (1219mm) x 30W (762mm) 1 Clinical Panel, 80H (2032mm) x 48W (1219mm) 1 Light, 24W (610mm) 5 Light 48W (1219mm) 2 Electric/Data Channel 48W (1219mm) 1 Electrical/Data Channel 72W (1829mm) 2 Electrical/Data Channel, Corner 4 Cantilevered Work Surf, 30D (762mm) x 48W (1219mm) 1 Cantilevered Work Surf, 30D (762mm) x 72W (1829mm) 1 Height Adjustable Table, 30D (762mm) x 48W (1219mm) 3 DR, 3H (76mm) 3 DR, 6H (152mm) 1 Lockable Flipper Unit, 24W (610mm) 4 Lockable Flipper Unit, 48W (1219mm) 3 Mobile Drawer Caddie with Drawers 1 Adjustable Keyboard Tray 4 Shelf, Storage/Display 48W (1219mm) 1 3 Shelf Unit with Door, 48W (1219mm) 1 Shelf, Storage/Display 24W (610mm) 1 Extra Deep Shelf, 48W (1219mm) 10 Paper Tray 1 Sink Base Cab, w/Door, Backsplash, 30D (762mm) x 48W (1219mm) 1 Swing-Away Eyewash 1 SS Double Sink 19D (483mm) x 33D (838mm) 1 Gooseneck Mixing Faucet ASSY. with Wristbands 1 Strainer and Tailpiece 1 Coat Hook Drawer Organizer Bins * Connecting hardware required to complete installation. [Workstation requires interface between the modular furniture and																

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

building for both electrical and plumbing.]

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:
EA	84	120	96	2,243 lb	--	--	--	--	NO
	CM: 213	305	244	1,019 kg	2:	--	--	--	NO

E0589	6530	Workstation, Chemistry Lab, Medium	F	F	F	F	--	A	A	--	--	--	--
-------	------	------------------------------------	---	---	---	---	----	---	---	----	----	----	----

THIS TYPICAL INCLUDES:

- 1 Module, 80H (2032mm) x 48W (1219mm),w/ 7-1/4 inch utility chase, w/ service shelf
- 1 Clinical Panel, Open 80H (2032mm) x 24W (610mm)
- 3 Clinical Panel, Open 80H (2032mm) x 30W (762mm)
- 1 Clinical Panel, Open 80H (2032mm) x 48W (1219mm)
- 3 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 30W (762mm)
- 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 48W (1219mm)
- 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 48W (1219mm) x 48W (1219mm)
- 2 Clinical Panel, 48H (1219mm) x 30W (762mm)
- 1 Clinical Panel, 48H (1219mm) x 48W (1219mm)
- 3 Clinical Panel, 80H (2032mm) x 30W (762mm)
- 2 Vertical Chase Cover
- 1 Electrical/Data Channel 30W (762mm)
- 1 Electrical/Data Channel 48W (1219mm)
- 1 Electrical/Data Channel 72W (1829mm)
- 1 Electrical/Data Channel, Corner
- 1 Light, 24W (610mm)
- 11 Light, 48W (1219mm)
- 1 Cantilevered Work Surface, 30D (762mm) x 24W (610mm)
- 10 Cantilevered Work Surface, 30D (762mm) x 48W (1219mm)
- 2 Cantilevered Corner Work Surface, 30D (762mm) x 48W (1219mm)
- 1 Height Adjustable Table, 36D (914mm) x 72W (1829mm)
- 3 Adjustable Keyboard Tray
- 6 Mobile Drawer Caddie with Drawers
- 5 DR, 3H (76mm)
- 11 DR, 6H (152mm)
- 1 DR, 9H (229mm)
- 2 Storage Frame
- 3 Storage Cabinet With Door
- 1 Mobile Cart w/Top Surface
- 1 Lockable Flipper Unit, 24W (610mm)
- 8 Lockable Flipper Unit, 48W (1219mm)
- 3 3 Shelf Unit with Door, 48W (1219mm)
- 1 Shelf, Storage/Display 24W (610mm)
- 8 Shelf, Storage/Display 48W (1219mm)
- 4 Extra Deep Shelf, 48W (1219mm)
- 4 Paper Trays
- 1 Sink Base Cabinet, w/Double Door, Backsplash 30D (762mm) x 60W (1524mm)
- 1 Swing-Away Eyewash
- 1 SS Sink 19D (483mm) x 19D (483mm)
- 2 Cup Sink 6D (152mm) x 3D (76mm)
- 3 Gooseneck Mixing Faucet ASSY. With Wristbands
- 3 Strainer and Tailpiece
- 2 Coat Hooks
- Drawer Organizer Bins

* Connecting hardware required to complete installation.

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:
EA	84	196	120	6,685 lb	--	--	--	0	NO
	CM: 213	498	305	3,035 kg	2:	--	--	--	NO

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
E0590	6530	Workstation, Urinalysis Lab, Medium	F	F	F	F	--	A	A	--	--	--	--	--	--	--	--	--
		<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Equipment Rail, Wall MNTD. 48W (1219mm) 1 Clinical Panel, Open 80H (2032mm) x 24W (610mm) 5 Clinical Panel, Open 80H (2032mm) x 48W (1219mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 30W (762mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 48W (1219mm) 1 Clinical Panel, 48H (1219mm) x 30W (762mm) 2 Clinical Panel, 80H (2032mm) x 48W (1219mm) 1 Electrical/Data Channel 30W (762mm) 3 Electrical/Data Channel 48W (1219mm) 1 Electrical/Data Channel 72W (1829mm) 2 Electrical/Data Channel, Corner 1 Light, 24W (610mm) 5 Light, 48W (1219mm) 1 Cantilevered Work Surface, 30D (762mm) x 72W (1829mm) 3 Cantilevered Work Surface, 30D (762mm) x 48W (1219mm) 2 Cantilevered Corner Work Surface, 30D (762mm) x 48W (1219mm) 2 Adjustable Keyboard Tray 1 Mobile Drawer Caddie with Drawers 3 DR, 3H (76mm) 3 DR, 6H (152mm) 2 Storage Cabinet With Door 1 Lockable Flipper Unit, 24W (610mm) 5 Lockable Flipper Unit, 48W (1219mm) 1 Shelf, Storage/Display 24W (610mm) 5 Shelf, Storage/Display 48W (1219mm) 4 Extra Deep Shelf, 48W (1219mm) 4 Paper Trays 1 Sink Base Cabinet, w/Double Door, Backsplash 30D (762mm) x 48W (1219mm) 1 Swing-Away Eyewash 1 SS Sink 19D (483mm) x 33D (838mm) 1 Gooseneck Mixing Faucet ASSY. With Wristbands 1 Strainer and Tailpiece 1 Coat Hooks Drawer Organizer Bins <p>* Connecting hardware required to complete installation.</p>																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH CM:	WEIGHT:	VOLTS:	PHASE:	AMPS:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	84	213	366	2,643 lb 1,200 kg	1:	120	1	2	60	NO	--					
							2:	--	--	--	YES	--						

E0591	6530	Workstation, Hematology Lab, Medium	F	F	F	F	--	A	A	--	--	--	--	--	--	--	--	--
		<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 Module, 48H (1219mm) x 48W (1219mm),w/ 7-1/4 inch utility chase, w/ service shelf 1 Clinical Panel, Open 80H (2032mm) x 30W (762mm) 2 Clinical Panel, Open 80H (2032mm) x 48W (1219mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 30W (762mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 48W (1219mm) 1 Clinical Panel with Floor Entry ELEC/Data Channel, 48W (1219mm) x 30W (762mm) 7 Clinical Panel, 48H (1219mm) x 30W (762mm) 1 Clinical Panel, 80H (2032mm) x 30W (762mm) 2 Clinical Panel, 80H (2032mm) x 48W (1219mm) 1 Vertical Chase Cover 1 Electrical/Data Channel 30W (762mm) 4 Electrical/Data Channel 48W (1219mm) 2 Electrical/Data Channel 60W (1829mm) 2 Electrical/Data Channel 96W (2438mm) 1 Electrical/Data Channel, Corner 																

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
		7 Light, 48W (1219mm) 9 Cantilevered Work Surface, 30D (762mm) x 48W (1219mm) 2 Cantilevered Work Surface, 30D (762mm) x 60W (1524mm) 3 Cantilevered Corner Work Surface, 30D (762mm) x 48W (1219) 1 Height Adjustable Table, 36D (914mm) x 72W (1829mm) 3 Adjustable Keyboard Tray 7 Mobile Drawer Caddie with Drawers 14 DR, 3H (76mm) 7 DR, 6H (152mm) 4 Storage Cabinet With Door 6 Lockable Flipper Unit, 48W (1219mm) 1 3 Shelf Unit with Door, 48W (1219mm) 6 Shelf, Storage/Display 48W (1219mm) 8 Extra Deep Shelf, 48W (1219mm) 6 Paper Trays 1 Sink Base Cabinet, w/Double Door, Backsplash 30D (762mm) x 60W (1524mm) 1 Sink 19D (483mm) x 19D (483mm) 1 Cup Sink 6D (152mm) x 3D (76mm) 2 Gooseneck Mixing Faucet ASSY. With Wristbands 2 Strainer and Tailpiece 2 Coat Hooks Drawer Organizer Bins * Connecting hardware required to complete installation.																	
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
			EA	84	213	288	176	5,541 lb 2,516 kg	1: 120 2: --	1 --	3 --	60 NO YES	NO YES	-- --					

E0592	6530	Workstation, Shipping/Receiving Lab, Medium	F	F	F	F	--	A	A	--	--	--	--	--
TTHIS TYPICAL INCLUDES: 1 Equipment Rail, Wall MNTD. 48W (1219mm) 1 Clinical Panel, Open 80H (2032mm) x 24W (610mm) 4 Clinical Panel, Open 80H (2032mm) x 48W (1219mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 30W (762mm) 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 48W (1219mm) 1 Clinical Panel, 48H (1219mm) x 30W (762mm) 1 Clinical Panel, 48H (1219mm) x 48W (1219mm) 1 Clinical Panel, 80H (2032mm) x 30W (762mm) 2 Clinical Panel, 80H (2032mm) x 48W (1219mm) 2 Electrical/Data Channel 30W (762mm) 3 Electrical/Data Channel 48W (1219mm) 1 Electrical/Data Channel 72W (1829mm) 2 Electrical/Data Channel, Corner 1 Light, 24W (610mm) 5 Light, 48W (1219mm) 5 Cantilevered Work Surface, 30D (762mm) x 48W (1219mm) 1 Cantilevered Work Surface, 30D (762mm) x 72W (1829mm) 1 Height Adjustable Table, 30D (914mm) x 60W (1524mm) 1 Cantilevered ADA Sink Cabinet w/ Backsplash, 30D (762mm)x 24W (610mm) 2 Adjustable Keyboard Tray 4 Mobile Drawer Caddie with Drawers 3 DR, 3H (76mm) 3 DR, 6H (152mm) 1 Lockable Flipper Unit, 24W (610mm) 5 Lockable Flipper Unit, 48W (1219mm) 1 Shelf, Storage/Display 24W (610mm) 5 Shelf, Storage/Display 48W (1219mm) 4 Extra Deep Shelf, 48W (1219mm)														

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

4 Paper Trays
 1 SS ADA Sink 19D (483mm) x 19D (483mm)
 1 Gooseneck Mixing Faucet ASSY. with Wristbands
 1 Strainer and Tailpiece
 1 Coat Hooks
 Drawer Organizer Bins
 * Connecting hardware required to complete installation.

UNIT OF ISSUE:	HEIGHT IN:	WIDTH IN:	DEPTH IN:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	84	144	144	2,814 lb	1: 120	1	2	60	NO
	CM: 213	366	366	1,278 kg	2: --	--	--	DEPENDENT: YES	--

E0593	6530	Workstation, Histopathology Lab, Medium	F F F F --	A A -- -- -- --
-------	------	---	------------	-----------------

THIS TYPICAL INCLUDES:

2 Module, 48H (1219mm) x 24W (610mm),w/ 7-1/4 inch utility chase, w/ service shelf
 5 Module, 48H (1219mm) x 48W (1219mm),w/ 7-1/4 inch utility chase, w/ service shelf
 5 Clinical Panel, Open 80H (2032mm) x 30W (762mm)
 6 Clinical Panel, Open 80H (2032mm) x 48W (1219mm)
 2 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 48W (1219mm)
 6 Clinical Panel, 48H (1219mm) x 30W (762mm)
 1 Clinical Panel, 80H (2032mm) x 30W (762mm)
 2 Vertical Chase Cover
 7 Electrical/Data Channel 48W (1219mm)
 1 Electrical/Data Channel 60W (1829mm)
 1 Electrical/Data Channel, Corner
 4 Light, 30W (762mm)
 8 Light, 48W (1219mm)
 13 Cantilevered Work Surface, 30D (762mm) x 48W (1219mm)
 1 Cantilevered Work Surface, 30D (762mm) x 60W (1524mm)
 1 Cantilevered Work Surface, 30D (762mm) x 72W (1829mm)
 4 Height Adjustable Table, 36D (914mm) x 72W (1829mm)
 2 Adjustable Keyboard Tray
 8 Mobile Drawer Caddie with Drawers
 21 DR, 3H (76mm)
 8 DR, 6H (152mm)
 7 Storage Cabinet With Door
 4 Lockable Flipper Unit, 30W (762mm)
 7 Lockable Flipper Unit, 48W (1219mm)
 1 3 Shelf Unit with Door, 48W (1219mm)
 4 Shelf, Storage/Display 30W (762mm)
 7 Shelf, Storage/Display 48W (1219mm)
 4 Extra Deep Shelf, 24W (610mm)
 12 Extra Deep Shelf, 48W (1219mm)
 4 Paper Trays
 2 Sink Base Cabinet, w/Double Door, Backsplash 30D (762mm) x 60W (1524mm)
 2 Swing-Away Eyewash
 2 SS Sink 19D (483mm) x 19D (483mm)
 2 Gooseneck Mixing Faucet ASSY. With Wristbands
 2 Strainer and Tailpiece
 3 Coat Hooks
 Drawer Organizer Bins
 * Connecting hardware required to complete installation.

UNIT OF ISSUE:	HEIGHT IN:	WIDTH IN:	DEPTH IN:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	84	456	168	5,187 lb	1: 120	1	5	60	NO
	CM: 213	1158	427	2,355 kg	2: --	--	--	DEPENDENT: YES	--

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
E0594	6530	Workstation, Microbiology Lab, Medium	F	F	F	F	--	A	A	--	--	--	--	--	--	--	--	--
<p>THIS TYPICAL INCLUDES:</p> <p>2 Module, 48H (1219mm) x 24W (610mm),w/ 7-1/4 inch utility chase, w/ service shelf</p> <p>4 Module, 48H (1219mm) x 48W (1219mm),w/ 7-1/4 inch utility chase, w/ service shelf</p> <p>1 Clinical Panel, Open 80H (2032mm) x 24W (610mm)</p> <p>4 Clinical Panel, Open 80H (2032mm) x 30W (762mm)</p> <p>6 Clinical Panel, Open 80H (2032mm) x 48W (1219mm)</p> <p>2 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 48W (1219mm)</p> <p>6 Clinical Panel, 80H (2032mm) x 30W (762mm)</p> <p>2 Vertical Chase Cover</p> <p>5 Electrical/Data Channel 48W (1219mm)</p> <p>1 Electrical/Data Channel 72W (1829mm)</p> <p>2 Electrical/Data Channel, Corner</p> <p>1 Light, 24W (610mm)</p> <p>2 Light, 30W (762mm)</p> <p>8 Light, 48W (1219mm)</p> <p>7 Cantilevered Work Surface, 30D (762mm) x 48W (1219mm)</p> <p>5 Cantilevered Work Surface, 30D (762mm) x 72W (1829mm)</p> <p>2 Cantilevered Corner Work Surface,30D (762mm) x 48W (1219) x 48W (1219mm)</p> <p>1 Height Adjustable Table, 30D (762mm) x 60W (1524mm)</p> <p>1 Height Adjustable Table, 30D (762mm) x 72W (1829mm)</p> <p>1 Height Adjustable Table, 36D (914mm) x 72W (1829mm)</p> <p>3 Adjustable Keyboard Tray</p> <p>11 Mobile Drawer Caddie with Drawers</p> <p>13 DR, 3H (76mm)</p> <p>11 DR, 6H (152mm)</p> <p>1 Lockable Flipper Unit, 24W (610mm)</p> <p>2 Lockable Flipper Unit, 30W (762mm)</p> <p>7 Lockable Flipper Unit, 48W (1219mm)</p> <p>1 3 Shelf Unit with Door, 48W (1219mm)</p> <p>1 Shelf, Storage/Display 24W (610mm)</p> <p>2 Shelf, Storage/Display 30W (762mm)</p> <p>7 Shelf, Storage/Display 48W (1219mm)</p> <p>12 Extra Deep Shelf, 48W (1219mm)</p> <p>8 Paper Trays</p> <p>2 Sink Base Cabinet, w/Double Door, Backsplash 30D (762mm) x 60W (1524mm)</p> <p>2 Swing-Away Eyewash</p> <p>3 SS Sink 19D (483mm) X 19D (483mm)</p> <p>2 Gooseneck Mixing Faucet ASSY. With Wristbands</p> <p>2 Strainer and Tailpiece</p> <p>2 Coat Hooks</p> <p>Drawer Organizer Bins</p> <p>* Connecting hardware required to complete installation.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	84	264	168	7,086 lb	1:	120	1	4	NO							
		CM:	213	671	427	3,217 kg	2:	--	--	--	NO							

E0595	6530	Workstation, Blood Bank Lab, Medium	F	F	F	F	--	A	A	--	--	--	--	--	--	--	--	--
<p>THIS TYPICAL INCLUDES:</p> <p>6 Module, 80H (2032mm) x 48W (1219mm),w/ 7-1/4 inch utility chase, w/ service shelf</p> <p>1 Clinical Panel, Open 80H (2032mm) x 30W (762mm)</p> <p>5 Clinical Panel, Open 80H (2032mm) x 48W (1219mm)</p> <p>1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 24W (610mm)</p> <p>1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80W (2032mm) x 30W (762mm)</p> <p>1 Clinical Panel with Floor Entry ELEC/Data Channel, 48W (1219mm) x 30W (762mm)</p> <p>6 Clinical Panel, 48H (1219mm) x 30W (762mm)</p> <p>3 Clinical Panel, 80H (2032mm) x 30W (762mm)</p> <p>2 Vertical Chase Cover</p>																		

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES						
				R	A	F	A	H							1	2

- 1 Electrical/Data Channel 24W (610mm)
 1 Electrical/Data Channel 48W (1219mm)
 1 Electrical/Data Channel 60W (152429mm)
 1 Electrical/Data Channel 72W (1823mm)
 3 Electrical/Data Channel, Corner
 1 Light, 24W (610mm)
 11 Light, 48W (1219mm)
 1 Cantilevered Work Surface, 30D (762mm) x 24W (610mm)
 6 Cantilevered Work Surface, 30D (762mm) x 48W (1219mm)
 1 Cantilevered Work Surface, 30D (762mm) x 60W (1524mm)
 3 Cantilevered Corner Work Surface,30D (762mm) x 48W (1219) x 48W (1219mm)
 2 Height Adjustable Table, 30D (762mm) x 48W (1219mm)
 4 Adjustable Keyboard Tray
 6 Mobile Drawer Caddie with Drawers
 6 DR, 3H (76mm)
 10 DR, 6H (152mm)
 1 DR, 9H (229mm)
 2 Storage Frame
 1 Storage Cabinet With Door
 1 Lockable Flipper Unit, 24W (610mm)
 10 Lockable Flipper Unit, 48W (1219mm)
 1 3 Shelf Unit with Door, 48W (1219mm)
 1 Shelf, Storage/Display 24W (610mm)
 10 Shelf, Storage/Display 48W (1219mm)
 6 Extra Deep Shelf, 48W (1219mm)
 4 Paper Trays
 1 Sink Base Cabinet, w/Double Door, Backsplash 30D (762mm) x 48W (1219mm)
 2 Cantilevered Sink Cabinet, w/Backsplash, 30D (762mm) x 48W (1219mm)
 3 Swing-Away Eyewash
 3 SS Sink 19D (483mm) x 33D (838mm)
 2 Cup Sink 6D (152mm) x 3D (76mm)
 5 Gooseneck Mixing Faucet ASSY. With Wristbands
 5 Strainer and Tailpiece
 1 Coat Hooks
 Drawer Organizer Bins
 * Connecting hardware required to complete installation.

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:	
EA	84	456	144	144	6,486 lb	1:	120	1	5	60	NO	BTUs / HR:
	CM:	213	1158	366	2,945 kg	2:	--	--	--	DEPENDENT:	YES	--

E0603	6530	Shelf Unit, Pharmacy, Wall Mtd, 88"Hx48"Wx9"D	F	F	F	F	--	--	--	--	--	--
-------	------	---	---	---	---	---	----	----	----	----	----	----

THIS TYPICAL INCLUDES:

- 2 Vertical Hanging Strips
 3 3 Shelf, Unit

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:	
EA	88	48	9	9	75 lb	1:	--	--	--	--	NO	BTUs / HR:
	CM:	224	122	23	34 kg	2:	--	--	--	DEPENDENT:	NO	--

E0606	6530	Shelf Unit, Pharmacy, Wall Mtd, 88"Hx24"Wx16"D	F	F	F	F	--	--	--	--	--	--
-------	------	--	---	---	---	---	----	----	----	----	----	----

THIS TYPICAL INCLUDES:

- 2 Vertical Hanging Strips
 3 3 Shelf, Unit

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:	
EA	88	24	16	16	75 lb	1:	--	--	--	0	NO	BTUs / HR:
	CM:	224	61	41	34 kg	2:	--	--	--	DEPENDENT:	NO	--

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
E0609	6530	Shelf Unit, Pharmacy, Wall Mtd, 88"Hx30"Wx16"D	F F F F --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 3 3 Shelf, Unit															
UNIT OF ISSUE: EA		HEIGHT IN: 88 CM: 224	WIDTH: 30	DEPTH: 16 CM: 41	WEIGHT: 100 lb CM: 46 kg	VOLTS 1: --	PHASE 2: --	AMPS: --	HZ: 0	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --			
E0612	6530	Shelf Unit, Pharmacy, Wall Mtd, 88"Hx48"Wx16"D	F F F F --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 3 3 Shelf, Unit															
UNIT OF ISSUE: EA		HEIGHT IN: 88 CM: 224	WIDTH: 48	DEPTH: 16 CM: 41	WEIGHT: 160 lb CM: 73 kg	VOLTS 1: --	PHASE 2: --	AMPS: --	HZ: 0	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --			
E0615	6530	Shelves, Pharmacy, Wall Mtd, 88"Hx48"Wx13"D	F F F F --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 9 Shelf, Storage/Display															
UNIT OF ISSUE: EA		HEIGHT IN: 88 CM: 224	WIDTH: 48	DEPTH: 13 CM: 33	WEIGHT: 150 lb CM: 69 kg	VOLTS 1: --	PHASE 2: --	AMPS: --	HZ: --	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --			
E0618	6530	Shelves, Pharmacy, Wall Mtd, Tall, 88"Hx48"Wx16"D	F F F F --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 5 Extra Deep Shelves															
UNIT OF ISSUE: EA		HEIGHT IN: 88 CM: 224	WIDTH: 48	DEPTH: 16 CM: 41	WEIGHT: 75 lb CM: 34 kg	VOLTS 1: --	PHASE 2: --	AMPS: --	HZ: 0	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --			
E0624	6530	Counter, Work, w/Storage, Pharm, Wall Mtd, 48"W	F F F F --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 3 Shelf, Unit 1 Cantilevered Work Surface 2 Extra Deep Shelves															
UNIT OF ISSUE: EA		HEIGHT IN: 88 CM: 224	WIDTH: 48	DEPTH: 24 CM: 61	WEIGHT: 120 lb CM: 55 kg	VOLTS 1: --	PHASE 2: --	AMPS: --	HZ: 0	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --			
E0627	6530	Counter, Work, w/Storage, Cab, Pharm, Wall Mtd, 48"	F F F F --	--	A	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 3 Shelf, Unit 1 Cantilevered Work Surface 2 Storage Cabinets 4 Pull-Out Bottle Drawers															
UNIT OF ISSUE: EA		HEIGHT IN: 88 CM: 224	WIDTH: 48	DEPTH: 24 CM: 61	WEIGHT: 125 lb CM: 57 kg	VOLTS 1: --	PHASE 2: --	AMPS: --	HZ: 0	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --			

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES										
				R	A	F	A	H		1	2	3	4	5	6					
E0630	6530	Table, Work, w/Storage, Pharm, Wall Mtd, 48"W	F F F F --																	
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 5-Shelf Unit 1 Freestanding Work Surface 1 Drawer, 6"H (152mm)																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:							
EA		IN:	88	48	24	125 lb	1:	--	--	--	NO		--							
		CM:	224	122	61	57 kg	2:	--	--	--	NO		--							
E0633	6530	Counter, w/Sink, Storage, Pharm, Wall Mtd, 66"W	F F F F --																	
THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Cabinet With Doors 1 Light 1 Cantilevered Work Surface 1 Cantilevered Sink Adaptable Work Surface 1 Extra Deep Shelf																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:							
EA		IN:	88	66	24	135 lb	1:	120	1	1	NO		--							
		CM:	224	168	61	62 kg	2:	--	--	--	YES		--							
E0636	6530	Counter, Work, w/Storage, Cab, Pharm, Wall Mtd,72"	F F F F --																	
THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips 2 3 Shelf, Units 2 Cantilevered Work Surfaces 2 Storage Cabinets 4 Pull-out Bottle Drawers 2 Shelves, Storage/Display																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:							
EA		IN:	88	72	24	225 lb	1:	--	--	--	NO		--							
		CM:	224	183	61	103 kg	2:	--	--	--	NO		--							
E0639	6530	Counter, Work, w/Storage, Pharm, Wall Mtd, 96"W	F F F F --																	
THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips 2 Cabinets With Doors 2 Lights 1 Cantilevered Work Surface 1 Freestanding Sink Adaptable Cabinet w/integral Backsplash 2 Extra Deep Shelves 2 Drawers, 6"H (152mm)																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:							
EA		IN:	88	96	24	251 lb	1:	120	1	1	NO		--							
		CM:	224	244	61	114 kg	2:	--	--	--	YES		--							
E0645	6530	Station, Picking, Pharm, Straight, Wall Mtd, 144"W	F F F F --																	
This JSN includes: 5 vertical hanger strips; 8 shelves, storage/display; 1 shelf, storage, micro; 60 bins, 2-1/4"W (57mm) x 2-3/16"W (57mm); 25 bins, 4-9/16"W (114mm) x 2-3/16"H (57mm); 4 bins, 4-9/16"W (114mm) x 5-3/16"H (133mm); 1 mini-shelf; 1 tack board; 2 cantilevered work surfaces w/attached backsplashes; 1 cantilevered, sink adaptable work surface w/attached backsplash; 1 lockable drawer, 6"H (152mm); 1 adjustable keyboard tray; 1 drawer, 6"H (152mm); 2 storage cabinets; 3 pull-out bottle drawers; 1 lockable drawer, 6"H (152mm); 1 pull-out gravity feed shelf and 1 drawer, 8"H (203mm).																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:							
EA		IN:	88	146	24	401 lb	1:	--	--	--	NO		--							
		CM:	224	371	61	182 kg	2:	--	--	--	NO		--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
E0648	6530	Station, Picking, Pharm, U-Shape, Free Std, 144x72	F	F	F	F	--	--	--	--	--	--	--	--	--	--	--	--	
This JSN includes: 12 solid panels, 85"H (2159mm) x 24"W (610mm); 1 solid panel, 85"H (2159mm) x 48"W (1219mm); 4 panel connectors, 2-way corner, 85"H (2159mm); 8 panel-to-panel connectors; 2 finished end hardware kits; 2 9-shelf units, 24"W (610mm); 1 5-shelf unit, 48"W (1219mm); 2 5-shelf corner units, 48"W (1219mm); 400 bins, 2-1/4"W (57mm) x 2-3/16"H (57mm); 50 bins, 4-9/16"W (114mm) x 2-3/16"W (57mm); 2 cantilevered, corner work surfaces, 48"W (1219mm); 1 cantilevered work surface, 48"W (1219mm); 1 drawer, 3"H (76mm) and 1 drawer, 6"H (152mm).																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	85	150	78	350 lb	1:	--	--	--	NO	--							
			216	381	198	159 kg	2:	--	--	--	NO	--							
E0651	6530	Station, Picking, Pharm, U-Shape, Stor, F/S	F	F	F	F	--	--	--	--	--	--	--	--	--	--	--	--	
A U-shaped, pharmacy picking and storage station, approximate size 72" by 144". This JSN includes: 6 solid panels, 85"H (2159mm) x 24"W (610mm); 4 solid panels, 85"H (2159mm) x 48"W (1219mm); 4 panel connectors, 90 degree corner, 85"H (2159mm); 5 panel-to-panel connectors; 2 finished end hardware kits; 20 dispensing rails, 48"W (1219mm); 240 bins, 2-1/4"W (57mm) x 2-1/4"H (57mm); 40 bins, 4-1/2"W (114mm) x 2-1/4"H (57mm); 40 bins, 4-1/2"W (114mm) x 5-1/4"H (133mm); 2 cantilevered work surfaces, 48"W (1219mm); 2 cantilevered work surfaces, 72"W (1829mm); 4 drawers, 3"H (76mm); 4 drawers, 6"H (152mm); 2 extra deep shelves and drawer organizer bins.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	85	150	78	302 lb	1:	--	--	--	NO	--							
			216	381	198	138 kg	2:	--	--	--	NO	--							
E0657	6530	Module, Storage, Pharm, U-Shape, F/S, 155x55	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
This JSN includes: 6 solid panels, 85"H (2159mm) x 48"W (1219mm); 3 solid panels, 85"H (2159mm) x 12"W (305mm); 5 panel connectors, 2-way corner, 85"H (2159mm); 1 panel connector, 3-way corner, 85"H (2159mm); 1 panel-to-panel connector; 3 finished end hardware; 3 U-shaped, 9-shelf units.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	85	155	55	500 lb	1:	--	--	--	NO	--							
			216	394	140	227 kg	2:	--	--	--	NO	--							
E0660	6530	Module, Storage, Pharm, Straight, F/S, 154"Wx21"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
This JSN includes: 2 solid panels, 85"H (2159mm) x 24"W (610mm); 2 solid panels, 85"H (2159mm) x 48"W (1219mm); 3 solid panels, 85"H (2159mm) x 18"W (305mm); 2 panel connectors, 2-way corner, 85"H (2159mm); 1 panel connector, 3-way corner, 85"H (2159mm); 2 panel-to-panel connectors; 3 finished end hardware; 6 3-shelf units, 24"W (610mm) and 6 3-shelf unit, 48"W (1219mm).																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	85	154	21	250 lb	1:	--	--	--	0	NO	--						
			216	391	53	114 kg	2:	--	--	--	NO	--							
E0665	6530	Pharmacy Bulk Storage Low Volume	F	F	F	C	--	--	--	--	F	--	--	--	--	--	--	--	
E0665 BULK STORAGE 4 Solid Panel, 53H (1346mm) x 24W (610mm) 12 Solid Panel, 85H (2159mm) x 18W (457mm) 1 Solid Powered Panel, 85H (2159mm) x 24W (610mm) 3 Solid Panel, 85H (2159mm) x 24W (610mm) 2 Solid Powered Panel, 85H (2159mm) x 48W (1219mm) 3 Solid Panel, 85H (2159mm) x 48W (1219mm) 1 Open Panel, 85H (2159mm) x 24W (610mm) 1 Open Panel, 85H (2159mm) x 48W (1219mm) 3 Cantilevered Work Surface, 48W (1219mm) 36 Shelf Storage Display 24W (610mm) 40 Shelf Storage Display 48W (1219mm) 1 Lockable Flipper Unit 48W (1219mm) 1 Tackboard, 48W (1219mm) 1 Tool Rail 6 Deep Shelf with add-on 24W (610mm) 6 Deep Shelf with add-on 48W (1219mm) 1 Cart Body Style-A Wide with Top Spine and Double Doors 2 Drawer 3H (76mm)																			

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES										
				A	N	A	V	I						
				R	A	F	A	H	1	2	3	4	5	6

- 2 Wire Shelf With Dividers
- 4 Caster, Swivel, Brk
- 4 Caster, Swivel
- 1 Wire Cart 5 Shelves 24D (610mm) x 36W (914mm) x 68H (1721mm)
- 1 Wire Cart 3 Shelves, Push Handles, 21D (533mm) x 36W (914mm) x 40H (1016mm)
- 1 Mobile Pedestal, File/File
- 2 Light, 48W (1219mm)
- 1 Paper Tray
- 2 Adjustable Keyboard Tray
- 3 3-Shelf Unit, 24W (610mm)

*Connecting hardware required to complete installation. [No other source(s) identified with this description/specification.]

UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	IN: 85 CM: 216	444 1128	192 488	-- lb -- kg	1: 120 2: --	1 --	20 --	60 NO YES	--

E0666	6530	Pharmacy Manufacturing & Prepack Low Volume	F F F C --	D -- -- -- -- --
-------	------	---	------------	------------------

E0666 MANUFACTURING AND PREPACK (low volume)

- 1 Eyewash
- 1 Shelf Storage Display 24W (610mm)
- 4 Shelf Storage Display 36W (915mm)
- 4 Vertical Hanger Strip
- 1 Equipment Rail
- 1 Cantilevered Work Surface 72W (1829mm)
- 1 Cantilevered Sink-Adaptable Work Surface with Integral Backsplash 24W (610mm)
- 1 Adjustable Keyboard Tray
- 1 Sink and Faucet
- 1 Storage Cabinet
- 1 Lockable Drawer 4H (102mm)
- 3 Pullout Bottle Drawer 6H (152mm) [No other source(s) identified with this description/specification.]

UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	IN: 85 CM: 216	156 396	32 81	-- lb -- kg	1: -- 2: --	-- --	-- --	0 NO NO	--

E0667	6530	Pharmacy Dispensing & Storage Low Volume	F F F C --	-- F -- -- -- -- --
-------	------	--	------------	---------------------

E0667 DISPENSING AND STORAGE

- 1 Eyewash
- 8 Solid Panel, 53H (1346mm) x 24W (610mm)
- 2 Solid Panel, 53H (1346mm) x 48W (1219mm)
- 4 Solid Panel, 85H (2159mm) x 18W (457mm)
- 3 Solid Powered Panel, 85H (2159mm) x 24W (610mm)
- 2 Solid Panel, 85H (2159mm) x 30W (762mm)
- 2 Solid Powered Panel, 85H (2159mm) x 48W (1219mm)
- 1 Open Panel, 85H (2159mm) x 30W (762mm)
- 1 Open Panel, 85H (2159mm) x 48W (1219mm)
- 1 Cantilevered Work Surface, 48W (1219mm)
- 1 Peninsula Work Surface 60W (1524mm)
- 2 Transaction Countertop 24W (610mm)
- 6 Shelf Storage/Display 24W (610mm)
- 1 Shelf Storage/Display 30W (762mm)
- 11 Shelf Storage/Display 48W (1219mm)
- 1 Lockable Flipper Unit 30W (762mm)
- 1 Lockable Flipper Unit 48W (1219mm)
- 1 Tackboard 30W (762mm)
- 4 Tackboard 48W (1219mm)
- 5 Tool Rail
- 6 Vertical Hanger Strip
- 1 Equipment Rail

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

- 6 Cantilevered Work Surface 48W (1219mm)
 3 Cantilevered Work Surface 72W (1829mm)
 1 Cantilevered ADA Sink-Adaptable Work Surface with Integral Backsplash 48W (1219mm)
 1 Height-Adjustable Table 48W (1219mm)
 3 Height-Adjustable Table 72W (1829mm)
 1 Storage Frame
 1 Drawer 3H (76mm)
 3 Drawer 6H (152mm)
 1 Drawer 9H (229mm)
 1 Light 30W (762mm)
 1 Light 48W (1219mm)
 6 Paper Trays
 11 Adjustable Keyboard Tray
 1 ADA Sink and Faucet
 3 Storage Unit with Door
 5 3-Shelf Unit 24W (610mm)
 7 3-Shelf Unit 48W (1219mm)
 6 3-Shelf Unit 30W (762mm)
 11 Storage Cabinet
 10 Shelf, Fixed
 12 Drawer 4H (102mm)
 2 Drawer 8H (203mm)
 15 Pullout Bottle Drawer

*Connecting hardware required to complete installation. [No other source(s) identified with this description/specification.]

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:		
OF ISSUE:	IN:	85	408	240	-- lb	1:	120	1	20	HZ SWITCH: NO	BTUs / HR:
EA	CM:	216	1036	610	-- kg	2:	--	--	--	DEPENDENT: YES	--

E0668	6530	Pharmacy IV Admixture Low Volume	F F F C --	D A -- -- -- --
-------	------	----------------------------------	------------	-----------------

- E0668 I.V. ADMIXTURE
 1 Eyewash
 1 Height-Adjustable Table 48W (1219mm)
 1 Freestanding Sink Adaptable Cabinet with Integral Backsplash 24W (610mm)
 2 Tray/Shelf
 1 Storage Frame
 3 Drawer, 3H (76mm)
 2 Drawer, 6H (152mm)
 1 Drawer, 9H (229mm)
 1 Mobile Cart with Top Surface
 3 Wire Shelf
 1 Large Storage Container on Wheels
 1 Adjustable Keyboard Tray
 1 Sink and Faucet

Drawer Organizer Bins [No other source(s) identified with this description/specification.]

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:		
OF ISSUE:	IN:	85	120	144	-- lb	1:	120	1	1	HZ SWITCH: NO	BTUs / HR:
EA	CM:	216	305	366	-- kg	2:	--	--	--	DEPENDENT: YES	--

E0673	6530	Pharmacy Bulk Storage Medium Volume	C C C C --	D F -- -- -- --
-------	------	-------------------------------------	------------	-----------------

- E0673 BULKSTOR
 1 Eyewash
 2 Solid Panel, 47H (1194mm) x 18W (457mm)
 1 Solid Powered Panel, 47H (1194mm) x 24W (610mm)
 5 Solid Panel, 47H (1194mm) x 24W (610mm)
 2 Solid Powered Panel, 47H (1194mm) x 36W (914mm)
 2 Solid Powered Panel, 47H (1194mm) x 36W (914mm)
 2 Solid Powered Panel, 47H (1194mm) x 48W (1219mm)

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I			UTILITIES			
				R	A	F	A	H	1	2

- 1 Solid Powered Panel, 53H (1346mm) x 24W (610mm)
 - 3 Solid Panel, 53H (1346mm) x 24W (610mm)
 - 19 Solid Panel, 85H (2159mm) x 18W (457mm)
 - 1 Solid Powered Panel, 85H (2159mm) x 24W (610mm)
 - 1 Solid Panel, 85H (2159mm) x 24W (610mm)
 - 4 Solid Panel, 85H (2159mm) x 30W (762mm)
 - 1 Solid Powered Panel, 85H (2159mm) x 36W (914mm)
 - 1 Solid Panel, 85H (2159mm) x 36W (914mm)
 - 1 Solid Panel, 85H (2159) x 42W (1067mm)
 - 4 Solid Powered Panel, 85H (2159mm) x 48W (1219mm)
 - 16 Solid Panel, 85H (2159mm) x 48W (1219mm)
 - 1 Open Powered Panel, 85H (2159mm) x 36W (914mm)
 - 4 Open Powered Panel, 85H (2159mm) x 48W (1219mm)
 - 4 Cantilevered Work Surface 48W (1219mm)
 - 3 Cantilevered Work Surface 72W (1829mm)
 - 1 Cantilevered Work Surface Corner, 48W (1219mm)
 - 2 Transaction Countertop 48W (1219mm)
 - 2 Transaction Countertop 72W (1829mm)
 - 2 Hanging File Drawer
 - 2 Shelf Storage/Display 36W (914mm)
 - 147 Shelf Storage/Display 48W (1219mm)
 - 2 Lockable Flipper Unit, 24W (610mm)
 - 2 Lockable Flipper Unit, 36W (914mm)
 - 2 Lockable Flipper Unit, 48W (1219mm)
 - 3 Tackboard, 36W (914mm)
 - 4 Tackboard 48W (1219mm)
 - 11 Tool Bars
 - 1 Equipment Rail
 - 24 Deep Shelf with Add-on, 48W (1219mm)
 - 2 Height-Adjustable Table, 48W (1219mm)
 - 1 Cantilevered ADA Sink-Adaptable Work Surface with Integral Backsplash, 48W (1219mm)
 - 2 Storage Frame
 - 6 Drawer 3H (76mm)
 - 4 Drawer 6H (152mm)
 - 2 Drawer 9H (229mm)
 - 4 Wire Shelf
 - 1 Large Storage Containers on Wheels
 - 1 Wire Cart, 5 Shelves 24D (610mm) x 48W (1219mm) x 68H (1727mm)
 - 6 Caster, Swivel, Brake
 - 6 Caster, Swivel
 - 2 Wire Cart, Push Handles, 3 Shelves, 21D (533mm) x 36W (914mm) x 40H (1016mm)
 - 3 Mobile Pedestal
 - 1 Stationary Pedestal
 - 2 Light 36W (914mm)
 - 5 Light 48W (1219mm)
 - 21 Paper Trays
 - 5 Adjustable Keyboard Trays
 - 1 ADA Sink and Faucet
 - 6 3-Shelf Unit, 30W (762mm)
 - 2 3-Shelf Unit, 48W (1219mm)
 - 1 Storage Cabinet
 - 2 Shelf, Fixed
 - 1 Lockable Drawer 4H (102mm)
 - Drawer Organizer Bins
- *Connecting hardware required to complete the installation. [No other source(s) identified with this description/specification.
Electrical Requirements dependent on configuration.]

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	CM:	--	--	--	-- lb	1: 120	1	1	60	NO
		--	--	--	-- kg	2: --	--	--	DEPENDENT:	YES

E0674	6530	Pharmacy Manuf & Prepack Medium Volume	C C C C --	D A -- -- -- --
-------	------	--	------------	-----------------

E0674 MFG PRPK

- 1 Eyewash
- 4 Shelf Storage Display 24W (610mm)
- 6 Shelf Storage Display 48W (1219mm)
- 9 Vertical Hanger Strip
- 1 Cantilevered Work Surface 48W (1219mm)
- 1 Cantilevered Work Surface 72W (1829mm)
- 1 Cantilevered Sink-Adaptable Work Surface with Integral Backsplash 48W (1219mm)
- 1 Height-Adjustable Table 48W (1219mm)
- 1 Storage Frame
- 2 Drawer, 3H (76mm)
- 2 Drawer, 6H (152mm)
- 2 Light, 48W (1219mm)
- 1 Adjustable Keyboard Tray
- 1 Sink and Faucet
- 1 Storage Cabinet
- 1 Drawer 4" (102mm)
- 3 Pullout Bottle Drawer
- Drawer Organizer Bins

*Connecting hardware required to complete the installation. [The database electrical requirement is only for the module's lights. Other electrical requirements dependent on configuration.]

UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA	CM:	85	120	132	-- lb	1: 120	1	1	60	NO
		216	305	335	-- kg	2: --	--	--	DEPENDENT:	YES

E0675	6530	Pharmacy Dispensing & Storage Medium Volume	C C C C --	D F -- -- -- --
-------	------	---	------------	-----------------

E0675 DISP_STOR

- 1 Eyewash
- 5 Solid Panel, 47H (1194mm) x 24W (610mm)
- 16 Solid Panel 53H (1346mm) x 24W (610mm)
- 14 Solid Panel 85H (2159mm) x 18W (457mm)
- 6 Solid Panel 85H (2159mm) x 24W (610mm)
- 2 Solid Powered Panel 85H (2159mm) x 30W (762mm)
- 2 Solid Panel 85H (2159mm) x 30W (762mm)
- 13 Solid Powered Panel, 85H (2159mm) x 48W (1219mm)
- 4 Solid Panel, 85H (2159mm) x 48W (1219mm)
- 1 Open Panel, 67H (1702mm) x 30W (762mm)
- 1 Open Panel, 67H (1702mm) x 48W (1219mm)
- 1 Open Panel, 85H (2159mm) x 24W (610mm)
- 2 Open Panel, 85H (2159mm) x 30W (762mm)
- 2 Open Panel, 85H (2159mm) x 48W (1219mm)
- 4 Cantilevered Work Surface, 72W (1829mm)
- 1 Peninsula Work Surface, 48W (1219mm)
- 4 Shelf Storage/Display, 30W (762mm)
- 72 Shelf Storage/Display 48W (1219mm)
- 1 Lockable Flipper Unit 24W (610mm)
- 5 Lockable Flipper Unit 30W (762mm)
- 1 Lockable Flipper Unit 42W (1067mm)
- 4 Lockable Flipper Unit 48W (1219mm)
- 7 Tackboard 24W (610mm)
- 5 Tackboard 30W (762mm)

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

- 1 Tackboard 42W (1067mm)
- 3 Tackboard 48W (1219mm)
- 7 Tool Bar
- 10 Vertical Hanger Strip
- 2 Module With Utility Chase
- 1 Equipment Rail
- 1 Vertical Utility Chase
- 20 Cantilevered Work Surface, 48W (1219mm)
- 5 Cantilevered Work Surface, 60W (1524mm)
- 15 Deep Shelf with Add-on, 48W (1219mm)
- 1 Deep Shelf with Add-on, 60W (1524mm)
- 6 Height-Adjustable Table, 72W (1829mm)
- 1 Height-Adjustable Table, 60W (1524mm)
- 2 Lockable Overhead Storage Cabinet with Doors, 30W (762mm)
- 2 Lockable Overhead Storage Cabinet with Doors, 48W (1219mm)
- 1 Freestanding Sink-Adaptable Cabinet with Integral Backsplash, 48W (1219mm)
- 8 Drawer 6H (152mm)
- 6 Mobile Drawer Caddie with Drawers
- 2 Caster, Swivel, Brake
- 2 Caster Swivel
- 1 Wire Cart 5 Shelves, 24D (610mm) x 36W (914mm) x 68H (1727mm)
- 1 Pedestal, Mobile
- 2 Pedestal, Stationary
- 1 Light 24W (610mm)
- 4 Light 30W (762mm)
- 6 Light 48W (1219mm)
- 5 Paper Trays
- 18 Adjustable keyboard Tray
- 1 Sink and Faucet
- 27 3-Shelf Unit, 24W (610mm)
- 6 3-Shelf Unit, 30W (762mm)
- 20 3-Shelf Unit, 48W (1219mm)
- 28 Storage Cabinet
- 21 Shelf, Fixed
- 27 Drawer 4H (102mm)
- 2 Lockable Drawer 8H (204mm)
- 2 Drawer 8H (204mm)
- 2 Drawer 12H (306mm)
- 45 Pullout Bottle Drawer
- Drawer Organizers

*Connecting hardware required to complete the installation. [No other source(s) identified with this description/specification.
Electrical Requirements dependent on configuration.]

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:		
OF ISSUE:	IN:	85	672	432	-- lb	1:	120	1	1	HZ SWITCH: NO	
EA	CM:	216	1707	1097	-- kg	2:	--	--	--	DEPENDENT: YES	--

E0676	6530	Pharmacy Offsite Satellite Medium Volume	C	C	C	C	--	D	F	--	--	--	--
E0676 OFFSITE SAT. PHARM.													
1 Eyewash													
10 Solid Panel, 53H (1346mm) x 24W (610mm)													
19 Solid Panel, 85H (2159mm) x 18W (457mm)													
4 Solid Powered Panel, 85H (2159mm) x 24W (610mm)													
5 Solid Panel, 85H (2159mm) x 24W (610mm)													
2 Solid Panel 85H (2159mm) x 30W (762mm)													
4 Solid Powered Panel 85H (2159mm) x 48W (1219mm)													
5 Solid Panel, 85H (2159mm) x 48W (1219mm)													
1 Open Panel, 85H (2159mm) x 30W (762mm)													

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I			UTILITIES					
				R	A	F	A	H	1	2	3	4

- 2 Open Panel, 85H (2159mm) x 48W (1219mm)
 9 Cantilevered Work Surface 48W (1219mm)
 1 Peninsula Work Surface 60W (1524mm)
 2 Transaction Counterop 24W (610mm)
 42 Shelf Storage/Display 24W (610mm)
 1 Shelf Storage/Display 30W (762mm)
 61 Shelf Storage/Display 48W (1219mm)
 1 Lockable Flipper Unit, 30W (762mm)
 2 Lockable Flipper Unit, 48W (1219mm)
 1 Tack board 30W (762mm)
 5 Tack board 48W (1219mm)
 3 Tool Bar
 5 Vertical Hanger Strip
 1 Equipment Rail
 2 Cantilevered Work Surface 72W (1829mm)
 1 Cantilevered ADA Sink-Adaptable Work Surface with Integral Backsplash, 48W (1219mm)
 7 Deep Shelf with Add-on 24W (610mm)
 8 Deep Shelf with Add-on 48W (1219mm)
 5 Height-Adjustable Table 48W (1219mm)
 1 Height-Adjustable Table 72W (1829mm)
 1 Overhead Storage Cabinet with Doors 48W (1219mm)
 1 Storage Frame
 1 Drawer 3H (76mm)
 5 Drawer 6H (152mm)
 1 Drawer 9H (229mm)
 4 Caster, Swivel, Brake
 4 Caster, Swivel
 1 Wire Cart 5 Shelves 24D (610mm) x 36W (914mm) x 68H (1727mm)
 1 Wire Cart 3 Shelves Push Handle 21D (533mm) x 36W (914mm) x 40H (1016mm)
 1 Pedestal, Mobile
 1 Light 30W (762mm)
 3 Light 48W (1219mm)
 2 Paper Trays
 12 Adjustable Keyboard Tray
 1 ADA Sink and Faucet
 5 Storage Unit with Door
 7 3-Shelf Unit 24W (610mm)
 7 3-Shelf Unit 48W (1219mm)
 6 3-Shelf Unit 30W (762mm)
 9 Storage Cabinet
 8 Shelf, Fixed
 9 Drawer 4H (102mm)
 14 Pullout Bottle Drawer
 Drawer Organizers

*Connecting hardware required to complete the installation. [No other source(s) identified with this description/specification.
 Electrical Requirements dependent on configuration.]

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	
OF ISSUE:	IN:	85	696	480	-- lb	1:	120	1	1	HZ SWITCH: NO
EA	CM:	216	1768	1219	-- kg	2:	--	--	--	DEPENDENT: YES

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I					
				R	A	F	A	H	
				UTILITIES					
				1	2	3	4	5	6
E0677	6530	Pharmacy IV Admixture Medium Volume	C C C C --	D	F	--	--	--	--
<p>E0677 UNIT DOSE/IV ADMIX</p> <p>2 Eyewash</p> <p>1 Solid Powered Panel 47H (1194mm) x 24W (610mm)</p> <p>1 Solid Panel 47H (1194mm) x 24W (610mm)</p> <p>4 Solid Panel 47H (1194mm) x 30W (762mm)</p> <p>1 Solid Powered Panel 47H (1219mm) x 48W (1219mm)</p> <p>8 Solid Panel 53H (1346mm) x 24W (610mm)</p> <p>2 Solid Powered Panel 67H (1762mm) x 36W (915mm)</p> <p>1 Solid Powered Panel 67H (1762mm) x 48W (1219mm)</p> <p>2 Solid Panel 85H (2159mm) x 12W (304mm)</p> <p>4 Solid Panel 85H (2159mm) x 18W (457mm)</p> <p>6 Solid Powered Panel 85H (2159mm) x 24W (610mm)</p> <p>2 Solid Panel 85H (2159mm) x 24W (610mm)</p> <p>1 Solid Powered Panel 85H (2159mm) 30W (762mm)</p> <p>1 Solid Panel 85H (2159mm) x 30W (762mm)</p> <p>2 Solid Panel 85H 2159mm) x 36W (915mm)</p> <p>4 Solid Powered Panel 85H (2159mm) x 48W (1219mm)</p> <p>3 Solid Panel 85H (2159mm) 48W (1219mm)</p> <p>3 Open Powered Panel 67H (1762mm) x 48W (1219mm)</p> <p>2 Open Powered Panel 67H (1762mm) x 36W (914mm)</p> <p>1 Open Powered Panel 67H (1762mm) x 48W (1219mm)</p> <p>1 Cantilevered Work Surface 24W (610mm)</p> <p>11 Cantilevered Work Surface 48W (1219mm)</p> <p>3 Cantilevered Work Surface 72W (1829mm)</p> <p>3 Cantilevered Work Surface Corner 48W (1219mm)</p> <p>1 Transaction Countertop 72W (1829mm)</p> <p>10 Shelf Storage Display, 24W (610mm)</p> <p>5 Shelf Storage Display, 30W (762mm)</p> <p>16 Shelf Storage Display, 48W (1219mm)</p> <p>2 Lockable Flipper Unit 36W (914mm)</p> <p>4 Lockable Flipper Unit 48W (1219mm)</p> <p>2 Tackboard 36W (914mm)</p> <p>3 Tackboard 48W (1219mm)</p> <p>5 Tool Bar</p> <p>4 Vertical Hanger Strip</p> <p>1 Mobile Printer Table</p> <p>1 Equipment Rail</p> <p>1 Cantilevered Work Surface 30W (762mm)</p> <p>1 Cantilevered Sink-Adaptable Work Surface with Integral Backsplash 48W (1219mm)</p> <p>2 Deep Shelf with Add-on 24W (610mm)</p> <p>1 Deep Shelf with Add-on 30W (762mm)</p> <p>3 Deep Shelf with Add-on 48W (1219mm)</p> <p>2 Height-Adjustable Table 72W (1829mm)</p> <p>1 Cantilevered ADA Sink-Adaptable Work Surface with Integral Backsplash 24W (610mm)</p> <p>5 Storage Frame</p> <p>7 Drawer 3H (76mm)</p> <p>9 Drawer 6H (152mm)</p> <p>4 Drawer 9H (229mm)</p> <p>4 Mobile Cart with Top Surface</p> <p>1 Cart Body Style A Wide with Top Spine and Double Doors</p> <p>2 Wire Shelf Double Wide</p> <p>4 Caster, Swivel, Brake</p> <p>4 Caster, Swivel</p> <p>2 Wire Cart 5 Shelves 24D (610mm) x 48W (1219mm) x 68H (1727mm)</p> <p>2 Pedestal, Mobile</p> <p>4 Light 36W (915mm)</p> <p>9 Light 48W (1219mm)</p>									

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H							

- 4 Paper Trays
- 6 Adjustable Keyboard Tray
- 1 Sink and Faucet
- 1 ADA Sink and Faucet
- 1 3-Shelf Unit 24W (610mm)
- 12 3-Shelf Unit 48W (1219mm)
- 1 5-Shelf Unit 30W (762mm)
- 1 5-Shelf Unit 48W (1219mm)
- 1 5-Shelf Unit Corner 48W (1219mm)
- 7 Storage Cabinet
- 4 Shelf, Fixed
- 2 Shelf, Pullout
- 7 Drawer Lockable 4H (102mm)
- 12 Pullout Bottle Drawer
- Drawer Organizers

*Connecting hardware required to complete the installation. [No other source(s) identified with this description/specification.
Electrical Requirements dependent on configuration.]

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH CM:	WEIGHT -- lb	WEIGHT -- kg	VOLTS 1:	VOLTS 2:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:
EA	85	216	640	--	--	120	--	1	1	60	NO	--
										DEPENDENT:	YES	--

E0685	6530	Pharmacy Bulk Storage High Volume	C C C C --	D F -- -- -- --
-------	------	-----------------------------------	------------	-----------------

E0685 PHARMACY BULK STORAGE HIGH VOLUME

- 1 Eyewash
- 2 Solid Panel 47H (1194mm) x 18W (457mm)
- 1 Solid Powered Panel 47H (1194mm) x 24W (610mm)
- 5 Solid Panel 47H (1194mm) x 24W (610mm)
- 2 Solid Powered Panel 47H (1194mm) x 36W (914mm)
- 3 Solid Powered Panel 47H (1194mm) x 48W (1219mm)
- 1 Solid Powered Panel 53H (1346mm) x 24W (610mm)
- 2 Solid Panel 53H (1346mm) x 24W (610mm)
- 33 Solid Panel 85H (2159mm) x 18W (457mm)
- 1 Solid Powered Panel 85H (2159mm) x 24W (610mm)
- 2 Solid Panel 85H (2159mm) x 24W (610mm)
- 5 Solid Powered Panel 85H (2159mm) x 30W (762mm)
- 3 Solid Panel 85H (2159mm) x 30W (762mm)
- 2 Solid Powered Panel 85H (2159mm) x 36W (914mm)
- 2 Solid Panel 85H (2159mm) x 42W (1067mm)
- 2 Solid Powered Panel 85H (2159mm) x 48W (1219mm)
- 23 Solid Panel 85H (2159mm) x 48W (1219mm)
- 1 Open Panel 85H (2159mm) x 24W (610mm)
- 1 Open Powered Panel 85H (2159mm) x 36W (914mm)
- 1 Open Panel 85H (2159mm) x 36W (914mm)
- 2 Open Powered Panel 85H (2159mm) x 48W (1219mm)
- 2 Open Panel 85H (2159mm) x 48W (1219mm)
- 2 Cantilevered Work Surface 48W (1219mm)
- 3 Cantilevered Work Surface 72W (1829mm)
- 2 Cantilevered Work Surface 84W (2134mm)
- 1 Cantilevered Work Surface Corner 48W (1219mm)
- 2 Transaction Countertop, 48W (1219mm)
- 2 Transaction Countertop, 72W (1829mm)
- 2 Suspended Lateral File, 24W (610mm)
- 6 Shelf Storage/Display, 24W (610mm)
- 30 Shelf Storage/Display, 30W (762mm)
- 4 Shelf Storage/Display, 36W (914mm)
- 239 Shelf Storage/Display, 48W (1219mm)
- 2 Lockable Flipper Unit 24W (610mm)

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I			UTILITIES					
				R	A	F	A	H	1	2	3	4

- 4 Lockable Flipper Unit 36W (914mm)
- 5 Lockable Flipper Unit 48W (1219mm)
- 5 Tackboard 36W (914mm)
- 5 Tackboard 48W (1219mm)
- 14 Tool Bar
- 1 Equipment Rail
- 1 Cantilevered ADA Sink-Adaptable Work Surface with Integral Backsplash 24W (610mm)
- 1 Deep Shelf with Add-on 24W (610mm)
- 5 Deep Shelf with Add-on 30W (762mm)
- 39 Deep Shelf with Add-on 48W (1219mm)
- 2 Height-Adjustable Table 48W (1219mm)
- 2 Height-Adjustable Table 60W (1524mm)
- 4 Storage Frame
- 12 Drawer 3H (76mm)
- 6 Drawer 6H (152mm)
- 4 Drawer 9H (229mm)
- 4 Wire Shelf
- 1 Large Storage Container on Wheels
- 8 Caster, Swivel, Brake
- 8 Caster, Swivel
- 2 Wire Cart 5 Shelves 24D (610mm) x 36W (914mm) x 68H (1727mm)
- 2 Wire Cart 3 Shelves Push Handles 21D (533mm) x 36W (914mm) x 40H (1016mm)
- 3 Pedestal, Mobile
- 2 Pedestal, Stationary
- 4 Light 36W (914mm)
- 5 Light 48W (1219mm)
- 29 Paper Trays
- 5 Adjustable Keyboard Tray
- 1 ADA Sink and Faucet

*Connecting hardware required to complete the installation. [No other source(s) identified with this description/specification.
Electrical Requirements dependent on configuration.]

UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	
OF ISSUE:	IN:	85	668	240	-- lb	1:	120	1	1	HZ SWITCH: NO
EA	CM:	216	1697	610	-- kg	2:	--	--	--	DEPENDENT: YES

E0686	6530	Pharmacy Manuf & Prepack High Volume	C C C C --	D F -- -- -- --
-------	------	--------------------------------------	------------	-----------------

- E0686 MANUF & PREPACK
- 1 Eyewash
 - 2 Solid Panel, 53H (1346mm) x 24W (610mm)
 - 1 Solid Panel, 85H (2159mm) x 24W (610mm)
 - 4 Solid Powered Panel 85H (2159mm) x 48W (1219mm)
 - 9 Shelf Storage Display, 48W (1219mm)
 - 1 Lockable Flipper Unit 48W (1219mm)
 - 1 Tackboard 48W (1219mm)
 - 1 Tool Bar
 - 4 Vertical Hanger Strip
 - 5 Cantilevered Work Surface 48W (1219mm)
 - 1 Cantilevered Sink-Adaptable Work Surface with Integral Backsplash 48W (1219mm)
 - 1 Deep Shelf with Add-on 48W (1219mm)
 - 1 Height-Adjustable Table 48W (1219mm)
 - 8 Height-Adjustable Table 72W (1829mm)
 - 1 Height-Adjustable Table 60W (1524mm)
 - 1 Freestanding Sink-Adaptable Cabinet and Integral Backsplash 48W (1219mm)
 - 2 Overhead Cabinet with Doors 48W (1219mm)
 - 5 Drawer 3H (76mm)
 - 1 Double Bowl Sink and Faucet
 - 5 Light 48W (1219mm)

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
		1 Paper Tray 1 Adjustable Keyboard Tray 1 Storage Unit with Door 3 3-Shelf Unit, 24W (610mm) 2 Storage Cabinet 1 Drawer 4H (102mm) 3 Pullout Bottle Drawer *Connecting hardware required to complete the installation. [The database electrical requirement is only for the module's lights. Other electrical requirements dependent on configuration.]																
			UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 85 180 156 216	DEPTH 156 396	WEIGHT -- lb -- kg	VOLTS 1: 2:	PHASE 1 --	AMPS 1 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --				

E0687	6530	Pharmacy Dispensing & Storage High Volume	C	C	C	C	--	D	F	--	--	--	--	--
		E0687 DISPENS & STORAGE 2 Eyewash 4 Solid Panel, 39H (991mm) x 24W (610mm) 14 Solid Panel, 53H (1346mm) x 24W (610mm) 4 Solid Panel 67H (1702mm) x 18W (457mm) 2 Solid Panel 67H (1702mm) x 48W (1219mm) 25 Solid Panel, 85H (2159mm) x 18W (457mm) 1 Solid Powered Panel 85H (2159mm) x 24W (610mm) 10 Solid Panel 85H (2159) x 24W (610mm) 16 Solid Powered Panel 85H (2159mm) x 30W (762mm) 1 Solid Panel 85H (2159mm) x 30W (762mm) 1 Solid Panel 85H (2159mm) x 36W (914mm) 6 Solid Powered Panel 85H (2159mm) x 48W (1219mm) 13 Solid Panel 85H (2159mm) x 48W (1219mm) 2 Open Panel 67H (1702mm) x 24W (610mm) 2 Open Panel 67H (1702mm) x 30W (762mm) 2 Open Panel 67H (1702mm) x 48W (1219mm) 2 Cantilevered Work Surface 72W (1829mm) 2 Peninsula Work Surface 60W (1524mm) 70 Shelf Storage/Display, 30W (762mm) 123 Shelf Storage/Display, 48W (1219mm) 2 Lockable Flipper Unit 24W (610mm) 2 Lockable Flipper Unit 36W (914mm) 2 Lockable Flipper Unit 48W (1219mm) 2 Tackboard 24W (610mm) 6 Tackboard 30W (762mm) 4 Tackboard 48W (1219mm) 10 Tool Bar 4 Vertical Hanger Strip 3 Equipment Rail 6 Cantilevered Work Surface 48W (1219mm) 8 Cantilevered Work Surface 60W (1829mm) 1 Cantilevered Sink-Adaptable Work Surface with Integral Backsplash 48W (1219mm) 24 Deep Shelf with Add-on 48W (1219mm) 4 Height-Adjustable Table 48W (1219mm) 8 Height-Adjustable Table 72W (1829mm) 1 Height-Adjustable Table 60W (1524mm) 1 Freestanding Sink-Adaptable Cabinet and Integral Backsplash 48W (1219mm) 2 Overhead Cabinet with Doors 48W (1219mm) 3 Drawer 6H (152mm) 2 Cart Body Style A, Cord Wrap, Single Wide Door 2 Wire Shelf 16 Light 30W (762mm)												

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1	2

18 Paper Tray
 12 Adjustable Keyboard Tray
 2 Sink and Faucet
 4 Storage Unit Without Door
 36 3-Shelf Unit 48W (1219mm)
 16 3-Shelf Unit 24W (610mm)
 17 3-Shelf Unit 30W (762mm)
 3 3-shelf Unit 36W (914mm)
 12 Storage Cabinet
 4 Shelf, Fixed
 12 Drawer Lockable 4H (204mm)
 30 Pullout Bottle Drawer

*Connecting hardware required to complete the installation. [No other source(s) identified with this description/specification.

Electrical Requirements dependent on configuration.]

UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH CM:	WEIGHT -- lb	WEIGHT -- kg	VOLTS 1:	VOLTS 2:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:
EA	85	216	975	--	--	120	--	1	1	60	NO	--
										DEPENDENT:	YES	--

E0688	6530	Pharmacy Offsite Satellite High Volume	C C C C --	D F -- -- -- --
-------	------	--	------------	-----------------

E0688 OFFSITE SAT. PHARM.

2 Eyewash
 2 Solid Panel 47H (1194mm) x 18W (457mm)
 1 Solid Powered Panel 47H (1194mm) x 24W (610mm)
 5 Solid Panel 47H (1194mm) x 24W (610mm)
 2 Solid Powered Panel 47H (1194mm) x 36W (914mm)
 3 Solid Powered Panel 47H (1194mm) x 48W (1219mm)
 4 Solid Panel 53H (1346mm) x 18W (457mm)
 1 Solid Powered Panel 53H (1346mm) x 24W (610mm)
 18 Solid Panel 53H (1346mm) x 24W (610mm)
 4 Solid Panel 53H (1346mm) x 48W (1219mm)
 35 Solid Panel 85H (2159mm) x 18W (457mm)
 8 Solid Powered Panel 85H (2159mm) x 24W (610mm)
 2 Solid Panel 85H (2159mm) x 24W (610mm)
 5 Solid Powered Panel 85H (2159mm) x 30W (762mm)
 3 Solid Panel 85H (2159mm) x 30W (762mm)
 2 Solid Powered Panel 85H (2159mm) x 36W (914mm)
 2 Solid Panel 85H (2159mm) x 42W (1067mm)
 6 Solid Powered Panel 85H (2159mm) x 48W (1219mm)
 25 Solid Panel 85H (2159mm) x 48W (1219mm)
 1 Open Powered Panel 85H (2159mm) x 24W (610mm)
 1 Open Panel 85H (2159mm) x 30W (762mm)
 2 Open Powered Panel 85H (2159mm) x 36W (914mm)
 3 Open Powered Panel 85H (2159mm) x 48W (1219mm)
 5 Open Panel 85H (2159mm) x 48W (1219mm)
 16 Cantilevered Work Surface 48W (1219mm)
 8 Cantilevered Work Surface 72W (1829mm)
 2 Cantilevered Work Surface 84W (2134mm)
 1 Cantilevered Work Surface Corner 48W (1219mm)
 1 Peninsula Work Surface 60W (1524mm)
 4 Transaction Countertop 24W (610mm)
 2 Transaction Countertop, 48W (1219mm)
 2 Transaction Countertop, 72W (1829mm)
 2 Suspended Lateral File, 24W (610mm)
 18 Shelf Storage/Display, 24W (610mm)
 30 Shelf Storage/Display, 30W (762mm)
 4 Shelf Storage/Display, 36W (914mm)
 268 Shelf Storage/Display, 48W (1219mm)

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES														
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
		2 Lockable Flipper Unit 24W (610mm) 1 Lockable Flipper Unit 30W (762mm) 4 Lockable Flipper Unit 36W (914mm) 5 Lockable Flipper Unit 48W (1219mm) 5 Tackboard 36W (914mm) 8 Tackboard 48W (1219mm) 1 Tackboard 30W (762mm) 20 Tool Bar 6 Vertical Hanger Strip 2 Equipment Rail 1 Cantilevered Sink-Adaptable Work Surface with Integral Backsplash 48W (1219mm) 1 Cantilevered ADA Sink-Adaptable Work Surface with Integral Backsplash 24W (610mm) 1 Deep Shelf with Add-on 24W (610mm) 5 Deep Shelf with Add-on 30W (762mm) 41 Deep Shelf with Add-on 48W (1219mm) 4 Height-Adjustable Table 48W (1219mm) 5 Height-Adjustable Table 72W (1829mm) 2 Height-Adjustable Table 60W (1524mm) 1 Overhead Cabinet and Doors 48W (1219mm) 6 Storage Frame 14 Drawer 3H (76mm) 11 Drawer 6H (152mm) 6 Drawer 9H (229mm) 4 Wire Shelf 1 Large Storage Container on Wheels 8 Caster, Swivel, Brake 8 Caster, Swivel 2 Wire Cart 5 Shelves 24D (610mm) x 36W (914mm) x 68H (1727mm) 2 Wire Cart 3 Shelves Push Handle 21D (533mm) x 36W (914mm) x 40H (1016mm) 3 Pedestal, Mobile 2 Pedestal, Stationary 1 Light 30W (762mm) 4 Light 36W (914mm) 5 Light 48W (1219mm) 38 Paper Trays 23 Adjustable Keyboard Tray 1 Sink and Faucet 1 ADA Sink and Faucet 5 Storage Unit with Doors 9 3-Shelf Unit 24W (610mm) 15 3-Shelf Unit 48W (1219mm) 24 Storage Cabinet 22 Shelf, Fixed 25 Drawer 4H (102mm) 2 Drawer 8H (203mm) 35 Pullout Bottle Door *Connecting hardware required to complete the installation. [No other source(s) identified with this description/specification. Electrical Requirements dependent on configuration.]																		
			UNIT	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60								
			OF ISSUE:	IN:	85	600	624	-- lb	1:	120	1	1	HZ SWITCH:	NO	BTUs / HR:					
			EA	CM:	216	1524	1585	-- kg	2:	--	--	--	DEPENDENT:	YES	--					

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
			A R	N A	A F	V A	I H	1	2	3	4	5	6
E0689	6530	Pharmacy IV Admixture High Volume	C C C C --	D	F	--	--	--	--	--	--	--	--
		<p>E0689 UNIT_IV</p> <ul style="list-style-type: none"> 2 Eyewash 2 Solid Powered Panel 47H (1194mm) x 36W (914mm) 4 Solid Powered Panel 47H (1194mm) x 48W (1219mm) 8 Solid Panel 53H (1346mm) x 24W (610mm) 3 Solid Powered Panel 67H (1702mm) x 48W (1219mm) 16 Solid Panel 85H (2159mm) x 18W (457mm) 4 Solid Powered Panel 85H (2159mm) x 24W (610mm) 1 Solid Panel 85H (2159mm) x 24W (610mm) 2 Solid Powered Panel 85H (2159mm) x 48W (1219mm) 13 Solid Panel 85H (1346mm) x 48W (1219mm) 4 Open Panel 85H (1346mm) x 24W (610mm) 2 Open Panel 85H (1346mm) x 30W (762mm) 14 Cantilevered Work Surface 48W (1219mm) 2 Cantilevered Work Surface 72W (1829mm) 4 Cantilevered Work Surface Corner 48W (1219mm) 88 Shelf Storage/Display 48W (1219mm) 6 Lockable Flipper Unit 48W (1219mm) 2 Tackboard 36W (914mm) 3 Tackboard 48W (1219mm) 4 Tool Bar 4 Vertical Hanger Strip 1 Mobile Table 20W (508mm) x 20D (508mm) 2 Equipment rail 2 Cantilevered Work Surface 30W (762mm) 1 Cantilevered Sink-Adaptable Work Surface with Integral Backsplash 48W (1219mm) 15 Deep Shelf with Add-on 1 Height-Adjustable Table 48W (1219mm) 5 Height-Adjustable Table 60W (1524mm) 1 Cantilevered ADA Sink-Adaptable Work Surface with Integral Backsplash 24W (610mm) 13 Storage Frame 37 Drawer 3H (76mm) 23 Drawer 6H (152mm) 11 Drawer 9H (229mm) 5 Mobile Cart with Top Surface 20 Wire Shelf 5 Large Storage Container on Wheels 6 Cart Body Style A with Lock Bar 6 Lockable Drawer with Lockable Lid 64W (1626mm) 18 8-Bin Cassette 6H (152mm) 8 Caster, Swivel, Brake 8 Caster, Swivel 1 Wire Cart 5 Shelves 24D (610mm) x 36W (914mm) x 68W (1727mm) 1 Wire Cart 3 Shelves Push Handle 21D (533mm) x 36W (914mm) x 40W (1067mm) 4 Pedestal, Mobile 7 Light 48W (1219mm) 12 Paper Trays 8 Adjustable Keyboard Tray 1 Sink and Faucet 1 ADA Sink and Faucet 3 3-Shelf Unit 24W (610mm) 11 3-Shelf Unit 48W (1219mm) 2 5-Shelf Unit 30W (762mm) 2 5-Shelf Unit 48W (1219mm) 2 5-Shelf Unit, Corner 48W (1219mm) 1 9-Shelf Unit, Corner 48W (1219mm) 8 Storage Cabinet 											

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
		6 Shelf, Fixed 8 Drawer Lockable 4H (102mm) 15 Pullout Bottle Drawer *Connecting hardware required to complete the installation. [No other source(s) identified with this description/specification. Electrical Requirements dependent on configuration.]																
			UNIT OF ISSUE: EA	HEIGHT IN: 85 CM: 216	WIDTH 540 DEPTH 360 914	WEIGHT -- lb -- kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 1 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --							
E0703	6530	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D								C C C C --	-- -- -- -- --							
		Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" (610mm) or 30" (762mm) depth. This work surface includes: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H (76mm); 1 drawer, 6"H (152mm); 1 drawer, 9"H (229mm) and drawer organizer bins.																
			UNIT OF ISSUE: EA	HEIGHT IN: 38 CM: 97	WIDTH 48 DEPTH 24 61	WEIGHT 75 lb 34 kg	VOLTS 1: -- 2: --	PHASE -- --	AMPS -- --	HZ: -- HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --							
E0706	6530	Table, Process, Adj Height, 5 Drawer, 60"W x 24"D								C C C C --	-- -- -- -- --							
		Height adjustable table. The table is available in plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All surfaces will accept various storage components underneath. These tables are available in 24" (610mm) or 30" (762mm) depth. This work surface also includes: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H (76mm); 1 drawer, 6"H (152mm); 1 drawer, 9"H (229mm) and drawer organizer bins.																
			UNIT OF ISSUE: EA	HEIGHT IN: 38 CM: 97	WIDTH 60 DEPTH 24 61	WEIGHT 100 lb 46 kg	VOLTS 1: -- 2: --	PHASE -- --	AMPS -- --	HZ: -- HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --							
E0709	6530	Table, Process, Adj Height, Mbl, 10 Drwr, 60"Wx24"D								C C C C --	-- -- -- -- --							
		THIS TYPICAL INCLUDES: 1 Height Adjustable Table 4 Storage Frames 4 Drawers, 3"H (76mm) 4 Drawers, 6"H (152mm) 2 Drawers, 9"H (229mm) Drawer organizer bins																
			UNIT OF ISSUE: EA	HEIGHT IN: 38 CM: 97	WIDTH 60 DEPTH 24 61	WEIGHT 100 lb 46 kg	VOLTS 1: -- 2: --	PHASE -- --	AMPS -- --	HZ: -- HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --							
E0712	6530	Table, Process, Adj Height, 10 Drawer, 60"W x 24"D								C C C C --	-- -- -- -- --							
		THIS TYPICAL INCLUDES: 1 Height Adjustable Table 4 Storage Frames 4 Drawers, 3"H (76mm) 6 Drawers, 6"H (152mm) Drawer organizer bins																
			UNIT OF ISSUE: EA	HEIGHT IN: 38 CM: 97	WIDTH 60 DEPTH 24 61	WEIGHT 100 lb 46 kg	VOLTS 1: -- 2: --	PHASE -- --	AMPS -- --	HZ: -- HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
E0715	6530	Table, Process, Adj Height, 9 Drawer	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Height adjustable table approximate size 72" wide and 24" deep with approximately 9 drawers. The table top is available in plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" (610mm) or 30" (762mm) depth. This table also includes: 2 storage frames; 5 drawers, 3"H (76mm); 2 drawers, 6"H (152mm); 2 drawers, 9"H (229mm) and drawer organizer bins.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:								
EA		IN:	38	72	24	126 lb	1:	--	--	--	NO	--							
		CM:	97	183	61	58 kg	2:	--	--	--	NO	--							
E0718	6530	Table, Process, Adj Height, 15 Drawer, 72"W x 24"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
THIS TYPICAL INCLUDES: 1 Height Adjustable Table 6 Storage Frames 6 Drawers, 3"H (76mm) 9 Drawers, 9"H (229mm) Drawer organizer bins																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:								
EA		IN:	38	72	24	150 lb	1:	--	--	--	NO	--							
		CM:	97	183	61	69 kg	2:	--	--	--	NO	--							
E0721	6530	Table, Process, Adj Height, 20 Drawer, 72"W x 36"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
THIS TYPICAL INCLUDES: 1 Height Adjustable Table 8 Storage Frames 4 Drawers, 3"H (76mm) 12 Drawers, 6"H (152mm) 4 Drawers, 9"H (229mm) Drawer organizer bins																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:								
EA		IN:	38	72	36	150 lb	1:	--	--	--	NO	--							
		CM:	97	183	91	69 kg	2:	--	--	--	NO	--							
E0751	6530	Sink, Cantilevered, Wall Mtd, 24"W x 24"D	F	F	F	F	--	--	--	--	D	--	--	--	--	--	--	--	
Cantilevered sink unit module that can be hung from vertical hanging strips or lab modules. All cantilevered sink modules have an attached backsplash. There are no storage capabilities in this unit. All sink modules are available in 24" (610mm) or 30" (762mm) depths. The work surface tops on sink modules are Chem-surf laminate. The top of the sink unit is delivered as a solid laminate and the hole for the sink bowl is field cut. The sink bowl, strainer, tailpiece and faucet are provided. The sink can also be specified separately.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:								
EA		IN:	30	24	24	50 lb	1:	--	--	--	0	NO	--						
		CM:	76	61	61	23 kg	2:	--	--	--	NO	--							
E0754	6530	Sink, Cantilevered, Wall Mtd	F	F	F	F	--	--	--	--	D	--	--	--	--	--	--	--	
Cantilevered sink unit module, approx. 30"W and 24"D, that can be hung from vertical hanging strips or lab modules. All cantilevered sink modules have an attached backsplash. There are no storage capabilities in this unit. All sink modules are available in approximately 24" (610mm) or 30" (762mm) depths. The work surface tops on sink modules are Chem-surf laminate. The top of the sink unit is delivered as a solid laminate and the hole for the sink bowl is field cut. The sink bowl, strainer, tailpiece and faucet are provided. The sink can also be specified separately.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:								
EA		IN:	30	30	24	62 lb	1:	--	--	--	NO	--							
		CM:	76	76	61	29 kg	2:	--	--	--	NO	--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
E0766	6530	Sink, w/Cabinet, Free Standing, 24"W x 24"D	F	F	F	F	--	D	--	--	--	--	--	--	--	--	--	--
Cabinet mounted sink unit which does not need to hang from a panel or module but can be used up against the face of an architectural wall. The freestanding sink module has an integral backsplash. The lower part of the cabinet can be used for storage. All sink modules are available in 24" (610mm) or 30" (762mm) depths. The work surface top on sink modules are Chem-Surf laminate. The cabinet top is delivered as a solid piece and the hole for the sink bowl is field cut. The sink can also be specified separately. The sink bowl, strainer, tailpiece, and faucet are provided.																		
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			IN:	50	24	24	125 lb	1:	--	--	--							
			CM:	127	61	61	57 kg	2:	--	--	--							
E0769	6530	Sink, w/Cabinet, Free Standing, 30"W x 24"D	F	F	F	F	--	D	--	--	--	--	--	--	--	--	--	--
Cabinet mounted sink unit which does not need to hang from a panel or module but can be used up against the face of an architectural wall. The freestanding sink module has an integral backsplash. The lower part of the cabinet can be used for storage. All sink modules are available in 24" (610mm) or 30" (762mm) depths. The work surface top on sink modules are Chem-Surf laminate. The cabinet top is delivered as a solid piece and the hole for the sink bowl is field cut. The sink can also be specified separately. The sink bowl, strainer, tailpiece, and faucet are provided.																		
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			IN:	50	30	24	150 lb	1:	--	--	--							
			CM:	127	76	61	69 kg	2:	--	--	--							
E0772	6530	Sink, w/Cabinet, Free Standing, 48"W x 24"D	F	F	F	F	--	D	--	--	--	--	--	--	--	--	--	--
Cabinet mounted sink unit which does not need to hang from a panel or module but can be used up against the face of an architectural wall. The freestanding sink module has an integral backsplash. The lower part of the cabinet can be used for storage. All sink modules are available in 24" (610mm) or 30" (762mm) depths. The work surface top on sink modules are Chem-Surf laminate. The cabinet top is delivered as a solid piece and the hole for the sink bowl is field cut. The sink can also be specified separately. The sink bowl, strainer, tailpiece, and faucet are provided.																		
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			IN:	50	48	24	225 lb	1:	--	--	--							
			CM:	127	122	61	103 kg	2:	--	--	--							
E0775	6530	Sink, w/Cabinet, Free Standing, 60"W x 24"D	F	F	F	F	--	D	--	--	--	--	--	--	--	--	--	--
Sink unit consisting of: 1 Freestanding, Sink Adaptable Cabinet w/Integral Backsplash 1 Sink & Faucet																		
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			IN:	50	60	24	250 lb	1:	--	--	--							
			CM:	127	152	61	114 kg	2:	--	--	--							
E0803	6530	Module, Storage, File/Cabinet, Wall Mtd, 30"x16"	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
This unit has 2 vertical hanging strips, 2 lockable flipper units and 3 hanging file drawers with shelf dividers.																		
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			IN:	80	30	16	100 lb	1:	--	--	--							
			CM:	203	76	41	46 kg	2:	--	--	--							
E0806	6530	Module, Storage, File/Cabinet, Wall Mtd, 48"x16"	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 2 Lockable Flipper Units 3 Hanging File Drawers Shelf Dividers																		
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			IN:	80	48	16	150 lb	1:	--	--	--							
			CM:	203	122	41	69 kg	2:	--	--	--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
E0809	6530	Module, Storage, File/Cabinet, Free Std, 48"x16"	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>This JSN will provide a whole storage area typical to quickly plan areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 1 solid panel, 85"H (2159mm) x 48"W (1219mm); 2 solid panels, 47"H (1194mm) x 24"W (610mm); 2 panel connectors, 2-way corner, 85"H (2159mm); 2 finished end hardware kits; 3 lockable flipper units, 48"W (1219mm) and 2 hanging file drawers, 48"W (1219mm).</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	85	55	22	150 lb	1:	--	--	--	NO	--							
			216	140	56	69 kg	2:	--	--	--	NO	--							
E0821	6530	Module, Storage, Files/Shelves, Wall Mtd	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Storage module, approx 30" x 16". THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 3 Shelves 2 Hanging File Drawers Shelf Dividers</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	80	30	16	75 lb	1:	--	--	--	NO	--							
			203	76	41	34 kg	2:	--	--	--	NO	--							
E0824	6530	Module, Storage, Files/Shelves, Wall Mtd, 48"x16"	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 3 Shelves 2 Hanging File Drawers Shelf Dividers</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	80	48	16	125 lb	1:	--	--	--	0	NO	--						
			203	122	41	57 kg	2:	--	--	--	NO	--							
E0836	6530	Module, Storage, Shelves, Wall Mtd, 72"W x 16"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>This JSN includes: 3 Vertical Hanger Strips 6 Extra Deep Shelves for Storage w/Open Space Below for Free Standing Equipment.</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	88	72	16	50 lb	1:	--	--	--	NO	--							
			224	183	41	23 kg	2:	--	--	--	NO	--							
E0839	6530	Module, Storage, Shelves, Wall Mtd, 96"W x 16"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>This JSN includes: 3 Vertical Hanger Strips 6 Extra Deep Shelves for Storage w/Open Space Below for Free Standing Equipment.</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	88	96	16	100 lb	1:	--	--	--	NO	--							
			224	244	41	46 kg	2:	--	--	--	NO	--							
E0851	6530	Display, Tackboard & Markerboard, Wall Mtd	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Tack/Marker-board approx. 48"W. THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Tack board 1 Marker Board</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	80	48	6	35 lb	1:	--	--	--	0	NO	--						
			203	122	15	16 kg	2:	--	--	--	NO	--							

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
E0903	6530	Locker, Supply, w/Shelves, Wall Mtd, 23"W x 20"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 E1500 Wall Mounting Rail is required 1 Supply Locker 1 Drawer, 9"H (229mm) 4 Tray/Shelves <p>Consider the need for an E0921 to transport the locker from place to place. [This locker requires JSN E0921 if needed to transport it from site to site.]</p>															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:		
EA		IN: 80	23	20	75 lb	1:	--	--	--	NO		--			
		CM: 203	58	51	34 kg	2:	--	--	--	NO		--			
E0906	6530	Locker, Supply, General, Wall Mtd, 23"W x 20"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H (76mm) 3 Drawers, 6"H (152mm) 2 Drawers, 9"H (229mm) 1 Tray/Shelf Divider Drawer Organizer Bins <p>Consider the need for an E0921 to transport the locker from place to place.</p>															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:		
EA		IN: 78	23	20	100 lb	1:	--	--	--	NO		--			
		CM: 198	58	51	46 kg	2:	--	--	--	NO		--			
E0909	6530	Locker, Supply, Cassette, Wall Mtd, 23"W x 20"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 1 Tray/Shelf 7 8-Bin Cassette Assemblies 1 Cassette Lid 1 Locked Drawer with Locked Lid [This locker requires JSN E0921 to transport it from site to site.] 															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:		
EA		IN: 76	23	20	150 lb	1:	--	--	--	NO		--			
		CM: 193	58	51	69 kg	2:	--	--	--	NO		--			
E0912	6530	Locker, Supply, Med Surg, Wall Mtd	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
<p>Medical/Surgical Supply locker, Wall Mounted, Approx 23"W x20"D. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H (76mm) 2 Drawers, 6"H (152mm) 2 Tray/Shelf Dividers Drawer Organizer Bins <p>Consider the need for an E0921 to transport the locker from place to place.</p>															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:		
EA		IN: 78	23	20	126 lb	1:	--	--	--	0		NO			
		CM: 198	58	51	58 kg	2:	--	--	--	NO		--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
E0915	6530	Locker, Supply, Medication, Wall Mtd, 23"W x 20"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 E1500 Wall Mounting Rail is required 1 Locked Storage Container 2 Tray/Shelves 1 Locker Drawer with Locked Lid, 6"H (152mm) 5 Drawers, 3"H (76mm) 3 Drawers, 6"H (152mm) 2 Tray/Shelves Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place. [This locker mounts on an installed wall rail and requires JSN E0921 to transport it from site to site.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			78	198	23	58	20	51	125 lb	57 kg	1: --	2: --	--	--	--	--	--	--
E0918	6530	Locker, Supply, Endoscopy, Wall Mtd, 24"W x 14"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 Scope Storage Cabinet 1 Bracket, Endoscope 1 Bracket, Distal Tube 1 Cabinet Drip Pan. E1500 Wall Mounting Rail is required Consider the need for an E0921 to transport the locker from place to place. [This locker mounts on an installed wall rail.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			92	234	24	61	14	36	75 lb	34 kg	1: --	2: --	--	--	--	--	--	--
E0921	6530	Transporter, Locker, Supply, 27"W x 25"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES 1 transporter for large storage containers. The unit is used to move supply lockers.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			42	107	27	69	25	64	50 lb	23 kg	1: --	2: --	--	--	--	--	--	--
E0927	6530	Locker, Supply, Wire Shelves, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Supply Locker w/ wire shelves, approximately 29"W x 20"D. THIS TYPICAL INCLUDES: 1 Mobile Supply Locker 1 Drawer, 6"H (152mm) 5 Wire Shelves																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			72	183	29	74	20	51	101 lb	46 kg	1: --	2: --	--	--	--	--	--	--
E0930	6530	Locker, Supply, 6 Drawers, Mobile, 29"W x 20"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 Mobile Supply Locker 2 Tray/Shelf 3 Drawers, 3"H (76mm) 3 Drawers, 6"H (152mm) Drawer Organizer Bins																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			73	185	29	74	20	51	101 lb	46 kg	1: --	2: --	--	--	--	--	--	--

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES									
				R	A	F	A	H		1	2	3	4	5	6				
E0933	6530	Locker, Supply, Shelf & Drawer, Mbl, 29"W x 20"D	C C C C --																
THIS TYPICAL INCLUDES: 1 Mobile Supply Locker 3 Drawers, 6"H (152mm) 5 Tray/Shelves 5 Tray/Shelf Dividers Drawer Organizer Bins																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	73	29	20	125 lb	1:	--	--	--	NO		--						
		CM:	185	74	51	57 kg	2:	--	--	--	NO		--						
E0936	6530	Cart, Machine, Mobile, 36"H x 32"W x 22"D	C C C C --																
THIS TYPICAL INCLUDES: 1 cart body, style-A narrow, w/raised edge top and an access hole in the back panel; 1 accessory rail, side; 1 accessory rail, back; 1 accessory rail, above cart; 1 electrical box, 4 outlet; 2 cord wraps; 1 rail hung tray; 1 flip-up shelf; 1 wire shelf; 2 drawers, 3"H (76mm); 1 drawer, 6"H (152mm) and drawer organizer bins.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	62	46	22	75 lb	1:	--	--	--	NO		--						
		CM:	157	117	56	34 kg	2:	--	--	--	NO		--						
E0939	6530	Cart, Anesthesia, Mobile	C C C C --																
Anesthesia Cart approximately 64"H x 43"W x 22"D. THIS TYPICAL INCLUDES: 1 cart body, style-A narrow, w/raised edge top and right side lock bar; 2 accessory rails, above cart; 2 accessory rails; side and supply baskets; 1 rail hung tray; 1 sharps container holder; 1 wastebasket and holder; 4 drawers, 3"H (76mm); 2 drawers, 6"H (152mm), rail hung storage bins and drawer organizer bins. [See JSN M8800, Cart Anesthesia for alternative sources.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	64	43	22	101 lb	1:	--	--	--	NO		--						
		CM:	163	109	56	46 kg	2:	--	--	--	NO		--						
E0942	6530	Cart, Cast, Mobile, 36"H x 46"W x 22"D	C C C C --																
THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Accessory Rail, Side 1 Wastebasket and Holder 1 Flip-up Shelf 2 Drawers, 3"H (76mm) 1 Drawer, 6"H (152mm) Drawer Organizer Bins																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	36	46	22	75 lb	1:	--	--	--	NO		--						
		CM:	91	117	56	34 kg	2:	--	--	--	NO		--						
E0945	6530	Cart, Computer, Mobile, 48"H x 54"W x 22"D	C C C C --																
THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket and Holder 1 Chart Holder 2 Drawers, 3"H (76mm) 2 Drawers, 6"H (152mm) Drawer Organizer Bins																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	48	54	22	100 lb	1:	--	--	--	NO		--						
		CM:	122	137	56	46 kg	2:	--	--	--	NO		--						

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I R A F A H						UTILITIES					
				1	2	3	4	5	6	1	2	3	4	5	6
E0948	6530	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 CRT CART, SERIES 20, w/ RAISED EDGE TOP AND BREAKAWAY LOCK BAR W/TABS 2 DRAWERS, SERIES 20 CART, 3"H 2 DRAWERS, SERIES 20 CART, 6"H 1 ACCESSORY RAIL, SIDE 2 Chest Tube Rack, Side Drawer Organizer Bins															
UNIT OF ISSUE: EA		HEIGHT IN: CM:	WIDTH 42 107	DEPTH 32 81	DEPTH 22 56	WEIGHT 75 lb 34 kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	HZ: --	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --		
E0951	6530	Cart, Proctology Treatment, Mobile	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Proctology Treatment Cart, approximately 68"Hx50"Wx22"D. THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 1 Accessory Rail, Above Cart 2 Accessory Rails, Side 1 Wastebasket and Holder Supply Baskets 1 Flip-up Shelf 2 Drawers, 3"H (76mm) 4 Drawers, 6"H (152mm) Drawer Organizer Bins.															
UNIT OF ISSUE: EA		HEIGHT IN: CM:	WIDTH 68 173	DEPTH 50 127	DEPTH 22 56	WEIGHT 126 lb 58 kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	HZ: --	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --		
E0954	6530	Cart, Emergency, Mobile, 66"H x 52"W x 22"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 Cart body, style-A narrow, w/raised edge top and breakaway lock bar w/tabs 2 Accessory rails, side 1 Accessory rail, back 1 Defibrillator tray; 1 IV pole 1 Flip-up shelf 1 Wastebasket and holder 1 Oxygen tank holder 1 Cardiac board and hanger 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H (76mm) 3 Drawer, 6"H (152mm) Drawer organizer bins. [This equipment requires emergency power to continually recharge its battery.]															
UNIT OF ISSUE: EA		HEIGHT IN: CM:	WIDTH 66 168	DEPTH 52 132	DEPTH 22 56	WEIGHT 125 lb 57 kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	HZ: --	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --		
E0957	6530	Cart, Medication, Mobile, 68"H x 54"W x 22"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES: 1 cart body, style-A narrow, w/raised edge top and right side lock bar; 3 accessory rails, side; 1 wastebasket and holder; 1 sharps container holder; 1 flip-up shelf; 1 flashlight holder; 1 wall lock; 2 drawers, 3"H (76mm); 1 locked drawer, 6"H (152mm) w/locked lid; 3 8-bin cassette assembly and drawer organizer bins.															
UNIT OF ISSUE: EA		HEIGHT IN: CM:	WIDTH 68 173	DEPTH 54 137	DEPTH 22 56	WEIGHT 126 lb 57 kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	HZ: --	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --		

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
E0960	6530	Cart, Lockable, Mobile, 42"H x 49"W x 22"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES:															
1 Cart Body, Style-A Wide, w/Full Spine and Breakaway Lock Bars w/Tabs															
3 Drawers, 3"H (76mm)															
4 Drawers, 6"H (152mm)															
1 Drawer, 6"H (152mm) w/lockable lid															
1 Drawer, 9"H (229mm)															
2 8-Bin Cassette Assemblies															
Drawer Organizer Bins															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
EA		CM:	42	49	22	152 lb	1:	--	--	--	NO	NO	--		
			107	124	56	69 kg	2:	--	--	--	NO	NO	--		
E0963	6530	Cart, General Storage, Mobile	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Mobile General Storage Cart, approximately 72"H x 23"W x 22"D. THIS TYPICAL INCLUDES:															
1 Locker Storage Container on Wheels, w/Solid Door															
3 Tray/Shelves															
2 Drawers, 3"H (76mm)															
4 Drawers, 6"H (152mm)															
Drawer Organizer Bins															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
EA		CM:	72	23	22	126 lb	1:	--	--	--	NO	NO	--		
			183	58	56	58 kg	2:	--	--	--	NO	NO	--		
E0966	6530	Cart, Storage, Dbl Width, Mbl, 74"H x 51"W x 22"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES:															
1 Cart Body, Style-A Wide, w/Full Spine															
6 Tray Shelves															
8 Drawers, 3"H (76mm)															
4 Drawers, 6"H (152mm)															
1 Cart Cover															
Drawer Organizer Bins															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
EA		CM:	74	51	22	175 lb	1:	--	--	--	NO	NO	--		
			188	130	56	80 kg	2:	--	--	--	NO	NO	--		
E0969	6530	Cart, Bulk Supply, Mobile, 74"H x 51"W x 22"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES:															
1 Cart Body, Style-A Wide, w/o Spine															
4 Wire Shelves															
1 Cart Cover															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
EA		CM:	74	51	22	126 lb	1:	--	--	--	NO	NO	--		
			188	130	56	57 kg	2:	--	--	--	NO	NO	--		
E0972	6530	Cart, Endoscopy, Mobile, 78"H x 62"W x 24"D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
THIS TYPICAL INCLUDES:															
1 Wire Cart															
3 Laminated Shelves															
1 Keyboard Tray															
1 Storage Frame															
1 Drawer, 3"H (76mm)															
1 Drawer, 6"H (152mm)															
2 Flip-up Shelves															
1 Supply Basket															
1 Cord Wrap															
1 Outlet Strip															

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:							
			EA	78	62	24	100 lb	1: --	--	--	--	NO	--						
				CM:				2:											
			EA	198	157	61	46 kg	2: --	--	--	--	NO	--						
E0975	6530	Cart, Wire, Mobile											C	C	C	C	--	--	--
			Wire Cart with Wire Shelves approximately 60"H x 42"W x 24"D. THIS TYPICAL INCLUDES: 1 Wire Cart 3 Wire Shelves 1 Stainless Steel Shelf 1 Wire Side/Back Panels [See JSN M2100, Cart Shelving, Storage, Mobile, for alternative sources.]																
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:							
			EA	60	42	24	51 lb	1: --	--	--	--	NO	--						
				CM:				2:											
			EA	152	107	61	24 kg	2: --	--	--	--	NO	--						
E0978	6530	Cart, Wire, Mobile, 72"H x 42"W x 24"D											C	C	C	C	--	--	--
			THIS TYPICAL INCLUDES: 1 Wire Cart 4 Wire Shelves with Fences and Dividers 4 Vertical Back/Side Panels 1 Cart Cover Label Clips																
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:							
			EA	72	42	24	75 lb	1: --	--	--	--	NO	--						
				CM:				2:											
			EA	183	107	61	34 kg	2: --	--	--	--	NO	--						
E0981	6530	Cart, Wire, Mobile, 61"W x 48"H x 24"D											C	C	C	C	--	--	--
			THIS TYPICAL INCLUDES: 1 Wire Cart 2 Wire Shelves 5 Vertical Back/Side Panels 1 Storage Frame 1 Drawer, 3"H (76mm) 2 Drawers, 6"H (152mm) 1 Drawer Cover Drawer Organizer Bins.																
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:							
			EA	48	61	24	50 lb	1: --	--	--	--	NO	--						
				CM:				2:											
			EA	122	155	61	23 kg	2: --	--	--	--	NO	--						
E0984	6530	Cart, Wire, Mobile, 72"H x 61"W x 24"D											C	C	C	C	--	--	--
			THIS TYPICAL INCLUDES: 1 Wire Cart 3 Wire Shelves with Fences and Dividers 5 Vertical Back/Side Panels 1 Storage Frame 1 Drawer, 3"H (76mm) 2 Drawers, 6"H (152mm) 1 Drawer Cover 1 Cart Cover Label Clips Drawer Organizer Bins																
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:							
			EA	72	61	24	100 lb	1: --	--	--	--	NO	--						
				CM:				2:											
			EA	183	155	61	46 kg	2: --	--	--	--	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES							
				R	A	F	A	H		1	2	3	4	5	6		
E0987	6530	Cart, Closed, w/Totes, Mobile, 72"H x 48"W x 22"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	
THIS TYPICAL INCLUDES: 1 Cart Body, Style A-Wide, w/Half Spine 3 Drawer, 3" H (76mm) 5 Drawer, 6" H (152mm) 1 Drawer, 9" H (229mm) 3 Wire Shelf w/Dividers 1 Cart door, Solid Drawer Organizer Bins																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		IN:	72	48	22	130 lb	1:	--	--	0	NO	--					
		CM:	183	122	56	59 kg	2:	--	--	NO	NO	--					
E0990	6530	Cart, Closed, w/Shelves, Mobile, 72"Hx48"Wx22"D	C	C	C	C	--	--	--	--	--	--	--	--	--	--	
THIS TYPICAL INCLUDES: 1 Cart body, Style A-Wide, w/o Spine 4 Wire Shelves w/Dividers 1 Cart Door, Solid																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		IN:	72	48	22	125 lb	1:	--	--	0	NO	--					
		CM:	183	122	56	57 kg	2:	--	--	NO	NO	--					
E1500	7310	Rail, MOD, W/MNTD, HX144XD	C	C	C	F	--	--	--	--	--	--	--	--	--	--	
Wall mounted rail used for hanging (mounting) lockers, shelves drawers on a wall. [The Herman Miller Standard Wall Rail comes in 12 foot sections at \$191 a section. This JSN is no longer listed in Herman Miller's DoD Joint Schedule Numbers (JSNs) document of typicals, budget pricing and elevations, however, the item is still available.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		IN:	3	144	2	-- lb	1:	--	--	0	NO	--					
		CM:	8	366	5	-- kg	2:	--	--	NO	NO	--					
F0005	9925	Altar	C	C	C	C	--	--	--	--	--	--	--	--	--	--	
Altar. The unit is constructed of wood and used in churches and chapels for worship services.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		IN:	40	84	36	275 lb	1:	--	--	0	NO	--					
		CM:	102	213	91	125 kg	2:	--	--	NO	NO	--					
F0010	9925	Ark w/External Light	C	C	C	C	--	--	--	--	--	--	--	--	--	--	
The Ark is a receptacle or cabinet containing the Torah Scrolls in the synagogue. Its size, configuration and ornateness is dependent on the decor of the synagogue and if the Ark is to be built-in or portable. The light is for accent and varies with the degree of light in the room. [Unit price ranges from \$250.00 To \$ 6000.00 depending on material used and ornateness. Many facilities and synagogues will have local craftsmen design and build an Ark that compliments the decor of the room or building. Wooden Arks that are custom made will start at about \$250.00.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		IN:	--	--	--	-- lb	1:	--	--	0	NO	--					
		CM:	--	--	--	-- kg	2:	--	--	NO	NO	--					
F0015	9925	Chair, Chapel, w/ Kneeler	C	C	C	C	--	--	--	--	--	--	--	--	--	--	
The chair is made of sturdy wood construction. It is available with a kneeler and with ganging bookrack or ganging devices that permit all chairs in a row to be connected. This unit is used in churches and chapels for seating. Optional upholstery available. [Database pricing includes kneeler, ganging device and upholstery. Model 2 also includes a side or rear mounted book rack in their price.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		IN:	32	21	24	25 lb	1:	--	--	0	NO	--					
		CM:	81	53	61	12 kg	2:	--	--	NO	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
F0020	9925	Pew, Chapel w/Fold Up Kneeler	A A A A --	--	--	--	--	--	--	--	--	--	--
Chapel pew with fold up kneeler. This unit is constructed of solid hard wood and upholstered fabric. This unit is used in churches and chapels for seating. Unit dimensions are fabrication users specification. [Prices are based on pews 6 foot in length. Two ends are required per pew.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA	CM:	IN: 34	72	21	180 lb	1: --	--	--	0	NO	--		
		CM: 86	183	53	82 kg	2: --	--	--	DEPENDENT:	NO	--		
F0025	9925	Pulpit, Chapel	C C C C --	--	--	--	--	--	--	--	--	--	--
Chapel pulpit. The unit is constructed of solid hard wood. This unit is used in churches and chapels for worship services.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA	CM:	IN: 53	41	41	160 lb	1: --	--	--	0	NO	--		
		CM: 135	104	104	73 kg	2: --	--	--	DEPENDENT:	NO	--		
F0035	9925	Cross, Chapel	C C C C --	--	--	--	--	--	--	--	--	--	--
Chapel cross, made from high polished brass. For use in a chapel, church or place of worship. Wall mounted.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA	CM:	IN: 36	19	2	15 lb	1: --	--	--	0	NO	--		
		CM: 91	48	5	7 kg	2: --	--	--	DEPENDENT:	NO	--		
F0040	9925	Crucifix, Chapel	C C C C --	--	--	--	--	--	--	--	--	--	--
Crucifix, wall mounted, for use in a chapel or place of worship.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA	CM:	IN: 20	10	3	4 lb	1: --	--	--	0	NO	--		
		CM: 51	25	8	2 kg	2: --	--	--	DEPENDENT:	NO	--		
F0045	9925	Font, Baptismal	C C C C --	--	--	--	--	--	--	--	--	--	--
Baptismal font. This unit is constructed of wood with approximately a 9 inch stainless steel bowl. The receptacle is for holy water and/or type of fountain.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA	CM:	IN: 39	30	32	100 lb	1: --	--	--	0	NO	--		
		CM: 99	76	81	46 kg	2: --	--	--	DEPENDENT:	NO	--		
F0050	9925	Organ, Chapel	C C C C --	--	A	--	--	--	--	--	--	--	--
Shall be an organ designed for use in a church or chapel setting. It shall consist of 2 sets of manual keys for hand playing and a set of pedal keys. [Model 2 includes the bench and external speakers for 4 channels of amplification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA	CM:	IN: 55	58	41	475 lb	1: 120	1	9	60	NO	--		
		CM: 140	147	104	216 kg	2: --	--	--	DEPENDENT:	NO	--		
F0055	9925	Tabernacle, Chapel	C C C C --	--	--	--	--	--	--	--	--	--	--
Chapel Tabernacle, used in a church or place of worship, to hold the consecrated elements of the Eucharist.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA	CM:	IN: 8	9	9	5 lb	1: --	--	--	0	NO	--		
		CM: 20	23	23	3 kg	2: --	--	--	DEPENDENT:	NO	--		
F0060	9925	Table, Sacrament	C C C C --	--	--	--	--	--	--	--	--	--	--
This unit is made of sturdy wood construction. Used in a chapel or church and serves as a center of worship or ritual.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA	CM:	IN: 39	60	40	225 lb	1: --	--	--	0	NO	--		
		CM: 99	152	102	103 kg	2: --	--	--	DEPENDENT:	NO	--		

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES										
				A	N	A	V	I	1	2	3	4	5	6
				R	A	F	A	H						
F0065	9925	Set, Statue, Chapel	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Chapel statue set. This set is available in fiberglass or wood. Generally used in catholic services. It includes the holy family, mother and child and St. Joseph. [Database price is based on wood carved statues.]														
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		CM:	48	--	--	30 lb	1:	--	--	--	0		NO	
			122	--	--	14 kg	2:	--	--	--	NO		--	
F0070	9925	Set, Stations Of The Cross	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Stations of the cross set. This unit is a series of fourteen images or pictures in a church that represent the stages of Christ's passion. The figures are approximately 20 inch and overall size is approximately 26" x 13". Available in either hand carved linden wood, fiberglass or cast bronze. [Price difference is due to material make-up. Low end is fiberglass while the high end is carved linden wood. Model 1 is fiberglass with a size of 8" H x 6" W.]														
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
ST		CM:	19	13	2	4 lb	1:	--	--	--	0		NO	
			48	33	5	2 kg	2:	--	--	--	NO		--	
F0075	9925	Holder, Candle, Altar	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Used in a church or chapel to hold the candles on the altar during religious services. Made from either brass or bronze. Specify enamel color where indicated.														
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		CM:	7	6	6	2 lb	1:	--	--	--	0		NO	
			18	15	15	1 kg	2:	--	--	--	NO		--	
F0080	9925	Star Of David, Chapel	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Shall be a figure of the Star-of-David. It may be on a stand and made of metal or wood. It is designed for use in a interdenominational chapel. [Prices are dependent on material used (example: silver, brass or stainless steel). Only known source (s) found with this description.]														
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		CM:	31	27	4	10 lb	1:	--	--	--	--		NO	
			79	69	10	5 kg	2:	--	--	--	NO		--	
F0085	9925	Chair, Chancel, Chapel	C C C C --	--	--	--	--	--	--	--	--	--	--	--
These chairs are available in different styles and wood finishes. Used in churches and chapels as seating for the clergy and choir.														
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		CM:	50	30	23	80 lb	1:	--	--	--	0		NO	
			127	76	58	37 kg	2:	--	--	--	NO		--	
F0090	9925	Piano, Upright w/Bench	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Upright piano, 45" high x 58" wide x 25" deep with full eighty-eight (88) keyboard and bench. Used in chapel and patient day room(s).														
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		CM:	46	59	25	450 lb	1:	--	--	--	0		NO	
			117	150	64	205 kg	2:	--	--	--	NO		--	
F0095	9925	Font, Holy Water	C C C C --	--	--	--	--	--	--	--	--	--	--	--
This unit is either a floor standing unit made of sturdy wood construction, or a wall mounted unit, made from bronze. Bowls are approximately 6 3/4" diameter. This receptacle is for use in a chapel or church, to hold holy water. [Model 3 is a wall mounted font.]														
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		CM:	34	15	15	18 lb	1:	--	--	--	--		NO	
			86	38	38	9 kg	2:	--	--	--	NO		--	

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
F0096	9925	Wardrobe, Vestment, Built In	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Vestment wardrobe. This unit must be custom designed to conform to built-in requirements. Surfaced inside and out with high-pressure plastic laminates. [Prices are estimates only as they will vary based on design requirements. Models and prices shown are for a single door vestment wardrobe.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	84	36	30	225 lb	1:	--	--	--	NO		--					
		CM:	213	91	76	103 kg	2:	--	--	--	NO		--					
F0097	9925	Screen, Confessional, Portable	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
This portable confessional screen is used in churches, chapels and places of worship, as a division between confessionals for privacy. Screens are available in many different stain finishes and fabrics. Please specify when ordering. [Many distributors found for this item, but there appears to be only one manufacturer. Model 2 includes a kneeler and has dimensions of 32" W x 19" D x 66" H and weighs 90 lbs.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	66	32	3	65 lb	1:	--	--	--	NO		--					
		CM:	168	81	8	30 kg	2:	--	--	--	NO		--					
F0100	7110	Bin, Mail Sorting, Table Mounted	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Table mounted mail sorting bin with sufficient adjustable dividers to accommodate all standard size papers, and computer reports. Typical number of compartments for bin is forty eight (48). [Does not include the table.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	50	60	14	166 lb	1:	--	--	--	NO		--					
		CM:	127	152	36	76 kg	2:	--	--	--	NO		--					
F0102	6530	Cabinet, Distribution, Mail	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Mail distribution cabinet. Horizontal style distribution boxes. Unit consists of adjustable horizontal dividers and/or adjustable shelves. Unit can be customized to fit the client needs. Used for mail distribution. [Model 1 has 24 mail slots. The other two models have 36 slots. Many other sizes and models available.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	39	59	13	96 lb	1:	--	--	--	NO		--					
		CM:	99	150	33	44 kg	2:	--	--	--	NO		--					
F0110	7110	Bookcase, 3 Shelf	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Freestanding open metal shelf book case, approximately 60" high X 36" wide X 18" deep with three (3) adjustable shelves and four (4) non-marking floor glides.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	59	36	14	77 lb	1:	--	--	--	NO		--					
		CM:	150	91	36	35 kg	2:	--	--	--	NO		--					
F0115	7110	Bookcase, Open, 5 Shelf	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Freestanding open shelf bookcase, approximately 82" high X 37" wide X 18" deep with 5 (five) adjustable shelves. Unit can be separate or part of a system with available add-on shelving.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	84	37	16	154 lb	1:	--	--	--	NO		--					
		CM:	213	94	41	70 kg	2:	--	--	--	NO		--					
F0120	7110	Bookcase, Executive, 3 Shelf, Wood	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Freestanding open shelf woodgrain bookcase, approximately 48" high X 36" wide X 13" deep with three (3) adjustable shelves and four (4) non-marking floor glides.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	48	36	13	122 lb	1:	--	--	--	NO		--					
		CM:	122	91	33	56 kg	2:	--	--	--	NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
F0130	7195	Bookstack, Single	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
<p>Freestanding closed base single open faced book stack, approximately 84" H X 36" W X 13" D with six (6) or seven (7) adjustable shelves and one base shelf. Single-faced units should be transverse-brace secured, or wall, or floor anchored for stability.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	84	36	13	102 lb	1:	--	--	0	NO	--						
			213	91	33	47 kg	2:	--	--	NO	NO	--						
F0190	7110	Chair, Auditorium, With Tablet Arm	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
<p>Tablet arm auditorium chair. Chair consists of wood or upholstered arm rest with Dexlon plastic rear panel and self-rise molded foam over upholstered spring seat. It includes a folding writing surface that stores at the side of the chair. Unit is constructed with 3/16" steel. To be used in auditoriums during conferences or lectures.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	33	24	29	65 lb	1:	--	--	--	NO	--						
			84	61	74	30 kg	2:	--	--	NO	NO	--						
F0200	7110	Chair, Arm Writing	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Standard leg chair with 24" x 18" writing tablet. Book basket connected to underside of chair. Minimum distance of seat-to-floor is 17".</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	32	24	18	48 lb	1:	--	--	0	NO	--						
			81	61	46	22 kg	2:	--	--	NO	NO	--						
F0205	7110	Chair, Side With Arms	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	36	23	27	45 lb	1:	--	--	0	NO	--						
			91	58	69	21 kg	2:	--	--	NO	NO	--						
F0210	7110-01-188-5296	Chair, Side, Without Arms	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	36	21	22	30 lb	1:	--	--	0	NO	--						
			91	53	56	14 kg	2:	--	--	NO	NO	--						
F0215	7100	Chair, Child's	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Armless stacking chair scaled for use by children. Lightweight and available with a choice of different seat heights. [All models come in various seat heights.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	14	14	12	7 lb	1:	--	--	0	NO	--						
			36	36	30	4 kg	2:	--	--	NO	NO	--						
F0220	7110	Chair, Conference	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	41	25	28	44 lb	1:	--	--	--	NO	--						
			104	64	71	20 kg	2:	--	--	NO	NO	--						
F0225	7110	Chair, Dining Room	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	40	19	24	46 lb	1:	--	--	0	NO	--						
			102	48	61	21 kg	2:	--	--	NO	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
F0230	7110-00-281-4469	Chair, Drafting, Rotary	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			49	124	20	38 lb 18 kg	1: --	--	--	0	NO	NO	--		
			20	51	20		2: --	--	--						
F0235	7110	Chair, Executive, Side	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Executive side chair, 35" high x 26" wide x 27" deep with cushioned seat, back and arms. Straight leg or sled base available.															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			34	86	24	35 lb 16 kg	1: --	--	--	--	NO	NO	--		
			27	61	27		2: --	--	--						
F0240	7110	Chair, Executive, Swivel	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Executive swivel chair, 39" high X 26" wide X 26" deep with arms, a five (5) caster base and tilt mechanism. Seat and back have foam rubber cushions. Upholstery may be either woven fabric or vinyl.															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			46	117	28	46 lb 21 kg	1: --	--	--	--	NO	NO	--		
			26	71	26		2: --	--	--						
F0245	7110-00-753-5551	Chair, Executive, Rotary, Highback	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Executive high back swivel chair, 43" high X 23" wide X 31" deep with upholstered arms & five (5) caster swivel tilt base. Both seat and back are foam padded and upholstered with woven textile fabric, leather or vinyl.															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			48	122	27	75 lb 34 kg	1: --	--	--	0	NO	NO	--		
			32	81	32		2: --	--	--						
F0250	7100	Chair, Arm, Lounge Type	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Lounge chair approximately 33" high X 28" wide X 29" deep, with arms and floor glides. Chair completely padded and upholstered in either woven textile fabric or vinyl.															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			33	84	28	55 lb 25 kg	1: --	--	--	0	NO	NO	--		
			29	74	29		2: --	--	--						
F0255	7100	Chair, Easy	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Easy chair approximately 35" high X 28" wide X 32" deep with arms and floor glides. Arms, back and seat are foam padded and upholstered in woven textile fabric or vinyl.															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			31	79	33	81 lb 37 kg	1: --	--	--	0	NO	NO	--		
			32	81	32		2: --	--	--						
F0260	6530	Chair, High Back, Patient	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
High back patient chair, approximately 45" H X 24" W X 30" D with padded and upholstered back and seat. Straight legs have floor glides. Upholstery material is vinyl.															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			42	107	25	57 lb 26 kg	1: --	--	--	0	NO	NO	--		
			30	76	30		2: --	--	--						
F0265	6530	Chair, Recliner	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Reclining chair, 46" high X 33" wide X 40" deep with arms, straight leg base and floor glides or lockable two (2) inch casters. Seat, back and foot rest are foam padded and upholstered with woven textile fabric or vinyl. [Recliners are priced with medium grade fabric.]															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			47	119	29	120 lb 55 kg	1: --	--	--	--	NO	NO	--		
			36	91	36		2: --	--	--						

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES									
				R	A	F	A	H		1	2	3	4	5	6				
F0270	7110	Chair, Rocking, High Back	C C C C --																
High back rocking chair or glider. Designed for patient comfort and support. Available with sled base or straight leg base. [Price difference verified.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	45	32	26	55 lb	1:	--	--	--	NO		--						
		CM:	114	81	66	25 kg	2:	--	--	--	NO		--						
F0275	7110	Chair, Swivel, High Back	C C C C --																
Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	42	24	27	56 lb	1:	--	--	--	NO		--						
		CM:	107	61	69	26 kg	2:	--	--	--	NO		--						
F0280	7110	Chair, Swivel, Low Back	C C C C --																
Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	37	25	31	53 lb	1:	--	--	--	NO		--						
		CM:	94	64	79	24 kg	2:	--	--	--	NO		--						
F0285	7110	Chair, Secretarial, Tilt Back, Adjustable Height	C C C C --																
Secretarial chair, 38" high X 19" wide X 21" deep with adjustable seat height, non-tilting seat and a five (5) caster swivel base. Seat and back are foam padded and upholstered with woven textile fabric or vinyl.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	39	19	23	37 lb	1:	--	--	--	NO		--						
		CM:	99	48	58	17 kg	2:	--	--	--	NO		--						
F0290	7110	Chair, Secretarial, Executive	C C C C --																
Executive secretarial chair, 33" high X 20" wide X 20" deep with adjustable seat height, five (5) casters, swivel base, foam padded seat and back upholstered with either woven textile fabric or vinyl and design to blend with any of the four executive furniture schemes.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	41	25	25	40 lb	1:	--	--	--	NO		--						
		CM:	104	64	64	19 kg	2:	--	--	--	NO		--						
F0295	7100	Chair, Stacking	C C C C --																
Stacking chair, approximately 34" H X 21" W X 24" D. May be stacked up to 20 high depending upon the model selected. These chairs are intended primarily as overflow capacity for conference rooms.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	32	22	24	15 lb	1:	--	--	--	NO		--						
		CM:	81	56	61	7 kg	2:	--	--	--	NO		--						
F0300	7100-04-018-042	Chair, Task, Swivel, With Arms	C C C C --																
Task chair, approximately 34" H X 26" W X 22" D with adjustable arms and a five caster adjustable swivel base. Seat and back are foam padded and upholstered in woven fabric or vinyl.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	38	27	23	45 lb	1:	--	--	--	NO		--						
		CM:	97	69	58	21 kg	2:	--	--	--	NO		--						

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
F0305	7100	Chair, Waiting Room, Single	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	34	28	28	55 lb	1:	--	--	--	HZ SWITCH:	NO	--		
		CM:	86	71	71	25 kg	2:	--	--	--	DEPENDENT:	NO	--		
F0310	7100	Chair, Waiting Room, Tandem	C C C C --	--	--	--	--	--	0	NO	BTUs / HR:				
Three seat tandem waiting chair with foam padded seats and backs upholstered with either woven fabric textile or vinyl. Arms and floor glides included.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	34	86	29	170 lb	1:	--	--	--	HZ SWITCH:	NO	--		
		CM:	86	218	74	78 kg	2:	--	--	--	DEPENDENT:	NO	--		
F0315	7110	Chair, Sleeper	C C C C --	--	--	--	--	--	0	NO	BTUs / HR:				
Sleeper chair, 39" high X 36" wide X 74" deep (as a bed). Chair designed to convert (either fold-out or reclining) into a temporary bed used by either hospital staff or a patient's immediate family. [The sleep chair width and depth represent the dimensions in the sleep position.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	39	35	86	219 lb	1:	--	--	--	HZ SWITCH:	NO	--		
		CM:	99	89	218	100 kg	2:	--	--	--	DEPENDENT:	NO	--		
F0340	6530	Stool, Self Adjusting	C C C C --	--	--	--	--	--	--	NO	BTUs / HR:				
Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	38	18	18	39 lb	1:	--	--	--	HZ SWITCH:	NO	--		
		CM:	97	46	46	18 kg	2:	--	--	--	DEPENDENT:	NO	--		
F0350	7100	Stool, Step, Retractable Caster	C C C C --	--	--	--	--	--	--	NO	BTUs / HR:				
Step stool, 18" high X 16" diameter with three retractable casters, skid proof rings and ribbed treads.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	18	16	16	11 lb	1:	--	--	--	HZ SWITCH:	NO	--		
		CM:	46	41	41	5 kg	2:	--	--	--	DEPENDENT:	NO	--		
F0355	6530-00-708-6975	Footstool, Straight	C C C C --	--	--	--	--	--	--	NO	BTUs / HR:				
Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	8	30	12	10 lb	1:	--	--	--	HZ SWITCH:	NO	--		
		CM:	20	76	30	5 kg	2:	--	--	--	DEPENDENT:	NO	--		
F0375	7110	Sofa, Upholstered	C C C C --	--	--	--	--	--	0	NO	BTUs / HR:				
Executive sofa with woven fabric textile or vinyl upholstery, foam padded arms, steel spring and foam rubber backs and seats, and floor glides. [Price may vary depending on quality of fabric covering selected. Example: Model 3 with a grade 6 fabric covering (Adden has grades 1 through 12) would list for \$2,287.00.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:				
EA		IN:	34	85	35	150 lb	1:	--	--	--	HZ SWITCH:	NO	--		
		CM:	86	216	89	68 kg	2:	--	--	--	DEPENDENT:	NO	--		
F0400	6530	Cabinet, Bedside, Door, Drawer	C C C C --	--	--	--	--	--	--	--	BTUs / HR:				
Bedside cabinet for storage of both the patient's personal items and small patient support items. Approximately 31" high X 21" wide X 19" deep with one (1) drawer and one (1) closed storage closet. Drawer is removable so interior can be sanitized. May come in a 3 drawer version. [Model 2, from Hill-Rom is a three drawer cabinet instead of the one drawer and a door. The only model with drawer and a door that Hill-Rom currently provides is in their VIP series at a price of \$798. Recommend the Nomenclature and Description be changed to allow for either a "door, drawer" version or a "three drawer" version.]															

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
			EA	32	81	20	80 lb 37 kg	1: --	--	--	--	NO	--						
F0405	7110-00-551-5485	Cabinet, Filing, Full Height, 4-5 Drawer																	
			Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with locking device. Each drawer has label holder, handle and roller cradle.																
			EA	52	132	27	159 lb 73 kg	1: --	--	--	0	NO	--						
F0410	7110	Cabinet, Filing, Half Height, 2 Drawer																	
			Two (2) drawer letter size vertical filing cabinet approximately 29" high X 15" wide X 26" deep with locking device. Each drawer has label holder, handle and roller cradle.																
			EA	29	74	28	75 lb 34 kg	1: --	--	--	0	NO	--						
F0415	7110-00-386-3796	Cabinet, Filing, Lateral, Full Height, 5 Drawer																	
			Full height five (5) drawer lateral filing cabinet, 65" high X 42" wide X 18" deep with floor levelers (front), locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.																
			EA	67	170	19	307 lb 140 kg	1: --	--	--	--	NO	--						
F0420	7110	Cabinet, Filing, Lateral, Half Height																	
			Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.																
			EA	29	74	19	162 lb 74 kg	1: --	--	--	--	NO	--						
F0425	7110	Cabinet, Filing, Security, Full Height																	
			Class 6 full height security filing cabinet, 58" high X 21" wide X 28" deep with five (5) drawers. Used for storage of classified or controlled materials. [Hamilton Products Group is the only GSA and Defense Security Service (DSS) approved manufacture of security filing cabinets. Mosler Inc the previous supplier since 1963, ceased operations in 2001.]																
			EA	58	147	28	595 lb 271 kg	1: --	--	--	--	NO	--						
F0435	7110	Cabinet, Storage, Video Tape																	
			Video tape storage cabinet, approximately 60" high X 36" wide X 14" deep with six (6) shelves and door lock. [Model 2 is 88" high and has 7 shelves. Model 3 has 5 shelves.]																
			EA	67	170	14	182 lb 83 kg	1: --	--	--	0	NO	--						
F0440	7100	Cabinet, Filing, Cardex																	
			Cardex filing cabinet 9" high X 16" wide X 20" deep with holding trays for patient record pocket frames. Used in medical records, admissions and pharmacy to hold patient care and medication administration record cards. Total capacity of 480 pockets. [C&H Distributors (Cage Code # 04718) and Jacobs Garner (Gage Code 7R579) have discontinued their Cardex and Vizidex lines. No other source(s) identified with this description/specification.]																
			EA	13	33	19	59 lb 27 kg	1: --	--	--	0	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
F0445	7110	Cabinet, Storage, Data Processing	C C C C --	--	--	--	--	--	--	--	--	--	--
Data processing storage cabinet. This unit is a multi-media storage cabinet. Characteristic and components include lock and roll out bin drawer. This unit is constructed of sturdy steel. [Roll out bins do not come standard on this cabinet, but are available as an accessory. No other source(s) identified with this description/specification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	83	34	17	85 lb	1:	--	--	--	NO	--	
		CM:	211	86	43	39 kg	2:	--	--	--	NO	--	
F0465	7100	Cabinet, Storage, 2 Door, 5 Shelf	C C C C --	--	--	--	--	--	0	NO	--		
Storage cabinet, 78" high X 48" wide X 24" deep with two (2) doors and five (5) adjustable shelves.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	78	48	24	215 lb	1:	--	--	--	NO	--	
		CM:	198	122	61	98 kg	2:	--	--	--	NO	--	
F0470	7100	Cabinet, Television / Video Recorder	C C C C --	--	A	--	--	--	0	NO	--		
Television / video cabinet with one (1) shelf for a television set, one (1) shelf for a video recorder, and additional space for storage. Locking doors for added security.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	67	38	26	179 lb	1:	--	--	--	NO	--	
		CM:	170	97	66	82 kg	2:	--	--	--	NO	--	
F0475	7110	Cabinet, Storage, Photographic Slides	C C C C --	--	--	--	--	--	0	NO	--		
35 mm photographic slide storage cabinet, 12" high X 17" wide X 14" deep. Used to organize, store and protect slides and slide presentations. Unit may be stacked for archiving. [Price difference verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	16	17	18	33 lb	1:	--	--	--	NO	--	
		CM:	41	43	46	15 kg	2:	--	--	--	NO	--	
F0490	7125	Cabinet, Keys	A A A A --	--	--	--	--	--	--	NO	--		
Key cabinet. Made of heavy gauge steel. Equipped with a sturdy lock and screws for wall mounting. Used for key storage.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	18	14	5	10 lb	1:	--	--	--	NO	--	
		CM:	46	36	13	5 kg	2:	--	--	--	NO	--	
F0500	7110	Cart, Janitor's	C C C C --	--	--	--	--	--	0	NO	--		
Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included). [Price difference verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	40	22	46	77 lb	1:	--	--	--	NO	--	
		CM:	102	56	117	35 kg	2:	--	--	--	NO	--	
F0505	7100	Bucket, Mop, With Wringer, 26 Quart	C C C C --	--	--	--	--	--	0	NO	--		
Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	38	16	23	24 lb	1:	--	--	--	NO	--	
		CM:	97	41	58	11 kg	2:	--	--	--	NO	--	
F0510	7100	Cart, Linen, Soiled	C C C C --	--	--	--	--	--	0	NO	--		
Soiled linen collection cart, approximately 70" H x 68" W x 28" D with four (4) casters. Used to transport clean or soiled laundry.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	70	60	29	301 lb	1:	--	--	--	NO	--	
		CM:	178	152	74	137 kg	2:	--	--	--	NO	--	

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES										
				A	N	A	V	I	1	2	3	4	5	6
F0515	7100	Cart, Supply, Linen	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Closed linen supply cart. Equipped with four (4) non-marking rubber tire roller bearing casters and heavy duty cover. May be used for the delivery and user storage of clean linen as well as the return of soiled linen. [Price difference verified.]														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
EA		IN:	66	54	27	265 lb	1:	--	--	0	NO			
		CM:	168	137	69	121 kg	2:	--	--	NO	--			
F0525	7100	Cart, Supply	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Medical/surgical supply cart with swivel or combination swivel and rigid non-marking rubber tire casters, and from two (2) to five (5) adjustable shelves. Unit designed to accept a variety of function related accessories (drawers, shelves). Note: Carts are typically made to specification to accommodate the facility's transport system. Covers are available as accessories for the carts. [Models 1 and 3 are constructed of stainless steel.]														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
EA		IN:	69	61	27	150 lb	1:	--	--	0	NO			
		CM:	175	155	69	68 kg	2:	--	--	NO	--			
F0530	7110	Cart, Trash	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Heavy duty trash cart, 42" high X 74" wide X 34" deep with two (2) solid non-marking rubber roller bearing wheels, two (2) swivel casters, 2000 pound capacity and tilt mechanism.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
EA		IN:	44	73	34	155 lb	1:	--	--	0	NO			
		CM:	112	185	86	71 kg	2:	--	--	NO	--			
F0535	7110	Cart, Utility	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Utility cart, 32-39" high X 36" wide X 24" deep, with 4 (four) heavy duty caster wheels.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
EA		IN:	40	25	36	53 lb	1:	--	--	0	NO			
		CM:	102	64	91	24 kg	2:	--	--	NO	--			
F0545	7310	Cart, Library, Mobile	C C C C --	--	--	--	--	--	--	--	--	--	--	--
Cart, library, mobile, with 4 (four) sloping shelves and 4 (four) heavy duty caster wheels.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
EA		IN:	42	37	18	80 lb	1:	--	--	0	NO			
		CM:	107	94	46	37 kg	2:	--	--	NO	--			
F0550	7110	Armoire, Resuscitation	C C C . --	--	A	--	--	--	--	--	--	--	--	--
Resuscitation Armoire used in LDR and LDRP. The cabinet contains equipment needed for infant resuscitation. Equipped with Integrated Infant Warmer System, automatic exhaust fan, bassinet or fold down bed, accessory mounting rails, and writing surface. Other options include a manometer and hook up for suction and oxygen. Also contains adjustable shelves and drawers for storage of supplies and monitoring equipment. [No other source(s) identified with this description/specification. When purchased with a patient wardrobe similar to JSN:F0555, the specification must indicate the same type finish and color to insure that the furniture matches. Ohmeda offers both a bassinet or fold down bed (Murphy) style unit. Price is for the bassinet style unit.]														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
EA		IN:	81	50	24	250 lb	1:	120	1	0	NO			
		CM:	206	127	61	114 kg	2:	--	--	NO	--			
F0555	7110	Wardrobe, Patient Clothing	C C C . --	--	--	--	--	--	--	--	--	--	--	--
Clothing wardrobe for storage of patient clothing in a LDR/ LDRP or patient rooms. This item is selected to match the resuscitation Armoire, JSN F0550, if used, in finish and style. [Ohmeda's wardrobe armoire is the same basic cabinet as the Resuscitation Armoire, JSN: F0550, but without the medical equipment. When purchased with a Resuscitation Armoire similar to JSN: F0550 the specification must indicate the same type finish and color to insure that the furniture matches. Models 2 and 3 are wardrobes only, and may not maatch the Resuscitation Armoire, JSN F0550.]														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
EA		IN:	81	50	25	275 lb	1:	--	--	0	NO			
		CM:	206	127	64	125 kg	2:	--	--	NO	--			

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1 2 3 4 5 6	
F0560	7110	Wardrobe, Television	C C C C --	--	--	--	--	--	--	
A combination wardrobe that combines the storage of clothing along with a television cabinet. Item is intended for use in patient bedrooms particularly the LDR and LDRP.										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	78	58	25	350 lb	1:	-- -- --	0	
		CM:	198	147	64	159 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
F0570	7110	Dresser, 6 Drawer	C C C C --	--	--	--	--	--	--	
A 6 drawer dresser used to store clothing. [Price difference verified.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	36	56	24	200 lb	1:	-- -- --	0	
		CM:	91	142	61	91 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
F0600	7110	Credenza, Executive, Wood	C C C C --	--	--	--	--	--	--	
Executive credenza with two (2) box drawers, two (2) file drawers, a center closed storage area with adjustable shelf and floor glides.										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	30	72	24	300 lb	1:	-- -- --	0	
		CM:	76	183	61	137 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
F0610	7195	Desk, Folding, W/M	A A A A --	--	--	--	--	--	--	
Wall mounted fold down desk, approximately 18" high X 23" wide X 3" deep, with writing surface, pencil-pen rack and multiple form holders. [These models are manual closing units. Self closing units are available from the manufacturers/vendors shown. Various other sizes are also available.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	20	26	4	15 lb	1:	-- -- --	0	
		CM:	51	66	10	7 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
F0620	7110	Desk, Secretary, Executive	C C C C --	--	--	--	--	--	--	
Executive secretarial desk, approximately 29" high X 60" wide X 30" deep with return (right or left hand), approximately 27" high X 45" wide X 21" deep. One (1) box drawer, one (1) file drawer, one (1) pencil drawer. Return has three box drawers.										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	30	68	30	538 lb	1:	-- -- --	0	
		CM:	76	173	76	245 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
F0635	7110	Desk, Double Pedestal, 30 x 60 x 30	C C C C --	--	--	--	--	--	--	
Double pedestal flat top desk, 30" high X 60" wide X 30" deep with center pencil drawer, choices of combinations of file and box drawers, floor glides and modesty panel.										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	30	60	30	189 lb	1:	-- -- --	--	
		CM:	75	152	76	86 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
F0640	7110	Desk, Single Pedestal	C C C C --	--	--	--	--	--	--	
Single pedestal flat top desk, 30" high X 66" wide X 30" deep with right or left hand pedestal, one (1) box drawer, one (1) file drawer, modesty panel and floor glides. [Model 1 is 55" wide and has a mobile 2 drawer pedestal unit.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	30	66	31	246 lb	1:	-- -- --	--	
		CM:	76	168	79	112 kg	2:	-- -- --	NO	--
DEPENDENT: NO										
F0650	7110	Desk, Executive, Wood	C C C C --	--	--	--	--	--	--	
Double pedestal executive desk, 30" high X 72" wide X 36" deep with center pencil drawer, three (3) box drawers and reference slide in right hand pedestal; one (1) box drawer, one (1) file drawer, and reference slide in left hand pedestal, locks for each section (pedestal) of the desk, and metal suspension hardware for the file drawer.										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	30	72	36	350 lb	1:	-- -- --	0	
		CM:	76	183	91	159 kg	2:	-- -- --	NO	--
DEPENDENT: NO										

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
F0690	7110	Workstation, Computer, Enclosed, With Lock	C C C C --	--	--	--	--	--	--	--	--	--	--
Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	65	36	30	191 lb	1:	--	--	--	0	NO	
		CM:	165	91	76	87 kg	2:	--	--	--	DEPENDENT:	NO	
F0695	7110	Workstation, Computer, Open	C C C C --	--	--	--	--	--	--	--	--	--	--
Computer operator workstation, 55" high X 60" wide X 27" deep with large work surface and one (1) 17" high X 48" wide X 16" deep hutch. Desk has one (1) pull-out keyboard shelf. Hutch has adjustable open shelves.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	60	60	30	125 lb	1:	--	--	--	--	NO	
		CM:	152	152	76	57 kg	2:	--	--	--	DEPENDENT:	NO	
F0700	7110	Table, Computer, Medium Size	C C C C --	--	--	--	--	--	--	--	--	--	--
Medium sized computer table, approximately 35" high X 48" wide X 30" deep with enough surface for a CPU, monitor, keyboard and (optional) printer.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	40	53	31	105 lb	1:	--	--	--	--	NO	
		CM:	102	135	79	48 kg	2:	--	--	--	DEPENDENT:	NO	
F0705	7110	Table, Computer, Small	C C C C --	--	--	--	--	--	--	--	--	--	--
Small sized computer table, approximately 35" high X 36" wide X 30" deep with enough surface for a CPU, monitor and keyboard.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	32	36	30	105 lb	1:	--	--	--	0	NO	
		CM:	81	91	76	48 kg	2:	--	--	--	DEPENDENT:	NO	
F0710	7110	Table, Computer, With Print Shelf	C C C C --	--	--	--	--	--	--	--	--	--	--
Computer work table, approximately 31" high X 49" wide X 24" deep with retractable shelf(s) for keyboard and/or extra work space, adjustable shelves for printer and printer paper, and (optional) dual wheel casters (two locking).													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	36	48	30	98 lb	1:	--	--	--	0	NO	
		CM:	91	122	76	45 kg	2:	--	--	--	DEPENDENT:	NO	
F0715	7110	Carrel, Study Table	C C C C --	--	A	--	--	--	--	--	--	--	--
Study carrel with table. Equipped with shelf for one (1) 12" monitor and book shelf, built-in electrical outlet (optional) and adjustable floor glides. A convenience outlet is required at point of use when the optional 120 VAC 60 Hz built-in electrical outlet is specified and used. Work surface is 29" high.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	48	46	29	146 lb	1:	120	1	6	60	NO	
		CM:	122	117	74	67 kg	2:	--	--	--	DEPENDENT:	NO	
F0720	7110	Table, Writing	C C C C --	--	--	--	--	--	--	--	--	--	--
Table writing approximately 29" H X 30" W X 18" D for use in day rooms, sleep rooms or as appropriate. [Other sizes are available.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	30	30	18	28 lb	1:	--	--	--	0	NO	
		CM:	76	76	46	13 kg	2:	--	--	--	DEPENDENT:	NO	
F0725	7110	Table, Occasional, Executive, Wood	C C C C --	--	--	--	--	--	--	--	--	--	--
Executive chairside table, approximately 21" high X 26" wide X 20" deep. Used as an occasional table in an executive suite.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	21	24	25	37 lb	1:	--	--	--	--	NO	
		CM:	53	61	64	17 kg	2:	--	--	--	DEPENDENT:	NO	

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
F0735	7110	Table, Coffee	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Coffee table, approximately 18" high X 52" wide X 24" deep.															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:			
EA		CM:	16	48	24	46 lb	1:	--	--	--	0	NO		--	
			41	122	61	21 kg	2:	--	--	--	DEPENDENT:	NO		--	
F0740	7110	Table, Occasional, Lamp, 20 x 27 x 27	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Occasional lamp table (end table) 20" high X 27" wide X 27" deep with choice of finishes (wood, oak veneer, or high pressure laminate).															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:			
EA		CM:	20	27	27	25 lb	1:	--	--	--	--	NO		--	
			51	69	69	12 kg	2:	--	--	--	DEPENDENT:	NO		--	
F0745	7110	Table, Drafting	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Drafting table, approximately 38" high X 57" wide X 38" deep with tilt and height adjustment.															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:			
EA		CM:	37	57	38	250 lb	1:	--	--	--	0	NO		--	
			94	145	97	114 kg	2:	--	--	--	DEPENDENT:	NO		--	
F0750	7110	Table, Office, (size as required)	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Office table, sized as required, may be used as either a four (4) to six (6) person conference table or as an extra work surface area.															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:			
EA		CM:	29	96	48	250 lb	1:	--	--	--	--	NO		--	
			74	244	122	114 kg	2:	--	--	--	DEPENDENT:	NO		--	
F0755	7110	Table, Conference, Wood	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:			
EA		CM:	30	96	48	468 lb	1:	--	--	--	--	NO		--	
			76	244	122	213 kg	2:	--	--	--	DEPENDENT:	NO		--	
F0760	7110	Table, Child's	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Child's table, 25" high X 48" wide X 24" deep with floor glides. Table used for testing, observation, meals, education and play.															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:			
EA		CM:	25	48	24	52 lb	1:	--	--	--	--	NO		--	
			64	122	61	24 kg	2:	--	--	--	DEPENDENT:	NO		--	
F0775	7110	Table, Work, 2 Drawer	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Work table approximately 32" high X 72" wide X 30" deep with two drawers and a hard wood top.															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:			
EA		CM:	32	72	30	195 lb	1:	--	--	--	0	NO		--	
			81	183	76	89 kg	2:	--	--	--	DEPENDENT:	NO		--	
F0780	7110	Table, Work, 60W x 30D	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Work table approximately 29" high X 60" wide X 30" deep with top and four (4) non-folding legs.															
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:			
EA		CM:	30	60	30	103 lb	1:	--	--	--	--	NO		--	
			76	152	76	47 kg	2:	--	--	--	DEPENDENT:	NO		--	

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
F0790	7110	Table, Work, 60W x 48D	C C C C --	--						--					
Work table approximately 30" high x 60" wide x 48" deep with a thick laminate top and four (4) non-folding legs.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	30	60	48	188 lb	1:	--	--	8	NO				
		CM:	76	152	122	86 kg	2:	--	--	--	NO				
F0795	7110	Table, Dining	C C C C --	--						--					
Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons. [Database pricing is for a 42"diameter table.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	31	42	42	55 lb	1:	--	--	--	NO				
		CM:	79	107	107	25 kg	2:	--	--	--	NO				
F0800	6530	Table, Inspection, Linen	C C C C --	--						A --					
Linen inspection table, 36" high X 72" wide X 32" deep. Plexiglas view panel under-lit with fluorescent lighting. Furnished with 10-foot power cord with a 3-prong grounded plug. Designed for inspecting and folding linens. Convenience outlet required. [No other source(s) identified with this description/specification. Previous vendors Blickman (Cage4M773) and Steris (02TU3) discontinued the item.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	36	72	32	300 lb	1:	120	1	15	NO				
		CM:	91	183	81	137 kg	2:	--	--	--	NO				
F0810	7110	Table, Pool	C C C C --	--						--					
Pool table approximately 32" high X 100" wide X 56" deep with 3/4" full size slate bed.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	32	112	62	1,100 lb	1:	--	--	--	NO				
		CM:	81	284	157	500 kg	2:	--	--	--	NO				
F0815	7110	Table, Ping Pong, Folding	C C C C --	--						--					
Folding ping pong table, 30 high X 108" wide X 60" deep.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	30	108	62	250 lb	1:	--	--	--	NO				
		CM:	76	274	157	114 kg	2:	--	--	--	NO				
F0820	7110	Table, Office, Round	C C C C --	--						--					
Round office table, approximately 29" high X 42" diameter.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	29	42	42	118 lb	1:	--	--	--	NO				
		CM:	74	107	107	54 kg	2:	--	--	--	NO				
F0827	7110	Table, Work, Standup, 37 X 60 X 30	C C C C --	--						--					
Standup work table, 37" high X 60" wide X 30" deep.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	38	60	30	128 lb	1:	--	--	--	NO				
		CM:	97	152	76	59 kg	2:	--	--	--	NO				
F0835	7195	Stand, Projection	C C C C --	--						A --					
Mobile projection stand with electrical outlet. Equipped with four (4) swivel casters with anti-shimmy spring cups, non-marking wheels, two (2) locking, and shelf storage. Convenience outlet required at point of use. [Model 3 height is adjustable from 27" to 41".]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	42	40	23	64 lb	1:	120	1	10	NO				
		CM:	107	102	58	29 kg	2:	--	--	--	NO				

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES						
				R	A	F	A	H		1	2	3	4	5	6	
F0850	7110	Stand, Dictionary	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Dictionary stand, 43" high X 25" wide X 18" deep with shelf space for reference book storage.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
EA		IN:	46	24	19	60 lb	1:	--	--	0	NO	--				
		CM:	117	61	48	28 kg	2:	--	--	NO	--					
F0855	7310	Table, Typing, Mobile	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Table, typing, mobile. Equipped with drop leaf shelf that adds additional working space. [Width dimensions are with drop leaf shelf (s) extended.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
EA		IN:	27	39	18	41 lb	1:	--	--	0	NO	--				
		CM:	69	99	46	19 kg	2:	--	--	NO	--					
F0860	7310	Table, Mobile	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Mobile table. The unit provides mobile or isolated freestanding work surface. Characteristics and components include 3-1/2 inch casters and attached drawer bearers. Unit is used for general work applications primary in dry areas.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
EA		IN:	38	60	30	145 lb	1:	--	--	--	NO	--				
		CM:	97	152	76	66 kg	2:	--	--	NO	--					
F0910	7100	Reader, Microfilm	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Microfilm reader/projector approximately 38" high X 22" wide X 22 deep. Must specify roll film (35mm, 16mm) or flat film (microfiche, super-fiche, micro-jackets, and aperture cards). Convenience outlet required at point of use.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
EA		IN:	30	22	26	105 lb	1:	120	1	60	NO	--				
		CM:	76	56	66	48 kg	2:	--	--	NO	--					
F0915	7100	Reader / Printer, Microfilm	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Microfilm reader / printer, 26" high X 19" wide X 26" deep with bi-modal printing to produce black on white from either positive or negative film(s). Printer is electrostatic and may use either individual paper sheets or roll stock. Some models may require a film roll attachment (optional) to accommodate 16mm and 35mm film. Convenience outlet required at point of use.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
EA		IN:	27	19	26	83 lb	1:	120	1	60	NO	--				
		CM:	69	48	66	38 kg	2:	--	--	NO	--					
F2000	7520-00-205-1857	Basket, Wastepaper, Round, Metal	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
EA		IN:	18	16	16	10 lb	1:	--	--	0	NO	--				
		CM:	46	41	41	5 kg	2:	--	--	NO	--					
F2005	7520	Basket, Wastepaper, Executive, Wood, 15 x 13 x 13	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Executive wastepaper basket, 15" high X 13" wide X 13" deep. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
EA		IN:	15	13	13	25 lb	1:	--	--	--	NO	--				
		CM:	38	33	33	12 kg	2:	--	--	NO	--					
F2010	7240-00-788-3953	Basket, Wastepaper, Step-On	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
EA		IN:	18	16	16	12 lb	1:	--	--	--	NO	--				
		CM:	46	41	41	6 kg	2:	--	--	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
F2015	7240-00-634-0133	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	37	16	16	30 lb	1:	--	--	0	NO	--						
			94	41	41	14 kg	2:	--	--	NO	NO	--						
F2020	7100	Can, Trash, 44 Gallon	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	32	24	24	15 lb	1:	--	--	--	NO	--						
			81	61	61	7 kg	2:	--	--	NO	NO	--						
F2025	7100	Container, Recycling, Small	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Recycling container shall be approximately 10-gallons in capacity. The container may be Recycle Blue in color with the recycle symbol identified on the container.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	14	16	20	6 lb	1:	--	--	0	NO	--						
			36	41	51	3 kg	2:	--	--	NO	NO	--						
F2026	7100	Container, Recycling, Large	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Recycling container shall be approximately 30-gallons in capacity. The container may include a lid and be Recycle Blue in color with the recycle symbol identified on the container. [Price of container includes a lid. Price for Models 2 and 3 includes a dolly.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	33	22	22	30 lb	1:	--	--	0	NO	--						
			84	56	56	14 kg	2:	--	--	NO	NO	--						
F2045	6530	Furniture, Playroom, Assorted	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Assorted playroom furniture. Part of the interior design package. Exact configuration to be determined by using activity. Vendors listed for reference. [No cut sheets provided, as playroom furniture will be tailored to the project and interior design. All three vendors currently offer a line of children's playroom furniture.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
LT		CM:	--	--	--	-- lb	1:	--	--	--	NO	--						
			--	--	--	-- kg	2:	--	--	NO	NO	--						
F2050	6515	Recorder, Cassette Tape, Audio	C	C	C	C	--	--	--	--	A	--	--	--	--	--	--	--
Cassette tape recorder, approximately 4" H X 7" W X 11" D, with both record and play capabilities. Auto stop, pause, tone control and built in microphone; AC/DC. Requires convenience outlet at point of use when not using batteries.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	2	6	11	3 lb	1:	120	1	60	NO	--						
			5	15	28	2 kg	2:	--	--	NO	NO	--						
F2100	7105	Lectern, Mobile, With Reading Light	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Portable floor lectern with reading light and self-contained audio. May use 110V or batteries (not included). Convenience outlet required if not using batteries.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	52	24	17	138 lb	1:	120	1	60	NO	--						
			132	61	43	63 kg	2:	--	--	NO	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
F2105	6600	Lectern, Mobile, With Self Contained Audio	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Portable floor lectern with built-in public address system. May use 110V or batteries (not included). Convenience outlet required at point of use if not using batteries.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	47	25	20	119 lb	1:	110	1	1	60	NO						
EA		CM:	119	64	51	54 kg	2:	--	--	--	DEPENDENT:	NO						
F2125	7110	Cash Register, With Locking Drawer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Electronic cash register system. This unit includes multiple menu capabilities. Equipped with removable cash drawer for complete security. Calculator function and tax table. Convenience outlet required at point of use.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	12	16	17	33 lb	1:	120	1	10	60	NO						
EA		CM:	30	41	43	15 kg	2:	--	--	--	DEPENDENT:	NO						
F2225	6730	Projector, Overhead	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Overhead transparency projector with hi-low lamp switch, thermal safety switch and 15 foot power cord. Convenience outlet required at point of use.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	38	15	19	25 lb	1:	120	1	2	60	NO						
EA		CM:	97	38	48	12 kg	2:	--	--	--	DEPENDENT:	NO						
F2248	6730	Photographic Optical Printer System	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Optical printer system used for a wide variety of close up medical photography. Various configurations available. [No other source(s) identified with this description/specification. Prices will vary depending on the options selected.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	6	7	6	4 lb	1:	120	1	2	60	NO						
EA		CM:	15	18	15	2 kg	2:	--	--	--	DEPENDENT:	NO						
F2250	5836	Camera, Portable, CCTV, With Recorder	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Portable camera/recorder (camcorder) with video-out capacity to accommodate a remote recorder. [No other source(s) identified with this description/specification. Camera is powered by a battery pack but an AC adapter is available as an accessory.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	6	10	19	7 lb	1:	--	--	--	--	NO						
EA		CM:	15	25	48	4 kg	2:	--	--	--	DEPENDENT:	NO						
F2280	7100	Television, Color, 27", w/stand	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Color television (27") with wireless remote control, automatic color balance and stereo sound to include a base, stand or cabinet. Item may be used for rehabilitation, patient education, or entertainment.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	47	35	23	184 lb	1:	120	1	2	60	NO						
EA		CM:	119	89	58	84 kg	2:	--	--	--	DEPENDENT:	YES						
F2300	7105-00-082-5449	Rack, Magazine, Wall Mounted	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Wall mounted magazine rack with nine (9) magazine holding compartments.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	37	30	3	15 lb	1:	--	--	--	--	NO						
EA		CM:	94	76	8	7 kg	2:	--	--	--	DEPENDENT:	NO						
F2305	7100	Rack, Magazine, F/S	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Free standing magazine rack. Used to display publications in offices, lobbies, and waiting areas.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	63	33	19	35 lb	1:	--	--	--	--	NO						
EA		CM:	160	84	48	16 kg	2:	--	--	--	DEPENDENT:	NO						

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
F2310	7100	Rack, Pamphlet, Wall Mounted	A A A A --	--	--	--	--	--	--	--	--	--	--
Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	27	30	3	15 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	69	76	8	7 kg	2:	--	--	--	DEPENDENT:	NO	--
F2320	7110	Rack, Mail Bag	C C C C --	--	--	--	--	--	0	--			
Mail Bag Rack. Used in mail rooms when bagging mail. Rack holds bags open for ease in sorting mail and keeps bags suspended off the floor. Folds away for easy storage.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	44	44	19	54 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	112	112	48	25 kg	2:	--	--	--	DEPENDENT:	NO	--
F2400	6530	Bed, Bunk, Watchroom	C C C C --	--	--	--	--	--	0	--			
Bunk bed, approximately 36" high X 85" wide X 44" deep (each). When stacked, a double unit is 72" high.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	72	83	44	200 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	183	211	112	91 kg	2:	--	--	--	DEPENDENT:	NO	--
F2405	7100	Bed, Non-medical, Single	C C C C --	--	--	--	--	--	0	--			
Single bed, approximately 18" high X 83" wide X 40" deep. Bed is used for non-inpatient stay activities (testing, visitor/staff sleeping).													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	36	85	39	85 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	91	216	99	39 kg	2:	--	--	--	DEPENDENT:	NO	--
F2420	6230	Lamp, Table, With Shade	C C C C --	--	A	--	--	--	60	--			
Table lamp, 27-34" high X 6" wide X 6" deep with linen shade. Convenience outlet required at point of use. [Width and depth dimensions are for the lamp base.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	28	6	6	10 lb	1:	120	1	1	HZ SWITCH:	NO	--
		CM:	71	15	16	5 kg	2:	--	--	--	DEPENDENT:	NO	--
F2435	6230-00-682-3423	Lamp, Desk, Fluorescent	C C C C --	--	A	--	--	--	60	--			
Fluorescent desk lamp, approximately 13"H X 9"W X 6" D with a 14" wide X 2" deep shade and two (2) 15 Watt fluorescent tubes. Used for general reading luminosity. Convenience outlet required at point of use.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	13	19	8	10 lb	1:	120	1	1	HZ SWITCH:	NO	--
		CM:	33	48	20	5 kg	2:	--	--	--	DEPENDENT:	NO	--
F2455	7200	Transcription Unit, Standalone	C C C C --	--	A	--	--	--	60	--			
Desk top individual transcription unit with foot control, headset and AC adapter. Convenience outlet required at point of use.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	3	7	9	6 lb	1:	120	1	1	HZ SWITCH:	NO	--
		CM:	8	18	23	3 kg	2:	--	--	--	DEPENDENT:	NO	--
F2485	7910	Cleaner, Carpet, Vacuum, Industrial	C C C C --	--	A	--	--	--	60	--			
Heavy duty vacuum cleaner with vacuum tank for disposable bags, power head and 50 foot power cord. Used for heavy traffic areas or deep cleaning prior to steam cleaning. For dry pick up only. Convenience outlet required at point of use. [Model 3 has a 40' power cord.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	48	19	16	30 lb	1:	120	1	9	HZ SWITCH:	NO	--
		CM:	122	48	41	14 kg	2:	--	--	--	DEPENDENT:	NO	--

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
F2490	7910	Cleaner, Carpet / Floor, Vacuum, Portable	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Portable vacuum cleaner, approximately 45" high X 12" wide X 18" deep with vacuum unit, heavy duty dust bag, 6 foot flexible hose, 22 foot power cord, wand and assorted wand accessories. Small unit used for routine cleaning of light traffic areas and non-liquid spills. Convenience outlet required at point of use.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	45	12	18	16 lb	1:	120	1	12	60		NO						
			114	30	46	8 kg	2:	--	--	--	DEPENDENT:		NO						
F2515	3910	Conveyor, Clothing, On Hangers	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Clothing conveyor, 77" high X 51" wide X "required depth", (depth depends upon installation requirements). Equipped with accommodations for ten (10) garment hangers per each foot of hanging capacity, motor driven, and hand or foot control switch at operational end. Used to store hanging clothing in laundry. [Numerous conversions are available and the end price will depend on the configurations chosen. No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	77	51	--	-- lb	1:	120	1	10	60		NO						
			196	130	--	-- kg	2:	--	--	--	DEPENDENT:		NO						
F2520	7100	Imprinter, Clock, Day / Date / Time	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Day / date / time clock imprinter, approximately 5" high X 3" wide X 2" deep.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	6	4	9	4 lb	1:	120	1	1	60		NO						
			15	10	23	2 kg	2:	--	--	--	DEPENDENT:		NO						
F2525	7110	Burnisher, Floor	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Floor burnisher, approximately 39" high X 26" wide X 38" deep with direct drive motor and 50 foot power cord. Convenience outlet required at point-of-use. [Model 3 GSA price is \$927.00.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	47	26	38	100 lb	1:	120	1	15	60		NO						
			119	66	97	46 kg	2:	--	--	--	DEPENDENT:		NO						
F2530	7100	Drill, Paper	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Paper drill, 17" high X 20" wide X 20" deep with spring-loaded paper hold down bar, and 1 (one) 1/4" drill. Unit used to drill holes in stacks of paper up to one inch thick. This is a table top unit. Requires convenience outlet at point of use.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	17	20	20	33 lb	1:	120	1	2	60		NO						
			43	51	51	15 kg	2:	--	--	--	DEPENDENT:		NO						
F2540	7100	Shredder, Paper, Security	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Paper shredder, approximately 18" high X 15" wide X 12" deep with shredding unit and waste receptacle.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	18	15	12	20 lb	1:	120	1	7	60		NO						
			46	38	30	9 kg	2:	--	--	--	DEPENDENT:		NO						
F2550	7100	Shredder, Paper Heavy Duty	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Shredder shall be able to process a minimum of 25 sheets of paper per pass at a minimum rate of 25 feet per minute. The unit shall have a 16 inch throat to accept paper. Paper shall be shredded into 1/4 inch strips. [The previous mean price was in error.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		CM:	37	26	19	190 lb	1:	115	1	20	60		NO						
			94	66	48	87 kg	2:	--	--	--	DEPENDENT:		NO						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
F2700	7200	Reader, Bar Code, Hand Held, With Interface	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers / labels. Convenience outlet required at point of use. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	12	10	6	--	1b	1:	120	1	1	60	NO	--				
		CM:	30	25	15	--	kg	2:	--	--	--	NO	--					
F3010	7195	Board, Bulletin, 48 x 48	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages. [Model 1 is 36' H x 48' W.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	48	48	2	21	lb	1:	--	--	--	0	NO	--				
		CM:	122	122	122	10	kg	2:	--	--	--	NO	--					
F3025	7195	Board, Bulletin, Wood Framed, 36 x 24	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Bulletin board. Wood framed 1/2" cork posting panel with moisture proof backing. Units are factory assembled and have keyhole hangers for easy installation.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	30	36	1	5	lb	1:	--	--	--	0	NO	--				
		CM:	76	91	3	3	kg	2:	--	--	--	NO	--					
F3030	7195	Board, Scheduling, Magnetic, 36 X 48	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Magnetic scheduling board. Porcelain enamel magnetic surface. Used for letter transferring while posting messages or scheduling. For use with marker pens.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	48	3	54	lb	1:	--	--	--	--	NO	--				
		CM:	91	122	8	25	kg	2:	--	--	--	NO	--					
F3035	7110	Chalkboard	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Chalkboard approximately 36" H X 60" W. Satin finish with moisture-proof backing. Full length chalk tray attached. Used in classrooms or conference rooms. [Chalkboards are available in various widths. Model 1 is 72" W.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	48	72	2	31	lb	1:	--	--	--	--	NO	--				
		CM:	122	183	5	14	kg	2:	--	--	--	NO	--					
F3045	6730	Whiteboard / Projection Screen, Cabinet	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Whiteboard / Projection screen with cabinet. Panels are porcelain over steel construction. Unit is a surface mounted cabinet with choice of cabinet doors constructed of either ebony lacquer, gray granite laminate or woodgrain finish.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	48	48	6	120	lb	1:	--	--	--	0	NO	--				
		CM:	122	122	15	55	kg	2:	--	--	--	NO	--					
F3050	7110	Whiteboard, Dry Erase	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang. [Various sizes are available from each manufacturer/vendor.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	48	2	30	lb	1:	--	--	--	0	NO	--				
		CM:	91	122	5	14	kg	2:	--	--	--	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
F3055	6730	Whiteboard, With Sliding Panels.	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Standard installations consist of sliding panels and a fixed back panel with the choice of chalkboard, markerboard, bulletin board, or a combination of these choices. [Based on a two track unit approximately 48" x 72".]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	48	72	6	168 lb	1:	--	--	--	NO							
		CM:	122	183	15	77 kg	2:	--	--	--	NO							
F3060	6730	Whiteboard, Projection Screen Combination	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Whiteboard and projection screen combination approximately 48" H x 72" W. Magnetic surface with matte finish for projection. Hard board stabilizer with aluminum foil back. For use with water color pens.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	48	72	1	58 lb	1:	--	--	--	NO							
		CM:	122	183	243	27 kg	2:	--	--	--	NO							
F3070	6730	Case, Display	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Display case. Equipped with glass doors, adjustable glass shelves, security locks and choice of either fabric or mirror backing.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	77	48	24	345 lb	1:	--	--	--	0							
		CM:	196	122	61	157 kg	2:	--	--	--	NO							
F3100	7110	Safe, Collection Agent	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Collection agent safe. Unit consists of thick door equipped with combination lock. All steel welded construction. For special document and record storage.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	21	17	19	137 lb	1:	--	--	--	0							
		CM:	53	43	48	63 kg	2:	--	--	--	NO							
F3105	7110	Safe, F/S , Class 5	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Class 5 safe, floor standing model with combination lock. Used for storage of narcotics, plans, film, and other classified or control materials. [Schwab Corporation, (Cage Code # 53572) does not offer security rated safes. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	29	23	25	490 lb	1:	--	--	--	--							
		CM:	74	58	64	223 kg	2:	--	--	--	NO							
F3200	6645	Clock, Battery, 12" Diameter	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	12	12	2	2 lb	1:	--	--	--	--							
		CM:	30	30	5	1 kg	2:	--	--	--	NO							
F3202	7100	Clock, Ship's, With Barometer	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Brass ship's clock with a separate barometer. The clock and barometer are mounted inside individual heavy brass cases and set in a stand or plaque. The clock and barometer can require mounting to the base or come preassembled. The instrument faces are 4" to 4-1/2" in diameter.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	8	18	4	10 lb	1:	--	--	--	--							
		CM:	20	46	10	5 kg	2:	--	--	--	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES							
				R	A	F	A	H		1	2	3	4	5	6		
F3230	5340	Rack, Hat / Coat, Wall Mounted		A	A	A	A	--	--	--	--	--	--	--	--	--	--
Wall mounted hat / coat rack. Decoratively styled and equipped with bars, hooks and hat shelf. For use in waiting rooms.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:							
EA		IN:	8	36	12	10 lb	1:	--	--	--	HZ SWITCH:	NO					
		CM:	20	91	30	5 kg	2:	--	--	--	DEPENDENT:	NO					
F3235	5340	Rack, Hat / Coat, Floor Standing		C	C	C	C	--	--	--	--	--	--	--	--	--	--
Floor standing hat / coat rack. Decoratively styled unit that provides hat rack at top, coat bar and hotel type hangers.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:							
EA		IN:	60	36	22	45 lb	1:	--	--	--	HZ SWITCH:	NO					
		CM:	152	91	56	21 kg	2:	--	--	--	DEPENDENT:	NO					
F8010	8345	Flags, Command & Staff		C	C	C	C	--	--	--	--	--	--	--	--	--	--
Flags, Command & Staff. [Recommend this JSN be used only as a place holder. Command and Staff Flags are normally authorized by service authorization documents and requisitioned only through command supply channels. Cost is dependent on size, application, type and level of command.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:							
EA		IN:	--	--	--	-- lb	1:	--	--	--	HZ SWITCH:	NO					
		CM:	--	--	--	-- kg	2:	--	--	--	DEPENDENT:	NO					
G0144	6530	Ergometer, Recumbent Stepper		C	C	C	C	--	--	--	--	--	--	--	--	--	--
Seated stepping ergometer for total body, arms and/or legs low impact conditioning. The unit features a closed kinetic chain action which combines reciprocal stepping and arm action. The arm settings and seat are adjustable. A battery operated performance computer allows for adjusting workload level. The unit has a heavy duty steel frame construction with low-density plastic covers. [No other source(s) identified with this description/specification. Several companies (Kettler Fitness, Master Fitness, Hard Gear, Bollinger and Cateye Fitness) provide recumbent cycles or steppers. However NuStep is the only manufacturer found that provides a total body recumbent stepper.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:							
EA		IN:	44	29	56	142 lb	1:	--	--	--	HZ SWITCH:	NO					
		CM:	112	74	142	65 kg	2:	--	--	--	DEPENDENT:	NO					
G1000	6530	Bench, Weightlifting, Utility, Adjustable		C	C	C	C	--	--	--	--	--	--	--	--	--	--
Utility bench with an adjustable incline for weightlifting. The bench back support and seat can adjust from a flat surface to a nearly vertical seat. The range of settings permits isolating a wide variety of arm, chest and shoulder muscle groups for development or rehabilitation. On most manufacturer's models, the seat and back support pads are independently adjustable. Some models feature foot rests for relieving pressure on the lower back or wheels for easy movement.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:							
EA		IN:	49	27	56	102 lb	1:	--	--	--	HZ SWITCH:	NO					
		CM:	124	69	142	47 kg	2:	--	--	--	DEPENDENT:	NO					
G1001	6530	Bench, Weightlifting, Supine		C	C	C	C	--	--	--	--	--	--	--	--	--	--
Supine bench for weightlifting use in a gym or the exercise area of Physical Therapy. Benches are available in standard duty or Olympic specification models depending on anticipated use. Some models feature racking pegs on the bench uprights to support heavier weights.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:							
EA		IN:	53	57	63	158 lb	1:	--	--	--	HZ SWITCH:	NO					
		CM:	135	145	160	72 kg	2:	--	--	--	DEPENDENT:	NO					
G1002	6530	Board, Abdominal Exercise		C	C	C	C	--	--	--	--	--	--	--	--	--	--
Abdominal exercise board for physical training or rehabilitation of the stomach and oblique muscles. The board may have padding for positioning the legs to better isolate the stomach wall. This equipment is found in the gym or the exercise area of Physical Therapy.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:							
EA		IN:	50	29	82	125 lb	1:	--	--	--	HZ SWITCH:	NO					
		CM:	127	74	208	57 kg	2:	--	--	--	DEPENDENT:	NO					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
G1003	6530	Exercise Board, Abdominal, Raised and Bent Leg	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Abdominal board designed to hold the upper portion of the user's legs perpendicular to the user's torso. This position isolates the abdominal muscles more effectively than bent leg exercises done on a flat abdominal board which only holds the user's legs at the ankle. The board can tilt from an incline through a horizontal plane and further into a decline to provide increasingly strenuous workouts depending on the user's physical condition. The board's durable padding provides stability and prevents injury. The board is used in a gymnasium or the exercise area of physical therapy.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	45	28	65	128 lb	1:	--	--	--	0		NO							
		CM:	114	71	165	59 kg	2:	--	--	--	NO		NO							
G1004	6530	Bench, Weightlifting, Incline Press, Fixed Height	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Fixed height incline bench for strength training or rehabilitation use in a gym or Physical Therapy. The bench has an incline angle of 30 degrees to best isolate the upper chest muscles. A series of racking pegs on the bench's uprights support the loaded barbell before and after lifting. The bench's design permits easy second person safety spotting for heavy lifts. Some models have adjustable seat pads and foot supports which compensate for differing leg lengths and better position the lifter's torso to relieve pressure on the lower back. Other available models do not have upright racking pegs and/or feature fixed inclines up to 45 degrees. Refer to JSN G1000 for weightlifting benches with adjustable inclines. [Price difference verified.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	60	67	75	240 lb	1:	--	--	--	0		NO							
		CM:	152	170	190	109 kg	2:	--	--	--	NO		NO							
G1005	6530	Bench, Decline	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Decline bench for weight training use in a gym or the exercise area of Physical Therapy. Some models have an adjusting height pole beneath the exerciser's knees. Other models have a fixed decline angle or racking uprights with pegs to stabilize heavy weights before and after lifting.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	53	51	76	200 lb	1:	--	--	--	--		NO							
		CM:	135	130	193	91 kg	2:	--	--	--	NO		NO							
G1006	6530	Bar, Chinning, Wall Mount	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Wall mounted chinning bar for use in a gym or the exercise area of Physical Therapy. The bar hangs from support rails which bolt to the wall. Some models have adjustable heights.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	54	40	18	30 lb	1:	--	--	--	--		NO							
		CM:	137	102	46	14 kg	2:	--	--	--	NO		NO							
G1007	6530	Ergometer, Stationary, Stair	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--		
Stair climbing exercise unit for use in physical training in a gym or in rehabilitation exercise protocols in a physical therapy clinic. The unit includes foot pedals, variable resistance settings, several exercise routines with varying intensity settings and a display for motivation and monitoring. Some models have optional direct or telemetric pulse monitoring. Database electrical specifications are for those models which require power. Refer to the manufacturers' specifications to verify electrical requirements. [The Star Trac (SR414) is powered by battery.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	69	36	44	230 lb	1:	110	1	3	60		NO							
		CM:	175	91	112	105 kg	2:	--	--	--	NO		NO							
G1008	6530	Exerciser, Upper Body, Weight Assisted	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Weight assisted upper body exercise apparatus. The weight stack partially compensates for the exerciser's body weight and allows the exerciser to move through the full dip, chin-up or pull up motion while not lifting his or her full body weight. By progressively lowering the assistance the machine provides, the exerciser can eventually work up to unassisted lifting. The room ceiling may have to be raised to accommodate the equipment and exerciser when the exerciser is at the top of a chin up or pull up. See specific manufacturer's requirements. The unit is used in a gym for upper body strength training or in physical therapy for rehabilitation. [Price difference verified.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	96	49	54	703 lb	1:	--	--	--	0		NO							
		CM:	244	124	137	320 kg	2:	--	--	--	NO		NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
G1010	6530	Exercise Machine, Neck	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--		
Neck exercise machine for use in a gym or the exercise area of Physical Therapy. The machine uses a configuration of weights, pulleys and cables or belts to apply resistance against a bio-mechanically correct neck movement by the exerciser. The progressive increase of the resistance weight leads to strengthening of the neck muscles. Many manufacturers offer range of motion limiters or different configurations of weight stacks for specific applications. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			62	40	48	415 lb	1:	--	--	--	NO	NO	--						
			157	102	122	189 kg	2:	--	--	--	NO	NO	--						
G1011	6530	Exercise Machine, Abdominal	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--		
Abdominal exercise machine for use in a gymnasium or the exercise area of Physical Therapy. The machine uses a configuration of weights, pulleys and cables or belts to apply resistance against a bio-mechanically correct abdominal muscle contraction by the exerciser. The progressive increase of the resistance weight leads to strengthening of the upper and lower abdominal as well as the oblique muscles.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			68	48	64	600 lb	1:	--	--	--	NO	NO	--						
			173	122	163	273 kg	2:	--	--	--	NO	NO	--						
G1012	6530	Exercise Machine, Leg Press/Squat	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--		
Leg press/squat exercise machine for use in a gymnasium or the exercise area of Physical Therapy. The machine uses a configuration of weights, pulleys and cables or belts to apply resistance against bio-mechanically correct leg movements by the exerciser. The progressive increase of the resistance weight leads to strengthening of the gluteus maximus, quadriceps and hamstring muscles. The database physical dimensions will accommodate a leg press machine or a plate loaded squat station.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			78	45	89	1,150 lb	1:	--	--	--	0	NO	NO	--					
			198	114	226	522 kg	2:	--	--	--	NO	NO	--						
G1013	6530	Exercise Machine, Chest	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--		
Chest press exercise machine for use in a gymnasium or the exercise area of Physical Therapy. The machine uses a configuration of weights, pulleys and cables or belts to apply resistance against bio-mechanically correct arm and chest movements by the exerciser. The progressive increase of the resistance weight leads to strengthening of the upper and lower arms, pectoralis and deltoid muscles. The database information is for a pectoral deck/fly machine (the most expensive of the chest machines).																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			80	53	70	585 lb	1:	--	--	--	NO	NO	--						
			203	135	178	266 kg	2:	--	--	--	NO	NO	--						
G1014	6530	Exercise Machine, Biceps	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--		
Biceps exercise machine for use in a gym or the exercise area of Physical Therapy. The machine uses a configuration of weights, pulleys and cables or belts to apply resistance against bio-mechanically correct arm movements by the exerciser. The progressive increase of the resistance weight leads to strengthening of the biceps muscle of the upper arm.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			61	41	44	600 lb	1:	--	--	--	NO	NO	--						
			155	104	112	273 kg	2:	--	--	--	NO	NO	--						
G1015	6530	Exercise Machine, Triceps	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--		
Triceps exercise machine for use in a gymnasium or the exercise area of Physical Therapy. The machine uses a configuration of weights, pulleys and cables or belts to apply resistance against bio-mechanically correct arm movements by the exerciser. The progressive increase of the resistance weight leads to strengthening of the triceps muscle on the back of the upper arm. The database information reflects the most expensive non-computerized triceps machine for each manufacturer.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			80	52	67	605 lb	1:	--	--	--	NO	NO	--						
			203	132	170	275 kg	2:	--	--	--	NO	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
G1018	6530	Exercise Machine, Hip Abduction	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Hip abduction exercise machine for use in a gymnasium or the exercise area of Physical Therapy. The machine uses a configuration of weights, pulleys, cams and cables or belts to apply resistance against bio-mechanically correct hip and leg movements made by the exerciser. The progressive increase of the resistance weight leads to strengthening of the outer hip and thigh muscles.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	60	66	70	590 lb	1:	--	--	--	NO							
		CM:	168	168	178	268 kg	2:	--	--	--	NO							
G1019	6530	Exercise Machine, Hip Adduction	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Hip adduction exercise machine for use in a gymnasium or the exercise area of Physical Therapy. The machine uses a configuration of weights, pulleys, cams and cables or belts to apply resistance against bio-mechanically correct hip and leg movements made by the exerciser. The progressive increase of the resistance weight leads to strengthening of the inner hip and thigh muscles. [The Universal Gym Equipment model is a total hip machine that provides exercises in adduction, abduction, flexion and hip-extension.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	66	67	65	600 lb	1:	--	--	--	NO							
		CM:	168	170	165	273 kg	2:	--	--	--	NO							
G1020	6530	Exercise Machine, Rotary Shoulder	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Internal/external rotation shoulder exerciser. The unit is used in a gym for physical development or in the exercise area of Physical Therapy for rehabilitation. The machine uses a configuration of weights, pulleys and cables or belts to apply resistance against bio-mechanically correct shoulder and arm movements by the exerciser. The progressive increase of the resistance weight leads to strengthening of the muscles which stabilize the shoulder joint. Many manufacturers offer range of motion limiters for specific applications. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	90	54	54	600 lb	1:	--	--	--	NO							
		CM:	229	137	137	273 kg	2:	--	--	--	NO							
G1021	6530	Exercise Machine, Pullover	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Pullover exercise machine for use in a gymnasium or the exercise area of Physical Therapy. The machine uses a configuration of weights, cams, pulleys and cables or belts to apply resistance against bio-mechanically correct shoulder, arm and upper body movements by the exerciser. The progressive increase of the resistance weight leads to strengthening the triceps, biceps, latissimus dorsi, rhomboids and other upper body muscle groups.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	71	48	71	770 lb	1:	--	--	--	NO							
		CM:	180	122	180	350 kg	2:	--	--	--	NO							
G1024	6530	Exercise Machine, Rowing	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Rowing exercise machine for use in a gymnasium or the exercise area of Physical Therapy. The machine simulates the resistance and motions of rowing or kayaking to give a simultaneous strength and aerobic conditioning workout. The machine consists of a seat on a rail or bench, cable pull or rigid oar handle, display and a variable resistance adjustment. Some manufacturers' higher line models offer heart rate monitoring.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	90	35	90	585 lb	1:	--	--	--	NO							
		CM:	229	89	229	266 kg	2:	--	--	--	NO							
G1026	6530	Exercise Apparatus, Weight Training, Multi-Station	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Multi-station weight training apparatus for physical development and rehabilitation. Unit features a variety of benches, pull bars, supports and seats grouped around a central frame containing one or more weight stacks. Each station is designed to exercise specific muscle groups. A person can perform an extensive weight training routine by moving around the apparatus from station to station. More than one person can use the apparatus simultaneously by training at different stations. The number and types of exercises available depend on the specific model of equipment chosen. Greater system weight capacities for high level athletic competition training are available on some models. The room ceiling may have to be raised to accommodate this equipment. The database specifications refer to a higher end system with a large number of training stations and a standard weight set. [This JSN is similar to JSN G1029. Recommend one or the other be deleted.]																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE 2:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	94	192	168	2,505 lb	--	--	--	--	NO	--		
			EA	CM: 239	488	427	1,138 kg	--	--	--	DEPENDENT:	NO	--		
G1027	6530	Exercise Machine, Closed Chain													
			Closed chain exercise machine used in physical therapy for rehabilitation and strengthening most major muscle groups. The machine offers quantitative measurement of ranges of motion and exercise protocols with partial weight bearing for earlier treatment. [This is the only manufacturer of this equipment. See the related equipment at JSN M8137.]												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE 2:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	54	36	84	100 lb	--	--	--	--	NO	--		
			EA	CM: 137	91	213	46 kg	--	--	--	DEPENDENT:	NO	--		
G1028	6530	Net, Volleyball w/Stanchions & Wires													
			Volleyball net including stanchions and guy wires for use in a gym. Poles require floor plates for installation. Dimensions refer to items consolidated and packed in a storage bag.												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE 2:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	24	72	24	100 lb	--	--	--	--	NO	--		
			EA	CM: 61	183	61	46 kg	--	--	--	DEPENDENT:	NO	--		
G1030	6530	Platform, Referee, Volleyball w/Pads													
			Volleyball referee platform with protective pads for use in a gym.												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE 2:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	93	38	38	75 lb	--	--	--	--	NO	--		
			EA	CM: 236	97	97	34 kg	--	--	--	DEPENDENT:	NO	--		
G1031	6530	Floor Cover, Rubber, Interlock													
			Interlocking rubber floor covering for use in a gymnasium. Database cost is for colored, 5/16" or 3/8" thick matting priced per square foot. [Price is based on center piece per square foot. Corner and end pieces are also available.]												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE 2:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	1	12	12	5 lb	--	--	--	0	NO	--		
			EA	CM: 3	30	30	3 kg	--	--	--	DEPENDENT:	NO	--		
G1032	6530	Rack, Barbell Weight													
			Rack or tree for holding barbell plate weights. The unit can be of upright, A-frame or other heavy duty construction. The rack is designed to hold and separate different sizes of exercise weights for easy removal and return to storage. Different models have different holding capacities. Several racks may be necessary to hold a sufficient quantity of standard weights in an exercise or rehabilitation facility. Some models also store weightlifting bars as well as the weights.												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE 2:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	49	41	41	76 lb	--	--	--	--	NO	--		
			EA	CM: 124	104	104	35 kg	--	--	--	DEPENDENT:	NO	--		
G1033	6530	Exercise Machine, Back Extension													
			Back extension bench for strengthening the lower back muscles. Many manufacturers offer range of motion limiters for specific applications. The unit is used in a gym for physical training or in a physical therapy rehabilitation regimen.												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE 2:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	61	50	57	609 lb	--	--	--	0	NO	--		
			EA	CM: 155	127	145	277 kg	--	--	--	DEPENDENT:	NO	--		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
G1034	6530	Exercise Machine, Shoulder	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Shoulder press machine for use in a gymnasium or the exercise area of physical therapy. The manufacturers have different types and different names for the machines for this JSN. These include the lateral raise, shoulder press, seated incline press, overhead press and military press. The machine uses a configuration of weights, pulleys and cables or belts to apply resistance against bio-mechanically correct shoulder and arm movements by the exerciser. The progressive increase of the resistance weight leads to strengthening of the shoulder and upper chest muscles. [Price difference verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			68	53	71	700 lb	1:	--	--	--								
			173	135	180	318 kg	2:	--	--	--								
G1035	6530	Kit, Wallyball	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Wallyball kit includes ball, net, net tightener, storage bag, rule book and hardware. The kit is used to convert a racquetball court to play wallyball (a variant of volleyball). The kit is installed on a hook embedded in the walls of the court or by using suction cups on glass walls. Database dimensions refer to the items in the storage bag.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			12	36	12	20 lb	1:	--	--	--								
			30	91	30	9 kg	2:	--	--	--								
G1036	6530	Weight Set, Exercise, Barbell Plate	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Cast iron plate weights for use with barbells and weightlifting equipment. Set consists of a variety of different weight plates marked in pounds and kilos, weight lifting bar(s), and securing collars. Database information is for a large Olympic specification weight set (approx. 500 lb.) Stacked on the floor with a weightlifting bar, one set of collars, (6) 45-lb. Plates, (2) 35-lb. Plates, (2) 25-lb. Plates, (2) 10-lb. Plates, (4) 5-lb. Plates and (2) 2.5-lb. Plates. Different manufacturers offer differing configurations of weight plates and bars. This set may also be purchased conveniently from local sports distributors.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			30	24	72	490 lb	1:	--	--	--								
			76	61	183	223 kg	2:	--	--	--								
G1037	6530	Weight Set, Exercise, Dumbbell	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Set of weightlifting dumbbells for use in physical training or rehabilitation. Weights can be plain metal, rubber cushioned metal or chrome plated and are in matched pairs at each weight increment. Database information refers to a large set of matched weights increasing in 5-lb. Increments range approximately from 20 to 115 lb. (20 pairs of weights) stacked on the floor. Differing manufacturers may offer more or less extensive selections. The individual facility's requirement will determine the exact set configuration and cost. See JSN G1040 for the racks to hold these weights. [Most 20 pair,5-lb increment, weight sets start at 5-lb and end at 100-lb.]																		
UNIT OF ISSUE:		ST	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			18	91	48	2,700 lb	1:	--	--	--								
			46	231	122	1,226 kg	2:	--	--	--								
G1038	6530	Bar, Weightlifting	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Bar designed to hold plate weights for weight training or rehabilitation. This JSN should be used for bars not otherwise included in weight sets (see JSN G1036). Typical bars include curling bars bent at the handgrip area to facilitate biceps development, Olympic length power lifting bars (7'), and trap and biceps/triceps bars which have handgrips which rotate to fixed positions inside a retaining ring. Database information reflects a 7' length Olympic specification bar since it is the most expensive optional bar readily available. [Width and depth dimensions are for the diameter of the bar. The height is the length.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			87	2	2	50 lb	1:	--	--	--								
			221	5	5	23 kg	2:	--	--	--								
G1040	6530	Rack, Dumbbell	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Rack for holding dumbbells in a gym or rehabilitation facility. The manufacturers provide several different rack styles and capacities depending on the number and type of dumbbells the rack(s) will hold. The database information is for a double rail rack holding twenty (ten pairs) of full size metal plate dumbbells.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			35	31	97	259 lb	1:	--	--	--								
			89	79	246	118 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
G1041	6530	Exercise Machine, Leg Curl	C C C C --	--	--	--	--	--	--	--	--	--	--
Leg curl machine for unilateral and bilateral exercising and strengthening of the hamstring muscles. The unit features padding or a bench configuration to restrict upper leg movement during the exercise, adjustable resistance settings and support rails. Some manufacturers' equipment features a sitting exercise position; on other manufacturers' machines, the exerciser lies on his or her stomach. Many manufacturers offer range of motion limiters for specific applications.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	68	42	60	498 lb	1:	--	--	--	NO		
		CM:	173	107	152	226 kg	2:	--	--	--	NO	--	
G1042	6530	Exercise Machine, Leg Extension	C C C C --	--	--	--	--	--	0	NO	--		
Leg extension machine for unilateral or bilateral strengthening and development of the quadriceps muscles. The unit features easily selectable variable resistance and is used in a gym or a rehabilitation therapy protocol. Many manufacturers offer range of motion limits for specific applications.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	61	44	55	600 lb	1:	--	--	--	NO		
		CM:	155	112	140	273 kg	2:	--	--	--	NO	--	
G1043	6530	Ergometer, Recumbent Bicycle, Computer Assisted	C C C C --	--	A	--	--	--	0	NO	--		
Computer assisted recumbent bicycle aerobic trainer. The trainer provides aerobic workouts on a computer controlled and monitored recumbent bicycle ergometer. The ergometer has several training routines and intensities which either the exerciser or a therapist can select. The unit display provides a readout of work accomplished as well as graphics to motivate the exerciser. Many models offer optional heart rate monitoring and wheels for easy mobility. Depending on the manufacturer and model, the computer is powered by the exerciser or an external source. The database electrical requirements are for those units requiring electrical power. The trainer is used for cardio-respiratory development in a gym or the exercise area of Physical Therapy. [None of these models require external power.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	52	25	64	188 lb	1:	110	1	2	NO		
		CM:	132	64	163	86 kg	2:	--	--	--	YES	--	
K0450	7310	Curtain, Air	A A A A --	--	G	--	--	--	60	YES	--		
Air curtain. The unit is generally fabricated to size for operation. This unit is used at entrances and docks to prevent cold and humid or dry and hot air from entering through openings which are exposed to weather conditions. The database pricing reflects an unheated air door 6-1/2' wide with a 3" or 6" deep discharge nozzle to cover a standard two-door width entry. Some units run on 120V power; refer to the manufacturer's specifications for the model chosen. Larger width and industrial duty air doors are available. [Price variance verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	22	89	52	260 lb	1:	208	3	4	YES		
		CM:	56	226	132	118 kg	2:	--	--	--	YES	--	
K0500	7310	Baker, Waffle, Dual Plate	C C C C --	--	F	--	--	--	60	NO	--		
Waffle baker. The baker has two 7 inch diameter pans, side by side in a single machine or is two single pan units side by side. The grids are removable for cleaning and the cabinet is constructed of stainless steel. The database height dimensions are for an open pan. Two separate electrical outlets may be needed for two single units operating side by side. It is used in large restaurants and food service operations for hot waffles. [Heartland Food Products (CAGE SR086) and SFP Food Products (Cage 05JR3) offer their waffle irons free to clients using their batter mixes.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	22	20	16	41 lb	1:	120	1	15	NO		
		CM:	56	51	41	19 kg	2:	--	--	--	YES	--	
K0700	7310	Bin, Ingredient, Mobile, 150 Lb. Capacity	C C C C --	--	--	--	--	--	0	NO	--		
Mobile ingredient bin. This unit has a 150 lb. capacity with a slide-off or lifting cover. The unit is constructed of stainless steel or durable plastic with 4 inch casters. A one piece rubber bumper encircles stainless steel models. This bin is used to store ingredients in commercial and institutional food service operation. [Price difference verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	28	23	22	50 lb	1:	--	--	--	NO		
		CM:	71	58	56	23 kg	2:	--	--	--	NO	--	

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K0710	7310	Bin, Ingredient, Mobile, 250 Lb. Capacity	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Mobile ingredient bin. This unit has a 250 lb. capacity with a slide-off or lifting cover. The unit is constructed of stainless steel or durable plastic with 4 inch casters. A one piece rubber bumper encircles stainless steel models. This bin is used to store ingredients in commercial and institutional food service operations. [Price difference verified. Model 2 is stainless steel while the other two models are heavy duty plastic.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			29	23	30	60 lb	1:	--	--	--								
			74	58	76	28 kg	2:	--	--	--								
K0800	7310	Blender, Heavy Duty, 1 Gal, CRS Bowl	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Heavy duty blender. This is a one gallon blending device with a stainless steel container. It has a heavy duty motor with a 3 speed switch. The unit is used to blend foods in restaurants and hospital kitchens. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			23	9	9	38 lb	1:	120	1	10								
			58	23	23	18 kg	2:	--	--	--								
K0810	7310	Blender, Heavy Duty, 1/2 Gal, CRS Bowl	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Heavy duty blender. This is a 64 ounce capacity blender with a stainless steel container. It has a four cutter, one piece stainless steel blade. The unit is used to blend foods in commercial restaurants, hotels and hospital kitchens. [No other source(s) identified with this description/specification. All the distributors we found, carry either one or both of these lines.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			14	7	7	15 lb	1:	120	1	8								
			35	18	18	7 kg	2:	--	--	--								
K0820	7310	Breader, Mobile, Manual	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Mobile breadmaking machine. The unit is made of stainless steel and has a fully enclosed 1/4 HP motor to drive the sifter. Equipped with counter compartments, a storage bucket and heavy duty casters. [Model 3 is refrigerated which is reason for difference in price. This feature helps promote safety during food preparation.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			55	68	37	180 lb	1:	120	1	7								
			140	173	94	82 kg	2:	--	--	--								
K0830	7310	Breader, Table Mounted, Automatic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Table mounted breadmaking machine. This breader has a semi-automatic gravity feed which moves food pieces through the rotating breadmaking drum. The drum is removable for cleaning. The machine can bread up to 400 lb. of food per hour. [No other source(s) identified with this description/specification for a table top model breadmaking machine. AyrKing Corporation makes a compact model (BBS-EC-3814) with a work table of 38" W x 15" D.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			21	33	16	70 lb	1:	120	1	2								
			53	84	41	32 kg	2:	--	--	--								
K0860	7310	Broiler, Infrared, Gas, Dual	A	A	A	A	--	--	A	--	--	--	A	E				
<p>Dual infrared broiler. The unit features two broiling units which are heated by the power blown combustion of natural gas in the vicinity of ceramic tile infrared generators. The unit has gas pressure regulators and pilot lights. Each broiling grid moves on roller bearings and its distance from the tiles can be adjusted using a manual lever. The broiler has a stainless steel front and top; stainless steel sides are available. The database height dimension is for the greatest height in the manufacturers' series of this type of oven. The unit is used in commercial kitchens and hospitals for large volume food preparation.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	208,000	--
			82	36	39	1,100 lb	1:	120	1	10								
			208	91	100	495 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K0870	7310	Broiler, Infrared, Electric, Double	A	A	A	A	--	--	G	--	--	--	--	E				
<p>Infrared broiler. This is an electrically operated, stand mounted broiler with a stainless steel front and sides. The unit is equipped with solid sheathed overhead broiler elements and two infinite head controls. A stainless steel back is optional and the unit is also available without a supporting cabinet for counter mounting. The broiler is also available mounted over an oven. The unit is used in hospitals and commercial food preparation areas. [Only two sources could be found that provide electric infrared broilers as described. Other double broilers found are gas operated similar to JSN K0860.]</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:			
			CM:	87	36	39	940 lb	1:	208	3	67		DEPENDENT:	YES	--			
				221	91	99	427 kg	2:	--	--	--							
K0900	7310	Broiler, Char-Broiler, 1 Grid	A	A	A	A	--	--	G	--	--	--	E					
<p>Char-broiler. This is a counter model with one self-cleaning grid and 4 inch legs. Below the grid, channels route grease to a collection drawer for easy removal. See the manufacturers' specifications for required clearances from combustible materials. The unit is used in commercial kitchen and hospital cooking areas to prepare hamburgers and other quick broiling foods. [No other source(s) identified with this description/specification. Hobart,(Cage Code # 28873), and Toastmaster, (Cage Code # 78770), have both recently discontinued they're lines of Char-Broilers. No replacements were offered.]</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:			
			CM:	21	30	26	128 lb	1:	208	3	42		DEPENDENT:	YES	--			
				54	76	66	58 kg	2:	--	--	--							
K0950	7310	Broiler, Char-Broiler, 2 Grid	A	A	A	A	--	--	G	--	--	A	E					
<p>Char-broiler. This unit is stand mounted with two self-cleaning grids and 4 inch legs. Below the grids, channels route grease to a collection drawers for easy removal. See the manufacturers' specifications for required clearances from combustible materials. The unit is used in commercial kitchen and hospital cooking areas to prepare hamburgers and other quick broiling foods. [Model 1 is electric. Models 2 and 3 are gas.]</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:			
			CM:	18	48	30	425 lb	1:	208	3	42		DEPENDENT:	YES	--			
				46	122	76	193 kg	2:	--	--	--							
K1000	7310	Cabinet, Pastry, Mobile, Medium	A	A	A	A	--	--	--	--	--	--	--					
<p>Mobile pastry cabinet. The cabinet is made from aluminum or stainless steel, is mounted on four swivel casters and holds thirty 18 inch by 26 inch full sheet pans. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). Smaller capacity units are available. For larger capacity units see JSN K1010. The cabinet is used for storage and transport of pastries in hotels, restaurants, hospitals, and commercial food service operations. [Model 3 is stainless steel. The other two models are aluminum.]</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:			
			CM:	67	27	33	1,190 lb	1:	--	--	--		DEPENDENT:	NO	--			
				170	69	84	541 kg	2:	--	--	--							
K1010	7310	Cabinet, Pastry, Mobile, Large	A	A	A	A	--	--	--	--	--	--	--					
<p>Mobile pastry cabinet. This is a heavy duty, aluminum or stainless steel unit on four swivel casters which holds approximately forty 18 inch by 26 inch full sheet pans. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). See JSN K1000 for smaller capacity units. The cabinet is used for storage and transport of pastries in hotels, restaurants, hospitals, and commercial food service operations.</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:			
			CM:	70	25	32	136 lb	1:	--	--	--		DEPENDENT:	NO	--			
				178	64	81	62 kg	2:	--	--	--							
K1020	7310	Cabinet, Heated, Food, Mobile, Large	A	A	A	A	--	--	B	--	--	--	--					
<p>Insulated food warming cabinet. The cabinet is made of aluminum or stainless steel and is mounted on four heavy duty casters. The interior of the cabinet has slide ledges on both sides spaced at 1-1/2 inch intervals. The unit holds thirty or more 18 inch by 26 inch full size pans or trays. Double door and non-insulated cabinets are available, the second door reduces the tray capacity by one. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). The cabinet is used in commercial and hospital kitchens for food storage prior to serving.</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:			
			CM:	70	29	37	480 lb	1:	120	1	17		DEPENDENT:	YES	--			
				178	74	94	218 kg	2:	--	--	--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES										
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5
K1030	7310	Cabinet, Hot/Cold, Food, Mobile, Counter Height	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--
		Half-height food holding cabinet (adjunct to cafeteria counter) which can heat stored food or keep it cold. The cabinet is made of corrosion resistant steel, is fully insulated, has a full length hinged door with lock, has four lifting handles and has channel type interior slides to hold seven or eight 12 inch wide, 20 inch long and 2-1/2 inch deep pans. The cabinet will also hold 4 inch and 6 inch deep pans. The cabinet has a heating unit, a cold holding plate or cooling unit and four 4 inch casters. For dual compartment cabinets, see JSN K6250. This unit is used to hold hot and cold food in commercial kitchens and hospitals. [Only one source was found that meets this description.]															
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
		EA	IN: 42	30	26	237 lb	1: 120	1	9	60	NO	--					
			CM: 107	76	66	108 kg	2: --	--	--	DEPENDENT:	YES	--					
K1040	7310	Cabinet, Proofing, Mobile	A	A	A	A	--	--	B	--	--	--	--	--	--	--	
		Mobile proofing cabinet. The cabinet is made of stainless steel or aluminum and is mounted on four heavy duty casters. The cabinet has a temperature control, a temperature gauge and an on-off timer. The unit is designed to produce large quantities of raised dough of uniform quality. It is used in commercial and hospital kitchens for high volume baking and warming foods. [Pricing is for aluminum constructed cabinets.]															
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
		EA	IN: 73	31	33	212 lb	1: 120	1	14	60	NO	--					
			CM: 185	79	84	97 kg	2: --	--	--	DEPENDENT:	YES	--					
K1050	7310	Cabinet, Proofing, Counter Top	A	A	A	A	--	--	A	--	--	--	--	--	--		
		Counter mounted or undercounter proofing cabinet. The unit is made from stainless steel or aluminum and can have one or two doors. The interior supports hold 18" x 26" baking pans or racks. Some models run on 120V rather than 208V power; refer to the manufacturers' specifications. The unit may be wall or undercounter mounted for space savings. [The term "undercounter" has been added to the Description to allow for more sources. Eagle Group (www.eaglegrp.com) and EPCO (www.epco-cabinets.com) also make undercounter or half size models.]															
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
		EA	IN: 35	60	40	245 lb	1: 120	1	27	60	NO	--					
			CM: 89	152	102	112 kg	2: --	--	--	DEPENDENT:	YES	--					
K1140	7310	Cabinet, Refrigerated, Mobile	A	A	A	A	--	--	A	--	--	--	--	--			
		Mobile refrigerated cabinet for food storage. This unit is designed with pan slides, a compressor, a condensate evaporator and stainless steel construction. Most models have doors whose hinges are set or have springs to cause the doors to automatically swing closed. This unit is used for cold storage in large commercial and hospital kitchens.															
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
		EA	IN: 84	32	38	452 lb	1: 120	1	10	60	NO	--					
			CM: 213	81	97	206 kg	2: --	--	--	DEPENDENT:	YES	--					
K1160	7310	Cabinet, Warming, Pass-Thru, CRS	A	A	A	A	--	--	D	--	--	--	--				
		Mobile or stationary warming cabinet. This is a pass-through model with doors that can be opened from either side for easy use. The cabinet can have single or double Dutch doors on either or both sides. The unit has an exterior temperature gauge for easy monitoring. The cabinet has a slide in humidity pan or controlled humidity vents in the top of the cabinet. Some models run on 120V power, others on 208V. Refer to the manufacturers specification sheets. The database electrical specifications cover both possibilities. The unit is used in commercial and hospital kitchens for warming prepared food items.															
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
		EA	IN: 84	33	40	370 lb	1: 120	1	12	60	NO	--					
			CM: 213	84	102	168 kg	2: 208	1	8	DEPENDENT:	YES	--					
K1240	7310	Transport Cart, Meal Tray, Heated, Large	C	C	C	C	--	--	B	--	--	--	--				
		Heated meal tray transport cart for delivering food. This cart is used for maintaining cooked food at serving temperatures while waiting to be moved or while en route to wards or other areas of the hospital. The unit has 5 or 6 inch diameter heavy duty casters and durable stainless steel construction welded to withstand severe service. The cabinet generally has three hinged doors and the interior compartment(s) hold a wide variety of prepared meal trays. Some manufacturers offer combination heated/refrigerated carts. The cabinet is used in food service operations for mobile storage, bussing and general food handling in hotels, restaurants, schools and healthcare facilities. [Price variance verified.]															

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE: EA	HEIGHT IN: 67 CM: 170	WIDTH 66 DEPTH 81	DEPTH 32 WEIGHT 590 lb 268 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 13 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --				
K1250	7310	Transport Cart, Meal Tray, 3 Door, Standard Height	C	C	C	C	--	--	--	--	--				
Standard height, three compartment food tray cart. This is a non-heated, centralized tray service unit with 6" diameter (or larger) casters. The unit is designed to move approximately twenty 14" x 18" or 15" x 20" food trays quickly from centralized kitchens to distant service areas while insuring the food arrives fresh and without loss of flavor. The unit is also used to return used trays to the kitchen for cleaning. Larger, smaller and low profile configurations are available. [No other source(s) identified with this description/specification.]															
			UNIT OF ISSUE: EA	HEIGHT IN: 55 CM: 140	WIDTH 66 DEPTH 79	DEPTH 31 WEIGHT 500 lb 227 kg	VOLTS 1: -- 2: --	PHASE -- --	AMPS -- --	HZ: -- HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --				
K1260	7310	Transport Cart, Meal Tray, w/Beverages	C	C	C	C	--	--	F	--	--				
Meal tray cart. This is a centralized service unit mounted on four 6" casters or tires and capable of carrying approximately twenty 15" x 20" meal trays. The cart includes two to four beverage wells with faucets or a shelf which holds 5-gallon insulated jugs. Some units feature refrigerated and heated sections and require special electrical outlets. The unit is designed to move food and beverages quickly from centralized kitchens to distant service areas such as banquets or remote patient areas while insuring the food arrives kitchen-fresh and without loss of flavor. This unit is used in hospitals and other patient care facilities for food service.															
			UNIT OF ISSUE: EA	HEIGHT IN: 69 CM: 175	WIDTH 71 DEPTH 76	DEPTH 30 WEIGHT 575 lb 261 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 16 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --				
K1280	7310	Transport Cart, Meal Tray, 2 Door, Standard Height	C	C	C	C	--	--	--	--	--				
Standard height, two compartment meal tray cart. This is a centralized tray service unit with stainless steel construction, a bumper and four 6" casters to withstand heavy duty cart washing. The cart will hold about 28 meal trays depending on the interior slide separation. The unit is used in hospitals, schools and hotels for food service.															
			UNIT OF ISSUE: EA	HEIGHT IN: 44 CM: 112	WIDTH 65 DEPTH 97	DEPTH 38 WEIGHT 440 lb 200 kg	VOLTS 1: -- 2: --	PHASE -- --	AMPS -- --	HZ: 0 HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --				
K1285	7310	Cart, Buffet, Medium	C	C	C	C	--	--	--	--	--				
Medium size buffet cart. The cart can support self service items such as a large soup tureen or coffee service. The unit has stainless steel construction and heavy duty casters. The cabinet top can be stainless steel or wood laminate. Two casters are fixed and two casters swivel and have brakes. Varying models have laminated sides over the stainless steel and storage areas beneath the cart top.															
			UNIT OF ISSUE: EA	HEIGHT IN: 39 CM: 99	WIDTH 41 DEPTH 81	DEPTH 32 WEIGHT 225 lb 103 kg	VOLTS 1: -- 2: --	PHASE -- --	AMPS -- --	HZ: 0 HZ SWITCH: NO DEPENDENT: NO	BTUs / HR: --				
K1350	7310	Washer, Pressure, Mobile w/Sanitizer	C	C	C	C	--	D	A	--	--				
Pressure washer for cleaning and sanitizing kitchen or other areas. This is a mobile, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. Refer to K9300 for a fixed version of this equipment. The unit is used for cleaning in commercial areas and institutions such as hospitals. [Models 1 and 2 are 110-115V units while Model 3 is a 220V unit.]															
			UNIT OF ISSUE: EA	HEIGHT IN: 40 CM: 102	WIDTH 25 DEPTH 81	DEPTH 32 WEIGHT 190 lb 87 kg	VOLTS 1: 115 2: 220	PHASE 1 1	AMPS 15 9	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K1550	7310	Brewer, Coffee, Auto, Elect, 3 Burner, Side/Side	A	A	A	A	--	B	A	--	--	--	--	--	--	--	--	
Side by side automatic coffee maker. This unit includes a heating tank, a connection for a cold water supply, a decanter service with three burners, a funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in office building cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). Larger size units are available.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--
			CM:	18	17	18	37 lb	1:	120	1	15							
				46	43	46	17 kg	2:	--	--	--							
K1552	7310	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	C	C	C	C	--	J	A	--	--	--	--	--	--	--	--	
Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--
			CM:	22	9	18	37 lb	1:	120	1	15							
				56	23	46	17 kg	2:	--	--	--							
K1580	7310	Conveyor, Meal Tray Makeup, CRS	A	A	A	A	--	--	B	--	--	--	--	--	--	--	--	
Food conveyor. This is an all stainless steel food portioning and packaging unit with 5" inch casters or optional fixed feet. This system is used to assemble meal trays for feeding patients in wards and other remote locations. Many lengths and configurations are available. The database information refers to a 12' long unit. This system should be specified to conform with the institution's requirement.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--
			CM:	37	144	22	704 lb	1:	120	1	20							
				94	366	56	320 kg	2:	--	--	--							
K1600	7310	Counter, Cafeteria, Cold Food, Mobile, 5-Pan	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	
Mobile cold food cafeteria counter. The counter features a refrigeration unit with coils around the counter compartment, an open compartment top which can hold five 12" x 20" pans, a double display shelf above the counter unit, sneeze guards, a drop-type solid or three rail tray slide, a server's workshelf, open shelving on the server's side and four 5" swivel casters. Some manufacturers offer a second refrigerated section below the cold pan. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the fold down tray rail but does include the 8-10" working shelf on the server's side. The unit is used for self-service of cold food in cafeterias and commercial food service areas.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--
			CM:	60	78	42	575 lb	1:	120	1	10							
				152	198	107	261 kg	2:	--	--	--							
K1610	7310	Counter, Cafeteria, Cold Food, Mobile, 4-Pan	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	
Mobile cold food cafeteria counter. The counter features a refrigeration unit with coils around the counter compartment, an open compartment top which can hold four 12" x 20" pans, a double display shelf above the counter unit, sneeze guards, a drop-type solid or three rail tray slide, a workshelf on the server's side, open shelving below the cold pan and four 5" swivel casters. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the fold down tray rail but does include the 8-10" working shelf on the server's side. The unit is used for self-service of cold food in cafeterias and commercial food service areas.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--
			CM:	60	64	40	525 lb	1:	120	1	8							
				152	163	102	239 kg	2:	--	--	--							

JSN	NSN	NOMENCLATURE	CATEGORY:		UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K1620	7310	Counter, Cafeteria, Filler, Approximately 36x80x32	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Cafeteria counter. This is a stainless steel flat top counter with a drop type tray slide and four 5-inch casters. The unit is available with cutouts and with many other options. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the depth of the fold down tray rail slide. This unit is used for self-service of meals in cafeterias of hospitals, schools and commercial food service operations.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			36	91	79	31	329 lb	1:	--	--	--							
			79	201	79	150 kg	2:	--	--	--								
K1630	7310	Counter, Cafeteria, Filler, Approximately 39x74x33	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Cafeteria counter. This is a stainless steel, mobile filler counter that is generally configured to specifications. The unit should include a drop-type solid or three rail tray slide, a removable glass protective front; and four 5-inch casters. Some manufacturer's equipment features a decorative canopy. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the depth of the drop-type tray slide. The unit is used for self-service of meals in cafeterias, hotels, restaurants and hospital food service areas. Dimensions are determined by configuration.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			36	91	74	33	436 lb	1:	--	--	--							
			74	188	84	198 kg	2:	--	--	--								
K1640	7310	Counter, Cafeteria, Filler, Approximately 52x50x30	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Cafeteria counter. This is a stainless steel, mobile filler counter that is generally configured to specifications. The unit should include a drop-type solid or three rail tray slide, a removable glass protective front and four 5-inch casters. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the depth of the drop-type tray slide. The unit is used for self-service of meals in cafeterias, hotels, restaurants and hospital food service areas. [Price difference verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			52	132	50	30	350 lb	1:	--	--	--							
			50	127	76	159 kg	2:	--	--	--								
K1650	7310	Counter, Cafeteria, Hot Food, Mobile, 5-Pan	A	A	A	A	--	--	--	--	--	--	C	--	--	--	--	--
Mobile, hot food cafeteria counter. This unit has a top compartment capable of holding five (5) 12" by 20" pans, a full length food display shelf with sneeze guard, a drop-type solid or three rail tray slide, four (4) 5 inch swivel casters, shelving underneath the warming wells and a work shelf on the server's side. The complete unit is insulated as is each well. Each well is also individually thermostatically controlled with an individual heating element. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the fold down tray rail but does include the 8-10" working shelf on the server's side. The unit is used in hospitals, schools and commercial food service establishments. [Price difference verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			52	132	78	40	420 lb	1:	208	1	28							
			78	198	102	191 kg	2:	--	--	--								
K1690	7310	Conveyor, Tray, Electric, Moveable	A	A	A	A	--	--	--	--	--	--	A	--	--	--	--	--
Tray conveyor. This is a moveable unit constructed of stainless or zinc plated steel with a 1/2 HP electric motor driving the conveyor belt. When not in use, the unit can be pushed to the side. The database pricing is for a 8' - 9' conveyor. Longer length models are available; see related conveyers at JSN K1580. This conveyor moves food trays from one area to another with minimal worker effort in the kitchens and food serving areas of restaurants, schools and hospitals. [Price variance verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			38	97	120	21	695 lb	1:	120	1	5							
			21	305	53	316 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K1695	7310	Conveyor, Meal Tray Return	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Fixed conveyor for returning soiled meal trays from the main dining room to the tray processing area for cleaning. The database pricing is per linear foot based on a 24 feet of straight conveyor and 4 corner sections. This conveyor could lead to a second conveyor for tray processing or directly to a dishwasher with tray processing en route. Multiple power outlets will be required depending on the conveyors length. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	34	720	24	880 lb	1:	120	1	15	60	NO	--					
		CM:	86	1829	61	400 kg	2:	--	--	--	60	YES	--					
K1700	7310	Counter, Cafeteria, Utility, W/ Power 57x50x40	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Mobile utility cafeteria counter. The unit can serve as a mobile utility table and has a double-shelf food display case with sneeze guard, a drop-type solid or three rail tray slide, 120V AC, 10A convenience outlets, a control panel, a server's side work shelf, a lower work shelf and four 5-inch swivel casters. Multiple facility-level outlets may be required depending on the number of convenience outlets the end user requires. See the base counter at JSN K1640. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the fold down tray rail but does include the 8-10" working shelf on the server's side. This unit is used in commercial and hospital food service areas. [Accessories for Model 1 and 3 include tray slide, work shelf, double deck display case with guard, under shelves and convenience outlets and are reflected in the price for each model. Model 2 accessories are shown as options.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	57	50	40	415 lb	1:	120	1	20	60	NO	--					
		CM:	145	127	102	189 kg	2:	--	--	--	60	YES	--					
K1710	7310	Counter, Cafeteria, Utility, W/Power 61x80x42	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Mobile cafeteria counter. The counter can serve as a mobile utility table and has a double-shelf food display case with sneeze guard, a drop-type solid or three rail tray slide, 120V AC outlets, a work shelf, below the counter shelves and four 5-inch swivel casters. The end user must specify the outlet requirements and configuration. Multiple facility-level outlets may be required depending on the number of convenience outlets the end user requires. The database depth dimension does not include the fold down tray rail but does include the 8-10" working shelf on the server's side. This unit is used in commercial and hospital service areas. [Database price is for 2 electrical outlets per unit. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	61	88	42	700 lb	1:	120	1	20	60	NO	--					
		CM:	155	224	107	318 kg	2:	--	--	--	60	YES	--					
K1720	7310	Counter, Cafeteria, Utility, W/Power 36x50x40	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Mobile cafeteria utility counter. The unit is made of stainless steel, can serve as a mobile utility table and has an open working side with bottom and intermediate shelves, a drop-type solid or three rail tray slide, four 5-inch swivel casters and 120V AC outlets. User must specify outlet requirements and configuration. Multiple facility-level outlets may be required depending on the number of convenience outlets the end user requires. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the fold down tray rail but does include the 8-10" working shelf on the server's side. This unit is used in commercial and hospital food service areas.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	36	50	39	314 lb	1:	120	1	15	60	NO	--					
		CM:	91	127	99	143 kg	2:	--	--	--	60	YES	--					
K1730	7310	Counter, Cafeteria, Utility, W/Power 48x64x32	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Mobile cafeteria utility counter. This is a stainless steel unit with a sneeze guard, a drop-type solid or three rail tray slide, intermediate and bottom shelves, four 5-inch swivel casters and two 120V AC outlets in the control panel below work shelf. The end user must specify outlet requirements and configuration. The database depth dimension does not include the tray slide. The database width and depth dimensions vary slightly according to manufacturer. The counter height is 36". Multiple facility level connections may be required for powering this unit. This unit is used in commercial and hospital service areas.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	48	64	32	504 lb	1:	120	1	20	60	NO	--					
		CM:	122	163	81	229 kg	2:	--	--	--	60	YES	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
K1740	7310	Counter, Cafeteria, Utility, W/Power 57x50x42	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--			
<p>Mobile cafeteria solid top utility counter. The counter has a double-shelf food display case with sneeze guard, a drop-type solid or three rail tray slide, intermediate and bottom shelves, four 5-inch swivel casters, a work shelf, two 120V AC outlets on left side and two 120V AC outlets on right in the control panel below work shelf. Multiple facility level outlets may be required for connecting power to these outlets. User must specify outlet requirements and configuration. The database height dimension includes the above-counter double shelf. The depth dimension includes the depth of the work shelf but not the depth of the tray slide. See closely related units at JSN K1700. This unit is used by commercial and hospital service areas. [The original description had 208V outlets in it. All the manufacturers offer 120V outlets as a standard option and 208V outlets as a custom option only.]</p>			UNIT OF ISSUE:		HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	VOLTS 1:	PHASE 1:	AMPS 1:	VOLTS 2:	PHASE 2:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
			EA	57	145	54	137	42	107	453 lb	120	1	20	--	--	--	60	NO	NO	--
K1750	7310	Counter, Cafeteria, Mobile, Utility	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Mobile cafeteria counter, approximately 36"H x 80"L x 32"D. The counter is made of stainless steel construction, has intermediate and bottom shelves on the working side, a drop-type solid or three rail tray slide and 5-inch swivel casters. The database depth does not include the depth of the tray slide. It is used for service of food items in hospitals and restaurants.</p>			UNIT OF ISSUE:		HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	VOLTS 1:	PHASE 1:	AMPS 1:	VOLTS 2:	PHASE 2:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
			EA	36	92	85	216	32	81	614 lb	--	--	--	--	--	--	NO	NO	--	
K1760	7310	Counter, Cafeteria, Mbl, Util, W/Power 36x39x28	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--	--	
<p>Cafeteria counter. The counter is made of stainless steel construction, has a drop-type solid or three rail tray slide, has stainless steel middle and bottom shelves on the working side, has six 120V AC outlets and has four 5-inch swivel casters. Multiple facility level outlets may be required to supply power for this unit. This unit is used in commercial and hospital service areas. [This is the only manufacturer making a standard counter this length. The original description had 208V outlets in this counter. These outlets are now a custom option only. The original description also had a double deck display case on top of this counter; that option is no longer available.]</p>			UNIT OF ISSUE:		HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	VOLTS 1:	PHASE 1:	AMPS 1:	VOLTS 2:	PHASE 2:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
			EA	35	89	36	91	31	79	170 lb	120	1	20	--	--	--	60	NO	YES	--
K1800	7310	Sink/Drainboard, Dishwashing, Triple Bowl	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	--	
<p>Triple bowl dishwashing sink with two drainboard counters. The sink is made of 16 gauge stainless steel, has three 20" x 20" sink bowls, has supporting legs and/or wall attachment points and is pre-drilled for faucet and drain connections. Custom sized units are available. The database price includes the cost of welding the disposal cone to the bottom of one sink. See JSN K2620 for disposal units and JSN K9320 for accessory spray arms. The database height dimension is to the top of the backsplash; see the specification sheets for the sink rim height. Larger and smaller units are available as well as units with fewer sink bowls. This unit is used to wash dishes in institutions and commercial kitchens.</p>			UNIT OF ISSUE:		HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	VOLTS 1:	PHASE 1:	AMPS 1:	VOLTS 2:	PHASE 2:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
			EA	45	114	115	292	27	69	199 lb	--	--	--	--	--	--	NO	NO	--	
K1850	7310	Sink, Pot, Double Compartment, w/Drainboards	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	--	
<p>Pot washing and scraping counter. This unit has two sink compartments, one for rinse and one for wash, and is constructed of stainless steel. The dimensions should be specified as required. See JSN K2620 for disposers and K9320 for pre-rinse hoses. This unit is used to wash pots in food service operations of hospitals, hotels and restaurants. [Extra lengths of counter/drainboard or provisions for a disposal unit on either side of the sink are custom alterations and not included in the above data. Database pricing is for a 24" x 24" sink with (2) 24" each drainboards.]</p>			UNIT OF ISSUE:		HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	VOLTS 1:	PHASE 1:	AMPS 1:	VOLTS 2:	PHASE 2:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
			EA	45	114	98	249	33	84	175 lb	--	--	--	--	--	--	NO	NO	--	

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
K1860	7310	Sink, Pot, Triple Compartment, w/Drainboards	A	A	A	A	--	D	F	--	--	--	--	--	--	--	--		
<p>Pot washing and scraping counter. This unit has three sink compartments and is constructed of stainless steel. The dimensions should be specified as required. See JSN K2620 for disposers and K9320 for pre-rinse hoses. Some models are built to accommodate two faucets. See related dishwashing and scullery triple compartment sinks at JSNs K1800 and K6660. This unit is used to wash pots in food service operations of hospitals, hotels and restaurants. [Extra lengths of counter/drainboard or provisions for a disposal unit on either side of the sink are custom alterations and not included in the above data.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	45	120	33	297 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	114	305	84	135 kg	2:	--	--	--									
K1910	7310	Table, Work, Stainless Steel	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--		
<p>Work table approximately 36x120x30. The table is made of heavy duty stainless steel with all edges rolled down at 90 degrees. The edges are 2" high and have rounded corners. The table has stainless steel legs and a stainless steel under-shelf. The unit is used as a work station in large kitchens, hotels, restaurants and hospitals. [Model 3 has an adjustable under shelf.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	36	120	30	223 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	91	305	76	102 kg	2:	--	--	--									
K1920	7310	Cutter, Food, Electric, Bench Mounted	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--		
<p>Electric food cutter. The cutter body is made from stainless steel or aluminum. The large holding bowl and cutting knives are stainless steel. The cover is interlocked with the electrical switch so the cutter can't be turned on when the cover is open nor can the cover be opened while the cutting knives are in motion. An attachment hub and various attachments are available to further process the food. The database height dimension refers to a unit with the bowl cover opened. The unit is used to rapidly process salad ingredients, dips, chopped steaks, and other finely textured foods in hotels, schools, restaurants, and hospitals. [These are the only two manufacturers found. All the distributors are handling either one or both of these lines.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	29	32	19	127 lb	1:	120	1	10	DEPENDENT:	YES	--						
		CM:	74	81	48	58 kg	2:	--	--	--									
K1930	7310	Cutter/Mixer, Electric, 10-15 Qt Capacity	A	A	A	A	--	--	G	--	--	--	--	--	--	--	--		
<p>Electric cutter-mixer with a 10-15 quart capacity bowl. The bowl is stainless steel and the bowl cover arm has a safety interlock with the motor to keep the motor from running while the cover is open. The two speed motor is enclosed in a easily cleaned metal base. Larger sizes are available. Refer also to specification MIL-F-43569. [No other source(s) identified with this description/specification.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	23	19	25	130 lb	1:	208	3	15	DEPENDENT:	YES	--						
		CM:	58	48	64	59 kg	2:	--	--	--									
K1940	7310	Cutter/Mixer, Electric, 40 Quart	A	A	A	A	--	D	G	--	--	--	--	--	--	--	--		
<p>Electric cutter-mixer. The unit has a 40 quart or larger stainless steel pivoting bowl, tubular steel frame base, 5 HP motor, a bowl cover that mechanically interlocks with the electric motor to prevent operation when the cover is open and a second interlock to prevent the motor's running when the bowl is tilted for pouring. A drag mechanism holds the bowl in position when tilted away from vertical to keep it from spilling. Some models are also equipped with timers. The database height dimension includes the clearance required to fully open the cover. The depth dimension is for a fully tilted unit with the cover fully open. The cutter/mixer cuts, mixes and blends food in seconds with complete control from start to finish. The unit is used in large kitchens of commercial food service establishments and hospitals. [No other source(s) identified with this description/specification.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	63	39	51	450 lb	1:	208	3	30	DEPENDENT:	YES	--						
		CM:	160	99	130	205 kg	2:	--	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES						
				R	A	F	A	H		1	2	3	4	5	6	
K1950	7310	Cutter/Slicer, Vegetable		A	A	A	A	--		--	A	--	--	--	--	
Vegetable cutter/slicer. The slicer has a minimum 1/2 HP drive unit to which a slicer, dicer or another vegetable cutting knife can be attached. The housing can be anodized aluminum or stainless steel. Most manufacturers offer several machines with different capacities and configurations. The database information is for the highest capacity machine in a manufacturer's line running on 120 volts. One manufacturer (CAGE 0H0S2) makes machines which run on 220 volts, have 1-1/2 HP motors and have very high production rates. The unit is used to slice, chop, dice, julienne, shred or grate vegetables in large kitchens of hospitals and restaurants. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	33	27	25	77 lb	1:	120	1	15	60					
		CM:	84	69	64	35 kg	2:	--	--	--	NO					
								DEPENDENT:			YES					
K2020	7310	Dispenser, Detergent, Automatic		A	A	A	A	--		C	A	--	--	--	--	
Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit. Sized for the operation. [Model 1 also includes a rinse additive dispenser called a Rinse Max II. Ecolab is the only manufacturer who would provide pricing information for the reservoir by itself. All the other manufacturers supply the dispenser free as part of using their detergent and do not supply, or sell the dispenser separately.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	21	11	9	-- lb	1:	120	1	5	60					
		CM:	53	28	23	-- kg	2:	--	--	--	NO					
								DEPENDENT:			NO					
K2040	7310	Dispenser, Iced Tea		C	C	C	C	--		B	B	--	--	--	--	
Instant tea beverage dispenser. The unit uses either liquid concentrate tea or a brewing system to provide consistent tea in a continuous flow dispensing system. The unit is used to dispense instant tea in hotels, restaurants, hospitals, clubs and other food service operations. [Price variance verified.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	35	11	22	57 lb	1:	120	1	15	60					
		CM:	89	28	56	26 kg	2:	--	--	--	NO					
								DEPENDENT:			YES					
K2050	7310	Dispenser, Bread, CRS, 2 Compartment		C	C	C	C	--		--	--	--	--	--	--	
Bread dispenser. This unit is either an in-counter two compartment system consisting of two sleeves and a facing plate or an above the counter unit holding two or three loaves. The in-counter units have self-leveling dispensers and covers. Either system will store two or three loaves. The unit is designed for use on work boards, sandwich counters, salad bars and other service points.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	29	13	19	38 lb	1:	--	--	--	--					
		CM:	74	33	48	18 kg	2:	--	--	--	NO					
								DEPENDENT:			NO					
K2060	7310	Dispenser, Milk, Bulk, Single		C	C	C	C	--		--	A	--	--	--	--	
Milk dispenser cabinet. The stainless steel cabinet has one lift valve for dispensing milk, a capacity of six gallons, magnetic door seals and a self-contained mechanical refrigeration system. This unit is used for self-service of milk in cafeteria of schools, hospitals and commercial restaurants. [The description has been changed from a twelve gallon capacity to a six gallon capacity. No one lift valve units could be found with a twelve gallon capacity.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	40	15	18	139 lb	1:	120	1	5	60					
		CM:	102	38	46	64 kg	2:	--	--	--	NO					
								DEPENDENT:			YES					
K2080	7310	Dispenser, Milk, Mobile, Individual Container		C	C	C	C	--		--	A	--	--	--	--	
Milk dispenser cabinet. The cabinet is made of stainless steel which is welded, ground and polished to a uniform finish. The convenient reach-in cooler stores milk or beverages by case or individually stacked container. The dispenser can be used as an individual server or as part of a continuous serving line. The unit is used in food service areas for self-service issue of milk in schools, restaurants and hospitals.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	44	49	34	460 lb	1:	120	1	7	60					
		CM:	112	124	86	209 kg	2:	--	--	--	NO					
								DEPENDENT:			YES					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K2085	7130	Dispenser, Milk, Bulk, Double	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Milk dispenser cabinet. The stainless steel cabinet has two lift valves for dispensing milk, a capacity of twelve total gallons, magnetic door seals and a self-contained mechanical refrigeration system. This unit is used for self-service of milk in cafeteria of schools, hospitals and commercial restaurants. [No other source(s) identified with this description/specification. APW/Wyott (Cage Code # 66745) and Nor-Lake Scientific (Cage Code # 13543) have both discontinued they're line of milk dispensers. No replacements were offered.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	40	26	18	145 lb	1:	120	1	5	NO		--					
		CM:	102	66	46	66 kg	2:	--	--	--	DEPENDENT: YES		--					
K2100	7310	Dispenser, Cream, Eutectic, 2 Quart	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Portable 2 quart cream dispenser. The unit uses a sealed re-freezable (eutectic) cooling element to keep cream cold for up to four hours. The unit features portion control, has stainless steel product contact areas, can be permanently mounted and is easily cleaned. [No other source(s) identified with this description/specification. Model 2 is an alternative and is a packaged Cream Dispenser holding 150 cream containers chilled for up to eight hours. This unit comes with one eutectic device and is stainless steel and plexiglass as shown in the cut sheet provided. Cost for this item is \$286.00 per unit.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	21	8	9	12 lb	1:	--	--	--	NO		--					
		CM:	53	20	23	6 kg	2:	--	--	--	DEPENDENT: NO		--					
K2110	7310	Dispenser, Drink, Non-Carbonated	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Non-carbonated drink dispenser. The unit has a 3-5 gallon capacity beverage bowl with a cover. This unit serves non-carbonated drinks to patients in hospitals.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	17	11	16	7 lb	1:	--	--	--	NO		--					
		CM:	43	28	41	4 kg	2:	--	--	--	DEPENDENT: NO		--					
K2111	7310	Dispenser, Drink, Non-Carbonated w/Refrigeration	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Non-carbonated drink dispenser with a refrigeration unit. The unit cools or maintains the coldness of liquid or frozen drinks during serving. [No other source(s) identified with this description/specification. Jet Spray was purchased by IMI Cornelius.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	28	18	19	77 lb	1:	120	1	15	NO		--					
		CM:	71	46	48	35 kg	2:	--	--	--	DEPENDENT: YES		--					
K2115	7310	Dispenser, Drink, Carbonated	D	D	D	D	--	B	A	--	--	--	--	--	--	--	--	--
Carbonated drink dispenser. The unit dispenses eight carbonated beverages and ice from a self service counter machine. The ice hopper holds 100 lb. of ice and may be connected to a remote ice maker from which it automatically loads ice. If not connected to an ice maker, the unit's ice bin will require manual refilling. The unit does not include the syrup racks, mixing valves, carbon dioxide supply or the chilled water pump. This unit is used to dispense cold carbonated drinks in food service activities. [Dimensions referenced are to above counter top height.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	32	31	343 lb	1:	120	1	13	NO		--					
		CM:	91	81	79	156 kg	2:	--	--	--	DEPENDENT: YES		--					
K2120	7310	Dispenser, Cup/Saucer, Unheated, Mobile, 4 Stack	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Mobile, unheated cup and saucer dispenser. The cabinet is made of stainless steel, is mounted on four casters and has a full perimeter strip bumper. The unit includes four self-leveling dispensing stacks which are sized to match or are self-adjusting to match the size of the dishware being stored. Heated units, units which hold less than four self-leveling dispensers and units which store larger dishes are also available. The facility's selection of dishware ultimately determines which exact model will be required. The unit is used for self-service of tableware in food service operations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	26	41	247 lb	1:	--	--	--	NO		--					
		CM:	91	66	104	113 kg	2:	--	--	--	DEPENDENT: NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES																																					
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6																										
K2130	7310	Dispenser, Plate, Mobile, Unheated, 4 Stack	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--																											
<p>Mobile, unheated dinner plate dispenser. The cabinet is made of stainless steel, is mounted on four casters and has a full perimeter strip bumper. The unit includes four self-leveling dispensing stacks which are sized to match the size of the plates being stored. See JSN K2140 for a heated 4 stack unit and JSN K2160 for a heated 2 stack unit. Other units are available. The database specifications refer to units which hold 10" plates. The facility's selection of dishware ultimately determines which exact model will be required. The unit is used to dispense dishes in food service facilities, restaurants and hospitals.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>40</td> <td>102</td> <td>31</td> <td>229 lb 104 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>31</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	40	102	31	229 lb 104 kg	1:	--	--	--	--				31		2:	--	--	--	--	<table border="1"> <thead> <tr> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>NO</td> <td>NO</td> <td>--</td> </tr> </tbody> </table>			HZ SWITCH:	DEPENDENT:	BTUs / HR:	NO	NO	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																			
EA	40	102	31	229 lb 104 kg	1:	--	--	--	--																																			
			31		2:	--	--	--	--																																			
HZ SWITCH:	DEPENDENT:	BTUs / HR:																																										
NO	NO	--																																										
K2140	7310	Dispenser, Plate, Mobile, Heated, 4 Stack	C	C	C	C	--	--	B	--	--	--	--	--	--	--																												
<p>Mobile, heated dinner plate dispenser. The cabinet is made of stainless steel, is mounted on four heavy duty casters and has a full perimeter strip bumper. The unit includes four self-leveling dispensing stacks which are sized to match the size of the plates being stored. See JSN K2130 for an unheated 4 stack unit and JSN K2160 for a heated 2 stack unit. Heated and unheated units with other capacities are available. The database specifications refer to units which hold 10" plates. The facility's selection of dishware ultimately determines which exact model will be required. The unit is used to dispense plates in food service facilities, restaurants and hospitals.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>40</td> <td>102</td> <td>31</td> <td>273 lb 124 kg</td> <td>1:</td> <td>120</td> <td>1</td> <td>15</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>31</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	40	102	31	273 lb 124 kg	1:	120	1	15	--				31		2:	--	--	--	--	<table border="1"> <thead> <tr> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>NO</td> <td>YES</td> <td>--</td> </tr> </tbody> </table>			HZ SWITCH:	DEPENDENT:	BTUs / HR:	NO	YES	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																			
EA	40	102	31	273 lb 124 kg	1:	120	1	15	--																																			
			31		2:	--	--	--	--																																			
HZ SWITCH:	DEPENDENT:	BTUs / HR:																																										
NO	YES	--																																										
K2150	7310	Dispenser, Drinking Glass, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--																												
<p>Mobile drinking glass dispenser. The unit is made of heavy gauge stainless steel, is enclosed on all four sides and mounted on four heavy duty casters. The unit stores racks filled with drinking glasses and holds the top rack at a constant dispensing height for customer convenience. Stationary units, units with open sides and cantilever style units are also available. This unit is used to dispense glasses in food service operations of hospitals and restaurants.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>37</td> <td>94</td> <td>27</td> <td>204 lb 93 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>31</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	37	94	27	204 lb 93 kg	1:	--	--	--	--				31		2:	--	--	--	--	<table border="1"> <thead> <tr> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>NO</td> <td>NO</td> <td>--</td> </tr> </tbody> </table>			HZ SWITCH:	DEPENDENT:	BTUs / HR:	NO	NO	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																			
EA	37	94	27	204 lb 93 kg	1:	--	--	--	--																																			
			31		2:	--	--	--	--																																			
HZ SWITCH:	DEPENDENT:	BTUs / HR:																																										
NO	NO	--																																										
K2160	7310	Dispenser, Plate, Mobile, Heated, 2 Stack	C	C	C	C	--	--	B	--	--	--	--	--	--																													
<p>Mobile, heated dinner plate dispenser. The dispenser is made of stainless steel, is mounted on four casters, has closed sides and has a full perimeter strip bumper. The unit includes two self-leveling dispensing stacks which are sized to match the size of the plates being stored. See JSN K2140 for a heated 4 stack unit and JSN K2130 for an unheated 4 stack unit. Other unit configurations are also available. The facility's selection of dishware ultimately determines which exact dispenser model will be required. The database specifications are for units holding 12" plates. The unit is used to dispense dishes in food service facilities, hospitals and restaurants.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>40</td> <td>102</td> <td>20</td> <td>180 lb 82 kg</td> <td>1:</td> <td>120</td> <td>1</td> <td>9</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>36</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	40	102	20	180 lb 82 kg	1:	120	1	9	--				36		2:	--	--	--	--	<table border="1"> <thead> <tr> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>NO</td> <td>YES</td> <td>--</td> </tr> </tbody> </table>			HZ SWITCH:	DEPENDENT:	BTUs / HR:	NO	YES	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																			
EA	40	102	20	180 lb 82 kg	1:	120	1	9	--																																			
			36		2:	--	--	--	--																																			
HZ SWITCH:	DEPENDENT:	BTUs / HR:																																										
NO	YES	--																																										
K2170	7310	Dispenser, Coffee, Freeze Dried	C	C	C	C	--	B	A	--	--	--	--	--	--																													
<p>Freeze dried coffee dispenser. The unit's dispensing water temperature is thermostatically controlled and adjustable to suit specific tastes. The dispenser can also provide hot water at the push of a button for other needs. Larger units with other power configurations are available. The unit is used to serve fresh freeze dried coffee in food service operations.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>28</td> <td>71</td> <td>9</td> <td>40 lb 19 kg</td> <td>1:</td> <td>120</td> <td>1</td> <td>15</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>24</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	28	71	9	40 lb 19 kg	1:	120	1	15	--				24		2:	--	--	--	--	<table border="1"> <thead> <tr> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>NO</td> <td>YES</td> <td>--</td> </tr> </tbody> </table>			HZ SWITCH:	DEPENDENT:	BTUs / HR:	NO	YES	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																			
EA	28	71	9	40 lb 19 kg	1:	120	1	15	--																																			
			24		2:	--	--	--	--																																			
HZ SWITCH:	DEPENDENT:	BTUs / HR:																																										
NO	YES	--																																										
K2180	7310	Dispenser, Meal Tray, w/Flatware Cylinders	C	C	C	C	--	--	--	--	--	--	--	--	--																													
<p>Twin stack stainless steel meal tray dispenser with an eight to ten cylinder silverware dispenser above. The dispenser can be mobile or stationary. Self-leveling dispensers are available. Some models have decorative laminating over portions of the stainless steel. [No other source(s) identified with this description/specification.]</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>40</td> <td>102</td> <td>37</td> <td>250 lb 114 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>24</td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	40	102	37	250 lb 114 kg	1:	--	--	--	--				24		2:	--	--	--	--	<table border="1"> <thead> <tr> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>NO</td> <td>NO</td> <td>--</td> </tr> </tbody> </table>			HZ SWITCH:	DEPENDENT:	BTUs / HR:	NO	NO	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																			
EA	40	102	37	250 lb 114 kg	1:	--	--	--	--																																			
			24		2:	--	--	--	--																																			
HZ SWITCH:	DEPENDENT:	BTUs / HR:																																										
NO	NO	--																																										

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K2190	7310	Dispenser, Flatware, 8-12 Basket, Counter Mounted	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	
<p>Flatware dispenser. The unit is made of polished stainless steel, holds 8 - 12 standard flatware baskets and sits on top of a counter. Refer to MIL-D-23828 for additional specifications. Several larger and smaller models are available. Database pricing includes dispenser and plastic or stainless steel cylinders. This unit is used to dispense silverware in food service facilities, restaurants and hospitals. [Database price is for an 8 cylinder holder with stainless steel inserts. Model 1 vendor, Steril-Sil Company (Cage Code 07009) does not, as of yet have a web site.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	12	34	12	30 lb	1:	--	--	--	NO		--					
		CM:	30	86	30	14 kg	2:	--	--	--	NO		--					
K2200	7310	Dispenser, Bowl/Plate, Mobile, Unheated, 4 Stack	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	
<p>Mobile, unheated bowl and small plate dispenser. The unit is made from stainless steel, is mounted on four casters and has a full perimeter strip bumper. The unit includes four self-leveling, adjusting dispensing stacks which adjust to the size of the dishware being stored and keep the next available dish at a convenient height for removal. The unit is easily cleaned. Heated, non-self adjusting and units with less than four stacks are also available. See JSNs K2210 and K2220 for 2 stack heated and unheated models. The database specifications are for a unit holding bowls and plates between 4-1/4" and 7" in diameter. The facility's selection of dishware ultimately determines which exact model is required. The unit is used to dispense bowls and small plates in food service operations, hotels, restaurants and hospitals.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	40	31	31	178 lb	1:	--	--	--	NO		--					
		CM:	102	79	79	81 kg	2:	--	--	--	NO		--					
K2210	7310	Dispenser, Bowl/Plate, Mobile, Heated, 2 Stack	C	C	C	C	--	--	A	--	--	--	--	--	--	--		
<p>Mobile, heated bowl and small plate dispenser. The unit is made from stainless steel, is mounted on four casters and has a full perimeter strip bumper. The unit includes two self-leveling, adjusting dispensing stacks which adjust to the size of the dishware being stored and keep the next available dish at a convenient height for removal. The unit is easily cleaned. Units with non-self adjusting dispensers and units with more than two stacks are also available. See JSNs K2200 and K2220 for larger and 2 stack unheated models. The database specifications are for a unit holding bowls and plates between 4-1/4" and 7" in diameter. The facility's selection of dishware ultimately determines which exact model is required. The unit is used to dispense bowls and small plates in food service operations, hotels, restaurants and hospitals.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	40	18	31	128 lb	1:	120	1	6	NO		--					
		CM:	102	46	79	59 kg	2:	--	--	--	YES		--					
K2220	7310	Dispenser, Bowl/Plate, Mobile, Unheated, 2 Stack	C	C	C	C	--	--	--	--	--	--	--	--	--	--		
<p>Mobile, unheated bowl and small plate dispenser. The unit is made from stainless steel, is mounted on four casters and has a full perimeter strip bumper. The unit includes two self-leveling, adjusting dispensing stacks which adjust to the size of the dishware being stored and keep the next available dish at a convenient height for removal. The unit is easily cleaned. Units with non-self adjusting dispensers and units with more than two stacks are also available. See JSNs K2200 and K2210 for larger and 2 stack heated models. The database specifications are for a unit holding bowls and plates between 4-1/4" and 7" in diameter. The facility's selection of dishware ultimately determines which exact model is required. The unit is used to dispense bowls and small plates in food service operations, hotels, restaurants and hospitals.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	40	18	31	127 lb	1:	--	--	--	NO		--					
		CM:	102	46	79	58 kg	2:	--	--	--	NO		--					
K2230	7310	Dispenser, Meal Tray, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--		
<p>Meal tray dispenser. The dispenser is made of stainless steel, is mounted on heavy duty casters with brakes on at least two casters and has protective bumpers. Self-leveling springs keep trays at a convenient height for use. The dispenser can hold either 14" x 18" or 15" x 20" meal trays. Cantilever, fully enclosed and open side models are available. Many models offer cutlery/silverware dispensers as optional attachments. Tray dispensers are used in serving lines and tray makeup lines in food service operations in hotels, restaurants and hospitals.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	37	24	33	113 lb	1:	--	--	--	NO		--					
		CM:	94	61	84	52 kg	2:	--	--	--	NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
K2240	7310	Dispenser, Hot Chocolate, Counter Mounted	C	C	C	C	--	B	A	--	--	--	--	--	--	--	--		
Hot chocolate dispenser. This is an electric, counter mounted unit. The dispenser provides portion-controlled, single cup size servings in commercial and institutional food service operations.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	28	10	24	48 lb	1:	120	1	15	60	NO							
		CM:	71	25	61	22 kg	2:	--	--	--	DEPENDENT:	YES		--					
K2250	7310	Dispenser, Tray/Flatware, 2 Stacks, 8-12 Cylinder	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--		
Tray and flatware dispenser. The dispenser is made of stainless steel and has two self-leveling tray carriers and an overhead silverware shelf with between eight and twelve cylinders. The unit is used to dispense trays and silverware in commercial and institutional food service operations.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	54	41	33	228 lb	1:	--	--	--	0	NO							
		CM:	137	104	84	104 kg	2:	--	--	--	DEPENDENT:	NO		--					
K2260	7310	Dispenser, Milk Shake, 8 Gal	C	C	C	C	--	--	G	--	--	--	--	--	--	--	--		
Shake-maker dispenser. The dispenser is made of stainless steel and can serve eight gallons or more of milk shakes per hour in ambient room temperatures. [No other source(s) identified with this description/specification]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	59	17	40	385 lb	1:	208	3	18	60	YES							
		CM:	97	61	51	69 kg	2:	--	--	--	DEPENDENT:	YES		--					
K2270	7310	Dispenser, Ice Cream, Soft, Freestanding	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--		
Ice-cream dispenser. The dispenser is made of stainless steel and uses a gravity freezer. The unit can serve either of two flavors or a twist combination. Unit is used to serve frozen desserts in commercial and institutional food service operations.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	61	27	40	710 lb	1:	208	1	30	60	NO							
		CM:	155	69	102	323 kg	2:	--	--	--	DEPENDENT:	YES		--					
K2290	7310	Dishwasher, Conveyor, Steam, 2 Tank	A	A	A	A	--	D	G	--	A	--	E						
Automatic dishwasher which uses steam to heat the water in its two tanks. The unit is constructed of stainless steel and has a pre-wash, wash and rinse cycle. A 1/10 HP or larger electric motor powers the conveyor on which the dishracks ride. Three 1 HP or larger motors power the pre-wash, wash and rinse water circulating pumps. The unit collects and disposes of food dislodged from dishware, has curtains at each end and has large doors for inspection of the machine. The dishwasher's controls are mounted for ease of operator use. Optional blower/dryer units remove the last of the rinse water. Accessory condensing units may eliminate the need to vent the dishwasher to the atmosphere. Propane, natural gas and electrically heated models are also available. Because they vary widely from model to model, the dishwasher's final physical and utility configurations should be carefully reconciled with the facility drawings. The database height dimension reflects the clearance required to raise a machine door for servicing but not the clearance required beneath a ventilation hood. The machine listed in the database is each manufacturer's top line unit for the specified number of tanks. [Model 3 uses a 1/2 HP motor for the pre-wash.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	90	126	35	1,200 lb	1:	208	3	25	60	NO		104,000					
		CM:	229	320	89	545 kg	2:	--	--	--	DEPENDENT:	YES							
K2490	7310	Dishwasher, Conveyor, Steam, 1 Tank	A	A	A	A	--	D	G	--	A	--	E						
Automatic dishwasher which uses steam to heat the water in the single tank. The unit is constructed of stainless steel and has a pre-wash, wash and rinse cycle. A 1/10 HP or larger electric motor powers the conveyor on which the dishracks ride. Two 1/2 HP or larger motors power the pre-wash and wash water circulating pumps. The unit collects and disposes of food dislodged from dishware, has curtains at each end and has large doors for inspection of the machine. The dishwasher's controls are mounted for ease of operator use. Optional blower/dryers remove the last of the rinse water. Accessory condensing units may eliminate the need to vent the dishwasher to the atmosphere. Propane, natural gas and electrically heated models are also available. Because they can vary widely from model to model, the dishwasher's final physical and utility configurations should be carefully reconciled with the facility drawings. The database height dimension reflects the clearance required to raise a machine door for servicing but not the clearance required beneath a ventilation hood. The machine listed in the database is each manufacturers top line unit for the specified number of tanks.																			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K2750	7310	Fryer, Gas, 30-40 Lb. Capacity, Free Standing	A	A	A	A	--	--	B	--	--	A	E					
<p>Two basket gas heated deep fat fryer. The unit is freestanding, holds 30-40 lb. of hot oil and has leveling legs, swing up or removable corrosion resistant heating elements, solid state or programmable controls, self-diagnostics, a backsplash and an electronic or thermostatic over-temperature shutoff. The unit can have one large oil tank holding both baskets or two smaller tanks holding one basket each. The basic unit has painted sides, an aluminized back and a stainless steel front and top; a full stainless steel enclosure is optional. Some models have automatic basket lifts. The fryer can run on either natural or liquid propane gas. The database height dimension refers to a unit with its coils lifted for cleaning. The electrical specifications are for the automatic basket lifts and power controls. See the manufacturers' specifications for required clearances from combustible materials and open heating elements. [Model 1 includes basket lift and electronic ignition. An automatic basket lift option for Model 2 adds \$2,620 to the price. Model 3 includes automatic basket lift and is all stainless steel.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	49	16	31	215 lb	1:	120	1	12	60		YES		110,000			
		CM:	124	41	79	98 kg	2:	--	--	--	DEPENDENT:		YES					
K2800	7310	Fryer, Electric, 30 Lb. Capacity, Free Standing	A	A	A	A	--	--	G	--	--	--	E					
<p>Two basket electric deep fat fryer. The unit is freestanding, holds 30-35 lb. of hot oil, has leveling legs, swing up or removable corrosion resistant heating elements, solid state or programmable controls, self-diagnostics, a backsplash and an electronic or thermostatic over-temperature shutoff. The basic unit has painted sides, an aluminized back and a stainless steel front and top; a full stainless steel enclosure is optional. Some models have automatic basket lifts. The database height dimension refers to a unit with its coils lifted for cleaning.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	60	20	39	210 lb	1:	208	3	38	60		NO		--			
		CM:	152	51	99	96 kg	2:	--	--	--	DEPENDENT:		YES					
K2810	7310	Fryer, Electric, 15 Lb. Capacity, Counter Mounted	A	A	A	A	--	--	C	--	--	--	E					
<p>Countertop, 15 lb. oil capacity, electric deep fat fryer. The unit has adjustable feet, swing up immersion heating coils, a thermostatic control and half-size baskets. The database height dimension includes the clearance required to lift the heating coils for cleaning. Options on some models include timers and automatic basket lifts. This unit is used to fry foods in commercial and institutional food service operations. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	32	18	20	37 lb	1:	208	1	22	60		NO		--			
		CM:	81	46	51	17 kg	2:	--	--	--	DEPENDENT:		YES					
K2820	7310	Fryer, 30 Lb. Capacity, Electric, Counter Mounted	A	A	A	A	--	--	G	--	--	--	E					
<p>Two basket electric deep fat fryer. The baskets can sit in individual frying oil reservoirs or both can be in a single larger reservoir. The unit is counter mounted, holds 30-35 lb. of hot oil and has swing up or removable corrosion resistant heating elements, solid state or programmable controls, self-diagnostics, a backsplash and an electronic or thermostatic over-temperature shutoff. The basic unit has painted sides, an aluminized back and a stainless steel front and top; a full stainless steel enclosure is optional. Some models have automatic basket lifts. The database height dimension refers to a unit with its coils lifted for cleaning.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	24	24	27	105 lb	1:	208	3	47	60		NO		90,000			
		CM:	61	61	69	48 kg	2:	--	--	--	DEPENDENT:		YES					
K2850	7310	Fryer, Fat, Deep, 50 Lb. Capacity, Gas	A	A	A	A	--	--	A	--	--	A	E					
<p>Deep fat fryer. The fryer has a 60 lb. capacity, stainless steel pot, cabinet with doors, an automatic melt cycle and electrical ignition. The database electrical requirements include the power needed for optional basket lifts. The database height dimension includes the clearance for the basket lift arm. This unit is used for frying foods in commercial and institutional food service operations.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	55	18	38	315 lb	1:	120	1	12	60		NO		120,000			
		CM:	140	46	97	143 kg	2:	--	--	--	DEPENDENT:		YES					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K2900	7310	Fryer, Electric, 85 Lb. Capacity, Freestanding	A	A	A	A	--	--	G	--	--	--	--	E				
<p>Large dual or single basket electric fryer with a fat capacity of 85-90 pounds. The unit features a stainless steel front and top with painted sides, welded frame and cabinet, swing top and immersion type tubular elements with stainless steel exterior surfaces. Stainless steel side panels are available. The unit has solid state controls; programmable controls are also available. Some models require direct electrical connections without plugs. The database height specification includes the space needed to raise the heating elements. See manufacturers' technical sheets for the clearance required for roll-out draining tubs on some models. This unit is used to prepare fried foods in commercial and institutional food service operations.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	
			57	145	21	38	300 lb	1:	208	3	67							
						137 kg	2:	--	--	--	--							
K2950	7310	Fryer, Electric, 50-70 Lb. Capacity, Free Standing	A	A	A	A	--	--	G	--	--	--	E					
<p>Electric deep fat fryer. The floor standing unit has a 50-70 lb. shortening capacity, stainless steel construction with a welded frame, cabinet, swing top and immersion type tubular elements. The front and top faces are stainless steel. The sides and back are painted or stainless steel depending on the manufacturer. Optional basket lifts add significantly to the unit price and may require 120V power in addition to the 208V power for the heating elements. The database height dimension includes the clearance needed to raise the heating elements out of the tank for cleaning. This unit is used to prepare fried foods in commercial and institutional food service operations. [The addition of an automatic lift for Model 2 adds \$2,720 to the price.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	
			56	142	24	38	350 lb	1:	208	3	64							
						159 kg	2:	--	--	--	--							
K2960	7310	Fryer, Pressure, 70 Lb. Capacity, Electric	A	A	A	A	--	--	G	--	--	--	E					
<p>Pressure fryer. The fryer is made from stainless steel, has a large covered and sealable pressure frying chamber, holds 70 lb. of shortening, is mounted on casters and features electromechanical controls. Computer controlled and gas models are available. The database height dimension includes the clearance to raise the cover. The unit is used for frying foods in commercial and institutional food service operations. [No other source(s) identified with this capacity. Hobart Corporation, Ballantyne Food Service Equipment, and Commercial Cooking Systems all carry pressure fryers, but with a maximum capacity of 42 pounds.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	46,062	
			64	163	18	37	325 lb	1:	208	3	318							
						148 kg	2:	--	--	--	--							
K2970	7310	Pan, Frying, Tilting, Elect, 30 Gal, Free Standing	A	A	A	A	--	D	G	--	--	--	E					
<p>Free standing, tilting, frying (braising) pan with a 30 gallon capacity. The unit features a stainless steel pan body mounted in a heavy duty stainless or painted steel frame, a pan cover, thermostatically controlled electric heating and a heavy, 3/8 inch thick stainless steel cooking surface with clamped on electric heating elements. The pan has a pouring lip and a positive locking tilting mechanism to hold the pan at any angle of tilt while pouring. The database height specification includes the space for opening the pan cover. The width dimension does not include the clearance for optional fold down side tables. See the individual manufacturers' specifications for the additional width required for side tables. An optional swing away faucet on some models will require hot water, cold water and a drain. Gas heated, larger and smaller pans are available. The unit is used to braise meat, pan fry chicken, steam vegetables and fry short order items in commercial and institutional food service operations.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	
			72	183	49	42	405 lb	1:	208	3	34							
						184 kg	2:	--	--	--	--							
K2980	7310	Pan, Frying, Tilting, Gas, 30 Gal, Floor Mounted	A	A	A	A	--	D	A	--	--	A	E					
<p>Gas fired, free standing, tilting, frying (braising) pan with a 30 gallon capacity. The unit features a stainless steel pan body mounted in a heavy duty stainless or painted steel frame, pan cover, thermostatically controlled electric heating and a heavy, 5/8 inch thick stainless steel cooking surface with welded heat transfer fins. The pan has a pouring lip and a positive locking tilting mechanism to hold the pan at any angle of tilt while pouring. The database height specification includes the space for opening the pan cover. The width dimension does not include the clearance for optional fold down side tables. See the individual manufacturers' specifications for the additional width required for side tables. The depth dimension includes a 6" rear wall clearance. An optional swing away faucet on some models will require hot water, cold water and a drain. Electrically heated, smaller and larger pans are available. The unit is used to braise meat, pan fry chicken, steam vegetables and fry short order items in commercial and institutional food service operations.</p>																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE: EA	HEIGHT IN: 72 CM: 183	WIDTH 49 DEPTH 112	DEPTH 44	WEIGHT 455 lb 207 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 6 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: 108,750			
K3100	7310	Griddle, Electric, Counter Mounted, 36" Wide	A	A	A	A	--	--	G	--	--	--	E		
Electric griddle. The griddle has a 1/2 inch thick (or greater) steel heating surface, stands on legs on top of a counter, has a thermostat control for each linear foot of griddle and has a drippings channel which empties into a grease drawer for easy cleaning. The griddle has side and rear splash guards. Some manufacturers offer models of differing depths. The model chosen should match the supporting counter or table. The database specifications and pricing reflect a standard depth unit. The griddle is used for food preparation in commercial and institutional food service operations.															
			UNIT OF ISSUE: EA	HEIGHT IN: 22 CM: 56	WIDTH 36 DEPTH 71	DEPTH 28	WEIGHT 252 lb 115 kg	VOLTS 1: 208 2: --	PHASE 3 --	AMPS 45 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --			
K3200	7310	Griddle, Gas, Counter Mounted, 36" Wide	A	A	A	A	--	--	A	--	--	A	E		
Gas griddle. The griddle has a 3/4 inch thick steel heating surface, stands on legs on top of a counter, has a thermostat control for each linear foot of griddle and has a grease trough which empties into a drawer for easy cleaning. The griddle will require a supporting counter or table. Unit is used for food preparation in commercial and institutional food service operations.															
			UNIT OF ISSUE: EA	HEIGHT IN: 26 CM: 66	WIDTH 42 DEPTH 102	DEPTH 40	WEIGHT 430 lb 196 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 10 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: 90,000			
K3210	7310	Griddle, Gas, Stand Mounted, 36" Wide	A	A	A	A	--	--	A	--	--	A	E		
Gas griddle. The griddle has a minimum 3/4 inch thick steel heating surface, rests on a fixed floor stand, has a thermostat control for each linear foot of griddle and has a grease trough which empties into a drawer for easy cleaning. The stand comes with a stainless steel lower shelf. Casters may be added to the stand for mobility allowing the griddle to be moved as necessary. The unit is used for food preparation in commercial and institutional food service. [The price for casters for Model 1 is \$325.00, Model 2 \$360.00 and Model 3 \$440.00.]															
			UNIT OF ISSUE: EA	HEIGHT IN: 42 CM: 107	WIDTH 36 DEPTH 79	DEPTH 31	WEIGHT 515 lb 234 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 5 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: 90,000			
K3230	7310	Griddle, Gas, Mobile Stand Mounted, 48" Wide	A	A	A	A	--	--	A	--	--	A	E		
Gas griddle. The griddle has a 3/4 inch thick steel heating surface, rests on a mobile stand, has a thermostat control for each linear foot of griddle and has a grease trough which empties into a drawer for easy cleaning. The griddle can be moved as necessary. Unit is used for food preparation in commercial and institutional food service.															
			UNIT OF ISSUE: EA	HEIGHT IN: 39 CM: 99	WIDTH 54 DEPTH 102	DEPTH 40	WEIGHT 715 lb 325 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 5 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: 120,000			
K3250	7310	Grinder, Meat, 20 Lb./Minute Capacity, Electric	A	A	A	A	--	--	A	--	--	--	--		
Electric meat grinder. The grinder can produce 20 lbs./minute using a minimum 1 HP motor. This unit is a heavy duty model for chopping food in commercial and institutional food service operations.															
			UNIT OF ISSUE: EA	HEIGHT IN: 25 CM: 64	WIDTH 17 DEPTH 76	DEPTH 30	WEIGHT 207 lb 94 kg	VOLTS 1: 120 2: --	PHASE 1 --	AMPS 13 --	HZ: 60 HZ SWITCH: NO DEPENDENT: YES	BTUs / HR: --			
K3300	7310	Grinder, Meat, 40-50 Lb./Minute Capacity, Mobile	A	A	A	A	--	--	G	--	--	--	--		
Meat grinder. The unit contains one motor for mixing and another for grinding; a heavy duty grinding motor is available. The unit is mounted on 4 casters; has a large, easily filled holding cylinder capable of accepting up to 140 lb. of meat at a time and easily operated controls. A remote foot switch is available for some models. The hopper and moving parts are easily removed for thorough cleaning. The database height dimensions are for a unit with its cover open. The unit is used for chopping food in commercial and institutional food service operations.															

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
			UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	IN: 81	25	50	610 lb	1: 208	3	16	60	NO	--					
				CM: 206	64	127	277 kg	2: --	--	--	DEPENDENT:	YES	--					
K3350	7310	Grinder, Meat, 80 Lb./Minute Capacity	A	A	A	A	--	--	G	--	--	--	--	--	--	--	--	
			Meat grinder. The unit has a 7 HP or larger motor and is capable of grinding 85 pounds of meat per minute through a 1/8 inch plate on the first cutting. The grinder has an electrical safety interlock to prevent operation when the feed pan is removed. All surfaces which come in contact with the meat are stainless steel, chrome or heavily tinned cast iron and are easily exposed or removed for cleaning. A variety of slicing attachments are available.															
			UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	IN: 43	29	55	513 lb	1: 208	3	27	60	NO	--					
				CM: 109	74	140	233 kg	2: --	--	--	DEPENDENT:	YES	--					
K3370	7310	Pulper/Grinder, Water Fed, Freestanding	A	A	A	A	--	B	G	--	--	--	--	--	--	--	--	
			Freestanding pulper/grinder for food waste disposal. The unit grinds food waste into small pieces and uses a water press to remove fluids. The product is a waste slurry with less volume, with less water content and which is less susceptible to the immediate microorganism growth which generates foul odors. The database price for the unit includes an accessory table/trough but the pulper can be integrated into a dishwasher conveyor system to save floor space. The pulper units listed on the database process 475 lb. per hour and has a series of motors totaling at least 7 HP. Multiple drains may be required for the unit. Larger pulpurs are available which process up to 3,000 lb. per hour. Model numbers vary according to the orientation of the input and output chutes. The pulper chosen for installation must be verified against the final kitchen utility and plumbing configuration to ensure compatibility.															
			UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	IN: 51	81	34	1,500 lb	1: 208	3	24	60	NO	--					
				CM: 130	206	86	681 kg	2: 115	1	5	DEPENDENT:	YES	--					
K3400	7310	Hood, Exhaust, Kitchen	A	A	A	A	--	--	A	--	--	--	--	--	--	--	E	
			Stainless steel kitchen exhaust hood. The unit has removable grease filters for use over any area, is fabricated to dimensions as required, provides for forced upward air flow through a hood and the grease filter and can pull the exhaust down through a vent and dissipate it below the kitchen to an outside area with complete automatic grease extraction. The database reflects the requirements for a 12 foot wide unit. The database price does not include the filter elements. The database electrical requirements are for any light fixture that is part of the hood. The fan that draws the air from this unit is not part of this unit. This hood facilitates exhaust dissipation in commercial and institutional food service operations.															
			UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	IN: 24	144	48	685 lb	1: 120	1	5	60	NO	--					
				CM: 61	366	122	311 kg	2: --	--	--	DEPENDENT:	YES	--					
K3401	7310	Hood, Exhaust, Non-Commercial	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	
			The exhaust hood shall be designed for installation and general use over an electric range. It shall have as a minimum; an exhaust capacity of 160 CFM, two fan speeds, a work light and removable grease filters.															
			UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	IN: 8	30	20	31 lb	1: 120	1	2	60	NO	--					
				CM: 20	76	51	14 kg	2: --	--	--	DEPENDENT:	NO	--					
K3402	7310	Oven, Microwave, Over-the Range w/ Hood	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	
			The microwave oven shall have an integrated exhaust hood that ventilates to the outside or through a built-in recirculating charcoal filter. The oven shall be designed for installation over an electric range. It shall have as a minimum; a power rating of 1000 watts, a capacity of 1.4 cu. ft., an electronic touch pad control, a timer and power level selection.															
			UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	IN: 17	30	17	68 lb	1: 120	1	15	60	NO	--					
				CM: 43	76	43	31 kg	2: --	--	--	DEPENDENT:	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
K3420	7310	Hose, Retractable, Wall Mounted	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	15	8	17	32 lb	1:	--	--	NO	--								
		CM:	38	20	44	15 kg	2:	--	--	NO	--								
K3430	7310	Cabinet, Heated, Service Pan/Tray, Mobile	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Mobile, heated service pan/tray cabinet. The cabinet body is made from aluminum or stainless steel. The cabinet's thermostat controls the heat over a wide range of temperatures. The unit has a thermometer visible from the outside, insulated double wall construction, complete seam welding throughout and moves on heavy duty swivel and fixed plate casters. The heater can be used to keep food warm in the centralized tray service area or behind the main serving line. Some models feature double doors.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	71	31	36	350 lb	1:	120	1	15	60	NO							
		CM:	180	79	91	159 kg	2:	--	--	--	60	YES							
K3560	7310	Cabinet, Ice Cream, Mobile, Self-Service	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Ice cream cabinet for self-service. The cabinet has stainless steel/galvanized steel double walled sides with formed-in-place polyurethane insulation on all sides and the bottom, adjustable temperature control, removable cover, a drain from the inner compartment and externally mounted dial thermometer. The cabinet can be placed adjacent to a food service counter during service of meals. [Price difference verified.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	40	32	46	470 lb	1:	120	1	8	60	NO							
		CM:	102	81	117	214 kg	2:	--	--	--	60	NO							
K3570	7310	Cabinet, Ice Cream, Mobile, Storage	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Ice-cream cabinet for storage. The cabinet has stainless steel/galvanized steel double walled sides with formed-in-place polyurethane insulation on all sides and the bottom, adjustable temperature control, removable cover, an inner compartment drain and an externally mounted dial thermometer. This unit is used for storage of ice cream in commercial and institutional food service operations. [Price difference verified.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	42	66	32	395 lb	1:	120	1	8	60	NO							
		CM:	107	168	81	180 kg	2:	--	--	--	60	YES							
K3600	7310	Steamer, Stack, 2 Compartments, Gas Boiler	A	A	A	A	--	B	A	--	--	A	E						
Stack steamer. The unit is made of stainless steel and features two pressureless steamer compartments above a gas fired boiler (electric boilers are available). Each compartment has its own sealed door and a switch which turns off the blower and steam supply to that compartment when the door is opened. A further safety shuts the unit off if the water level in the boiler gets too low or the steam pressure gets too high. A drip sink for catching condensation is positioned under the compartments. A side access door allows maintenance and repair of piping and other utilities. See manufacturers' installation notes for locating the drain for this unit and the required minimum clearances from combustible materials.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	61	25	35	800 lb	1:	120	1	7	60	NO							
		CM:	155	64	89	364 kg	2:	--	--	--	60	YES	200,000						
K3640	7310	Kettle, Jacketed, Steam, Tilting, 5 GAL, Table MTD	A	A	A	A	--	D	G	--	A	--	--						
Two-thirds (2/3) or fully jacketed table mounted steam kettle with a 5-6 gallon capacity. The kettle features direct steam heating from the facility or a self contained steam generator, adjustable feet, an anti-splash screen and a flexible drain hose. The unit requires a separate base cabinet or table. The database electrical requirements are for units with a self-contained electrically powered steam source. The database height dimension includes the handle for tilting the kettle. This unit uses steam heat for the preparation of gravies, stews and meat sauces in commercial and institutional food service operations.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	27	24	18	140 lb	1:	208	3	21	60	NO							
		CM:	69	61	46	64 kg	2:	--	--	--	60	YES							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K3700	7310	Kettle, Jacketed, Gas, 20 Gallon Capacity	A	A	A	A	--	D	A	--	--	A	E					
Fully jacketed steam kettle with a 20 gallon capacity. The unit features stainless steel construction, a gas heated, sealed steam compartment with a relief valve and a sloped bottom in the inside cooking vessel leading toward the draw off valve. The database height and width dimensions include the space required to open the lid. The system is used to prepare meat dishes, vegetables, soups and poultry items in commercial and institutional food service operations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA	IN:	64	42	44	588 lb	1:	120	1	3	HZ SWITCH: NO	100,000							
	CM:	163	107	112	267 kg	2:	--	--	--	DEPENDENT: YES								
K3750	7310	Kettle, Jacketed, 20 Gal Cap, Elect, Freestanding	A	A	A	A	--	D	G	--	--	--	--					
Freestanding 2/3 jacketed kettle with a 20 gallon capacity and an electrically heated self-contained steam generator. The unit is made from stainless steel, tilts for pouring and has a draw-off valve. The tilting mechanism will safely hold the kettle in any position away from vertical. This unit is used for the preparation of meat dishes, soups, sauces and poultry in commercial and institutional food service operations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA	IN:	64	36	35	495 lb	1:	208	3	34	HZ SWITCH: NO	--							
	CM:	163	91	89	225 kg	2:	--	--	--	DEPENDENT: YES								
K3770	7310	Kettle, Jacketed, Steam, Tilting, 20 Gal Capacity	A	A	A	A	--	D	A	--	A	--	--					
Tilting, direct steam system heated and jacketed kettle with a 20 gallon capacity. The kettle features heavy-duty stainless steel construction, 2/3 kettle height steam jacket, mounting on a pedestal or frame base, direct linking to facility steam system for heating and a self locking tilt mechanism which holds the kettle at any angle for pouring. The database height specification includes the space required for opening the optional lid. The water and drain requirements are for the optional kettle faucet. Unit installation may require a steam trap and drilling anchoring holes in the floor. This unit is used for the preparation of meat dishes, vegetables and soups in commercial and institutional food service operations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: --		BTUs / HR:							
EA	IN:	60	37	34	255 lb	1:	--	--	--	HZ SWITCH: NO	--							
	CM:	152	94	86	116 kg	2:	--	--	--	DEPENDENT: NO								
K3800	7310	Kettle, Jacketed, 40 Gal Cap, Gas, Freestanding	A	A	A	A	--	D	A	--	--	A	E					
Self-contained 2/3 jacketed kettle with a 40 gallon capacity and a gas fired steam generator. The unit will operate on several types of gas (natural, propane, butane or mixture) and tilts for pouring. The kettle has heavy-duty stainless steel construction, is mounted on a pedestal or frame base and uses a self locking tilt mechanism which holds the kettle at any angle for pouring. The database height specification includes the space required for opening the optional lid. The water and drain requirements are for the optional kettle faucet. The unit is used for preparing meat dishes, soup, gravies and poultry in commercial and institutional food service operations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA	IN:	76	55	44	850 lb	1:	120	1	5	HZ SWITCH: NO	100,000							
	CM:	193	140	112	386 kg	2:	--	--	--	DEPENDENT: YES								
K3850	7310	Kettle, Jacketed, Steam, Fixed, 40 Gallon Capacity	A	A	A	A	--	D	--	--	A	--	--					
Two-thirds (2/3) or fully jacketed, stationary, 40 gallon capacity kettle. The unit features direct steam heating from the facility system, stainless steel construction, cover, faucet, draw off valve, base cabinet and a kettle body of solid one piece welded construction with heavy duty bar rim. The database height specification includes the space for opening the kettle lid. The unit is used for wet roasting meats, soups, pie fillings and stews in commercial and institutional food service operations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: --		BTUs / HR:							
EA	IN:	69	36	48	475 lb	1:	--	--	--	HZ SWITCH: NO	--							
	CM:	175	91	122	216 kg	2:	--	--	--	DEPENDENT: NO								
K3860	7310	Kettle, Jacketed, Steam, Tilting, 40 Gal Capacity	A	A	A	A	--	D	--	--	A	--	--					
Two-thirds (2/3) or fully jacketed, tilting, 40 gallon capacity kettle. The unit features direct steam heating from the facility system, stainless steel construction, lifting cover, faucet, draw off valve and a kettle body of solid one piece welded construction with heavy duty bar rim. The kettle is mounted on a pedestal base or in a support structure. Wall mounted kettles are available. The tilting mechanism will securely hold the kettle at any angle away from vertical. The kettle requires a steam trap as part of its installation. The database height specification includes the space for opening the kettle lid. The unit is used for wet roasting meats, soups, pie fillings and stews in commercial and institutional food service operations.																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE: EA	HEIGHT IN: 66 CM: 168	WIDTH 43 DEPTH 81	DEPTH 32 WEIGHT 300 lb 137 kg	WEIGHT 300 lb 137 kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	HZ: --	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --	
K3870	7310	Kettle, Jacketed, Steam, 60 Gallon Capacity	A	A	A	A	--	D	--	--	A	--	--		
Fully jacketed steam kettle with a 60 gallon capacity. The kettle body is supported on a pedestal or legs bolted to the floor. The unit operates dependably at any steam pressure between 5 and 25 PSI and requires a steam trap. This unit does not tilt; see JSN K3990 for a tilting kettle. The database height dimension includes the clearance needed to open the kettle cover. The kettle is used in the preparations of soups, sauces, and vegetables in commercial and institutional food service operations. [Price deference verified.]															
			UNIT OF ISSUE: EA	HEIGHT IN: 71 CM: 180	WIDTH 55 DEPTH 109	DEPTH 43 WEIGHT 450 lb 205 kg	WEIGHT 450 lb 205 kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	HZ: --	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --	
K3940	7310	Kettle, Jacketed, Steam, Tilt, 10 Gal, Table Mtd	A	A	A	A	--	D	G	--	A	--	--		
Two-thirds (2/3) or fully jacketed table mounted steam kettle with a 10 gallon capacity. The kettle features direct steam heating from the facility or a self contained steam generator, adjustable feet, anti-splash screen and a flexible drain hose. The unit requires a separate base cabinet or table. The database electrical requirements are for units with a self-contained electrically powered steam source. The database height dimension includes the handle for tilting the kettle. The unit is used to cook food preparations in commercial and institutional food service operations.															
			UNIT OF ISSUE: EA	HEIGHT IN: 33 CM: 84	WIDTH 27 DEPTH 51	DEPTH 20 WEIGHT 163 lb 74 kg	WEIGHT 163 lb 74 kg	VOLTS 1: 2:	PHASE 208 3	AMPS 34 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --	
K3950	7310	Kettle, Jacketed, Tilting, 60 Gallon Capacity, Gas	A	A	A	A	--	D	A	--	--	A	E		
Two-thirds (2/3) or fully jacketed, tilting, 60 gallon capacity kettle. The unit features a self-contained gas-fired steam generator, stainless steel construction, lifting cover, faucet, draw off valve and a kettle body of solid one piece welded construction with heavy duty bar rim. The kettle is mounted on a pedestal base or in a support structure. The tilting mechanism will securely hold the kettle at any angle away from vertical. The database height specification includes the space for opening the kettle lid. The unit is used for wet roasting meats, soups, pie fillings and stews in commercial and institutional food service operations. [All models include both hot and cold water faucets.]															
			UNIT OF ISSUE: EA	HEIGHT IN: 82 CM: 208	WIDTH 59 DEPTH 117	DEPTH 46 WEIGHT 1,000 lb 454 kg	WEIGHT 1,000 lb 454 kg	VOLTS 1: 2:	PHASE 120 1	AMPS 5 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: 150,000	
K3960	7310	Kettle/Mixer, Jacketed, Tilting, Steam, 60 Gal Cap	A	A	A	A	--	D	G	--	A	--	--		
Tilting, direct steam heated, sixty (60) gallon jacketed cooker/mixer. The kettle features a heavy duty stainless steel or painted steel housing, 60 gallon capacity bowl jacketed to 2/3 of the bowls height, primary and secondary agitators powered by heavy duty electric motor(s) which can be tilted up and away from the bowl for pouring and a tilt mechanism which positively locks the bowl in position during pouring. The bowl itself is of solid one-piece welded construction with a heavy reinforced bar rim and a pouring lip. The unit's final installation requires a steam trap assembly. The database height specification includes the clearance needed to lift the mixing assembly clear of the bowl. The depth specification includes the clearance behind the kettle for the lifted agitator mechanism. The unit is a cooker/mixer used to prepare soups, stews, poultry and vegetables in commercial and institutional food service operations.															
			UNIT OF ISSUE: EA	HEIGHT IN: 80 CM: 203	WIDTH 65 DEPTH 150	DEPTH 59 WEIGHT 731 lb 332 kg	WEIGHT 731 lb 332 kg	VOLTS 1: 2:	PHASE 208 120	AMPS 14 10	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --	

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K3980	7310	Kettle/Mixer, Jacketed, Tilting, Steam, 40 Gal Cap	A	A	A	A	--	D	G	--	A	--	--					
<p>Tilting, direct steam heated, forty (40) gallon jacketed cooker/mixer. The kettle features a heavy duty stainless steel or painted steel housing, 40 gallon capacity bowl jacketed to 2/3 of the bowls height, primary and secondary agitators powered by heavy duty electric motor(s) which can be tilted up and away from the bowl for pouring, a faucet and a tilt mechanism which positively locks the bowl in position during pouring. The bowl itself is of solid one-piece welded construction with a heavy reinforced bar rim and a pouring lip. The unit's final installation requires a steam trap assembly. The database height specification includes the clearance needed to lift the mixing assembly clear of the bowl. The depth specification includes the clearance behind the kettle for the lifted agitator mechanism. The unit is a cooker/mixer used to prepare soups, stews, poultry and vegetables in commercial and institutional food service operations. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			76	62	60	700 lb	1: 208	3	14									
			193	157	152	318 kg	2: --	--	--									
K4000	7310	Kettle/Mixer, Jacketed, Tilting, Steam, 80 GAL Cap	A	A	A	A	--	D	G	--	A	--	--					
<p>Tilting, direct steam heated, eighty (80) gallon jacketed cooker/mixer. The kettle features a heavy duty stainless steel or painted steel housing, 80 gallon capacity bowl jacketed to 2/3 of the bowls height, primary and secondary agitators powered by heavy duty electric motor(s) which can be tilted up and away from the bowl for pouring, a faucet and a tilt mechanism which positively locks the bowl in position during pouring. The bowl itself is of solid one-piece welded construction with a heavy reinforced bar rim and a pouring lip. The unit's final installation requires a steam trap assembly. The database height specification includes the clearance needed to lift the mixing assembly clear of the bowl. The depth specification includes the clearance behind the kettle for the lifted agitator mechanism. The unit is a cooker/mixer used to prepare soups, stews, poultry and vegetables in commercial and institutional food service operations. [No other source (s) identified with this description/specification. Vulcan-Hart Corporation discontinued this item with no replacement.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			81	68	64	840 lb	1: 208	3	14									
			206	173	163	382 kg	2: --	--	--									
K4010	7310	Kettle, Cabinet, 2 Unit, Tilting, Steam, 20 Qt Ea.	A	A	A	A	--	D	--	--	A	--	--					
<p>Direct steam heated modular cabinet unit holding two tilting 20-24 quart (5-6 gallon) kettles. The unit has a filling faucet, water and waste connections. Cabinet has a pouring sink. Water and steam controls are mounted for ease of operation and safety. Models with differing size kettles or with electric and gas steam boilers are available. The database height dimension includes the handles for tilting the kettles. This unit is used for preparing food items in commercial and institutional food service operations.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			56	37	35	400 lb	1: --	--	--									
			142	94	89	182 kg	2: --	--	--									
K4030	7310	Kettle/Mixer, Tilting, Table Mtd, Electric, 20 Qt	A	A	A	A	--	D	D	--	--	--	--					
<p>Table mounted, jacketed, tilting, 20 quart mixer/cooker. The unit is made of stainless steel, requires a supporting table and has a self-contained electric steam generator. Larger models are available. The database height and depth specifications include the clearances for lifting the mixing head. The unit is used for preparation of food items in commercial and institutional food service operations. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			41	27	22	291 lb	1: 208	3	18									
			104	69	56	133 kg	2: 120	1	1									
K4150	7310	Roller, Dough, Pie, Counter Mounted	C	C	C	C	--	--	A	--	--	--	--					
<p>Pie dough roller machine. The unit has a stainless steel frame, feeding chute and receiving tray. The unit can be a single or double pass machine and will sheet dough up to 20 inches in diameter. The machine has an operator adjustable thickness control. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			22	33	36	257 lb	1: 120	1	10									
			56	84	91	117 kg	2: --	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K4200	7310	Mixer, Table Mounted, 10 Qt.	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Table mounted food mixer with a 10 quart capacity stainless steel bowl. Unit comes complete with the basic beater and whipping attachments. It is used in large food service operations to mix food items. [These are the only two manufacturers found for a mixer of this size. Hubert (CAGE SR285) offers a 12 Qt. Mixer. Dito Dean (CAGE 0H0S2) has a smaller 5.5 quart machine. Varimixer's (CAGE 0WXJ8) machines start at 20 quarts. No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA		IN:	32	18	25	170 lb	1:	120	1	6	NO							
EA		CM:	81	46	64	78 kg	2:	--	--	--	DEPENDENT: YES							
K4210	7310	Mixer, Table Mounted, 5 Quart	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Tabletop mixer with a 5 quart capacity stainless steel bowl. The unit comes complete with beater and whip attachments. Other attachments are available. The unit is used to prepare food in hotels, restaurants and hospital food service areas. [Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA		IN:	17	11	16	55 lb	1:	120	1	3	NO							
EA		CM:	43	28	41	25 kg	2:	--	--	--	DEPENDENT: YES							
K4230	7310	Mixer, Table Mounted, 20 Quart	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Table mounted mixer with a 20 quart stainless steel bowl. The unit comes complete with beater and wire whip attachments. Some models feature timers and bowl cages. Other accessories and floor standing configurations are available. The unit is gear driven and used to prepare food in hotels, restaurants and hospital kitchen areas.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA		IN:	35	21	27	214 lb	1:	120	1	12	NO							
EA		CM:	89	53	69	98 kg	2:	--	--	--	DEPENDENT: YES							
K4250	7310	Mixer, Free Standing, 30 Quart	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Floor standing mixer with a 30 quart stainless steel bowl. The mixer has a 3/4 HP motor, hand lever bowl lift, overload protection and safety interlocks. Unit comes complete with a flat beater and a wire loop attachment. Bowl guards, other accessories and other voltage models are available. This unit is used in hospital kitchens for mixing food.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA		IN:	54	26	36	456 lb	1:	120	1	20	NO							
EA		CM:	137	66	91	207 kg	2:	--	--	--	DEPENDENT: YES							
K4300	7310	Mixer, Free Standing, 60 Quart	A	A	A	A	--	--	G	--	--	--	--	--	--	--	--	--
Floor standing mixer with a 60 quart tinned or stainless steel bowl. The unit features a 2 HP motor, power bowl lift, timer, overload protection, bowl guards, bowl clamp and safety interlocks. The mixer comes complete with a beater, loop whip and dough arm. Other attachments and voltage/phase options are available. This unit is used in hotels, restaurants and hospital kitchens for mixing food.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA		IN:	58	29	40	1,025 lb	1:	208	3	8	NO							
EA		CM:	147	74	102	466 kg	2:	--	--	--	DEPENDENT: YES							
K4350	7310	Mixer, Free Standing, 80 Quart	A	A	A	A	--	--	G	--	--	--	--	--	--	--	--	--
Floor standing mixer with an 80 quart tinned bowl. The unit features a 2 HP motor, power bowl lift, timer, overload protection, bowl guards, bowl clamp and safety interlocks. The mixer comes complete with a beater, loop whip and dough arm. Other attachments are available. This unit is used in hotels, restaurants and hospital kitchens for mixing food.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA		IN:	65	32	45	1,025 lb	1:	220	3	30	NO							
EA		CM:	165	81	114	466 kg	2:	--	--	--	DEPENDENT: YES							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
K4400	7310	Stand, Mixer, CRS, 2 Shelf, w/Attachment Pole	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Stainless steel mixer stand with mixer attachment pole. The stand body has two shelves, four heavy duty casters (two locking) with rotation bumpers, and a pole with four attachment hooks. The cabinet top is constructed of 14 gauge stainless steel with raised "V" edge on all sides. The cabinet body is of 18 gauge stainless steel, with seamless construction. The database height specification includes the pole height. [.No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
			79	201	27	39 kg	1:	--	--	60	60	NO	--						
			30	69	76		2:	--	--			NO	--						
K4500	7310	Stove, Household, 4 Burner, w/Oven, Electric	A	A	A	A	--	--	G	--	--	--	--	--	--	--	--	E	
Electric household range with four burner stove and oven. Gas models are available. This unit is used in rehabilitation settings to teach daily living skills to patients.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--				
			49	124	30	82 kg	1:	208	3	60	60	NO	--						
			28	76	71		2:	--	--			NO	--						
K4505	7310	Stove, 4 Burner, w/Oven, Microwave	A	A	A	A	--	--	D	--	--	--	--	--	--	--	--	--	
Four burner stove w/oven and microwave, with a conventional oven under the cook top and a microwave oven above the cook top. Unit should incorporate a range hood with a vent to atmosphere. Unit to be used primarily by food inspection team members for checking food quality. [This is the only maker for this item. All of the other major appliance manufacturers have discontinued their lines. An alternative configuration is a standard range with an above-the-range microwave oven which includes a fume hood. The microwave is mounted to the underside of a quarter height or half height cabinet above.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--				
			67	170	30	138 kg	1:	208	1	60	60	NO	--						
			27	69	69		2:	--	--			YES	--						
K4550	7310	Oven, Convection, Double, Electric, Free Standing	A	A	A	A	--	--	G	--	--	--	--	--	--	--	--	E	
Floor mounted double compartment electric convection oven. Each section of the oven has its separate heating elements, dual speed fan, window and controls. Each oven will operate from 150 degrees to 500 degrees Fahrenheit. Either oven compartment can be used as a single oven without requiring the second compartment to heat. Opening the oven doors turns off power to the heating elements and blower motor. The unit has stainless steel sides, front, top and legs. Some manufacturers offer extra deep models or models on casters. The database physical dimensions do not include the manufacturer's recommended clearances for proper ventilation; refer to each manufacturer's technical sheet. The oven is used for roasting, baking and general cooking in large restaurants and hospitals.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--				
			72	183	39	463 kg	1:	208	3	60	60	NO	--						
			40	102	102		2:	--	--			YES	--						
K4560	7310	Oven, Convection, Double, Gas, Free Standing	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	A	E
Floor mounted, double compartment gas convection oven. Each section of the oven has its separate heating elements, dual speed fan, window and controls. Each oven will operate from 150 degrees to 500 degrees Fahrenheit. Either oven compartment can be used as a single oven without requiring the second compartment to heat. Opening the oven doors turns off gas to the heating elements and power to the blower motor. The unit has stainless steel sides, front, top and legs. Some manufacturers offer extra deep models or models on casters. The electrical requirements are for the blower motors and electronic spark ignition. Some models require two electrical circuits (one per oven); refer to the individual model specifications. The database electrical requirements are for the complete oven. The database physical dimensions do not include the manufacturer's recommended clearances for proper ventilation; refer to each manufacturer's technical sheet. The oven is used for roasting, baking and general cooking in large restaurants and hospitals.																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	120,000				
			74	188	38	463 kg	1:	120	1	60	60	NO	120,000						
			40	102	102		2:	--	--			YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
K4640	7310	Oven, Triple, Modular Deck, Gas	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Triple deck gas oven unit with any combination of modular baking and roasting ovens (3 bake, 2 bake/1 roast, 1 bake/2 roast, 3 roast). The three ovens are mounted on a 10" high stand with four (4) 9" high legs. The oven has a stainless steel front with painted sides, top and back. Stainless steel side, top and back panels are available as options. Steam injection for maintaining moisture content is also an option on most models. Each of the three ovens will hold two standard size baking pans. The overall temperature in each oven is regulated by a thermostat adjustable from 150 to 550 degrees Fahrenheit. A signal light in each oven indicates when the oven's heating elements are on. Refer to the manufacturers specific installation instructions for the selected model. The database pricing and dimensions reflect the most costly and largest of the basic oven configurations. The electrical specifications are for powering the temperature controls, signal lights, oven lamps and pilot light igniters. The unit is used in large hospital kitchens and restaurants for baking and roasting food. [Recommend this item remain in database. Sources have been found as indicated.</p> <p>The price difference has been verified. The weight shown is for model 2 and has also been verified. The weight for Model 1 is only 520 lbs. The difference is due in part to ceramic hearths used in the decks of Model 2. Neither model requires electrical connections.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	78	51	33	2,200 lb	1:	--	--	0	144,000								
		CM:	198	130	84	999 kg	2:	--	--	NO									
									DEPENDENT:	NO									
K4660	7310	Oven, Microwave, Heavy Duty, 1000 Watts	A	A	A	A	--	--	B	--	--	--	--	--	--	--	--	--	
<p>Heavy duty, counter mounted, microwave oven which delivers 1000 watts of microwave energy for rapid reheating, defrosting or cooking. The unit's cabinet is made from stainless steel or other rugged material. The touchpad has programmable keys for timing the cooking of specific items and a multiple portion cooking time adjustment key. The unit features an electronic timer with a digital readout. Some models have an additional manual dial timer. The unit can be mounted in a cabinet recess or on a shelf. [Model 2 has an added convection oven feature.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	21	30	20	64 lb	1:	120	1	60	--								
		CM:	53	76	51	29 kg	2:	--	--	NO									
									DEPENDENT:	YES									
K4665	7310	Oven, Microwave, Consumer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
<p>Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	14	24	19	60 lb	1:	120	1	60	--								
		CM:	36	61	48	28 kg	2:	--	--	NO									
									DEPENDENT:	YES									
K4670	7310	Oven, Microwave, Heavy Duty, 1500 Watts	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	--	
<p>Heavy duty, counter mounted microwave oven which delivers 1500 or more watts of microwave energy for rapid reheating, defrosting or cooking. The unit has multiple cooking power levels. The unit's cabinet is made from stainless steel or other rugged material. The touchpad has programmable keys for timing the cooking of specific items and a multiple portion cooking time adjustment key. The unit features an electronic timer with a digital readout. Some models have an additional manual dial timer. Some units will operate at 120 volt power; refer to manufacturers specifications. The unit can be mounted in a cabinet recess or on a shelf. [Price differences verified.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	19	26	26	119 lb	1:	208	1	60	--								
		CM:	48	66	66	54 kg	2:	--	--	NO									
									DEPENDENT:	YES									
K4700	7310	Range, w/Oven, Gas	A	A	A	A	--	--	A	--	--	A	E						
<p>Gas range with a standard or convection oven. The unit features a stainless steel front and top with painted sides; stainless steel sides are available. The range top can have a variety of configurations. The database specifications and pricing are for a six burner basic range with three burners in front and three burners in the rear. The oven has five matched rack position guides and three racks. The gas connections may be via a front or rear manifold. Different models have specific installation requirements, clearances from combustible materials and installation restrictions. Refer to the manufacturers' technical sheets. The database height dimension does not include the riser for an above range shelf. The database electrical specifications are for automatic pilot lighting. The unit is used in hospital food service operations. [The price for the convection oven feature for Model 2 is \$6,540.00. The BTU amount is for the six burners on top of the stove.]</p>																			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
			EA	42	107	40	535 lb 243 kg	120	1	5	60	NO	198,000					
								2:				DEPENDENT:						
K5100	7310	Peeler, Vegetable, 50 Lb. Capacity, Free Standing	A	A	A	A	--	D	G	--	--	--	--					
			Free standing, 50 lb. capacity, electric stainless steel vegetable peeler with a stand, peel strainer and trap. The peeler has a 1 HP motor and peels vegetables using a large, reinforced, rotating plastic peeling disk with the abrasive permanently bonded to its surface. The interior of the hopper also has abrasive bonded to its surface to ensure tumbling of the vegetables. The unit has a lock-on hopper cover, adjustable legs and centralized controls. The peeler can also be configured with a disposal unit rather than a peel strainer and trap. The disposal unit configuration may require a second outlet with a different voltage. This unit is used in large food service operations for peeling vegetables. [No other source(s) identified with this description/specification]															
			EA	60	152	28	262 lb 119 kg	208	3	6	60	NO	--					
								2:				DEPENDENT:						
K5150	7310	Peeler, Vegetable, 30 Lb. Capacity, Free Standing	A	A	A	A	--	D	A	--	--	--	--					
			Free standing, 30 lb. capacity, electric stainless steel vegetable peeler with a stand, peel strainer and trap. The peeler has a 1/2 HP motor and peels vegetables using a large, reinforced, rotating plastic peeling disk with the abrasive permanently bonded to its surface. The interior of the hopper also has abrasive bonded to its surface to ensure tumbling of the vegetables. The unit has a lock-on hopper cover, adjustable legs and centralized controls. The peeler can also be configured with a disposal unit rather than a peel strainer and trap. The disposal unit configuration may require a second outlet with a different voltage. This unit is used in large food service operations for peeling vegetables.															
			EA	56	142	28	242 lb 110 kg	120	1	13	60	NO	--					
								2:				DEPENDENT:						
K5200	7310	Peeler, Vegetable, 15 Lb. Capacity, Portable	A	A	A	A	--	D	A	--	--	--	--					
			Portable, electric, stainless steel vegetable peeler with a 15 lb. capacity. The unit has a 1/3 HP motor, a reinforced plastic peeling disc coated with abrasive, a removable aluminum hopper door and a cam-type pressure lock. The unit can be equipped with a peel strainer and trap or mounted on a wheeled mobile stand. The unit can be easily plugged in and connected to an available faucet for immediate use. The database pricing and physical dimension information refer to a unit with the peel strainer and trap options. This unit is used in hospital kitchens for peeling vegetables. [No other source(s) identified with this description/specification]															
			EA	56	142	21	101 lb 46 kg	120	1	8	60	NO	--					
								2:				DEPENDENT:						
K5550	7310	Rack, Mobile, Refrigerator/Freezer/Transport	A	A	A	A	--	--	--	--	--	--	--					
			Mobile food storage rack for use in food preservation and transport. The unit is made of stainless steel or aluminum, has four heavy duty recessed plate casters and matching pan ledges on the sides. The unit can be used in room temperature, freezer or refrigerated storage and can roll from one type of storage to another. The unit's sides are open or perforated to permit air circulation around the pans when used for refrigerated or freezer storage. Models come with varying types of and distances between the pan ledges. The unit must be able to pass through refrigerator and freezer doorways. The doorway dimensions of the refrigeration equipment selected will determine the size of the rack to procure.															
			EA	70	178	23	82 lb 38 kg	--	--	--	0	NO	--					
								2:				DEPENDENT:						
K5600	7310	Saw, Band, Meat Cutting	C	C	C	C	--	--	D	--	--	--	--					
			Band saw. This is an all aluminum head and door with stainless steel carriage and table working surface. The unit has a direct-reading blade tension indicator and a 1 HP (or greater) electric motor. This unit is used to cut large pieces of meat for cooking. The saw is used in hospital and hotel food service areas.															
			EA	72	183	37	492 lb 224 kg	220	3	15	60	NO	--					
								2:				DEPENDENT:						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
K6245	7310	Cabinet/Server, Heated, 2 Drawer/Compartment	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Two drawer hot food warmer and server with temperature control and full insulation. The unit may be mobile or counter mounted and requires a convenience outlet at point of use. It is used in hospital kitchens to keep hot foods warm prior to serving. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	36	30	34	302 lb	1:	120	1	13	60		NO		--				
		CM:	91	76	86	138 kg	2:	--	--	--	DEPENDENT:		YES		--				
K6250	7310	Cabinet, Food, Heated, Mbl, 2 Compart, Counter Ht	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Mobile electric hot food warmer and server with dual side by side compartments, temperature and moisture controls, full insulation and casters. The unit holds sixteen 2-1/2" x 12" x 20" pans. Models are also available with heating wells on the top of the cabinet. The unit is used in food service operations for keeping hot food warm in the kitchen prior to serving. [No other source(s) identified with this description/specification]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	33	36	28	240 lb	1:	120	1	9	60		NO		--				
		CM:	84	91	71	109 kg	2:	--	--	--	DEPENDENT:		YES		--				
K6255	7310	Cabinet/Server, Heated, Mbl, 3 Drawer/Compartment	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--	
Mobile food heater with drawers or compartments which can hold food items in or out of standard size pans. The unit features stainless steel construction, compartment controls, casters and 3 compartments. Smaller, larger and models with different configurations (such as pass-thru) are available. The unit is designed to keep potatoes and other quick preparation items hot until served. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	47	30	27	350 lb	1:	120	1	13	60		NO		--				
		CM:	119	76	69	159 kg	2:	--	--	--	DEPENDENT:		YES		--				
K6260	7310	Rack, Storage, Food, CRS	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
Four (4) shelf open food storage rack approximately 61" H x 48" W x 15" D. The unit has heavy duty construction with solid 16 or 18 gauge CRS shelves and posts. Some manufacturers' models have galvanized steel shelves which are primed, polyurethane coated and baked to a hard finish. Wire, louvered, perforated and mobile shelving variations are available. The unit is used for open food storage in hospital kitchens.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	63	48	18	88 lb	1:	--	--	--	0		NO		--				
		CM:	160	122	46	40 kg	2:	--	--	--	DEPENDENT:		NO		--				
K6280	7310	Sheeter/Moulder, Dough	A	A	A	A	--	--	G	--	--	--	--	--	--	--	--	--	
Automatic dough sheeter and molder. The unit is electrically powered, has long tables and is designed for heavy use. [No other source(s) identified with this description/specification. Hobart/Adamatic (CAGE 28873) has discontinued its line.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	42	159	48	704 lb	1:	208	3	5	60		NO		--				
		CM:	107	404	122	320 kg	2:	--	--	--	DEPENDENT:		YES		--				
K6300	7310	Sink, Cook's, 1 Compartment	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
Single compartment cook's sink. The sink bowl is 24" long x 24" wide x 14" deep. The sink meets specification MIL-S-19114 for a type I, style C unit. This sink has no drainboards.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	45	31	30	85 lb	1:	--	--	--	0		NO		--				
		CM:	114	79	76	39 kg	2:	--	--	--	DEPENDENT:		NO		--				
K6305	7130	Sink, Cook's, 2 Compartment	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
Cook's sink. This is a two (2) compartment stainless steel sink. The sink's bowls are one-piece, deep drawn seamless 16 gauge stainless steel with all horizontal and vertical corners generously covered. The unit's bowls are 15 inches deep at front and 14 inches deep over the partition between the two compartments. The drain hole is furnished with crumb cup strainer and rubber stopper. The models priced for the database do not include drainboards. This unit is used in large kitchens of hospitals and restaurants for processing food.																			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	CM:	45	52	29	102 lb	--	--	--	--						
					114	132	74	47 kg	2:	--	--	--	DEPENDENT:	NO				
K6660	7310	Sink, Scullery, Triple Compartment	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--
			Three compartment scullery sink with drainboards. The sink bowls are one piece, deep drawn, seamless 16 gauge stainless steel with coved corners. This unit is often modified on site to include a hot water dispenser, a disposal unit (see JSN K2620) and a whirlpool for water circulation and cleaning. It is also frequently a component of a dish-table system leading to a dishwasher. The database pricing is for the sink only. This unit is used in large production kitchens to clean dishes.															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	CM:	45	124	30	410 lb	--	--	--	--						
					115	315	76	187 kg	2:	--	--	--	DEPENDENT:	NO				
K6670	7310	Sink, Soak, Mobile, 1 Compartment	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
			Mobile soak sink. This is a single compartment stainless steel unit. The sink legs are fitted with 4 or 5 inch swivel casters. Two casters have foot locking brakes. The unit is used in kitchens for soaking flatware and other kitchen items.															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	CM:	34	28	28	78 lb	--	--	--	0						
					86	71	71	36 kg	2:	--	--	--	DEPENDENT:	NO				
K6700	7310	Sink, Vegetable Preparation, 2 Compartment	A	A	A	A	--	D	F	--	--	--	--	--	--	--	--	--
			Vegetable preparation sink. This is a two-compartment stainless steel unit with drainboards. The sink is usually fitted with a heavy duty garbage disposal unit (see JSN K2620). The unit can be custom fabricated to specifications. The unit is used for cleaning and rinsing vegetables in a food service operations.															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	CM:	48	99	30	216 lb	--	--	--	0						
					122	251	76	98 kg	2:	--	--	--	DEPENDENT:	NO				
K6720	7310	Slicer, Meat, Table	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
			Table mounted stainless steel meat slicer with gear drive, 12" knife and ratchet lock. Some slicers have two table speeds. Other electrical power configurations are available. [Price difference verified.]															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	CM:	28	31	27	153 lb	120	1	17	60						
					71	79	69	70 kg	2:	--	--	--	DEPENDENT:	YES				
K6750	7310	Cooker, Pressure, Gas, Dual	A	A	A	A	--	D	A	--	--	A	--	--	--	--	--	--
			Two chamber gas pressure cooker. The cooker features a gas steam boiler, two chambers, timers and a supporting cabinet. The steamer is constructed of all-welded stainless steel. The doors have removable inner liners with a full perimeter gasket seal and a mechanism for securing the door against pressure. On some models, the upper chamber can also be used for unpressurized cooking. Single and triple chamber models are also available. This unit is used for the speedy preparation of food in hospital kitchens.															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	CM:	55	36	33	1,050 lb	120	1	6	60						
					139	91	89	477 kg	2:	--	--	--	DEPENDENT:	YES				250,000
K6800	7310	Scale, Ingredient, Dial Or Digital	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
			Ingredient scale with a stainless steel platform and a dial or digital readout for controlling portion size or ingredient amount. The database electrical requirements are for the digital scales.															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	BTUs / HR:						
			EA	CM:	11	11	11	15 lb	120	1	1	60						
					28	28	28	7 kg	2:	--	--	--	DEPENDENT:	YES				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES																		
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6							
K6805	98	Scale, Dial or Digital, Benchtop, 250 Lb. Capacity	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--							
Bench top scale. This is a 250 pound capacity dial or digital type scale. The unit handles light to medium duty weights. The column mounted dial, digital or remote digital readout offers an unobstructed view of the weighing results. The database electrical specifications refer to the digital scales.																									
UNIT OF ISSUE:		EA	HEIGHT IN:	36	WIDTH CM:	91	DEPTH	25	WEIGHT	60 lb	28 kg	VOLTS	120	PHASE	1	AMPS	1	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--	DEPENDENT:	YES
K7180	7310	Table, Bakers, w/Shelf	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	0	NO	NO	--	--	NO	
Baker's table approximately 36" x 84" x 36" with stainless steel frame and lower shelf. Table top can be either stainless steel or hard wood. Table is used to prepare bakery goods in a hospital food service operations and restaurants.																									
UNIT OF ISSUE:		EA	HEIGHT IN:	36	WIDTH CM:	91	DEPTH	36	WEIGHT	301 lb	137 kg	VOLTS	--	PHASE	--	AMPS	--	HZ:	0	NO	NO	--	--	NO	
K7250	7310	Table, Food Preparation, CRS, Mobile	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	--	NO	NO	--	--	NO	
Food preparation table approximately 36"H x 72"W x 36"D with a 5-6" stainless steel backsplash. This unit has options for heavy-duty casters with 5" hard rubber lockable wheels, under-shelves, stationary legs and storage drawers. Some models feature a removable backsplash, full or partial table replaceable plastic cutting boards, a decking section along the backsplash and tapered deck ends.																									
UNIT OF ISSUE:		EA	HEIGHT IN:	41	WIDTH CM:	104	DEPTH	36	WEIGHT	194 lb	88 kg	VOLTS	--	PHASE	--	AMPS	--	HZ:	--	NO	NO	--	--	NO	
K7300	7320	Table, Cutting, Meat	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	--	NO	NO	--	--	NO	
Meat cutting table. The table has a stainless steel frame and legs. Some tables feature replaceable plastic cutting board table tops; other table tops are stainless steel. Other options include casters, lower shelves and backsplashes. [No other source(s) identified with this description/specification.]																									
UNIT OF ISSUE:		EA	HEIGHT IN:	36	WIDTH CM:	91	DEPTH	36	WEIGHT	170 lb	78 kg	VOLTS	--	PHASE	--	AMPS	--	HZ:	--	NO	NO	--	--	NO	
K7400	7310	Table, Machine, CRS	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	0	NO	NO	--	--	NO	
Heavy duty 16 gauge stainless steel table. The table supports food processing machines such as cutter/slicers, mixers and grinders. The table is available in several tabletop sizes and heights or with casters. Custom fabrication is available from some manufacturers.																									
UNIT OF ISSUE:		EA	HEIGHT IN:	35	WIDTH CM:	89	DEPTH	27	WEIGHT	75 lb	34 kg	VOLTS	--	PHASE	--	AMPS	--	HZ:	0	NO	NO	--	--	NO	
K8150	7310	Table, Cook's, w/Pan Rack, 96x72x36	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	0	NO	NO	--	--	NO	
Cook's work table with a pan rack. The table has a stainless steel top, lower shelf and legs. The pot rack hangs approximately 60" above the table work surface. Some tables have risers on the rear edge. See JSN K8190 for a 96" wide table. This unit is used for preparing meals in a food service operation.																									
UNIT OF ISSUE:		EA	HEIGHT IN:	96	WIDTH CM:	244	DEPTH	36	WEIGHT	207 lb	94 kg	VOLTS	--	PHASE	--	AMPS	--	HZ:	0	NO	NO	--	--	NO	
K8190	7310	Table, Cook's, w/Pan Rack, 96x36x36	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	0	NO	NO	--	--	NO	
Cook's work table, 96" wide X 36" deep, with a pan rack and lower storage shelf. The table top, legs and lower shelf are stainless steel. The pot rack hangs approximately 60" above the table work surface. Some tables have risers on the rear edge. See JSN K8150 for a 72" wide table. This unit is used for preparing meals in a food service operation.																									
UNIT OF ISSUE:		EA	HEIGHT IN:	96	WIDTH CM:	244	DEPTH	36	WEIGHT	260 lb	118 kg	VOLTS	--	PHASE	--	AMPS	--	HZ:	0	NO	NO	--	--	NO	

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
K8200	7310	Rack, Wash, Pan/Utensil	A A A A --	--	--	--	--	--	--	--	--	--	--
Pan and utensil wash rack. This unit can be a set of racks to accommodate a specific dishwashing unit. The racks are all stainless steel and can be used in large food service operations for cleaning pots and pans. [No other source(s) identified with this description/specification. Most facilities have switched to using heavy duty plastic racks rather than stainless steel.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	5	28	28	25 lb	1:	--	--	NO	--		
		CM:	13	71	72	12 kg	2:	--	--	NO	--		
K8230	7310	Tenderizer, Meat, Electric	C C C C --	--	A	--	--	--	--	--	--	--	--
Electric meat tenderizer with clear plastic cover. This unit is used to tenderize meats in large food service operations. [No other source(s) identified with this description/specification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	22	20	11	66 lb	1:	120	1	NO	60		
		CM:	56	51	28	30 kg	2:	--	--	NO	--		
K8250	7310	Toaster, Pop-Up, 4 Slice, Electric	C C C C --	--	C	--	--	--	--	--	--	--	--
Four (4) slice, electric pop-up toaster. The toaster casing is made from stainless steel and can produce up to 290 slices/hr. This is used to toast sliced bread in food service kitchens and hospital cafeteria operations. Several electrical power configurations are available; some may require special wall receptacles. Refer to manufacturers' specifications.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	10	13	14	20 lb	1:	208	1	YES	60		
		CM:	25	33	36	9 kg	2:	--	--	YES	--		
K8300	7310	Toaster, Conveyor, 480 Slices/Hr, Electric	C C C C --	--	C	--	--	--	--	--	--	--	--
Electric conveyor toaster. This unit can toast 480 slices per hour. Other electrical configurations are available. This unit is used in large food service operations for fresh toast or warm buns.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	18	18	28	60 lb	1:	208	1	NO	60		
		CM:	46	46	71	28 kg	2:	--	--	YES	--		
K8400	7310	Toaster, Conveyor, 600 Slices/Hr, Electric	C C C C --	--	C	--	--	--	--	--	--	--	--
Conveyor toaster. This unit can toast up to 600 slices/hour. Some models use quartz heaters rather than resistive wire elements. The color of the toast is adjusted by varying the conveyor belt speed. This unit is used in large food service operations, for fresh toast or warm buns.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	18	20	24	65 lb	1:	208	1	NO	60		
		CM:	46	51	61	30 kg	2:	--	--	YES	--		
K8410	7310	Toaster, Conveyor, 1000 Slices/Hr, Gas	C C C C --	--	A	--	--	A	E				
Gas fired conveyor toaster 1000 slice per hour capacity. This unit is made of stainless steel and uses natural or propane gas. The toaster has an automatic pilot ignition system and requires venting. This unit is used in large kitchens and food service operations for efficient preparation of large quantities of toast and bread products. [No other source(s) identified with this description/specification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	34	22	15	87 lb	1:	120	1	NO	60		
		CM:	86	56	38	40 kg	2:	--	--	YES	--		
K8460	7310	Assembly Line, Tray, Custom	C C C C --	--	--	--	--	--	--	--	--	--	--
Custom built tray assembly line. This unit shall be custom planned for individual hospital tray service requirements. The unit is stainless steel and mobile. The unit is used in hospitals for patient tray makeup. Price and dimensions depend on unit set-up requirements. [This JSN is an architectural note. There are too many possible variations from site to site to derive a reasonable cost estimate. All of the three listed vendors sell a complete line of the components that make up a tray assembly line.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	--	--	--	-- lb	1:	--	--	NO	0		
		CM:	--	--	--	-- kg	2:	--	--	NO	--		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K8470	7310	Starter Unit, Meal Tray Assembly Line, CRS	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
<p>Tray starter, patient tray service assembly line. The unit is made form corrosion resisting steel (CRS) and has a tray lifter section, dish lifter section, silverware compartments, doily shelf and condiment compartments. Some units also have shelves behind the tray dispenser. The database pricing is for a unit sized to hold 15" x 20" patient trays. The unit is mounted on heavy duty casters. This unit is used to start patient feeding tray assembly in a hospital food service operation. [No other source(s) identified with this description/specification. Levelmatic, Carter-Hoffman, Aztec and Lakeside all have wheeled self-leveling dispenser carts for silverware and trays and secondary condiment units. Together, the two units from these manufacturers are equivalent to this JSN. Database price includes an open rear storage compartment with 3 stainless steel shelves.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	DEPENDENT:	NO	BTUs / HR:	--	--
			61	155	32	32	325 lb	1:	--	--	--							
					81	81	148 kg	2:	--	--	--							
K8480	7310	Transport Cart, Meal Tray, Low Profile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Enclosed patient food tray transporter. The unit has the same tray capacity as most standard units but a lower profile due to closer tolerances and smaller casters. The unit is constructed of stainless steel and has 2 doors, 2 heavy duty swivel and 2 heavy duty fixed casters, push handles, tray guides and a full perimeter bumper. The size of the facility's food trays will determine which model to procure. This cart generally holds 28 meal trays. The unit is used in hospitals for transporting food to patients areas.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	DEPENDENT:	NO	BTUs / HR:	--	--
			50	127	57	36	381 lb	1:	--	--	--							
					145	91	173 kg	2:	--	--	--							
K8500	7310	Rack, Tray/Pan, Mobile, CRS, Light/Medium Duty	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Mobile tray and pan rack. The rack is made of stainless steel or aluminum and has matched ledges for holding trays and pans. The rack is mounted on medium duty casters. Racks are available in various heights, with channel or angled ledges and in several ledge spacing intervals. The size of the facility's pans and trays will determine the exact model procured. The rack is used to bus dirty trays from the serving line for cleaning and washing.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	DEPENDENT:	NO	BTUs / HR:	--	--
			73	185	23	29	70 lb	1:	--	--	--							
					58	74	32 kg	2:	--	--	--							
K8670	7310	Urn, Coffee, 2 Section, 3 Gallons Each, Electric	A	A	A	A	--	--	--	--	--	D	C	--	--	--	--	--
<p>Electric twin coffee urn with a total capacity of six (6) gallons, three (3) in each urn. The urn features an electronic power pack control panel and automatic brewing action. The unit is constructed of stainless steel and fully insulated on all sides. The unit is used in hospital food service operations for the preparation and service of fresh coffee.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	DEPENDENT:	YES	BTUs / HR:	--	--
			35	89	35	21	118 lb	1:	208	1	30							
					89	53	54 kg	2:	--	--	--							
K8820	7310	Urn, Coffee, 2 Section, 6 Gallons Each, Steam	A	A	A	A	--	--	--	--	--	D	A	--	A	--	--	--
<p>Steam heated twin coffee urn (without stand), 29" high X 34" wide X 19" deep with a total capacity of twelve (12) gallons, six (6) in each urn, an adjustable by-pass and automatic agitator. It also has a one and two pound selector for brewing either one or two pounds of coffee at a time. The unit may require a steam trap as part of its installation. This type of unit is used in hospital food service operations for the preparation of fresh coffee. [These are the only two manufacturers found making steam brewers. Brewmatic (Cage Code 00666) has discontinued their steam coffee urns. No other source identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	DEPENDENT:	YES	BTUs / HR:	--	--
			34	86	38	20	135 lb	1:	120	1	5							
					97	51	62 kg	2:	--	--	--							
K8920	7310	Urn, Coffee, 2 Sections, 6 Gallons Each, Electric	A	A	A	A	--	--	--	--	--	D	C	--	--	--	--	--
<p>Electric twin coffee urn (without stand) with a total capacity of twelve (12) gallons, six (6) in each urn, adjustable by-pass and an automatic agitator. The unit is used in hospital food service operations for preparing large volumes of fresh coffee.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	DEPENDENT:	YES	BTUs / HR:	--	--
			37	94	38	23	130 lb	1:	208	1	40							
					97	58	59 kg	2:	--	--	--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
K9080	7310	Urn, Coffee, 2 Section, 10-15 Gallons Each, Steam	A	A	A	A	--	D	A	--	A	--	--						
		Steam heated twin coffee urn with a capacity of 20-30 gallons (10-15 gallons in each urn), adjustable bypass and automatic agitation. The unit is used in hospital food service areas, for preparation and service of large volumes of hot coffee. [These are the only two manufacturers found making steam brewers. Price difference verified. Brewmatic (Cage Code 00666) has discontinued their steam coffee urns. No other source identified with this description/specification.]																	
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	HR:	
						35	46	22	212 lb	1:	120	1	5						
						89	117	56	97 kg	2:	--	--	--						
K9120	7310	Urn, Coffee, 2 Section, 10 Gallons Each, Gas	A	A	A	A	--	D	A	--	--	A	E						
		Gas heated twin coffee urn (without stand) with a total capacity of twenty (20) gallons, ten (10) in each urn, a safety pilot and two burners. This type unit is used in hospital food service operations to serve large volumes of hot coffee. [Only one manufacturer found making gas brewers this size. No other source(s) identified with this description/specification.]																	
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	HR:	
						38	42	23	212 lb	1:	120	1	5						
						97	107	58	97 kg	2:	--	--	--						35,000
K9140	7310	Urn, Coffee, 2 Section, 10-15 Gallons Ea, Electric	A	A	A	A	--	D	C	--	--	--	--						
		Electric twin coffee urn (without stand) with a total capacity of twenty (20) gallons, ten (10) in each urn, an adjustable by-pass and automatic agitation. The unit is used in hospital food service areas for preparing and serving large volumes of hot coffee. [Price difference verified.]																	
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	HR:	
						47	46	23	212 lb	1:	208	3	42						
						119	117	58	97 kg	2:	--	--	--						--
K9300	7310	Washer, Pressure w/Sanitizer	A	A	A	A	--	D	A	--	--	--	--						
		Pressure washer for cleaning and sanitizing kitchen or other areas. This is a wall mounted, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. See JSN K1350 for the mobile version of this unit. The unit is used for cleaning in commercial areas and institutions such as hospitals. [No other source(s) identified with this description/specification. There are other pressure washers available but they do not have NSF (National Sanitation Foundation) approval.]																	
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	HR:	
						37	20	20	140 lb	1:	120	1	13						
						94	51	51	64 kg	2:	--	--	--						--
K9320	7310	Hose, Spray, Pre-Rinse	A	A	A	A	--	D	--	--	--	--	--						
		Pre-rinse spray hose. The unit is a chrome plated wall or back deck mount design used to rinse dishes before racking in the dishwasher. It has a dual lever control which permits quick water temperature selection, large non-slip grip spray valve and spring loaded goose neck with storage hook.																	
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	HR:	
						40	8	15	10 lb	1:	--	--	--						
						102	20	38	5 kg	2:	--	--	--						--
K9450	7310	Washer, Tray, Automatic Stacking, Electric	A	A	A	A	--	D	G	--	--	--	E						
		Tray washer. This unit has eye thermometers, vacuum breaker, motor starter and standard overload protection mounted in a stainless steel enclosure. The unit features a remote stop button on the unloading side of the unit. The continuously moving belt has fingers or racks for easily mounting trays for cleaning. The database height dimension includes the clearance to open and remove a door panel. These washers vary widely in length and capacity; consult the manufacturer's specifications for the specific model. This washer can be found in food service operations of hotels, restaurants and hospitals. [Prices sensitive to the options selected. Price variance verified.]																	
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	HR:	
						85	168	37	2,000 lb	1:	208	3	54						
						216	427	94	908 kg	2:	--	--	--						--

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
K9600	7310	Washer, Cart, Automatic, Electric And Steam	A	A	A	A	--	D	G	--	A	--	E					
Automatic cart washer. This unit is a CRS, roll-through unit with wash, rinse and dry cycles to accommodate pastry cabinet utility carts and non-electric, non-motorized food carriers. The washer will be a compartment type and have a reciprocating spray pressure washer system constructed of stainless steel. With the spray head suspended on rollers from a stationary back in the washer, this unit is designed specifically for processing clustered racks and carts. [Model 1 is a roll-on roll-off with only one door. Price difference verified. Prices may vary based on options selected.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	104	85	96	4,500 lb	1:	208	3	140	NO		--					
		CM:	264	216	244	2,043 kg	2:	120	1	5	DEPENDENT: NO							
K9750	7310	Washer, Garbage Can, Pedestal, Steam	A	A	A	A	--	D	B	--	A	--	E					
Pedestal type garbage can washer, steam. Used to clean and sanitize both large and small, round, square or oblong, garbage refuse, waste or food cans, drums, barrels, or any other containers with an overall diameter up to 25 inches, (without limitation of height). [Model 2 can accept trash cans up to 36" in height and 22" in diameter. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	64	31	34	350 lb	1:	120	1	1	NO		--					
		CM:	163	79	86	159 kg	2:	--	--	--	DEPENDENT: YES							
K9760	7310	Washer, Pot/Pan, Electric	A	A	A	A	--	D	G	--	--	--	E					
Pot and pan washer. This unit's wash and rinse cycles pump water and cleaning solution under pressure through its upper and lower spray arms. The washer cleans pots, large preparation bowls and kitchen appliance parts. The unit drains after each cycle. The database information is for a straight pass through unit with an electric tank heater. Corner units and units with chemical or low temperature sterilization are available. The database physical specifications include the clearance needed to remove the unit's vertical doors and the extra footprint of exterior mounted control boxes and pipe connections. This unit is used in hospitals and large food service areas.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	106	51	42	800 lb	1:	208	3	50	NO		--					
		CM:	269	130	107	364 kg	2:	--	--	--	DEPENDENT: YES							
K9770	7310	Washer, Pot/Pan, Steam And Electric	A	A	A	A	--	D	G	--	A	--	E					
Pot and pan washer with a steam heated tank. The washer is made of stainless steel and has a 5 HP wash pump motor, hot water spray rinse, sanitizing hot fresh water rinse, steam or electric water temperature booster, exhaust fan and basket screens. See K8200 for the washing racks for this machine.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	109	51	36	1,050 lb	1:	208	3	125	NO		--					
		CM:	277	130	92	477 kg	2:	--	--	--	DEPENDENT: YES							
K9900	7310	Dispenser, Water Metering, Automatic, Electric	A	A	A	A	--	A	A	--	--	--	--					
Water metering device. The unit automatically measures and dispenses up to 80 gallons of water to its adjacent kettles, braising pans or other equipment. The dispenser housing is made of stainless steel and has an 18" swing spout. The database height dimension includes the faucet height. [Model 3 is 220V.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	32	51	14	55 lb	1:	120	1	3	NO		--					
		CM:	81	130	36	25 kg	2:	220	1	4	DEPENDENT: YES							
L0075	6650	Microscope, Stereo, Photographic, Desk Top	C	C	C	C	--	--	A	--	--	--	--					
Photo-Microscope system. Unit produces crisp, high resolution images over the entire photo magnification range. The system includes focusing tube, coupler, shock mounted shutter, distortion-free amplifier lens, cable release and 35mm camera. The unit has approximate 7.5 magnification factor, a halogen light source for color, balanced photomicrography, plan fluorite objectives for clarity and flatness of field for full image viewing and accurate image production and an automatic match of film to correct reciprocity. Other attachments are available. Unit is a stereo microscope for viewing of non-translucent samples. [Prices are determined by the manufacturers on an average configuration of the unit. Final price is dependent upon tailored options chosen.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	31	18	54	45 lb	1:	120	1	5	NO		--					
		CM:	78	46	137	20 kg	2:	--	--	--	DEPENDENT: YES							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES										
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5
L0080	6640	Microscope, Inverted, Tissue Culture	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
		Inverted phase contrast microscope. Can be easily changed to accommodate various brightfield, darkfield or phase contrast transmitted light techniques. Unit has a selective light source, fluorescence system for maximum transmission and various filter and objective combinations to meet specific requirements while using different techniques. Used for tissue culture research and routine medical laboratory examinations. Unit to be equipped with lighting and exposure controls suitable for photomicroscopy. Provided with optional camera mount, and 35mm camera back. Unit includes inverted stage and light sources to accommodate tissue culture bottles. This is not a stereo microscope. Models identified are representative systems; specific configurations will result in varying costs. [Prices are determined by manufacturers on average configuration of the unit. Final price is dependent upon options chosen.]															
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE 2:	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
		EA	22	55	22	33 lb 15 kg	120	--	1	60	YES	YES	--				
L0085	6650	Microscope, Karyotyping, Digital Image	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--
		Digitally enhanced microscope system capable of karyotyping GTG-stained smears for cytogenetic analysis. The system supports chromosome identification and fluorescent in situ hybridization (FISH) analysis. The system includes an optical microscope, video image capture system, filter wheel, printer, microcomputer, workstation and image enhancement software. It has an image spectral range of 510 to 620 nm. The system requires two dedicated electrical circuits to operate. [The prices provided include the cost of a microscope. Applied Imaging (OZTX4) does not normally supply the microscope. Consequently a microscope must be bought separately but must meet Applied Imaging's specifications. Applied Imaging's recommended vendors for microscopes include Carl Zeiss (CAGE 0VZ56), Olympus (CAGE 32212), Nikon (CAGE 1EC13) and Leica (CAGE 0F735). MetaSystems recommends and provides the Zeiss microscope Axioplan2ie with their Karyotyping System.]															
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE 2:	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
		EA	48	122	33	250 lb 114 kg	120	120	1	60	YES	YES	--				
L0090	6530	Table, Microscope, 1-2 Person	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--
		Microscope table for one to two viewers. The table has no casters, secured adjustable work positions and adjustable pedestal legs. Work top is 1" thick and pressure resistant. Different size options are available. Used as a single or dual teaching microscope table.															
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE 2:	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
		EA	33	84	72	152 lb 69 kg	--	--	--	--	NO	NO	--				
L0095	6530	Table, Microscope, Teaching, 3-5 Person	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
		Teaching microscope table. Table can seat four or more people at once and is equipped with non skid adjustable glides for precise leveling. Table top offers resistance to heat and chemicals. There are different sizes and options available. Used for microscope instruction and general biology experiments.															
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE 2:	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
		EA	30	76	42	300 lb 137 kg	--	--	--	--	NO	NO	--				
L0100	6650	Microscope, Binocular	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
		Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques. [Model 1 uses a 20 W halogen bulb. Price of all models will vary based on final configuration of microscope.]															
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE 2:	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
		EA	19	48	23	33 lb 15 kg	120	--	1	60	NO	YES	--				

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
L0105	6655-00-526-7785	Microscope, Binocular, Phase Contrast	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
		Binocular laboratory microscope. Characteristics include a 6V, 20W tungsten halogen lamp, quadruple revolving nosepiece, a binocular body, un-graduated mechanical stage, 4X, 10X, 40X and 100X plan achromatic objectives. Unit has a 1.25 condenser with mount, an auxiliary swing-in condenser, two (10X) widefield eyepieces, dual diopter adjustment and may include a carrying case. Used in the laboratory to perform observations on laboratory cultures and samples. Microscope to be provided with appropriate light source and filters for phase contrast microscopy.																	
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
		EA	16	10	15	18 lb	1:	120	1	1	60	NO	--						
			41	25	38	9 kg	2:	--	--	--	DEPENDENT:	YES	--						
L0110	6650	Microscope, Trinocular	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
		Trinocular microscope. The microscope is equipped with achromatic objectives for advanced work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen use and a high intensity 11V, 100 watt halogen lamp for constant color temperature and illumination. Characteristics/components include a centerable field diaphragm, two built-in filter turrets permitting combinations of selective light balance and color compensating filters. Unit also has an auxiliary swing in condenser, basic stand, graduated mechanical stage, 4X, 10X, 40X and 100X objective condenser with mount, immersion oil eye-piece with a 10X wide field eyepiece. [Prices are determined by the manufacturer on an average configuration of this unit. Final price is dependent upon tailored options chosen.]																	
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
		EA	14	7	8	14 lb	1:	120	1	2	60	NO	--						
			36	18	22	6 kg	2:	--	--	--	DEPENDENT:	YES	--						
L0115	6650	Microscope, Photographic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
		Photo-Microscope system. Unit produces crisp, high resolution images over the entire photo magnification range. The system includes focusing tube, coupler, shock mounted shutter, distortion-free amplifier lens, cable release and 35mm camera. The unit has a 7.5X magnification factor, halogen light source for color, balanced photomicrography, plan fluorite objectives for clarity and flatness of field for full image viewing and accurate image production and an automatic match of film to correct reciprocity. Other attachments are available. [Prices are determined by the manufacturers on an average configuration of the unit. Final price is dependent upon tailored options chosen.]																	
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
		EA	24	18	28	45 lb	1:	115	1	3	60	NO	--						
			61	46	71	20 kg	2:	--	--	--	DEPENDENT:	YES	--						
L0125	6650	Microscope, Projection / Video System	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
		Microscope with video output. The system enhances the image optically and electronically with amber and green illuminated arrows to point out interesting features. Four objectives 4X to 100X are available and there are different condensers for brightfield, darkfield and phase contrast. A special 1.40 achromatic condenser is available for use with fluorite objectives. Used for laboratory conferences and training. [No other source(s) identified with this description/specification.]																	
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
		EA	19	15	24	26 lb	1:	110	1	1	0	NO	--						
			47	38	60	12 kg	2:	--	--	--	DEPENDENT:	NO	--						
L0140	6640	Microscope, Fluorescence	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
		Fluorescence microscope. Provides different filter combinations that can be easily changed to accommodate various brightfield, darkfield or phase contrast transmitted light techniques. It has a selective light source, fluorescence system for maximum transmission and various filter and objective combinations to meet specific requirements while using different techniques. Used for research and routine medical examinations. [Final price is dependent upon selection of objectives.]																	
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
		EA	16	12	10	20 lb	1:	120	1	2	60	NO	--						
			41	30	25	9 kg	2:	--	--	--	DEPENDENT:	YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L0142	6640	Microscope, Fluorescent, Photographic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
		Fluorescent microscope. Provides different filter combinations that can be easily changed to accommodate various brightfield, darkfield or phase contrast transmitted light techniques. It has a selective light source, fluorescence system for maximum transmission and various filter and objective combinations to meet specific requirements while using different techniques. Used for research and routine medical examinations. Unit is equipped with lighting and exposure controls suitable for photomicroscopy. Provided with optional camera mount, and 35mm camera back. [Actual price is dependent upon selection of objectives.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	22	55	17	15	34 lb	120	1	3	60	NO	--					
			CM:				16 kg	2:	--	--	NO	--						
											YES	--						
L0145	6640	Microscope, Teaching, Multiple Head	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
		Multiple head teaching microscope. Designed to accommodate from two to six viewers simultaneously, providing each observer an identical image of the specimen with exact orientation and intensity of the image. Magnification ranges from 4X to 100X and there is a five-place nosepiece with knurled-edge gripping surface for easy rotation. The microscope accepts 32 or 45mm filters and has other accessories available for various configurations.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	19	48	72	24	53 lb	120	1	4	60	NO	--					
			CM:				24 kg	2:	--	--	NO	--						
											YES	--						
L0147	6640	Microscope, Teaching, Multiple Head (18)	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
		Eighteen head teaching microscope. [System is available, however without specific application/requirements a budget price cannot be determined. Use as a placeholder. System is available from the listed manufacturers. Specific application/requirements (objectives) will determine actual price.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	--	--	--	-- lb	115	1	10	60	NO	--						
			CM:			-- kg	2:	--	--	--	NO	--						
											NO	--						
L0160	6600	Tissue Processor, Vacuum	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
		Vacuum infiltrator tissue processor. The unit is computer controlled and has a self-contained cleaning system. A pressure/vacuum cycle is provided for better infiltration and exchange of fluids. Used for specimen preparation for electron microscopes.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	53	135	32	32	355 lb	120	1	12	60	YES	--					
			CM:				161 kg	2:	--	--	YES	--						
											YES	--						
L0200	6640	Protein Analysis System	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	
		Protein analysis system for use in the clinical laboratory. System includes the analyzer, a keyboard and CRT, and a printer for logging out the results of analysis. [Model 1 part # is 470000. Dimensions and weight are for the analyzer only and do not include the computer and printer.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	30	76	44	26	270 lb	120	1	12	60	NO	2,900					
			CM:				123 kg	2:	--	--	YES	--						
											YES	--						
L0205	6640	E.I.A. Analysis System, Advanced	C	C	C	C	--	C	B	--	--	--	--	--	--	--	--	
		Enzyme Immunoassay Analysis (E.I.A.) system for use in the clinical laboratory. System includes sample management center, dynamic incubator and parallel processing system.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	22	56	80	27	218 lb	115	1	15	60	NO	--					
			CM:				99 kg	2:	--	--	YES	--						
											YES	--						
L0210	6640	E.I.A. Analysis System, Basic	C	C	C	C	--	C	B	--	--	--	--	--	--	--	--	
		Basic Enzyme Immunoassay Analysis (E.I.A.) system for use in the clinical laboratory. System includes sample management center, analyzer module, and plate washing system. [No other source(s) identified with this description/specification]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	13	33	28	17	83 lb	110	1	5	50/60	NO	--					
			CM:				38 kg	2:	--	--	NO	--						
											NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
L0211	6640	E.I.A. Plate Washer System	C C C C --	C	B	--	--	--	--	--	--	--	--
Enzyme Immunoassay Analysis (E. I. A.) plate washer system for use in the clinical laboratory.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	BTUs / HR:			
EA	CM:	IN: 9	14	17	28 lb	1: 120	1	5	HZ SWITCH: YES	--			
		CM: 23	36	43	13 kg	2: --	--	--	DEPENDENT: NO	--			
L0215	6640	Hemoglobin Analysis System	C C C C --	--	B	--	--	--	--	--	--	--	H
Analyzer used to run glucated hemoglobin test for the A1c component of hemoglobin which is a specific clinical indicator used in tracking diabetes progress. System uses an automated ion exchange chromatography for specific analysis with C.V.S. of 2%. After sample preparation and loading, system will process up to 100 samples per batch in a walk away mode.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	BTUs / HR:			
EA	CM:	IN: 20	32	28	65 lb	1: 120	1	7	HZ SWITCH: NO	--			
		CM: 51	81	71	30 kg	2: --	--	--	DEPENDENT: YES	--			
L0990	6640	Analyzer, Urine, Basic	C C C C --	--	A	--	--	--	--	--	--	--	--
Basic urine analysis system. Automated system provides 8 chemistries. Unit requires only power connection. This unit is a benchtop instrument. [Price difference verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	BTUs / HR:			
EA	CM:	IN: 21	20	21	90 lb	1: 120	1	5	HZ SWITCH: YES	--			
		CM: 53	51	53	41 kg	2: --	--	--	DEPENDENT: NO	--			
L0995	6640	Analyzer, Urine, Advanced	C C C C --	--	A	--	--	--	--	--	--	--	--
Advanced urine analysis system. Automated system provides chemistry and image analysis of a batch of urine samples. Unit requires only power and a drain connection. This unit is a freestanding workstation. [Price differences verified. No other source(s) identified with this description/specification. When ordering from Nova Biomedical (Cage Code 59941), please specify, "With auto diluter".]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	BTUs / HR:			
EA	CM:	IN: 27	25	24	90 lb	1: 120	1	5	HZ SWITCH: YES	--			
		CM: 69	64	61	41 kg	2: --	--	--	DEPENDENT: NO	--			
L1000	6640	Analyzer, Blood Chem, Auto, 60 Samples/Hour	C C C C --	E	B	--	--	--	--	--	--	--	A
Automatic blood/chemistry analyzer. It is a four parameter electrolyte analyzer. The unit measures Na, K, Cl concentrations using an ion selective electrode and CO2 concentrations using differential pH. The analyzer also accepts whole blood, plasma, serum and urine and has an automatic calibration capability. [No other source(s) identified with this description/specification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60	BTUs / HR:			
EA	CM:	IN: 21	25	21	90 lb	1: 120	1	5	HZ SWITCH: NO	--			
		CM: 53	64	53	41 kg	2: --	--	--	DEPENDENT: YES	--			
L1005	6630	Chromatograph, Gas, General	C C C C --	--	F	--	--	--	--	--	--	--	--
General gas chromatograph. Unit can access all types of columns and has a dual module capability for combination of injection systems. It is equipped with automatic or manual sampling valves, programmable temperature vaporizer, six detectors to choose from, four independent heated zones, two signal outputs and memory protection for 24 hours. The gas chromatograph operates in the range of 10-40 degrees Centigrade with a 0-95% relative humidity. Used for packed or capillary column chromatography.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	BTUs / HR:			
EA	CM:	IN: 21	31	25	118 lb	1: 120	1	20	HZ SWITCH: NO	--			
		CM: 53	79	64	54 kg	2: --	--	--	DEPENDENT: YES	--			
L1010	6630	Chromatograph, Gas, Mass Spectrometer	C C C C --	--	F	--	--	--	--	--	--	--	D
Gas Chromatograph with mass spectrometer. The unit provides single or simultaneous dual channel operation, a range of injector and detector combinations, a full color display unit and a visual comparison of samples internally or externally. [Model 1, AutoSystem XL includes Programmable Pneumatic Control and Autosampler.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	BTUs / HR:			
EA	CM:	IN: 24	50	28	220 lb	1: 120	1	20	HZ SWITCH: YES	5,000			
		CM: 61	127	71	100 kg	2: --	--	--	DEPENDENT: YES	5,000			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L1015	6630	Chromatograph, Liquid	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--
Liquid chromatograph. The unit can accommodate up to 3 detectors. It provides low dispersion characteristics for short and narrow columns, UV/VIS detection, single or dual channel integration micro sampling from 1ml to 10ml, a single pump with low or high pressure gradients and wavelength change detection from 190nm to 700nm.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			23	23	22	161 lb	1:	120	1	15	60	NO	--					
			58	58	56	73 kg	2:	--	--	--	YES	YES	--					
L1020	6630	Chromatograph, Ion	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--
Ion chromatograph. Capabilities/components include automatic compensation for different carrier samples, multi-linear temperature programmability, 4 isothermal plateaus and injectors and detectors. It operates in the temperature range of 100-450 degrees C. The injection ports accept 1/8" and 1/4" columns and glass on-column. It has two auxiliary head zones and manual or automatic pneumatic controls. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			19	31	25	119 lb	1:	120	1	20	50/60	YES	--					
			48	79	64	54 kg	2:	--	--	--	NO	NO	--					
L1025	6620	Analyzer, Chemistry, Drug Screening	C	C	C	C	--	E	C	--	--	--	--	--	--	--	--	A
Drug screening analyzer. It is a random access chemistry analyzer system. The system's capabilities/components include 23 test channels. Over 600 tests per hour; it accepts sample volumes from 2ml to 20mL, fluorescence/light scatter. Used for measuring electrolytes, routine chemistries, special proteins, therapeutic drug monitoring, EIA and fluorescence immunoassay applications. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			69	111	32	1,166 lb	1:	208	1	20	60	YES	5,869					
			175	282	81	530 kg	2:	--	--	--	YES	YES	--					
L1030	6630	Analyzer, Chemistry, Stat, High Capacity	C	C	C	C	--	E	C	--	--	--	--	--	--	--	--	A
Stat chemistry analyzer, high capacity. The unit performs tests in 3-1/2 to 10 minutes. The test parameters are serum, urine and CSF. The unit performs at least 33 routine tests. The analyzer can process at least 63 samples at a time with a maximum analytical rate of at least 600 tests per hour. It is used for electrolytes, blood hematocrit and other routine chemistries. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			69	74	40	1,166 lb	1:	208	1	20	60	YES	6,000					
			175	188	102	530 kg	2:	--	--	--	NO	NO	--					
L1035	6630	Analyzer, Chemistry, Stat	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
Stat chemistry analyzer. The unit performs tests in <10 minutes. The test parameters are serum, urine and CSF. The unit performs over 37 routine tests. The analyzer can process 100 samples at a time with a maximum analytical rate of 420 tests per hour. It is used for electrolytes, blood hematocrit and other routine chemistries.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			69	74	36	1,135 lb	1:	220	1	20	60	NO	7,040					
			175	188	91	516 kg	2:	--	--	--	YES	YES	--					
L1040	6630	Spectrometer, Infrared, Single Beam	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--
Infrared Single Beam Spectrometer. Characteristics/components include 8mm beam size, LiTaO3 and temperature stabilized FR-DTGS detectors, scan time from 4 seconds at 4 cm-1, and scan range from 7800 to 350 cm-1. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			17	31	24	94 lb	1:	120	1	15	60	NO	--					
			42	79	62	43 kg	2:	--	--	--	YES	YES	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L1050	6640	Cytometer, Flow, Clinical Laboratory	C	C	C	C	--	--	F	--	--	A	F					
Flow cytometer. This system features the capability to analyze up to 4 colors of immunofluorescence from a single air cooled laser. Other multi-color applications include: multi-parametric DNA analysis, platelet studies, reticulocyte enumeration, cell biology/functional studies as well as broad range research. This instrument is self contained and biohazard safe. [No other source(s) identified with this description/specification. Dimensions are for Sensor unit only. Weight includes the computer. Two dedicated 20 amp, 120 VAC power circuits with dedicated grounds are required.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	27	40	26	350 lb	1:	120	1	20	60	NO	--					
		CM:	69	102	66	159 kg	2:	--	--	--	60	YES	--					
L1055	6640	Cytometer, Flow, Advanced Laboratory	C	C	C	C	--	B	D	--	--	A	F					
Flow cytometer. This is a high-performance system used for innovative research in immunobiology, cell physiology, molecular biology, genetics, water quality and plant cell analysis. This system features the capability to analyze and to sort up to 6 colors simultaneously while performing complex multi-parameter applications such as DNA qualifications, functional studies, chromosome enumeration or physiological measurements. [No other source(s) identified with this description/specification. Requires isolated ground and dedicated 20 amp circuit for cytometer. Additional lasers will require 220 VAC power. (Note: Model 2 does not have a vendor cover sheet due vendor imposed protection on their pdf document.)]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	51	70	70	800 lb	1:	120	1	20	60	NO	--					
		CM:	130	178	178	364 kg	2:	220	1	30	60	YES	--					
L1060	6640	Screening Device, Cystic Fibrosis	C	C	C	C	--	--	A	--	--	--	--					
Cystic fibrosis analyzer. The unit characteristics/components include a readout in mEq/l on a 2ml sample size, an analysis in less than one minute, for analysis capacity of up to 10 complete patient cycles per hour, analyzer range 0-200 mEq per liter and a pilocarp stimulator. Mostly used in pediatrics clinics for iontophoresis and analysis. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	8	9	8	9 lb	1:	120	1	2	60	NO	--					
		CM:	20	23	20	4 kg	2:	--	--	--	60	YES	--					
L1070	6640	Analyzer, BUN, Discrete	C	C	C	C	--	--	A	--	--	--	--					
Discrete BUN analyzer. The unit characteristics include blood, urea and nitrogen measurements, sample volume 10mL with not less than 51 samples per hour capacity, automatic fill and drain cycles and readout samples in mg/dL or mmol/L. Used to analyze serum or plasma. [No other source(s) identified with this description/specification. Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	21	20	21	90 lb	1:	120	1	5	60	NO	--					
		CM:	53	51	53	41 kg	2:	--	--	--	60	YES	--					
L1075	6530	Bath, Cryoprecipitate Thawing (+4 Deg C)	C	C	C	C	--	--	F	--	--	--	--					
A 17 gallon cryoprecipitate thawing water bath or equivalent. Unit designed to operate at plus 4 degrees centigrade for thawing units of cryoprecipitate in the blood bank. Unit includes both heating (650 watts) and cooling systems (1/4 HP) to maintain a constant temperature plus or minus 0.02 degrees centigrade around a plus 4 degree centigrade operating temperature. Unit includes dual stage circulating pump to maintain a uniform temperature throughout the tank. Unit capable of thawing twelve (12), 250ml plasma bags in approximately 2 hours. [Model's 2 and 3 are provided as possible alternatives to Model 1, Forma 2762 from Thermo Forma.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		IN:	35	32	28	304 lb	1:	120	1	13	60	NO	1,600					
		CM:	89	81	71	138 kg	2:	230	1	8	60	NO	1,600					

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
L1080	6640	Analyzer, Chemistry, Multichannel	C	C	C	C	--	E	D	--	--	--	--	--	--	--	--	--	
Laboratory chemistry analyzer. The unit is capable of at least 23 chemistries including electrolytes by ISE (ion-selective electrode). The analyzer can perform any combination of tests, panels or stats on a given sample. The unit has automatic QC and maintenance functions. The instrument is programmable for as many as 400 patient samples. [Price difference verified. The database width and depth dimensions include manufacturer's recommended clearances. Many instruments require a telephone line for remote diagnostics by the manufacturer (see JSN A1012). This instrument is often leased or used on a cost per test basis rather than purchased.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	HZ SWITCH: YES	BTUs / HR: 7,040				
			EA	IN:	75	74	47	1,500 lb	1:	220	1	20	DEPENDENT:	NO					
				CM:	190	188	119	681 kg	2:	120	1	30							
L1085	6625	Analyzer, Coagulation, Automatic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Automatic coagulation analyzer. The unit performs on-site blood coagulation tests, prothrombin time (PT), and partial thromboplastin time (PTT) tests on whole blood or plasma samples. The analyzer employs both single and duplicating or stat testing capabilities.			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60	HZ SWITCH: YES	BTUs / HR: --				
			EA	IN:	19	35	28	198 lb	1:	120	1	4	DEPENDENT:	NO					
				CM:	48	89	71	90 kg	2:	--	--	--							
L1090	6640	Cell Washer, Frozen Blood Deglycerolizer	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--	
Automated cell washer designed to deglycerolize frozen packed red cells. Used in the blood bank and at frozen blood depots to prepare frozen cells for administration to patients. [Prices verified. No other source(s) identified with this description/specification.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	HZ SWITCH: NO	BTUs / HR: --				
			EA	IN:	52	32	28	185 lb	1:	120	1	10	DEPENDENT:	YES					
				CM:	132	81	71	84 kg	2:	--	--	--							
L1095	6640	Cell Saver, Autologous Blood Recovery	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--	
Autologous blood recovery system, also known as a "Cell Saver." Used in the operating room and laboratory to wash extravascular blood free of debris, clots, etc., and to make the blood safe for re-infusion into the patient.			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60	HZ SWITCH: YES	BTUs / HR: --				
			EA	IN:	35	23	21	180 lb	1:	120	1	7	DEPENDENT:	NO					
				CM:	89	58	53	82 kg	2:	--	--	--							
L1097	6525	Irradiator, Blood	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Blood irradiator for suppressing graft versus host disease in immunocompromised patients. The irradiator exposes and rotates the blood product on the presence of a radioactive cesium-137 or cobalt-60 source. The radioactivity damages certain parts of the blood products so they do not attack the receiving patients tissues when infused. Database pricing reflects unit emitting between 2,200 to 3,400 Curies. [The price for Model 1 from MDS Nordion can range from \$100,000 up to \$170,000, depending on the options chosen.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	HZ SWITCH: NO	BTUs / HR: --				
			EA	IN:	80	32	39	4,700 lb	1:	120	1	15	DEPENDENT:	YES					
				CM:	203	81	99	2,134 kg	2:	--	--	--							
L1100	6630	Meter, pH	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
pH meter. The units capabilities/characteristics include ion analyzer capability, provides measurements of pH, temperature, MV and others. The unit includes self-diagnostics, an automatic buffer recognition and a gel-filled electrode. Used for direct measurement of activity concentration.			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60	HZ SWITCH: YES	BTUs / HR: --				
			EA	IN:	3	11	8	4 lb	1:	120	1	1	DEPENDENT:	NO					
				CM:	8	29	20	2 kg	2:	--	--	--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L1105	6640	Co-Oximeter	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Co-oximeter analyzer. The unit calculates hemoglobin/oxygenation concentrations. The analyzer characteristics/components include a sample readout in no longer than 45 seconds, dual beam optics and a hollow cathode lamp. It is used to calculate oxygen content, capacity, and measured saturation and correlates closely with reference methods.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			CM:					1:			60							
				19	12	19	40 lb	120	1	10	NO							
				48	30	48	19 kg	2:	--	--	YES							
L1110	6630	Pheresis Unit	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
Cyto/plasma pheresis unit. The unit processes blood withdrawn from a donor and separates and retains leukocytes and/or plasma and retransfuses the remainder to the donor. It processes the cells through a centrifugal action that allows separation of the components.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			CM:					1:			60							
				61	22	30	435 lb	120	1	15	NO							
				155	56	76	198 kg	2:	--	--	YES		1,900					
L1112	6630	Welder, PVC Blood Tubing, Sterile Process	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
PVC blood tubing welder used to provide custom, sterile connections for blood collection units and for determination of apheresis collection units. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			CM:					1:			60							
				10	10	10	15 lb	120	1	1	NO							
				25	25	25	7 kg	2:	--	--	YES							
L1115	6630	Analyzer, Hematology, Differential, Automatic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Automatic hematology counter/analyzer. The analyzers characteristics/components include the measurement of eight hematology parameters as well as platelet counts, auto-rinse cycle between analysis, minimum specimen requirement of 100 microliters, readout results in 40 seconds, automatic calibration and capable of computerized differential counting and manual verification of results. Used for hematology analysis. [Price difference verified.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			CM:					1:			50/60							
				40	32	27	360 lb	120	1	6	YES							
				102	81	69	164 kg	2:	--	--	YES							
L1120	6630	Electrophoresis, General	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
General purpose electrophoresis work center. All of the electrophoresis chambers, electrophoresis leads, incubator, drying oven, power supplies and staining dishes shall be combined into a single compact work center. The unit will have carbon graphite electrodes for better charge distribution, temperature control to 45 degrees C, and variable voltage settings from 50 to 300 Volts. It is used in research and diagnostic laboratories for various studies. [Dimensions are for the analyzers. Price difference verified.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			CM:					1:			60							
				26	36	24	158 lb	120	1	10	NO							
				66	91	61	72 kg	2:	--	--	YES							
L1125	6630	Electrophoresis, Thin Layer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Thin layer electrophoresis apparatus. The unit is complete with all accessories to cast and run agarose cells, including main chamber. Used in the laboratory for protein determinations.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			CM:					1:			60							
				6	13	11	19 lb	120	1	3	YES							
				15	33	29	9 kg	2:	--	--	YES							
L1130	6640	Densitometer, Scanning	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Scanning densitometer. This is a high capacity, fully automated unit. The unit can accommodate routine media, agarose film, cellulose acetate, TLC plates and fluorescence wavelengths. The carrier can accept media up to 150mm and run up to four tests and analyze 64 scans in 12 minutes. Used for electrophoresis scanning. System includes computer and printer. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
			CM:					1:			50/60							
				56	32	30	240 lb	120	1	4	YES							
				142	81	76	109 kg	2:	--	--	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
L1160	6640	Densitometer, Blood	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Blood densitometer. The characteristics include automatic computer capabilities, automatic calibration and scanning. The densitometer has a fluorescence lamp, two detectors, shall scan all standard media at a rate of 1 per 6 seconds and have a capacity of up to 30 fractions per sample. It can be used to handle both colorimetric and fluorometric procedures. Includes PC computer and printer. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	22	23	24	104 lb	1:	120	1	4	60		YES		--				
		CM:	56	58	61	48 kg	2:	--	--	--	NO		NO		--				
L1180	6640	Dilutor, 1:25,000 Dilution	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Pipetter/Diluter. It has a sample volume of 20 micro liters and a diluent volume of 5 ml and is compatible with most caustic lab solutions such as HCL, H2SO4 glacial acetic acid, cholesterol reagent, total lipid reagent and a vast number of other corrosives. Each instrument is precisely calibrated to assure dilution accuracy and reproducibility with in 1%. The system also has a factory preset volume ration. The cycle light indicates when units are ready to sample or the dispense hand has a reagent draw-back feature that prevents sample reagent mixing inside the pipette after the dispensing cycle. This is a precise automatic instrument for sampling and dispensing. Used for hemoglobin determinations, and other required dilutions.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	14	7	9	20 lb	1:	115	1	5	60		NO		--				
		CM:	36	18	23	9 kg	2:	--	--	--	NO		YES		--				
L1181	6630	Hemoglobinometer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Hemoglobinometer. This is a modular unit for determination of hemoglobin in grams /100/ml. The unit provides automatic rinse and self-blanks between samples and has a cuvette capacity of 3ml with a range of 0 to 25g/dl minimum. Used for determination of hemoglobin parameters. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	17	10	13	38 lb	1:	120	1	5	0		NO		--				
		CM:	43	25	33	18 kg	2:	--	--	--	NO		YES		--				
L1182	6640	Refractometer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Refractometer. Characteristics/ components include an accommodation of liquids, solids, solids-in-liquids and powders, temperature measured at interface of samples, photosensors measurement, automatic calibration, multi-channel programming, an accuracy of +/- .0001 refractive unit and automatic temperature compensation. Used for glucose and urine refractive indexes.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	14	10	12	16 lb	1:	120	1	3	60		NO		--				
		CM:	36	25	30	7 kg	2:	--	--	--	NO		YES		--				
L1185	6620	Analyzer, Glucose	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Discrete glucose analyzer. Characteristics include sample volume of 10 microliters, measurement principle of the oxygen rate method, throughput of 67 samples per hour and a glucose value displayed in mg/dl. This is a self contained system with automatic fill and drain cycles. Used for glucose analysis of serum plasma or saliva samples.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	15	14	12	42 lb	1:	120	1	6	60		NO		--				
		CM:	38	36	30	19 kg	2:	--	--	--	NO		YES		--				
L1190	6630	Osmometer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Osmometer. Characteristics/components include semi-automatic operation, measurement of osmolarity of 0.2ml samples, accuracy to (+/-) 0.5%, temperature controlled liquid freezing bath, flow-through cell assembly and high speed testing capability. Used to determine precise concentration of solute particles for urines, urea, free water clearances, electrolyte studies, serum and other applications.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	12	13	17	43 lb	1:	120	1	5	60		YES		--				
		CM:	30	33	43	20 kg	2:	--	--	--	YES		YES		--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L1200	6640	Cabinet, Specimen, Pass Thru, CRS	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Pass-through specimen cabinet. The unit has a sight-proof interlocking door that permits only one door to open at a time. It also includes a removable spill tray, corrosion resistant stainless steel welded construction with seamless corners and burr-free edges and is able to adjust to wall thickness between 3-6 inches. Used for passage of specimens from patient area to laboratory. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	13	14	6	-- lb	1:	--	--	--	NO							
		CM:	33	36	15	-- kg	2:	--	--	--	NO							
L1300	6640-00-145-1180	Centrifuge, Small, Blood Typing, Variable Speed	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Small laboratory centrifuge with variable speed allowing both regular and delicate centrifugation. It has a brake to allow a complete stop in 10 seconds, 0 to 30 minute timer, interchangeable heads and can accommodate up to 24 tubes. Used for blood grouping and cross matching.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	18	18	22	121 lb	1:	120	1	10	60 NO							
		CM:	46	46	56	55 kg	2:	--	--	--	60 YES							
L1350	6640-00-412-9450	Centrifuge, Table, Small, 3200 RPM, 6 Place	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Small table centrifuge. Characteristics/components include a speed range up to 3200 RPM, steel guard bowl, electric motor, speed controlled by a dial rheostat, a six place trunnion head to accommodate 15 ml tubes contained in metal shields with rubber cushions, numbered tube slots and a safety cap. Used in a laboratory for general purpose centrifugation of samples. [Model 3 is distributed by Cardinal (800 964-5227) under product #C1800-3.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	13	15	19	66 lb	1:	120	1	10	60 NO							
		CM:	33	38	48	30 kg	2:	--	--	--	60 YES							
L1400	6640-00-299-9835	Centrifuge, Microhematocrit, 24 Tube	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Microhematocrit centrifuge. Characteristics/components include speed up to 1300 RPM, a flat head to accommodate 24 capillary tubes, electronic automatic timer that times from 2-15 minutes, built-in precise hematocrit scale and a removable carrying tray. Used for determination of hematocrits.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	9	11	11	22 lb	1:	120	1	2	60 NO							
		CM:	24	28	28	10 kg	2:	--	--	--	60 YES							
L1500	6640-00-412-9008	Centrifuge, Medium Duty, Refrigerated, Floor Model	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Laboratory centrifuge. This is a medium to large capacity unit with an operating range of -20 degrees to 40 degrees C. It permits running samples at body temperature. It also has a rotor imbalance detector and an auto-shut down capability if the rotor load is out of balance. The unit is constructed of a stainless steel chamber with a rear exhaust and is a low heat output unit. Used in laboratories to spin samples for further analysis. [Model 2 temperature range is from -5 C to 40 C. Model 3 temperature range is from -10 C to 40 C.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	58	30	40	558 lb	1:	208	1	30	60 NO							
		CM:	147	76	102	254 kg	2:	220	1	10	60 YES		7,000					
L1502	2664-0	Centrifuge, Tabletop	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	--
Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis. [Manufacturer for Model 1 was formerly known as Sorvall, Inc.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	16	29	26	275 lb	1:	208	1	30	60 NO							
		CM:	41	74	66	125 kg	2:	--	--	--	60 YES		5,000					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L1660	6640	Cell Washer/Centrifuge	C	C	C	C	--	I	A	--	--	--	--	--	--	--	--	
Combination cell washer and centrifuge. The unit has two fixed speeds of 3600 or 12000 RPM. It is a microprocessor controlled unit with a programmable memory that can hold up to four wash cycles. It has a built-in peristaltic pump with a drain, dual angle rotor, low saline level alarm and uses 10 X 75mm or 12 X 75mm tubes. Used for compatibility testing, cytological studies and other laboratory applications.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	25	WIDTH CM:	14	DEPTH	17	WEIGHT	54 lb	VOLTS 1:	120	PHASE	1	AMPS	6	HZ:	60
									25 kg		2:	--		--			HZ SWITCH:	NO
																	DEPENDENT:	YES
																	BTUs / HR:	--
L1670	6640	Centrifuge, Refrigerated, Floor Model	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	
Refrigerated centrifuge. This is a floor standing unit with a solid state speed control system that has speeds ranging from 150 to 6000 RPM. Other characteristics include a temperature range of -9 to +39 degrees C., dual range digital timer, rotor imbalance detection, a programmable memory and a dynamic brake with three deceleration rates. The unit also has a refrigeration system that consists of a low maintenance compressor and a coil wrapped insulated guard bowl. Used in laboratories for processing heat sensitive samples.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	50	WIDTH CM:	127	DEPTH	40	WEIGHT	627 lb	VOLTS 1:	208	PHASE	1	AMPS	30	HZ:	60
									285 kg		2:	--		--			HZ SWITCH:	NO
																	DEPENDENT:	YES
																	BTUs / HR:	7,000
L1680	6640	Centrifuge, Refrigerated, Benchtop	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Refrigerated benchtop centrifuge. Characteristics/components include a 30 minute timer, an aluminum 18" diameter chamber, an automatic door interlock, an imbalance detector, a self-balancing drive, temperature range from -5 to 25 degrees C., 1/3 HP-compressor, chamber wrapped with direct-coil copper tubing providing precise temperature control and total maximum capacity of 4 X 250 ml. Used in laboratories to prepare samples for further analysis.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	16	WIDTH CM:	41	DEPTH	30	WEIGHT	237 lb	VOLTS 1:	120	PHASE	1	AMPS	13	HZ:	60
									108 kg		2:	--		--			HZ SWITCH:	NO
																	DEPENDENT:	YES
																	BTUs / HR:	3,071
L1690	6640	Centrifuge, Serological, Multi Speed, Benchtop	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Serological centrifuge. The unit is a multi speed, fast accelerating and braking centrifuge. It can utilize a swinging bucket rotor with inserts that have a capacity of 1.5ml to 4-150ml tubes. The unit's maximum speed is in the range of 10,000 to 15,000 RPM. It is designed for general-purpose serological applications with blood and urine.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	17	WIDTH CM:	43	DEPTH	26	WEIGHT	173 lb	VOLTS 1:	120	PHASE	1	AMPS	5	HZ:	60
									79 kg		2:	--		--			HZ SWITCH:	NO
																	DEPENDENT:	YES
																	BTUs / HR:	1,600
L1750	6640-00-412-9300	Centrifuge, Heavy Duty, Floor Model, Refrigerated	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	
Heavy duty laboratory centrifuge. Characteristics include a large sample capacity with multipurpose capabilities, maximum speed 6000 RPM, maximum volume of 4000 ml and a choice of three deceleration rates. Used in laboratories to prepare samples for analysis.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	63	WIDTH CM:	160	DEPTH	40	WEIGHT	700 lb	VOLTS 1:	208	PHASE	1	AMPS	30	HZ:	60
									318 kg		2:	--		--			HZ SWITCH:	NO
																	DEPENDENT:	YES
																	BTUs / HR:	7,000
L1770	6640	Ultracentrifuge	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	
Ultracentrifuge. The unit handles tubes from 0.2ml to 3.5ml, has a programmable memory for repeat of select runs and has selectable acceleration and deceleration rates. It operates in the range from 2-40 degrees C. The unit has a digital timer, and electronic door locking mechanism. The maximum speed is 90,000 RPM. Applications range from use as a simple pelleting device to the quantitation of molecular species by sedimentation equilibrium measurements. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	40	WIDTH CM:	102	DEPTH	27	WEIGHT	450 lb	VOLTS 1:	230	PHASE	1	AMPS	30	HZ:	60
									205 kg		2:	--		--			HZ SWITCH:	NO
																	DEPENDENT:	YES
																	BTUs / HR:	3,400

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
L1780	6640	Centrifuge, Cytology	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Cyto-Centrifuge. The characteristics/components include a specimen chamber designed to avoid slide damage, fluid path for premature absorption and a disinfectant tank for prevention of pathogenic aerosol. The unit has a maximum speed of approximately 2,000 RPM. Used for cell sedimentation and dispersion on a glass slide and other laboratory applications.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	10	17	25	32 lb	1:	120	1	5	60	NO	--						
			25	43	64	15 kg	2:	--	--	--	DEPENDENT:	YES	--						
L1930	6630	Analyzer, pH/Blood Gas	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
PH/blood gas analyzer. The unit has a pH, PCO2 and PO2 electrode and performs calculations for CO2, HCO3, and base excess. Characteristics of the unit include: an automatic calibration capability, measurement ranges of 6.4 to 8.0 for pH, 0 to 800 mmHg for PO2 and 8.0 to 200.mmHg. for PCO2, and an analysis time of 40 seconds. Used in laboratories for several pH/blood gas determinations.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	28	17	23	68 lb	1:	120	1	10	60	NO	--						
			71	43	58	31 kg	2:	--	--	--	DEPENDENT:	YES	--						
L1931	6630-00-065-4203	Analyzer, Blood Gas	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Blood/gas analyzer. The unit measures for pH, PO2, and PCO2 using a standard sample of 90 microliters or greater. A measurement range of 6.4 to 8.0 for pH, 8 to 200mmHg for PCO2 and 0 to 800 mmHg for PO2 is accommodated by the unit. Used in laboratories to measure blood gas parameters of patient samples. System to provide for the measurement of: pH, pCO2, pO2, BP, tHb, NA+, K+, and CL-, or CA++. Calculated values to include: tCO2, O2 Saturation, CT, HCO3 (actual and standardized), BE (vv and vt) and Hct.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	22	22	19	85 lb	1:	120	1	10	60	NO	--						
			56	56	48	39 kg	2:	--	--	--	DEPENDENT:	YES	--						
L1940	6630	Analyzer, Lead	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Lead analyzer used to determine the lead content of medical samples. Also used to test for iron. [Model 1 is a bench top model consisting of two components for rapid analysis. Models 2 and 3 are portable, battery operated hand held devices.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	18	19	17	36 lb	1:	120	1	2	50/60	NO	--						
			46	48	43	17 kg	2:	--	--	--	DEPENDENT:	YES	--						
L1945	6650	Distilling Apparatus, Xylene Recovery	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Xylene still for reprocessing used Xylene. Some manufacturers offer an accessory spill catch pan. [Larger sizes are available from each manufacturer/vendor.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	72	33	40	350 lb	1:	120	1	15	60	NO	--						
			183	84	102	159 kg	2:	--	--	--	DEPENDENT:	YES	--						
L1946	6650	Recycling System, Formalin	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	E	
Formalin recycling system. The system reclaims used formalin by means of a microprocessor controlled automated process. The system is capable of recycling up to 5 gallons in 6 to 8 hours (or less).																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	62	40	24	170 lb	1:	115	1	15	60	NO	--						
			157	102	61	78 kg	2:	--	--	--	DEPENDENT:	YES	--						
L1950	6640	Demineralizer, Water, Floor Mounted, 1/2-3 GPM	A	A	A	A	--	--	B	A	--	--	--	--	--	--	--	--	
Floor mounted water demineralizer. The unit has a one half to three gpm capacity. It has two beds, automatic calibration, purity meter, recirculation pump and disposable cartridges. The system continuously recirculates to discourage growth. Used to produce high purity water for laboratory use. May also be wall mounted. [These units are all wall mounted.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	31	35	18	100 lb	1:	120	1	12	60	NO	--						
			79	89	46	46 kg	2:	--	--	--	DEPENDENT:	YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES										
				A	N	A	V	I	1	2	3	4	5	6
L2000	4610	Purification System, Water	A A A A --	B	A	--	--	--	--					
Water Purification System (also referred to as a water-polishing unit) that is capable of producing not less than 24 liters of water per hour, free of ionic contamination and with reduced Total Organic Compounds (TOC) not to exceed 6 parts per billion and water resistivity up to 18.3 megohm-cm from a clean (tap) water source. Purified water to be used for HPLC or GC/MS applications and TOC analysis. System must utilize operator replaceable cartridges and UV light source to obtain the specified purity. System must be fully automatic and switch to a standby mode during periods of reduced use. Design must incorporate a resistivity indicator and a final bacterial 0.22 micrometer filter.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60	BTUs / HR:				
EA		IN:	24	20	16	80 lb	1:	120	1	3	HZ SWITCH: NO			--
		CM:	61	51	41	37 kg	2:	--	--	--	DEPENDENT: YES			
L2060	6640	Dryer, Glassware, Electric	A A A A --	I	F	--	A	--	--					
Electrically heated glassware dryer. The unit is constructed of stainless steel, has an adjustable automatic or manual timer and operates to a temperature of 325 degrees Fahrenheit. It has a hot air circulation and exhaust system with a drying compartment that is 25"W X 23"L minimum. Used to dry glassware and non heat sensitive parts in the hospital. [Model 1 is 208 V, 3 Phase while other models are one phase.]														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60	BTUs / HR:				
EA		IN:	90	41	37	1,200 lb	1:	208	1	22	HZ SWITCH: NO			13,000
		CM:	229	104	94	545 kg	2:	208	3	21	DEPENDENT: YES			
L2191	6525	Calibrator, Radioisotope	C C C C --	--	A	--	--	--	--					
Radioisotope dose calibrator. The characteristics/components include a self test feature that verifies the operation of the entire unit, continuous or on demand activity measurement, 0.1-199.9 micro Curie resolution range, response time less than 5 seconds, a hermetically sealed pressurized argon ionization chamber and an accuracy of plus or minus 0.5%. Used to ensure the dose rate of the radioisotope prescribed.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60	BTUs / HR:				
EA		IN:	17	12	21	43 lb	1:	120	1	1	HZ SWITCH: YES			--
		CM:	43	30	53	20 kg	2:	--	--	--	DEPENDENT: NO			
L2192	4460	Purifier, Air	A A A A --	--	A	--	--	--	--					
Air purifier. This is a commercial type unit, system may be wall or ceiling mounted, or portable. It has the capability to clean 10,000 cubic feet of area. It also has a variable speed control and a charcoal filter. Used in the facility anywhere that odors need to be removed from the air.														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60	BTUs / HR:				
EA		IN:	29	25	18	35 lb	1:	120	1	3	HZ SWITCH: NO			--
		CM:	74	64	46	16 kg	2:	--	--	--	DEPENDENT: YES			
L2200	6640	Hood, Fume, Floor Standing	A A A A --	I	B	--	--	--	E					
Floor standing fume hood. The unit presented is 4 Ft but is available in other sizes. It will include a fluorescent light fixture, blower switch with pilot light, at least one duplex receptacle, a cup sink and shall be acid resistant. The minimum average face velocity shall be 100 fpm. It includes a safety glass sash resistant to heat of up to 71 degrees centigrade. Static pressure loss is not to exceed 0.22 inches. The fume hood also has adjustable baffles. Other custom options are available. Used in laboratories to prepare samples requiring the use of toxic and or flammable materials. [Model 1 includes the following accessories: 9901000, 9847101, 4005200 and 1432600. Model 2 includes the following accessories: 164M34, 164424M156 and NU 55-424. Model 3 includes the following accessories: 36L260, 20LS8320, 121S8320, 32L657CW, 611S7320 and 34L9400.]														
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60	BTUs / HR:				
EA		IN:	98	49	40	682 lb	1:	120	1	15	HZ SWITCH: NO			--
		CM:	249	124	102	310 kg	2:	--	--	--	DEPENDENT: YES			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L2205	6640	Hood, Fume, Floor Standing, Explosion Proof	A	A	A	A	--	I	B	--	--	--	--	E				
<p>Floor standing fume hood. A 4 foot model is specified, other sizes available. It will include an incandescent or fluorescent light fixture (if compatible with being explosion proof), blower switch with pilot light, at least one duplex receptacle, a cup sink and shall be acid resistant. The minimum average face velocity shall be 100 fpm. It includes a steel framed safety glass sash resistant to heat of up to 71 degrees centigrade. Static pressure loss is not to exceed 0.22 inches. The fume hood also has adjustable baffles. Other custom options are available. Used in laboratories to prepare samples requiring the use of toxic and or flammable materials. Unit shall be explosion proof and suitable for use with organic volatile substances. Duplex receptacle will be external to the hood work area. All fittings will be explosion proof. [Model 1 has an explosion proof integral blower.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			100	48	34	822 lb	1:	120	1	15	60	NO	--					
			254	122	86	374 kg	2:	--	--	--	YES	--						
L2210	6640	Hood, Fume, Floor Standing, Perchloric	A	A	A	A	--	I	B	--	--	--	E					
<p>Floor standing fume hood. The unit is 4 Ft wide, also available in 5 or 6 Ft width. It will include a vapor proof incandescent light fixture, blower switch with pilot light, at least one duplex receptacle, a cup sink and shall be acid resistant. The minimum average face velocity shall be 100 fpm. It includes a steel framed safety glass sash resistant to heat of up to 71 degrees centigrade. Static pressure loss is not to exceed 0.22 inches. The fume hood also has adjustable baffles. Other custom options are available. Used in laboratories to prepare samples requiring the use of toxic and or flammable materials. Unit shall be suitable for use with strong acids and will include the needed wash down facilities. Duplex receptacle will be mounted exterior to the hood.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			95	48	34	784 lb	1:	120	1	20	60	NO	--					
			241	122	86	356 kg	2:	--	--	--	YES	--						
L2250	6640	Hood, Fume, Bench	A	A	A	A	--	I	F	--	--	--	E					
<p>Benchtop fumehood. This is an auxiliary air type to be sized as required. The unit will have a remote switch with a pilot light, a fluorescent light, an acid resistant fan and blower housing. The minimum average face velocity shall be 100 fpm. It shall include a steel frame sash that is heat resistant to 71 degrees centigrade. The static pressure loss shall not exceed 0.22 inches of water at 100 fpm face velocity. Other accessories and gases are as defined during the design of the facility.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			66	48	43	347 lb	1:	120	1	15	60	NO	--					
			168	122	109	158 kg	2:	--	--	--	YES	--						
L2255	6640	Canopy, Hood, Exhaust Stack, Individual	A	A	A	A	--	--	--	--	--	--	E					
<p>Canopy fumehood. The unit is fabricated from corrosion resistant steel or aluminum, dimensions as indicated on design drawings, fire suppression systems and any other special requirements to be defined during the facility design. This approximate 9 inch by 9 inch canopy hood provides for removal of the exhaust from the exhaust stack of an atomic absorption spectrophotometer or flame photometer used in clinical or research laboratory settings. Canopy attaches to a dedicated exhaust stack which is part of the building HVAC system. Device does not have any local motor/blower and flow rate is to be determined by the A&E's mechanical engineers. [This item must be custom built to specifications unique to each facility. Estimated cost is \$1000.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			16	15	15	4 lb	1:	--	--	--	--	NO	--					
			41	38	38	2 kg	2:	--	--	--	NO	--						
L2270	6640	Hood, Fume, Radioisotope	A	A	A	A	--	B	D	--	--	--	E					
<p>Radioisotope fumehood. The unit requires a charcoal trap filter, lead-lined or HEPA filter as required by codes and use criteria in the exhaust stack, not part of this hood. Other characteristics are that it be strong enough to support lead shielding bricks, have at least two duplex receptacles and a cup sink. The minimum average face velocity shall be 100 fpm and the static pressure loss through the hood shall not exceed 0.2 inches of water at 100 fpm face velocity (700 CFM).</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			96	48	33	769 lb	1:	120	1	15	60	NO	--					
			244	122	84	350 kg	2:	208	1	10	YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L2275	6640	Hood, Fume, Radioisotope, Bench, w/Glovebox	A	A	A	A	--	--	F	--	--	--	--	C				
		<p>Bench type radioisotope fumehood. Characteristics/components include a glove-box, a 75 cfm. blower with indicating switch and variable speed power stat and manometer mounted on box front to indicate air flow, 1/4" safety glass viewing panel, three polarized and grounded electrical outlets with indicating switches, a 24 inch fluorescent light with fixtures and switch, two 8 inch double grooved glove ports and neoprene gloves, an inlet filter, two absolute filters with connecting hoses and 40 inches of 2 inch spiral exhaust hose with clamps and a variable height mobile bench, 30-37"H. Unit is customized to fit the specified use requirements. [Model 1 includes the following accessories: 5065100, 5062001 and 5005600. Manufacturer recommends a 4"round exhaust hose to reduce static pressure.</p> <p>Model 2, LabGard 704-400 has two electrical outlets instead of the three shown in the Description. The LabGard 704-400 is a 4 ft. model but also comes in 3 ft. and 6 ft. models.</p> <p>Only two sources found that meet this description.]</p>																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 83	63	32	800 lb	1: 120	1	15	60	NO	--						
			CM: 211	160	81	364 kg	2: --	--	--	60	YES	--						
L2280	6640	Hood, Laminar Flow, Horizontal, Free Standing, 6ft	C	C	C	C	--	--	B	--	--	--	--					
		<p>Horizontal laminar flow hood. This is a freestanding unit that meets or exceeds Class 100 requirements set for Federal Standard 209B. The unit will have HEPA filters, a washable and reusable pre-filter, a work surface and side walls of type 304 stainless steel construction, duplex electrical receptacles, high velocity return air slots that provide an air curtain at the work area, work surface and side walls and blowers with an average velocity of 100 fpm. Used for work with non-hazardous materials where clean particle free air is required. 6 foot model, other sizes available.</p>																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 75	76	34	775 lb	1: 120	1	19	60	NO	--						
			CM: 190	193	86	352 kg	2: --	--	--	60	YES	--						
L2290	6640	Hood, Laminar Flow, Horizontal, Bench Top, 4ft	C	C	C	C	--	--	B	--	--	--	--					
		<p>Bench top horizontal laminar flow fumehood. The unit meets or exceeds Class 100 requirements set for Federal Standard 209B. The unit characteristics/components are: HEPA filters, a washable and reusable pre-filter, work surface and side walls of type 304 stainless steel, duplex electrical receptacles, high velocity return air slots to provide an air curtain at the work area, work surface and side walls and a blower to provide an average velocity of 100 fpm. Used for work with non-hazardous materials where clean particle-free air is required. 4 Foot model represented, other sizes are available.</p>																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 60	52	35	450 lb	1: 120	1	17	60	NO	4,910						
			CM: 152	132	89	205 kg	2: --	--	--	60	YES	--						
L2310	6640	Cabinet, Bio Safety, Class II/A, F/S, Vert, 4ft	C	C	C	C	--	--	B	--	--	--	--					
		<p>Bio safety cabinet, Class II, Type A. This is a vertical freestanding unit with a face velocity of 100 fpm, constructed of type 304 stainless steel. The inside walls have a high velocity air return. The unit utilizes 70% air recirculation 30% exhaust either into room or through to the outside. It requires HEPA and includes a removable work tray, built-in drain valve, two valve penetrations with blanking plugs, duplex outlet and a fluorescent lamp. Used for low to moderate risk biological agents with the absence of volatile toxic chemicals and radionuclides. 4 foot model, other sizes available.</p>																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 92	52	35	730 lb	1: 120	1	15	60	NO	--						
			CM: 234	132	89	332 kg	2: --	--	--	60	YES	--						
L2315	6640	Cabinet, Bio Safety, Class II/A, Bench, Vert, 4ft	C	C	C	C	--	--	B	--	--	--	--					
		<p>Class II, type A, bio safety cabinet. This is a bench type vertical unit with a face velocity of 100 fpm of type 304 corrosion resistant stainless steel with one piece construction of side walls and rear. The safety cabinet's side walls are slotted for high velocity air return. This utilizes a 70% air recirculation and 30% exhausted either into the room or outside. It is equipped with zero probed HEPA filters, removable work trays, a built in drain valve, two grounded key petcocks, a grounded duplex receptacle and a fluorescent lamp. Used in the laboratory for low to moderate risk biological agents with an absence of volatile toxic chemicals and radionuclides. 4 foot model, other sizes available.</p>																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 66	56	33	688 lb	1: 120	1	15	60	NO	--						
			CM: 168	142	84	313 kg	2: --	--	--	60	YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L2320	6640	Cabinet, Bio Safety, Class II/B1, F/S, Vert, 4ft	A	A	A	A	--	--	F	B	--	--	E					
<p>Class II, type B1, bio safety cabinet. This is a vertical, freestanding unit. The interior work surfaces shall be constructed of type 304 stainless steel and the exterior shall be of 16 gauge or heavier steel. The unit utilizes a 30% recirculated air and 70% direct exhaust through an in-house duct system, the face velocity is 100 fpm and includes an audible alarm when the window is at an unsafe operating level. It includes grounded duplex receptacles and two HEPA filters zero-probed. Used for low to moderate risk biological agents treated with minute quantities of toxic chemicals and trace amounts of radionuclides. A 4 foot cabinet is presented, other sizes are available. [No other source(s) identified with this description/specification.</p> <p>Labconco (www.labconco.com) does not make a Class II, Type B1 Cabinet. They recommend using either a Class II, Type B2 Cabinet or a Class II, Type A2 Cabinet.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	91	53	34	1,100 lb	1:	120	1	15	NO		--					
		CM:	231	135	86	500 kg	2:	--	--	--	DEPENDENT: YES		--					
L2325	6640	Cabinet, Bio Safety, Class II/B1, F/S, Vert, 6ft	A	A	A	A	--	--	B	B	--	--	E					
<p>Class II, type B1, bio-safety cabinet. This is a vertical, free standing unit. The interior work surfaces are constructed of type 304 stainless steel and the exterior is 16 gauge or heavier steel. The unit utilizes 30% recirculated air and 70% direct exhaust through an in-house duct system with a face velocity of 100 fpm and has an audible alarm when window is at an unsafe level. It includes a duplex receptacle for grounded plugs and two HEPA filters zero-probed. Used for low to moderate risk biological agents treated with minute quantities of toxic chemicals and trace amounts of radionuclides. A 6 foot model is presented, other sizes are available. [No other source(s) identified with this description/specification. Labconco (Cage Code 94841, www.labconco.com) does not make a Class II, Type B1 Cabinet. They recommend using either a Class II, Type B2 Cabinet or a Class II, Type A2 Cabinet.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	95	73	34	1,175 lb	1:	120	1	16	NO		--					
		CM:	241	185	86	534 kg	2:	--	--	--	DEPENDENT: YES		--					
L2330	6640	Cabinet, Bio Safety, Class III	A	A	A	A	--	--	F	--	--	--	E					
<p>Class III, bio safety cabinet. The unit includes an 85 CFM blower with a variable speed power stat, a manometer mounted on box front to indicate flow, 1/4 inch safety glass viewing panel, polarized and grounded electrical outlets with indicating switches, one pair of 24 inch long neoprene gloves, one inlet filter, one absolute filter with connecting hoses, and 40" of 2" diameter exhaust hose with clamps, one fluorescent light with fixture and switch, one ultraviolet light, two grooved glove ports, one variable height mobile bench, with 5" ball bearing, toe operated, locking casters, and a 1/25 HP motor. Used for cultivation of microorganisms, serological dissections, and aerosol exposures. [No other source(s) identified with this description/specification. The price for Model 2 is a beginning estimate only. All units are custom made based on user needs and specifications.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	70	58	34	-- lb	1:	120	1	20	NO		--					
		CM:	178	147	86	-- kg	2:	--	--	--	DEPENDENT: YES		--					
L2335	6640	Cabinet, Bio Safety, Class II/B2, F/S, 4ft	A	A	A	A	--	--	F	--	--	--	E					
<p>Class II, Type B2, bio safety cabinet. This is a freestanding vertical laminar flow unit. It includes two HEPA filters, one supply and one exhaust zero-probed. The intake velocity averages 105 fpm. It includes an audible alarm to notify the operator of an unsafe window position, an audio-visual alarm to monitor exhaust pressure, type 304 stainless steel construction with side walls slotted for high velocity air return, an exterior of 16 gauge or heavier steel, two grounded key petcocks and a duplex receptacle for grounded plugs. Used for low to moderate risk biological agents treated with toxic chemicals and radio-nucleotides. 4 foot model presented, other sizes are available.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	104	54	36	853 lb	1:	120	1	12	NO		--					
		CM:	264	137	91	388 kg	2:	--	--	--	DEPENDENT: YES		--					
L2336	6640	Cabinet, Bio Safety, Class II/B2, Bench Top, 4ft	A	A	A	A	--	--	B	--	--	--	E					
<p>Class II, Type B2, benchtop biological safety cabinet. The unit includes two HEPA filters, one supply and one exhaust, zero probed, high intake velocity that averages 105 fpm, an audible alarm to notify operator of unsafe window positions an audio-visual alarm to monitor exhaust pressure, interior of type 304 stainless steel with side walls slotted for high velocity air return, an exterior of 16 gauge or heavier steel, two ground key petcocks, a grounded duplex receptacle. Used for low to moderate risk biological agents treated with toxic chemicals and radionucleotides. This unit requires 100% exhaust to the atmosphere. 4 foot model presented, other sizes are available.</p>																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	72	54	36	736 lb	120	1	15	60	NO	--		
				CM:				2:			DEPENDENT:				
				183	137	91	335 kg	--	--	--	YES	--			
L2337	6640	Canopy, Hood, Fume, 6 foot	A	A	A	A	--	--	F	--	--	--	E		
<p>Canopy fumehood. The unit includes a switched fan unit with pilot light; corrosion resistant steel, aluminum, or chemical resistant and fire retardant seamless fiberglass construction; dimensions as indicated on design drawings; fire suppression systems and any other special requirements to be defined during the facility design. It also includes a 3/4 horsepower motor blower. The static pressure loss shall not exceed 0.91 at 1290 cfm and 1.65 at 1935 cfm. It is equipped with baffles to maximize slot velocities and control fumes. Used in laboratories for low to moderate risk biological agents. Other sizes may be available. Blower motor mounted separate from the canopy and may not be included in the size specification. [Model 2 includes part numbers 36L1300, 36L12600 and 54L48800.</p> <p>Model 3 has a chemical resistant and fire retardant seamless fiberglass hood instead of metal. This has been added to the description..]</p>															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	24	72	36	100 lb	120	1	12	60	NO	--		
				CM:				2:			DEPENDENT:				
				61	183	91	45 kg	--	--	--	YES	--			
L2338	6640	Cabinet, Bio Safety Class II/B2, 6 ft, Bench Top	C	C	C	C	--	--	B	--	--	--	E		
<p>Bio safety cabinet, Class II, type B2. The unit includes construction of type 304 stainless steel and is equipped with a storage area below the work area. It has visual and audible alarms that warn of unsafe operating conditions. Used to work with volatile and particulate chemicals, carcinogens and radioisotopes. 6 foot model presented, other sizes are available.</p>															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	72	78	36	904 lb	120	1	14	60	NO	--		
				CM:				2:			DEPENDENT:				
				183	198	91	411 kg	--	--	--	YES	--			
L2339	6640	Hood, Fume, Histopathology Staining	A	A	A	A	--	--	F	--	--	--	E		
<p>Histopathology staining fume hood to be used to contain manual and automatic staining stations. Double sliding doors permit access to entire height and half the width of the hood at one time. Integral fluorescent lighting provided for interior visibility. Unit provided with integral blower and hooks to building systems for exhaust to the atmosphere. Unit provides for front to back flow to protect technicians from volatile staining solution vapors. Base model is 30 inches wide but may be procured in widths up to 72 inches wide. Unit is designed to sit on existing bench tops. [The Baker unit (Model 1) comes in 4 to 6 foot sizes and built to user specifications at time of order. Price may vary from amount shown depending on user requirements. Model 3 provides an alternative to a hood requiring ducting to the outside. This model is ductless and does not require an external exhaust system.]</p>															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	32	59	29	114 lb	120	1	15	60	NO	--		
				CM:				2:			DEPENDENT:				
				81	150	74	52 kg	--	--	--	YES	--			
L2510	6640	Room, Controlled Environment, Small	A	A	A	A	--	--	F	--	--	--	--		
<p>Walk-in controlled environment room, approximately 7.8' H x 4.6' D x 6.6' W. It has a temperature operating range of ambient to 60 degrees centigrade. The unit is constructed of enameled steel exterior with aluminum interior. It includes a thermo-pane observation window in the door, a forced air circulation system with split capacitor blower, fluorescent lighting, dual thermostats and aluminum shelves. It provides a controlled environment in which to grow cultures and cells. [These manufacturers produce environmental rooms in many sizes and configurations. Some sizes can be considered standard boxes, however, the many options available to meet various applications makes these units custom designed. Prices shown are for budgetary purposes and will vary based on specific requirements. Prices are based on a room with approximately 236 CUFT. Model 1 price does not include installation. Price difference verified.]</p>															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	94	55	79	-- lb	120	1	15	60	NO	--		
				CM:				2:			DEPENDENT:				
				239	140	201	-- kg	208	3	8	YES	--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L2540	6640	Incubator, Co2, 2 Chamber	C	C	C	C	--	B	A	--	--	--	--	--	--	--	--	
Dual chamber Co2 incubator. The unit includes a temperature range of from 5 above ambient to 60 degrees centigrade, stainless steel construction, adjustable shelves, inner glass doors, 10 to 12 cubic foot capacity and a temperature safety controller. This is a fully automatic unit. It is used in laboratories to grow anaerobic bacterial cultures.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	80	27	29	648 lb	1:	120	1	9	YES		--					
		CM:	203	69	74	295 kg	2:	--	--	--	NO		--					
L2550	6640-00-428-8620	Incubator, Bacteriological, 34x37x25	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Bacteriological incubator. The unit comes with a thermostat and LED display, corrosion resistant interior with chrome plated shelves, fiberglass insulation in the shell, tempered glass inner door, a capacity of 10.5 cubic feet, a temperature range of 35-65 degrees centigrade and a forced air circulation system. Used in laboratories to grow cultures.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	39	42	27	325 lb	1:	120	1	7	YES		--					
		CM:	99	107	69	148 kg	2:	--	--	--	NO		--					
L2570	6640-00-428-9120	Incubator, Bacteriological, Single	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Small bacteriological incubator. It has a corrosion resistant chamber with adjustable shelves and a temperature range of approximately 30-70 degrees centigrade. Used in laboratories to grow cultures.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	39	23	25	315 lb	1:	120	1	6	NO		--					
		CM:	99	58	64	143 kg	2:	--	--	--	YES		--					
L2575	6530	Incubator, Platelet, Freestanding, w/Rotator	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Freestanding platelet incubator. Unit is equipped with a rotator. The unit can be a single or dual capacity unit and can hold platelet rotators and agitators for continual mixing at 22 degrees centigrade. It has forced air circulation to maintain a uniform temperature throughout the incubator, a temperature range of 15-40 degrees centigrade, an alarm system for temperature deviations or power failure and a rotation speed of 6 rpm to maintain the viability of platelet concentrations. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	59	40	28	505 lb	1:	120	1	12	NO		4,517					
		CM:	150	102	71	230 kg	2:	--	--	--	YES		--					
L2600	6630	Counter, Cell, Auto	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Automatic blood cell counter. The counter has a built-in monitoring system. It can perform a test in 13 seconds using a 100 microliter sample and give the results of 3 to 5 parameters of WBC, RBC, Hgb, Hct, and MCV. It has programs that include control data, calibration settings and tests and it has a temperature compensation circuit. Used for hematology analysis.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	20	19	20	75 lb	1:	120	1	7	NO		1,571					
		CM:	51	48	51	34 kg	2:	--	--	--	YES		--					
L2610	6640	Fibrometer, Auto	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Automatic fibrometer. Characteristics/components include four basic circuits, motor and timer, detection, temperature control and preheat circuit. It has six warming wells and controls. Used for prothrombin time determinations and diagnostic use in therapy control.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	5	6	8	7 lb	1:	120	1	2	NO		--					
		CM:	13	15	20	4 kg	2:	--	--	--	YES		--					
L2630	6625	Counter/Timer, Digital	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Digital counter/timer. The unit can perform frequency measurements in the range of 225 MHz and can perform time interval measurements between two events (start and stop events). The unit has not less than a 6 digit read out. Used for a variety of measurement functions such as frequency, period, time interval (Channel A to Channel B), frequency ratio (Channel A/Channel B), totaling, etc.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	4	13	16	10 lb	1:	120	1	1	NO		--					
		CM:	10	33	41	5 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
L2650	6640-00-418-8200	Counter, Bacteria	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Bacteria colony counter. This unit is manually adjusted. It is used in bacteriology, virology and mycology laboratories to count or measure bacteria colonies.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	10	12	13	12 lb	1:	120	1	2	60		NO		--				
		CM:	25	30	33	6 kg	2:	--	--	--	60		YES		--				
L2655	6640	Apparatus, Culture, Anaerobic	C	C	C	C	--	--	A	B	B	--	--	--	--	--	--	--	
Anaerobic culture apparatus. The unit is made of stainless steel with two adjustable shelves. The unit has multiple electrical outlets, fluorescent lights, a charcoal wafer and has a temperature range from ambient to 70 degrees centigrade. Used for processing anaerobic blood cultures and any other culture growth that requires anaerobic conditions.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	38	61	35	290 lb	1:	120	1	15	60		NO		--				
		CM:	97	155	89	132 kg	2:	--	--	--	60		YES		--				
L2660	6640	Microbiological Identification System	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Microbiological identification system. The systems basic principles of operation consists of: photometry, fluorescence, radiometry, infrared spectrophotometry, and video image analysis, together with a MPLS (multiple-parameter light scattering technique) and a continuous flow-through detection system. It consists of an auto-prep station, auto filter, incubator, detector/reader, waste reservoir, and computer sample throughput of over 200/day. Designed to detect presence of micro organisms in body fluids, test susceptibility of micro organisms to anti microbial agents, and/or determine the minimum inhibitory concentrations of antibiotics in order to identify pathogens. [Price difference verified.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	29	40	29	400 lb	1:	120	1	10	60		NO		3,300				
		CM:	74	102	74	182 kg	2:	--	--	--	60		NO		3,300				
L2665	6640	Microbiological Susceptibility/ID System	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Automated microbiological susceptibility and identification system. This instrument incubates inoculated samples, adds reagent and reads the panel automatically. Used for organism identification and susceptibilities, statistical probabilities and commentaries suggesting additional tests for identifying unusual organisms. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	36	39	30	488 lb	1:	120	1	10	60		YES		3,300				
		CM:	91	99	76	221 kg	2:	--	--	--	60		YES		3,300				
L2690	6630	Computer, Mean Cell Volume	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Mean cell volume computer. Characteristics/components include an internal regulation, a direct readout, reproducibility +/-1% for use with the counter, automatic calibration and quality control functions. System is used to perform complete hematology parameters, cell morphology and a histogram differential from cytochemistry on every sample.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	34	48	32	522 lb	1:	120	1	16	60		NO		--				
		CM:	86	122	81	237 kg	2:	--	--	--	60		YES		--				
L2691	6630	Hematocrit Accessory, Automatic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Automatic hematocrit accessory. This accessory calculates the volume of packed cells from total cell count and MCV and provides a reproducibility to plus or minus 1% for use with the counter. The hematocrit accessory is integrated into the total instrument package. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	20	26	21	122 lb	1:	120	1	8	60		NO		1,571				
		CM:	51	66	53	56 kg	2:	12	1	--	60		YES		1,571				

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R A F A H						1 2 3 4 5 6					
L3160	6640	Washer, Labware, Steam, approx. 80x39x31		A	A	A	A	--	F	G	--	A	--	--	
Single door steam operated cabinet mounted metalware and glassware washer. Used in hospitals to wash glassware and metal utensils. Optional electric heating may be available (add 40 Amps to power requirements). [No other source(s) identified with this description/specification.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA	EA	IN: 78	34	44	1,000 lb	1: 208	3	16	HZ SWITCH: NO		8,500				
		CM: 198	86	112	454 kg	2: --	--	--	DEPENDENT: YES						
L3190	6640-00-756-2595	Washer, Pipette, Automatic, 22-1/4x10-3/8dia		C	C	C	C	--	D	A	--	--	--		
Automatic pipette washer. This is a single wall, CRS, cylindrical unit with a pipette basket. It cleans pipettes in a continuous fill and flushing cycle in one minute. The unit requires water input from 1-1/2 to 12 liters per minute. It can accommodate pipettes up to 375mm long. Used in laboratories to clean pipettes.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA	EA	IN: 18	12	11	37 lb	1: 120	1	4	HZ SWITCH: NO		--				
		CM: 46	30	28	17 kg	2: --	--	--	DEPENDENT: YES						
L3365	6640	Washer, Labware, Electric, Under Counter		A	A	A	A	--	F	B	--	--	--		
Under counter labware washer. It has an electric steam generator to achieve a high temperature wash and steam cycle. It also has a high capacity pump and blower dryer. Used to wash laboratory glassware. [Model 3 requires a 230V electrical hookup.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA	EA	IN: 34	26	27	189 lb	1: 120	1	20	HZ SWITCH: NO		--				
		CM: 86	66	69	86 kg	2: 230	1	15	DEPENDENT: YES						
L3400	6640-00-433-6000	Microtome, Rotary, Tilt, Bench Mounted		C	C	C	C	--	--	--	--	--	--		
Bench mounted tilting rotary microtome. The unit's features include horizontal advancement, a feed indicator and selection dial that provide settings from 1 to 30 microns, a quick change holder system that allows the use of different holders, an angle adjustment from 0 to 15 degrees and a hand wheel that allows speed control without backflash. Used for histological techniques and slide preparation.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 0		BTUs / HR:				
EA	EA	IN: 20	12	21	88 lb	1: --	--	--	HZ SWITCH: NO		--				
		CM: 51	31	53	40 kg	2: --	--	--	DEPENDENT: NO						
L3430	6640-00-982-8223	Microtome, Rotary, Tilt, Refrigerated		C	C	C	C	--	--	B	--	--	--		
Refrigerated rotary microtome/cryostat. The unit's features include horizontal advancement, sectioning from 2-20 microns, combination unit consisting of an automatic defrost of chamber and microtome, a temperature range from -30 degrees centigrade to room temperature, a defrost cycle of 10 minutes every 24 hours. Used to prepare samples for slide studies.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA	EA	IN: 47	28	28	275 lb	1: 120	1	12	HZ SWITCH: NO		1,500				
		CM: 119	71	70	125 kg	2: --	--	--	DEPENDENT: YES						
L3570	6640	Incubator, Bacteriological, Dry Block		C	C	C	C	--	--	A	--	--	--		
Dry block bacteriological incubator. The unit characteristics/components include a temperature range from 30 to 120 degrees centigrade, an anodized aluminum heating block, standard calibration at 37 degrees centigrade and holds a minimum of 6 interchangeable heating blocks. Used for cross matching, Coombs test, antibodies testing, immunohematology incubation and other laboratory procedures. [Price difference verified.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA	EA	IN: 4	9	8	9 lb	1: 120	1	5	HZ SWITCH: NO		--				
		CM: 10	23	20	4 kg	2: --	--	--	DEPENDENT: YES						
L4080	6650-00-122-6991	Photometer, Flame		C	C	C	C	--	--	A	D	--	--		
Flame Photometer. This is a fully automatic computer controlled unit. It requires a 20 micro liter sample size and a 40 PSI compressed air supply. It can provide through put of up to 100 samples per hour. It also has stat capabilities. Used for NA/K/Li level determinations in serum and urine samples. [The Jenway product as listed from Daigger and Techne (Cage Codes 15747 and 2729) are not automated systems.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA	EA	IN: 26	17	26	37 lb	1: 120	1	7	HZ SWITCH: NO		--				
		CM: 66	43	66	17 kg	2: --	--	--	DEPENDENT: YES						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L4200	6640-00-765-0621	Bath, Water, Serology, Electric	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Serological water bath. It operates in the temperature range of 60 to 100 degrees centigrade. It has a corrosion-proof stainless steel water tank with a 3 gallon capacity. Models have drain spouts for easy emptying of media. Used to provide a controlled temperature environment for the preparation of samples for study.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	33	32	47	73 lb	1:	120	1	12	NO		--					
		CM:	84	81	119	34 kg	2:	--	--	--	YES		--					
L4205	6640	Bath, Water, Tissue Processing	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Tissue processing water bath. It has a sensitive thermostat providing regulation to +/-0.1 degree C., a temperature range from ambient to 72 degrees centigrade, black coating in chamber to provide visual contrast, fiberglass insulated sides and bottom and a dependable gravity convection.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	12	12	6 lb	1:	120	1	3	YES		--					
		CM:	25	30	30	3 kg	2:	--	--	--	NO		--					
L4210	6640	Bath, Water, Refrigerated, Circulating	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	--
<p>Refrigerated circulating water bath. The unit's characteristics include: maximum temperature of 140 degrees centigrade, low level bath fluid safety alarm, large digital temperature display, chamber with approximately 12 liter volume capacity, a maximum flow rate of 14-20 liters per minute, a duplex pump that provides pressure and suction permitting use in both open and closed loop system applications, motor protected against thermal overload and a temperature capability to -25 degrees centigrade. Used in blood banks.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	28	16	20	101 lb	1:	208	1	15	NO		1,800					
		CM:	71	41	51	46 kg	2:	--	--	--	YES		--					
L4215	6640	Incubator, Multipurpose, Dry Block	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>A compact, single dry block, multipurpose unit used for incubation and activation of cultures, enzyme reaction, blood urea nitrogen determination and a variety of laboratory procedures. The unit holds a minimum of 9 separate interchangeable aluminum heating blocks that accommodate various tube sizes.. It has a minimum temperature range of ambient to 95 degrees centigrade with an accuracy of + or - .5 degree centigrade. [This item has been recommended for use in blood bank and serology departments by the U.S. Air Force Laboratory Consultant. The aluminum dry blocks are sold separately depending on incubator application. The cost of each dry block is approximately \$75.00 to \$98.00.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	4	9	10	3 lb	1:	120	1	1	NO		--					
		CM:	10	23	25	2 kg	2:	--	--	--	YES		--					
L4300	6630-00-299-9834	View Box, RH Typing	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>RH typing view box. The unit is a heat and light source utilizing a fluorescent light and providing a temperature range of 37-39 degrees centigrade, an adjustable thermostat and a built in Hg thermometer. Used for blood typing and cross matching, tissue typing and enzyme antibody reading.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	4	13	4	5 lb	1:	120	1	2	NO		--					
		CM:	10	33	10	3 kg	2:	--	--	--	NO		--					
L4350	6650	Bilirubinometer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Bilirubinometer. It has a readout directly in MG/100 ml. The instrument measures color of bilirubin concentration against color of highly stable reference standard. The unit provides direct spectrophotometry technique, measures with a 30 micro liter sample size, a readout in two minutes, measurement range from 0 to 30 mg/dl and has stat capabilities. Used for determinations of total and direct bilirubin in newborns. [No other source(s) identified with this description/specification. Advanced Instruments Inc. (Cage Code # 24377), also distributes MN: BR2, manufactured by Fisher Scientific Co. Additional distributors also found, all carrying the same brand.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	7	13	11	9 lb	1:	120	1	5	NO		--					
		CM:	18	33	28	4 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES																																																		
				A	N	A	V	I	1 2 3 4 5 6																																													
L4360	6640	Warmer, Slide	C C C C --	--	A	--	--	--	--	--																																												
Slide warmer used to mount paraffin sections. Used in microbiology. Holds 48 slides.																																																						
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>5</td> <td>24</td> <td>14</td> <td>18 lb</td> <td>1: 115</td> <td>1</td> <td>5</td> <td>50/60</td> <td>YES</td> </tr> <tr> <td></td> <td></td> <td>13</td> <td>61</td> <td>36</td> <td>9 kg</td> <td>2: --</td> <td>--</td> <td>--</td> <td>DEPENDENT:</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>--</td> </tr> </tbody> </table>											UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	5	24	14	18 lb	1: 115	1	5	50/60	YES			13	61	36	9 kg	2: --	--	--	DEPENDENT:	NO											--
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																												
EA	CM:	5	24	14	18 lb	1: 115	1	5	50/60	YES																																												
		13	61	36	9 kg	2: --	--	--	DEPENDENT:	NO																																												
										--																																												
L5218	6670	Scale, Autopsy	C C C C --	--	--	--	--	--	--	--																																												
Autopsy scale. It has an 8" diameter dial or (battery operated) electronic display and a 400 pound capacity. Used in pathology departments to weigh body parts and bodies. [Health o Meter is consolidated under Sunbeam Health Division.]																																																						
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>96</td> <td>35</td> <td>43</td> <td>85 lb</td> <td>1: --</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>243</td> <td>89</td> <td>109</td> <td>39 kg</td> <td>2: --</td> <td>--</td> <td>--</td> <td>DEPENDENT:</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>--</td> </tr> </tbody> </table>											UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	96	35	43	85 lb	1: --	--	--	--	NO			243	89	109	39 kg	2: --	--	--	DEPENDENT:	NO											--
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																												
EA	CM:	96	35	43	85 lb	1: --	--	--	--	NO																																												
		243	89	109	39 kg	2: --	--	--	DEPENDENT:	NO																																												
										--																																												
L5220	4100	Sink, Cup, Raceway	A A A A --	I	--	--	--	--	--	--																																												
Raceway cup sink. Unit is made of stainless steel or tempered glass with a 1-1/2 inch outlet connection. Used as a laboratory cup sink in a casework raceway.																																																						
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>11</td> <td>5</td> <td>8</td> <td>2 lb</td> <td>1: --</td> <td>--</td> <td>--</td> <td>0</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>28</td> <td>13</td> <td>20</td> <td>1 kg</td> <td>2: --</td> <td>--</td> <td>--</td> <td>DEPENDENT:</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>--</td> </tr> </tbody> </table>											UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	11	5	8	2 lb	1: --	--	--	0	NO			28	13	20	1 kg	2: --	--	--	DEPENDENT:	NO											--
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																												
EA	CM:	11	5	8	2 lb	1: --	--	--	0	NO																																												
		28	13	20	1 kg	2: --	--	--	DEPENDENT:	NO																																												
										--																																												
L5610	6650	Pipettor, Micro, 3 Range	C C C C --	--	A	--	--	--	--	--																																												
Micro-pipetting system. It is a sampler unit for precision pipetting of 1, 2, or 3 reagent volumes. It can accommodate different volume ranges from 25 micro-liter to 25 milliliters with dilution ratios up to 1:100. [All distributors found carry the Microlab line of Pipettor Diluters/Dispensers by Hamilton. No other manufacturer found matching this description/specification.]																																																						
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>14</td> <td>7</td> <td>7</td> <td>11 lb</td> <td>1: 120</td> <td>1</td> <td>5</td> <td>50/60</td> <td>YES</td> </tr> <tr> <td></td> <td></td> <td>36</td> <td>18</td> <td>18</td> <td>5 kg</td> <td>2: --</td> <td>--</td> <td>--</td> <td>DEPENDENT:</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>--</td> </tr> </tbody> </table>											UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	14	7	7	11 lb	1: 120	1	5	50/60	YES			36	18	18	5 kg	2: --	--	--	DEPENDENT:	NO											--
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																												
EA	CM:	14	7	7	11 lb	1: 120	1	5	50/60	YES																																												
		36	18	18	5 kg	2: --	--	--	DEPENDENT:	NO																																												
										--																																												
L5630	6650	Pipettor, 20-100 Micro Liter	C C C C --	--	A	--	--	--	--	--																																												
Pipettor. Unit operates with a plus or minus 0.5% reproducibility and precision. Used for repetitive deliveries of pre-set reagent volumes from chemicals to sterile solutions.																																																						
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>14</td> <td>6</td> <td>6</td> <td>5 lb</td> <td>1: 120</td> <td>1</td> <td>2</td> <td>60</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>36</td> <td>15</td> <td>15</td> <td>3 kg</td> <td>2: --</td> <td>--</td> <td>--</td> <td>DEPENDENT:</td> <td>YES</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>--</td> </tr> </tbody> </table>											UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	14	6	6	5 lb	1: 120	1	2	60	NO			36	15	15	3 kg	2: --	--	--	DEPENDENT:	YES											--
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																												
EA	CM:	14	6	6	5 lb	1: 120	1	2	60	NO																																												
		36	15	15	3 kg	2: --	--	--	DEPENDENT:	YES																																												
										--																																												
L6000	6625	Detector, Mercury	C C C C --	--	A	--	--	--	--	--																																												
Mercury detector. The unit can be AC or battery operated up to 8 hours operating time on a charge. The unit's sensitivity is less than 0.2 Hg. It has an approximate analysis time of 15 seconds and a flow rate of 1.5 L/min. Used for identifying locations of spilled mercury. [Bacharach the manufacturer of gas analyzers marketed by lab-safety no longer makes mercury vapor meters. No other source(s) identified with this description/specification.]																																																						
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>9</td> <td>6</td> <td>13</td> <td>7 lb</td> <td>1: 120</td> <td>1</td> <td>1</td> <td>60</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>23</td> <td>15</td> <td>33</td> <td>4 kg</td> <td>2: --</td> <td>--</td> <td>--</td> <td>DEPENDENT:</td> <td>YES</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>--</td> </tr> </tbody> </table>											UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	9	6	13	7 lb	1: 120	1	1	60	NO			23	15	33	4 kg	2: --	--	--	DEPENDENT:	YES											--
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																												
EA	CM:	9	6	13	7 lb	1: 120	1	1	60	NO																																												
		23	15	33	4 kg	2: --	--	--	DEPENDENT:	YES																																												
										--																																												
L7050	6640	Spectrophotometer, Infrared, Two Beam	C C C C --	--	A	--	--	--	--	--																																												
Dual beam infrared spectrophotometer. Dual beam optical null with microprocessor controlled abscissa functions spectrophotometer. It has a LED display that indicates wave number positions, a flow chart recorder, auto-check gain adjustments, an f/5 filter grating monochromator, scan times of 3 and 12 minutes with an accuracy of +/-2%. Used for analysis in the organic chemistry laboratory.																																																						
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>IN:</th> <th>HEIGHT</th> <th>WIDTH</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>CM:</td> <td>13</td> <td>39</td> <td>26</td> <td>198 lb</td> <td>1: 120</td> <td>1</td> <td>5</td> <td>60</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td>33</td> <td>100</td> <td>66</td> <td>90 kg</td> <td>2: --</td> <td>--</td> <td>--</td> <td>DEPENDENT:</td> <td>NO</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>--</td> </tr> </tbody> </table>											UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:	EA	CM:	13	39	26	198 lb	1: 120	1	5	60	NO			33	100	66	90 kg	2: --	--	--	DEPENDENT:	NO											--
UNIT OF ISSUE:	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:																																												
EA	CM:	13	39	26	198 lb	1: 120	1	5	60	NO																																												
		33	100	66	90 kg	2: --	--	--	DEPENDENT:	NO																																												
										--																																												

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L7060	6640	Spectrometer, Atomic Absorption, Double Beam	C	C	C	C	--	--	F	D	B	H	E					
Multi-element atomic absorption spectrometer, double beam. A high energy optical system with computer controlled flame gases for enhanced automation with a dual option burner system for aqueous and organic solutions. It has a built-in CRT graphite furnace and an automatic calibration and wavelength selection. Used for atomization applications in laboratories.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	23	34	23	214 lb	1:	120	1	4	60		YES		--			
		CM:	58	86	58	98 kg	2:	--	--	--	DEPENDENT:		YES		--			
L7070	6640	Spectrophotometer, Atomic Absorption	C	C	C	C	--	--	F	D	C	H	--					
Atomic absorption spectrophotometer. This is a double beam unit with a graphite furnace for background absorption. It has an automatic lamp selection, corrosion resistant materials construction, high resolution graphics, wavelength ranges from 190 to 900nm, a flame atomizer with pneumatic nebulization, the ability to accommodate an impact bead or a flow spoiler and an automatic calibration capability. Used in laboratories to process samples for analysis. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	23	54	23	214 lb	1:	120	1	3	60		NO		--			
		CM:	58	137	58	98 kg	2:	--	--	--	DEPENDENT:		YES		--			
L7080	6640	Spectrophotometer, Atomic Absorption, Computerized	C	C	C	C	--	--	F	D	C	H	--					
Double beam atomic absorption spectrophotometer. It is fully automatic, using cold vapor Hg and hydride generation sampling techniques. It's software is designed for use with a PC. It has a stable optical system with high energy wavelengths and high performance dual option system with stainless steel nebulizer.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	26	43	26	108 lb	1:	120	1	3	60		NO		--			
		CM:	65	109	65	49 kg	2:	--	--	--	DEPENDENT:		YES		--			
L7085	6630	Spectrophotometer, Fluorescence	C	C	C	C	--	--	A	--	--	--	--					
Fluorescence spectrophotometer. It is a high energy double monochromator system with a wavelength range from approximately 200-800 nm, precision is 0.1nm, xenon high pressure lamp, a fluorescence display of 0-200%, a scan speed of 5nm/minute, automatic calibration, 50mmX50mm filter and interchangeable flow cells. Used for analytical chemistry, pathology, organic chemistry and environmental testing.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	11	31	27	110 lb	1:	120	1	4	60		NO		--			
		CM:	28	79	69	50 kg	2:	--	--	--	DEPENDENT:		YES		--			
L7090	6650	Spectrophotometer, UV/Vis, Basic	C	C	C	C	--	--	A	--	--	--	--					
UV/Vis basic spectrophotometer. It is a photoelectric unit with a range of 190-900 milli-microns minimal. It has a double scale 0 to 100% transmittance and 0 to 2 absorbance units, an instrument cover and plastic light shield, scans speeds from 60-2400 nm/min, 40 full range scans, multi-wavelength readings and an accuracy of +/-0.5nm.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	9	21	19	24 lb	1:	120	1	10	50/60		YES		--			
		CM:	23	53	48	11 kg	2:	--	--	--	DEPENDENT:		NO		--			
L7095	6630	Nephelometer, Fluorescence	C	C	C	C	--	--	A	--	--	--	--					
Fluorescence nephelometer. Unit includes a calibration standard and a sample requirement of 25ml. Used to measure haze in fluids such as fuel, beverages, chemicals, pharmaceuticals and other waste water applications. [Price variation verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	3	11	11	7 lb	1:	120	1	1	50/60		YES		--			
		CM:	8	28	28	3 kg	2:	--	--	--	DEPENDENT:		NO		--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L7100	4110	Room, Controlled Environment	A	A	A	A	--	B	G	--	--	--	--	A				
Walk-in controlled environmental room, approximately 9.5' x 4.5' x 8.5'. It has a temperature range of 5 to 60 degrees centigrade, textured aluminum interior and exterior, 4-inch thick polyurethane insulation, self-closing insulated door, false ceiling construction that allows maximum air and light distribution, air or water-cooled condensing unit circulates through a conditioning plenum for heating/cooling humidification and a blower system for quiet operation. Unit is customized to meet the facility requirements. [These manufacturers produce environmental rooms in many sizes and configurations. Some sizes can be considered standard boxes, however, the many options available to meet various applications makes these units custom designed. Prices shown are for budgetary purposes and will vary based on specific requirements, e.g. degree of relative humidity control, etc. Prices are based on a room with approximately 360 CUFT. Model 3 price includes installation.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	102	60	120	1,000 lb	1:	208	3	10	60		NO		--			
		CM:	259	152	305	454 kg	2:	230	1	10	DEPENDENT:		YES					
L7200	4500	Dispenser, Reagent, Phenolic	A	A	A	A	--	--	A	--	--	--	--	--				
Phenolic reagent dispenser. It dispenses from 5 to 50 cycles/min with a delivery range of 1-400ml and is constructed of corrosion resistant plastic. Used for dispensing and diluting solvents acids, alkalis, and radioactive fluids.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	7	10	13	12 lb	1:	120	1	3	60		NO		--			
		CM:	18	25	33	6 kg	2:	--	--	--	DEPENDENT:		YES					
L7300	6640-00-865-1729	Stirrer, Hot Plate, Magnetic	C	C	C	C	--	--	A	--	--	--	--	--				
Magnetic stirrer-hot plate. It has variable stirring speeds of near 1500 RPM, temperatures of up to about 400 degrees centigrade, back up safety thermostat, plate surface of about 49 square inches and Pyroceram glass ceramic top that is corrosion resistant. Used for reagent mixing and heating, preparing culture media, evaporation and distillation procedures.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	8	12	16	13 lb	1:	120	1	15	50/60		YES		--			
		CM:	20	30	41	6 kg	2:	--	--	--	DEPENDENT:		NO					
L7305	6600	Mixer, Vortex, Test Tube	C	C	C	C	--	--	A	--	--	--	--	--				
Vortex test tube mixer. This is a single well type with a stirring action that starts with a touch of the test tube. It is a variable speed unit from 100-3000 rpm. Used in a laboratory for mixing small samples in a test tube, colorimetric tubes or Erlenmeyer flasks.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	7	6	9	9 lb	1:	120	1	2	60		NO		--			
		CM:	18	15	23	4 kg	2:	--	--	--	DEPENDENT:		YES					
L7330	6630	Rotator, Mixer	C	C	C	C	--	--	A	--	--	--	--	--				
Rotator mixer. It operates between 1-20 RPM oscillation and has reversible cushioning that cradles specimen tubes. It can accommodate up to fifteen 12 X 75ml tubes or ten 17X100ml tubes and has a precision controlled platform with mixing adjusting zones of 1-48 degrees angle. Used for uniform specimen suspension mixing.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	12	14	6	3 lb	1:	120	1	3	60		NO		--			
		CM:	30	36	15	2 kg	2:	--	--	--	DEPENDENT:		YES					
L7500	6630	Viscometer	C	C	C	C	--	--	A	--	--	--	--	--				
Viscometer. It is fully automatic and constructed of 300 Series stainless steel. It has a digital display, computer capabilities and can calculate a choice of viscosity (centipedes) by shear stress or % scale. It also has multiple speeds and interchangeable spindles. Used for different viscosity applications such as textile fibers, chemicals, gums, gels and many more items.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	26	13	13	73 lb	1:	120	1	7	60		NO		--			
		CM:	66	33	33	34 kg	2:	--	--	--	DEPENDENT:		YES					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L8000	6640	Incubator, Anaerobic, Vacuum	C	C	C	C	--	--	A	B	E	--	--					
<p>Anaerobic incubator with vacuum. Unit has fluorescent lights, two adjustable shelves, reusable wafers and a 4 cubic foot capacity. Used for culture growth of anaerobic bacteria. Includes vacuum pump. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	30	61	31	525 lb	1:	120	1	15	NO		--					
		CM:	76	155	79	239 kg	2:	--	--	--	NO		--					
L8005	6640	Incubator, Blood Bank, Tabletop	C	C	C	C	--	--	A	--	--	--	--					
<p>The incubator is used to perform crossmatches, indirect Coombs test, Rh titers, Du tests. It maintains through the use of dry heat blocks a constant temperature of 37degrees centigrade with an accuracy within + or - .5 degrees centigrade. It accommodates up to 40 tubes with diameters of 12mm. It is designed to be placed on a table top and is approximately 5" x 9" x 3". [The U.S. Air Force Laboratory Consultant has recommended this item for use in blood bank and serology departments. Model 2, from Becton Dickinson, although higher in cost, provides a solid aluminum block frame with a removable thermometer and an external temperature adjustment. Model 3 has a modular block and adjustable temperature.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	4	10	11	9 lb	1:	120	1	2	NO		--					
		CM:	10	25	28	4 kg	2:	--	--	--	YES		--					
L8130	6640	Incubator, Bacteriological, 2 Compartment	C	C	C	C	--	--	A	--	E	--	--					
<p>Two compartment bacteriological incubator. The unit requires carbon dioxide and has a 10 cubic foot capacity. It is a radiant heat system made of stainless steel with an automatic carbon dioxide controller and an optional interior electrical outlet. Used for tissue culturing and for work with CO2-obligate organisms at atmospheric pressure.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	74	27	29	456 lb	1:	120	1	10	NO		3,753					
		CM:	188	69	74	207 kg	2:	--	--	--	YES		3,753					
L8150	6640	Incubator, Paraffin, +/- 10 Cubic Foot	C	C	C	C	--	--	A	--	--	--	--					
<p>Paraffin incubator. The chambers can be used in conjunction with drying and staining of slides. It has fiberglass insulation, a memory ring, temperature calibrating dial with a temperature range of (+/-) 5 to 65 degrees centigrade, an inner glass door, easy loading shelves and has approximately 10 cubic foot capacity. Use for paraffin embedding at 30 -65 degrees centigrade. [Price difference verified.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	42	45	26	400 lb	1:	120	1	12	NO		2,218					
		CM:	107	114	66	182 kg	2:	--	--	--	YES		2,218					
L8275	6640	Oven, Drying, Small, w/Timer	C	C	C	C	--	--	A	--	--	--	--					
<p>Small laboratory drying oven. It has a temperature range of ambient to 240 degrees centigrade, a stainless steel interior, a platinum temperature probe, a 99 hour 59 minute timer and approximate 0.35 cubic foot capacity. For tightly controlled heating processes in the laboratory. Temperature is stable to plus or minus 1.5% at 240 degrees.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	19	16	18	72 lb	1:	120	1	7	NO		--					
		CM:	48	41	46	33 kg	2:	--	--	--	YES		--					
L8280	6640	Oven, Drying, Medium, 2 Cubic Foot	C	C	C	C	--	--	A	--	--	--	--					
<p>Medium laboratory drying oven. It has a temperature range of ambient to 210 degrees centigrade, a stainless steel interior, temperature control, timer and a 1.7 to 2.2 cubic foot capacity minimum. For drying and heating applications in the laboratory.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	31	25	25	200 lb	1:	120	1	10	NO		--					
		CM:	79	64	64	91 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L8285	6640	Oven, Drying, Medium, 3 Cubic Foot	C	C	C	C	--	--	D	--	--	--	--	--	--	--	--	--
Medium laboratory drying oven. It has a temperature range of ambient to 210 degrees centigrade, a stainless steel interior, a hydraulic or electronic temperature control, timer and a 2.7 to 3.2 cubic foot capacity. For drying and heating applications in the laboratory. [Price difference verified. Model 3 has a volume of 4.0 cubic feet.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	60	27	27	2,010 lb	1:	220	1	12	NO		--					
EA		CM:	152	69	69	913 kg	2:	120	1	13	YES		--					
L8290	6640-00-435-7220	Oven, Drying, Large, 2 Door	C	C	C	C	--	--	G	--	--	--	--	--	--	--	--	--
Double door laboratory drying oven. Also called a dry air sterilizer. It has a temperature range of 15-325 degrees centigrade, a stainless steel interior, a platinum temperature probe, a horizontal air flow, 12 hour timer and a 34+ cubic foot capacity.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	85	59	65	1,100 lb	1:	208	3	30	NO		1,084					
EA		CM:	216	150	165	500 kg	2:	--	--	--	YES		1,084					
L8300	6640	Printer, Cassette Label, Laboratory	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Label maker for laboratory cassettes. The printer uses a heat-foil transfer process or indelible ink ribbons to permanently identify laboratory slide cassette boxes. The labels and printing resist being affected by processing reagents. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	19	14	21 lb	1:	110	1	4	NO		--					
EA		CM:	91	48	36	10 kg	2:	--	--	--	NO		--					
L8305	6640	Printer, Slide, Laboratory	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Label maker for laboratory slides. The printer uses a heat-foil transfer process or indelible ink ribbons to permanently identify individual laboratory specimen slides. The labeling is not affected by immersion in normal laboratory processing and staining solutions. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	22	13	14	35 lb	1:	115	1	5	NO		--					
EA		CM:	56	33	36	16 kg	2:	--	--	--	NO		--					
L8500	6640-00-299-8693	Shaker, Reciprocating	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Reciprocating type shaker. Interchangeable holders available for different laboratory shaking needs. The unit operates in a range of 100 to 200 RPM.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	24	18	37 lb	1:	120	1	3	NO		--					
EA		CM:	25	61	46	17 kg	2:	--	--	--	YES		--					
L8510	6640	Shaker, Platform, Frozen Blood Processing	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Platform shaking machine for use in the laboratory. Unit's platform is approximately 16 inches by 16 inches. Unit provides variable agitation rates for assorted tasks and may be used in the frozen blood processing section of the lab.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	8	16	24	31 lb	1:	120	1	1	NO		--					
EA		CM:	20	41	61	14 kg	2:	--	--	--	YES		--					
L8520	6640-00-982-4243	Shaker, Rotating, 12 Standard Tubes	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Rotor/shaker. The unit has a speed range approximately 6 to 60 RPM, an adjustable place head, and the capability to hold all tubes 10 to 19 mm in diameter. Used for hematology procedures, micro-diffusion techniques, precipitate washing, blood gas saturation and more.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	27	51	25	26 lb	1:	120	1	2	NO		--					
EA		CM:	69	130	64	12 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L8540	6640-00-438-9600	Shaker, Rotating, 15 Slides	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Platform rotator/shaker. It accepts at least 15 slides and has an operational speed range of 100-210 RPM. The timer can be set to operate up to 25 minutes. It has a rubber covered platform with rubber suction feet. Used for VDRL's, Kline, Mazzini, serological flocculation, and agglutination tests. [sr237]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	8	13	14	23 lb	1:	120	1	3	NO		--					
		CM:	20	33	36	11 kg	2:	--	--	--	YES		--					
L8570	7100	Cabinet, Microscope Slide	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Microscope slide storage cabinet. This is a stackable unit and is made of steel with metal partitions that divide drawers vertically. It has pull-bar drawers with optional feature ball suspension design to prevent accident pull-out. Base is mounted on rubber feet to protect bench surfaces. Unit accommodates up to 5,000 slides.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	7	21	19	17 lb	1:	--	--	--	NO		--					
		CM:	18	53	48	8 kg	2:	--	--	--	NO		--					
L8575	7110	Cabinet, Paraffin Block	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Paraffin block storage cabinet. This cabinet accommodates number 1215 paraffin blocks. Used for archiving paraffin embedded pathology specimens.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	13	13	12	10 lb	1:	--	--	--	NO		--					
		CM:	33	33	30	5 kg	2:	--	--	--	NO		--					
L8580	6640	Stainer, Slide, Automatic, Hematology	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Automatic slide stainer. This is a microprocessor controlled stainer designed for minimum of 20 slides at one time. It includes a staining station, rinsing station and drying station. For use in microbiology, histology, and hematology laboratories.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	22	32	21	62 lb	1:	120	1	6	NO		--					
		CM:	56	81	53	29 kg	2:	--	--	--	YES		--					
L8585	6640	Stainer, Slide, Batch, Histological	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Batch slide stainer. This is a microprocessor controlled stainer designed for a minimum of 20 slides at one time. It includes a staining station, rinsing station and drying station. For use in microbiology, histology, and hematology laboratories.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	35	43	30	198 lb	1:	120	1	5	NO		--					
		CM:	89	109	76	90 kg	2:	--	--	--	YES		--					
L8590	6640	Stainer, Immunostaining System	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
Automated immunostaining system for the staining of formalin-fixed, paraffin-embedded tissues, frozen sections, cytopspins, cell smears and fine needle aspirates, using a variety of reagents. [Price difference verified. A third source could not be found for this item. Sakura Finetek, USA is currently working on an automated immunostaining system to compliment their Tissue-Tek DRS 2000 used for Histology (JSN L8585).]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	24	40	27	140 lb	1:	120	1	3	YES		--					
		CM:	61	102	69	64 kg	2:	--	--	--	NO		--					
L8600	6640	Slide Cover, Automated	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Automatic slide cover slipper. Takes standard microscope slides and places a resin-coated film over the slide. This device uses reagent grade Xylene as the fixing agent. Fume exhaust cover available. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	23	29	16	110 lb	1:	110	1	3	NO		--					
		CM:	58	74	41	50 kg	2:	--	--	--	NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES										
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5
L9000	6630	Embedder, Tissue	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
Tissue embedding center. This is a table top unit with a paraffin reservoir and cold plate, grouped together. The unit consists of a paraffin bath and a reservoir draining ledge, a heated work surface, large cold plate, foot pedal or touch plate for dispensing paraffin, a forceps warmer, a heated cassette holder, a temperature range on the paraffin bath of 45-65 degrees centigrade with a paraffin capacity of at least 2 liters, a plate that cools to -5 degrees centigrade or lower, a digital LED temperature display and can accommodate at least 50 cassettes. [Possible additional source is Surgipath CAGE# 0U703]																	
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES
			CM:	15	36	26	105 lb	1:	120	1	15						
				38	91	66	48 kg	2:	--	--	--						
L9010	6630	Homogenizer, Tissue	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
Tissue homogenizer; also called a sonicator. It has a feedback system with a titanium probe. Used in cytology to create a tissue cell suspension, degradation of nucleic acid chains, etc. [Price difference verified.]																	
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES
			CM:	16	8	19	18 lb	1:	120	1	5						
				41	20	48	9 kg	2:	--	--	--						
L9015	6640	Sharpener, Blade, Microtome	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
Microtome blade sharpener. Sharpens knives while the knife is locked in place and held at proper angle to the honing plate. There is an electrical timer to set the desired time.																	
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES
			CM:	18	23	21	90 lb	1:	120	1	8						
				46	58	53	41 kg	2:	--	--	--						
L9020	6640-00-869-6074	Tissue Processor, Automatic, 2 Level	C	C	C	C	--	--	A	B	--	--	--	--	--	--	--
Automatic tissue processor. This is a rotating basket immersion type unit that uses a minimum of 10 solvents and two paraffin processing stations. It is controlled by a electrical or electronic timer. The paraffin bath temperature ranges from 50-65 degrees centigrade and is agitated. The fumes are removed by an integral fume collecting system. The process time/step is adjustable between 15 minutes to 24 hours. The drain time/step is 0 to 1 minute. Used to fix, dehydrate, clear and infiltrate tissue specimens to preserve the integrity of their cellular components for light microscopy.																	
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES
			CM:	31	28	28	200 lb	1:	120	1	8						
				78	71	71	91 kg	2:	--	--	--						
L9022	6640	Tissue Processor, Electron Microscopy	C	C	C	C	--	--	D	--	--	--	--	--	--	--	--
Automated Electron Microscopy tissue processor for use in preparing tissue samples for viewing in either electron or high resolution light microscopes. Unit provides automated processing of up to 20 specimen vials simultaneously. Processing programs may be timed in increments from 1 minute to 99 hours and 59 minutes. Unit includes battery backup to raise samples from reagents and maintain program sequence in the event of power failure. Differs from a standard laboratory tissue processor only in terms of the volume and numbers of samples that may be processed.																	
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	YES	BTUs / HR:	DEPENDENT:	NO
			CM:	23	23	21	121 lb	1:	120	1	10						
				58	58	54	55 kg	2:	220	1	5						
L9025	6640	Freeze-Dryer, Tissue	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
Freeze dryer. The maximum low temperature of the unit is -54 degrees centigrade. The unit has a built in electronic vacuum gauge and is built of epoxy-coated steel for chemical resistance, includes vacuum pump. Used for laboratory specimen preparations. Capable of collecting 12 liters of ice before defrosting, remove up to 8 liters of water in 24 hours. Various options are available such as stopping tray, manifolds and glassware. [No other source(s) identified with this description/specification. Additional options and accessories for Models 1 and 2 are available for selection at time of ordering.]																	
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES
			CM:	37	35	28	430 lb	1:	208	1	20						
				94	89	71	196 kg	2:	--	--	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L9030	6640	Pump, Vacuum, Laboratory Oven	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
Vacuum pump for laboratory use with vacuum drying ovens.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	14	12	20	66 lb	1:	120	1	8	NO		--					
		CM:	36	30	51	30 kg	2:	--	--	--	NO		--					
L9700	6530	Lift, Manual, Mortuary, 300 Lb. Capacity (Minimum)	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Manual cadaver lift. This is a manually operated 300 pound (minimal) capacity lift. It has launderable canvas straps or tray for holding and lifting cadavers. It uses a heavy duty manual winch for raising and lowering the cadaver and has heavy duty swivel casters with locks to aid in positioning the unit.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	138	58	58	303 lb	1:	--	--	--	NO		--					
		CM:	351	147	147	138 kg	2:	--	--	--	NO		--					
L9710	6530-00-708-8510	Table, Autopsy/Dissecting, Tank, CRS	A	A	A	A	--	D	A	B	--	--	--	--	--	--	--	--
Tank type autopsy/dissecting table with submersion tank. The unit is made of corrosion resistant stainless steel and has a 60 gallon capacity reservoir tank.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	34	87	485 lb	1:	--	--	--	NO		--					
		CM:	91	86	221	221 kg	2:	--	--	--	NO		--					
L9711	6530	Table, Autopsy, Stationary-Fixed-Height	A	A	A	A	--	D	A	--	--	--	--	--	--	--	--	--
Autopsy table shall be constructed of stainless steel. It shall be polished to a smooth finish without crevices, lapped edges, rivets, or bolts. Table comes with integrated sink, waste disposer, grid plates for flat work area and perimeter downdraft.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	31	104	760 lb	1:	115	1	15	NO		--					
		CM:	91	79	264	345 kg	2:	--	--	--	YES		--					
L9712	6530	Table, Autopsy, Stationary-Elevating	A	A	A	A	--	D	A	--	--	--	--	--	--	--	--	--
Autopsy table shall be constructed of stainless steel and adjust in height by means of electro-hydraulics. The table shall be polished to a smooth finish without crevices, lapped edges, rivets or bolts. Table comes with integrated sink, waste disposer, grid plates for a flat work area and perimeter downdraft.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	40	31	104	675 lb	1:	115	1	15	NO		--					
		CM:	102	79	264	307 kg	2:	--	--	--	YES		--					
L9715	6530	Table, Autopsy, Mbl, w/Stationary Service Center	A	A	A	A	--	D	A	--	--	--	--	--	--	--	--	--
Mobile autopsy table. The table is used in conjunction with a stationary service island equipped with operator work facilities. The stationary service island shall include a cabinet unit that contains all plumbing and built in operating services; such as an irrigation hose connection controlled by a thermostatic water mixing valve, duplex electrical outlet, a sink equipped with a swing faucet spout and wrist-blades, a specimen basket to hang in the sink and a removable swing drain to receive the mobile table drainage.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	76	114	81	900 lb	1:	120	1	15	NO		--					
		CM:	193	290	205	409 kg	2:	--	--	--	YES		--					
L9720	6640	Station, Pathology, Gross	A	A	A	A	--	D	F	--	--	--	--	--	--	--	--	--
Gross pathology station. The unit contains four, two-speed electronic fans to reduce the danger of formaldehyde toxicity, an exhaust system with filters that last 2 to 8 months to convert the formaldehyde to CO2 and water, built in fluorescent lamps for shadow-free illumination, a "voice capturing option" to allow the pathologist to dictate without having to fumble with a hand or foot control and a built-in faucet with catch pan in the rear. Used for gross preparation of pathology specimens.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	51	48	30	250 lb	1:	120	1	2	NO		--					
		CM:	130	122	76	113 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
L9740	7110	Pump, Embalming	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Embalming pump for use in the mortuary. Unit provides delivery of embalming fluids at pressures up to 100 pounds per square inch. Unit has 3-1/4 gallon capacity with stainless steel reservoir. Pump is a direct drive with pulsation capability and automatic shutoff.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	25	14	15	53 lb	1:	120	1	4	NO		--					
		CM:	64	36	38	24 kg	2:	--	--	--	YES		--					
L9835	6625	Counter, Radioimmunoassay, Multi Det	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Multi-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (Serum, Urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer. [Models 2 and 3 use an external computer. Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	21	26	31	280 lb	1:	120	1	4	NO		--					
		CM:	53	66	79	128 kg	2:	--	--	--	NO		--					
L9836	6625	Counter, Radioimmunoassay, Single Det	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Multi-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (Serum, Urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	28	27	32	140 lb	1:	120	1	6	NO		--					
		CM:	71	69	81	64 kg	2:	--	--	--	NO		--					
L9840	6625	Counter, Gamma, RIA, Manual	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Gamma counter. Unit can be either a single well or a multi-well system that requires manual sample changing. It includes a NAI crystal detector. Uses RIA techniques to measure trace quantities of gamma radiation in substances such as hormones, drugs, enzymes, viruses, antibodies, tumor markers and receptors that are found in serum, urine and other body fluids. [Prices will vary depending on configuration chosen. The price difference here ranges from a single well to multiple well (20) capacity.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	21	27	20	45 lb	1:	120	1	3	NO		--					
		CM:	53	69	51	21 kg	2:	--	--	--	YES		--					
M0005	6515	Audiometer, Screening, Group	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Audiometer with up to 10 person capacity. Unit requires a computer. Testing can be done automatically, semi-automatically or manually. Unit can be used in mobile applications. Used for screening audiologic examinations. [No other source(s) identified with this description/specification. Database pricing is for an 8 person testing station including computer, printer and software. Recommend description be changed to read 8 person capacity vs. 10 person. A 10 person unit could not be identified. Tremetrics no longer offers a 10 person unit. Some DOD agencies may supply their own software and computer. In that case deduct \$4250.00 from the price.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	9	7	13	7 lb	1:	120	1	10	NO		--					
		CM:	23	18	33	4 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0010	6515	Recorder, Tape, w/Delayed Audio Feedback	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Delayed audio feedback tape recorder. Unit consists of a recorder and playback mechanism which delays speech playback so the patient can directly associate what was said with how it sounds. The unit includes a delay mode/time selector, amplifier and microphone. Electrical specifications are for an optional battery recharger. Some manufacturers equipment requires an ancillary computer for operation; refer to the specific maker's literature. See JSN M1800 for computer equipment. Used for speech modification training and therapy. [No other source(s) identified with this description/specification]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	12	30	14	15 lb 7 kg	1: 120 2: --	1 --	1 --	60 NO YES	NO YES	YES	--					
M0015	6515	Tympanograph, w/X-Y Recorder	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Tympanograph with X-Y recorder. Provides tympanic and acoustic reflex tests. Unit features self-adjusting circuits, a motorized air system and a stimulus section. Used to diagnose and determine middle ear problems and Eustachian tube dysfunction.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	11	28	16	17 lb 8 kg	1: 120 2: --	1 --	1 --	60 NO YES	NO YES	YES	--					
M0020	6515	Hearing Aid Analyzer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Hearing aid analyzer. It includes a complete acoustic test system, comprised of a control unit, color monitor, and hearing aid test box. For use in automatically testing, calculating and printing all electrical and acoustical performance data of any hearing aid in accordance with ANSI S3.22. [Model 2 price, Cage Code 79393 (Frye Electronics), includes the Quik Probe.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	15	38	24	36 lb 17 kg	1: 120 2: --	1 --	1 --	60 YES YES	YES YES	YES	--					
M0025	6515	Audiometer, Diagnostic, Middle Ear, Impedance	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Diagnostic impedance audiometer. Unit includes a clinical ear analyzer and can link to a complete data base computer system that stores patient results. Used for diagnostic audiological testing for middle ear impedance / compliance.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	9	23	19	15 lb 7 kg	1: 110 2: --	1 --	1 --	60 NO YES	NO YES	YES	--					
M0030	6515	Audiometer, Diagnostic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		One person audiometer. Unit includes talk over communication between operator and patient, automatic calibration, frequency and hearing level controls. Unit may require an external printer. Used for clinical audiological testing. [Model 2 is 50/60 Hz while others are 60 Hz. Price difference verified. Model 3 is a portable unit.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	13	33	21	20 lb 9 kg	1: 120 2: --	1 --	1 --	60 YES YES	YES YES	YES	--					
M0031	6515	Screening Device, Newborn Hearing	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Newborn hearing screening device that is fully automated to perform auditory brainstem response (ABR) and otoacoustic emissions (OAE) testing. Used to screen and identify hearing loss in newborns. [The computer system requirements for the screening devices will require compatibility review with the PC that is intended to be used with the device.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	9	23	12	15 lb 7 kg	1: 120 2: --	1 --	2 --	60 YES YES	YES YES	YES	--					
M0035	6515	Analyzer, Auditory, Evoked Potential	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Evoked potential auditory analyzer. The unit features a large color monitor, a minimum of 4 channel analysis, a computer, built-in electrode impedance testing, a physiological signal amplifier, a digital auditory stimulator and a register recorder. The analyzer is used for analyzing the response of the central nervous system to a variety of external stimuli.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	53	135	27	220 lb 100 kg	1: 120 2: --	1 --	9 --	60 YES YES	YES YES	YES	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0036	6515	Inner Ear (Cochlear) Analyzer, Screen	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Screening analyzer for inner ear related hearing loss. System consists of insert probes, a digital computer interface, an analog interface and data acquisition software. Capable of transient and distortion measurements. This system requires a desktop or notebook computer and printer. [Biocoustics Instruments, Inc. (Cage Code # 7D476), and Grason Stadler, Inc. (Cage Code # 1R779), both include the computer and printer in their price. Madsen Electronics, Inc.(Cage Code # 38767) does not.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	21	14	18	24 lb	1:	115	1	2	NO		--					
		CM:	53	37	47	11 kg	2:	--	--	--	YES		--					
M0040	6515	Booth, Audio, Single Wall, 1 Person	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	E
Single wall audiological booth. Prefabricated. Unit is constructed with 4 inch total absorptive panels with vibration isolators. Inside dimensions are approximately 78 inches high, 40 inches wide, and 36 inches long. Booth includes a double-glazed window with moisture control desiccant between window sheets, and a magnetic seal door. Used for audiometric testing. [Dimensions shown are exterior.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	92	54	44	1,650 lb	1:	120	1	15	NO		--					
		CM:	234	137	112	750 kg	2:	--	--	--	YES		--					
M0041	6515	Booth, Audio, Double Wall, Suite	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Double wall audiometric testing suite with double walled examination and control rooms. Unit includes recessed incandescent lights, carpet, keyed locks on both outer doors, a twelve outlet surface mounted plug mold strip in both rooms. A 24"x30" viewing window and self contained ventilation system permit extended examinations. Unit also includes jack panel between the exam and control rooms. Height may require raising room ceiling.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	97	252	136	22,800 lb	1:	120	1	20	NO		--					
		CM:	246	640	345	10,352 kg	2:	--	--	--	NO		--					
M0045	6515	Booth, Audio, Double Wall, 6 Person	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	E
Double wall audiological booth. Minimum of 16 gauge steel walls with corrosion resisting steel floor. Unit may include divider curtains, stools, fluorescent lighting. All rooms include flush magnetic seal doors up to 36 inches wide; and double glazed acoustical window. Double wall booth is designed to be used for audiological examination areas having high background noise levels and where maximum noise reduction is required. Height may require raising room ceiling. [All models exceed 8' ceiling height.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	97	112	114	8,800 lb	1:	120	1	15	NO		--					
		CM:	246	284	290	3,996 kg	2:	--	--	--	YES		--					
M0050	6515-00-065-9600	Booth, Audio, Dbl Wall, Definitive Test, 1 Person	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Double wall audiometric examination booth. This unit maybe prefabricated with interior dimensions of approximately 78 inches high, 48 inches wide, and 40 inches long. The composite sheet metal and sound absorbing assembly must have a minimum overall noise-reduction coefficient of 0.95. The door can open to either the right or left. Doctors, nurses, and audiologists use this unit for definitive audiological testing in clinics and hospitals. Unit installation may require raising room ceiling. [All models exceed 8' ceiling height.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	97	89	101	4,200 lb	1:	120	1	15	NO		--					
		CM:	247	226	257	1,907 kg	2:	--	--	--	YES		--					
M0315	6740	Processor, Color Slide Film, High Capacity	C	C	C	C	--	D	G	C	B	--	E					
Color slide film processor (E-6 development process). Modular film processor with automatic chemical replenishment system. Minimum output of 550 slides/hr (23 rolls of 24 exposure film). For mass production of color slides from 35mm slide film. Includes parts kit, water temperature and water pressure regulator. Some manufacturer's equipment may require raising the room ceiling.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	97	39	120	3,000 lb	1:	220	1	49	NO		28,000					
		CM:	246	99	305	1,362 kg	2:	--	--	--	YES		28,000					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0317	6740	Processor, Color Film, High Capacity	C	C	C	C	--	D	C	C	B	--	E					
Color negative film processor (C-41 development process). Modular film processor with automatic chemical replenishment system. Minimum output of 550 negatives/hr (23 rolls of 24 exposure film). For mass production of color print negatives from 35mm film. Includes parts kit, water temperature and water pressure regulator. Some manufacturer's equipment may require raising the room ceiling.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	97	39	120	2,500 lb	1:	220	1	50	NO		28,000					
		CM:	246	99	305	1,135 kg	2:	--	--	--	YES							
M0318	6740	Processor, Black/White Slide Film, High Capacity	C	C	C	C	--	D	C	C	B	--	E					
Slide film processor. Modular unit with automatic chemical replenishment system. Output of 550 slides/hr (23 rolls of 24 exposure film). For mass production of black and white slides from 35mm slide film. Some manufacturer's equipment may require raising the room ceiling.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	97	39	93	2,000 lb	1:	220	1	40	NO		24,000					
		CM:	246	99	236	908 kg	2:	--	--	--	YES							
M0320	6740	Processor, Photo Film/Prints, Automated	C	C	C	C	--	D	B	--	--	--	--					
Automated film/print processor for low volume applications in laboratories, electron microscopy, medical photography, illustration sections and small photo labs. Unit mounts on a countertop. Depending on the specific model, the processor will develop film and/or exposed print paper in black and white or color. Maximum print size is 20" wide. Unit may require a water filtration system for installation.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	35	42	41	250 lb	1:	120	1	17	NO		--					
		CM:	89	107	104	114 kg	2:	--	--	--	YES							
M0330	6740	Dryer, Film/Print	C	C	C	C	--	--	A	--	--	--	--					
Cabinet type film/print dryer with illuminated interior. Capacity is 80, 35mm rolls. Optional racks to hold prints are available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	85	25	28	225 lb	1:	120	1	13	NO		5,300					
		CM:	216	64	71	102 kg	2:	--	--	--	YES							
M0335	6740	Dryer, Film/Print, High Capacity	C	C	C	C	--	--	A	--	--	--	--					
Dryer for large volume of roll film or prints. Extra large cabinet with large clear plastic inspection windows. Capacity is 120, 35-mm rolls of film. Optional removable print racks are available. [No other source (s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	77	36	25	400 lb	1:	120	1	20	NO		5,300					
		CM:	196	91	64	182 kg	2:	--	--	--	YES							
M0355	6740	Washer, Print, Automatic, Drum or Tilt/Rock	A	A	A	A	--	D	A	--	--	--	--					
Automatic print washer. Corrosion resistant stainless steel unit with circular rotation or tilt-rocking action. It includes continuous controlled fresh water flow, stand, temperature control and covers (as necessary). Used in the darkroom for print washing. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	38	36	28	200 lb	1:	120	1	4	NO		--					
		CM:	97	91	71	91 kg	2:	--	--	--	YES							
M0375	6740	Enlarger/Printer, Photographic, 3 Lens	C	C	C	C	--	--	A	--	--	--	--					
Unit consists of an oversized baseboard and tower/chassis with elevation adjustment, light source, negative holder, triple lens turret and controls. For enlarging and printing 35mm, 4" X 5" and other size negatives. Database prices do not include motorized focusing options, lens costs or other available accessories.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	64	29	22	165 lb	1:	120	1	7	NO		--					
		CM:	163	74	56	75 kg	2:	--	--	--	YES							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0385	6700	Projector, Multimedia/Data	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 600 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 800 X 600 pixels (SVGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	4	12	11	8 lb	1:	115	1	4	60	YES						
		CM:	10	30	28	4 kg	2:	--	--	--	DEPENDENT:	NO						
M0400	6730	Screen, Projection, 144x144, Remote Control	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	10	158	10	180 lb	1:	120	1	2	60	NO						
		CM:	25	401	25	82 kg	2:	--	--	--	DEPENDENT:	YES						
M0401	6730	Screen, Projection, 50 X 50	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Pull down, roll-up projection screen. Wall or ceiling mounted. Size of this screen permits use in small classrooms or conference rooms. Many other sizes available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	50	50	6	29 lb	1:	--	--	--	--	NO						
		CM:	127	127	15	14 kg	2:	--	--	--	DEPENDENT:	NO						
M0405	7100	Screen, Projection, 84x84	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Projection screen. 84 X 84 inches. Heavy duty wall or ceiling mounted manual pull-down screen. Equipped with grooved roller, a ball bearing mechanical system, and steel mounting brackets. Opens with one continuous motion. Convenient for classrooms, conference rooms, or auditorium.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	6	87	5	45 lb	1:	--	--	--	--	NO						
		CM:	15	221	13	21 kg	2:	--	--	--	DEPENDENT:	NO						
M0410	6730	Screen, Projection, 70x70	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Projection screen. Ceiling mounted unit, manual pull-down screen. Equipped with grooved roller, a ball bearing mechanical system, and a non-gloss mat white flame retardant and mildew resistant surface. Unit opens with one continuous motion. Designed for classrooms, conference rooms, and auditoriums.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	6	74	5	38 lb	1:	--	--	--	0	NO						
		CM:	15	188	13	18 kg	2:	--	--	--	DEPENDENT:	NO						
M0415	6700	Projector, Slide, Carousel	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Carousel slide projector, approximately 6"H X 14"W X 13"D with auto focus zoom lens, remote control and 10 foot power cord. Convenience outlet required at point of use. [Model 2 has a 100-150 mm zoom lens. Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	11	14	13	16 lb	1:	120	1	3	60	NO						
		CM:	28	36	33	8 kg	2:	--	--	--	DEPENDENT:	NO						
M0425	7100	Monitor, Television	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Color video monitor, 17-20", with a diagonal picture tube and audio capacity. Convenience outlet required at point of use.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	20	23	20	69 lb	1:	120	1	5	60	NO						
		CM:	51	58	51	32 kg	2:	--	--	--	DEPENDENT:	YES						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0430	7100	Recorder / Player, Cassette, Video	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Professional video cassette recorder / player, approximately 5" high X 15" wide X 14" deep with VHS, NTSC, PAL, SECAM, MESECAM video cassette recorder / player capacity; 10 X picture search forward and reverse; long pause mode; digital hour meter and channel 1 dubbing. Convenience outlet required at point of use. [No other source(s) identified with this description/specification. Sharp Electronics, Panasonic & Instant Replay Communications have all discontinued the worldwide VCR.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	4	18	13	11 lb	1: 120	1	1	60	YES	YES	--				
				10	46	33	5 kg	2: --	--	--				--				
M0435	5820	Monitor, CCTV, Small, 9" (Color)	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Nine (9) inch color CCTV monitor, 9" high X 9" wide X 14" deep with a 9" diagonal picture tube. Convenience outlet required at point of use.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	9	9	13	19 lb	1: 120	1	3	60	NO	NO	--				
				23	23	33	9 kg	2: --	--	--				--				
M0440	5820	Projector, Video	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Video projector consisting of a signal source projector with built in stereo amplifier, speakers and output jack. Convenience outlet required at point of use.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	7	15	19	18 lb	1: 120	1	7	60	NO	YES	1,297				
				18	38	48	9 kg	2: --	--	--				--				
M0500	7730	Television, Color, 20" Diagonal	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Color television. Unit consists of a color receiver/monitor, with remote control, full off-air channel capability, automatic light sensor, broadcast stereo sound and automatic color balance.																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	20	24	20	54 lb	1: 120	1	1	60	NO	YES	--				
				51	61	51	25 kg	2: --	--	--				--				
M0505	7730	Television, Color, Bedside	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--
Bedside color television. The small size allows the set to be mounted on a "gravity-free" support arm which permits the patient to position the TV for comfortable viewing. The television includes an earphone jack and an AM/FM radio. Database pricing includes television, support arm, support arm wall mount, remote power supply and remote power supply wall mount. Power supply electrical requirement is approximately 1 amp at 120 V per television. [Numerous distributors found for one or both of these models. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	11	12	13	20 lb	1: 28	1	4	--	NO	NO	--				
				28	30	33	9 kg	2: --	--	--				--				
M0507	7730	Video Teleconferencing System	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites. [These three manufacturers/suppliers have numerous configurations that can be adapted to the specific needs of the user. Model 3 does not include a cart.]																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	4	2	2	32 lb	1: 120	1	1	50	NO	YES	--				
				10	5	5	15 kg	2: --	--	--				--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0510	7730	TV/VCR Combination	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
TV/VCR Combination with Remote Control, The unit shall have the following minimum features: Front end audio/video/earphone inputs jacks, on screen menu display, 181 channel tuning capability and video tracking adjustment capability. [Model 1 is a 19" TV/4-head VCR. Model 2 is a 13" TV/2-head VCR Combo. Model 3 is a 13" TV/4-head VCR combo.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	19	19	16	43 lb	1: 115	1	2	60	NO	--						
			48	48	41	20 kg	2: --	--	--	DEPENDENT:	YES	--						
M0515		Television, Plasma	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	A
42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC tuner, built-in stereo speakers and surround sound. [Sets may require over the air, cable or satellite HDTV tuner.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	32	49	6	95 lb	1: 120	1	3	60	NO	--						
			81	124	15	44 kg	2: --	--	--	DEPENDENT:	NO	--						
M0520	6530	Plethysmograph System, Vascular	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
This type of plethysmograph non-invasively measures absolute blood volume changes. The system includes the computer, keyboard, software, printer and venous occlusion system. Cuffs are applied to the lower leg which inflate to a small pressure. Small pressure and volume changes of the calf are recorded in milliliters of blood volume.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	40	32	24	50 lb	1: 115	1	4	60	NO	--						
			102	81	61	23 kg	2: --	--	--	DEPENDENT:	YES	--						
M0550	6630	Sampler, Air Particulate (Pollen)	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Air sampler with calibration device and interchangeable filters. Portable units include charger. Units can have an internal or external vacuum/pressure pump. Filter pore size determines size of airborne particles collected. [Price difference verified.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	12	14	12	5 lb	1: 120	1	1	60	NO	--						
			30	36	30	2 kg	2: --	--	--	DEPENDENT:	YES	--						
M0610	6630	Oxygen Analyzer, 0-100%	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Oxygen analyzer. Unit has readouts with audible and visual alarms. Meter range from 0% to 100%. For oxygen monitoring during surgery or post surgery. [Price difference verified.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	9	18	14	57 lb	1: 120	1	2	60	NO	--						
			23	46	36	26 kg	2: --	--	--	DEPENDENT:	YES	--						
M0615	6530	Oxygen Analyzer, Battery or Rechargeable	C	C	C	C	--	--	D	--	--	--	--	--	--	--	--	--
Rechargeable or battery operated oxygen analyzer. Unit consists of an LCD electroluminescent display with galvanic fuel cell as its sensing element. It includes low/high O2 alarms, and a self-diagnostic circuit test. Designed for use in the OR, ICU, and neonatal ICU for routine monitoring of O2 concentrations delivered to the patient. Electrical requirements if indicated, are for recharging units only. [The MiniOX 3000 is an upgraded MiniOX III. The basic function and configuration is the same. The catalog no. 710817 is a military order number that provides the unit with a hard cover case. Note: none of these units have rechargeable batteries, but provide several hundred hours of operation on a single set of batteries.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	7	4	3	2 lb	1: --	--	--	0	NO	--						
			18	10	8	1 kg	2: --	--	--	DEPENDENT:	NO	--						
M0630	6515	Anesthesia Apparatus, 3 Gas	C	C	C	C	--	--	A	G	C	--	--	--	--	--	--	--
Three gas anesthesia apparatus. Basic unit consists of steel cabinet with casters with one shallow, one medium, and one deep drawer, seven long scale eleven-inch flowmeters, five cylinder yokes, and telescoping absorber post. It includes two-canister model carbon dioxide absorber with inhalation and exhalation check valves, switch valve, switch valve elbow, sidearm Vernitrol, flow calculator, mounting kit, ventilator calculator, ventilator and an oxygen piping inlet. Also features nitrous oxide fail safe valve kit, aspirator kit, gas evacuator with vacuum and a flow meter safety cover. Used to dispense a mixture of gases during surgical procedures.																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0730	6515	Cart, Metabolic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Basal Metabolism Rate (BMR) analysis cart for spontaneously breathing (non-ventilator) patients. Indirect calorimetry for ventilator assisted patients is available as an option on some of these models or as a metabolic monitor option to the ventilator itself. [No other source(s) were identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	56	24	27	31 lb	1:	120	1	5	NO		--					
		CM:	142	61	69	14 kg	2:	--	--	--	YES		--					
M0750	6530	Flowmeter, Air, Connect w/50 PSI Supply	C	C	C	C	--	--	--	K	--	--	--	--	--	--	--	--
Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	4	4	3 lb	1:	--	--	--	NO		--					
		CM:	25	10	10	2 kg	2:	--	--	--	NO		--					
M0755	6680	Flowmeter, Oxygen, Low Flow	C	C	C	C	--	--	--	A	--	--	--	--	--	--	--	--
Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	4	4	1 lb	1:	--	--	--	NO		--					
		CM:	25	10	10	1 kg	2:	--	--	--	NO		--					
M0760	6515	Proportioner (Blender), Oxygen/Air	C	C	C	C	--	--	--	F	--	--	--	--	--	--	--	--
An air/oxygen mixer is designed to accurately control a pressurized gas mixing with an oxygen concentration. Unit contains audible alarms to warn of supply failure, an auxiliary outlet and a oxygen concentration control adjustment range from 21% to 100%. The unit can also be used to supply an accurate pre-mixed gas source to respiration or ventilator units. A specific application may require an additional air inlet filter/water trap.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	6	7	6	6 lb	1:	--	--	--	NO		--					
		CM:	15	18	15	3 kg	2:	--	--	--	NO		--					
M0765	6515	Regulator, Vacuum	C	C	C	C	--	--	--	B	--	--	--	--	--	--	--	--
Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	6	3	4	2 lb	1:	--	--	--	NO		--					
		CM:	15	8	10	1 kg	2:	--	--	--	NO		--					
M0800	6530	Center, Infant Care	C	C	C	C	--	--	--	A	E	--	--	--	--	--	--	--
Consists of a radiant warmer with proportional controller and an integral bassinet/procedure table. All four sides of the bassinet fold out of the way for access to the infant. Bassinet bed can be tilted. Bassinet cabinet has storage drawers. Unit has shelving above bassinet to accommodate monitoring and resuscitation equipment. The entire unit is mounted on conductive casters, two with locking brakes. Designed for use in the neonatal intensive care unit, nursery, delivery room and special birthing units. [Accessories include warm weigh scales, drawer module and phototherapy capabilities. No other source identified with this item description.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	87	30	49	407 lb	1:	120	1	7	NO		--					
		CM:	221	76	124	185 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0805	6530	Incubator, Infant, ICU, Mobile/Transport	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Mobile/transportable intensive care infant incubator. Unit consists of a closed controlled environment in a clear plastic hood for direct observation. Equipped with access ports, doors, heating and humidification systems, temperature and oxygen controllers, physiological monitoring system and a mattress. Used in the intensive care unit or for helicopter, airplane and ground ambulance movement of critically ill neonates. The services have approved different models and manufacturers. Verify airframe compatibility with Army Aeromedical Research Laboratory at Ft. Rucker or Armstrong Laboratory (AFMC) at Brooks AFB before purchasing. [Army, Navy and Air Force approved equipment.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	515			
			23	51	23	185 lb	1:	120	1	5								
			58	130	58	84 kg	2:	--	--	--								
M0810	6530	Incubator, Infant, ICU, Mobile	C	C	C	C	--	--	A	G	--	--	--	--	--	--	--	--
<p>ICU mobile infant incubator. Mobile unit consisting of a plastic hood enclosed controlled environment. Includes port access, on-door thermometer, oxygen port inlets, heating and humidification systems to create forced air circulation. To be used in the neonatal ICU to provide warm comfortable environments to premature neonates and critically ill newborns. [Only two sources where found for this item.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	515			
			61	47	27	284 lb	1:	120	1	9								
			155	119	69	129 kg	2:	--	--	--								
M0815	6530-00-935-1089	Incubator, Infant, Mobile, Isolation	C	C	C	C	--	--	A	F	--	--	--	--	--	--	--	--
<p>Mobile infant isolation incubator. Unit consists of a closed controlled environment inside a clear plastic hood. Equipped with heating and humidification systems to create a forced flow of air, thermometer, controls, and two oxygen inlet ports. Unit used to provide a warm environment to neonates and newborns requiring a controlled environment. [No other manufacturer could be found for this item.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	515			
			60	46	28	198 lb	1:	120	1	6								
			152	117	71	90 kg	2:	--	--	--								
M0820	6530	Warmer, Infant, Mobile	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Unit includes a clear plastic bassinet, heat source and a temperature monitor/timer. [Numerous distributors were found but only these two manufacturers. No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	515			
			73	26	41	270 lb	1:	120	1	12								
			185	66	104	123 kg	2:	--	--	--								
M0825	6515	Transilluminator, Neonatal	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Fiberoptic transilluminator for use in newborn and neonatal intensive care nurseries. The source and fiberoptic bundle provide a variable intensity light for transillumination of infant body structures. Red or white light models available. Some models are handheld and have recharging stands; others have mounted power sources and long flexible arms. Database physical dimensions are for either the handheld unit or the fixed mount power source. The unit is used primarily to locate venipuncture sites and diagnose pneumothorax, intercranial hemorrhaging, hydrocephalus or other physiologic problems.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	515			
			8	16	11	10 lb	1:	120	1	2								
			20	41	28	5 kg	2:	--	--	--								
M0875	6515	Nebulizer, Ultrasonic	C	C	C	C	--	--	A	F	--	--	--	--	--	--	--	--
<p>Ultrasonic nebulizer. The nebulizer consists of two units, an oscillator and a nebulizer. The oscillator converts electric power to ultrasonic vibrations. The ultrasonic vibrations agitate a therapeutic solution causing droplets to form in a moving air stream above the liquid. The patient inhales the air containing the medication(s). [Model 2 is a high volume ultrasonic nebulizer. Models 1 and 3 weigh less than 1 lb and use rechargeable battery packs.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	515			
			7	10	31	9 lb	1:	120	1	1								
			18	25	79	4 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0910	6515	Ventilator, High Frequency, Infant	C	C	C	C	--	--	A	F	--	--	--	--	--	--	--	--
High frequency infant ventilator. Automatic unit consists of a breathing circuit, controls, monitors, and alarms. The system has several operating modes depending on the specific configuration. The unit assists and regulates the patient's breathing. For use in the intensive care nursery to initiate respiration when changes in the breathing condition of an infant occur. [Nellcor Puritan Bennett no longer carries a high frequency ventilator product line. Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	54	19	20	143 lb	1:	120	1	7	NO		--					
		CM:	137	48	51	65 kg	2:	--	--	--	DEPENDENT: YES		--					
M0915	6530	Ventilator, High Frequency, Adult	C	C	C	C	--	--	A	F	--	--	--	--	--	--	--	--
High frequency adult ventilator. Automatic unit consists of a breathing circuit, controls, monitors, and alarms. The system has several operating modes depending on the specific use and configuration. The unit assists and regulates the patient's breathing. For use in intensive care to initiate respiration when changes in the patient's breathing condition occur. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	54	19	20	143 lb	1:	120	1	8	NO		--					
		CM:	137	48	51	65 kg	2:	--	--	--	DEPENDENT: YES		--					
M0920	6515	Ventilator, High Frequency, Transport	C	C	C	C	--	--	--	F	--	--	--	--	--	--	--	--
High frequency transport ventilator. Equipment is pneumatically powered. Unit consists of a breathing circuit, controls, monitors, and alarms. For use in neonatal, pediatric and/or adult patients. Refer to manufacturers' data for patient applications and service specific approvals for use in aircraft. [No other source identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	14	15	13	13 lb	1:	--	--	--	NO		--					
		CM:	36	38	33	6 kg	2:	--	--	--	DEPENDENT: NO		--					
M0925	6515	Ventilator, ICU, Adult	C	C	C	C	--	--	A	F	--	--	--	--	--	--	--	--
Volume ventilator with options for pressure controlled respiration, respiratory mechanics, graphics and display. Unit allows variable flow according to the balance between control pressure and the patient resistance. The respiration unit features adjustable control pressure, cycling rate, sensitivity and oxygen concentration. The respiration unit functions as an assister and controller of the patient's breathing.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	61	23	25	159 lb	1:	120	1	4	YES		--					
		CM:	155	58	64	73 kg	2:	--	--	--	DEPENDENT: YES		--					
M0930	6515	Ventilator, ICU, Neonatal/Pediatric	C	C	C	C	--	--	A	F	--	--	--	--	--	--	--	--
Neonatal/pediatric ventilator. Unit consists of ventilator pump, breathing circuit, controls, monitors, and alarms. The control mode regulates patient breathing, not allowing the patient to breathe spontaneously. The assist mode is designed for patients who have difficulty breathing, but who can initiate inspiration. Both modes use a variety of parameters (pressure, volume, CPAP, etc.) to regulate respiration rates.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	60	21	22	75 lb	1:	120	1	4	YES		--					
		CM:	152	53	55	34 kg	2:	--	--	--	DEPENDENT: YES		--					
M0935	6515	Ventilator, Portable	C	C	C	C	--	--	A	F	--	--	--	--	--	--	--	--
Unit provides long term respiratory support for patients whose conditions do not require the sophistication of critical care ventilator units. These units are typically used in step down respiratory care units or extended care facilities. [Pricing reflects units equipped with humidifiers and a stand.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	15	14	35 lb	1:	120	1	2	NO		--					
		CM:	25	38	36	16 kg	2:	--	--	--	DEPENDENT: YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M0940	6530	Ventilator, Transport	C	C	C	C	--	--	A	F	--	--	--	--	--	--	--	--
Transport ventilator for use in moving patients between facilities by ground or air. Refer to service approvals for specific aircraft applications. Unit operates in a variety of respiration modes depending on the transport conditions and needs of the patient. Unit can operate from batteries, from line voltage through a charger or from line voltage directly. [The price shown for Models 1 and 2 are GSA prices. Model 3 price is list price.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	11	13	15	33 lb	1:	120	1	2	NO							
		CM:	28	33	38	15 kg	2:	--	--	--	YES							
M1000	6530	Tent, Mist, Aerosol or Oxygen	C	C	C	C	--	--	A	F	--	--	--	--	--	--	--	--
Mist, aerosol or oxygen therapy tent. Unit consists of a clear plastic (disposable or reusable) canopy suspended by a framework above the bed and a nebulizer. When expanded over a patient bed, the tent provides aerosol therapy to those patients suffering upper respiratory infections. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	78	30	50	165 lb	1:	120	1	5	NO							
		CM:	198	76	127	75 kg	2:	--	--	--	YES							
M1100	6515	Resuscitator, Bag-Mask, Hand Operated	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Hand operated bag-mask resuscitator. Consists of face mask, non-rebreathing valve, compression bag and tidal bag. Used for resuscitation in life saving situations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	12	24	12	3 lb	1:	--	--	--	NO							
		CM:	30	61	30	1 kg	2:	--	--	--	NO							
M1110	6515	Resuscitator, Bag-Mask, Hand Op, Infant	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Hand operated bag-mask resuscitator. Consists of an infant face mask, non-rebreathing, pressure limiting safety valve, compression bag, tidal bag, oxygen reservoir bag and manometer connection and wall bracket. Cleaning and decontamination methods include disinfecting, pasteurization, boiling and steam autoclaving. Used for resuscitation of infants in life saving situations. [Ambu, Inc (Model 3) does not provide a wall bracket.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	12	6	6	3 lb	1:	--	--	--	NO							
		CM:	30	15	15	2 kg	2:	--	--	--	NO							
M1205	6530	Balance, Analytical, Laboratory/Pharmacy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Analytical balance. Consists of a large weighting chamber accessible from three sides. Equipped with large digital display zero tracking, audible tare, and membrane switches; with built-in calibration weight. For use in the laboratory and the pharmacy. Weight capacity dual range 52/202 Gram Minimum.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	12	10	20	20 lb	1:	120	1	1	NO							
		CM:	31	25	50	9 kg	2:	--	--	--	NO							
M1210	6530	Balance, Electronic, Laboratory/Pharmacy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Electronic balance with high fluorescent display, built-in auto tracking and tape. Unit has a programmable selection for weight range and automatic calibration. Intended for use in the laboratory or pharmacy. Unit's weight limitation will be no less than 4000 grams.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	4	12	14	18 lb	1:	120	1	1	NO							
		CM:	10	30	36	8 kg	2:	--	--	--	NO							
M1215	6670-00-401-8400	Balance, Prescription, 10 mg Sensitivity	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Prescription balance. The unit consists of sealed case with a draft shelter, stainless steel pans and a digital or analog readout. NIST certified and meets specifications for Class III prescription balances. Used for weighing drugs before dispensing. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	12	13	7	15 lb	1:	--	--	--	NO							
		CM:	30	33	18	7 kg	2:	--	--	--	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M1220	6670-00-119-4623	Balance, Mechanical Torsion, Enclosed	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Enclosed mechanical balance with two equal stainless steel pans, magnetic damping and hinged cover. Operated by a graduated knob. The balance is used in pharmacies for prescription weighing. [The DLM-2 from Fulcrum, marketed by Allegiance is nationally discontinued. No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			11	28	8	13 lb 6 kg	1:	--	--	0	NO	NO	--					
			13	33			2:	--	--				--					
			8	20									--					
M1225	6670-00-401-7195	Balance, Trip, 2 Beam, 2kg Capacity, .1gm Division	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Double beam Harvard trip balance with 2 kg capacity, 0.1 gram sensitivity (divisions), tare bar and dual 6 inch diameter corrosion-resisting steel plates. Does not include weights. Suitable for laboratory use when weighing containers are employed and can be used for specific gravity measurements. [See M1205 and M1210 for other or alternative balances.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			11	28	9	6 lb 3 kg	1:	--	--	0	NO	NO	--					
			15	38			2:	--	--				--					
			9	23									--					
M1230	6670-00-401-8830	Weight Set, Calibration, 100 gm to 1 kg	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Weight set for calibrating mechanical and electronic balances. Item consists of a fitted case containing handling forceps and a series of specially manufactured weights. Weights range from 100 grams to 1000 grams (1 kg). Database pricing is for Class 1 weight sets with certificates. Other classes of weights are more or less precise.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			8	18	8	11 lb 5 kg	1:	--	--	--	NO	NO	--					
			16	41			2:	--	--	--			--					
			8	18									--					
M1235	6630	Weight Set, Calibration, 1 mg to 100 gm	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Weight set for calibrating mechanical and electronic balances. Item consists of a fitted case containing handling forceps and a series of specially manufactured weights ranging from 1 milligram to 100 grams. Database pricing is for Class 1 weight sets with certificates. Other classes of weights are more or less precise.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			3	8	7	4 lb 2 kg	1:	--	1	--	NO	NO	--					
			8	20			2:	--	--	--			--					
			8	18									--					
M1240	6630	Table, Balance, Marble	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Marble balance table approximately 36" W x 24" D x 31" H. Legs are reinforced with a cast iron support pipe and rounded edges. Marble top is at least 3" thick. Used for stability and vibration reduction when reading scales.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			31	79	25	700 lb 318 kg	1:	--	--	0	NO	NO	--					
			36	91			2:	--	--				--					
			25	64									--					
M1300	8120	Dewar, Liquid Nitrogen	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Liquid nitrogen Dewar. Unit consists of a 50 liter capacity insulated storage cylinder with stainless steel inside, dispensing spout and mobility cart. Used for bulk liquid nitrogen storage. [Weight is for an empty container. Price shown is the purchase price for the item with accessories.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			41	104	19	62 lb 29 kg	1:	--	--	0	NO	NO	--					
			19	48			2:	--	--				--					
			19	48									--					
M1400	6530	Chair, Blood Donor, Recliner, Manual or Pneumatic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Blood donor recliner chair constructed from wear and chemical resistant upholstery. Chair features extra-wide arm rests and a contoured back for lumbar and lateral support. Used for blood donor and pheresis procedures.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			54	137	74	170 lb 78 kg	1:	--	--	--	NO	NO	--					
			36	91			2:	--	--	--			--					
			74	188									--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
M1405	6530	Chair, Blood Donor, Recliner, w/Motor, Armrest	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--		
Donor chair, with motor and armrest. Contour chair with extra wide armrests, remote control, and power slide control. [No other source(s) identified with this description/specification.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	48	23	60	250 lb	1:	120	1	1	60		NO							
		CM:	122	58	152	114 kg	2:	--	--	--	DEPENDENT:		YES							
M1410	6640	Chair, Laboratory, Blood Drawing, w/Storage	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Laboratory blood drawing chair with storage. Chair has built-in storage cabinet(s) and locking arm assembly that may be positioned on either side of the fiberglass chair. [Price difference verified.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	38	47	28	121 lb	1:	--	--	--	--		NO							
		CM:	97	119	71	55 kg	2:	--	--	--	DEPENDENT:		NO							
M1411	6530	Phlebotomy Arm, Wheelchair Accessible	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
This item is a wall mounted phlebotomy arm designed for drawing blood from wheelchair patients. A mounting frame attaches to a wall and accommodates the armrest. The armrest may be adjusted from the wall to various lengths. The armrest may be positioned for right or left arm. [No other source(s) identified with this description/specification.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	30	28	36	20 lb	1:	--	--	--	0		NO							
		CM:	76	71	91	9 kg	2:	--	--	--	DEPENDENT:		NO							
M1450	3540-00-457-2699	Sealer, Electronic, Blood Bag	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--		
Electronic blood bag sealer. Used for sealing blood-filled plastic tubing of blood collecting-dispensing bag.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	9	12	13	13 lb	1:	120	1	1	60		NO							
		CM:	23	30	33	6 kg	2:	--	--	--	DEPENDENT:		YES							
M1605	6530	Holder, Chart, 20 Each	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Clinical chart holder cart. 20 chart capacity. 2 side-by-side tiers. May be ordered in various chart capacities. Constructed of heavy metal frames with vinyl laminated surfaces or painted panels. 3" casters with locks. Used to hold patient spring loaded charts.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	53	28	26	102 lb	1:	--	--	--	--		NO							
		CM:	135	71	66	47 kg	2:	--	--	--	DEPENDENT:		NO							
M1610	6530	Holder, Chart, Mobile, 45 Each	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Mobile chart holder with a 45 chart capacity. Unit is mounted on casters with rows of racks to accommodate chart holders and may include a drop-type writing shelf, a drawer centered below racks and a special lock mechanism. [No other source(s) identified with this description/specification]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	55	50	18	102 lb	1:	--	--	--	--		NO							
		CM:	140	127	46	47 kg	2:	--	--	--	DEPENDENT:		NO							
M1615	6530-00-774-1310	Holder, Chart, Mobile, 30 Each	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Mobile clinical chart holder cart. Thirty chart holder capacity. Accommodates standard 9" X 12" charts, 3" casters constructed of heavy steel and finished on a baked-on enamel. Unit used as a chart carriage.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	53	36	36	145 lb	1:	--	--	--	0		NO							
		CM:	135	91	91	66 kg	2:	--	--	--	DEPENDENT:		NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M1620	6530	Holder, Chart, Patient, Wall or Door Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall or door mounted patient chart holder. Constructed of durable plastic or metal. Used for holding patient records. Size as required.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	15	4	9 lb	1:	--	--	--	NO		--					
		CM:	25	38	10	4 kg	2:	--	--	--	NO		--					
M1625	6530	Rack, Chart, Desk/Table Mounted	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Desk/table mounted chart rack holder. Size as required to hold number of charts required. Used for holding patient charts. [Each model is for a counter top cabinet, flat storage with a capacity of 10 charts. Model 3 is vertical with dimensions of 49"H X 15"W X 16"D. This height dimension is not included in the overall dimensions shown.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	20	34	16	55 lb	1:	--	--	--	NO		--					
		CM:	51	86	41	25 kg	2:	--	--	--	NO		--					
M1715	6515	Hemodialysis Unit, Hollow Fiber or Plate	C	C	C	C	--	E	A	--	--	--	--	--	--	--	--	--
Complete hemodialysis unit using either hollow fiber or plate type dialyzers. Unit is freestanding in a wheeled cabinet and include water connection, concentrate pickup pump, proportioner, conductivity monitor, dialysate heater, blood pump, heparin pump, arterial pressure monitor, venous pressure monitor, TMP monitor, air/foam detector, optical detector, blood leak detector, power failure alarm, and remote alarm contacts. Accommodates single needle, two pump procedures. Database information reflects mobile units which carry their own water purification systems. Predominately stationary units within a clinic area can operate from a central water purification system. Electrical circuit should include a ground fault interrupter. Variations of this equipment include versions for pediatric use and peritoneal dialysis (JSN M4860). Optional equipment includes blood pressure monitoring and a variety of waste handling options. [GFI protection required for these units.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	54	23	30	225 lb	1:	120	1	14	NO		2,730					
		CM:	137	58	76	103 kg	2:	--	--	--	YES		--					
M1800	7025	Computer, Microprocessing, w/CRT Monitor	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Desk top microprocessing computer. The unit shall consist of a central processing mini tower, CRT monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 1.5 GHz Pentium processor; 256 MB memory; 40GB hard drive; 20/48x CD-ROM; a 3.5" floppy drive; 1.44MB network interface card; video 32 MB NVIDIA; a 19 inch CRT color monitor. The computer is used throughout the facility to input, manipulate and retrieve information.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	23	19	19	50 lb	1:	120	1	5	NO		--					
		CM:	58	48	48	23 kg	2:	--	--	--	YES		--					
M1801	7025	Computer, Microprocessing, w/Flat Panel Monitor	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 1.5 GHz Pentium processor; 256 MB memory; 40GB hard drive; 20/48x CD-ROM; a 3.5" floppy drive; 1.44MB network interface card; video 32 MB NVIDIA; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, manipulate and retrieve information.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	23	19	19	45 lb	1:	120	1	5	YES		--					
		CM:	58	48	48	21 kg	2:	--	--	--	NO		--					
M1802	7110	Work Station, Computer, Retractable, Wall Mounted	C	C	C	C	--	--	G	--	--	--	--	--	--	--	--	--
A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited. [This work station is custom designed and configured based on location, application and integrated computer system/equipment (i.e.. flat screen monitors, hand-helds, thin client or laptop computers) intended to be used with the station. Electrical data provided is estimated base on an installed laptop computer. Computers are an additional cost if purchased with the work station. No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	42	28	6	58 lb	1:	120	1	5	NO		--					
		CM:	107	71	15	27 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M1805	3610	Copier, Desk Top	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Desk top copier. Copier consists of two tray paper supply with clip tray, sort indicator, two page copy indicator, automatic paper selection and frame eraser with zoom capabilities. For use where low volume reproduction is required. [Copier speed based on 15 copies per minute for letter sized paper and a monthly volume of approximately 20,000 copies. Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	26	22	25	62 lb	1:	120	1	15	NO		--					
		CM:	66	56	64	29 kg	2:	--	--	--	YES		--					
M1810	3610	Copier, Floor Standing, Digital	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
Floor standing copier. Unit features automatic paper size selection, automatic document feeder and sorter. The system also has zoom capabilities and automatic two-sided copying. For use where medium volume reproduction is required in the range of 30 to 40 copies per minute.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	45	33	28	250 lb	1:	120	1	15	NO		--					
		CM:	114	84	71	114 kg	2:	--	--	--	YES		--					
M1815	7400	Embosser, Compact, Plastic Card	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Plastic card compact card-writer. Unit consists of a buffered typewriter keyboard, dual editing modes, format control, and automatic card handling. Duplicate card feature when needed. Designed for processing plastic cards. Magnetic stripe encoding is an available option for this system. See JSN M1816 for metal tag (dog tag) embossing machines.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	17	29	19	100 lb	1:	120	1	4	NO		--					
		CM:	43	74	48	46 kg	2:	--	--	--	YES		--					
M1816	6530	Embosser, Metal Tag	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Embossing unit capable of making a range of sizes of metal identification tags for a variety of purposes. This unit is used to make military identification tags (commonly referred to as "dog tags"). Some vendor's equipment is a modification to the plastic card embossers at JSN M1815 which is not available from the base unit manufacturers. [GSA price for Model 1 is \$14,350. The model number for Model 3 changed from DataCard 280 to 295, however, product specifics remain the same.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	17	32	30	167 lb	1:	120	1	10	NO		--					
		CM:	43	81	76	76 kg	2:	--	--	--	YES		--					
M1820	6530	Imprinter, Data Record, Electric	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Electric data record imprinter. The device accepts embossed plastic patient cards in either the 50 column or the 80 column format and adjusts automatically for card size and form thickness. Device will provide clear readable impressions with a cycle that is less than 1 second in length. Electro-mechanical design provides for a consistent impression that is independent of operator knowledge or technique. Unit may include a date/time stamp as an accessory.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	8	15	10	27 lb	1:	120	1	1	NO		--					
		CM:	20	38	25	12 kg	2:	--	--	--	YES		--					
M1822	6530	Imprinter, Data Record, Manual	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Manual data record imprinter. This manual device is used to imprint personalized information from the plastic patient identification card. The unit will accept a 51 column form set and a 80 column form set.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	5	5	13	4 lb	1:	--	--	--	NO		--					
		CM:	13	13	33	2 kg	2:	--	--	--	NO		--					
M1825	7025	Printer, Computer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	14	17	20	39 lb	1:	120	1	3	NO		--					
		CM:	36	43	51	18 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M1830	7100	Printer, Label, Pharmacy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	13	13	19	45 lb	1: 115	1	5	60	NO	--						
			33	33	48	21 kg	2: --	--	--	DEPENDENT:	YES	--						
M1832	7100	Printer, Color, Small	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Desktop color printer. Printer shall be capable of printing a minimum of 10 pages per minute (ppm) of black print and 7 ppm color print. Resolution shall be no less than 1440 X 720 dpi. It shall be capable of printing on multiple media types (plain, inkjet and photo paper) and be capable of accepting media sizes of 3 X 5 to 8.5 X 14 inches. The printer is used in small offices. [Models 1 and 3 are laser printers. Model 2 is an inkjet printer.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	16	20	19	70 lb	1: 120	3	1	60	NO	--						
			41	51	48	32 kg	2: --	--	--	DEPENDENT:	YES	--						
M1835	7100	Printer, Color Laser, Large	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Color laser printer that is designed for high volume use and is network capable.. The printer shall be capable of printing a minimum of 25 pages per minute (ppm) of black print and 20 ppm color print. Resolution shall be no less than 600 X 600 dpi. It shall be capable of printing on multiple media types (plain, inkjet, photo paper and transparencies) and be capable of accepting media sizes of 3 X 5 to 8.5 X 14 inches. The printer is used in multi-user network offices.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	41	28	26	177 lb	1: 120	1	9	60	NO	--						
			104	71	66	81 kg	2: --	--	--	DEPENDENT:	YES	--						
M1840	7100	Printer/Copier/Fax Combination	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine. [The multifunctional PFC all-in-one machines vary greatly in quality, capacity and capabilities. There are multiple choices available. Selection should be made based on intended application and volume anticipated. The units identified under this JSN are designed for an office staff of approximately 6 to 25 people where speed and printing quality are important and where integration with PCs is probable.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	20	22	21	40 lb	1: 120	1	9	60	NO	--						
			51	56	53	19 kg	2: --	--	--	DEPENDENT:	YES	--						
M1845	7100	Plotter/Printer, Large Format, Digital	C	C	C	C	--	--	D	--	--	--	--	--	--	--	--	--
Large format, digital plotter/printer, 42" wide. The unit will provide large format color graphics with photo realistic image quality and color fast prints. Will include, as minimum, Adobe PDF 1.3, Adobe PostScript 3 and 256MB memory. The unit will print with speed, transfer files at up to 4.5 megabytes per second, and provide for easy connectivity for multiple platform environments. [Model 2 is a high speed black and white printer/plotter. Xerox (Cage 3J850) will introduce a color large format printer/plotter later in the year.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	50	78	34	683 lb	1: 120	1	4	0	NO	--						
			127	198	86	310 kg	2: 220	1	13	DEPENDENT:	NO	--						
M1850	7100	Typewriter, Electric	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Electric typewriter. Unit is an electronic typewriter with spell check and automatic correction. It features 10, 12, or 15 characters per inch pitch, margin adjustment and phrase storage. Used for general typing tasks such as forms, envelopes, labels and letters. [Price differences verified.]																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	7	22	18	24 lb	1: 120	1	1	60	NO	--						
			18	56	46	11 kg	2: --	--	--	DEPENDENT:	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M1855	7100	Facsimile Machine	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Facsimile unit used to transmit printed matter or images over standard telephone lines. The unit operates at a minimum of 9600 baud and automatically recognizes and communicates with a variety of standard facsimile machines. Commonly referred to as "fax" unit.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	12	18	16	25 lb	1:	120	1	1	60	YES	--						
			30	46	41	12 kg	2:	--	--	--	DEPENDENT:	YES	--						
M1870	5830	Camera, Photo Identification Card System	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Photo identification card camera for producing identification card photographs. The minimum system comes complete with a photograph die cutter and laminator. More sophisticated systems can include graphics interfaces, door access management, signature capture and database management capabilities. Advanced systems may require a microcomputer (see JSN M1800). [Price difference verified.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	23	23	24	75 lb	1:	120	1	5	60	NO	--						
			58	58	61	34 kg	2:	--	--	--	DEPENDENT:	YES	--						
M1875	7210	Board, Copy, Electronic Facsimile	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	78	77	24	138 lb	1:	120	1	7	60	NO	--						
			198	196	61	63 kg	2:	--	--	--	DEPENDENT:	YES	--						
M1900	6930	Manikin, Training, ACLS/CPR	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
CPR/Advanced Life Support manikin for individual or team training with cardiac rhythm (arrhythmia) simulator accessory, realistic anatomical landmarks and carrying case. Supports intubation, suction, I.V. placement, blood pressure cuff placement, ECG monitoring and defibrillation. Video monitor and video interfaces available for some models (not included). Many other types of training manikins are available.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	12	72	24	100 lb	1:	--	--	--	0	NO	--						
			30	183	61	46 kg	2:	--	--	--	DEPENDENT:	NO	--						
M2005	7125	Cabinet, Storage, Acid, Floor Standing, Shelves	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Floor standing acid storage cabinet. A 30 gallon capacity standard two door cabinet with adjustable shelves, three-point latch with key-lock and 2" raised leak proof sill. An 18-gauge steel frame with vents, 1 1/2" airspace between walls and epoxy finish resistant to chemical attack. Note: Not for use with nitric and sulfuric acids.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	44	43	18	265 lb	1:	--	--	--	--	NO	--						
			112	109	46	121 kg	2:	--	--	--	DEPENDENT:	NO	--						
M2010	7125	Cabinet, Storage, Acid, Undercounter	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	E	
Undercounter acid/corrosives storage cabinet. Unit is of 18 gauge welded double wall with vents and grounding wire connections, leak proof sill and adjustable shelves. Equipped with built-in swinging doors and three-point locking doors. Note: Not recommended for phenol, sulfuric or nitric acids. [No other source(s) identified with this description/specification]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	35	35	22	212 lb	1:	--	--	--	--	NO	--						
			89	89	56	97 kg	2:	--	--	--	DEPENDENT:	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES																																													
				A	N	A	V	I	1	2	3	4	5	6																																			
M2015	7125	Cabinet, Storage, Flammable, Freestanding	C C C C --	--	--	--	--	--	--	--	--	--	--																																				
<p>Freestanding flammable safety storage cabinet. Size as required. Unit is of all welded steel wall construction with vented grounding attachments, raised leak proof door sill and adjustable shelving. Equipped with swinging doors and built-in key lock. Designed for storage of flammable fluids. Complies with OSHA standards, is FM approved and designed IAW NFPA 30.</p>																																																	
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>65</td> <td>165</td> <td>43</td> <td>376 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>0</td> <td>NO</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>18</td> <td>171 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>														UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	65	165	43	376 lb	1:	--	--	0	NO	NO	--				18	171 kg	2:	--	--				
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																																						
EA	65	165	43	376 lb	1:	--	--	0	NO	NO	--																																						
			18	171 kg	2:	--	--																																										
M2020	7125	Cabinet, Storage, Safety, Built-In, Vented	A A A A --	--	--	--	--	--	--	--	--	--	E																																				
<p>Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.</p>																																																	
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>36</td> <td>91</td> <td>48</td> <td>315 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>22</td> <td>143 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>														UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	36	91	48	315 lb	1:	--	--	--	NO	NO	--				22	143 kg	2:	--	--				
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																																						
EA	36	91	48	315 lb	1:	--	--	--	NO	NO	--																																						
			22	143 kg	2:	--	--																																										
M2025	7125	Rack, Storage, Cylinder, Gas	A A A A --	--	--	--	--	--	--	--	--	--	--																																				
<p>Medical gas cylinder storage rack. Unit is a modular cage frame for holding various sizes of gas cylinders. Nylon or fabric securing straps can be attached to the frame bars to stabilize gas cylinders. Add additional units or specify size as required when ordering. This item is often locally fabricated.</p>																																																	
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>40</td> <td>102</td> <td>34</td> <td>245 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>43</td> <td>112 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>														UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	40	102	34	245 lb	1:	--	--	--	NO	NO	--				43	112 kg	2:	--	--				
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																																						
EA	40	102	34	245 lb	1:	--	--	--	NO	NO	--																																						
			43	112 kg	2:	--	--																																										
M2030	7125	Cabinet, Storage, Acid, Freestanding	C C C C --	--	--	--	--	--	--	--	--	--	--																																				
<p>Freestanding acid/corrosives storage cabinet approximately 43"W x 18"D x 65"H. Height may vary with the volume required. Unit is of 18 gauge double wall stainless steel construction. Equipped with adjustable shelves, sliding door and three-point latch with key-lock. Designed for storage of acid/corrosive type fluids. Note: Not for use with nitric and sulfuric acids.</p>																																																	
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>65</td> <td>165</td> <td>43</td> <td>367 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>18</td> <td>167 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>														UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	65	165	43	367 lb	1:	--	--	--	NO	NO	--				18	167 kg	2:	--	--				
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																																						
EA	65	165	43	367 lb	1:	--	--	--	NO	NO	--																																						
			18	167 kg	2:	--	--																																										
M2035	6530	Rack, Storage, Mobile, Wire, CRS	C C C C --	--	--	--	--	--	--	--	--	--	--																																				
<p>Mobile, wire, storage rack. Unit has open, fully adjustable, corrosion resistant wire surfaces and is mounted on stem casters. Used for linen or other general purpose storage and transport. Racks are provided in various sizes and configurations. The price provided is for a unit approximately 68"H x 18"D x 48"W with four shelves, bumpers, two swivel and two braking casters.</p>																																																	
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>70</td> <td>178</td> <td>48</td> <td>89 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>0</td> <td>NO</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>18</td> <td>41 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>														UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	70	178	48	89 lb	1:	--	--	0	NO	NO	--				18	41 kg	2:	--	--				
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																																						
EA	70	178	48	89 lb	1:	--	--	0	NO	NO	--																																						
			18	41 kg	2:	--	--																																										
M2045	6525	Shelving, Storage, Beam Block Tray	C C C C --	--	--	--	--	--	--	--	--	--	--																																				
<p>Storage shelving unit for radiation therapy beam block and wedge trays. The unit has a wood core with plastic laminate finish. The shelving unit accommodates up to 44 custom beam block trays. Different size units, double sided units, mobile units and varying shelf configurations are available. [Price difference verified. See JSN M2100 for standard shelving units which may also be used for this purpose.]</p>																																																	
<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>66</td> <td>168</td> <td>68</td> <td>220 lb</td> <td>1:</td> <td>--</td> <td>--</td> <td>0</td> <td>NO</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td>15</td> <td>100 kg</td> <td>2:</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>														UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	66	168	68	220 lb	1:	--	--	0	NO	NO	--				15	100 kg	2:	--	--				
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																																						
EA	66	168	68	220 lb	1:	--	--	0	NO	NO	--																																						
			15	100 kg	2:	--	--																																										

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES						
				A	N	A	V	I	1 2 3 4 5 6	
M2050	7100	Shelving, Storage, 75"H X 36"W X 14"D	C C C C --	--	--	--	--	--	--	
Storage shelving unit. Unit is corrosion resistant stainless steel, galvanized steel or baked enamel on steel. It contains 5 adjustable shelves with 400 pound load capacity. Available in open or closed (end panels) designs. Unit is designed for storage and light industrial applications. [Price difference verified.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	75	36	14	106 lb	1:	-- -- --	NO	--
		CM:	191	91	36	49 kg	2:	-- -- --	NO	--
M2055	7100	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	C C C C --	--	--	--	--	--	--	
Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves. [No other source(s) identified with this description/specification]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	84	48	18	40 lb	1:	-- -- --	NO	--
		CM:	213	122	46	18 kg	2:	-- -- --	NO	--
M2070	7100	Shelving, Storage, 77hx36wx18d	C C C C --	--	--	--	--	--	--	
Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room. [Lyon Metal Products Inc., (Model 1) no longer has 77" H shelving. Their units are now 84" H.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	84	36	18	153 lb	1:	-- -- --	0	--
		CM:	213	91	46	70 kg	2:	-- -- --	NO	--
M2075	7100	Shelving, Storage, Enclosed	C C C C --	--	--	--	--	--	--	
Storage shelving unit approximately 87hx48wx12d. Unit is corrosion resistant baked enamel on steel and has adjustable shelves. This is a 5, 6 or 7 shelf, closed model with end panels. The shelving is designed for use in storage areas. [Model 1 manufactured by Lyon Metal Products is 18" deep. Twelve inch deep units must be custom ordered.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	85	48	12	145 lb	1:	-- -- --	0	--
		CM:	216	122	30	66 kg	2:	-- -- --	NO	--
M2080	7100	Shelving, Storage, Solid, CRS,w/Adjustable Shelves	C C C C --	--	--	--	--	--	--	
Stationary, solid, shelving unit. Unit has fully adjustable shelves constructed of solid stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 76"H x 18"D x 48"W with four shelves. [No other source(s) identified with this description/specification]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	74	48	18	136 lb	1:	-- -- --	NO	--
		CM:	188	122	46	62 kg	2:	-- -- --	NO	--
M2085	7100	Shelving, Storage, Pallet	C C C C --	--	--	--	--	--	--	
Pallet storage shelving starter section. This unit is of heavy duty construction and has channel type bracing in between columns, heavy duty foot plate with 3-point security. The size will be determined by weight load. It is designed for easy forklift access in storage areas and warehouses.										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	168	108	42	425 lb	1:	-- -- --	NO	--
		CM:	427	274	107	193 kg	2:	-- -- --	NO	--
M2090	7125-01-099-5763	Shelving, Storage, Warehouse	C C C C --	--	--	--	--	--	--	
Warehouse storage shelving approximately 75 inches high by 36 inches wide by 24 inches deep. [Model 3 shelving is 84" high. Lyon Metal Products no longer has 75" H shelving.]										
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:
EA		IN:	75	36	24	183 lb	1:	-- -- --	0	--
		CM:	190	91	61	83 kg	2:	-- -- --	NO	--

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES						
				R	A	F	A	H		1	2	3	4	5	6	
M2100	6530	Cart, Shelving, Storage, Mobile, SS	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	--
Mobile storage shelving cart 72" X 48" X 24" with four shelves. Constructed with corrosion resistant stainless steel and mounted on swivel casters. Designed for large carrying capacity and distribution of items from a central source. Options include wire or solid shelves, oversize casters, ledges, rods, tabs, dividers, drawers and bins as well as back and side enclosures. Casters add 6" to equivalent standing shelf height. [Model 1 must be created by separately identifying stainless steel posts (74UPS), shelves (2448NS) and casters (5MPBGSA). Model 2 is available in a number of configurations. Model 3 must also be created by separately identifying the stainless steel part numbers.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:					
EA		IN:	80	48	24	110 lb	1:	--	--	--	NO					
		CM:	203	122	61	50 kg	2:	--	--	--	NO					
M2105	3920	Pallet Lift, Hydraulic, Manual, 48" Pallet	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	--
Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates 48" pallets and is designed to handle all types of lifting tasks.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:					
EA		IN:	52	27	60	180 lb	1:	--	--	--	NO					
		CM:	132	69	152	82 kg	2:	--	--	--	NO					
M2110	5400	Ladder, Platform, Mobile	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	--
Mobile, platform ladder. Unit consists of a non-skid steel steps and platform. Top platform is at least 17" X 16". For reaching high storage areas.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:					
EA		IN:	98	33	63	90 lb	1:	--	--	--	NO					
		CM:	249	84	160	41 kg	2:	--	--	--	NO					
M2115	3920	Truck, Hand, 2 Wheel	C C C C --	--	--	--	--	--	--	0	--	--	--	--	--	--
2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:					
EA		IN:	47	20	24	44 lb	1:	--	--	--	NO					
		CM:	119	51	61	20 kg	2:	--	--	--	NO					
M2120	3920	Truck, Platform, 4 Wheel	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	--
A 4 wheel platform truck (push cart). Truck has heavy duty platform and is mounted on four 8" diameter casters. The load capacity is 2000-2500 pounds. It is designed for use in the receiving and other material handling areas.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:					
EA		IN:	36	30	60	60 lb	1:	--	--	--	NO					
		CM:	91	76	152	27 kg	2:	--	--	--	NO					
M2125	6530	Stacker, Straddle, 127" Lift, 2000 lb Capacity	C C C C --	--	A	--	--	--	--	60	--	--	--	--	--	--
Straddle stacker. Battery powered with 2000 pound lifting capacity. Unit lifts to heights up to 127". Equipped with a extra heavy duty hydraulic system. Unit has a built-in automatic battery charger. Electrical requirements are for the charger. Designed for pallet lifting. [Price differences verified.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:					
EA		IN:	153	56	73	2,660 lb	1:	120	1	15	NO					
		CM:	389	142	185	1,208 kg	2:	--	--	--	YES					
M2130	3930	Truck, Hydraulic Lift, Electric	C C C C --	--	A	--	--	--	--	60	--	--	--	--	--	--
Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger. Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long distances or over uneven surfaces.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:					
EA		IN:	92	27	60	650 lb	1:	120	1	10	NO					
		CM:	234	69	152	294 kg	2:	--	--	--	NO					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M2200	3930	Compactor, 1.5 - 6 CuYd, Receiver 15 - 40 CuYd Cap	A	A	A	A	--	--	D	--	--	--	--	--	--	--	--	--
Hydraulic ram waste compactor with a minimum ram face pressure of at least 2000 PSI. Receiving box varies with manufacturer from 1.5 to 6 cubic yards capacity. Able to accommodate waste receiving boxes from 15 to 40 cubic yard capacity. Feed station with sealed connection between compactor and container to control leakage. Manufacturers offer various units with sizes and capacities designed to meet specific waste compaction requirements. General purpose compacting system for institutional use.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	105	96	281	11,300 lb	1:	208	3	21	NO		--					
EA		CM:	267	244	714	5,131 kg	2:	120	--	1	YES		--					
M2205	3930	Compactor, VERT, Freestanding, Front Door Loading	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Front door loading. Freestanding vertical waste compactor. Totally enclosed heavy duty steel frame, hydraulic cylinders mounted on RAM plate, RAM thrust adjustable 500 to 3,000 PSI front door open loading, packages in plastic or paper bags, cartons or specially designed containers. For all routine maintenance requirements in hospitals and nursing homes. [Model 2 and 3 come in two additional sizes as well as the ones shown. The Model 3 manufacturer, Ver-Tech, also has marine models available.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	82	35	32	1,350 lb	1:	120	1	15	NO		--					
EA		CM:	208	89	81	613 kg	2:	--	--	--	YES		--					
M2300	3510	Washer, Clothes, Automatic	C	C	C	C	--	D	A	--	--	--	--	--	--	--	--	--
Large capacity automatic clothes washer with a heavy duty motor. The unit's control system programs load, cycle time, spin speed, fabric, water level and water temperature. The washer includes a bleach and/or fabric softener dispenser and a filter ring for trapping lint. [Height :56 inches is with lid open. Floor must be able to support 315 pounds.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	56	27	26	182 lb	1:	120	1	15	NO		--					
EA		CM:	142	69	66	83 kg	2:	--	--	--	YES		--					
M2400	3510	Dryer, Clothes, Automatic, Electric, Household	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	E
Automatic clothes dryer. Electric unit features automatic sensi-dry control with setting for different kinds of fabrics, timed cycle, removable lint filter, drum interior light and enamel finish. [There are many other models available from these manufacturers at varying prices from approximately \$275 to \$900.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	44	29	30	140 lb	1:	240	1	27	NO		22,000					
EA		CM:	112	74	76	64 kg	2:	--	--	--	YES		--					
M2500	3510	Marker, Linen	C	C	C	C	--	--	A	D	--	--	--	--	--	--	--	--
Linen marker. Unit consists of a dry ink ribbon, dual electronic temperature controls which allows easy switching between printing and sealing, transparent dust cover that permits monitoring of the ink ribbon, a ribbon rewind which provides convenient disposal of used ribbons or transfer papers, air regulator that sets pressure, a timer, which controls dwell time, a pilot light and an on/off switch. This item is designed for a wide range of applications for linen supply plants in small hospitals or nursing homes. Recommended for use wherever linen and textiles items are marked directly. Available options on some models include a platen for heat sealing. Compressed air required 75 PSI (5.2 bars) 0.4CFM (0.2liters/sec). [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	20	15	27	75 lb	1:	110	1	4	NO		--					
EA		CM:	51	38	69	34 kg	2:	--	--	--	YES		--					
M2505	3510	Patching Machine, Linen, Thermal	C	C	C	C	--	--	A	D	--	--	--	--	--	--	--	--
Heat seal machine. This electronic high pressure machine is designed for fast, strong application of computer labels, embroidered or printed emblems, hot paper transfers and for mending patches. Machine is designed as a table model unit for transfer and mending. Unit includes top and bottom heat. This high pressure design is excellent for the application of garment labels, and for mending patches and transfers at relatively short cycle times. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	19	7	20	60 lb	1:	110	1	15	NO		--					
EA		CM:	48	18	51	28 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
M2600	7910	Vacuum, Wet/Dry, HEPA Filtration	C C C C --	--	A	--	--	--	--	--	--	--	--
Wet/dry vacuum cleaner with HEPA filtration. Unit consists of a minimum 10 gallon capacity corrosion resistant waste tank, two stage vacuum motor and dual filtering system mounted on casters. Vacuum is designed for use in patient care areas and operating room suites. [Model 1 GSA price is \$1,448.00.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	46	22	24	75 lb	1:	120	1	13	60	NO	--
		CM:	117	56	61	34 kg	2:	--	--	--	DEPENDENT:	YES	--
M2605	6515	Pump, Breast	C C C C --	--	A	--	--	--	--	--	--	--	--
Electrically powered breast pump. The pump provides automatic or semi-automatic control of the pumping cycle and has a pressure limiting valve to prevent damage to breast tissues. Unit includes collection and overflow bottles as well as bacteria filters for the suction line between the pump and the overflow bottle. Options include a trolley, carrying case and several sizes of collection bottles. [Price difference verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	14	15	12	18 lb	1:	120	1	1	60	NO	--
		CM:	36	38	30	8 kg	2:	--	--	--	DEPENDENT:	YES	--
M2650	7910	Scrubber, Floor, Automatic, Rechargeable	C C C C --	--	A	--	--	--	--	--	--	--	--
Automatic rechargeable floor scrubber. Unit has a heavy gauge rust resistant metal frame, rust resistant or rust proof solution/recovery tanks, a heavy duty plastic or metal cover and 200 RPM offset brushes for close-to-wall cleaning. The brush drive motors are a minimum of 3/4 HP. Battery capacity is 240 amp/hour or better. Unit features a combination of manual and automatic controls for ease of use and safety. Database information reflects a machine with a 32" wide swath. Options include an extension cleaning wand, water recirculation for extended use, automatically lifting squeegee and narrower or wider cleaning swaths. [The GSA price for Model 2 is \$5,339.00 and for Model 3 is \$5,272.00.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	45	35	64	1,028 lb	1:	120	1	8	60	NO	--
		CM:	114	89	163	467 kg	2:	--	--	--	DEPENDENT:	YES	--
M2700	3540	Sealer, Heat, Plastic Bag, w/Motor, Portable	C C C C --	--	A	--	--	--	--	--	--	--	--
Portable plastic bag heat sealing machine. Heavy duty portable sealer, motor driven with foot switch, 16 inches long clamping jaw minimum, 1/8 inch (2mm) wide heat seal, grounding plug and 3-wire electrical cable. Equipped with low voltage impulse generator with electronic timer. For making air and water-tight seals on plastic bags.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	38	26	18	90 lb	1:	120	1	8	60	NO	--
		CM:	97	66	46	41 kg	2:	--	--	--	DEPENDENT:	NO	--
M3005	6530	Bassinet, w/Cart	C C C C --	--	--	--	--	--	--	--	--	--	--
Bassinet with cart. The cart shall be stainless steel construction and be mounted on 3" ball bearing rubber casters. The bassinet shall be clear plastic. Designed for use with infants. Cart may include shelves and drawers.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	40	28	31	72 lb	1:	--	--	--	--	NO	--
		CM:	102	71	79	33 kg	2:	--	--	--	DEPENDENT:	NO	--
M3010	6530	Bed, Air-Fluidized	C C C C --	--	A	--	--	--	--	--	--	--	--
Air fluidized bed consisting of a rectangular tank that contains millions of tiny soda lime glass beads (microspheres). An air compressor forces air up through the beads and a woven filter sheet. The beads' and filter sheet's resistance to the air flow creates an air dam which suspends the patient and better spreads the pressure from the patient's weight across the patient's body. The bed also features a rubber bumper guard around the tank, hand and foot operated fluidization switches, a fluidization control valve to regulate the pressure entering the tank, a main control panel with shut-off and alarm heating and cooling circuits and a digital temperature display. Used for patients who have spinal cord injuries, burns, skin grafts or open fractures. Due to the intensive service requirements for this bed, it is usually a leased (rather than purchased) piece of equipment. [No other source(s) identified with this description/specification. This type of equipment is normally made available through lease agreement. The purchase of the equipment usually requires an annual service contract.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	35	35	87	1,630 lb	1:	120	1	10	60	NO	--
		CM:	89	89	221	738 kg	2:	--	--	--	DEPENDENT:	YES	--

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
M3020	6530	Frame, Bed, Overhead, Balkan	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--			
Balkan overhead bed frame. Consists of steel or aluminum tubing with securing clamps. Designed for traction applications on orthopedic patients in retractable beds. Exact configurations, dimensions and catalog ordering numbers depend on the bed to which the frame is attached. Unit is adjustable and may include pulleys. Crib size units and side arm units are also available. [Frame design/ configuration is based on a particular manufacturer's bed. No other source(s) could be located that meet this description.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	48	36	96	50 lb	1:	--	--	--	0		NO							
		CM:	122	91	244	23 kg	2:	--	--	--	NO		NO							
M3025	6530	Mattress, Pressure Reduction	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--			
Pressure reduction mattress. Consists of polyurethane foam and air or gel cylinders to spread pressure of patient's body weight across a larger surface area. Some models have electric pumps for inflation and pressure adjustment; other manufacturers score the foam to distribute pressure. Used to prevent bed sores from developing and promote the healing of ulcers. Unit also relieves patient stress by reducing the amount of required patient turning. All-gel and all-foam mattresses as well as comparably therapeutic low air loss mattress systems are available. [Price difference verified.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	7	36	84	47 lb	1:	--	--	--	0		NO							
		CM:	18	91	213	22 kg	2:	--	--	--	NO		NO							
M3055	6530	Cart, Plaster	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--			
Plaster cart built from stainless steel. Includes a large storage capacity area with disposable buckets, waste basket and bucket liners and three sizes of drawers. Unit is designed to hold all equipment and supplies needed to apply and remove casts.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	45	45	29	150 lb	1:	--	--	--	--		NO							
		CM:	114	114	74	68 kg	2:	--	--	--	NO		NO							
M3065	6530	Cart, Traction Appliances, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--			
Mobile traction appliances cart. Unit consists of two pegboards, four storage drawers, trays below each pegboard, two fixed and two swivel casters. Designed to transport a variety of types and lengths of Balkan frame parts to the patient's bedside. [No other source(s) identified with this description/specification.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	48	75	29	180 lb	1:	--	--	--	--		NO							
		CM:	122	191	74	82 kg	2:	--	--	--	NO		NO							
M3070	7240	Hamper, Linen, Mobile, w/Lid	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--			
Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	35	26	26	20 lb	1:	--	--	--	--		NO							
		CM:	89	66	66	9 kg	2:	--	--	--	NO		NO							
M3072	7240	Frame, Infectious Waste Bag w/Lid	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--			
Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation. [Database pricing is for a unit that holds 25" trash bags. Model 2 has a plastic lid while other two models have SS lids.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	35	26	22	25 lb	1:	--	--	--	0		NO							
		CM:	89	66	56	12 kg	2:	--	--	--	NO		NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M3075	6530	Cabinet, Exam Room, 1 Door, 1 Drawer	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Stainless steel floor cabinet for instrument and supply storage in an examination room. Unit has a door, a drawer and one adjustable shelf. Cabinet top may have to be ordered as a separate item from some manufacturers.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			36	19	22	95 lb	1:	--	--	--	NO	NO	--					
			91	48	56	44 kg	2:	--	--	--	NO	NO	--					
M3080	6530-00-702-7000	Cabinet, Instrument, CRS, 2 Glass Door, 6 Shelf	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Non-magnetic stainless steel instrument cabinet with two glass doors and six shelves. Cabinet body has a single storage compartment and seamless welded face. Shelf heights are adjustable on full length perforated strips mounted to the back and inside front cabinet corners. Cabinet is mounted on glides or casters. Cabinet may be covered by a sloping top. [Price difference verified. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			80	36	16	330 lb	1:	--	--	--	NO	NO	--					
			203	91	41	150 kg	2:	--	--	--	NO	NO	--					
M3085	6530-00-702-9000	Cabinet, Instrument	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Type 304 stainless steel, chrome or painted steel instrument cabinet. Cabinet has separated upper and lower storage compartments, seamless welded face and doubled front edges. The upper compartment has glass shelves and glass paneled door with lock. The lower compartment contains two stainless steel removable shelves and a double walled door. Used for instrument storage.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			67	32	17	375 lb	1:	--	--	--	NO	NO	--					
			170	81	43	170 kg	2:	--	--	--	NO	NO	--					
M3090	6520	Cabinet, Treatment, 2 Door, 2 Drawer, Single Shelf	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Single shelf, two compartment, treatment cabinet. Heavy construction with two drawers and storage area with removable shelf in the compartment. Laminated moisture-proof working surface. Unit is mounted on casters or adjustable leveling glides. Used in laboratories, exam and procedure rooms.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			36	27	18	100 lb	1:	--	--	--	NO	NO	--					
			91	69	46	46 kg	2:	--	--	--	NO	NO	--					
M3105	6530	Cabinet, Warming, F/S, 1 Heated Compartment, Elect	A	A	A	A	--	--	--	--	F	--	--	--	--	--	--	--
Freestanding, single or double door warming cabinet with 1 compartment. Compartment and exterior walls are made of stainless steel. Thick fiberglass insulation maintains the interior temperature and prevents the exterior surface from becoming too hot. Equipped with a sealing door, thermostatic temperature control, status display, heat indicating light, over temperature protection, alarms and an air circulating fan. Unit may have an optional temperature recorder. Manufacturer recommends using a fused disconnect switch in the electrical power circuit. Cabinet may also be installed in a recess. Designed for heating and storing of solutions and blankets used in patient care areas.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			38	30	27	260 lb	1:	120	1	16	NO	NO	--					
			97	76	69	118 kg	2:	--	--	--	YES	YES	--					
M3108	6515	Electrosurgical Unit, Mobile, Unblended	C	C	C	C	--	--	--	--	A	--	--	--	--	--	--	--
Mobile electrosurgical apparatus, unblended current, console unit with hand control plugs, audible tones, pilot lights, coagulating fulgurating current and four other specialized cutting currents: tube cutting, spark-gap cutting with moderate hemostasis, marked hemostasis, and maximum hemostasis. Used to destroy tissue through a high-frequency electrical current and to control bleeding by causing coagulation at the surgical site and to provide a combination of cutting and hemostasis.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			40	25	18	100 lb	1:	120	1	12	NO	NO	--					
			102	64	46	46 kg	2:	--	--	--	YES	YES	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M3110	6530	Cabinet, Warming, F/S, 2 Heated Compartment, Elect	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	
		Freestanding, single or double door warming cabinet with 2 heated compartments. Compartment and exterior walls are made from stainless steel. Thick fiberglass insulation maintains the interior temperature and keeps the exterior from becoming too hot. Equipped with a sealing door, thermostatic temperature control, status display, heat indicating light, over temperature protection, alarms and an air circulating fan. Unit may have an optional temperature recorder. Manufacturer recommends using a fused disconnect switch in the electrical power circuit. Cabinet may also be installed in a recess. Designed for heating and storing solutions and blankets used in patient care areas.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	75	190	27	400 lb 182 kg	1:	120	1	14	60	NO	YES	1,850				
		EA	30	76	69		2:	--	--	--								
M3140	6530	Nourishment Station, Freestanding	A	A	A	A	--	D	D	--	--	--	--	--	--	--		
		Free standing nourishment station approximately 80"H x 84"W x 28"D, constructed of type 304 stainless steel. The unit includes an ice maker and dispenser, a removable microwave oven, a countertop, a built-in instant hot water heater, an automatic coffee maker, upper and lower storage areas, drawers and a built-in self-defrosting refrigerator/freezer. For the storage and preparation of food for supplementary patient feeding. [Model M-84-NSF requires a 1/2" (13mm) IPS hot water supply, a 1/2" (13mm) IPS cold water supply, a second 1/4" (6mm) IPS cold water supply and a 1-1/2" (38mm) OD drain.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	83	211	34	1,300 lb 591 kg	1:	208	3	45	60	NO	YES	--				
		EA	84	213	86		2:	120	1	5								
M3150	6530	Distribution System, Medication, Automatic	C	C	C	C	--	B	A	--	--	--	--	--	--			
		An automated dispensing system that provides controlled dispensing, inventory and security. Size and cost will vary dependent on number of modules selected. [JSN is established as a placeholder. The three sources are shown to provide alternative sources. Price varies significantly based on system design and Manufacturer/Supplier.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	--	--	--	-- lb -- kg	1:	--	--	--	--	NO	NO	--				
		EA	--	--	--		2:	--	--	--								
M3160	6530	Cabinet, Storage, Hanging Scopes	C	C	C	C	--	--	--	--	--	--	--	--	--			
		Scope hanging cabinet. Cabinet has the capacity to hold up to nine scopes. It has roll top closure and optional storage drawer.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	94	239	18	425 lb 193 kg	1:	--	--	--	--	NO	NO	--				
		EA	41	104	46		2:	--	--	--								
M3165	6530	Cabinet, Catheter Storage	C	C	C	.	--	--	--	--	--	--	--	--	--			
		A cabinet to be used for the hanging storage of catheters. Cabinet comes with adjustable laminate shelves, slide-out arms equipped with hangers to hold various size catheters, and doors. Door locks are an optional accessory.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	84	213	21	240 lb 109 kg	1:	--	--	--	0	NO	NO	--				
		EA	32	81	53		2:	--	--	--								
M3175	6515	Electrosurgical Unit, Dual Output	C	C	C	C	--	--	A	--	--	--	--	--	--			
		Dual output electrosurgical unit. Solid state power source with foot switch jacks, monopolar and bipolar outputs, and four independent modes of operation. Maximum power rating of 140 watts. Used in the operating room or surgicenter as an alternative to the scalpel for cutting tissue.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	6	15	16	34 lb 16 kg	1:	120	1	10	60	NO	NO	--				
		EA	19	48	41		2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES														
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6			
M3185	6515	Electrosurgical Unit, Monopolar, Wall Mounted	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--			
		Wall mounted monopolar electrosurgical unit. It has a wall mounted hyfrecator. Unit features solid-state transistorized circuitry, dual power output, output dial with timer control, bipolar forceps, and isolated bipolar output. Unit has a monopolar mode where the current passes through an active cable and active electrode to the patient and back to the generator through a return electrode. It can be table mounted and is designed for routine applications in dermatology, gynecology, proctology, dentistry, podiatry and other clinical areas. Wall mounting bracket not included in system size.																			
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	
						7	11	8	10 lb	1:	120	1	2								
						18	28	20	5 kg	2:	--	--	--								
M3195	6515	Coagulator, Infrared	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--			
		Coagulation system which uses infrared light for treating hemorrhoid, ENT and dermatological conditions. The coagulator's probes transmit infrared light from the generator to the treatment site. The probes' lengths and tip materials are designed for specific applications.																			
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	
						12	8	12	4 lb	1:	120	1	2								
						30	20	30	2 kg	2:	--	--	--								
M4000	6530	Lift, Cadaver	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--			
		Cadaver lift. Unit consists of a hydraulic lift with a stainless steel pallet. The pallet is equipped with 10 electro galvanized case hardened roller bearings to receive body tray. Unit is battery operated and has a built-in 120 V recharger. Lifting capacity is 1500 pounds. Units are available in various lift heights with variable lifting and lowering speeds. Designed to move cadavers from the transport cart to the refrigerator.																			
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	
						106	78	55	2,000 lb	1:	120	1	15								
						269	198	140	908 kg	2:	--	--	--								
M4005	6670	Scale, In-Bed, 400 Pound Capacity	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--			
		In-bed scale. Unit has a 1000 pound total capacity; 400 pound capacity for patient and 600 pound capacity for the bed. Unit consists of four individual load cell pods that can be placed under bed wheels, chair or crib. It has a computerized control with digital LED display. Scale is designed for weighing critically ill patients in bed. [Cardinal/Detecto Scale Company (Cage Code 009P6) has discontinued this line of scales. No replacement model was offered. No other source(s) identified with this description/specification.]																			
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	
						2	5	7	50 lb	1:	110	--	--								
						5	13	18	23 kg	2:	--	--	--								
M4010	6670	Scale, Infant, 0-35 Pounds	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--			
		Infant scale. 35 pound capacity. Unit consists of a removable acrylic cradle with built-in tape measure. Weighs in pounds and ounces or kilograms and grams, and it has an automatic weight lock, automatic averaging, zeroing and re-weight feature with tare function. Used to weigh newborns and infants. [Price variance verified. Units all operate from DC or AC Adapter.]																			
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	
						10	18	16	26 lb	1:	120	1	1								
						25	46	41	12 kg	2:	--	--	--								
M4015	6530	Scale, Infant, for Incubator	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--			
		Infant scale. Unit comes with a stainless steel platform. It is battery operated and equipped with low battery indicator. It has a self-contained digital LED display with automatic shutoff; accuracy to 1 gram. Unit is designed for daily/serial weighing of infants in incubators and cradle warmers. [No other source(s) identified with this description/specification]																			
		UNIT OF ISSUE:	EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	
						3	24	14	5 lb	1:	120	1	1								
						8	61	36	3 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M4020	7100	Scale, Person Weighing, High Capacity	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
High capacity, person weighing scale. Large digital readout displays weight in pounds, or kilograms. Hand rails. Shall be supported by fixed heavy-duty legs in stationary position. Capacity up to 800 pounds. Optional equipment: battery pack with rechargeable batteries and built-in recharger. Designed to weigh large ambulatory patients.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	36	32	34	166 lb	1:	--	--	0	NO								
		CM:	91	81	86	76 kg	2:	--	--	NO	DEPENDENT:								
M4025	6530	Scale, Roll On, Freestanding, 2000 Pound Capacity	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Freestanding roll on scale with a 2000 pound capacity. Unit consists of a heavy duty anodized aluminum platform with powered digital readout. For use in food service or the laundry.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	4	60	60	120 lb	1:	120	1	60	NO								
		CM:	10	152	152	55 kg	2:	--	--	YES	DEPENDENT:								
M4030	6670	Scale, Sit/Stand	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Sit/stand scale. Weighing capacity up to 800 pounds. Consists of a removable ramp, electronic load cells, oversized platform mounted on heavy duty wheels, handrail and weighing mechanisms with a LED display. Designed for wheelchair weighing.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	2	26	30	140 lb	1:	--	1	--	NO								
		CM:	5	66	76	63 kg	2:	--	--	NO	DEPENDENT:								
M4035	6670	Scale, Sling Type, Digital Read-Out	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Sling type scale with digital read-out. Scale is used to weigh patients by lifting the patient from the bed on the scale's sling using a hydraulic lift that is built into the scales U shaped base. Weighing capacity up to 400 pounds. Base is on 3" casters and may be rolled beneath the bed when weighing the patient. Read-out device is battery powered. [Power source: Batteries (DC)]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	65	26	60	140 lb	1:	--	--	0	NO								
		CM:	165	66	152	64 kg	2:	--	--	NO	DEPENDENT:								
M4040	6670-00-788-9000	Scale, Weighing, 300 Pound Capacity	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Person weighing scale with 300 pound capacity. Unit consists of a rugged base frame of 3/32" thick steel with a non-slip surface and a speedometer dial with ultra sensitive registering mechanisms. Scale is designed for medical use.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	36	12	15	18 lb	1:	--	--	--	NO								
		CM:	91	30	38	9 kg	2:	--	--	NO	DEPENDENT:								
M4100	6520	Sphygmomanometer, Aneroid, Wall Mounted	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	8	8	6	5 lb	1:	--	--	--	NO								
		CM:	20	20	15	3 kg	2:	--	--	NO	DEPENDENT:								
M4116	6515	Monitor, Vital Signs	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Electronic sphygmomanometer. LCD displays blood pressure, pulse and temp. This is a change for JSN M4105 from the old hand held BP cuff run on battery to the vital signs monitor used in check-in areas of hospitals and clinics.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:									
EA		IN:	10	11	9	13 lb	1:	120	1	60	NO								
		CM:	25	28	23	6 kg	2:	--	--	NO	DEPENDENT:								

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M4125	5820	Radio Communication System	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--	
Radio equipment to support daily administrative, patient transport, emergency, mass casualty, fire protection and security operations. Includes base station(s), handheld portables, vehicle units, antennas, power supplies, controllers, electrical panels, computers, pagers and other equipment as required. The size, complexity and cost of the system depend on the geographic region covered, dispersment of the facility staff, size and capability of the facility, facility mission and distances to supporting police, fire and disaster relief organizations. [This is an architectural note. The variances between systems are too great to make a reasonable assumption about size, cost or electrical requirements. Compatibility with post or base radio systems, i.e., police, fire or other emergency system must also be considered. Recommend this JSN be maintained as a placeholder for systems unique to each project.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
SY		IN:	--	--	--	-- lb	1:	--	--	--	0	NO	--						
		CM:	--	--	--	-- kg	2:	--	--	--	DEPENDENT:	NO	--						
M4200	6515	Otoscope/Ophthalmoscope, Wall Mounted	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms. [No other source(s) identified with this description/specification]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	4	10	4	5 lb	1:	115	1	1	60	NO	--						
		CM:	10	25	10	3 kg	2:	--	--	--	DEPENDENT:	NO	--						
M4245	6511-50-147-2324	Infuser, Rapid, Blood	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
A fluid management system used for the rapid infusion of warm fluids. The infuser is pole mounted and includes side poles for pressure infusers, syringe or infusion pumps. [Price difference verified.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	48	14	10	26 lb	1:	120	1	15	60	NO	--						
		CM:	122	36	25	12 kg	2:	--	--	--	DEPENDENT:	YES	--						
M4250	6530	Pump, Syringe, Infusion	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
The infusion syringe pump ensures highly accurate volume delivery and consistent flow for small volumes (<50 ml) of pharmacologic agents or thick feeding solutions. It shall be small, lightweight construction, making it transportable. Shall have menu-driven programming capable of flow rates (e.g. 0.1 or 1.0 mL/hr) that are intended for long-term bedside use and/or critical care patient transport, plunger positioning sensor, LCD display for easy viewing, volume limit programming to serve as a convenient cue of volume or dose delivery completion and multiple delivery modes for all applications requiring precisely controlled infusion rates. The infusion pump shall have automatic syringe size sensing which will give the flexibility to accept a wide range of syringe sizes (up to 60 mL) from different manufacturers. Shall be battery powered/AC adapter. [Price of Model 2 verified. The dimensions For Model 1 are 11" wide by 6" high. For the other two models they are basically 6" wide by 10" high.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	10	11	6	4 lb	1:	120	1	1	60	NO	--						
		CM:	25	28	15	2 kg	2:	--	--	--	DEPENDENT:	NO	--						
M4255	6530	Stand, IV, Adjustable	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	108	18	18	30 lb	1:	--	--	--	--	NO	--						
		CM:	274	46	46	14 kg	2:	--	--	--	DEPENDENT:	NO	--						
M4260	6515	Controller, Flow, Infusion, 5-60 DPM	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Flow infusion controller. Controller is self-regulating with automatic sensor and adjustable rate from 5 to 60 drops per minute. Equipped with visual/audible alarms and a 10 hour capacity battery. For the administration of routine gravity infusions such as IV antibiotics, vitamins and electrolyte solutions.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	11	10	7	12 lb	1:	120	1	2	60	NO	--						
		CM:	28	25	18	6 kg	2:	--	--	--	DEPENDENT:	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M4265	6515	Pump, Volumetric, Infusion, Single Line	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
<p>Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Unit is equipped with audible and visual alarms. The battery is rated for 5 hours at 125 ml/hr minimal. Pump is used for the administration of a wide variety of therapeutic agents where precise control is required.</p>																			
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			IN:	12	10	8	12 lb	1:	120	1	--	60	YES	--					
			CM:	30	25	20	6 kg	2:	--	--	--	NO	--						
M4266	6515	Pump, Volumetric, Infusion, Multiple Line	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
<p>Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.</p>																			
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			IN:	13	13	11	18 lb	1:	120	1	1	60	NO	--					
			CM:	33	33	28	9 kg	2:	--	--	--	YES	--						
M4270	6515	Pump, Enteral Feeding	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
<p>Enteral feeding pump that is self-regulating, with automatic sensor, and adjustable rate. Equipped with visual and audio alarms. Used for feeding patients via a naso gastric tube.</p>																			
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			IN:	8	8	6	6 lb	1:	120	1	1	60	NO	--					
			CM:	20	20	15	3 kg	2:	--	--	--	NO	--						
M4275	6515	Pump, Continuous, Analgesia (PCA)	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
<p>Continuous analgesia pump. Also known as a PCA or patient controlled analgesia pump. The unit provides a controlled, continuous or as required (PRN) dose of analgesia medications for postoperative patients. The patient can control administration of the prescribed drug up to a preset rate. The unit can be mounted to an IV pole and/or be small enough to be carried in a pouch. Use of this device speeds patient ambulation and reduces the length of hospital stays. Depending on the manufacturer, electrical requirements refer to either the unit itself or the battery recharging unit. [No other source(s) identified with this description/specification]</p>																			
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			IN:	5	12	12	12 lb	1:	120	1	1	60	NO	--					
			CM:	12	31	31	6 kg	2:	--	--	--	YES	--						
M4280	6515	Pump, Pneumatic Stocking/Cuff	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
<p>Pneumatic stocking/cuff pump. Pump provides alternating pressure to pneumatic stockings for reduction of the threat of deep vein thrombophlebitis in post operative patients. May also be used in the CCU for rotating cuff therapy for reduction of peripheral circulation in congestive heart failure patients.</p>																			
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			IN:	6	8	15	12 lb	1:	120	1	1	60	NO	--					
			CM:	15	20	38	6 kg	2:	--	--	--	YES	--						
M4285	6515	Pump, Pneumatic Tourniquet	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
<p>Tourniquet, pneumatic. Pump provides pressure to pneumatic tourniquet. Designed for use in the operating or emergency room. [Price difference verified. Model 1 is electric. Model 2 uses compressed air and does not require electric support. Electric models are also available. Both models include stand and basket. Dimensions are for pump only. No other source (s) identified.]</p>																			
UNIT OF ISSUE:		EA	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:						
			IN:	12	10	8	10 lb	1:	120	1	2	60	NO	--					
			CM:	30	25	20	5 kg	2:	--	--	--	YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M4650	6530	Stretcher, Transport, Cadaver	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Cadaver transport stretcher. All stainless steel tubular frame with durable welded construction. Unit is equipped with lifting mechanism and tray. It is mounted on four 8" rubber casters with locks and includes a white nylon cover. Unit is designed for the concealed transportation of cadavers.																		
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
			39	99	39	26	82	320 lb	1:	--	--	--	NO	NO	--			
								146 kg	2:	--	--	--	NO	NO	--			
M4655	6530	Stretcher, Mobile, CRS, 9 Position	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 10" conductive casters. Designed for patient transport as well as for minor surgical procedures.																		
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
			36	91	36	35	84	228 lb	1:	--	--	--	NO	NO	--			
								103 kg	2:	--	--	--	NO	NO	--			
M4656	6530	Stretcher, Mobile, CRS, Tapered Head Section	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Mobile stretcher. Item corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 10" conductive casters. It is designed for patient transport and minor surgical procedures of the head and neck. Head section is narrowed to permit better access to the head and neck. It is frequently used in oral surgery, ENT and ophthalmology.																		
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
			32	81	32	30	77	228 lb	1:	--	--	--	NO	NO	--			
								103 kg	2:	--	--	--	NO	NO	--			
M4657	6530	Tabletop, Decontamination	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Hazmat tabletop decontamination tray that fits on any standard hospital gurney or stretcher. The tray shall be light-weight and impermeable, washable and reusable. It shall include two waste water containers/reservoirs; flexible drain hose; adjustable locking straps and spray nozzle. Used for emergency medical treatment and decontamination of a contaminated/injured patient. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
			103	262	103	33	8	55 lb	1:	--	--	--	NO	NO	--			
								25 kg	2:	--	--	--	NO	NO	--			
M4660	6530	Stretcher, Recovery, Labor	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Labor recovery/ob-gyn procedure stretcher. The unit's height is adjustable and the patient bed has a manual backrest and crank operated knee gatch. The stretcher has 10" non-conductive carpet wheels, IV stand and folding chrome side-rails. The stretcher can be converted quickly to a birthing stretcher by removing the leg and foot section of the mattress. The available accessories include x-ray cassette holders, proctology boards, IV poles, fluid basins.																		
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
			38	97	38	36	88	300 lb	1:	--	--	--	NO	NO	--			
								137 kg	2:	--	--	--	NO	NO	--			
M4665	6530	Stretcher, Recovery, Surgical	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Recovery/surgical stretcher. Strong I-beam construction type unit. The height is adjustable with manual backrest and crank operated knee gatch. Stainless or painted steel top and chassis. Features 8" or 10" conductive casters, with lock and brake, folding, tuck-away chrome side-rails and IV stand and a flame retardant antibacterial mattress. Designed for operating room transport or recovery applications.																		
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:			
			36	91	36	36	84	276 lb	1:	--	--	--	NO	NO	--			
								126 kg	2:	--	--	--	NO	NO	--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M4670	6530	Tray, Body, Fiberglass or Plastic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Fiberglass or heavy duty plastic body tray for the storage and movement of bodies in the morgue. The tray is designed to withstand the effects of some of the reagents used in autopsies and pathological examinations better than stainless steel. The foot end of the tray has a drain hole and stopper. Some models offer optional x-ray cassette slide racks. [Price difference verified.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	5	31	82	75 lb	1:	--	--	--	NO	--							
			13	79	208	34 kg	2:	--	--	--	NO	--							
M4671	6530	Rack, Mortuary, Mobile, Four Tray	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Mobile mortuary rack to store or move four body trays. Unit is constructed of stainless steel and has heavy duty casters or rubber tires. The rack can be either an end loading or a front loading cantilever style. Each body tray rests on a set of roller bearings or two or more cantilever arms. Other rack configurations are available. The database pricing does not include the trays. The database physical dimensions, though, include enough room for trays to be placed on the rack. [Price variance verified.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	88	78	37	350 lb	1:	--	--	--	NO	--							
			224	198	94	159 kg	2:	--	--	--	NO	--							
M4705	6530	Wheelchair, Patient Transport, Folding	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Folding patient transport wheelchair. Constructed of chrome plated steel with detachable armrest and footrests. Unit has heavy duty front casters with sealed radial high-precision ball bearing assembly. Unit is used for patient transport.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	36	26	42	54 lb	1:	--	--	--	NO	--							
			91	66	106	24 kg	2:	--	--	--	NO	--							
M4800	6640	Urodynamic Measurement System w/Video	C	C	C	C	--	--	--	--	A	--	--	--	--	--	--	--	
Urodynamic measurement system. Unit consists of uroflowmeter to measure urinary flow, urethral pressure profilometer to measure urethral pressure, gas or liquid cystometer to measure bladder capacity and response, and electromyographic recording to measure sphincter and other muscle activity. It includes a 19" video monitor and recorder, a microprocessor, foot switch, thermal printer, and automatic calibration. System is designed to evaluate the storage and transportation of urine in the urinary tract and the cause of abnormal voiding (urination). [Numerous configurations are available from these manufacturers/suppliers.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	68	25	27	550 lb	1:	120	1	15	60	NO	--						
			173	64	69	250 kg	2:	--	--	--	YES	--							
M4801	6530	Commode Chair	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Commode Chair to be used in Urodynamics testing. Aluminum frame with plastic seat and funnel attached. Chair to be used in urodynamic testing. Free-standing adjustable heightf approximately 27" to 31". Aluminum frame with arm rests, plastic seat and funnel. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	31	20	20	15 lb	1:	--	--	--	0	NO	--						
			79	51	51	7 kg	2:	--	--	--	NO	--							
M4805	6515	Lithotripter, Ultrasound	C	C	C	C	--	--	--	--	A	--	--	--	--	--	--	--	
Percutaneous Lithotripter. Unit is a rigid tubular instrument that consists of an operating sheath, nephroscope or ureterorenoscope, and ultrasonic Lithotripter probe. A suction pump is connected to the nephroscope and serves as an outflow channel for fluids in the surgical field. Ultrasonic Lithotripters are used in a percutaneous or transurethral approach to urinary or renal calculi.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	8	12	8	15 lb	1:	120	1	10	60	NO	--						
			20	30	20	7 kg	2:	--	--	--	YES	--							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M4810	6530-00-027-00	Heart/Lung Machine, Bypass, Modular	C	C	C	C	--	--	A	G	--	--	--	--	--	--	--	--
Modular by-pass heart lung machine. Unit consists of an arterial pump, a backup arterial pump, one or two suction pumps, a water mixer, and a backup battery pack. To include disposable components: oxygenator/heater exchanger, cardiotomy reservoir, blood filters, and tubing. Unit is designed to temporarily replace the function of the patients heart and lungs during open-heart surgery or any surgical procedure that requires isolation of the heart. [Price for Model 1 can range from \$70K to \$120K depending on accessories selected.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	43	45	30	350 lb	1:	120	1	20	NO		--					
		CM:	109	114	75	159 kg	2:	--	--	--	YES		--					
M4811	6525	Pump, Intra-Aortic, Balloon	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Intra-aortic balloon pump. Item is used to treat cardiogenic shock resulting from extensive myocardial injury or damage. The pump shall function from line or battery power and is to be a mobile unit. It contains physiological monitoring, pacing, and pumping capabilities. It requires minimal set-up time and has immediate pumping capability. Adjustments can be accomplished without interruption of pumping. The monitor can be mounted remotely for the clinicians convenience and permits viewing of both cardio-pulmonary bypass and intra-aortic balloon pump simultaneously. The pump is designed for use in the critical care unit, operating room, cardiac cath lab and during transport. [No other source(s) identified with this description/specification. Bard and Cardiac-Assist-Div and Belmont have been incorporated into Arrow International.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	56	13	25	156 lb	1:	120	1	4	NO		--					
		CM:	142	33	64	71 kg	2:	--	--	--	NO		--					
M4815	6530	Hypo/Hyperthermia Unit, Automatic/Manual, Mobile	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Automatic/manual hypo/hyperthermia unit. Sealed refrigeration system. Microprocessor controlled with multiple alarm system constantly monitoring temperature and water levels. Cabinet type unit. Designed to regulate body temperature by application of water-filled hypothermia blankets. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	37	17	19	131 lb	1:	120	1	12	NO		--					
		CM:	94	43	48	60 kg	2:	--	--	--	YES		--					
M4816	6530	Warming Unit, Patient, Automatic/Manual, Air	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Automatic/manual patient warming unit. Unit delivers a flow of warmed air through a perforated plastic blanket. Used primarily for postoperative patients to speed recovery of normal body temperature.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	15	16	11	15 lb	1:	120	1	10	NO		--					
		CM:	38	41	28	7 kg	2:	--	--	--	NO		--					
M4820	6515	Hemodialysis Unit, Mbl, w/Reverse Osmosis System	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Mobile renal dialysis system with a reverse osmosis water purification unit. The system consists of three major components: the dialysate delivery system, the extracorporeal blood delivery circuit (blood pump) and the dialyzer. The system also has its own monitoring and control circuits with temperature controls. An alarm system is automatically activated when there is changes in pressure or in the existence of leaks. Multiple electrical circuits (one for the dialyzer, one for the reverse osmosis system) may be needed to power this equipment combination. This dialyzer is intended for self-contained use in intensive care or step down units which do not have the water purification machinery found in a hemodialysis clinic. See JSN M1715 for units used in a hemodialysis clinic.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	54	26	30	200 lb	1:	120	1	15	NO		--					
		CM:	137	66	76	91 kg	2:	--	--	--	YES		--					
M4825	6530	Cryosurgical Unit, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	G
Mobile cryosurgical unit. Cabinet mounted control unit, equipped with gas cylinder storage, foot switch, temperature gauge and timer. Includes an integral pressure regulator, and choice of two gases. Cylinder size: 20 pound capacity. Unit includes 2 tips. [All models use either N2O or CO2 which must be specified at time of order.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	40	15	14	30 lb	1:	--	--	--	NO		--					
		CM:	102	38	36	14 kg	2:	--	--	--	NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M4830	6515	Drill, Surgical, Air Drive	C	C	C	C	--	--	--	D	B	--	--					
Sterile air or nitrogen operated air drive drill. Drill and reamer are constructed of stainless steel. Includes bone screw sets. Used for large bone surgery. Requires operating pressure of 120 pi. [Price variance verified. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	8	12	3	5 lb	1:	--	--	--	NO		--					
		CM:	20	30	8	3 kg	2:	--	--	--	NO		--					
M4831	6515	Drill, Surgical, Electric Drive	C	C	C	C	--	--	A	--	--	--	--					
Electrically powered surgical drill system. Stainless steel construction of drill and reamers. May include a variety of reciprocating and rotary saw and drill heads. System may be battery powered. [Price variance verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	4	12	9	30 lb	1:	120	1	2	NO		--					
		CM:	10	30	23	14 kg	2:	--	--	--	YES		--					
M4835	6515	Cutter, Cast, w/Vacuum	C	C	C	C	--	--	A	--	--	--	--					
Vacuum cast cutter. Item has 2 HP motor and is enclosed in wheeled canister. It is equipped with built-in standpipe and handle, large bag, extractor hose, and 25 foot power cord. Item is designed for orthopedic use. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	16	--	12	14 lb	1:	115	1	3	NO		--					
		CM:	41	--	30	6 kg	2:	--	--	--	YES		--					
M4840	6530	ENT Unit, w/Air, Electric Power, Suction, Pressure	C	C	C	C	--	--	A	H	--	--	--					
Mobile ENT unit. Unit has air and electrical panels and integral suction and pressure system. Unit houses a control panel with functions selector, pressure regulator, pressure gauge and electrical outlets. It is equipped with foot-controlled vacuum and pressure plus a storage area.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	44	31	18	225 lb	1:	120	1	6	NO		--					
		CM:	112	79	45	103 kg	2:	--	--	--	NO		--					
M4850	6530	Flushing Unit, Renal Dialysis Cartridge	C	C	C	C	--	E	A	--	--	--	E					
Used for removing disinfectant or storage solution from renal dialysis cartridges prior to patient use. The manufacturer recommends a dedicated 20 amp ground fault interrupt protected circuit for this equipment. See manufacturer's pre-installation checklist for ventilation requirements. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	49	26	34	200 lb	1:	120	1	15	NO		--					
		CM:	124	66	86	91 kg	2:	--	--	--	YES		--					
M4860	6515	Peritoneal Dialysis Unit, Hollow	C	C	C	C	--	E	A	--	--	--	--					
Peritoneal dialysis system. Unit contains several pumps operating in sequence to infuse into and remove dialysate fluid from the peritoneal cavity of the patient. The unit contains a solution heater and solution concentration monitors to maintain thermal and electrolyte balances between the patient and dialysate. The unit contains alarms for low or no-flow conditions, overflow, low drain rate and may also have alarms for inconsistent parameter settings and tubing alignment. The display shows all alarms, system settings and a variety of parameters. The unit can be mounted on a table or cart. [No other source (s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	19	16	28 lb	1:	120	1	3	NO		--					
		CM:	25	48	41	13 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M4865	4100	Reprocessor, Renal Dialyzer Cartridge	C	C	C	C	--	E	A	--	--	--	E					
<p>Renal dialyzer disinfection system. Unit is used to flush and disinfect dialyzer cartridges after a hemodialysis session. The unit then refills the cartridge with preservative for storage until reuse by the same patient during a later session. The manufacturer recommends a dedicated 20 amp ground fault interrupt protected power circuit for this equipment. See manufacturer's pre-installation checklist for ventilation requirements. Use JSN M4850 to remove disinfectant from dialyzer cartridge prior to use. [MESA Laboratories (Cage Code #SR187) sells these units separately. Model MM1000 sells for \$8,975.00, and Model RDM sells for \$5750.00. Price difference verified.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			49	124	26	66	34	86	275 lb	120	1	15						
										2:	--	--	--					
M4870	4100	System, Reverse Osmosis, Water, Mobile	C	C	C	C	--	A	A	--	--	--	--					
<p>Mobile reverse osmosis water treatment system for use with portable dialysis stations which may be used in the intensive care or coronary care units. Unit to be connected to hose bib at point of use. Filtration system includes input pressure boost pump in addition to a membrane pressure pump. Backwash of membrane may be manually initiated. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	YES	BTUs / HR:	DEPENDENT:	NO	--	--
			28	71	22	56	22	56	183 lb	120	1	15						
										2:	--	--	--					
M4871	4100	System, Reverse Osmosis, Water	C	C	C	C	--	D	D	--	--	--	--					
<p>Reverse osmosis system to purify water in hemodialysis clinics and other clinical areas. The system consists of a pump, water softener, media and carbon filters, processing unit, ultraviolet sterilizer, final filtration, deionizers, osmosis units, controls and monitors. The system alarms when a malfunction occurs. The system usually requires a room of its own. Refer to the manufacturers specifications for exact installation requirements. Database system weight does not include the water in the piping or holding tanks of an operating system. [System cost is based on a 10,000 gallon per day capacity.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			76	193	40	102	45	114	700 lb	208	3	14						
										2:	120	1	15					
M4880	6515	Telemetry System, ECG, Ambulatory, Multi-Channel	C	C	C	C	--	--	A	--	--	--	--					
<p>Cardiac telemetry system for monitoring multiple ambulatory patients. System consists of portable digital or analog telemetry units, an antenna array, a multi-channel receiver, strip chart recorder(s), a central station signal processor/computer with monitor and the software necessary to run the system. Database pricing reflects a system sufficient to support monitoring eight patients but does not include installation costs (which vary per facility). Electrical characteristics reflect total system requirements through multiple power connections. Physical characteristics refer to the central station unit only; the other components are small or mounted above the ceiling grid. This equipment is often bundled with and bought as part of the direct care patient monitoring system (DCPMS) for a facility (see JSN M7800 series). [Agilent Technologies has sold its Healthcare Solutions Group to Phillips Medical Systems.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			20	244	20	450	18	76	50 lb	120	1	15						
										2:	--	--	--					
M4905	6530	Chair, Dialysis	C	C	C	C	--	--	--	--	--	--	--					
<p>Dialysis chair. Unit consists of a welded steel frame. It has durable stain resistant vinyl upholstery and is mounted on 4 casters. It contains an IV attachment and drainage bag hook. Unit has built-in Trendelenburg positioning. Chair is designed for long term seating comfort during dialysis treatment or any other extended chair treatment. [Depth is for fully reclined chair.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			50	127	35	89	75	190	180 lb	--	--	--						
										2:	--	--	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M4910	6530	Chair, Exam, Vestibular	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Vestibular examination chair. Base provides adjustable seat heights. Unit features a fully adjustable headrest with armrests and can be adjusted to the horizontal position. Unit has removable upholstery sections. [Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	41	27	70	550 lb	1:	120	1	12	NO		--					
		CM:	104	69	178	250 kg	2:	--	--	--	DEPENDENT: NO		--					
M4915	6540	Chair, Exam/Treatment, ENT, w/Adjustable Light	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
ENT exam/treatment chair with adjustable light. Chair can be rotated 330 degrees locking at desired position. Unit is electrically powered for precise positioning and has an adjustable headrest and armrest. It may include an adjustable gooseneck light. Unit is designed for use during examinations, treatments, and minor procedures.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	24	79	350 lb	1:	120	1	12	NO		--					
		CM:	91	61	201	159 kg	2:	--	--	--	DEPENDENT: YES		--					
M4920	6530	Chair, Exam/Treatment, Podiatry, w/Motor	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Podiatry exam/treatment chair. Unit is motor driven and has a foot control with gliding foot rest and debris tray. It may include a shoe tray. Unit is fully adjustable to the desired position. It is designed for podiatric examinations and procedures.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	41	23	79	350 lb	1:	120	1	12	NO		--					
		CM:	104	58	201	159 kg	2:	--	--	--	DEPENDENT: YES		--					
M4925	6530	Chair, Exam/Treatment, With Motor	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Exam/treatment chair with motor. Chair is electrically powered and can be positioned for a wide range of procedures. Unit is mounted on a 24"(approx) iron casting base with foot controls on both sides of the chair. Chair is equipped with footrests and fully adjustable headrest and armrests. It is used in hospitals, clinics, or office settings for examinations, treatments, and minor procedures. [Chairs average approximately 75 inches in length.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	60	25	18	345 lb	1:	120	1	12	NO		--					
		CM:	152	64	46	156 kg	2:	--	--	--	DEPENDENT: YES		--					
M5005	6540	Cabinet, Instrument, Lens Measuring	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Measuring lens and instruments cabinet. Unit features adjustable dividers to accommodate finished lenses and drawers with full width handles for instruments. Used for storage of measuring lenses and other types of ophthalmic instruments. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	59	36	27	500 lb	1:	--	--	--	NO		--					
		CM:	150	91	69	227 kg	2:	--	--	--	DEPENDENT: NO		--					
M5010	6515	Desk, Fitting/Dispensing, Optical	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Fitting/dispensing optical desk. Cabinet section consists of one larger drawer at top with seven small tray drawers below or eight equal drawers. Top surface is made of durable high pressure plastic or wood. Specify cabinet section to be technician's right or left, color and finish. Many types of drawer dividers are available. Unit can be custom configured. [This item presents a more industrial or lab fabrication presentation and may not be suitable for a high visibility clinical setting. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	37	72	30	310 lb	1:	--	--	--	NO		--					
		CM:	94	183	76	141 kg	2:	--	--	--	DEPENDENT: NO		--					
M5015	6540	Desk, Refraction, w/Sink, 33x92x25	A	E	A	A	--	F	F	--	--	--	--	--	--	--	--	--
Refraction desk. This unit has a plastic laminated finish, one tray drawer with full suspension, and three storage electrical drawers with single door. It has a five switch control panel for interior room illumination muscle light, OPH project, lens-o-meter, and option for additional accessories, came with single bowl sink, and gooseneck faucet with wrist blade controls. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. The unit is used during eye examinations in ophthalmic clinics and hospitals. This unit requires special electrical hookup. [No other source(s) identified with this description/specification.]																		

JSN	NSN	NOMENCLATURE	CATEGORY:						UTILITIES						
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	33	92	25	350 lb	120	1	10	60	NO	--		
				84	234	64	159 kg	2:	--	--	--	YES	--		
M5016	6540	Desk, Refraction w/console, w/o Sink	A	E	A	A	--	--	F	--	--	--	--		
		The ophthalmic refraction desk shall be specifically designed to conduct eye examinations in ophthalmic clinics and hospital. It shall have a control console consisting of three rechargeable instrument wells, two 110v auxiliary switches to control accessories, two low voltage switches to control fixation lights, a separate on/off dimmer control for room lights and an indirect ophthalmoscope control with hanger that provides power to the instrument when lifted. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. There shall be a swivel Lamp and a trial lens drawer. [The manufacturer's recommended room wiring instructions must be applied to effectively use the refraction desk console. No other source(s) identified with this description/specification.]													
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
		EA	32	76	29	350 lb	120	1	15	50	NO	--			
			81	193	74	159 kg	2:	--	--	--	NO	--			
M5020	6540	Workbench, Fabrication/Maintenance	C	C	C	C	--	--	--	--	--	--	--		
		Open work table/station approximately 34" H x 60" W x 30" D for general laboratory or ophthalmic laboratory use. The table consists of a steel frame with a stringer between the rear legs, a lower shelf and a laminate top which is resistant to burns and stains. The legs adjust to accommodate both sitting and standing height use. The table's depth varies by manufacturer and other size tables are available. The table is used for maintenance, fabrication and materials processing in laboratories, hospitals and scientific research facilities.													
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
		EA	38	60	30	150 lb	--	--	--	0	NO	--			
			97	152	76	68 kg	2:	--	--	--	YES	--			
M5025	6540-00-962-9964	Table, Instrument, Ophthalmic, Adjustable	C	C	C	C	--	--	A	--	--	--	--		
		Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments. [Model 3 has a motorized height adjustment feature.]													
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
		EA	36	24	18	66 lb	120	1	3	60	NO	--			
			91	61	46	30 kg	2:	--	--	--	NO	--			
M5027	6540	Table, Multiple Instrument, Ophthalmologic, Revolv	C	C	C	C	--	--	A	--	--	--	--		
		Revolving ophthalmic instrument table. This table is designed to hold multiple ophthalmologic instruments with the ability to rotate and position the desired instrument at the patients location. The table top has a power elevation that ranges approximately from 30 to 38 inches and a rotation capability of 360 degrees. The table consists of instrument trays that allow the instruments to be positioned in front of the patient and facilitates complete wheelchair accessibility to all instruments. [No other source(s) identified with this description/specification.]													
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
		EA	30	48	48	565 lb	120	1	10	60	NO	--			
			76	122	122	257 kg	2:	--	--	--	YES	--			
M5030	6530	Stool, Surgeon, Revolving	C	C	C	C	--	--	--	--	--	--	--		
		Revolving stool. Consists of a padded upholstered seat with height adjustment. Unit rotates and is mounted on ball bearing swivel casters. Designed for use in examinations, treatment, and surgical procedures.													
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
		EA	25	24	24	22 lb	--	--	--	--	NO	--			
			64	61	61	10 kg	2:	--	--	--	NO	--			

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M5500	6540	Autorefractor, Ophthalmic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Ophthalmic autorefractor. Unit is a tabletop model consisting of a instant display TV monitor, forehead rest, measuring head, height adjustment ring, and joystick lever. It features an automatic fogging and a high speed printer. Designed for visual acuity screening.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	20	12	21	44 lb	1:	120	1	1	60	NO						
		CM:	50	30	53	20 kg	2:	--	--	--	DEPENDENT:	NO						
M5505	6540	Camera, Fundus, Flash, Automatic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Automatic flash fundus camera. Fluorescent unit with objectives and a device for continuous compensation of astigmatism up to plus 20 diopter. It features continuous adjustable gear controlled tilt mechanism with fixation target, filter wheel to include instrument table with head and chin rest with manual height adjustment, chin pads, and fixation device. It has a connecting cable with clips, extension cables, a 12 volt bulb, cover plate with pin hole, soft plastic cover, double filament bulb 120 volt, 50 watt, eyepiece head, release lever, and Polaroid adapter for fundus camera for black and white Polaroid film only. Unit includes a stand. It is designed for use in diagnosing and recording ocular disorders.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	20	18	18	187 lb	1:	120	1	3	60	NO						
		CM:	52	45	46	85 kg	2:	--	--	--	DEPENDENT:	YES						
M5510	6540	Camera, Fundus, Digital	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
The digital fundus camera system is designed for use in diagnosing and recording ocular disorders. It shall consist of a digital imager, computer, printer, monitor, chin rest, joy stick and software to record, store, edit and print digital images. The system shall include a system table and an adjustable patient table.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	30	48	23	175 lb	1:	120	1	5	60	NO						
		CM:	76	122	58	80 kg	2:	--	--	--	DEPENDENT:	NO						
M5512	6515	Laser, Smoke Evacuator	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Filtration system used in conjunction with laser operations to remove surgical laser plume. The unit includes a pneumatic foot switch, disposable 0.12 micron HEPA primary filters, a secondary 0.12 micron ULPA/carbon filter, disposable funnels, reducer fittings and connector hoses.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	10	13	20	18 lb	1:	110	1	8	60	YES						
		CM:	25	33	51	9 kg	2:	--	--	--	DEPENDENT:	YES						
M5514	6515	Laser, Ophthalmic, Semiconductor Diode	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Ophthalmic treatment laser which uses a semiconductor diode as the source for generating a specific wavelength of light (usually 810 nm) for the treatment beam.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	14	18	16	47 lb	1:	120	1	1	60	NO						
		CM:	36	46	41	22 kg	2:	--	--	--	DEPENDENT:	NO						
M5515	6515	Laser System w/Slit Lamp or Ophthalmoscope	C	C	C	C	--	--	G	--	--	--	--	--	--	--	--	--
Dual delivery ophthalmic laser system. Unit allows rapid switching between two laser delivery systems. The unit includes safety goggles and a slit lamp or an indirect ophthalmoscope, both with high visibility safety filters. [Model 1's system includes an indirect ophthalmoscope. Surgical Laser Technologies' (CAGE 0UH89) system does not include either a slit lamp or an ophthalmoscope but does have the optical laser delivery tube to interface with most slit lamps or ophthalmoscopes. The average cost of a slit lamp (JSN M5530) has been added to this vendor's price to compensate.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:								
EA		IN:	46	18	33	350 lb	1:	220	3	35	60	NO						
		CM:	117	46	84	159 kg	2:	120	1	20	DEPENDENT:	YES						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M5517	6515	Laser, Photocoagulation, Dual Fiber, Ophthalmology	C	C	C	C	--	--	G	--	--	--	--	--	--	--	--	--
		Dual fiber argon laser for ophthalmologic use. Component include: console, interfaces with endoprobe, slit lamp or indirect ophthalmoscope. This unit is used to coagulate abnormal tissue, thereby improving the prognosis of patients with abnormal vascular tissue in the retina. [Model 1 includes a laser link and a laser indirect ophthalmoscope in the price. A slit lamp with chair/table is a \$6,900 option. No other source(s) identified with this description/specification]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 38	14	24	250 lb	1: 208	3	45	60	NO	--						
			CM: 97	36	61	114 kg	2: --	--	--	NO	NO	--						
M5518	6515	Laser, Corneal Surgery	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--
		Excimer laser device used to perform photorefractive keratectomy for the reduction or elimination of myopia (near-sightedness) and hyperopia (farsightedness) with or without astigmatism. The device shall be capable of performing LASIK (laser in-situ Keratomileusis) surgical procedures. [Recommended room size is 12ft by 16ft or larger with a 40 inch entry door.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 60	50	91	1,322 lb	1: 220	1	30	60	NO	3,611						
			CM: 152	127	231	601 kg	2: --	--	--	NO	NO	--						
M5520	6540-00-299-8134	Lensometer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Lensometer. Unit includes lamps, prism measuring lens marking device, cylinder axis wheel calibrated in two 180 degree segments and a green filter for tinted glass. The instrument may be inclined between 25 to 90 degrees. Used for measuring lens.																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 12	7	18	14 lb	1: 120	1	1	60	NO	--						
			CM: 31	17	45	7 kg	2: --	--	--	NO	NO	--						
M5525	6540	Lensometer, Soft Contact	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Soft contact lensometer. Unit features lens holder, external scale, prism holder, prism axis from 0 to 180 degree, external power and axis readings with an American style cross-line target. Used for measuring soft and hard contact lenses as well as conventional spectacle lenses.																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 19	10	18	15 lb	1: 120	1	1	60	NO	--						
			CM: 48	25	46	7 kg	2: --	--	--	NO	NO	--						
M5530	6515-01-032-4518	Lamp, Slit, w/Applanation Tonometer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp with head and chin rest and manual height and focusing adjustments. The instrument features a microscope head with parallel optics that will accept an applanation tonometer. Designed for use in ophthalmology during diagnostic examinations.																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 26	19	16	52 lb	1: 120	1	2	60	NO	--						
			CM: 66	48	40	24 kg	2: --	--	--	NO	NO	--						
M5531	6515	Lamp, Slit, Photographic w/Tonometer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp, with head and chin rest and manual height and focusing adjustments. The instrument also features a microscope head with parallel optics that will accept an applanation tonometer. For use in ophthalmology during diagnostic examinations. Unit to be supplied with appropriate beam splitter, 35 mm camera back, camera interface, enhanced illumination and illumination controls to permit photographs of the visual field to be obtained. Optional video/digital available. [No other source(s) identified with this description/specification.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 22	13	16	46 lb	1: 120	1	3	60	NO	--						
			CM: 56	33	40	21 kg	2: --	--	--	YES	YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M5535	6540-00-042-8380	Ophthalmoscope, Binocular, Indirect	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Binocular indirect ophthalmoscope. Unit consists of headband and crown, halogen quartz lamp, multi-coated aspherical lenses, scleral depressor and mirror. It also includes a control switch that regulates the illumination from 2 to 6 volts. Used to examine presence of blood vessels in patient's pupils.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			7	18	28	4 lb	1:	120	1	--	60	NO	--					
			20	46	1	2 kg	2:	--	--	--	NO	NO	--					
M5536	6540	Ophthalmoscope, Direct	C	.	.	.	--	--	A	--	--	--	--	--	--	--	--	--
The Direct Ophthalmoscope shall be an instrument for examining the back portion of the interior of the eyeball and produces an un-reversed image. The unit shall consist of a head, a rechargeable handle, 3.5 v long-life battery and a case.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			8	2	2	1 lb	1:	--	--	--	--	NO	--					
			20	4	4	1 kg	2:	--	--	--	NO	NO	--					
M5540	6515-00-318-6840	Power Supply, Ophthalmoscope	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Ophthalmoscope power supply. Unit is suitable for charging up to two instruments at once. The LED illuminates when instrument is being charged and controlled charging prevents overcharge. Used to charge diagnostic instruments. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			4	8	3	10 lb	1:	120	1	2	60	NO	--					
			10	20	8	45 kg	2:	--	--	--	NO	NO	--					
M5545	6515-00-353-3200	Ophthalmometer/Keratometer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism. [Manual keratometers will become less available in the future as technology brings ophthalmic instruments into the next generation. Equipment will be multifunctional such as the auto keratometer and refractometer as a single piece of equipment.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			16	7	19	18 lb	1:	120	1	1	60	NO	--					
			41	18	48	9 kg	2:	--	--	--	YES	YES	--					
M5550	6515-01-072-7983	Perimeter	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Perimeter. This is an ophthalmological, spherical projection type unit. It has 50 visual field charts printed on both sides, 50 static perimetry charts and chart holding plates. It has three sets of gray filters for measuring degrees of brightness, holder for ametropia corrective lenses at 30 CM, separate central scotoma plotting device and chin rest pads. Unit requires one 6 volt, 0.5 AMP, incandescent lamp for chart illumination, and one 6 volt, 4.35 AMP, incandescent lamp for base illumination. It measures both kinetic and static perimetry and can be adjusted for size and light intensity. It is provided with spring-balanced table, record charts, dust cover, trial lens holder and chin rest tissues. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			48	36	24	250 lb	1:	120	1	8	60	NO	--					
			122	91	61	114 kg	2:	--	--	--	YES	YES	--					
M5555	6540	Perimeter, Automated	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Automated ophthalmic perimeter. Unit has on screen display for rapid and accurate alignment of patients automatic pupil size measurement, seven different fixation aids, ergonomic chin rest, several threshold strategies, and high target intensity. [Model 3 requires external PC. Price difference verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			32	22	21	32 lb	1:	120	1	15	50/60	YES	--					
			81	56	53	15 kg	2:	--	--	--	NO	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M5560	6515-00-388-3600	Projector, Acuity w/Stand, Wall Mounted Screen	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Acuity test projector. Unit is a chart-projection type on a floor stand with slides and wall mounted screen (13x13 min) for projecting test object and characters. It is designed for use in eye refraction testing procedures. [Models 1 and 3 are manual type projectors. Model 2 can be programmed for up to two programs of 16 charts each. Automated projectors are also available from the manufacturer/vendor of Model 1 and 3.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	NO	NO	NO	NO
			12	8	19	12 lb	1:	120	1	1								
			30	20	48	6 kg	2:	--	--	--								
M5562	6540	Tester, Visual Acuity, Video/Microprocessor Based	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Visual acuity tester using video (television monitor) and microprocessor technology. This equipment replaces the projector chart and projector in an eye examination lane. Wall bracing is required for mounting the unit directly to the wall without support from below. An optional floor stand can also be used. The unit requires an electrical outlet on the far end wall of the examination lane. This differs from standard eye examination room configurations which normally do not have electrical outlets in that wall. Other options include binocular vision and contrast sensitivity testing. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	NO	YES	NO	NO
			17	15	15	38 lb	1:	120	1	2								
			43	38	38	18 kg	2:	--	--	--								
M5565	6540	Radiuscope	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Ophthalmic radiuscope. Unit consists of a fine compound microscope with concentric coarse and fine focusing adjustments. It includes a 6.5 V lamp, monochromatic filter, two lens mount and a built-in variable voltage selector. For contact lenses measuring and inspection. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	NO	NO	NO	NO
			19	8	10	13 lb	1:	120	1	2								
			48	20	25	6 kg	2:	--	--	--								
M5570	6540-01-375-9031	Armed Forces Vision Tester	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Armed Forces Vision Tester. Unit is spring balanced for easy height adjustment and has a tension lock. It contains rotating drums for slide alignment and 5 point tests. It is designed to provide accurate vision screening for near point and far point vision. This unit is a special order item normally procured through DSCP. This item is designed for the government and is not available on the open market. [This is a special order item made exclusively for the government and is normally obtained through DSCP. Stereo Optical now sells direct as well.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	NO	NO	NO	NO
			12	12	14	50 lb	1:	129	1	5								
			30	30	36	23 kg	2:	--	--	--								
M5575	6515	Tonometer, Noncontact	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	NO	NO	NO	NO
			18	11	20	44 lb	1:	120	1	--								
			46	28	51	20 kg	2:	--	--	--								
M5580	6515	Tonometer, Applanation	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Applanation tonometer. Unit is designed to be used in conjunction with a slit lamp. It provides direct pressure reading in mm of mercury. No adjustment is required on guide plate of slit lamp. Used for mass screening, checking of tensions of glaucoma patients, diagnosis of glaucoma and diurnal pressure curves. [The tonometer required will depend on the brand of the slit lamp in use.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	NO	NO	NO	NO
			8	4	5	2 lb	1:	--	--	--								
			20	10	13	1 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES						
				R	A	F	A	H		1	2	3	4	5	6	
M5585	6515	Gonioscope, Lens, Contact	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Contact lens gonioscope. Consists of a hand held instrument to be used in conjunction with a slit lamp. Made of stainless steel and is supplied with a locking ring, plastic protection ring and diagnostic mirror glass. Designed for contact lenses diagnostic purposes. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:					
EA		IN:	1	2	2	1 lb	1:	--	--	--	NO	--				
		CM:	3	5	5	1 kg	2:	--	--	--	NO	--				
M5590	6515	Magnet, Eye, Electric	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Electric eye magnet. Includes foot switch and three detachable points. Designed for the removal of embedded ferromagnetic foreign bodies in the eye. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	BTUs / HR:					
EA		IN:	5	13	11	17 lb	1:	120	1	3	NO	--				
		CM:	13	33	28	8 kg	2:	--	--	--	NO	--				
M5595	6540-00-685-5197	Test Set, Vision, Worth, Binocular	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Binocular vision test set. Consist of spectacles and a battery powered flashlight. Spectacles have one red and one green lens and are reversible. Flashlight lens mask has one white, one red and two green round openings. Used for testing visual fusion, suppression and diplopia. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	BTUs / HR:					
EA		IN:	2	2	8	1 lb	1:	--	--	--	NO	--				
		CM:	5	5	20	1 kg	2:	--	--	--	NO	--				
M5600	6515	Unit, Exam, Eye, w/Motor Chair, Phoropter	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Eye exam phoropter unit with motor operated chair. Unit consists of an adjustable chair, and phoropter unit for eye examination, mounted on a stand. Stand includes an additive tray with keratometer arm and tray and a integral instrument tray. Unit is designed for use during ophthalmic examinations. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	BTUs / HR:					
EA		IN:	74	28	48	271 lb	1:	120	1	6	NO	--				
		CM:	188	71	121	122 kg	2:	--	--	--	NO	--				
M5605	6515	Retinoscope, Streak	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Streak retinoscope. Lightweight instrument with interchangeable heads, rechargeable battery handle, mirror, forehead rest and one halogen lamp. Continuous 360-degree streak rotation.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	BTUs / HR:					
EA		IN:	9	3	3	1 lb	1:	120	1	1	NO	--				
		CM:	23	8	8	1 kg	2:	--	--	--	NO	--				
M5610	6540-00-299-8587	Lantern, Perception, Color	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Lantern for color perception testing. The unit is also known as a Farnsworth Lantern. The lantern comes complete with a carrying case, spare lamp and color plates. Used for detecting defective color vision. [No other source(s) identified with this description/specification. This item is considered by the manufacturer to be "Military Unique." Orders are generally placed through the Defense Supply Center Philadelphia at a quantity-negotiated price. Item is manufactured as required.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	BTUs / HR:					
EA		IN:	14	20	18	50 lb	1:	120	1	1	NO	--				
		CM:	36	51	46	23 kg	2:	--	--	--	YES	--				
M5700	6540	Frame Set, Lens, Trial	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Trial lens frame set. Set consists of light weight and color-coded marked lenses, holding tray, and a complete assortment of other accessories. It is used to determine visual acuity. Set features horizontal and vertical bridge adjustments with individual adjustments for temple length and angle. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	BTUs / HR:					
EA		IN:	2	21	13	15 lb	1:	--	--	--	NO	--				
		CM:	5	53	33	7 kg	2:	--	--	--	NO	--				

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
M5705	6540	Gauge, Distance, Pupillary	C C C C --	--	--	--	--	--	--	--	--	--	--
Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter. [No other source(s) identified with this description/specification. Keeler Instruments has available the Procyon Binocular Pupillometer. It provides computer controlled image analysis to measure pupil diameter. It also provides a comprehensive reporting system, graphs and tables as well as archives all patient data. The price for this item is \$13,900.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	2	6	10	2 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	5	15	25	1 kg	2:	--	--	--	DEPENDENT:	NO	--
M5710	6640	Mirror, Front Surface Reflector, Eye Exam	A A A A --	--	--	--	--	--	--	--	--	--	--
Front surface reflector eye exam mirror. Designed to lengthen the focal path length in a room where the room's length is less than required for direct projection and viewing. Item is usually shipped in sets of two. [No other source(s) identified with this description/specification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	13	13	2	12 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	33	33	5	6 kg	2:	--	--	--	DEPENDENT:	NO	--
M5715	6540	Prism Set, Square, w/Case	C C C C --	--	--	--	--	--	--	--	--	--	--
Square prism set. Consists of square plastic or glass prisms in a carrying case. Set has 1/2, 1, 2, 4, 6, 8, 10, 15, 20 and 25 diopter prisms as a minimum. Designed for use in ophthalmologic examinations.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	6	28	6	8 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	15	71	15	4 kg	2:	--	--	--	DEPENDENT:	NO	--
M5720	6540	Screen, Projection, Eye Exam	A A A A --	--	--	--	--	--	--	--	--	--	--
Eye exam projection screen (13x13 minimum). Unit has a washable non-glare finish and is designed for wall mounting. To be used in conjunction with the ophthalmic eye chart projector and mirror, where required.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	16	16	1	5 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	41	41	3	3 kg	2:	--	--	--	DEPENDENT:	NO	--
M5730	6540	Stand, Instrument, Ophthalmic	C C C C --	--	A	--	--	--	--	--	--	--	--
Ophthalmic instrument stand. Unit provides power supply for hand-held instruments, mounting post for phoropter, and mounting post and arm for slit lamp table adjacent to the ophthalmic exam chair. Used in the eye exam room. [No other source(s) identified with this description/specification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	74	51	24	292 lb	1:	120	1	3	HZ SWITCH:	NO	--
		CM:	188	130	61	133 kg	2:	--	--	--	DEPENDENT:	NO	--
M5735	6540-00-299-9590	Warmer, Spectacle, Plastic	C C C C --	--	A	--	--	--	--	--	--	--	--
Plastic spectacle warmer. Bath type. Thermostatically controlled. For use with glass beads or salt.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	5	12	8	10 lb	1:	120	1	3	HZ SWITCH:	NO	--
		CM:	13	30	20	5 kg	2:	--	--	--	DEPENDENT:	NO	--
M5740	6540-00-299-9590	System, Phacofragmentation (Cusa)	C C C C --	--	A	--	--	--	--	--	--	--	--
Phacofragmentation unit uses ultrasonic energy to break down tissue and allow the tissue fragments to be suctioned out of the operative site. Used in ophthalmic and other micro-surgery application where precise excision of tissue is required.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	48	24	24	250 lb	1:	120	1	10	HZ SWITCH:	NO	--
		CM:	122	61	61	114 kg	2:	--	--	--	DEPENDENT:	YES	--

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M6005	6540-00-116-5780	Edger, Lens, Automatic Beveling	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Lens edger with automatic beveling. Unit includes two diamond wheels, coolant pump, tank and other accessories. Used to edge lenses.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	21	30	25	134 lb	1:	120	1	20	NO		--					
		CM:	53	76	64	61 kg	2:	--	--	--	NO		--					
M6010	6540	Edger, Lens, Automatic Beveling, Cabinet Mounted	C	C	C	C	--	B	B	--	--	--	--	--	--	--	--	--
Automatic beveling, edging machine. Unit is cabinet mounted and includes a fixed head with an air-pressure chucking device and air compressor for edging lenses. It is capable of automatic beveling. It is intended for use with plastic or glass ophthalmic lenses. [No other source(s) identified with this description/specification. Recommend the description be reviewed. Use of compressed air is old technology.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	17	25	22	172 lb	1:	120	1	15	NO		--					
		CM:	43	64	56	78 kg	2:	--	--	--	YES		--					
M6015	6540	Generator, Lens	C	C	C	C	--	--	C	C	--	--	--	--	--	--	--	--
Lens generator. Table mounted unit equipped with pivoting control panel, variable sweep speed selector, back-cut generating capabilities and hydraulic chucking. For production of glass or plastic lenses. Optional vacuum chuck available. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	57	65	33	1,890 lb	1:	220	3	18	50/60 YES		--					
		CM:	145	165	84	858 kg	2:	--	--	--	NO		--					
M6020	6540	Polisher, Lens	C	C	C	C	--	--	A	D	--	--	--	--	--	--	--	--
Ophthalmic lens polishing unit. Heavy duty construction dual spindle unit with dual phase air control, separate slurry bowls, head positioning adjustments, and automatic timer. Designed to polish lenses and to produce concave spherical surfaces. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	54	18	29	251 lb	1:	120	1	10	60 NO		--					
		CM:	137	46	74	114 kg	2:	--	--	--	NO		--					
M6025	6540	Surfacer, Lens, Cylinder, 2 Spindle, Automatic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Surface, ophthalmic lens, cylinder, two spindle, automatic. Unit utilizes 120 AC, 500 watts. It has an automatic, 2 spindle, lens surfacer cylinder. The dual spindle with dual phase control starts at a lower pressure then converts to high pressure. It features pneumatic pressure spindle heads, separate slurry bowls, head positioning adjustments and single motor and stroke control. It is designed to produce concave spherical surfaces on glass or plastic lenses. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	52	21	27	360 lb	1:	120	1	5	0 NO		--					
		CM:	132	53	68	164 kg	2:	--	--	--	YES		--					
M6035	6540	Tempering Unit, Heat, Lens	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Glass lens heat treatment unit. Compact unit with automatic temperature control, built-in polariscope and air compressor. Unit is designed for hot air drying of spectacle lenses. [This item is still available but should be considered for deletion as it is used for glass lenses only.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	16	10	10	35 lb	1:	120	1	10	60 NO		--					
		CM:	41	25	25	16 kg	2:	--	--	--	YES		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M6040	6540	Pachymeter, Ultrasound, Corneal	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Ultrasonic pachymeter for measuring corneal thickness.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	18	9	11	14 lb	1:	120	1	1	60	YES	--						
			46	23	28	7 kg	2:	4	--	--	DEPENDENT:	YES	--						
M6045	6540	Corneal Topography Unit	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Computerized corneal mapping system for pre- and post- surgical diagnosis of astigmatism, refractive error, irregularly shaped corneas and other eye conditions. The unit performs analysis of 5,000 - 6,000 different points on a ring pattern reflected from the patient's cornea to quantify the curvature and contours of the corneal surface. [Price difference verified.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	55	38	28	99 lb	1:	120	1	5	60	NO	--						
			140	97	71	45 kg	2:	--	--	--	DEPENDENT:	YES	--						
M6050	6540	Retinal Imaging System, Fluorescein/Indocyanine	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Digital camera system for conducting fluorescing and indocyanine green studies of the choroid of the retina. The infrared sensitive camera has interchangeable barrier and exciter filters for the different dyes. The camera transmits images to a high resolution computer system and monitors for viewing, analysis, enhancement, manipulation, recording and color printing. Database reflects pricing and physical characteristics for the entire system with its required computer. [No other source identified with this description/specification.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
SY		CM:	36	21	41	192 lb	1:	120	1	10	60	NO	--						
			91	53	104	88 kg	2:	--	--	--	DEPENDENT:	YES	--						
M7000	6530	Bed, Birthing, Electric	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Electric birthing bed. Unit is designed as a maternity care system to enable management of both high and abnormal childbirth without transfer. It includes adjustable footrests, fluid basin, IV pole, braking steering, hand grips, leg supports, push pull bar, side-rails, and removable headboard. To be used as a birth chair, childbearing bed, labor bed, and recovery bed. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	42	42	90	300 lb	1:	120	1	4	60	NO	--						
			107	107	229	137 kg	2:	--	--	--	DEPENDENT:	YES	--						
M7005	6530	Bed, Hi-Low, Manual	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Manual Hi-Low bed. Heavily constructed steel frame with crank handles to lower the bed or obtain a full range of positions. Handle grip folds down when not in use. It also features six IV sockets and removable headboard mounted on four 3" ball bearing swivel casters. To be used in hospitals, clinics, nursing homes, and other appropriate areas.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	310	37	89	250 lb	1:	--	--	--	--	NO	--						
			787	94	226	113 kg	2:	--	--	--	DEPENDENT:	NO	--						
M7007	6530	Bed, Patient, Electric, Special Care	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Electric patient bed for special care areas. Unit features a control panel for the patients operation, IV rod locations and a full range of positions. Includes safety sides, thermal overload protection in the motors, provisions for chest x-rays and fluoroscopy. Bed deck is x-ray translucent. [Price difference verified.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	41	40	94	495 lb	1:	120	1	5	60	NO	--						
			104	102	239	225 kg	2:	--	--	--	DEPENDENT:	NO	--						
M7010	6530	Bed, Patient, Electric	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Electric patient bed. Includes safety side rails, IV rod insertion slots and patient control panel for a full range of positions. Four wheel locking breaks. Overall bed height adjustable between 16.5 and 31 inches. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	31	42	94	180 lb	1:	120	1	10	60	NO	--						
			79	107	239	82 kg	2:	--	--	--	DEPENDENT:	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
M7011	6530	Bed, Platform, Without Visible Legs, Psychiatric	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Platform bed and mattress with enclosed under carriage, no visible legs. Provided with 5/8" plywood deck, eight restraint holders, two at head and foot, three at each side, concealed steel frame, and means to bolt to the floor. Sides and ends are finished wood panels. [Model's 1 and 2 do not include a mattress. Model 1 to be modified at time of order to provide means to bolt to the floor. Model's 2 and 3 can be bolted to floor and do have legs that are visible.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	18	39	84	250 lb	1:	--	--	--	0		NO							
		CM:	46	99	213	114 kg	2:	--	--	--	NO		NO							
M7015	6530	Crib	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Pediatric crib. Constructed of heavy square steel. Side rails have maximum 2-3/4" bar spacing with a squeeze release. Spring height adjusts from 32 1/2" to 41 1/2" high. Mattresses should be water and stain resistant. The unit is mounted on ball bearing casters. To be used in pediatric departments.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	59	30	60	254 lb	1:	--	--	--	--		NO							
		CM:	119	76	152	115 kg	2:	--	--	--	NO		NO							
M7020	6530	Top, Crib, Safety	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Crib top safety/cover frame. Used to secure infant inside the crib. Frame can be all metal or of an impact/break-resistant, easy to clean, transparent material. [OHI, as of 2001, manages the Midmark line for the crib covers/ security tops. New literature will be available in the future.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	19	36	54	98 lb	1:	--	--	--	--		NO							
		CM:	48	91	137	45 kg	2:	--	--	--	NO		NO							
M7025	6530	Mattress, Bed, Hospital	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Hospital bed mattress. These mattresses are usually filled with multi-layered foam, wire coil innersprings, or a combination of both. Mattresses are made of a fire retardant material (to meet California standard) and are enclosed in waterproof anti-microbial covers. For hospital use.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	6	36	84	32 lb	1:	--	--	--	0		NO							
		CM:	15	91	213	15 kg	2:	--	--	--	NO		NO							
M7040	6515	Table, Overbed	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Overbed table. Adjustable height table constructed of heavy gauge steel. Mounted on 2" diameter twin swivel casters with bumper caps. Table top is constructed with a high pressure plastic laminated surface that resists chipping, scratching, and staining. It includes a vanity tray and a mirror. Table is designed for use over bed, wheelchair or large chair.																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	46	18	36	57 lb	1:	--	--	--	--		NO							
		CM:	117	46	91	26 kg	2:	--	--	--	NO		NO							
M7250	6530	Cart, Medication, Unit Dose	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--		
Unit dose medication cart. The cart consists of a thermoformed top with built-in rim, a cart body and locking drawers. The unit rolls on hard rubber casters. On some models, the drawers are available as cartridge units of one or more drawers which slide into the cart body and lock in place. The unit may also contain accessories such as a slide out writing surface and medication cup, lotion and hand disinfectant dispensers. The cart's size, drawer layout and locking system are configurable as required for the cart's specific area of use. The cart supports the pharmacy unit dose system. Database pricing is for a higher cost, single width, fully featured configuration. [Prices will vary according to the configurations chosen.]																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:									
EA		IN:	42	33	27	180 lb	1:	--	--	--	--		NO							
		CM:	107	84	69	82 kg	2:	--	--	--	NO		NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES														
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6			
M7260	6670	Counter/Dispenser, Pill/Tablet	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--			
Automated pill, capsule and tablet counter. The unit consists of an array of holding cells each of which dispenses a set number of pills into a prescription bottle. The counter has a control unit to start and stop pill flow. Each cell has a straight line pill flow pattern, a photoelectric counter which signals the controller, a count range from 1 to 10,000 and can dispense products at a rate up to 600 tablets per minute. A built-in sensor indicates dust build up or misalignment of the photoelectric counter. Each cell has easily removable bins and mechanisms for cleaning and refilling. Each cell features an LED display and there are varying sizes of cells for handling more frequently issued or physically larger drugs. Many different, including custom, array of sizes and configurations are possible and the final design depends on the facility layout and pharmacy practice preferences. Individual cells can also be equipped with coded locks. The entire array can be interfaced with a pharmacy computer system. These units are commonly leased rather than sold because of maintenance requirements. Database pricing and information reflects an 11-cell and one computer link countertop array leased over a 5 year period with a computer interface. [No other source(s) identified with this description/specification.]			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT lb:	WEIGHT kg:	VOLTS 1:	VOLTS 2:	PHASE 1:	PHASE 2:	AMPS 1:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:
			EA	51	130	31	79	15	38	100	46	120	--	1	--	1	--	60	NO	YES	--
M7265	6530	Counter, Pill/Tablet, Automated, Counter Mounted	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	--	--	--
Table mounted prescription counter device that counts tablets and capsules directly into the final container. The unit shall automatically count and dispense tablets and capsules into a container with speed and accuracy.			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT lb:	WEIGHT kg:	VOLTS 1:	VOLTS 2:	PHASE 1:	PHASE 2:	AMPS 1:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:
			EA	20	51	11	28	20	51	21	10	115	--	1	--	1	--	60	YES	YES	--
M7270	6530	Packager, Unit Dose, Liquid	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	--	--	--
Liquid unit dose packager. Item is used for I.V. admix, chemotherapy admix, batch filling of Luer and oral syringes, elastometric infusers and oral liquid vials. Various accessories are available depending upon the application(s) desired. [No other source(s) identified with this description/specification.]			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT lb:	WEIGHT kg:	VOLTS 1:	VOLTS 2:	PHASE 1:	PHASE 2:	AMPS 1:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:
			EA	10	25	7	18	10	25	28	13	120	--	1	--	2	--	60	NO	YES	--
M7275	6515	Packager, Unit Dose, Solids	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	--	--	--
Automated packager for inpatient unit dose pharmacy applications. The unit consists of an array of cells which hold pills and tablets. The system computer takes user instructions and directs the system to select the proper pill cell and dispense a tablet onto a plastic bottom sheet. At the same time, the system prints a plastic cover sheet for the pill which includes the type of pill and any facility specific coding necessary. The system then marries the two sheets (with the pill between them) and heat seals the sheets enclosing the pill. The system is designed to limit cross contamination by containing tablet dust and to alert the operator in case of malfunction. Several configurations are available depending on the size of the pharmacy and workload. [Omnicell, Model 2 (Cage Code AM206) has several sizes of units. Pyxis (Cage Code SR350) also has a automated packager called the iPak II. Packaging is automatic for oral solids and manually assisted for liquids. Price for this unit is \$182,900. However, the unit is slow when compared to Model 3, Pyxis Packaging Console XL.]			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT lb:	WEIGHT kg:	VOLTS 1:	VOLTS 2:	PHASE 1:	PHASE 2:	AMPS 1:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:
			EA	78	198	46	117	47	119	1,521	691	120	--	1	--	8	--	60	NO	YES	--
M7280		Dispensing System, Prescription, Robotic	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--	--	--	--
Robotic prescription dispensing system. System handles 200 tablets and capsules and delivers filled and labeled vials at a rate of up to 100 prescriptions per hour. System uses a computer controlled robotic arm to fill vials directly from medication dispensing cells. [GSA price for Model 1 is \$163,680 plus \$21,930 for installation. Model 3 is a new model from McKesson that will be available in June 2004. Price for Model 2 and 3 is from GSA/VA schedule and includes installation.]			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT lb:	WEIGHT kg:	VOLTS 1:	VOLTS 2:	PHASE 1:	PHASE 2:	AMPS 1:	AMPS 2:	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:
			EA	82	208	138	351	71	180	2,540	1,154	120	208	1	1	30	30	60	NO	YES	--

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M7400	6530	Light, Exam, Table Mounted, Spotlight	C	C	C	C	--	--	A	--	--	--	--	C				
		The exam light shall be table mounted. The light will be a halogen bulb that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down.																
		UNIT OF ISSUE: EA	HEIGHT IN: 55 CM: 140	WIDTH 3	DEPTH 4	WEIGHT 8 lb 4 kg	VOLTS 1: 120 2: --	PHASE 1	AMPS 3	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --					
M7401	6530	Light, Exam, Mobile, Spotlight, Mobile Stand	C	C	C	.	--	--	A	--	--	--	--					
		The exam light shall be a mobile floor unit. The light will be a halogen bulb that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.																
		UNIT OF ISSUE: EA	HEIGHT IN: 75 CM: 190	WIDTH 23	DEPTH 23	WEIGHT 62 lb 29 kg	VOLTS 1: 120 2: --	PHASE 1	AMPS 2	HZ: 50	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --					
M7405	6530	Light, Exam, Ceiling Mounted	A	A	A	A	--	--	F	--	--	--	--					
		Ceiling exam light. Consists of a lightheaded reflector supported by a ceiling mounted radial arm assembly that provides a wide range of positioning capabilities. Halogen bulbs and an intensity control provide cool, color corrected light. The minimum ceiling height in most cases is 8'-0"; refer to each manufacturer's specific installation requirements. Physical dimensions refer to the retracted light; one length of the dual swing arm around the center mount in width and depth and the combined height of the lamp head and folded arms. Unit may also have a center mount detachable and sterilizable control handle. For use in minor procedure or examination room applications.																
		UNIT OF ISSUE: EA	HEIGHT IN: 20 CM: 51	WIDTH 30	DEPTH 30	WEIGHT 55 lb 25 kg	VOLTS 1: 120 2: --	PHASE 1	AMPS 2	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --					
M7410	6530	Light, Exam, Ultraviolet (Woods)	C	C	C	C	--	--	A	--	--	--	--					
		Ultraviolet magnifier used in dermatology. Light is used in the diagnosing of disease and injuries to skin and eye, including detection of corneal scratches, foreign bodies in the eye, blocked tear ducts, fungus infections, Erythasma, Tinea Vesicolor, Vitiligo, Scabies and Microsporium Canis. [No other source(s) identified with this description/specification.]																
		UNIT OF ISSUE: EA	HEIGHT IN: 3 CM: 8	WIDTH 6	DEPTH 10	WEIGHT 3 lb 2 kg	VOLTS 1: 115 2: --	PHASE 1	AMPS 2	HZ: 60	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --					
M7415	6530	Light, Exam, Wall Mounted	A	A	A	A	--	--	A	--	--	--	--					
		Wall mounted examination light. Unit features high intensity color-corrected lighting, a tungsten halogen lamp and a supporting arm with minimum reach of 45 inches. Physical dimensions refer to the retracted light; one length of the dual swing arm from the wall mount in width and depth and the combined height of the lamp head and folded arms. See manufacturer's requirements for screws and pull-out strengths for mounting. Unit may also have a center mount detachable and sterilizable control handle. The unit is used in clinical treatment rooms and hospital rooms.																
		UNIT OF ISSUE: EA	HEIGHT IN: 16 CM: 41	WIDTH 31	DEPTH 31	WEIGHT 30 lb 14 kg	VOLTS 1: 120 2: --	PHASE 1	AMPS 2	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --					
M7420	6530	Light, Exam, Mobile	C	C	C	C	--	--	A	--	--	--	--					
		Mobile examination light mounted on a floor stand with casters. Unit features colored corrected light, an air-cooled shade and a balanced floating arm. Unit may also have a center mount detachable and sterilizable control handle. Designed for examination, treatment, and emergency areas where cool, color-corrected light is needed.																
		UNIT OF ISSUE: EA	HEIGHT IN: 85 CM: 216	WIDTH 34	DEPTH 30	WEIGHT 35 lb 16 kg	VOLTS 1: 120 2: --	PHASE 1	AMPS 2	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: --					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M7435	6230	Light, Overbed, Direct And Indirect	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Overbed patient room light which provides direct light for patient activity and indirect light for patient examination. The indirect portion of the light can be flipped down or redirected to provide dual intensity direct lighting. Unit is fully enclosed and is available in varying lengths. Some units feature a controlled power shut off to the light and patient bed when bumped by any item. Unit is designed to be wired directly to a junction box in the wall, a headwall service rail or patient service column. Dimensions are for a three foot light. [No other source(s) identified with this description/specification. Standard over-bed lighting is part of the general illumination plan, the database does not have a JSN for a standard over-bed light.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	HZ SWITCH: NO	BTUs / HR:			
			EA	IN:	9	38	7	29 lb	1:	120	1	2	NO	--				
				CM:	23	97	18	14 kg	2:	--	--	--	YES	--				
M7440	6530	Light, Surgical, Single, LDR/LDRP, In-Ceiling	A	A	A	.	--	--	A	--	--	--	--	--	--	--	--	--
A surgical lighting system shall be flush mounted or recessed in the ceiling with one lighthouse and a remote control. The light beam and beam intensity shall be adjustable. Light adjustments may be made from either a wall control panel or a hand held wand. This lighting system is for use in areas such as labor and delivery and minor surgery. [No other source(s) identified with this description/specification. The Skytron HA60AR-WC (Model 2) also includes the charging unit, control wand, control box and wall control (recessed).]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	HZ SWITCH: NO	BTUs / HR:			
			EA	IN:	20	19	19	55 lb	1:	120	1	3	NO	340				
				CM:	51	48	48	25 kg	2:	--	--	--	YES	--				
M7445	6530	Light, Surgical, Dual, LDR/LDRP, In-Ceiling	A	A	A	.	--	--	A	--	--	--	--	--	--	--	--	--
A surgical lighting system shall be flush mounted or recessed in the ceiling with two lighthouses and a remote control. The light beam and beam intensity shall be adjustable. Light adjustments may be made from either a wall control panel or a hand held wand. This lighting system is for use in areas such as labor and delivery and minor surgery. [No other source(s) identified with this description/specification. The Skytron HA60AR-WC (Model 2) also includes the charging unit, control wand, control box and wall control (recessed).]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	HZ SWITCH: NO	BTUs / HR:			
			EA	IN:	20	19	68	110 lb	1:	120	1	6	NO	680				
				CM:	51	48	173	50 kg	2:	--	--	--	YES	--				
M7455	6530	Light, Surgical, Ceiling Mounted, Single, Track	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Single track ceiling mounted surgical light. Light head hangs from a suspension arm attached to a vertical pole which glides along a ceiling track. Suspension arm rotates 360 degrees. Light head has a 28" depth of field and has a detachable, sterilizable handle. The lamp provides cool, color-corrected light and a variable intensity control. Minimum ceiling height is 8'. Height dimension below refers to the lamp head itself. Width and depth are the length of the swingarm plus the radius of the lamp head. [Getinge USA (Cage 32510) and Skytron (Cage 8J631) have discontinued their track mounted surgical lights. Model 3 is best used in an exam room or clinic setting.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	HZ SWITCH: NO	BTUs / HR:			
			EA	IN:	7	48	48	100 lb	1:	120	1	5	NO	--				
				CM:	18	122	122	46 kg	2:	--	--	--	NO	--				
M7465	6530	Light Grp, Surg, Ceiling, 2 Light, Parallel Track	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Ceiling mounted surgical lights. Two light heads mounted on two parallel ceiling surface tracks, each track with one light head and carriage. Includes one variable intensity control per light head. [Minimum ceiling height for most models is 9 foot; check the manufacturers' specific requirements. Database height dimension refers to the height of the light head itself. Width and depth are the distance from the center mounting pole's axis of rotation to the outer edge of the light head. Getting/Castle purchased (2001) ALM Surgical Equipment, Inc. and will hence forth carry ALM's OR Lighting as their main product line. ALM does not offer a track lighting system for ORs. They do offer an exam light track system but it is not intended of OR use. No other source(s) identified with this description/specification.]			UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60	HZ SWITCH: NO	BTUs / HR:			
			EA	IN:	15	46	46	350 lb	1:	120	1	10	NO	--				
				CM:	38	117	117	159 kg	2:	--	--	--	YES	--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M7470	6530	Light, Surgical, Ceiling, Single, Small	E	E	E	E	--	--	F	--	--	--	--	--	--	--	--	--
Ceiling mounted surgical light. Consists of a single lamp head up to 24" in diameter depending on the manufacturer. Unit provides heat filtered, color corrected light. Most lights require a minimum ceiling height of 8 feet 2 inches; check manufacturers' specific recommendations. Light head is in a movable yoke attached to a column hanging from the ceiling. For minor surgery and obstetrical procedures. Physical dimensions refer to the retracted light; one length of the dual swing arm around the center mount for width and depth and the height is the combined lamp head and folded arms height.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	20	32	32	165 lb	1:	120	1	2	DEPENDENT: YES		--					
		CM:	51	81	81	75 kg	2:	--	--	--								
M7475	6530	Light, Surgical, Ceiling Mounted, Single, Large	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Ceiling mounted surgical light generally 30-34" or larger in diameter depending on manufacturer. Light head is suspended from the ceiling by a mounting plate and pole. Light head contains several individual pods each with its own light source. Unit also has a detachable sterilizable handle. Minimum ceiling height for most models is 8'-9"; check the manufacturers' specific recommendations. Height dimension below refers to the height of the lamp housing. Width and depth are the length of the swing arm plus the light head diameter. This light is suitable for dual site surgery. [Skytron (Cage 8J631) no longer makes a surgical light greater than 29" in diameter. No other source found with a single light this large.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	20	54	54	172 lb	1:	120	1	5	DEPENDENT: YES		--					
		CM:	51	137	137	78 kg	2:	--	--	--								
M7480	6530	Light, Surgical, Ceiling Mounted, Single, Medium	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Single ceiling mounted surgical light with a light head diameter generally between 21" and 30" depending on the manufacturer. The light is mounted from a pole extending down from the ceiling and then from a pivotal arm assembly that rotates 360 degrees. It includes a variable intensity control and sterile focus handle. The minimum ceiling height for most models is 8'-9"; check the manufacturers' specific recommendations. The database height dimension below refers to the lamp head housing itself. Width and depth are the length of the swing arm plus the diameter of the light head. This light can be used for both minor and major surgical procedures. [.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	28	67	67	150 lb	1:	120	1	2	DEPENDENT: YES		478					
		CM:	71	170	170	68 kg	2:	--	--	--								
M7485	6530	Light, Surg, Ceiling Mtd, Dual, Equal Dia Heads	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Dual head surgical light mounted from a single pole. Both heads are of equal size and hang from individual swing arms. Each light head contains several light sources, an intensity control and a detachable, sterilizable handle. The minimum required ceiling height for most models is 9'-2"; refer to the manufacturers' specifications. The database height dimension below refers to the height of the lamp heads themselves. Width and depth are the sum of the swing arm length and lamp head diameter. This light is for use in major and minor surgical procedures.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	15	67	67	210 lb	1:	120	1	4	DEPENDENT: YES		--					
		CM:	38	170	170	96 kg	2:	--	--	--								
M7490	6530	Light, Surg, Ceiling Mtd, Dual, Unequal Dia Heads	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--
Dual head surgical light ceiling mounted from a single pole. Unit has two lamp heads of differing sizes mounted on individual swing arms. Unit features multiple lighting pods in each lamp head, deep cavity illumination, color-corrected light, intensity control and sterilizable handles. Refer to the manufacturers' specifications for minimum ceiling heights and installation data. The database height dimension below refers to the height of the lamp head itself. The width and depth measurements are the larger of the two sums of the swing arm length and the head diameter. For use in general purpose surgical suites. [.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	15	102	102	233 lb	1:	120	1	6	DEPENDENT: YES		1,433					
		CM:	38	259	259	106 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M7500	6530	Light, Surgical, Ceiling Mounted, 1 Light, Camera	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	
Ceiling mounted, surgical light with camera. Single-point ceiling suspension with one light head mounted from a pivotal arm assembly and one horizontal suspension arm to support pan and tilt camera unit. The system includes one variable intensity control for the light. Unit does not include the audiovisual system, the TV camera, zoom lens, pan and tilt unit, interconnecting wall box or the cart mounted controls. These latter items are provided by other vendors to the user's specifications. Lighting system provides high intensity deep cavity illumination. Designed for general purpose surgery video taping. Minimum required ceiling height is 8'-10". [Minimum ceiling height is 9' 4". Model 1 from Berchtold Corporation includes a single light (\$15,791) and a 24X zoom camera (\$19,958) mounted in the center of the lighthouse within a sterilized handle. The Skytron unit (Model 3) is an integrated system with the 10X camera also built into the lighthouse. These manufacturer's products are shown as examples of the wide differences and prices available depending on the specific equipment configuration required. They also provide an alternative choice to the separate single camera arm configuration noted in the description.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	780			
			48	71	71	150 lb	1:	120	1	50								
			122	180	180	68 kg	2:	--	--	--								
M7515	6530	Light, Surgical, Ceiling Mtd, Birthing/Retractable	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	
Ceiling mounted retractable surgical light. Single light system has a single-point ceiling suspension with one light head mounted from a pivotal arm assembly and one horizontal suspension arm which may be stored in a ceiling cabinet. Multiple lamp systems consist of separately fixed ceiling mounts whose ranges overlap to give the same shadowless illumination field. One variable intensity control. Lighting system provides high intensity deep cavity illumination. Designed for use in birthing rooms. [No other source(s) identified with a retractable ceiling mounted surgical light.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	340			
			20	62	40	150 lb	1:	120	1	6								
			51	157	102	68 kg	2:	--	--	--								
M7590	6530	Light, Corneal Microscope, Circular	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Circular fiberoptic light for use with surgical microscopes. The light consists of an illumination ring, center fixation bulb, power source and connecting fiberoptic cable. The unit attaches to the objective lens of a surgical microscope to provide shadow-free illumination and corneal centration during eye surgery. Electrical and dimensional data refer to the power supply only. The weight includes the entire system. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--			
			7	7	9	13 lb	1:	120	1	2								
			18	18	23	6 kg	2:	--	--	--								
M7625	6515	Colposcope System, Mobile, w/Accessories	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Colposcope with light source and accessories. Unit is mounted on a rolling floor stand and is compatible with laser therapeutic equipment used in obstetric and gynecologic procedures. Configuration options include magnification powers, positioning of the light source, laser micromanipulators, still photograph or video recording of procedures, optics for a second physician's observation and ceiling or wall mounting.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--			
			72	32	32	150 lb	1:	120	1	1								
			183	81	81	68 kg	2:	--	--	--								
M7650	6515	Defibrillator/Monitor, Acute Care	C	C	C	C	--	--	D	--	--	--	--	--	--	--	--	
Portable defibrillator/monitor for acute care includes biphasic defibrillator, pacing, SPO2, Interpretive 12-lead, NIBP monitoring, EtCO2 monitoring, Invasive pressure monitoring, Vital Sign monitoring, temperature probe, Fax transmission, PCMCIA Data Cards, Paddle accessories, and a color LCD. [Model 2, Lifepak 12 does not have a color LCD, but uses a electro-luminous (EL) display in black and gold.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--			
			13	16	9	19 lb	1:	120	1	5								
			33	41	23	9 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M7655	6515-01-135-0840	Defibrillator/Cardioscope, 5-Lead	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Unit consists of a 5 lead ECG and Defibrillator. Defibrillator consists of 2 paddles, charge control, synchronizer and charge indicator. Equipped with internal rechargeable batteries. ECG monitor includes 5 lead patient cable, display, recorder and battery charge indicator. For use in the ICU or during emergency life threatening situations.																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	DEPENDENT:	YES
				6	17	13	14 lb	1:	120	1	2								
				15	43	33	7 kg	2:	--	--	--								
M7660	6530-01-390-1460	Defibrillator/Monitor/Recorder, Portable	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead. [USAF approved for use in aeromedical evacuation situations.]																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	DEPENDENT:	NO
				7	11	9	11 lb	1:	120	1	2								
				18	28	23	5 kg	2:	--	--	--								
M7665	6515	Defibrillator/Monitor/Recorder Automatic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Portable defibrillator-monitor-recorder with built in advisory protocol. Unit is designed for use by ambulance crews and cardiac arrest teams where a physician will not be available to determine if defibrillation is appropriate. System provides lead II ECG monitoring only, recording and logging of a resuscitation event for later review. This system provides up to 360 joules output and has an external battery charger available. Unit is sometimes referred to as an "Automatic Advisory Defibrillator" or "AAD". Unit may be line powered with an optional battery substitute pack. [The AdvisoryAnalysis Program option for Model 3 is priced at \$8,465.00.]																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	DEPENDENT:	NO
				9	17	13	14 lb	1:	120	1	2								
				23	43	33	7 kg	2:	--	--	--								
M7705	6515	Electrocardiograph, 3 Channel Display/Printout	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Twelve lead electrocardiograph which prints and displays three channels switched in sequence between the leads. Many machines can also print 1, 4, 6 or all 12 channels, and feature computer analysis of wave patterns (computer assisted practice of cardiology or CAPOC).																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	DEPENDENT:	YES
				38	18	32	100 lb	1:	120	1	3								
				97	46	81	46 kg	2:	--	--	--								
M7710	6515	Electrocardiograph, 12 Lead, Portable	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Used to detect the electrical signals associated with cardiac activity, diagnose cardiac abnormalities, determine a patients response to drug therapy and reveal trends or changes in heart function. Capable of recording two or more leads simultaneously, recording an entire 12 lead ECG in about 10 seconds. Includes of a 3.5 inch, high density, floppy disk drive for test storage. Portable.																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	YES	BTUs / HR:	EA	CM:	DEPENDENT:	NO
				50	18	36	87 lb	1:	120	1	2								
				127	46	91	40 kg	2:	--	--	--								
M7715	6515	Electrocardiograph, Portable, Single Channel	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Portable direct writing electrocardiograph with a single channel printout/display. Automatic recording of 12 leads, switch-selectable sensitivity position, and isolated input for patient safety. For patient monitoring. [Price difference verified.]																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	DEPENDENT:	YES
				4	13	12	13 lb	1:	120	1	2								
				10	33	30	6 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M7723	6515	Electroencephalograph, 32 Channel	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
32 channel electroencephalograph. Unit consists of a cart, regulated power supply, a chart drive, an input cable, a master electrode selector, a monitor, electronic data storage devices, a computer and a plastic stimulator. Unit features fully automatic or manual operation, photic stimulation and a built-in impedance meter. The unit is designed for maximum efficiency in recording and performing encephalographic studies. The system offers a full range of electrode selection and programmed protocols. This is an advanced diagnostic unit for use in neurology clinics. [Options for Model 2 include a synchronized video patient imaging system (\$6,000), analysis software program to sort data (\$6,000) and a remote clinician review workstation (\$9,500).]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			55	140	31	175 lb	1:	120	1	5								
					30	80 kg	2:	--	--	--								
M7725	6515	Electromyograph	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Unit consists of a microcomputer, leads, electrically isolated amplifiers, stimulators, display and storage capabilities. The system measures muscular electrical activity during contractions which the patient or a stimulator can induce. Specific applications include nerve conduction studies to detect myelopathies (myelin degradation), neuropathies (nerve compression) or myopathies (muscle disease). Most units also include an evoked potential capability. See related auditory evoked potential units at JSN M0035 and similar electronystagmographs at JSN M7730.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			53	135	27	250 lb	1:	120	1	9								
					30	114 kg	2:	--	--	--								
M7730	6515	Electronystagmograph w/Accessories	C	C	C	C	--	D	A	--	--	--	--	--	--	--	--	--
Unit detects the electrical currents from muscular contractions which cause eye movement. For the analysis of eye motion as an indicator of brain stem dysfunction, multiple sclerosis, adverse drug reaction or other disorders causing irregular eye movements. The system consists of a electrical leads, large color display, recorder, 2 direct channels, auxiliary channel outputs and an electrode terminal box. The system requires one or more stimulation apparatuses such as an ear irrigator (which generates the plumbing requirements), light bar or rotating drum. System options include several microprocessor and printer configurations. Electrical requirements and weight are for the complete system. Height, width and depth are for the controlling microcomputer only. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			53	135	35	150 lb	1:	120	1	10								
					27	68 kg	2:	--	--	--								
M7735	6515	Recorder, ECG, Long Term, Portable, w/Case	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Solid state, battery operated, portable ECG recorder with 24 hour continuous data collection capacity (Holter recorder). The unit features a carrying case, batteries, disk (digital) or tape recording, electrodes, electrode extension cable and test cable. System does not lose information when the battery is removed from the unit. Unit requires a separate computer system for downloading and analyzing recorded information (see JSN M7770). Electrical data is for battery recharging system.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			2	4	3	1 lb	1:	120	1	2								
					5	1 kg	2:	--	--	--								
M7760	6515	Electrocardiograph, 3 Channel, CAPOC Compatible	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Electrocardiograph with a minimum 3 channel printout and a built in telecommunications port. The unit is compatible with the TRIMIS CAPOC (computerized assisted practice of cardiology) reading system. This unit detects the heart's electrical activity from several leads and produces a graphic record of the voltage versus time. The system is used to diagnose response to drug therapy and detect trends or changes in heart functions. The unit can often format the ECG tracings so that no cutting or mounting is necessary. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			3	8	13	10 lb	1:	120	1	1								
					11	5 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES																					
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6										
M7765	6530	Computer Assisted Cardiology Management System.	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--										
<p>Central processor for Computer Assisted Practice of Cardiology (CAPOC). Unit provides analysis of cardiograms from a variety of sources that are transmitted via the phone lines. Received cardiograms are analyzed, a report is formatted, and the report is transmitted back to the originating electrocardiograph unit. [System requires multiple outlets for a desktop PC/printer/monitor/UPS/storage device and about 6 feet of desk space. Model 2 price can range from \$55,000 to \$99,000 depending on configuration and size. No other source(s) identified with this description/specification.]</p>																												
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	24	72	20	-- lb	1:	120	1	15	DEPENDENT:	YES	--
				61	183	51	-- kg	2:	--	--	--	60	NO	YES	--													
M7770	6515	Computer, Holter Monitor Analysis System	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--										
<p>Central processor for the analysis of Holter monitor recordings. System permits the high speed downloading of Holter recordings into a central database, automated recording analysis and storage, report generation, listing clinical findings and tracking final reports. System includes a monitor, keyboard, scanner, printer, input port and a disk drive storage device.</p>																												
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	23	48	28	225 lb	1:	120	1	13	DEPENDENT:	YES	5,675
				58	122	71	103 kg	2:	--	--	--	60	NO	YES	5,675													
M7780	6515	Scanner, Document	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--										
<p>Scanner for recording printed material in an electronic format. Some models process both color and black-and-white images. Options include automatic paper feeders and transparency adapters. Most models require connection to a microcomputer for independent operation or use as part of a network. Larger models for high use applications which connect directly to a network without passing information through a microcomputer are available. [Price difference verified.]</p>																												
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	12	26	20	62 lb	1:	120	1	1	DEPENDENT:	YES	--
				30	66	51	29 kg	2:	--	--	--	60	NO	YES	--													
M7806	6515	Telemetry System, ECG	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--										
<p>Modular ECG telemetry system consisting of transmitter, receiver and mainframe. System monitors patient ECG and heart rate via ultra high frequency radio transmission. The size and configuration of the system is dependent on the number and placement of antennae in support of the system and the area to be monitored. Database configuration is for one transmitter, one receiver, and one mainframe. Telemetry antennae cost is based on an average of approximately \$ 1.- per square foot. Optional capabilities include central station or bedside monitor interface.</p>																												
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	YES	BTUs / HR:	EA	CM:	17	17	18	45 lb	1:	120	1	2	DEPENDENT:	NO	--
				43	43	46	21 kg	2:	--	--	--	60	YES	NO	--													
M7807	6615	Monitor, 4 Channels, Telemetry, Bedside	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--										
<p>4-channel monitor. Unit consists of a compact monitor showing 4 traces from 3 leads on a bright non-fading display. The unit measures ECG, heart rate, temperature and non-invasive blood pressure. The monitor includes audible and visual alarms. The unit also has a telemetry transmitter for ECG and heart rate. Temperature and noninvasive blood pressure can not be telemetered. Used to monitor and record patient's vital signs. [Price difference verified.]</p>																												
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	9	19	24	15 lb	1:	120	1	2	DEPENDENT:	NO	--
				23	48	61	7 kg	2:	--	--	--	60	NO	NO	--													
M7815	6515-11-000-2960	Monitor, ECG/Respiration, Infant (Apnea)	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--										
<p>Infant ECG/respiration monitor. Unit includes a microprocessor control unit, alarms and display. Designed to monitor infants heart/respiration rate and includes a rechargeable battery.</p>																												
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	4	10	10	7 lb	1:	120	1	1	DEPENDENT:	NO	--
				10	25	25	4 kg	2:	--	--	--	60	NO	NO	--													

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M7820	6515	Monitor, Fetal, Bedside/Stand Alone	C	C	C	C	--	--	A	--	--	--	--	D				
<p>Bedside fetal monitor. May be stand alone or connected to a central monitoring station. It includes dual heart rate, direct fetal ECG and ultrasound methods for monitoring fetal heart rate, it also monitors uterine activity. It has a 2 channel recording mechanisms with automatic annotation and a highly sensitive Doppler. Unit has telephone transmission capabilities. Used to monitor and evaluate contractions ante-partum. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	4	13	12	13 lb	1:	120	1	1	60	YES	--				
				11	34	31	6 kg	2:	--	--	--	NO	--	--				
M7825	6515	Monitor, Fetal, Central	C	C	C	C	--	--	A	--	--	--	--					
<p>Central display system provides immediate access and scanning of up to 16 bedside monitors. Central unit can be equipped with an optional automatic power back-up, remote display capabilities and laser printer. [Prices can vary significantly depending on configuration and extent of system options that must be determined at time of order. System capabilities can include, in addition to central surveillance, archival and bedside charting and documentation. Other options include optical disc storage, statistical evaluation and reporting. Price for a total system, including software, hardware and installation can easily approach \$400,000.]</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	23	18	17	60 lb	1:	120	1	6	60	YES	--				
				58	46	43	28 kg	2:	--	--	--	YES	--	--				
M7845	6515	Monitor, Physiological, Bedside, 4 Channel	C	C	C	C	--	--	A	--	--	--	D					
<p>4 channel bedside physiological monitor. The unit consist of a four-channel non-fade monochrome display monitor, an alarm system and printer-recording capabilities. The monitor has color coded controls and automatic calibration. The unit displays up to four waveforms simultaneously. The parameters to be monitored are user selectable. The monitor may be connected to a central monitoring station. The unit monitors patients in most acute care areas, step-down units, procedure rooms and emergency rooms.</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	10	13	8	15 lb	1:	120	1	5	60	YES	--				
				25	33	20	7 kg	2:	--	--	--	NO	--	--				
M7850	6515	Monitor, Physiological, Central, 8 Bed, Color	C	C	C	C	--	--	A	--	--	--	D					
<p>Eight bed central physiologic monitoring station. System consists of a central monitor that displays patient information from bedside monitors. It also centralizes alarm and recording functions from ECG tracings to vital signs display. Up to eight patients monitoring capabilities. Designed for use in the ICU, CCU, emergency room or recovery room. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	14	30	18	70 lb	1:	120	1	4	60	NO	--				
				34	76	46	32 kg	2:	--	--	--	NO	--	--				
M7855	6515	Monitor, Physiological, Infant.	C	C	C	C	--	--	A	--	--	--						
<p>Infant physiological monitor. Unit consists of blood pressure, ECG, respiration amplifier and temperature display. Used to monitor infants vital signs such as heart rate, temperature, respiration rate and oxygen saturation. Optional capabilities include tissue/blood gas values.</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	17	15	25	20 lb	1:	120	1	2	60	NO	--				
				43	38	64	9 kg	2:	--	--	--	NO	--	--				
M7860	6515	Monitoring System, Cardiac Catheterization Lab	C	C	C	C	--	--	F	--	--	--						
<p>Computerized monitoring system for use in cardiac catheterization labs and cardio-thoracic operating rooms. The system can display up to 32 different waveforms simultaneously, perform calculations of hemodynamic parameters, valve areas and cardiac output, archive procedure results and accept inputs from a variety of monitoring devices. The installed system can also include remote monitors/terminals and additional workstations and may interface with hospital-wide physiological monitoring or clinical information systems. The system includes several configurations in different locations. Database physical dimensions reflect the largest of these work centers. The estimated total 20 amp electrical requirements will be spread across several circuits in several locations. The system price varies greatly on the size and sophistication of the end user's requirements.</p>																		
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			CM:	50	60	32	340 lb	1:	120	1	24	60	NO	3,623				
				127	152	81	155 kg	2:	--	--	--	YES	--	--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M7865	6515	Monitor, Physiologic, Respiratory Gas	C	C	C	C	--	--	A	--	--	--	--	D				
<p>Physiologic monitor for end expiratory CO2 monitoring. Unit may be battery/line powered and provides numeric display of CO2 level in end expiratory gases. Unit to be provided with analog output to permit values to be slaved into a central monitor or bedside monitor. Monitor also provides for nitrous oxide and oxygen monitoring. Audible and visual alarms provided for high expired CO2, high inspired CO2/O2, high/low inspired N2O, respiration rate, apnea, and circuit occlusion. Some models available will display waveforms. Printer output is optional.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			14	13	16	22 lb	1:	115	1	2	60	YES	--					
			36	33	41	10 kg	2:	--	--	--	YES	--	--					
M7900	6630	Monitor, Anesthesia/Respiratory Gas	C	C	C	C	--	--	A	--	--	--	E					
<p>Anesthesia/respiratory gas monitor for an operating room or suite. Unit uses mass spectrometry, infrared analysis, laser analysis or other technology for quantifying levels of anesthetic agents and normal respiratory gases. Unit consists of one stand alone unit per operating room or a central analyzer connected to remote sampling stations in several operating rooms. Central analysis units will require conduit for routing gas sampling catheters from the surgical rooms. The system includes a gas pump with backup, vacuum sensors, system display, detectors, exhaust for sampled gases, diagnostics and an alarm system with apnea detection. This equipment may not be required if its capability is already included in the anesthesia apparatus or in the patient physiological monitoring system. [Model 1 is a stand alone unit while the other two models work with their respective monitors. This is the reason for the price variance. Model 2 works in conjunction with the Poet Plus 8100 and Model 3 works with the Passport 2 or Spectrum monitors.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			8	13	16	22 lb	1:	120	1	12	60	NO	--					
			20	33	41	10 kg	2:	--	--	--	YES	--	--					
M7905	6515	Oximeter, Pulse	C	C	C	C	--	--	A	--	--	--	--					
<p>Pulse oximeter for continuous surveillance of patient pulse and oxygen saturation rates. Instrument features LED display, audio and visual alarms, automatic calibration and battery operation in case of power failure. Other applications include sleep studies, exercise testing and monitoring certain patients in the home (e.g. infants or patients requiring respiratory therapy).</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			4	11	9	7 lb	1:	120	1	1	60	NO	--					
			10	28	23	4 kg	2:	--	--	--	YES	--	--					
M7910	6515	Thermometer, Electronic	C	C	C	C	--	--	--	--	--	--	--					
<p>Electronic thermometer. Pocket size unit with easy to read zero Fahrenheit or zero Centigrade LCD display in approximately 40 seconds. Battery operated and enclosed in a heavy duty plastic case. Unit is hand-held portable and may be stand or wall mounted. For patient body temperature readings.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			9	4	4	1 lb	1:	--	--	--	0	NO	--					
			23	10	10	1 kg	2:	--	--	--	NO	--	--					
M8000	6530	Shower Trolley System, Complete	A	A	A	A	--	--	--	--	--	--	--					
<p>Shall be a hydraulically height-adjustable shower trolley for patient transfer and shower. It shall be approximately 77" long x 30" wide with minimum height adjustments range between 23 - 33". It shall have a minimum lift capacity of 330 pounds. Casters shall be a minimum of 4" with wheel locking brakes. Shower Trolley may be configured to work manually or with a battery/electric height adjustment. The unit shall come complete with a wall panel that includes a patient shower and disinfection system, thermostatic mixer and temperature gauge and a stainless steel flush sink. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			35	30	76	267 lb	1:	--	--	--	--	NO	--					
			89	76	193	122 kg	2:	--	--	--	NO	--	--					

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M8002	6530	Shower Cabinet, Complete	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
<p>The shower cabinet is designed to accommodate ambulatory and non-ambulatory patients that have the ability to sit up. A sliding seat assists patients entering and exiting the cabinet. The unit is configured to securely and safely shower a patient sitting while providing the caregiver easy access without getting wet. The unit is approximately 44d x 31w x 39h and comes complete with a wall panel that includes a patient shower system, pressure and temperature-controlled thermostatic mixer and temperature gauge. [Wall Panel size is approximately 30 x 22 x 8 inches with a weight of 22 lbs. No other source(s) identified with this description/specification.]</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:					
EA		CM:	38	31	60	165 lb	1:	--	--	--		DEPENDENT:	NO	--					
			97	79	152	75 kg	2:	--	--	--				--					
M8005	6530	Bath, Hydrotherapy, Body, 34x106x78	A	A	A	A	--	D	B	--	--	--	--	A					
<p>Full body hydrotherapy bath. Unit is a rounded "Y" shaped, heavy gauge, 425 gallon capacity, seamlessly welded stainless steel tank. The bath has two movable electric turbine water stream ejectors, a water temperature thermometer, tank fittings, head rest, body hammock, pin stretcher and a steel base supported by chromium plated legs. The unit includes a thermostatic water mixing console and a patient stretcher lift. The bath is used for full body hydrotherapy treatments. The database weight figure is for a filled tank. See manufacturer's literature for floor loading requirements. [The model 850 mixing console requires a 3/4" IPS hot and cold water connections and a 1" NPT tub fill. Bath requires a 3" tank drain and 1-1/2" overflow drain. The main drain should be positioned beneath the tank drain plug; overflow drain should be positioned under the tank's overflow lip. Review exact tank positioning for proper placement. The patient lift requires a 120 VAC conventional receptacle for its battery charger (115V/60Hz/1phase/3 amps).]</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:					
EA		CM:	75	77	106	3,865 lb	1:	115	1	16		DEPENDENT:	YES	--					
			191	196	269	1,755 kg	2:	--	--	--				--					
M8010	6530	Pool, Hydrotherapy, Tank	A	A	A	A	--	D	G	--	--	--	--	--					
<p>Pool hydrotherapy tank. The unit's tank has an acid resistant stainless steel frame, acrylic glass sides and a fiberglass reinforced polyester bottom. The pool includes: a water or hydraulic patient lift, patient entry and exit stairs, a water circulation system, heaters, temperature controls, a water filtration system and tank maintenance tools. This system serves as a substitute for an in-ground pool while still allowing patients full range of motion during hydrotherapy treatments. Dimensions do not include the unit purification equipment which requires about 55 sq. ft. of floor space and separate installation in an adjacent space. Electrical requirements are for the pool only. Other components require electrical power depending on the final pool configuration. Floor loading for a filled pool is about 190 lbs. per sq. ft. [Electrical requirements are for control panel only, other components require electrical and or plumbing connections. Arjo no longer makes large hydrotherapy pools. No other source identified with this description/specification.]</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:					
EA		CM:	78	219	192	65,000 lb	1:	208	3	43		DEPENDENT:	YES	--					
			198	556	488	29,510 kg	2:	--	--	--				--					
M8015	6520	Bath, Hydrotherapy, Sitting	A	A	A	A	--	D	F	--	--	--	--	A					
<p>Hydrotherapy sitting bath with a lift. The lift is freestanding and is constructed of chrome plated tubing. The seat will be injection molded, gel-coated fiberglass with a seat and foot rest on fixed legs. The unit includes two whirlpool outlets, a thermostatic mixing valve for filling and showering, a readout for bath time and temperature, a hot water alarm, a shut-off monitor, a cleaner/disinfection system, a bath oil/shampoo dispensing system and a mobile lift. The bath is used for sitting body treatments and other nursing care operations. [Model 60XR bath requires 3/4" IPS cold and hot water connections and a 2" drain. Local building codes may require a 30 Amp GFCI (ground fault circuit interrupt) breaker. Mobile lift requires 120 V conventional outlet for battery charger. No other source(s) identified with this description/specification.]</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:					
EA		CM:	57	28	95	325 lb	1:	120	1	20		DEPENDENT:	YES	--					
			145	71	241	148 kg	2:	--	--	--				--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M8020	6530	Bath, Hydrotherapy, w/Elevating Tub	A	A	A	A	--	D	F	--	--	--	--	A				
<p>Hydrotherapy bath with lift trolley. The bath is a freestanding tub on adjustable legs. The control panel has a water hydraulic lift cylinder for height adjustment and a thermostatic mixer for controlling water temperature during filling. The disinfection unit has a flow meter to vary the concentration of disinfectant as needed. This bath is used for hydromassage and therapeutic bathing. [Each model requires a 3/4" hot and cold water supply equipped with a shut-off valve. The units also require a 3" drain pipe. The lift trolley requires a 120V conventional outlet for its battery recharger. The Model 2 tub is stainless steel. Prices may vary based on specific components determined at time of order.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	62	39	87	450 lb	1:	120	1	9	60	NO	--					
			157	99	221	205 kg	2:	--	--	--	DEPENDENT:	YES	--					
M8025	6530	Bath, Hydrotherapy, Burn, w/Lift	A	A	A	A	--	D	F	--	--	--	A					
<p>Hydrotherapy treatment bath for burn patients with lift trolley. The bath has an acid proof stainless steel rectangular treatment tank which is free standing on adjustable legs. Unit has a large drain for changing water and cleaning. The control panel has a fill water thermometer and separate thermostatic mixers for filling the bath and showering. The built-in disinfection unit has a flowmeter to vary the concentration of disinfectant as needed. The bath includes a hydrotherapy unit and is used for bathing burn patients in water carefully controlled to the appropriate temperature. Physical dimensions shown include the water control panel. [These therapy tanks require hot and cold feeds terminating in 1" BSP male fittings. The fittings should be equipped with shut-off valves. The unit also requires a 3" drain pipe. The lift trolley requires a 120V conventional outlet for its battery recharger.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	53	36	103	948 lb	1:	115	1	17	60	NO	--					
			135	91	262	431 kg	2:	--	--	--	DEPENDENT:	YES	--					
M8030	6530	Whirlpool, Mobile, Extremity, Medium	C	C	C	C	--	D	A	--	--	--	--					
<p>Mobile extremity whirlpool with a single or dual tanks for treating feet, ankles, calves, knees and arms. The tank is made from heavy-gauge corrosion resistant stainless steel or fiberglass which has fully finished seams, is leak-proof and is mounted on casters. The unit has a turbine ejector and aerator, thermometer and an auxiliary floor drain valve. Unit may require a ground fault interrupt power circuit and may use a thermostatic mixing valve for controlling water temperature when filling. Used for hydrotherapy treatments.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	42	26	30	581 lb	1:	120	1	3	60	NO	--					
			107	66	76	264 kg	2:	--	--	--	DEPENDENT:	YES	--					
M8035	6530-00-710-3005	Whirlpool, Arm, Pedestal Mounted	A	A	A	A	--	D	A	--	--	--	--					
<p>Pedestal mounted arm whirlpool. Freestanding fixed height unit with stainless steel tank, flow control valve and turbine ejector-aerator. Unit may require a ground fault interrupt power circuit and may use a thermostatic mixing valve for controlling water temperature when filling. [Arjo (Cage Code #1U001), has discontinued it's pedestal mounted model. The "SideKick" model was the replacement. No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	36	15	28	170 lb	1:	120	1	3	60	NO	--					
			91	38	71	78 kg	2:	--	--	--	DEPENDENT:	YES	--					
M8040	6530	Whirlpool, Extremity, Floor Mounted	A	A	A	A	--	D	B	--	--	--	A					
<p>Floor mounted extremity whirlpool. Unit has a corrosion-resistant stainless steel tank, thermostatic water mixing console and an overflow drain. The whirlpool can be easily recessed into the floor or mounted on a pedestal. The unit is used for water hydromassage of arms, legs and other extremities. Weight shown is for a filled whirlpool. [Price variance verified. The mixing console requires 3/4" IPS cold and hot water connections and a 1" tub fill. The whirlpool requires 2" drain. Local codes may require a GFCI circuit breaker.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	45	15	25	235 lb	1:	115	1	8	60	NO	--					
			114	38	64	107 kg	2:	--	--	--	DEPENDENT:	YES	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M8045	6530	Whirlpool, Extremity, Mobile, Large	C	C	C	C	--	D	A	--	--	--	--	--	--	--	--	
<p>Mobile extremity whirlpool for full leg and large limb hydrotherapy. Unit includes a turbine ejector and aerator for strong, precise whirlpool action, thermometer, casters and an auxiliary floor drain valve. Unit may require a ground fault interrupt power circuit and may use a thermostatic mixing valve for controlling water temperature when filling. [Model 3 has a 75 gallon capacity versus 60 gallon for the other two models.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			43	24	36	200 lb	1:	120	1	4	60	NO	--					
			109	61	91	91 kg	2:	--	--	--	YES	--						
M8050	6530-00-710-4005	Whirlpool, Leg, CRS, Floor Mounted	A	A	A	A	--	D	B	--	--	--	--	A				
<p>Floor mounted leg whirlpool. The whirlpool consists of a heavy gauge, leak proof, stainless steel corrosion resistant tank, an electric turbine ejector and aerator, a dial thermometer, a thermostatic water mixing console, a treatment timer and a built-in overflow lip. The database height dimension includes the turbine and the database weight figure is for a filled unit. [The mixing console requires 3/4" IPS cold and hot water connections and a 1" tub fill. The whirlpool requires a 2" drain. Models 1 and 2 have 72 gallon tanks while Model 3 has a 90 gallon tank.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			57	22	36	950 lb	1:	115	1	8	60	NO	--					
			145	56	91	432 kg	2:	--	--	--	YES	--						
M8055	6530	Whirlpool, Leg, Floor Mounted	A	A	A	A	--	D	B	--	--	--	--	A				
<p>Floor mounted leg whirlpool. The whirlpool consists of a heavy gauge stainless steel leak proof tank, an electric turbine ejector and aerator, a dial inside thermometer, hand grips, a drain valve and a thermostatic water mixing console. The unit is used for leg whirlpool treatments. The database weight figure is for a filled tank. [The mixing console for the model 690 requires 3/4" IPS cold and hot water connections and a 1" tub fill. The whirlpool requires a 2" drain.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			24	66	18	205 lb	1:	115	1	8	60	NO	--					
			61	168	46	93 kg	2:	--	--	--	YES	--						
M8060	6530	Whirlpool, Full Body, Mobile	C	C	C	C	--	D	A	--	--	--	--	--				
<p>Mobile whirlpool for leg/hip or full body treatments. Unit consists of a heavy gauge, welded, leak-proof, corrosion resistant stainless steel tank with an aerator/ejector, a solid stem thermometer and a thermostatically controlled heater. The drainage system includes an electric pump and an auxiliary drain valve. Unit moves on 4 casters. Used for hydromassage of legs, hips and other extremities. Unit may require a thermostatic mixing valve for temperature controlled filling and a ground fault interrupt protected circuit for power.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			27	66	18	250 lb	1:	120	1	4	60	NO	--					
			69	168	46	114 kg	2:	--	--	--	YES	--						
M8065	7100	Chair, Whirlpool, Adjustable	C	C	C	C	--	--	--	--	--	--	--	--				
<p>Patient whirlpool treatment chair. Constructed of chrome plated steel with non-slip rubber tipped legs and locking casters. Adjustable height. For use with a leg, arm or combination arm/leg treatment tank.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			60	25	25	35 lb	1:	--	--	--	--	NO	--					
			152	63	64	16 kg	2:	--	--	--	NO	--						
M8075	6630	Lift, Patient, Physical Therapy	A	A	A	A	--	B	--	--	--	--	--	--				
<p>Physical therapy patient lift. The unit is constructed of durable stainless steel and bolted to the floor. The lift consists of a water powered hydraulic lift cylinder, lift swing arm and swivel chair with armrests. The unit is equipped with a control panel and below the floor foundation tube. This lift is custom made to meet specific buyer's needs. Refer to JSN descriptions for hydrotherapy baths and whirlpools before specifying this JSN in drawings. Lifts are integral parts of many baths and pools. The unit is used in physical therapy areas.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			110	61	61	250 lb	1:	--	--	--	0	NO	--					
			280	155	155	114 kg	2:	--	--	--	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M8080	6530	Lift, Patient, Hydraulic, 350 Lb. Cap, Adj U-Base	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Hydraulic patient lift with an adjustable U shaped base and a 350 pound capacity. Unit can also be equipped with battery power and an automatic recharger, nylon stretcher and weighing mechanisms. The unit is mounted on locking ball bearing casters for safety and stability. The database height refers to fully extended lifting arms. Designed for patient lifting. [Model 1 is a battery powered lift and the reason for the price difference between the other two models. Models 2 and 3 can also be purchased with battery power.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			77	41	48	145 lb	1:	--	--	--	0	NO	--					
			196	104	122	66 kg	2:	--	--	--	NO	NO	--					
M8105	6530	Bath, Paraffin, Hand/Foot	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Paraffin bath for heat treatment of injuries. Unit features a chrome plated, corrosion resistant, double walled Monel metal tank to prevent loss of heat, thermostatic control, drain, timer, thermometer and stand with casters. Smaller models are available.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			30	18	30	185 lb	1:	120	1	10	60	NO	--					
			76	46	76	84 kg	2:	--	--	--	YES	YES	--					
M8115	6530	Conditioner, Cold Treatment Pack	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Refrigeration unit for twelve cold therapy packs. Unit features thermostatic temperature control, automatic defrosting and refrigeration grade insulation. Interior chamber is designed to facilitate periodic cleaning. Smaller capacity models are available. [Price variance verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			35	32	23	190 lb	1:	120	1	2	60	NO	--					
			89	81	58	87 kg	2:	--	--	--	YES	YES	--					
M8120	6530	Therapy Unit, Hydrocollator	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Moist Heat Therapy Unit, also referred as a Hydrocollator Heating Unit, are used to apply effective heat to hot packs used in moist heat therapy. Unit is supplied ready for immediate use and requires no special plumbing. Unit features: stainless steel insulated wall, thermostatically controlled, casters (mobile units only), and standard size Hot Packs. Other unit sizes and accessories (variety of hot packs, tongs, side table rack, etc.) are available. [Pricing, dimensions, and amperage based on a standard-size 12 Hot Pack mobile unit.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			32	24	16	100 lb	1:	120	1	9	60	NO	--					
			81	61	41	46 kg	2:	--	--	--	YES	YES	--					
M8125	6530	Ergometer, Bicycle, Stationary	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Bicycle ergometer. The unit includes an adjustable seat, pedals with toe clips, disc brakes, and tachometer/odometer. The display provides readouts of time, speed and distance. The unit features steel construction for durability and reliability. The ergometer is used in progressive rehabilitation or physical training programs.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			46	21	44	116 lb	1:	--	--	--	0	NO	--					
			117	53	112	53 kg	2:	--	--	--	NO	NO	--					
M8130	6530	Ergometer, Bicycle, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Mobile ergometer. Unit consists of adjustable seats and handle bars, pedals with toe clips and variable pedaling resistance connected to a speed and timer controller. Used in conjunction with many types of diagnostic equipment to monitor stress testing and pulmonary function analysis. Unit can be relocated to point of use.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			58	24	60	115 lb	1:	--	--	--	--	NO	--					
			147	61	152	53 kg	2:	--	--	--	NO	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES						
				R	A	F	A	H		1	2	3	4	5	6	
M8133	6530	Ergometer, Upper Body	C C C C --	--	A	--	--	--	--							
Ergometer for measuring upper body exertion during an exercise regimen. The unit consists of a seat and a hand crank mechanism at shoulder height. The unit is used for physical rehabilitation protocols and stress testing. The unit quantifiably measures the effort exerted by the patient.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:					
EA		IN:	68	33	64	212 lb	1:	120	1	5	60		NO		--	
		CM:	173	84	163	97 kg	2:	--	--	--	NO		NO		--	
M8135	6530	Ergometer, Bicycle, Testing/Evaluation	C C C C --	--	A	--	--	--	--							
Stationary ergometer. Unit features an adjustable seat and handle bars, pedals with toe clips and variable pedaling resistance. The ergometer is designed to accurately measure the rate at which work is performed by a group of muscles under controlled conditions in which the work load is independent of the patient's body weight. In many cases, the unit is used in place of a treadmill to subject patients with pulmonary problems to stress testing.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:					
EA		IN:	50	24	49	200 lb	1:	115	1	5	60		NO		--	
		CM:	127	61	124	91 kg	2:	--	--	--	NO		NO		--	
M8137	6530	Horizontal Exerciser, Upper and Lower Extremities	C C C C --	--	--	--	--	--	--							
Horizontal exerciser for strengthening muscles, improving range of motion and improving functionality of the upper extremities, lower extremities and trunk. The exercisers uses range from high intensity but low impact plyometrics to low resistance functional closed chain exercises. The unit includes a pulley system, lower extremity isolation belt and a twenty pound wobble board with adapter. [No other source(s) identified with this description/specification. See related equipment at JSN G1027.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:					
EA		IN:	48	108	31	190 lb	1:	--	--	--	--		NO		--	
		CM:	122	274	79	87 kg	2:	--	--	--	NO		NO		--	
M8140	6530	Exerciser, Ladder	A A A A --	--	--	--	--	--	--							
Shoulder abduction ladder. Exercise ladder consists of a hardwood unit with 33-36 steps each 2 1/2"W X 1 1/2"H.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:					
EA		IN:	58	3	2	4 lb	1:	--	--	--	--		NO		--	
		CM:	147	6	4	2 kg	2:	--	--	--	NO		NO		--	
M8145	6530	Exerciser, Staircase, Convertible	C C C C --	--	--	--	--	--	--							
Convertible exercise staircase. Staircase is sturdily built in two sections permitting a corner type or straight type arrangement. It consists of steps 30-36" wide and a square platform. It includes handrails to accommodate both children and adults. Both steps and platform are covered with non-slip tread.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:					
EA		IN:	15	30	55	450 lb	1:	--	--	--	--		NO		--	
		CM:	38	76	140	204 kg	2:	--	--	--	NO		NO		--	
M8150	6530	Exerciser, Ramp and Curbs	C C C C --	--	--	--	--	--	--							
Heavily constructed ramp and curbs exerciser. Unit includes three wide, deep curbs which are 2", 4" and 6" high. The ramp section is also deep and wide and rises gradually from 1/2" to 8" high. The end portion of the ramp section is an 8" high platform which the curb sections meet. The curbs and ramp have a sure-grip, long wearing, non-slip surface. The exerciser is used for training in walking techniques as well as balance.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:					
EA		IN:	8	44	87	125 lb	1:	--	--	--	0		NO		--	
		CM:	20	112	221	57 kg	2:	--	--	--	NO		NO		--	
M8155	6515	Isokinetic Unit, Testing and Treatment	C C C C --	--	--	--	--	--	--							
Testing and treatment isokinetic unit. The unit consists of a steel frame with lever arms, hand grips, stabilizing straps and a vinyl bench seat which adjusts from a fully upright to fully flat position. The unit includes a set of weights and is used as an exercise and measurement station for physical therapy. [Only one source could be found for this non motorized item. Previous sources no longer carry this type unit.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:					
EA		IN:	57	30	80	340 lb	1:	--	--	--	--		NO		--	
		CM:	145	76	203	155 kg	2:	--	--	--	NO		NO		--	

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M8165	6515	Stimulator, Neuromuscular	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Low or high voltage neuromuscular stimulator. Unit provides timed electrical treatments with one or more current types (surge, tetanizing or pulsation). Some units offer an additional variety of waveforms (i.e.: interferential, premodulated, Russian, microcurrent), data collection, data correlation, microprocessor controls and data downloading for trend analysis over time.</p>																		
UNIT OF ISSUE:		EA	IN:	9	20	14	WEIGHT	20 lb	1:	120	1	2	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	23	51	36	9 kg	2:	--	--	--	--	--	DEPENDENT:	YES	BTUs / HR:	--	--	--
M8170	6515-00-937-9697	Stimulator, Neuromuscular, Portable	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Neuromuscular stimulator. Rugged outer casing with all solid-state components, time and parameter controls. Unit can provide one or more types of stimulation and operate from a battery or an AC power adapter. [Portable battery (DC only) units are available from BMR, Masters Medical, Ness, Mettler, Chattanooga.]</p>																		
UNIT OF ISSUE:		EA	IN:	4	9	11	WEIGHT	4 lb	1:	120	1	1	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	10	23	28	2 kg	2:	--	--	--	--	--	DEPENDENT:	YES	BTUs / HR:	--	--	--
M8171	6515-00-937-9697	Stimulator, Neuromuscular, Interferential	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Unit features fixed frequency carrier waves and premodulated sweep frequencies. The two frequencies combine to generate therapeutic electric stimulation. In some models, interferential therapy is one of several different modalities. Some models also feature more than one channel. [The AMREX 1F150 stimulator is sold only through distributors like Ali Med. The model CPS 400 is distributed through the Chattanooga Group.]</p>																		
UNIT OF ISSUE:		EA	IN:	6	12	14	WEIGHT	14 lb	1:	120	1	2	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	15	30	36	7 kg	2:	--	--	--	--	--	DEPENDENT:	YES	BTUs / HR:	--	--	--
M8172	6515	Stimulator, Transcutaneous Electric Nerve	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Transcutaneous electric nerve stimulator (TENS) unit. Device delivers current of high or low frequency to external electrodes to provide nerve stimulation for pain relief. Unit is battery powered. Electrical data refers to recharging unit. [Model 3 weight includes the case.]</p>																		
UNIT OF ISSUE:		EA	IN:	4	3	1	WEIGHT	2 lb	1:	120	1	1	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	10	8	3	1 kg	2:	--	--	--	--	--	DEPENDENT:	YES	BTUs / HR:	--	--	--
M8173	6515-00-937-9697	Stimulator, Neuromuscular, Multi-Channel	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Neuromuscular stimulator with two or more independently controllable channels. Unit employs several types of current waveforms across high or low voltages for different therapy protocols. Unit controls time, current intensity and current frequency during treatments. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		EA	IN:	13	16	10	WEIGHT	10 lb	1:	120	1	2	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	33	41	25	5 kg	2:	--	--	--	--	--	DEPENDENT:	YES	BTUs / HR:	--	--	--
M8174	6515-00-937-9697	Ultrasound/Neuromuscular Stimulation Combo Unit	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Ultrasound unit in combination with a neuromuscular stimulator; unit can deliver both types of treatments simultaneously or individually. The ultrasound unit operates at one or more frequencies. The electrotherapy portion of the instrument can operate at set voltages or continuously variable across a range. Depending on the ultrasound frequency and electrotherapy voltage, the clinician selects one of several treatment unit heads. Some models feature microprocessor controls, data collection, data correlation and data downloading for analysis over time.</p>																		
UNIT OF ISSUE:		EA	IN:	9	20	14	WEIGHT	25 lb	1:	120	1	2	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	23	51	36	11 kg	2:	--	--	--	--	--	DEPENDENT:	YES	BTUs / HR:	--	--	--

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M8175	6515	Therapy Feedback Unit	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Battery powered electromyograph, temperature or skin conductance unit for monitoring progress and effort in rehabilitation sessions. Unit has a single or dual channels and provides sound and/or visual feedback to the patient. Electrical requirements are for separate battery recharging unit.																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	7	14	11	6 lb	1:	120	1	1	60	NO	--						
			18	36	28	3 kg	2:	--	--	--	DEPENDENT:	YES	--						
M8180	6515	Biofeedback Analysis System	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Computer based biofeedback testing and analysis system. Unit accepts electroencephalograph (EEG), electromyograph (EMG), DC potential, goniometry, body temperature and other physiologic measurements for correlation and analysis. The system is primarily used in psychiatry and psychology clinics for rehabilitation treatments and pain management training. [No other source(s) identified with this description/specification. Configured with computer and monitor.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	23	48	19	100 lb	1:	120	1	5	60	NO	--						
			58	122	48	46 kg	2:	--	--	--	DEPENDENT:	YES	--						
M8185	6515	System, Stress Exercise, w/Treadmill	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--	
Stress exercise system with treadmill and respiratory/metabolic assessment. The system includes an ECG amplifier, chart recorder, display, console, treadmill and modules for respiratory/metabolic assessment. Used to determine patient's functional capacity, predict and diagnose cardiopulmonary and vascular diseases and for rehabilitation of patients recovering from leg injuries or other type of illness. Treadmill from some vendors requires a NEMA 5-20R non-locking receptacle. [Price difference verified. Prices may vary based on customization to meet specific user requirements. The treadmill for Model 2 has a 208 VAC power requirement.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	70	54	88	780 lb	1:	120	1	27	60	NO	--						
			178	137	224	355 kg	2:	208	1	20	DEPENDENT:	YES	--						
M8190	6530	Booth, Treatment, Ultraviolet	C	C	C	C	--	--	D	--	--	--	--	--	--	--	--	A	
Ultraviolet treatment booth which uses a combination of UVA and UVB light. Unit consists of a full body cabinet constructed with seven aluminum panels, magnetic door and a viewing window. The interior consists of wall reflector panels, hand rails, a padded floor, screen protection for lamps and a ventilation system. The unit also features dual exposure controls for managing exposure time and UVA and UVB measuring devices. The unit is used in dermatology for UV body treatment. [The manufacturer for Model 2 will be bringing out a new model in the future. It will be called a 3 Series 311/350 with a unit price of \$17,750. Price difference verified. Model 3 is a light weight, 24 lamp system for home use.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	87	46	49	780 lb	1:	120	1	60	60	NO	--						
			221	117	124	355 kg	2:	208	1	30	DEPENDENT:	YES	--						
M8192	6530	Booth, Treatment, Ultraviolet, Hand-Foot	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Hand/foot ultraviolet cabinet UVA-UVB combination system. Unit consists of one cabinet with two units in the cabinet. Patients hands are placed into the upper and feet in the lower level unit. Device is used in Dermatology for the treatment of certain skin conditions with ultraviolet light. [Price difference verified.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	44	30	24	150 lb	1:	120	1	10	60	NO	--						
			112	76	61	68 kg	2:	--	--	--	DEPENDENT:	YES	--						
M8195	6530	Diathermy Treatment Unit	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Short-wave or microwave diathermy apparatus. Unit is used for deep tissue heating in rehabilitation treatments. Units have treatment timers and continuously adjustable or stepped power controls. Pulsed radiation units are also available. [Numerous distributors found but only one manufacturer. No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	40	18	18	50 lb	1:	120	1	2	60	NO	--						
			102	46	46	23 kg	2:	--	--	--	DEPENDENT:	YES	--						

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M8200	6530	Ultrasonic Treatment Unit	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Ultrasonic treatment unit which operates at one or more frequencies. Unit features a treatment timer, variable interrupted outputs and a variable power range. Unit has one or more treatment heads depending on sound wave frequency. Used for physiologic stimulation.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	9	15	14	14 lb	1:	120	1	2	NO		--					
		CM:	23	38	36	7 kg	2:	--	--	--	YES		--					
M8201	6530	Ultrasonic Unit, Treatment	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Portable ultrasonic treatment unit. Continuous ultrasound, pulsed ultrasound, quartz crystal, dual output.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	5	14	11	8 lb	1:	120	1	1	NO		--					
		CM:	13	36	28	4 kg	2:	--	--	--	YES		--					
M8202	6530	Ultrasonic Unit, Patient Treatment	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Mobile ultrasonic treatment unit. Continuous ultrasound, pulsed ultrasound, quartz crystal, single output.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	5	14	12	12 lb	1:	120	1	1	NO		--					
		CM:	13	36	30	6 kg	2:	--	--	--	YES		--					
M8205	6515	Light, Infrared/Ultraviolet Combination	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Therapy lamp which provides ultraviolet and infrared radiation simultaneously or independently. The interior is a highly polished metal reflector. Unit is supported on a mobile stand. [Price difference verified. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	64	18	24	130 lb	1:	120	1	6	NO		--					
		CM:	163	46	61	59 kg	2:	--	--	--	YES		--					
M8210	6630	Cart, Weight, Physical Therapy, w/Weights	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Physical therapy weight cart equipped with weights, two storage shelves, and racks to store dumbbells. Unit is constructed of quality hardwood and mounted on 4 heavy-duty casters. Used for storage of weights.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	60	35	46	222 lb	1:	--	--	--	NO		--					
		CM:	152	89	117	101 kg	2:	--	--	--	NO		--					
M8215	6515	Light, Phototherapy, Mobile	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Mobile photo-therapy light. Unit has an adjustable stand and head with a halogen quartz bulb. Unit is mounted on a wheeled base. Used to produce a therapeutic blend of light to lower the serum bilirubin level in newborn children. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	66	19	18	40 lb	1:	120	1	2	NO		--					
		CM:	167	48	45	19 kg	2:	--	--	--	YES		--					
M8217	6530	Phototherapy Unit, Fiberoptic w/ Bili-Lite Pad,	C	.	.	.	--	--	A	--	--	--	--	--	--	--	--	--
Shall be a fiberoptic photo-therapy system consisting of a fiberoptic light source, a flexible fiberoptic cable and a transparent plastic pad. The unit is used to treat hyperbilirubinemia.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	7	10	13	18 lb	1:	120	1	3	NO		--					
		CM:	18	25	33	9 kg	2:	--	--	--	NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M8220	6515	Light, Infrared	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Infrared treatment light. Unit consists of a single or double reflector head which is adjustable in any direction and a telescopic arm with adjustable height. Some models feature timer switches. Unit is mounted on a 4 ball bearing caster stand.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			83	211	83	24	61	28 lb 13 kg	1:	120	1	7	60	NO	YES	--			
M8225	6515	Light, Ultraviolet, Mobile	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Ultraviolet light. Mercury-vapor type unit with mobile base, adjustable arm, protective spectacles and timer. To be used in physical therapy during radiation treatments. [Atlantic Ultraviolet, (Cage Code SR279), offers a UV light that can be mounted on a stand, No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			63	160	63	18	46	30 lb 14 kg	1:	120	1	7	60	NO	YES	--			
M8240	6530	Parallel Bars, Physical Therapy	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--	
Physical therapy parallel bars. Unit can have manual or electrically powered adjustments. Bar height is adjustable from 25" to 40" and the bar width is adjustable from 16" to 25". Hand rails are chrome plated 1-1/2" steel tubing. Walking aisle is a minimum of 24" wide and finished in natural wood or covered with vinyl matting. Database information reflects 10' or 12' bar length electrically powered units.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			43	109	43	47	144	750 lb 341 kg	1:	120	1	15	60	NO	YES	--			
M8245	6530	Platform, Exercise, w/Mat	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Exercise platform with mat. Platform is ruggedly constructed to resist dents and scratches from wheelchairs and braces. Item has thickly upholstered 2" polyfoam mat with nylon-reinforced tear proof cover. Item is normally used by patients in wheelchairs or with braces. [All models shown are 5' X 7'. Other sizes are available. See JSN M8305 for powered, adjustable height exercise platforms.]																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			20	51	20	60	84	175 lb 80 kg	1:	--	--	--	0	NO	NO	--			
M8250	6530	Mat, Exercise	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Exercise mat. Mat is filled with 2" resilient antibacterial foam. Handles are provided for hanging or transporting. Used in physical therapy. [Many other sizes are available.]																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			2	5	2	48	72	17 lb 8 kg	1:	--	--	--	0	NO	NO	--			
M8260	6530	Hooks, Mat, Gym	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Gym mat hooks. Metal hook and bracket mounted on a hardwood base. Two hangers hold four 2" thick mats.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			10	25	10	6	8	5 lb 2 kg	1:	--	--	--	--	NO	NO	--			
M8265	3630	Wheel, Potters	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Potter's wheel. Stand-up model adjustable in height to accommodate wheelchair patients, which can be controlled by hand or foot. The frame and table are all welded steel. Unit features a squash pan and a metal head. The motor is 1/3 HP or greater, can center 50 pounds of clay and features varying speeds. The wheel is used in hospitals, clinics, schools and other institutions for rehabilitation therapy, exercise and recreation.																			
UNIT OF ISSUE:		EA	IN:	CM:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:				
			38	97	38	51	45	310 lb 141 kg	1:	120	1	3	60	NO	YES	--			

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
M8270	6530	Rack, Pack, Hot/Cold, Wall Mounted	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Wall mounted hot/cold pack rack. Unit is a stainless steel rack used to store and dry cold packs.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	2	33	17	-- lb	1:	--	--	0	NO	--				
		5	83	43	-- kg	2:	--	--	NO	NO	--				
M8275	6530	Pulley, Triplex	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--
Triplex pulley for physical therapy use. Unit consists of two handles at chest level, two handles at the floor, and two handles suspended from the ceiling. Unit features 20 to 27 pounds of adjustable weights.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	120	24	18	110 lb	1:	--	--	0	NO	--				
		305	61	46	50 kg	2:	--	--	NO	NO	--				
M8280	6530	Evaluator, Hand Impairment, Computer Assisted	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Computer assisted hand impairment evaluation system. System includes an electronically interfaced hand glove dynamometer, pinch meter, and goniometer. The system allows evaluation of grip strength; pinch strength; range of motion of minor digits, thumb, and wrist; sensation-static two point discrimination; moving two point discrimination; Semmes-Weinstein monofilament and Tinell's signs; coverage/cosmesis; amputation; pain; edema; and volume. The system also provides for assisted input of manually collected data and produces a hand impairment rating in accordance with AMA 1989 specifications. System includes computer, computer stand, and printer in addition to evaluation instruments. A video option is available. [No other source(s) identified with this description/specification.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	24	30	25	75 lb	1:	120	1	60	NO	--				
		61	76	64	34 kg	2:	--	--	NO	YES	--				
M8285	6530	Simulator, Driving, Work Therapy	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Driving simulator used for work hardening programs in occupational and physical therapy. Device includes driver's seat which may be adjusted to simulate a variety of seat configurations and an adjustable steering wheel/control console to permit a variety of vehicles to be simulated. Entire system is mounted on retractable castors for mobility within the clinic. Simulator includes vibration generator in the seat section to accurately reproduce driving stresses. [No other source(s) identified with this description/specification.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	84	30	60	250 lb	1:	120	1	60	NO	--				
		213	76	152	114 kg	2:	--	--	NO	YES	--				
M8290	6530	Treatment System, Occup/Phys Ther, Computer Assist	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Computer assisted treatment system used for work hardening programs in occupational therapy or rehabilitation programs in physical therapy. The system includes an exercise head on a stand and a microprocessor control panel. The gimballed exercise head and its accessories may be positioned at a variety of angles and heights to simulate the motions of a great variety of work situations. The same equipment can be used to provide diagnosis, rehabilitation treatments and strength evaluations. In this latter role, the equipment can provide isokinetic, isometric, isotonic, concentric or eccentric resistance. The work head and control panel provide outputs to a computer which records patient activity, level of effort, device configuration and duration of exercise. The system provides objective evaluation of patient performance and recovery. Some equipment requires 220V power rather than 120V. Verify the manufacturers' specific electrical requirements in the equipment technical sheets. [No other source(s) identified with this description/specification]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	84	108	72	320 lb	1:	120	1	60	NO	--				
		213	274	183	146 kg	2:	--	--	NO	YES	--				
M8300	6530	Table, Examination/Treatment, Wood	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Examination/treatment table, wood construction. The table is capable of supporting at least 285 lbs. (120 KGP) and is of a "H" brace design with shelf and may have one drawer. Includes a leatherette covered 2 inch foam pad. Pad is removable and designed to fit the table top in a slip resistant manner.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA	CM:	32	31	78	180 lb	1:	--	--	0	NO	--				
		81	79	198	82 kg	2:	--	--	NO	NO	--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES																																				
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6																									
M8305	6530-00-926-9068	Platform, Exercise, w/Mat, Powered	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--																									
<p>Exercise platform with power height adjustment. The platform rests on one or two pedestal bases which contain the power mechanism for adjusting the table height. The platform top or removable mattress is covered with heavy duty, nylon-reinforced vinyl for durability. The adjustable height feature is designed to accommodate patients who have difficulty sitting or transferring from a wheelchair as well as providing an optimal working height for the physical therapist once the patient is on the table. Larger and smaller units as well as manual crank platform tables are available. [These units also come in 4' x 7' and 5' x 7' sizes. See non-powered platform exercise tables at JSN M8245.]</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>28</td> <td>71</td> <td>72</td> <td>183</td> <td>584 lb 266 kg</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	EA	28	71	72	183	584 lb 266 kg	<table border="1"> <thead> <tr> <th>VOLTS:</th> <th>PHASE:</th> <th>AMPS:</th> </tr> </thead> <tbody> <tr> <td>1: 120</td> <td>1</td> <td>9</td> </tr> <tr> <td>2: --</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			VOLTS:	PHASE:	AMPS:	1: 120	1	9	2: --	--	--	<table border="1"> <thead> <tr> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> </tr> </thead> <tbody> <tr> <td>60</td> <td>NO</td> <td>YES</td> </tr> </tbody> </table>			HZ:	HZ SWITCH:	DEPENDENT:	60	NO	YES	<table border="1"> <thead> <tr> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>--</td> </tr> </tbody> </table>			BTUs / HR:	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:																																						
EA	28	71	72	183	584 lb 266 kg																																						
VOLTS:	PHASE:	AMPS:																																									
1: 120	1	9																																									
2: --	--	--																																									
HZ:	HZ SWITCH:	DEPENDENT:																																									
60	NO	YES																																									
BTUs / HR:																																											
--																																											
M8310	6530	Table, Tilt	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--																									
<p>Automatically or manually powered tilt exercising table. Table consists of a durable steel frame with a padded board. The inclination angle of the table surface adjusts from 0 to 90 degrees. Table includes extra wide safety straps and casters with locking brakes. Some models also have an adjustable level height feature (hi-lo). Height dimension below refers to level table; fully tilted height is 78". Table is used for treatment of patients in physical therapy and rehabilitation programs.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>33</td> <td>84</td> <td>28</td> <td>71</td> <td>175 lb 80 kg</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	EA	33	84	28	71	175 lb 80 kg	<table border="1"> <thead> <tr> <th>VOLTS:</th> <th>PHASE:</th> <th>AMPS:</th> </tr> </thead> <tbody> <tr> <td>1: 120</td> <td>1</td> <td>4</td> </tr> <tr> <td>2: --</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			VOLTS:	PHASE:	AMPS:	1: 120	1	4	2: --	--	--	<table border="1"> <thead> <tr> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> </tr> </thead> <tbody> <tr> <td>60</td> <td>NO</td> <td>YES</td> </tr> </tbody> </table>			HZ:	HZ SWITCH:	DEPENDENT:	60	NO	YES	<table border="1"> <thead> <tr> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>--</td> </tr> </tbody> </table>			BTUs / HR:	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:																																						
EA	33	84	28	71	175 lb 80 kg																																						
VOLTS:	PHASE:	AMPS:																																									
1: 120	1	4																																									
2: --	--	--																																									
HZ:	HZ SWITCH:	DEPENDENT:																																									
60	NO	YES																																									
BTUs / HR:																																											
--																																											
M8315	6530	Table, Traction, Physical Therapy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--																									
<p>Physical therapy traction table. Upholstered table top with a removable non-friction rolling lumbar section for smooth efficient traction. Mounting board is height adjustable. Some tables include traction units. Used in physical therapy during traction treatments.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>38</td> <td>97</td> <td>28</td> <td>71</td> <td>310 lb 141 kg</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	EA	38	97	28	71	310 lb 141 kg	<table border="1"> <thead> <tr> <th>VOLTS:</th> <th>PHASE:</th> <th>AMPS:</th> </tr> </thead> <tbody> <tr> <td>1: 120</td> <td>1</td> <td>4</td> </tr> <tr> <td>2: --</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			VOLTS:	PHASE:	AMPS:	1: 120	1	4	2: --	--	--	<table border="1"> <thead> <tr> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> </tr> </thead> <tbody> <tr> <td>60</td> <td>NO</td> <td>YES</td> </tr> </tbody> </table>			HZ:	HZ SWITCH:	DEPENDENT:	60	NO	YES	<table border="1"> <thead> <tr> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>--</td> </tr> </tbody> </table>			BTUs / HR:	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:																																						
EA	38	97	28	71	310 lb 141 kg																																						
VOLTS:	PHASE:	AMPS:																																									
1: 120	1	4																																									
2: --	--	--																																									
HZ:	HZ SWITCH:	DEPENDENT:																																									
60	NO	YES																																									
BTUs / HR:																																											
--																																											
M8320	6530	Table, Treatment, Hi/Lo	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--																									
<p>Hi/lo metal treatment table. Unit consists of a hydraulic electromechanical power system operated with a hand or foot control. Includes a foam pad, upholstered top with back section adjustable to a full chair position. Adjustable height from 24" to 39". Provides easy access for patients in wheelchair or stretcher. Designed for general examinations as well as orthopedic and Ob-Gyn.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>40</td> <td>102</td> <td>27</td> <td>69</td> <td>500 lb 226 kg</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	EA	40	102	27	69	500 lb 226 kg	<table border="1"> <thead> <tr> <th>VOLTS:</th> <th>PHASE:</th> <th>AMPS:</th> </tr> </thead> <tbody> <tr> <td>1: 120</td> <td>1</td> <td>12</td> </tr> <tr> <td>2: --</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			VOLTS:	PHASE:	AMPS:	1: 120	1	12	2: --	--	--	<table border="1"> <thead> <tr> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> </tr> </thead> <tbody> <tr> <td>60</td> <td>NO</td> <td>NO</td> </tr> </tbody> </table>			HZ:	HZ SWITCH:	DEPENDENT:	60	NO	NO	<table border="1"> <thead> <tr> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>--</td> </tr> </tbody> </table>			BTUs / HR:	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:																																						
EA	40	102	27	69	500 lb 226 kg																																						
VOLTS:	PHASE:	AMPS:																																									
1: 120	1	12																																									
2: --	--	--																																									
HZ:	HZ SWITCH:	DEPENDENT:																																									
60	NO	NO																																									
BTUs / HR:																																											
--																																											
M8325	6530	Traction Unit, Portable	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--																									
<p>Hydraulic or electric portable traction unit. The traction unit can be directly mounted to and removed from a traction table or can have its own mobile stand which clamps securely to the traction table. The unit controls treatment times from 1-99 minutes with hold times up to 60 seconds. Traction can be increased in gradual steps. The unit incorporates as many as four treatment modes and features a pulling force from 0 to 200 lbs. The unit can also be used with a treatment table, chair or hospital bed.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>16</td> <td>41</td> <td>20</td> <td>51</td> <td>100 lb 46 kg</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	EA	16	41	20	51	100 lb 46 kg	<table border="1"> <thead> <tr> <th>VOLTS:</th> <th>PHASE:</th> <th>AMPS:</th> </tr> </thead> <tbody> <tr> <td>1: 120</td> <td>1</td> <td>4</td> </tr> <tr> <td>2: --</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			VOLTS:	PHASE:	AMPS:	1: 120	1	4	2: --	--	--	<table border="1"> <thead> <tr> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> </tr> </thead> <tbody> <tr> <td>60</td> <td>NO</td> <td>YES</td> </tr> </tbody> </table>			HZ:	HZ SWITCH:	DEPENDENT:	60	NO	YES	<table border="1"> <thead> <tr> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>--</td> </tr> </tbody> </table>			BTUs / HR:	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:																																						
EA	16	41	20	51	100 lb 46 kg																																						
VOLTS:	PHASE:	AMPS:																																									
1: 120	1	4																																									
2: --	--	--																																									
HZ:	HZ SWITCH:	DEPENDENT:																																									
60	NO	YES																																									
BTUs / HR:																																											
--																																											
M8326	6530	Traction Unit, Hydraulic, Low Back	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--																									
<p>Table mounted, hydraulic, low back traction unit. Traction unit package includes: traction machine, table, stand and timer. The traction machine incorporates four treatment modes and features a pulling force from 0 to 200 lbs. Complete for low back traction setup for the hospital, clinic or office settings.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>38</td> <td>97</td> <td>28</td> <td>71</td> <td>350 lb 159 kg</td> </tr> </tbody> </table>			UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:	EA	38	97	28	71	350 lb 159 kg	<table border="1"> <thead> <tr> <th>VOLTS:</th> <th>PHASE:</th> <th>AMPS:</th> </tr> </thead> <tbody> <tr> <td>1: 120</td> <td>1</td> <td>10</td> </tr> <tr> <td>2: --</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			VOLTS:	PHASE:	AMPS:	1: 120	1	10	2: --	--	--	<table border="1"> <thead> <tr> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> </tr> </thead> <tbody> <tr> <td>60</td> <td>NO</td> <td>YES</td> </tr> </tbody> </table>			HZ:	HZ SWITCH:	DEPENDENT:	60	NO	YES	<table border="1"> <thead> <tr> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>--</td> </tr> </tbody> </table>			BTUs / HR:	--
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT:																																						
EA	38	97	28	71	350 lb 159 kg																																						
VOLTS:	PHASE:	AMPS:																																									
1: 120	1	10																																									
2: --	--	--																																									
HZ:	HZ SWITCH:	DEPENDENT:																																									
60	NO	YES																																									
BTUs / HR:																																											
--																																											

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
M8330	6515	Treadmill, Electric	C C C C --	--	A	--	--	--	--						
Electric treadmill. Unit consists of a strong steel frame with front and side handrails covered with foam rubber, a remote control unit and a moving belt with a speed range from 0 to 10 mph. The unit also has a patient-controlled start/stop switch and a resettable distance counter. The motor controls the belt speed and changes the elevation of one end of the treadmill up to a 20 degree incline. The unit can be used as an exercise/therapy apparatus or in the practice of preventive medicine. Because of their power requirements, treadmills are also available as 208V powered units. At 110V, a treadmill may require a dedicated circuit. Refer to the manufacturer's literature and the specific installation site for deciding which voltage to use. See JSN M8185 for treadmill/electrocardiography systems used in cardiology studies.															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			61	155	81	500 lb 227 kg	1: 120	1	20	60	NO	YES	--		
M8331	6515	Treadmill, Weight Bearing System	C C C C --	--	--	--	--	--	--						
Incremental weight bearing system. Unit is used to limit weight bearing while exercising on a treadmill. Includes frame, harness, sensor, controller and side pads. [Does not include a treadmill. No other source (s) identified with this description/specification.]															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			94	239	114	200 lb 91 kg	1: --	1	3	0	NO	NO	--		
M8335	6515	Exerciser, Continuous Passive Motion (CPM)	C C C C --	--	A	--	--	--	--						
Continuous passive motion exerciser (CPM). The unit provides mobilization of a patient's limbs with little or no effort required by the patient. The exerciser is used postoperatively to mobilize knees or shoulders to reduce recovery time and speed ambulation of the patient. The unit is motor driven and may be adjusted to fit a variety of patients. The exerciser also includes adjustments for limiting the range of motion. [No other source(s) identified with this description/specification.]															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			20	51	30	35 lb 16 kg	1: 120	1	5	60	NO	YES	--		
M8500	6515	Nasopharyngoscope, Fiberoptic, Examination Only	C C C C --	--	--	--	--	--	--						
Flexible nasopharyngoscope for examination of the upper nose and pharynx. Unit consists of a thin flexible casing with light guides, an objective lens with an optical image fiber cluster, an eyepiece and a cable for connection to a light source. Unit is used for imaging only and does not include an instrument channel. Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8605-M8607 for supporting equipment. [No other source(s) identified with this description/specification.]															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			6	15	5	5 lb 3 kg	1: --	--	--	--	NO	NO	--		
M8501	6515	Nasopharyngoscope, Fiberoptic, Therapeutic	C C C C --	--	--	--	--	--	--						
Flexible fiberoptic nasopharyngoscope. Unit consists of a thin flexible casing with a suction adapter, a disposable suction valve, an instrument channel, light guides, an objective lens with an optical image fiber cluster, an eyepiece and a cable for connection to a light source. Unit is designed for exploration and surgical procedures in the nose and pharynx of children and adults. Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8605-M8607 for supporting equipment.															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			6	15	15	10 lb 5 kg	1: --	--	--	0	NO	NO	--		
M8502	6515	Bronchoscope, Fiberoptic, Examination Only	C C C C --	--	--	--	--	--	--						
Flexible fiberoptic bronchoscope. This scope is designed for bronchial observation/exploration only. Unit consists of a thin flexible casing with light guides, an objective lens with optical image fiber cluster, an eyepiece and a cable for connection to a light source. The eyepiece may include an automatic camera shutter feature. [See JSNs M8503 and M8504. For supporting equipment refer to JSNs M8516, M8550, M8555-M8557, M8600, and M8605- M8607.]															
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			6	15	15	5 lb 3 kg	1: --	--	--	0	NO	NO	--		

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
M8503	6515	Bronchoscope, Fiberoptic, Therapeutic	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Flexible fiberoptic bronchoscope. This scope is designed for bronchial exploration, volume washings, large biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, a disposable suction valve, an instrument channel, light guides, an objective lens with an optical image fiber cluster, an eyepiece and a cable for connection to a light source. Casings and instrument channels can have varying dimensions depending on bronchoscope design and intended procedure. May feature dual instrument channels for more complex procedures. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8605-M8607 for supporting equipment.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:			
EA		IN:	6	2	33	5 lb	1:	--	--	--	NO	--			
		CM:	15	5	84	3 kg	2:	--	--	--	NO	--			
M8504	6515	Bronchoscope, Video, Therapeutic	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Flexible fiberoptic bronchoscope. This scope is designed to function with video equipment and for bronchial exploration, washings, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, a disposable suction valve, an instrument channel, light guides, an objective lens with a charge-coupled device (CCD) chip, electronic image cable and a cable for connection to the light source and video equipment. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8610-M8611 for supporting equipment.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:			
EA		IN:	6	2	33	5 lb	1:	--	--	--	NO	--			
		CM:	15	5	84	3 kg	2:	--	--	--	NO	--			
M8505	6515	Bronchoscope, Fiberoptic, Adult, Slim Casing	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Flexible fiberoptic bronchoscope. This scope is designed for bronchial exploration, washings, biopsy and suctioning. The bronchoscope consists of a thin submersible operating section with a suction adapter, a disposable suction valve, an instrument channel, light guides, an optical image fiber cluster and an automatic camera shutter/eyepiece. The bronchoscope's slimmer casing size allows for upper bronchial tree observations. [This item is a subset of the bronchoscope classification at JSN M8503. Refer to JSNs M8550, M8600, M8605 or M8610 for supporting equipment.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:			
EA		IN:	6	6	33	5 lb	1:	--	--	--	NO	--			
		CM:	15	15	84	3 kg	2:	--	--	--	NO	--			
M8506	6515	Bronchoscope, Fiberoptic, Adult, Large Channel	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Flexible fiberoptic bronchoscope. This scope is designed for bronchial washings, biopsy or suctioning. The scope consists of a headpiece, a thin flexible casing and connections to a light source, suction apparatus or other instruments. The headpiece includes an observation lens, a suction adapter and an automatic camera shutter. The flexible casing houses the fiberoptic bundles for illumination and observation, a suction tube and an instrument channel. The larger diameter instrument channel enhances therapeutic capabilities. [This instrument is a subset of the bronchoscope classification at JSN M8503. Refer to JSNs M8550, M8600, M8605 or M8610 for supporting equipment.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:			
EA		IN:	6	2	33	5 lb	1:	--	--	--	NO	--			
		CM:	15	5	84	3 kg	2:	--	--	--	NO	--			
M8507	6515	Bronchoscope, Fiberoptic, Pediatric	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Flexible fiberoptic bronchoscope for pediatric use. This scope is designed for bronchial washings, biopsy or suctioning. The scope consists of a headpiece, a thin flexible casing and connections to a light source, suction apparatus or other instruments. The headpiece includes an observation lens, a suction adapter and an automatic camera shutter. The flexible casing houses the fiberoptic bundles for illumination and observation, a suction tube and an instrument channel. [This instrument is a subset of the bronchoscope classification at JSN M8503. Refer to JSNs M8550, M8600, M8605 or M8610 for supporting equipment.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:	BTUs / HR:			
EA		IN:	6	3	33	5 lb	1:	--	--	--	NO	--			
		CM:	15	8	84	3 kg	2:	--	--	--	NO	--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
M8508	6515	Bronchoscope, Fiberoptic, Adult	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Flexible fiberoptic bronchoscope. The scope consists of a headpiece, a thin flexible casing and connections to a light source, suction apparatus or other instruments. The headpiece includes an observation lens, a suction adapter and an automatic camera shutter. The flexible casing houses the fiberoptic bundles for illumination and observation, a suction tube and an instrument channel. The scope is designed for bronchial washings, biopsy or suctioning. Refer to JSNs M8550, M8600, M8605 or M8610 for supporting equipment. [This equipment is a subset of the bronchoscope classification at JSN M8503.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
			3	3	33	3 lb	1:	--	--	--									
			8	8	84	2 kg	2:	--	--	--									
M8510	6515	Colonoscope, Fiberoptic, Therapeutic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Flexible fiberoptic colonoscope. This scope is designed for colon/large intestine exploration, washing, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, light guides, an air/water channel, an objective lens with an optical image fiber cluster, an eyepiece and a cable for connection to a light source. Casings and instrument channels can have varying dimensions depending on colonoscope design and intended procedure. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8605-M8607 for supporting equipment.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
			6	6	78	10 lb	1:	--	--	--									
			15	15	198	5 kg	2:	--	--	--									
M8511	6515	Colonoscope, Video, Therapeutic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Flexible fiberoptic video colonoscope. This scope is designed to function with video equipment and for colon/large intestine exploration, washing, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, light guides, an air/water channel, an objective lens with a charge-coupled device (CCD) chip, electronic image cable and a cable for connection to the light source and video equipment. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8610-M8611 for supporting equipment.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
			6	6	82	10 lb	1:	--	--	--									
			15	15	208	5 kg	2:	--	--	--									
M8512	6515	Duodenoscope, Video, w/Accessories	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Flexible fiberoptic video duodenoscope. This scope is designed to function with video equipment and for duodenal exploration, washings, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, an air/water channel, a light guide, an objective lens with a charge-coupled device (CCD) chip, a forceps raiser, an electronic image cable and a cable for connection to the light source and video equipment. Casings and instrument channels can have varying dimensions depending on duodenoscope design and intended procedure. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8610-M8611 for supporting equipment.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
			6	6	61	10 lb	1:	--	--	--									
			15	15	156	5 kg	2:	--	--	--									
M8513	6515	Duodenoscope, Fiberoptic, Therapeutic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Flexible fiberoptic duodenoscope. This scope is designed for duodenal exploration, volume washings, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, an air/water channel, a light guide, an objective lens with an optical image fiber cluster, a forceps raiser, an eyepiece and a cable for connection to a light source. Casings and instrument channels can have varying dimensions depending on duodenoscope design and intended procedure. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8605-M8607 for supporting equipment.]																			
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--				
			6	6	63	10 lb	1:	--	--	--									
			15	15	161	5 kg	2:	--	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES																		
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6							
M8514	6515	Duodeno/Choledochoscope System, Mother/Daughter	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--							
		Flexible fiberoptic mother/daughter duodenoscopy/choledochoscope system. Unit consists of a mother endoscope with an instrument channel large enough to allow passage of a second (daughter) endoscope. The mother scope consists of a thin flexible casing with an air/water channel, a suction adapter, an instrument channel with elevating forceps, a light guide, an objective lens with an optical image fiber cluster, an eyepiece and a cable for connection to a light source. The daughter scope consists of a thinner flexible casing which contains light guides, an objective lens with optical image fiber cluster and an instrument channel. [Different models and combinations of scopes will have varying degrees of flexion and fields of view. Refer to manufacturers' specifications. Physical dimensions refer to the daughter scope since it is the longer of the two. The weight is the combined weight of the two scopes. This scope combination requires twice the support equipment as a single endoscope. Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8605-M8607 for supporting equipment. No other source(s) identified with this description/specification.]																							
		UNIT OF ISSUE:	EA	IN:	6	WIDTH	6	DEPTH	86	WEIGHT	20 lb	VOLTS	1:	--	PHASE	--	AMPS	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	
		EA	CM:	15	15	219	9 kg	2:	--	--	--	DEPENDENT:	NO	--	--	--	NO	--	NO	--	NO	--	--	--	
M8515	6515	Gastroscope, Fiberoptic, Therapeutic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
		Flexible fiberoptic gastroscope. This scope is designed for gastrointestinal exploration, cleaning, biopsy, tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, light guides, an objective lens with an optical image fiber cluster, an air/water channel, an eyepiece and a cable for connection to a light source. Casings and instrument channels can have varying dimensions based on gastroscope design and intended procedure. Some scopes feature dual instrument channels for more complex procedures. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8605-M8607 for supporting equipment.]																							
		UNIT OF ISSUE:	EA	IN:	6	WIDTH	6	DEPTH	53	WEIGHT	10 lb	VOLTS	1:	--	PHASE	--	AMPS	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	
		EA	CM:	15	15	135	5 kg	2:	--	--	--	DEPENDENT:	NO	--	--	--	NO	--	NO	--	NO	--	--	--	
M8516	6515	Heat Probe Unit, Endoscopic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
		Heat probe unit for gastrointestinal endoscopy with water container, footswitch, power cord, heat probes, soaking cup and cleaning tube. Unit uses an analog computer to control the amount of energy delivered to tissue and the depth of coagulation. [No other source(s) identified with this description/specification. Refer also to the related electrosurgical apparatuses at JSN M8556. This item is also a component of the JSN M8605-M8607 and M8610-M8611 endoscopy carts.]																							
		UNIT OF ISSUE:	EA	IN:	8	WIDTH	10	DEPTH	13	WEIGHT	15 lb	VOLTS	1:	120	PHASE	1	AMPS	1	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--	
		EA	CM:	21	25	34	7 kg	2:	--	--	--	DEPENDENT:	YES	--	--	--	NO	YES	60	NO	YES	--	--		
M8517	6515	Enteroscope, Fiberoptic, Therapeutic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
		Flexible fiberoptic enteroscope. This scope is designed for small bowel exploration, washing, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, light guides, an air/water channel, an objective lens with an optical image fiber cluster, an eyepiece and a cable for connection to a light source. Casings and instrument channels can have varying dimensions depending on enteroscope design and intended procedure. Sonde-type scopes feature a second water channel for balloon cuff inflation. [Refer also to the video enteroscopes at JSN M8519. Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8605-M8607 for supporting equipment.]																							
		UNIT OF ISSUE:	EA	IN:	6	WIDTH	6	DEPTH	110	WEIGHT	15 lb	VOLTS	1:	--	PHASE	--	AMPS	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	
		EA	CM:	15	15	279	7 kg	2:	--	--	--	DEPENDENT:	NO	--	--	--	NO	--	NO	--	NO	--	--		
M8518	6515	Gastroscope, Video, Therapeutic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
		Flexible fiberoptic video gastroscope. This scope is designed for use with video equipment and for gastrointestinal exploration, washings, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, light guides, an air/water channel, an objective lens with a charge-coupled device (CCD) chip, electronic image cable and a cable for connection to the light source and video equipment. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8610-M8611 for supporting equipment.]																							
		UNIT OF ISSUE:	EA	IN:	6	WIDTH	6	DEPTH	56	WEIGHT	10 lb	VOLTS	1:	--	PHASE	--	AMPS	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	
		EA	CM:	15	15	141	5 kg	2:	--	--	--	DEPENDENT:	NO	--	--	--	NO	--	NO	--	NO	--	--		

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I R A F A H						UTILITIES					
				1	2	3	4	5	6						
M8519	6515	Enteroscope, Video, Therapeutic	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Flexible fiberoptic video enteroscope. This scope is designed for use with video equipment and for small bowel exploration, washing, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, an air/water channel, light guides, an objective lens with a charge-coupled device (CCD) chip, an electronic image cable and a cable for connection to the light source and video equipment. [No other source(s) identified with this description/specification. Database pricing refers to the most expensive of this series of enteroscopes. Physical dimensions are from the largest instrument in the series. Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8610-M8611 for supporting equipment.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	6	6	98	15 lb	1:	--	--	--	NO				
		CM:	15	15	250	7 kg	2:	--	--	--	NO		--		
M8520	6515	Laparoscope	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Place Holder. Specifications to be provided by the SEPS equipment committee.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	--	--	--	-- lb	1:	--	--	--	0				
		CM:	--	--	--	-- kg	2:	--	--	--	NO		--		
M8525	6515	Laser, Surgical, CO2, Mobile	C C C C --	--	D	--	--	--	--	--	--	--	--	--	--
CO2, mobile, surgical laser. Unit consists of a laser tube containing the laser medium laser pump, cooling system and an aiming system enclosed in a wheeled steel frame. Unit delivers up to 80 watts-on tissue. It includes a microprocessor based control, variable operation and delivery modes, regulated gas system and a spring-balanced articulated arm. Designed for a variety of therapeutic procedures, to create a surgical incision, to excise or necrose deeper tissues or for ablation of delicate tissue. [The Nidek UniPulse CO2 laser (Nidek Inc., Cage Code SR190) provides a wide range of surgical applications but is limited to 40 watts.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	81	22	22	290 lb	1:	120	1	20	60				
		CM:	206	56	56	132 kg	2:	--	--	--	NO		--		
M8526	6515	Laser, Pulsed Dye	C C C C --	--	C	--	--	--	--	--	--	--	--	--	--
Pulsed dye laser used in the dermatology service. This laser is flash lamp-excited pulsed dye.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	45	20	32	300 lb	1:	230	1	30	60				
		CM:	114	51	81	137 kg	2:	--	--	--	YES		--		
M8527	6515	Laser, Surgical, KTP	C C C C --	--	C	--	--	--	--	--	--	--	--	--	--
KTP, mobile, surgical laser. Unit consists of a laser tube containing the medium laser pump, cooling system, and aiming system, enclosed in a wheeled steel frame. Unit delivers 50 milli-Watts to 36 watts at resonator. It includes a microprocessor based control, variable operation and delivery modes, regulated gas system, and a spring-balanced articulated arm. Designed for a variety of therapeutic procedures, to create a surgical incision, to excise or necrose deeper tissues. [Price difference verified. Price can vary based on delivery devices selected. In some instances the delivery unit can exceed the price of the base laser unit. The base price for Model 3 is \$80,000 with the delivery devices approximately \$40,000 on average for unit sales.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	77	23	39	625 lb	1:	208	1	50	60				
		CM:	196	58	99	284 kg	2:	--	--	--	NO		--		
M8530	6515	Microscope, Operating, Ceiling Mounted	C C C C --	--	F	--	--	--	--	--	--	--	--	--	--
Ceiling mounted operating microscope. Unit consists of a binocular microscope body equipped with a range of available accessories for co-observation, documentation and illumination, motorized zoom and precision focusing system. Foot-pedal controlled. Unit is held by an adjustable arm attached to a ceiling support mechanism. For multi-specialty use (ENT, ophthalmological, neuro surgery, reconstructive surgery). [No other source(s) identified with this description/specification.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:				
EA		IN:	--	--	--	132 lb	1:	120	1	10	60				
		CM:	--	--	--	60 kg	2:	--	--	--	NO		--		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M8534	6515-II-000-2491	Microscope, Operating, Portable, General Use	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Portable operating microscope complete with objectives and stand. Unit consists of a binocular microscope body equipped with a range of accessories for co-observation, documentation and illumination. Control knobs equipped with sterilizable handles. Mounted on a large swinging-arm stand. Used in surgical procedures for magnification of the operating field. Can be configured for different specialty use (ENT, hand surgery, etc.).</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			73	56	28	537 lb	1:	120	1	8	60	YES	--					
			186	143	72	244 kg	2:	--	--	--	NO	--	--					
M8535	6515-II-000-2491	Microscope, Operating, Portable	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Portable operating microscope complete with objectives and stand. Unit consists of a binocular microscope body equipped with a range of accessories for co-observation, documentation and illumination. Control knobs equipped with sterilizable handles. Mounted on a large swinging-arm stand. For examinations and diagnosis in medical consultancies and as a laboratory training instrument. Configured for use primarily for eye and neuro surgery.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			64	25	25	132 lb	1:	120	1	6	60	NO	--					
			162	64	64	60 kg	2:	--	--	--	NO	--	--					
M8540	6530	Microscope, Operating, Wall Mounted	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Wall mounted operating microscope. Unit consists of a binocular microscope body mounted to a wall support. A magnification changer to determine the magnification ratio is enclosed in the body tube of the microscope. The lens system consists of a range of objectives from 3 to 15 in 5 steps. Includes a fiberoptic halogen light source with beam-splitter, manual or pedal focusing controls and zoom capabilities. Used in clinics, hospitals and doctor's offices during surgery to clarify the surgeon's view of microscopic structures.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			36	60	60	77 lb	1:	120	1	2	60	NO	--					
			91	152	152	35 kg	2:	--	--	--	YES	--	--					
M8545	6515	Sigmoidoscope, Fiberoptic, Therapeutic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Flexible fiberoptic sigmoidoscope. This scope is designed for colon (sigmoid bend) exploration, washing, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, light guides, an air/water channel, an objective lens with an optical image fiber cluster, an eyepiece and a cable for connection to a light source. Casings and instrument channels can have varying dimensions depending on scope design and intended procedure. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8605-M8607 for supporting equipment.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			6	6	37	10 lb	1:	--	--	--	--	NO	--					
			15	15	94	5 kg	2:	--	--	--	NO	--	--					
M8546	6515	Sigmoidoscope, Video, Therapeutic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Flexible fiberoptic sigmoidoscope. This scope is designed for use with video equipment and for lower colon (sigmoid bend) exploration, washing, biopsy or tissue removal and suctioning. Unit consists of a thin flexible casing with a suction adapter, an instrument channel, light guides, an air/water channel, an objective lens with a charge-coupled device (CCD) chip, electronic image cable and a cable for connection to the light source and video equipment. [Refer to JSNs M8516, M8550, M8555-M8557, M8600 and M8610-M8611 for supporting equipment.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			42	6	6	10 lb	1:	--	--	--	--	NO	--					
			107	15	15	5 kg	2:	--	--	--	NO	--	--					
M8550	6515	Light Source, Fiberoptic, Endoscopy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Fiberoptic light source for endoscopy procedures. Unit includes variable air control system, built-in emergency lamp, built-in automatic exposure system, set point memory and lock button. Built-in LED indicator. [This item may also a component of the M8605-M8607 and M8610-M8611 endoscopy carts. No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			7	23	21	48 lb	1:	120	1	3	60	NO	--					
			18	58	53	22 kg	2:	--	--	--	YES	--	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M8551	6515	Light Source, Fiberoptic Headlamp	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Fiberoptic light source for surgical headlamps. This unit provides color corrected light for surgical procedures where photography is not required.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	7	18	12	20 lb	1:	120	1	6	NO		--					
		CM:	18	46	30	9 kg	2:	--	--	--	NO		--					
M8552	6515	Source,Light, Fiberoptic Headlamp w/Camera Control	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
High resolution head mounted camera with choice of at least three lenses (7.5mm, 15mm, 24mm), a headlight module, adjustable head band and replaceable sweat pads. Unit includes a high quality fiberoptic cable, 300 Watt Xenon light source with choice of 3 rotary turrets that permit attachment to any headlight instrument or endoscope for added flexibility. Mobile stand and carrying case for camera are also available. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	54	12	8	33 lb	1:	120	1	7	NO		--					
		CM:	137	30	20	15 kg	2:	--	--	--	NO		--					
M8555	6515	Insufflator, Automatic Controls	C	C	C	C	--	--	A	--	E	--	--	--	--	--	--	--
Automatic controlled insufflator is used to infuse CO2 during endoscopic and laser surgery. Unit provides controlled pressure of CO2 within the cavity of interest and eliminates air from the site. This item is also a component of the JSN M8605-M8607 and M8610-M8611 endoscopy carts.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	7	14	13	22 lb	1:	120	1	1	NO		--					
		CM:	18	36	34	10 kg	2:	--	--	--	YES		--					
M8556	6515	Electrosurgical Unit, Endoscopy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Electrosurgical unit for endoscopy procedures. Unit is designed for tissue cutting, coagulation, polyp removal and general surgical procedures. Unit produces varying radio frequency electric current waveforms (cut, blended, coagulation), for different treatment procedures. Unit can support monopolar and bipolar electrosurgical instruments and includes a safety system which shuts off current if leads or cables are improperly connected. This unit is also a component of the M8605-M8607 and M8610-M8611 endoscopy carts. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	7	15	15	31 lb	1:	120	1	9	NO		--					
		CM:	18	38	37	14 kg	2:	--	--	--	YES		--					
M8557	6515	Suction Unit, Endoscopy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Suction unit for endoscopy procedures. Unit works with a wide variety of fiberoptic and video endoscopes. This unit is also a component of the JSN M8605-M8607 and M8610-M8611 endoscopy carts. [Numerous distributors found for this item, but only one manufacturer. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	16	16	12	25 lb	1:	120	1	1	NO		--					
		CM:	41	41	30	12 kg	2:	--	--	--	YES		--					
M8600	6515	Workstation, Endoscopy Video Documentation	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Networked endoscopy video enhancement and documentation system which allows the images from several endoscopy procedure rooms to be recorded and saved for later review. System permits remote activation from the procedure room and recall of previous procedures for comparison. Patient data and images are integrated on the system along with physician notes. The system prints text reports and color graphic images in a variety of formats. System consists of an image processing unit at each endoscopy location, a scheduling console, a central image management console, data storage devices and one or more remote reporting consoles. Each system is specifically designed for its installed location and system cost will vary. Database pricing is for a 10-user system including a network station, software, a color printer, a text printer, a medical grade monitor, a network server, an archive server, Ethernet hubs, tape backups, processor upgrades, charting system, optical storage devices, remote patient registration station, workstation monitor upgrade, slide maker, power supply, cabling and device racks. Electrical requirements and physical dimensions refer to the network station and archive server only. [Prices shown are estimates only and can vary significantly based on actual user requirements. No other source(s) identified with this description/specification.]																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES							
			A	N	A	V	R	A	F	A	H	1	2	3
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:	
			EA	CM:	--	--	-- lb	120	1	15	60	NO	--	
							-- kg	2:	--	--	DEPENDENT:	YES	--	
M8605	6515	Endoscopy Cart, Fiberoptic, Basic	C	C	C	C	--	--	A	--	E	--	--	
			Endoscopic procedure cart. System contains a cart, light source, heat probe unit, electrosurgical unit, insufflator and a suction pump. This cart does not contain an endoscope or video equipment and does not support video endoscopes. Refer to JSNs M8500-M8550 for endoscopes and JSNs M8606-M8607 for fiberoptic endoscope video carts. Each cart can support one or more types of endoscopes and should be specifically tailored to its intended use. Database pricing and physical information are for a higher cost system which contains one of each of the above components. [No other source(s) identified with this description/specification.]											
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:	
			EA	CM:	48	31	23	200 lb	120	1	15	60	NO	
							91 kg	2:	--	--	DEPENDENT:	YES	--	
M8606	6515	Endoscopy Cart, Fiberoptic, w/Video Accessories	C	C	C	C	--	--	A	--	E	--	--	
			Endoscopy cart with video and print capabilities for use with fiberoptic (direct vision) endoscopes. This cart does not work with videoscopes. System takes optical images from a single endoscope and directly records them or converts them to digital signals for recording. A typical system cart includes the cart, a light source, an insufflator, a suction unit, a heat probe unit, an electrosurgical apparatus, a digital camera converter or color video camera, a camera controller, a monitor, a video recorder and a color printer. This JSN does not include the endoscope; refer to the endoscopes at JSNs M8500-M8550. Each cart can support one or more types of endoscope and should be specifically tailored to its intended use(s). This cart can be configured to interface with a network endoscopy information management system; refer to JSN M8600. Database physical information and pricing is for a higher cost system containing one of each of the above components. [Cost per unit will vary depending on final equipment configuration. No other source(s) identified with this description/specification.]											
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:	
			EA	CM:	64	36	30	300 lb	120	1	20	60	NO	
							137 kg	2:	--	--	DEPENDENT:	YES	--	
M8607	6515	Endoscopy Cart, Fiberoptic, w/Video, Info. Mgmt.	C	C	C	C	--	--	A	--	E	--	--	
			Endoscopy cart with video, print and information management capabilities for use with fiberoptic (direct vision) endoscopes. This cart does not work with videoscopes. System takes optical images from a single endoscope and directly records them or converts them to digital signals for recording and enhancement. A typical system includes two carts, a light source, an insufflator, a suction unit, an electrosurgical apparatus, a heat probe unit, a digital camera converter, a camera controller, a monitor, a video recorder, a computer system with software, a digital slide making system and a color printer. This JSN does not include the endoscope; refer to the endoscope JSNs from M8500-M8550. Each cart can support one or more types of endoscopes and should be specifically tailored to its intended use. This cart is intended for stand alone use although it may be connected to an endoscopy information management system. Database physical information and pricing is for a high end system on two carts containing one of each of the mentioned components. The electrical power draw will require two separate circuits. [No other source(s) identified with this description/specification.]											
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:	
			EA	CM:	64	48	33	400 lb	120	1	28	60	NO	
							182 kg	2:	--	--	DEPENDENT:	YES	--	
M8610	6515	Endoscopy Cart, Video (CCD) Scope	C	C	C	C	--	--	A	--	E	--	--	
			Video support system for endoscopes which have a charge coupled device (CCD) camera chip or similar technology embedded in the distal end of the endoscope. This system does not support direct observation fiberoptic endoscopes. Refer to JSNs M8505-M8507 for fiberoptic endoscope carts. A typical cart system includes the cart, a light source, an insufflator, a suction unit, a heat probe unit, an electrosurgical apparatus, a video controller, a monitor, a video recorder and a color printer. This JSN does not include the endoscope; refer to the endoscopes at JSNs M8500-M8550. Each cart can support one or more types of video endoscope and should be specifically tailored to its intended use(s). This cart can be configured to interface with a network endoscopy information management system; refer to JSN M8600. Database physical information and pricing is for a higher cost system containing one of each of the above components. Electrical draw may require two separate electrical circuits to support one cart. [No other source(s) identified with this description/specification.]											

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	72	36	36	200 lb	120	1	21	60	NO	--		
				CM:				2:			DEPENDENT:				
			EA	183	91	91	91 kg	--	--	--	YES	--			
M8611	6515	Endoscopy Cart, Video (CCD) Scope, with Info. Mgmt	C	C	C	C	--	--	A	--	E	--	--		
		Endoscopy cart with video, printing and information management capabilities for use with endoscopes which have a charge coupled device (CCD) camera chip or similar technology embedded in the distal end of the endoscope. This system does not support direct observation fiberoptic endoscopes. Refer to JSNs M8505-M8507 for the correct carts. A typical system includes two carts, a light source, an insufflator, a suction unit, an electrosurgical apparatus, a heat probe unit, a control unit, a monitor, a video recorder, a computer system with software, a digital slide making system and a color printer. This JSN does not include the endoscope; refer to the endoscope JSNs from M8500-M8550. Each cart can support one or more types of endoscopes and should be specifically tailored to its intended use. This cart is intended for stand alone use although it may be connected to an endoscopy information management system; refer to JSN M8600. Database physical information and pricing is for a high end system on two carts containing one of each of the mentioned components. The electrical power draw will require two separate circuits. [No other source(s) identified with this description/specification.]													
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
		EA	74	43	25	400 lb	120	1	28	60	NO	--			
			CM:				2:			DEPENDENT:					
		EA	188	109	64	182 kg	--	--	--	YES	--				
M8650	6515	System, Esophageal Motility Recording	C	C	C	C	--	--	A	--	--	--	--		
		Automated esophageal motility recording and analysis system. The system provides automated standard protocols for motility monitoring and records the results of tests. The system performs analysis of the results, generation of clinical reports and printing of the results. The system includes an infusion pump, a mechanical motility transducer system, a computer, a printer and appropriate software. Some standard packages also include a system cart. [The software for these systems is very sensitive to the exact hardware configuration. Some vendors will not guarantee their product unless they have provided or inspected the computer prior to installation. There are numerous configurations available with this system. Prices will vary based on specific user requirements.]													
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
		EA	15	19	14	30 lb	120	1	10	60	NO	--			
			CM:				2:			DEPENDENT:					
		EA	38	48	36	14 kg	--	--	--	NO	--				
M8655	6515	Recorder, Esophageal Motility, Ambulator	C	C	C	C	--	--	--	--	--	--	--		
		24 hour ambulatory one channel pH monitoring system. Unit consists of: a pH data recorder with software, 10 each disposable combination pH/reference electrodes, an adapter cable for single channel operation using disposable electrodes, 4.00 pH buffer solution, a 9-V DC alkaline battery, a computer interface cable with a 25 pin serial port and pH analysis software (IBM or compatible). For successful operation this system requires the use of a computer, see JSN M1800. [No other source(s) identified with this description/specification. Units are powered by one 9-volt and or one AA battery. Medtronic (Cage Code OHZR5) also offers this configuration with a lap top version for \$17,784.00 part # Digi 400 DX.]													
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
		EA	1	5	6	1 lb	--	--	--	--	NO	--			
			CM:				2:			DEPENDENT:					
		EA	3	13	15	1 kg	--	--	--	NO	--				
M8665	6515	Analyzer, Hydrogen, Breath	C	C	C	C	--	--	A	--	--	--	--		
		Hydrogen breath analyzer offers a reliable, non-invasive test for carbohydrate, malabsorption, bacterial overgrowth and intestinal transit time which accurately measures parts per million (PPM) hydrogen in alveolar air. These analyzers typically use electrochemical or gas chromatography measuring methods. [Model 1 is a sophisticated analyzer primarily used in a laboratory. Models 2 and 3 are used in clinics as points-of-care analyzers. Model 3 is battery operated. No other source(s) could be found with this description/specification.]													
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:			
		EA	11	18	10	20 lb	120	1	1	60	NO	--			
			CM:				2:			DEPENDENT:					
		EA	28	46	25	9 kg	--	--	--	NO	--				

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I R A F A H						UTILITIES 1 2 3 4 5 6						
M8755	6515	Aspirator, Low Pressure/Low Volume, Surgical	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Low pressure, low volume surgical aspirator. Stand mounted stainless steel unit. 1/8 HP motor with variable suction intensity. It includes 600 ml graduated collection bottle, hydrophobic bacteria filter, a precision suction regulating valve, timer and a foot regulator. For post operative surgical wound drainage and general suction use. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	33	18	17	69 lb	1:	120	1	5	60					
		CM:	84	46	43	32 kg	2:	--	--	--	NO					
											DEPENDENT: NO					
M8760	6515	Aspirator, Uterine, Mobile	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Mobile, uterine aspirator. Unit has a stainless steel top with a protective rubber bumper mounted on a mobile cabinet with casters. It includes an explosion proof motor, two 1400 cc collection bottles, vacuum gauge, vacuum control, and storage drawer. Flow range to 4.00 cu ft per minute. Used in operating rooms or other areas where curettage is necessary.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	42	27	19	135 lb	1:	120	1	5	60					
		CM:	107	69	48	62 kg	2:	--	--	--	NO					
											DEPENDENT: NO					
M8765	6515	Aspirator, Low Pressure/High Volume, Chest/Abdomen	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Low pressure, high volume suction apparatus for chest/abdomen use. Stand mounted durable stainless steel console unit. Stand includes 2 1/2" casters with chemical resistant top. Unit includes collection bottle, bacteria filter, suction regulating valve and drainage tubes. This unit provides regulation of suction from 0 to 50 cm of water for rapid removal of fluids and gas from the pleural cavity.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	33	19	20	63 lb	1:	120	1	3	60					
		CM:	84	48	51	29 kg	2:	--	--	--	NO					
											DEPENDENT: NO					
M8770	6515	Aspirator/Pressure Unit, General Purpose	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
General purpose suction/pressure apparatus. Double stainless steel console unit with a 1/8 HP motor, stand-mounted. Stands include 2 1/2" casters with chemical resistant top. Pumps suction capacity: 22 LPM. Unit includes collection bottle, bacteria filter and suction regulating valve. Used for oral/nasal, tracheal suctioning and other emergency purposes. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	33	18	17	70 lb	1:	120	1	2	60					
		CM:	84	46	43	32 kg	2:	--	--	--	NO					
											DEPENDENT: NO					
M8800	6530	Cart, Anesthesia	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Mobile anesthesia cart. The cart shall be built of stainless steel and mounted on 4" casters for easy mobility. It shall be capable of being equipped with bottles holders, adjustable IV pole, storage drawers, shelves and a top bar/rail.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	37	29	18	145 lb	1:	--	--	--	--					
		CM:	94	74	45	66 kg	2:	--	--	--	NO					
											DEPENDENT: NO					
M8805	6530	Table, Instrument, Straddle	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Instrument table to straddle an operating table. All stainless steel welded construction, mounted on 3" ball-bearing casters with foot brakes. Adjustable height from approximately 40 to 60 inches. For instruments and diagnostic equipment during surgery.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	56	48	32	160 lb	1:	--	--	--	0					
		CM:	142	122	81	73 kg	2:	--	--	--	NO					
											DEPENDENT: NO					
M8810	6530	Stand, Mayo	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	62	16	24	39 lb	1:	--	--	--	--					
		CM:	157	41	61	18 kg	2:	--	--	--	NO					
											DEPENDENT: NO					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M8815	6530	Table, Instrument/Dressing, Angular	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Angular instrument/dressing table. Heavy duty design and stainless steel construction. Tops are hemmed and bent together to form a sturdy sound-deadened surface. Mounted on electrically conductive ball-bearing casters. Designed for use in operating or procedure rooms.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	34	64	15	150 lb	1:	--	--	--	NO							
		CM:	86	162	38	68 kg	2:	--	--	--	NO							
M8820	6530	Table, Instrument/Dressing, CRS	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Mobile instrument and dressing table, approximately 34"H x 33"W x 18"D. The cart shall be built of stainless steel and mounted on 2" swivel casters for easy mobility. The unit shall include a table top and a bottom shelf with a continuous guard rail on both surfaces. [Models 1 and 3 are 20" W x 16" D.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	36	33	18	55 lb	1:	--	--	--	0							
		CM:	91	84	46	25 kg	2:	--	--	--	NO							
M8825	6530	Table, Instrument/Dressing, CRS, approx. 36x20x34	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Instrument and dressing table. Made of corrosion resistant stainless steel with a sound deadened top. Includes guard rail, shelf and two side-by-side drawers. The table is mounted on swivel, ball-bearing casters.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	34	36	20	100 lb	1:	--	--	--	0							
		CM:	86	91	51	46 kg	2:	--	--	--	NO							
M8830	6530	Table, Instrument/Dressing, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Mobile instrument/dressing table, approximately 34" H x 20" W x 16" D Corrosion resistant stainless steel mobile table with sound-deadening shelf and drawer. Unit is mounted on 2" casters. Designed for all purpose use in the hospital or clinic.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	38	21	17	45 lb	1:	--	--	--	0							
		CM:	97	53	43	20 kg	2:	--	--	--	NO							
M8900	6530	Carriage, Pail, CRS, Without Pail	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Carriage, pail (kick bucket) CRS. Consists of a stainless steel ring type carriage mounted on ball bearing casters. Includes circular non-marring bumper. For use in the surgical operating room.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	14	15	15	5 lb	1:	--	--	--	--							
		CM:	36	38	38	2 kg	2:	--	--	--	NO							
M8905	6530	Pail, Utility, CRS, Without Carriage	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Utility pail (kick bucket). Shall be a stainless steel 12 quart bucket for use in surgical operating rooms.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	14	14	14	12 lb	1:	--	--	--	--							
		CM:	36	36	36	6 kg	2:	--	--	--	NO							
M8910	6530	Cart, Surgical Case	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Surgical case cart. Unit consists of two hinged cabinet sections, each section equipped with two pull-out shelves with stops. The entire unit is mounted on six heavy duty conductive swivel casters. Used to transport surgical packs and supplies to surgery and soiled items back to central supply.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	40	57	29	285 lb	1:	--	--	--	0							
		CM:	102	145	74	130 kg	2:	--	--	--	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES											
				A	N	A	V	I	1	2	3	4	5	6	
M8915	6530	Cart, Surgical Dressing, CRS, Mobile	C C C C --	--	--	--	--	--	--	--	--	--	--	--	
Mobile surgical dressing cart. The cart has all corrosion resistant stainless steel construction. The cart is mounted on casters, has two sound-deadened shelves with solid round guard rails, a CRS basin and pail. Designed for transporting and storing of dressing supplies.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	40	53	22	100 lb	1:	--	--	--	0	NO		--	
		CM:	102	135	56	45 kg	2:	--	--	--	DEPENDENT:	NO		--	
M8920	6530-00-709-1000	Stand, Basin, CRS, Mobile, Double	C C C C --	--	--	--	--	--	--	--	--	--	--	--	
CRS, mobile, double basin stand with shelf. Stainless steel corrosion resistant frame constructed from two continuous inverted "U" shaped tubes, forming four legs and mounted on casters. Circular rings welded to top receive two removable 8 quart stainless steel basins. For open heart and other procedures.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	33	29	16	40 lb	1:	--	--	--	--	NO		--	
		CM:	84	74	41	18 kg	2:	--	--	--	DEPENDENT:	NO		--	
M8925	6530-00-700-1025	Stand, Basin, CRS, Mobile, Single	C C C C --	--	--	--	--	--	--	--	--	--	--	--	
Mobile single basin stand with shelf. The stand shall be constructed of tubular stainless steel and mounted on 2" swivel casters. Shall include a shelf and an 8 quart stainless steel basin. Intended for use in ORs and treatment areas.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	33	15	28	20 lb	1:	--	--	--	--	NO		--	
		CM:	83	38	71	9 kg	2:	--	--	--	DEPENDENT:	NO		--	
M8930	6530	Suspension Unit, Utility, Ceiling, Microsurgery	A A A A --	--	F	--	--	--	--	--	--	--	--	--	
Microsurgery ceiling suspension arm consisting of a ceiling mounted column with a power supply unit and a hydraulic control/pumping system. The unit features free movement along a track above the surgery site and operates from a hand or foot switch. The database height dimension refers to the column length. Width and depth refer to the length of the suspension arm. Depending on the weight bearing capacity of the ceiling, the track may need to be hung from the underside of the slab above. The track may need minimum ceiling height: 3.10 meters. [This item must be custom configured to meet the specific room, surgical application and optical microscope it holds. No other source(s) identified with this description/specification.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	52	48	48	264 lb	1:	120	1	15	60	NO		--	
		CM:	132	122	122	120 kg	2:	--	--	--	DEPENDENT:	YES		--	
M8940	6530	Stool, Anesthesia, With Back	C C C C --	--	--	--	--	--	--	--	--	--	--	--	
Anesthesia stool with back. All stainless steel with well-curved back panel and wide conductive seat. Designed for the anesthesiologist during surgical procedures.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	48	18	18	22 lb	1:	--	--	--	--	NO		--	
		CM:	122	46	46	10 kg	2:	--	--	--	DEPENDENT:	NO		--	
M8950	6515	Warmer, Blood	C C C C --	--	B	--	--	--	--	--	--	--	--	--	
Unit consists of a temperature regulated water bath or circulating fluid with controls and an audible high temperature alarm. The warmer provides a stable environment for the controlled warming of blood or other fluids prior to being transfused to a patient.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	61	31	24	148 lb	1:	110	1	15	60	YES		--	
		CM:	155	79	61	68 kg	2:	--	--	--	DEPENDENT:	NO		--	
M8960	6515	Cart, Surgical Case, Birthing Room	C C C C --	--	--	--	--	--	--	--	--	--	--	--	
Surgical case cart for use in birthing rooms. Unit has two cabinet sections, each section equipped with two pull-up shelves with stops. The entire unit is mounted on four heavy duty swivel casters. Used to transport surgical packs and supplies to the birthing room, and soiled items back to central supply. [No other source(s) identified with this description/specification.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	38	25	40	220 lb	1:	--	--	--	--	NO		--	
		CM:	96	64	102	100 kg	2:	--	--	--	DEPENDENT:	NO		--	

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
M8965	6515	Cart, Fetal Monitoring, Birthing Room	C C C C --	--	--	--	--	--	--	--	--	--	--
Physiological monitoring cart for use in birthing rooms. Multiple section mobile cabinet for storing monitoring equipment and bedside supplies. Includes one deep drawer and an enclosed cabinet area in addition to the monitor storage area which is equipped with a door. Monitor shelf location is waist high and includes a pull out writing surface. Cart may include CPU storage shelf.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA	CM:	IN: 48	28	27	118 lb	1:	--	--	0	NO	NO	--	
		CM: 122	71	69	54 kg	2:	--	--					
M8970	6515	Warmer, Blood, High Volume	C C C C --	--	B	--	--	--	--	--	--	--	--
Unit contains a proportional controller to regulate temperature in the heat exchanger and an audible high temperature alarm. Designed to provide a stable temperature for the controlled warming of blood or other fluids prior to being transfused to a patient. Unit may be a cuff type or circulating water heat exchanger. [No other source(s) identified with this description/specification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA	CM:	IN: 45	14	14	30 lb	1:	115	1	60	YES	NO	--	
		CM: 114	36	36	14 kg	2:	--	--					
M9010	6530	Table, Casting	C C C C --	--	--	--	--	--	--	--	--	--	--
Unit is equipped to accommodate hip pinning and hip spica procedures. It includes a transverse A-P cassette tunnel, a foot operated brake pedal and leg spar and traction controls. The unit is height adjustable and is mounted on four conductive swivel casters. To be used during casting procedures. [Recommend JSN M9010 be deleted. Getinge/Castle no longer offer this item as described. JSN M9075, Table, Operating, Fracture, Orthopedic, meets the descriptive requirements of JSN M9010.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA	CM:	IN: --	--	--	-- lb	1:	--	--	--	NO	NO	--	
		CM: --	--	--	-- kg	2:	--	--					
M9012	6530	Table, Treatment/Casting, Heavy Duty	C C C C --	--	--	--	--	--	--	--	--	--	--
Heavy duty treatment/casting table approximately 32" H X 78" D X 30" W. Detachable pad consists of 2" foam rubber. Unit has fully enclosed cabinet base with drawer and sliding doors. Comes in natural or walnut finish.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA	CM:	IN: 32	30	78	385 lb	1:	--	--	0	NO	NO	--	
		CM: 81	81	198	175 kg	2:	--	--					
M9020	6530	Table, Exam, Pediatric, With Scale	C C C C --	--	A	--	--	--	--	--	--	--	--
Pediatric exam table with scale. Cabinet type, free standing unit. It consists of one drawer and double cupboard, built-in electronic or mechanical scale and measuring tape, vinyl covered work surface and built-in paper dispenser. Equipped with protective high rim on three sides of table top. Designed for use in pediatric exam rooms. [No other source(s) identified with this description/specification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA	CM:	IN: 36	43	24	300 lb	1:	--	--	--	NO	NO	--	
		CM: 91	109	61	136 kg	2:	--	--					
M9025	6530	Table, Examination/Treatment, With Cabinet	C C C C --	--	A	--	--	--	--	--	--	--	--
Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armboard. Unit is designed for general use examination/treatment rooms.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	
EA	CM:	IN: 36	67	73	330 lb	1:	120	1	60	NO	NO	--	
		CM: 91	170	185	150 kg	2:	--	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M9030	6530	Chair, Examination/Treatment, Surgical, ENT	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>ENT examination/treatment chair. Unit is equipped with a Electro-hydraulic lift system and mounted on a swivel base. It is lockable at any point of rotation and has power controls for elevation, reclining and adjusting headrest. Footrest retracts when chair is in low position. Arms of chair swing out of way for easier patient entry and exit. For use with ear, nose and throat operating apparatus. [Depth dimension is in the fully reclined position. Height is at the raised seat level. For information the government price for Model 2, Midmark 491 is \$3,999.00.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	25	86	350 lb	1:	120	1	8	NO		--					
		CM:	91	64	218	159 kg	2:	--	--	--	NO		--					
M9035	7110-LL-000-6217	Chair/Table, Combination Unit	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Chair/table combination unit. Unit consists of an upholstered chair with foot and head sections. Unit can be operated and positioned to a table position by a hydraulic mechanism. Features "memory" power positioning, controlled by pedal switches or finger switches. Unit is designed for use in clinics, doctor's office or treatment rooms.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	42	27	76	325 lb	1:	120	1	12	NO		--					
		CM:	107	69	193	148 kg	2:	--	--	--	YES		--					
M9045		Table, Chiropractic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	A
<p>Adjustable chiropractic table with automatic and manual cocking for head, chest, lumbar and pelvic drops. Table height is adjustable from approximately 19" to 36". Table may have an air compressor to assist in flexion-distraction adjustments.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	27	84	395 lb	1:	120	1	6	NO		--					
		CM:	91	69	213	180 kg	2:	--	--	--	NO		--					
M9050	6530	Table, Exam, CRS, 2 Section	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Two section, CRS, exam table. Unit consists of a stainless steel two section tabletop. Adjustable head section, and leg holder straps. Legs are mounted on crutch tips reinforced and stabilized by "H" shaped or equivalent bracing. Exam table is designed for use in general exam rooms. [Price difference verified. These are the only manufacturers found for non-upholstered CRS exam tables. See JSNs M9025, M8300 for possible alternatives. No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	33	20	72	150 lb	1:	--	--	--	NO		--					
		CM:	84	51	183	68 kg	2:	--	--	--	NO		--					
M9055	6530	Table, Exam, Orthopedic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>Orthopedic exam table. Consists of a steel or wood frame with pull out drawers and storage area. Upholstered top section adjustable to any angle. Used for orthopedic examinations.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	31	30	78	160 lb	1:	--	--	--	NO		--					
		CM:	79	76	198	72 kg	2:	--	--	--	NO		--					
M9060	6530	Table, Minor Surgery, Pedestal, 4 Section, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
<p>A 4-section, mobile, pedestal mounted minor surgery exam table. Pedestal is mounted on a base with locking casters. Table is made from all stainless steel construction with chromium plated surfaces. Table has a foot control pedal for Trendelenburg and reverse Trendelenburg positions. Table padding is removable for cleaning. Table top consists of four hinged sections. Designed for minor operating rooms or outpatient surgery centers.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	40	22	89	690 lb	1:	--	--	--	NO		--					
		CM:	102	56	226	314 kg	2:	--	--	--	NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES										
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5
M9065	6530	Table, Examination, Proctology, Electro/Hydraulic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
<p>Electro-hydraulic proctology examination table. Unit consists of a stainless steel base with an Electro-hydraulic system and foot controls. It includes a vacuum formed vinyl contoured top, a padded arm rest, an adjustable knee rest, a stainless steel drainage pan and a built-in paper roll retainer/cutter. The table is designed for proctology, urology and OB/GYN exams.</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	45	27	84	550 lb	1:	120	1	12	NO		--				
		CM:	114	69	213	250 kg	2:	--	--	--	YES		--				
M9066	6530	Table, Examination, Treatment, Electro/Hydraulic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
<p>Electro-hydraulic examination treatment table. Unit consists of a stainless steel base with an Electro-hydraulic system with foot controls. It includes vacuum formed vinyl contoured top, padded arm rest, adjustable knee rest, stainless steel drainage pan and built-in paper roll retainer/cutter. Designed for general use in treatment rooms for minor surgical procedures.</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	42	27	80	550 lb	1:	120	1	20	NO		--				
		CM:	107	69	203	250 kg	2:	--	--	--	YES		--				
M9075	6530	Table, Operating, Fracture, Orthopedic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--
<p>Orthopedic and fracture repair operating table. Pedestal type table with 400 pound lifting capacity. Equipped with hydraulic controls, rotating perineal post, pelvic supports and radiographic accessories. Mounted on locking swivel casters. Accessories available to accommodate pediatric patients. Designed for casting procedures as well as orthopedic surgical procedures. [Price difference verified. Model 2 has a top rail height of 104" (see cut sheet).]</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	52	33	126	617 lb	1:	110	1	10	NO		--				
		CM:	132	84	320	280 kg	2:	--	--	--	NO		--				
M9080	6530	Table, Operating, Pedestal, 5 Section	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
<p>Pedestal type major operating table with 5 sections. Table is mounted on a solid base with casters and locks. Table top surface is fabricated from radio-translucent, conductive panels and the larger table sections are equipped with radiographic cassette tunnels. Table includes Electro-hydraulic controls, side rail locking system, kidney elevator, grounding receptacle and dual arm support section. Designed for use in the operating room in a variety of surgical procedures. [Ohio Medical Instrument Company, Inc. during 2000 acquired the Hospital Products Division of MIDMARK Corporation. Literature will reflect OMI in the future. The date is unknown.]</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	46	22	73	745 lb	1:	120	1	4	NO		--				
		CM:	117	56	185	339 kg	2:	--	--	--	YES		--				
M9095	6530	Table, Operating, Remote Control	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
<p>Remote control surgical table. Table is a stainless steel pedestal type mounted on conductive locking casters. It consists of an Electro-hydraulic system with remote control and foot pedals. Unit's positioning capabilities include lateral tilt of 30 degrees, Trendelenburg and reverse Trendelenburg. It is equipped with side rails, kidney bridge and a radio translucent top. Table is designed for a variety of procedures in the operating room.</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	44	25	89	750 lb	1:	120	1	5	NO		--				
		CM:	112	64	226	341 kg	2:	--	--	--	YES		--				
M9100	6530	Table, Procedure, Urological	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--
<p>Manual or electric tilt urological table. The unit consists of a heavy duty metal base and an upholstered patient cushion. The unit includes a screened stainless steel basin which drains into a reservoir, adjustable Bierhoff crutches, steel storage drawer(s), pullout leg rests and an adjustable foot section. The unit is equipped with foot controls for height and positioning adjustments. The table is designed for use during urological procedures, treatment, examinations and minor surgery.</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	41	27	74	650 lb	1:	120	1	12	NO		--				
		CM:	104	69	188	296 kg	2:	--	--	--	YES		--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
M9110	6530	Table, Operating, 5 or 6 Section, Trauma	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
<p>Pedestal type, 5 or 6 section, operating table. Pedestal table, mounted on a solid base with casters and locks. Table top surface is fabricated from radio-translucent and conductive panels and is equipped with cassette tunnels in each of the table top sections. Table includes: Electro-hydraulic controls, side rail locking system, grounding receptacle and dual arm support section. It is designed for use in the operating room in a variety of surgical procedures. Table is configured to address the needs of trauma surgery.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	45	23	89	890 lb	1:	120	1	10	60		NO		--			
		CM:	114	58	226	404 kg	2:	--	--	--	DEPENDENT:		YES		--			
M9115	6530	Table, Operating, Spinal	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
<p>Unit provides an elevated surface for supporting a patient's body during spinal surgical procedures, stabilizing the patient's position and providing optimal exposure of the surgical field. The unit has a C-Spine base allowing unrestricted C-Arm integration for A/P, lateral and oblique views as well as for fluoroscopic procedures. The table is capable of supporting a patient weighing up to 500 pounds. The unit has an electrically adjustable table top height that ranges from 24-48 inches. [The price on this table will vary according to the accessories chosen. No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	48	32	106	790 lb	1:	120	1	15	60		NO		--			
		CM:	122	81	269	359 kg	2:	--	--	--	DEPENDENT:		NO		--			
P0305	6740	Sink, Processing, Film, Color/Black & White	A	A	A	A	--	D	A	C	B	--	E					
<p>Film processing sink. Unit has a 3-1/2 gallon tank capacity for processing film, color (C-41 development process) or black and white. It is 100% stainless steel construction including heavy duty sink, control panel, tanks, and covers. All stainless steel compartments are heliarc welded, ground, and polished. Includes an automatic gas burst agitation system, tempered water supply faucet, water inlet control valves, and a temperature regulator. Designed for cut sheet or roll film.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	53	63	30	325 lb	1:	120	1	--	60		NO		--			
		CM:	135	160	76	147 kg	2:	--	--	--	DEPENDENT:		YES		--			
P0310	6740	Sink, Processing, Film, Color, E-6 Type	C	C	C	C	--	D	A	C	B	--	E					
<p>3-1/2 gallon tank capacity film processor for color (E-6 development process) film. Stainless steel construction, including the heavy duty sink, control panels and tanks. Equipped with water temperature regulator, dial thermometer, gas/air agitation timer, air outlet for direct connection to air supply, 7 chemical tanks and covers.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	51	118	30	600 lb	1:	115	1	1	60		NO		--			
		CM:	130	300	76	273 kg	2:	--	--	--	DEPENDENT:		YES		--			
P0350	6740	Sink, Processing, Photographic Print	A	A	A	A	--	D	A	C	B	--	E					
<p>Photographic print sink. Unit consists of a stainless steel sink with 1-1/2" drain, separate washing compartments, flow control valves, spray inlets in tray compartments, and built-in vacuum breakers. 20" X 24" tray capacity. For use in the darkroom for print developing. Many sizes available. 36"D x 96"W x 5-10"H (inside dimension of sink), quoted for planning purposes.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	41	100	40	550 lb	1:	120	1	1	60		NO		--			
		CM:	104	254	102	250 kg	2:	--	--	--	DEPENDENT:		YES		--			
P1050		Bathtub, Patient	A	A	A	A	--	D	--	--	--	--	--					
<p>White acrylic bathtub used for patient bathing. Includes drain and skirt.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	20	60	42	92 lb	1:	--	--	--	0		NO		--			
		CM:	51	152	107	42 kg	2:	--	--	--	DEPENDENT:		NO		--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
P1060	4530	Tub/Shower, Combination, Pediatric	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--
A recess, acid-resisting, heavy gauge, porcelain enameled steel, one-piece tub (left or right-hand outlet) with shower. Unit features: slip-resistant surface bottom; end drain outlet; pressure balanced, single lever mixing valve with check stops; tub diverter and filler; hand-held shower with hose and in-line vacuum breaker; and slide guide. For general purpose use in pediatric patient bathrooms. [No other sources(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	16	60	30	85 lb	1:	--	--	--	NO		--					
		CM:	41	152	76	39 kg	2:	--	--	--	NO		--					
P1150	4510	Valve, Rinse, Bedpan, With Disinfectant Injector	A	A	A	A	--	J	--	--	--	--	--	--	--	--	--	--
Bedpan rinsing valve with deodorant/disinfectant spray. Unit is wall mounted above a water closet having an exposed flush valve. Flush water shall be available to rinse the pan with the balance used to flush the waste. Used in dirty utility rooms located in patient care areas throughout the hospital. Unit is used to flush and disinfect a dirty bedpan.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	8	20	8 lb	1:	--	--	--	NO		--					
		CM:	91	20	51	4 kg	2:	--	--	--	NO		--					
P1950	4510	Eyewash, Floor Mounted	A	A	A	A	--	B	--	--	--	--	--	--	--	--	--	--
Pedestal standing eye wash station. Unit is hand operated to provide streams of water to clean foreign particles or liquids from the eyes in emergency situations. Used in laboratories and hospital areas where employees are susceptible to exposure to foreign, caustic or irritating matter to the eyes.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	42	13	19	20 lb	1:	--	--	--	NO		--					
		CM:	107	33	48	9 kg	2:	--	--	--	NO		--					
P1960	4510	Eyewash, Counter Top	A	A	A	A	--	B	--	--	--	--	--	--	--	--	--	--
Counter top mounted emergency eye wash station. Unit is hand operated to provide streams of water to clear or dilute foreign particles or liquids from the eyes in emergency situations. It is equipped with a stainless steel bowl, face spray ring and dual automatic pressure compensation devices. The valve remains open until manually closed. Used in laboratories and areas of the hospital where employees are subject to exposure to foreign bodies or caustic liquid matter to the eyes.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	9	12	10	9 lb	1:	--	--	--	NO		--					
		CM:	23	30	25	4 kg	2:	--	--	--	NO		--					
P1965	4510	Eyewash, Eye/Face, Sink Mounted, Hands-free	A	A	A	A	--	A	--	--	--	--	--	--	--	--	--	--
A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	16	12	6	7 lb	1:	--	--	--	NO		--					
		CM:	41	30	15	4 kg	2:	--	--	--	NO		--					
P2000	4510	Eyewash, Wall Mounted, Hands-Free	A	A	A	A	--	B	--	--	--	--	--	--	--	--	--	--
Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	12	15	15	8 lb	1:	--	--	--	NO		--					
		CM:	30	38	38	4 kg	2:	--	--	--	NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
P2050	4510	Eyewash, Eye/Face, Deck Mounted w/Squeeze Handle	A	A	A	A	--	J	--	--	--	--	--	--	--	--	--	--	
A deck/countertop mounted, hand-held, squeeze valve activated, emergency eye/face and body spray station. It is equipped with a hose guide bracket, a deck flange, and a minimum eight foot hose. Suitable for flushing foreign matter from the eyes/face or for total body flushing. Useful in areas where harmful substances may contaminate the eyes or other body areas.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	8	4	2	5 lb	1:	--	--	0	NO	--							
		CM:	20	10	5	3 kg	2:	--	--	NO	--								
P2100	4540	Disposal, Garbage, 2 HP Motor	A	A	A	A	--	B	C	--	--	--	--	--	--	--	--	--	
Garbage disposal. A two (2) horsepower versatile waste disposal unit suitable for facilities where 500 to 1000 meals are prepared and served daily. Requires eight (8) gallons per minute water flow rate, and outlet flange tapped for a two (2) inch pipe. Unit will have a manual reversing switch and shall comply with MIL SPEC No. MIL-G-15840. Multiple electrical configurations are available.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	38	19	19	115 lb	1:	208	1	60	NO	--							
		CM:	97	48	48	53 kg	2:	--	--	YES	--								
P2450	6530	Valve, Mixing, Thermostatic	A	A	A	A	--	A	--	--	--	--	--	--	--	--	--	--	
Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments. [The price for Model 2 includes \$1,095.00 for the washout hose attachment (C9236-25)]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	24	24	6	-- lb	1:	--	--	--	NO	--							
		CM:	61	61	15	-- kg	2:	--	--	NO	--								
P3000	4510	Lavatory, Vitreous China, Straight Back	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	13	21	18	41 lb	1:	--	--	--	NO	--							
		CM:	33	53	46	19 kg	2:	--	--	NO	--								
P3070	4510	Lavatory, Vitreous China, Under or Counter Top Mtd	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
An undercounter or countertop mounted vitreous china lavatory (approximate bowl size 6"x17"x14") with gooseneck spout, wrist blade handles, and grid drain. Counter top mounted lavatory to be self rimming with mounting kit provided. Undercounter lavatory to have unglazed rim with a mounting kit also provided. For general purpose use in vanity tops in public, patient and staff toilet rooms.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	19	19	16	25 lb	1:	--	--	--	NO	--							
		CM:	48	48	41	11 kg	2:	--	--	NO	--								
P3100	4510	Lavatory, Vitreous China, Slab Type	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:								
EA		IN:	20	20	18	52 lb	1:	--	--	--	NO	--							
		CM:	51	51	46	24 kg	2:	--	--	NO	--								
P3200	4510	Lavatory, Vitreous China, Slab Type w/Sens Op Fauc	A	A	A	.	--	D	--	--	--	--	--	--	--	--	--	--	
Wall mounted, slab type, vitreous china, lavatory (approximately 7 x 15 x 10 inches) with faucet holes on 4 inch centers; electronic sensor operated, goose neck spout and grid strainer. It shall be suitable for use in clinics, offices and patient care areas. [No other source(s) identified with this description/specification. Sources are limited by the requirement that two separate end items (lavatory and sensor faucet) be combined into a single end item or JSN. The Kohler Co. is the only source identified that provides both the lavatory and electronic sensor operated gooseneck faucet. Several companies (Sloan Valve Co. Chicago Faucets and Grohe) offer electronic faucets as part of their product line but do not offer lavatories.]																			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	9	20	18	-- lb	1: 40	1	1	60	NO	--		
				CM:			-- kg	2:			DEPENDENT:				
				23	51	46		--	--	--	NO	--			
P3520	4510	Sink, Plaster, China	A	A	A	A	--	D	--	--	--	--			
			Plaster sink approximately 10" x 28" x 18". Unit is made of vitreous china. Faucet is equipped with 2 inch spray, 6 inch handles with screwdriver stops, grid drain with 1-1/2 inch tailpiece, a 2 inch outside diameter drain connection to trap and wall and a plaster interceptor trap. Space must be left above trap for removal of screen for cleaning. Used in orthopedic clinic cast rooms, emergency rooms and other areas where plaster is soaked or rinsed in a sink. [No other source (s) could be located that match this description/specification. Eljer Industries only carries sinks and no longer provides plumbing accessories. Jay R. Smith Manufacturing Company (Cage Code 88150) makes plaster interceptors that are sold separately.]												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	29	30	22	145 lb	1: --	--	--	--	NO	--		
				CM:			66 kg	2:			DEPENDENT:				
				74	76	56		--	--	--	NO	--			
P4700	4510	Sink, Mop, Molded Stone, 10x36x24	A	A	A	A	--	D	--	--	--	--			
			Mop service sink. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	10	36	24	70 lb	1: --	--	--	--	NO	--		
				CM:			32 kg	2:			DEPENDENT:				
				26	91	61		--	--	--	NO	--			
P5040	4510	Shower, Single, Hand-Held	A	A	A	A	--	D	--	--	--	--			
			A complete, barrier-free, single hand-held, personal shower system. The shower system includes: pressure balanced mixing valve with high temperature limit stop; personal hand shower; shower hose; wall supply; and slide bar. For general purpose use throughout the facility in shower stalls.												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	--	--	--	3 lb	1: --	--	--	--	NO	--		
				CM:			1 kg	2:			DEPENDENT:				
				--	--	--		--	--	--	NO	--			
P5210	4510	Shower, Safety, Freestanding, With Eye/Face Wash	A	A	A	A	--	B	--	--	--	--			
			Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	94	15	32	45 lb	1: --	--	--	--	NO	--		
				CM:			21 kg	2:			DEPENDENT:				
				239	38	81		--	--	--	NO	--			
P5350	5410	Shower, Patient, Psychiatric	A	A	A	A	--	D	--	--	--	--			
			Psychiatric patient shower. Shall be vandal-proof. Shower head shall be designed for prison use, shall have smooth surfaces with no projection that can be used as a catch or hook; shall have flat back arranged for bolting directly to the wall and shall be tapped for 1/2 inch pipe connecting to tempered water line; the head shall have a tamperproof removable face not less than 3-1/2 inch diameter; the shower head shall be installed not less than 6 feet above the floor and shall deliver the spray within a 3 foot circle. [No other source(s) identified with this description/specification.]												
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	20	10	4	12 lb	1: --	--	--	--	NO	--		
				CM:			6 kg	2:			DEPENDENT:				
				51	25	10		--	--	--	NO	--			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
P6150	5410	Sink, Cage Washing, SS, Single Compartment, F/S	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--		
A free standing, single compartment (16"x36"x24"), #14 gauge Type 304 stainless steel, cage washing sink with gooseneck spout and lever handle drain. Sink is all welded construction with rolled rims. Ends and integral drainboards are welded. Sink has 15" high back, stainless steel adjustable angle frame legs and soap dish. It is available with or without drainboard(s). For general purpose use in laboratory research and vet areas for washing small animal cages. Pricing based upon a sink with 24" left drainboard. [No other sources(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	51	62	27	190 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	130	157	69	87 kg	2:	--	--	--			--						
P6350	5410	Sink, Flushing Rim, China, 18x26x22	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--		
Flushing rim sink. Also called a clinic service sink. Unit is constructed of vitreous china with an integral flushing rim. It includes: faucet with a fork brace; 6 inch wrist control handles; plain end spout with bucket hook; stainless steel spring type front rim guard; and grid drain. If it is to be floor mounted, a base must be provided. Unit is used in utility rooms to clean equipment and materials. [Flush valves are required but not manufactured by these companies. These companies generally sell through local distributors that do offer appropriate flush values based on utility specifications. Two leading manufacturers of commercial flush valves are Sloan and Delany.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	18	20	30	60 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	46	51	76	28 kg	2:	--	--	--			--						
P6500	4510	Sink, Service, Cast Iron	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--		
Service sink approximately 18" D x 22" W x 20" H which includes a polished chromium-plated combination hot and cold water faucet with integral stops and extended spout. Spout will have a pail hook, 3/4 inch hose coupling thread and shall include a backflow preventer. The faucet will be provided with a top brace and wall fittings for mounting above service sink. Service sink will be made of enameled cast iron. Used throughout the facility in utility rooms for washing and cleaning equipment. [Dimensions are for the sink and back splash.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	23	23	19	118 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	58	58	48	54 kg	2:	--	--	--			--						
P6900	4510	Sink, Surgeon's Scrub, Vitreous China	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--		
A vitreous china surgeon's scrub sink with a single-hole punched, centered on back ledge, for a gooseneck spout. Sink provided with gooseneck spout, manual knee-action control mixing valve, grid strainer, concealed wall hangers or exposed wall brackets. For general purpose use in surgical and clinical areas of the facility where a scrub sink is required. [Crane Plumbing (Cage Code OATZ2) and Eljer Industries (Cage Code SR165) both make a vitreous china scrub sink, but do not offer the plumbing accessories.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	18	28	22	123 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	46	71	56	56 kg	2:	--	--	--			--						
P6950	4510	Sink, Scrub, With Knee Valve, 13.5x22x19	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--		
Surgeon's scrub-up sink. Unit is operated by knee-action valve and gooseneck supply. Sink shall conform to FED. SPEC. WW-P-541/9B, Type IV, class 1. Unit is used as a scrub sink in surgical and clinical areas of the facility. [No other sources(s) identified with this description/specification. Eljer still offers the scrub sink but no longer carries a knee operated mixing valve.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	14	22	20	100 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	36	56	51	46 kg	2:	--	--	--			--						
P6980	4510	Sink, Scrub, SS, 1-3 Bay, With Knee Valve	A	A	A	A	--	D	B	--	--	--	--	--	--	--	--		
Surgeon's scrub-up sink. Unit is constructed of polished stainless steel. This sink unit has a hydro-mechanical knee operating water control valve and a knee operated surgical soap dispenser. It can be a one, two or three bay model as required. Used in surgical suites or scrub-up areas for surgical teams. Optional electrical configurations are available. Dimensional and price data is based on a three bay unit.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	50/60	HZ SWITCH:	YES	BTUs / HR:						
EA		IN:	54	96	28	575 lb	1:	120	1	2	DEPENDENT:	NO	--						
		CM:	137	244	71	261 kg	2:	--	--	--			--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
P6990	4510	Sink, Scrub, Double, Automatic	A	A	A	A	--	D	B	--	--	--	--	--	--	--	--	
Surgical scrub station. Unit is a two station unit with automatic controls. It includes thermostatic controlled water temperature selector, solid state timer, automatically timed scrub period, automatic water shut-off, full arm wash/rinse spray, and built-in detergent dispenser (knee or thigh controlled). Unit is used in surgical suites or scrub-up areas for surgical teams. Optional electrical configurations are available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	52	64	28	425 lb	1:	120	1	2	YES		--					
		CM:	132	163	71	193 kg	2:	--	--	--	NO		--					
P7600	4510	Interceptor, Solids, Large Capacity, Floor Type	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	
A solid/sediment interceptor that is flush with or on the floor, large capacity, with a coated steel or coated cast iron body. Furnished with 2 inch low inlet and high inlet. Unit provides a means of collecting solids such as metal chips and plaster before entering the drain line. It is cleaned by removing cover and lifting strainer and screen assembly vertically out of the body. For general purpose use in areas where it is necessary to preclude solids from entering the drain lines. Note: This unit is not for installation in an undercounter or base sink cabinet.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	17	18	18	139 lb	1:	--	--	--	NO		--					
		CM:	43	46	46	64 kg	2:	--	--	--	NO		--					
P7650	6520	Trap, Plaster, Small	A	A	A	A	--	I	--	--	--	--	--	--	--	--	--	
Plastic or metal bodied plaster trap. The unit has a one piece body which is approximately 12 inches deep. The top has 1.5 inch inlet and drain connections. The trap is used in laboratories to capture solids and preclude the clogging of drain lines. The installation must allow sufficient clearance above or below the unit (depending on the manufacturer) to remove the basket for cleaning.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	13	10	10	22 lb	1:	--	--	--	NO		--					
		CM:	33	25	25	10 kg	2:	--	--	--	NO		--					
P8150	4510	Urinal, Wall Hung	A	A	A	A	--	B	--	--	--	--	--	--	--	--	--	
A low consumption (1.0 gallon per flush) vitreous china, wall hung, washout flush action urinal with extended sides, flushing rim, 3/4" inlet spud, 2" I.P.S. female outlet connection and stainless steel strainer. For general purpose use in male toilet rooms. [The nomenclature and description are for a urinal only and do not include the flushing unit. Recommend use of a Sloan Valve Company Royal Flushometer model 186-1.0 or comparable unit for low water consumption. This unit costs \$139.00 and is compatible with the three urinal models. A cut sheet for the flushometer is included with each model for information.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	28	19	15	72 lb	1:	--	--	--	NO		--					
		CM:	71	48	38	33 kg	2:	--	--	--	NO		--					
P8705	4100	Dialysis Box, Recessed, Single Valve	A	A	A	A	--	B	--	--	--	--	--	--	--	--	--	
A single cold water valve supply, recessed dialysis box with door. Box is constructed of stainless steel and includes the following standard equipment: cold water valve with 1/2" nom. copper female inlet, 3/4" male hose thread outlet and vacuum breaker; discharge hose bracket, waste water receptor, and removable wall flange. For use only in the ICU and other acute areas when a patient cannot be moved to the dialysis unit. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	11	11	4	5 lb	1:	--	--	--	NO		--					
		CM:	28	28	10	3 kg	2:	--	--	--	NO		--					
P8710	4100	Utility Center, Plumbing Connection	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	
Plumbing connection utility center, sometimes referred to as a 'GUY GRAY BOX'. This recessed utility center provides for hot and cold water connections and a drain connection at sink and other equipment locations. The utility center includes cutoff valves for the water connections, a plug seal for the drain and an outside cover to provide an aesthetic appearance when connections are no longer required. This center may be installed in locations where no plumbing fixtures are included in a design as a future flexibility device, saving many dollars for later facility modifications to incorporate sinks as functions change.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	10	12	6	10 lb	1:	--	--	--	NO		--					
		CM:	25	30	15	5 kg	2:	--	--	--	NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
P9050	4510	Toilet, Wall Hung, Siphon Jet	A	A	A	A	--	B	--	--	--	--	--	--	--	--	--	--	
Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flush valve, seat with open front and check hinge, and carrier. Used throughout the health care facility in restrooms. [Flush valves are required but not manufactured by these companies. These companies generally sell through local distributors that do offer appropriate flush values based on utility specifications. Two leading manufacturers of commercial flush valves are Sloan and Delany.]																			
UNIT OF ISSUE:		EA	IN:	14	17	26	WEIGHT	60 lb	VOLTS	1:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	36	43	66	WEIGHT	28 kg	VOLTS	2:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	
P9052	4510	Seat, Toilet, Child, Fold-Down	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
A fold down toilet seat designed for child use. The toilet seat permanently attaches to a standard size toilet and functions in conjunction with a standard toilet seat. The child's seat flips up to allow use by an adult and folds down for use by a child without requiring it's removal. [No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		EA	IN:	--	--	--	WEIGHT	-- lb	VOLTS	1:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	--	--	--	WEIGHT	-- kg	VOLTS	2:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	
P9145	6510	Bath/Shower, Nursing Table, Freestanding	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
A freestanding, fixed height, nursing table with bath, shower mixer. A molded fiberglass tabletop with integral bath, which can be located on the right or left side (appropriate bath placement to be indicated on equipment elevation drawings), thermostatic mixer with shut-off valve, and treatment area with mattress located opposite bath. Unit features: epoxy coated steel tubing frame; hand-held spray nozzle, with retracting hose; self-draining soap dish; and recessed, lever operated, drain valve. For general purpose use in maternity wards, nurseries or pediatric wards to bathe or shower infants. Unit available in various widths. Price based upon a 55" width with left side bath. [No other source(s) identified with this description/specification]																			
UNIT OF ISSUE:		EA	IN:	33	55	28	WEIGHT	270 lb	VOLTS	1:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	84	140	71	WEIGHT	123 kg	VOLTS	2:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	
P9150	5410	Water Closet, Lavatory, Combination, Module	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
A patient care module, combination lavatory and water closet (right or left-hand orientation). Unit features: cabinet which conceals the water closet; high plastic laminate finish countertop; stainless steel lavatory with rigid gooseneck, deck-mounted hot and cold faucet with wrist-blade handles; stainless steel, siphon-jet type toilet with elongated bowl and white seat; toilet tissue holder; backsplash; and optional back-wall, floor, or side wall, waste outlet. For use in intensive care areas where there is limited use of a toilet. [No other source(s) identified with this description/specification]																			
UNIT OF ISSUE:		EA	IN:	39	40	17	WEIGHT	145 lb	VOLTS	1:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	99	102	43	WEIGHT	66 kg	VOLTS	2:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	
P9160	5410	Lavatory, China, for Disturbed Patient	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
Disturbed patient lavatory. Unit shall be constructed of vitreous china with integral faucet and soap dish. Shall have self-closing pushbutton valves. Used in psychiatric wards of the hospital.																			
UNIT OF ISSUE:		EA	IN:	17	14	13	WEIGHT	36 lb	VOLTS	1:	--	--	--	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	43	36	33	WEIGHT	17 kg	VOLTS	2:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	
P9180	5410	Lavatory, Wheelchair, 7x20x27	A	A	A	A	--	D	--	--	--	--	--	--	--	--	--	--	
Wheelchair lavatory. Shall be made of vitreous china and accessible to wheelchair bound patients and visitors. Unit is equipped with wrist control handles. Used throughout the facility in handicapped access restrooms. [Crane no longer offers faucets in combination with this lavatory. A faucet would have to be identified and added by the distributor. An additional \$ 230 the faucet has been added to the Crane laboratory to reflect a more legitimate price for the unit.]																			
UNIT OF ISSUE:		EA	IN:	7	20	27	WEIGHT	60 lb	VOLTS	1:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	18	51	69	WEIGHT	27 kg	VOLTS	2:	--	--	--	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--	

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
P9400	5410	Toilet, Wall Hung, Siphon Jet, Psychiatric	A	A	A	A	--	B	--	--	--	--	--	--	--	--	--	--
Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, back spud push button flush valve, seat with open front and check hinge, and carrier. For general purpose use in restrooms on psychiatric patient nursing units. [Flush valves are required but not manufactured by these companies. These companies generally sell through local distributors that do offer appropriate flush values based on utility specifications. Two leading manufacturers of commercial flush valves are Sloan and Delany.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	14	17	26	60 lb	1:	--	--	--	HZ SWITCH:	NO						
		CM:	36	43	66	28 kg	2:	--	--	--	DEPENDENT:	NO						
R0990	4110	Freezer, Ice Cream, Chest, 5 Cubic Foot	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Ice cream freezer. This unit is a chest design. It has a stainless steel exterior with lid lock device. It is used to store single portions of ice cream and other frozen deserts in hospital or commercial cafeteria serving lines. [Model 1 has an exterior finish of baked enamel with a stainless steel cap. Model 2 has a painted steel exterior. Model 3 has an exterior and interior of stainless steel.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	40	33	32	311 lb	1:	120	1	8	HZ SWITCH:	NO						
		CM:	102	84	81	142 kg	2:	12	1	--	DEPENDENT:	YES	818					
R1000	4110	Freezer, Ice Cream, 15 Gallon	A	A	A	A	--	--	B	--	--	--	--	--	--	--	--	--
Ice cream freezer approximately 33x43x39. The unit is used for storage and dispensing of packaged ice cream. The stainless steel exterior can be easily cleaned and maintained. The unit is used in patient care facilities and commercial cafeteria serving lines. [The exterior of Model 2 is not all stainless steel.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	40	33	46	470 lb	1:	120	1	8	HZ SWITCH:	NO						
		CM:	102	84	117	214 kg	2:	--	--	--	DEPENDENT:	YES	818					
R1200	4110	Freezer, Ice Cream, 25 Gallon	A	A	A	A	--	I	B	--	--	--	--	--	--	--	--	--
Ice cream freezer. This unit holds 400 five ounce cups. It is used for storage and dispensing individual packages of ice cream. Freezer is used in hospital and cafeteria serving lines.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	44	45	31	380 lb	1:	120	1	8	HZ SWITCH:	NO						
		CM:	112	114	79	173 kg	2:	--	--	--	DEPENDENT:	YES	506					
R1400	4110	Freezer, Ice Cream, 35 Gallon	A	A	A	A	--	I	B	--	--	--	--	--	--	--	--	--
Ice cream freezer. The chest has a stainless steel top with molded rubber frame and is of metal construction with foamed, in-place polyurethane insulation for maximum insulating efficiency and added cabinet rigidity. Condensing unit slides out for easy maintenance. The unit is used to store and serve packaged ice cream. [Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	43	57	33	448 lb	1:	120	1	8	HZ SWITCH:	NO						
		CM:	109	145	84	204 kg	2:	--	--	--	DEPENDENT:	YES						
R1600	4110	Freezer, Ice Cream, 45 Gallon	A	A	A	A	--	--	B	--	--	--	--	--	--	--	--	--
Ice cream freezer, approximate outside dimensions 40"D x 84"L x 32"H. This unit has a 45 gallon capacity. The chest has easy to clean surfaces and is used to store ice cream and frozen food.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	40	89	32	598 lb	1:	120	1	8	HZ SWITCH:	NO						
		CM:	102	226	81	272 kg	2:	--	--	--	DEPENDENT:	YES	1,160					
R1700	4110	Freezer, 2 Section, CRS	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Freezer cabinet approximately 84x53x36. The unit is a two section, 46 cu. Ft. self contained freezer with adjustable shelves. The cabinet front and doors are constructed of heavy gauge polished stainless steel to maintain an attractive appearance. The unit is used in hospitals and commercial kitchen operations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	85	55	37	674 lb	1:	115	1	16	HZ SWITCH:	NO						
		CM:	216	140	94	306 kg	2:	--	--	--	DEPENDENT:	YES	3,790					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
R1705	4110	Freezer, Drawer, Undercounter	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Drawer type freezer. This is a space-saving under the counter design. The exterior is made of stainless steel. There are also three stainless steel drawers, and a solid bottom. This unit is used for cold storage of whole blood or plasma in hospitals or research laboratories.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	36	27	25	250 lb	1:	120	1	8	NO		600					
		CM:	91	69	64	114 kg	2:	--	--	--	DEPENDENT: YES							
R1800	4110	Freezer, CRS, Prefabricated -20 F	A	A	A	A	--	I	G	--	--	--	--	--	--	--	--	--
<p>Walk-in freezer. This unit is prefabricated, CRS, lightweight, and has finger tip action door, adjustable steel shelves, prefabricated sag-proof floor, sectional construction, paneled electrical connections, thermometer and alarm system. It is used in hospitals or commercial institutions for indoor cold storage. Size and shape may vary due to location requirements. [Model 1 price is for an 8'x10'x7'7" box with roof mounted refrigeration unit. Model 2 price is for an 8'x8'x7'6" box with a semi-hermetic condensing unit. Model number represents the size of the box. Model 3 price is for an 8'x10'x8'6" box with a 3 HP refrigerant unit. Price difference verified.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	102	96	120	3,155 lb	1:	208	3	34	NO		14,950					
		CM:	259	244	305	1,433 kg	2:	--	--	--	DEPENDENT: YES							
R2200	4110	Fountain, Water	A	A	A	A	--	B	B	--	--	--	--	--	--	--	--	--
<p>Water dispenser, approximately 40" H x 18" W x 14"D. This unit is a self-contained device which is flush-mounted to the wall. It has a removable front panel. It is used to provide cool water for drinking. The dispenser is used in public and private institutions which include hospitals and office buildings.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	42	18	15	87 lb	1:	120	1	8	NO		--					
		CM:	107	46	38	40 kg	2:	--	--	--	DEPENDENT: YES							
R2201	4110	Fountain, Water, CRS, Wall Mounted, 2 Level	A	A	A	A	--	B	B	--	--	--	--	--	--	--	--	--
<p>Drinking water fountain. This unit is a wall mounted, combination handicap and general public (2 level) dispenser. It contains an air cooled compressor with CRS wall protector. Specify with or without glass filler. It provides cool fresh drinking water, for hospitals and commercial office buildings.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	40	35	19	170 lb	1:	120	1	5	NO		--					
		CM:	102	89	49	78 kg	2:	--	--	--	DEPENDENT: YES							
R2202	4110	Fountain, Water, CRS, Wall Mounted, Handicap	A	A	A	A	--	B	B	--	--	--	--	--	--	--	--	--
<p>Drinking water fountain. This unit is semi-recessed and wall mounted at handicap level with an air cooled compressor. The unit provides easy access with push-bar/button. The unit provides cool drinking water in hospitals and commercial office buildings to include access by handicapped persons.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	26	18	19	68 lb	1:	120	1	5	NO		--					
		CM:	66	46	48	31 kg	2:	--	--	--	DEPENDENT: YES							
R2203	4110	Fountain, Water, CRS, Wall Mounted, Recessed	A	A	A	A	--	B	B	--	--	--	--	--	--	--	--	--
<p>Drinking water fountain. Unit is fully-recessed and wall mounted, with an air-cooled compressor. Unit must be specified with or without glass filler. The unit provides easy access with push bars or button. The unit is used in hospitals and commercial office buildings.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	54	19	16	140 lb	1:	120	1	5	NO		--					
		CM:	137	48	41	64 kg	2:	--	--	--	DEPENDENT: YES							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES										
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5
R4000	4110	Ice Maker, Cubes (approx 400lbs/24hrs)	A	A	A	A	--	B	B	--	--	--	--	--	--	--	--
Ice cube maker. The unit is a self-contained, freestanding, automatic load ice dispenser for food service and healthcare use. The unit can store 65 to 100 pounds and produces approximately 400 pounds of ice per 24 hour period. Manual load capability allows addition of backup ice to meet peak demands. This unit is intended for hospitals and commercial food service operations.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	73	30	32	305 lb	1:	120	1	20	NO		8,356				
		CM:	185	76	81	139 kg	2:	--	--	--	DEPENDENT: YES						
R4400	4110	Ice Maker, Cubes, Undercounter	A	A	A	A	--	B	B	--	--	--	--	--	--	--	--
Ice cube maker approximately 34" H x 25" D x 17" W. This unit is self-contained and makes and stores ice cubes. It will produce 39 pounds of half-cubes daily and stores approximately 34 pounds. It will fit neatly under a bar or counter and is perfect for use in restaurants, luncheonettes, hotels and nursing stations.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	34	18	24	110 lb	1:	120	1	15	NO		3,325				
		CM:	86	46	61	50 kg	2:	--	--	--	DEPENDENT: YES						
R4650	4110	Ice Maker, Flaked, With Dispenser, 71x19x24	A	A	A	A	--	B	B	--	--	--	--	--	--	--	--
Ice maker dispenser. This unit provides flaked ice and cooled water automatically. The unit has a daily capacity up to 650 pounds and a 100 pound capacity stainless steel storage compartment with water station. It is a freestanding, automatic load ice dispenser for food service and healthcare use. The unit stores 50 pounds of ice and produces approximately 400 pounds of ice in a 24 hour period. The unit is used in healthcare institutions and various commercial food service operations for dispensing ice.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	82	36	30	400 lb	1:	120	1	22	NO		--				
		CM:	208	91	76	182 kg	2:	--	--	--	DEPENDENT: YES						
R4700	4110	Ice Maker, Cubes, 250 Pound, 39x29x26	A	A	A	A	--	B	B	--	--	--	--	--	--	--	--
Ice cube maker. This unit is self-contained and provides 250 pounds of ice every 24 hours. The exterior is made of sturdy stainless steel. It is used in hospitals, hotels, and restaurants for dispensing ice.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	39	30	31	198 lb	1:	120	1	20	NO		--				
		CM:	99	76	79	90 kg	2:	--	--	--	DEPENDENT: YES						
R4780	4110	Ice Maker, 500 Pound	A	A	A	A	--	B	B	--	--	--	--	--	--	--	--
Ice maker. This unit provides either solid, flake or nugget ice. Unit is self-contained and can store 700 pounds of ice and produce approximately 500 pounds of ice in a 24 hours period. The unit is used in healthcare institutions and various commercial food service operations. End user to specify model number for type ice required. [Specific vendor/manufacturer model number must be used to specify either solid, flake or nugget ice. There are no combination units available. Model 1 is for nugget ice while the other two models are for flake ice.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	74	42	33	625 lb	1:	120	1	20	NO		--				
		CM:	188	107	84	284 kg	2:	--	--	--	DEPENDENT: YES						
R5100	6520	Freezer,Biological, -85, 19-25 Cubic Feet, Upright	C	C	C	C	--	B	F	--	--	--	--	--	--	--	C
Biological freezer, -85 degrees centigrade, 19-25 cubic feet with temperature recorder, remote alarm, and storage baskets. Optional auxiliary water cooling available. Upright type freezer. [A dedicated circuit is recommended.]																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	79	49	36	1,000 lb	1:	208	1	20	NO		--				
		CM:	201	124	91	454 kg	2:	--	--	--	DEPENDENT: NO						
R5110	6520	Freezer, Rapid, Blood/Plasma, 4 Cubic Feet	C	C	C	C	--	--	G	--	--	--	--	--	--	--	--
Rapid freezer for blood products and plasma. This unit uses a liquid cooling medium for rapid heat reduction and consistent freezing rate. The unit is insulated with a minimum of 3 1/2 " of poured in place urethane insulation. Refrigeration system is 2 hp. air cooled system. This unit may be a chest or upright type freezer.																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	74	34	80	1,574 lb	1:	250	3	25	NO		10,000				
		CM:	188	86	203	715 kg	2:	--	--	--	DEPENDENT: YES						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
R5115	6520	Freezer, Blood, Chest, Double Compartment	C	C	C	C	--	--	C	--	--	--	--	C				
<p>Double dual cascade compressor chest freezer for frozen blood storage. Unit has approximately 20 cubic feet of storage capacity, without storage racks, which provides storage for approximately 300 standard red cell canisters. Unit is used for frozen blood storage in laboratories and blood banks. [Model 1 new product model number is 8628. Catalog info is not yet on-line. The new model's specifications are similar to 8590, however.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			41	103	29	950 lb 432 kg	1:	208	1	12	60	NO	--					
			96	244	74		2:	--	--	--	YES	YES	--					
R5120	6520	Freezer, Blood/Platelet,Upright, -85C, 20-30 Cu Ft	C	C	C	C	--	--	E	--	--	--	--	C				
<p>Whole blood freezer. This unit has 7 day recording thermometer, high/low alarms, battery powered power failure alarm and remote alarm. The upright unit is used to store blood and blood products. Operating temperature set points and is adjustable in 1øC increments from -40øC to -85øC. This unit is used in laboratories and hospital facilities for blood and blood products storage. Shall include JSN R5125, Inventory Management System. [Model 1 is a 208V unit.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			80	203	38	950 lb 432 kg	1:	120	1	16	60	NO	--					
			44	112	97		2:	208	1	12	60	YES	YES					
R5130	6520	Freezer, Plasma, Upright, -35c, 20 Cubic Feet	C	C	C	C	--	--	F	--	--	--	--	C				
<p>Upright plasma freezer. This unit is used to provide uniform cold storage of plasma and related blood components that are produced in accordance with AABB, ANRC, and FDA guidelines for temperature uniformity, alarm and monitoring. This unit is used in laboratories and hospitals for storage of plasma and related blood components. [A dedicated circuit is recommended.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			83	211	35	846 lb 384 kg	1:	230	1	15	60	NO	3,000					
			30	76	89		2:	--	--	--	YES	YES	3,000					
R5135	4110	Freezer, Undercounter, 5 Cubic Feet	C	C	C	C	--	--	A	--	--	--	--					
<p>Under counter freezer. This unit features space-saving thin-wall construction and has the flexibility of being built with existing cabinets, installed under-counter without top or custom-finished to specifications. This unit is general purpose laboratory freezer. [The model number shown for Model 1 (Jewett UCF206-1B) is a change from that shown on the cut sheet. This new model has all the same characteristics as the previous one, but literature showing the new number was not available. Model 2 and 3 have a volume of 6 CUFT.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			34	86	24	230 lb 105 kg	1:	120	1	5	60	NO	1,300					
			24	61	61		2:	--	--	--	YES	YES	1,300					
R5200	4110	Freezer, Counter High, -70 C, 5 CUFT	C	C	C	C	--	--	F	--	--	--	--	C				
<p>Freezer chest. The chest has easy open counter-balanced lid and includes a silicone compression gasket to minimize frost build-up. The unit has tamper proof controls with key operated switches for power and alarm. This ultra-low temperature unit operates with temperature set points adjustable in 1c increments from -20 C to -90 C. This unit is used for cold storage of critical or non-replaceable laboratory samples. [Recommend the Nomenclature and Description be reviewed. The unit capacity in CUFT must be added to adequately determine requirement. The models shown range in size from 5.0 - 6.9 CUFT, however, other models are available up to 20 CUFT. Price variance confirmed.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			46	117	35	525 lb 239 kg	1:	115	1	20	60	NO	--					
			49	124	89		2:	--	--	--	YES	YES	--					
R6010	6520	Refrigerator, Blood Bank, Glass Do, Dr, 25 Cu Ft	C	C	C	C	--	--	A	--	--	--	--	C				
<p>Blood bank refrigerator. This unit has a single glass door, pull-out drawer, 7 day recording thermometer, high/low alarm system, battery-powered power failure alarm and remote alarm. The unit is used for storage of blood as required by AABB, ANRC and FDA for whole blood.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			83	211	36	635 lb 289 kg	1:	120	1	15	60	NO	2,400					
			30	76	91		2:	--	--	--	NO	NO	2,400					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
R6030	4110	Refrigerator, Blood Bank, Undercounter, Drawer	C	C	C	C	--	--	F	--	--	--	--	C					
Blood bank refrigerator. Unit can be designed with counter surface or for under the counter installation, and has a thermometer and alarm system. The unit is used to store small quantities of blood samples in laboratories and hospitals.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	36	24	26	250 lb	1:	120	1	8	60		NO		900				
EA		CM:	91	61	66	114 kg	2:	--	--	--	DEPENDENT:		YES						
R6040	6520	Refrigerator, Blood Bank, 2 Glass Do, Dr, 48 Cu Ft	C	C	C	C	--	--	A	--	--	--	C						
Blood bank refrigerator. Unit has double glass doors, pull-out drawers and a 7 day recording thermometer. It also includes high/low alarm, battery power failure alarm, and remote alarm. This unit is used in hospitals and blood collection points for storage of blood products.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	80	55	41	1,100 lb	1:	120	1	13	60		YES		3,800				
EA		CM:	203	140	104	499 kg	2:	--	--	--	DEPENDENT:		YES						
R6050	4110	Freezer, Biological, Chest, -70c, 12 Cubic Feet	C	C	C	C	--	--	B	--	--	--	C						
Biological freezer. This is a chest type, 12 cubic feet, ultra-low unit. Characteristics include two hermetically sealed compressors and 5 inches of rigid non-setting urethane foam insulation.. [A dedicated circuit is recommended.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	46	72	35	725 lb	1:	115	1	24	60		NO		--				
EA		CM:	117	183	89	330 kg	2:	--	--	--	DEPENDENT:		NO						
R6060	4110	Refrigerator, Biological, SS, 2 Door, 40 Cu Ft	C	C	C	C	--	--	A	--	--	--	C						
Biological refrigerator. This unit shall have a minimum volume of 40 cubic feet, double doors, stainless steel cooler storage with stainless steel drawers, three adjustable shelves and one stationary stainless steel shelf. This refrigerator is used in research laboratories and hospital pharmacies for storage and dispensing of drugs.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	83	59	36	1,100 lb	1:	120	1	13	60		NO		3,800				
EA		CM:	211	150	90	500 kg	2:	--	--	--	DEPENDENT:		YES						
R6070	4110	Refrigerator/Freezer, Biological,Upright, 18 Cu Ft	C	C	C	C	--	--	A	--	--	--	C						
Biological refrigerator with freezer. This unit includes a freezer compartment for general laboratory use. Its independent direct-set temperature controllers allow temperature selection for +2ø to 14øC for the refrigerator, and from -20ø to -30øC for the freezer.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	74	29	30	550 lb	1:	120	1	10	60		NO		--				
EA		CM:	188	74	76	250 kg	2:	--	--	--	DEPENDENT:		YES						
R6080	4110	Refrigerator/Freezer, Biological, SS, 2 Door	C	C	C	C	--	--	A	--	--	--	C						
Biological refrigerator/freezer. This unit has double doors, stainless steel exterior and shelves. It is used in laboratories and hospital pharmacies for cold storage and general use. Size and capacity is dependent on site requirements.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	82	32	35	550 lb	1:	120	1	13	60		NO		--				
EA		CM:	208	81	89	250 kg	2:	--	--	--	DEPENDENT:		YES						
R6090	4110	Refrigerator/Freezer, Biological, 1 Door	C	C	C	C	--	--	A	--	--	--	C						
Biological refrigerator/freezer approximately 61x28x27. This unit has a single door and stainless steel exterior. It includes foamed-in place urethane insulation for low energy consumption, quiet hermetically sealed compressor, non-sparking magnetic gasket for positive seal, built-in door locks and defrost. [Model 3 comes only in a 2 door, 208V model. No other appropriate source could be found with a single door for a refrigerator/freezer combination.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	80	35	33	340 lb	1:	120	1	6	60		NO		--				
EA		CM:	203	89	84	155 kg	2:	208	1	2	DEPENDENT:		YES						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
R6100	4110	Freezer, Food, Upright, CRS, 23 Cu Ft, 84x27x37	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Food freezer. This unit has a stainless steel case front and doors. The cabinet front and doors are constructed of heavy gauge polished stainless steel to maintain an attractive appearance. The heavy-duty wire shelves are adjustable in one inch increments, used for frozen food storage in food service departments.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	84	WIDTH CM:	213	DEPTH	35	WEIGHT	315 lb	VOLTS	120	PHASE	1	AMPS	12	HZ:	60
										143 kg		2:	--	--	--		HZ SWITCH:	NO
																	DEPENDENT:	YES
																		BTUs / HR:
																		2,400
R6110	4110	Refrigerator, 2 Swing Doors, Shelves, 40 CUFT	C	C	C	C	--	I	A	--	--	--	--	--	--	--	--	--
Refrigerator. This unit has a large storage capacity with no loss of floor space due to the swinging doors. The refrigerator is generally used for cold storage in commercial institutes and hospital facilities. In addition to shelving, it may include roll-out baskets with safety catches. [All three models have a capacity of 49 CUFT.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	85	WIDTH CM:	216	DEPTH	38	WEIGHT	660 lb	VOLTS	120	PHASE	1	AMPS	11	HZ:	60
										300 kg		2:	--	--	--		HZ SWITCH:	NO
																	DEPENDENT:	YES
																		BTUs / HR:
																		2,610
R6111	4110	Freezer, Cryogenic, Chest	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--
Cryogenic freezer. This is a chest type unit that will maintain uniform temperatures to -140 and -150 degrees centigrade. It shall have a microprocessor control system, key-operated master switch for power and alarm, washable, reusable condenser filter to maintain peak operating efficiency and full-function safety system. The cabinet shall have a convenient size lid handle and lid locking provision to prohibit unauthorized access. The refrigerant shall be non-flammable and preferably CFC-free. [Requires a 30 amp breaker. A dedicated circuit is recommended. Three phase power models are available.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	43	WIDTH CM:	109	DEPTH	29	WEIGHT	825 lb	VOLTS	208	PHASE	1	AMPS	25	HZ:	60
										375 kg		2:	--	--	--		HZ SWITCH:	NO
																	DEPENDENT:	YES
																		BTUs / HR:
																		--
R6180	4110	Refrigerator/Freezer, Explosion Proof, 13 Cu Ft	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Explosion-proof refrigerator. This unit offers protection from explosions caused by fume seepage from containers within working chambers. Unit shelves rest on brackets to permit easy removal. Unit has an adjustable temperature range of -20°C to 0°C. This unit is generally used in laboratories and hospitals for cold storage.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	84	WIDTH CM:	213	DEPTH	31	WEIGHT	265 lb	VOLTS	120	PHASE	1	AMPS	3	HZ:	60
										121 kg		2:	--	--	--		HZ SWITCH:	NO
																	DEPENDENT:	YES
																		BTUs / HR:
																		--
R6200	4110	Refrigerator, U/C or F/S, 5 Cu Ft	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	35	WIDTH CM:	89	DEPTH	24	WEIGHT	210 lb	VOLTS	120	PHASE	1	AMPS	4	HZ:	60
										96 kg		2:	--	--	--		HZ SWITCH:	NO
																	DEPENDENT:	YES
																		BTUs / HR:
																		900
R6280	4110	Refrigerator, Lab, SS, 2 Door, 6 Shelves	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage. [Model 1 price includes recorder/alarm. Models 1 and 3 have approximately 49 CUFT capacities while Model 2 has 38 CUFT.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	84	WIDTH CM:	213	DEPTH	39	WEIGHT	850 lb	VOLTS	120	PHASE	1	AMPS	12	HZ:	60
										386 kg		2:	--	--	--		HZ SWITCH:	NO
																	DEPENDENT:	YES
																		BTUs / HR:
																		3,800

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
R6400	4110	Refrigerator, 5 CUFT	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Household refrigerator approximately 35x24x24 in size. This unit has a positive mechanical latch with keyed cylinder lock, is stackable and is a space saver. It has an automatic defrost system with built-in condensate evaporator. The unit is generally used in laboratories and households for cold storage. [Models 2 and 3 have capacities of 6 CUFT.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			35	89	27	125 lb	1:	120	1	4								
			25	69	64	57 kg	2:	--	--	--								
R6800	4110	Refrigerator/Freezer, 2 Door, 10 Cubic Feet	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
This is a 10 cubic foot frostless top mount refrigerator/freezer combination that is used in households or other areas where general purpose storage of perishable items is required.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			60	152	28	157 lb	1:	120	1	2								
			30	76	76	72 kg	2:	--	--	--								
R6900	4110	Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	C	C	C	C	--	--	A	--	--	--	--	C				
Radiopharmaceutical and biological refrigerator with key-lock door. This unit is lead-lined with 1/8 inch lead on all sides for radiopharmaceuticals, biologicals and other radioactive materials. Freezer compartment and refrigerator eliminates thermal lag placement of cooling units inside the shielding. This unit is used as a storage unit in hospitals and laboratories that handle radioactive materials.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			37	94	31	802 lb	1:	120	1	2								
			24	61	61	365 kg	2:	--	--	--								
R7000	4110	Refrigerator, 14 Cubic Feet	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
This is a 14 Cubic Foot frostless top mount refrigerator/freezer approximately 64" H x 28" W x 29" D. Combination unit that is used in households or other areas where general purpose storage of perishable items is required.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			63	160	29	215 lb	1:	120	1	15								
			33	84	84	98 kg	2:	--	--	--								
R7050	4110	Refrigerator, 25 Cubic Feet	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
General purpose refrigerator approximately 84x27x37. This unit is corrosion resistant stainless steel. It has a single self closing door with safety stops. This refrigerator is generally used in commercial kitchens, hospitals and schools.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	2,610	--
			85	216	29	590 lb	1:	115	1	9								
			35	89	89	268 kg	2:	--	--	--								
R7100	4110	Refrigerator, 50 Cubic Feet	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Two sectional refrigerator approximately 84" H x 53" W x 37"D. This unit is two sections with two separate stainless steel doors. The doors are self-closing with safety stops. This refrigerator is used for general storage in commercial kitchens, hospitals and schools.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	3,600	--
			84	213	55	750 lb	1:	120	1	12								
			37	94	94	341 kg	2:	--	--	--								
R7200	4110	Refrigerator, 20 Cubic Feet, 70x32x27	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Commercial refrigerator. This unit is generally used to store perishable goods for safekeeping in commercial kitchens, hospitals and schools.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	2,200	--
			84	213	28	552 lb	1:	120	1	12								
			37	94	94	251 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES																						
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6											
R7250	4110	Refrigerator/Freezer, 20 Cubic Feet	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--											
Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of commercial or residential design and use.																													
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	70	36	32	324 lb	1:	120	1	7	60	NO	--	
R7300	4110	Refrigerator/Freezer, 40 Cubic Feet	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--											
Refrigerator/freezer. This unit has a stainless steel exterior with dual temperature controls. The unit is normally used in restaurants and hospitals, for storage of perishable items.																													
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	85	56	37	885 lb	1:	120	1	16	60	NO	5,470	
R7400	4110	Refrigerator, 45 Cubic Feet, 84x55x35	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--												
Commercial refrigerator. This unit is a commercial design, general purpose unit, used to store perishable items in laboratories.																													
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	84	55	35	816 lb	1:	120	1	16	60	NO	3,600	
R7600	4110	Refrigerator, 65 CUFT	C	C	C	C	--	--	A	--	--	--	--	--	--	--													
Commercial refrigerator approximately 65 CUFT and 84x83x35 in size. This is a general purpose unit used to store perishable goods in commercial kitchens and institutional establishments. [Model 1 has a capacity of 79 CUFT. Models 2 and 3 have capacities of 68 and 72 CUFT respectfully. Note: Model 2's list price is \$13,270 while the GSA price is \$6,296. Another source is Nor-Lake, Inc. that makes a 75 CUFT model #NR763 that is similar in size and electrical requirements with a price of \$7,727.]																													
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	85	83	35	965 lb	1:	120	1	14	60	NO	4,200	
R7900	4110	Refrigerator, Morgue, 2 Cadaver	A	A	A	A	--	I	B	--	--	--	--	C															
Mortuary refrigerator. This unit's entire front, including doors, is finished in polished stainless steel. It includes a removable body tray and supports two cadaver. The refrigerator is used in hospital morgues and funeral homes for refrigerated cadaver storage. The user must specify side or end-loading when ordering. [Prices and dimensions are for end-loading units. The side-loading units have the same overall dimensions with the width and depth reversed, however, they cost more. For Model 2, the KC 200 is priced at \$14,718. For Model 3, the LMR-2-SO is priced at \$12,649. Model 1 only comes as a end-loading unit.]																													
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	81	39	96	1,575 lb	1:	120	1	18	60	NO	4,740	
R7950	4110	Refrigerator, Morgue, Side Opening, 3 Cadaver	A	A	A	A	--	I	B	--	--	--	--	C															
Mortuary refrigerator. This unit is designed for three cadaver capacity. To be used in hospital morgues and funeral homes for refrigerated cadaver storage. [Various Voltages 208/115 1/3 phase are available.]																													
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	102	96	39	2,400 lb	1:	208	1	20	60	NO	4,250	
R8000	4110	Refrigerator, Morgue, 4 Cadaver, 76x73x96	A	A	A	A	--	I	C	--	--	--	--	C															
Mortuary refrigerator. This unit accommodates four cadavers. The unit is used in hospital morgues and funeral homes for refrigerated cadaver storage.																													
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	EA	CM:	76	73	96	2,840 lb	1:	208	1	15	60	NO	6,300	

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES							
			A	N	A	V	I	1	2	3	4	5	6
R8200	4110	Refrigerated Room, Mortuary, 3 Cart	A	A	A	A	--	--	F	--	--	--	--
Mortuary refrigerated room accommodates 3 cadaver carts. The unit is used in hospital morgues and funeral homes to store cadavers under refrigeration where the cadaver cart is also the autopsy table. Custom built to meet site requirements. [Budgetary cost does not include mechanical and electrical installation. Prices and refrigerator configuration will vary depending on site requirements.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:		
EA		IN:	102	118	117	2,243 lb	1:	208	1	12	HZ SWITCH: NO		7,175
EA		CM:	259	300	297	1,019 kg	2:	115	1	1	DEPENDENT: YES		
R8205	4110	Refrigerated Room, Mortuary, 4 Cart	A	A	A	A	--	I	F	--	--	--	C
Mortuary refrigerated room accommodates 4 cadaver carts. The unit is used in hospital morgues and funeral homes to store cadavers under refrigeration where the cadaver cart is also the autopsy table. Custom built to meet site requirements. [Prices and refrigerator configurations will vary depending on site requirements.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:		
EA		IN:	103	156	173	3,156 lb	1:	208	1	17	HZ SWITCH: NO		11,840
EA		CM:	262	396	439	1,433 kg	2:	115	1	1	DEPENDENT: YES		
R8210	4110	Refrigerated Room, Mortuary, 5 Cart	A	A	A	A	--	I	F	--	--	--	C
Mortuary refrigerated room accommodates 5 cadaver carts. The unit is used in hospital morgues and funeral homes to store cadavers under refrigeration where the cadaver cart is also the autopsy table. Custom built to meet site requirements. [Prices and refrigerator configuration will vary depending on site requirements.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:		
EA		IN:	103	162	139	3,364 lb	1:	208	1	17	HZ SWITCH: NO		11,840
EA		CM:	262	411	353	1,528 kg	2:	115	1	1	DEPENDENT: YES		
R8215	4110	Refrigerated Room, Mortuary, 6 Cart	A	A	A	A	--	I	F	--	--	--	C
Mortuary refrigerated room accommodates 6 cadaver carts. The unit is used in hospital morgues and funeral homes to store cadavers under refrigeration where the cadaver cart is also the autopsy table. Custom built to meet site requirements. [Price does not include mechanical or electrical installation. Prices and refrigerator configuration will vary depending on site requirements. Price differences verified. Jewett International Corp also provides refrigerated mortuary rooms, however they are all custom designed and priced accordingly.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:		
EA		IN:	96	161	380	-- lb	1:	208	1	20	HZ SWITCH: NO		--
EA		CM:	244	409	965	-- kg	2:	--	--	--	DEPENDENT: YES		--
R8400	4110	Refrigerator, Passthru, 50 Cubic Feet, 84x53x40	A	A	A	A	--	--	A	--	--	--	--
Pass through refrigerator, approximately 50 cubic feet. This unit has 2 sections with a pass through feature. All components of the self-contained refrigeration system are mounted on top of the cabinet and concealed behind a louvered grill. This unit is used in large kitchens of hotels, restaurants and hospitals for food storage.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:		
EA		IN:	86	57	40	961 lb	1:	120	1	12	HZ SWITCH: NO		3,300
EA		CM:	218	145	102	437 kg	2:	--	--	--	DEPENDENT: YES		
R8420	4110	Refrigerator, Passthru, 75 Cubic Feet, 84x78x40	A	A	A	A	--	--	A	--	--	--	--
Pass through refrigerator, approximately 75 cubic feet. This unit is used in commercial kitchens and opens on both sides for easy access to cold storage items. Unit is also used in hospitals and laboratories to store perishables. [Hobart Corp. anticipates transferring its refrigeration line to Traulsen during 2002.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:		
EA		IN:	84	84	40	995 lb	1:	120	1	16	HZ SWITCH: NO		5,400
EA		CM:	214	213	102	452 kg	2:	--	--	--	DEPENDENT: YES		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
R8450	4110	Refrigerator, Rollthru, 40 Cubic Feet	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Roll through refrigerator, approximately 40 cubic feet and 89" H x 39" W x 30" D. This unit accommodates the cart loading feature through the refrigerator from kitchen to service area. The unit is normally used in commercial establishments, schools and hospitals. [The GSA price for Model 1 is \$4,128.00.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	92	39	40	675 lb	1:	120	1	14	NO		3,780					
		CM:	234	99	102	307 kg	2:	--	--	--	DEPENDENT: YES							
R8470	4110	Refrigerator, Rollthru, 75 Cubic Feet, 89x67x40	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
Roll thru refrigerator. Unit is designed to roll a service cart through both ends of the refrigerator. All refrigeration components are self-contained, mounted on top of the cabinet and concealed behind a louvered grill. This unit is used in commercial restaurants, hospitals and hotels to support cart service.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	89	69	41	1,424 lb	1:	120	1	16	NO		6,340					
		CM:	226	175	104	647 kg	2:	--	--	--	DEPENDENT: YES							
R8600	4110	Refrigerator, Prefab, 320 Cubic Feet, 108x108x108	A	A	A	A	--	--	C	--	--	--	--	--	--	--	--	--
Prefabricated refrigerator. Unit is an architect planned, custom-sized, walk-in cooler. It has a side mounted unitized saddle and self-contained easily serviced refrigeration system assembled on the steel channel (saddle). Unit is used for bulk, indoor cold storage in commercial institutions and hospital kitchens. Size and shape may vary depending on site configuration.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	108	108	108	2,460 lb	1:	208	1	20	NO		--					
		CM:	275	274	275	1,115 kg	2:	--	--	--	DEPENDENT: YES							
R9600	4110	Shelving, Wire, Chrome, Mobile, 65x25x26	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Mobile wire shelving. This shelving can speed service by enabling preparation of food in advance and providing easy material handling. The unit also provides a system of sorting and separating a variety of items to assist in bussing and dishwashing, backup serving lines and providing extra storage. Shelving is used in hospital kitchens for food preparation and storage. To be used with roll-through refrigerators. To insure compatibility with the roll-in refrigerator, verification of size is required.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	69	25	27	125 lb	1:	--	--	--	NO		--					
		CM:	175	64	69	57 kg	2:	--	--	--	DEPENDENT: NO							
S0105	6530	Sterilizer, STM, GV, 1DO, CAB, 16x16x26 Chamber	A	A	A	A	--	--	B	F	--	A	--	--	--	--	--	--
A cabinet mounted, single power door (vertical sliding), gravity, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 100°C to 135°C (212°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). [Chamber size for Model 1 is 17.5" x 17.5" x 26" D.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	75	27	36	750 lb	1:	120	1	12	NO		4,300					
		CM:	190	69	91	341 kg	2:	--	--	--	DEPENDENT: YES							
S0107	6530	Sterilizer, Elec, GV, 1DO, CAB, Small Chamber	A	A	A	A	--	--	D	F	--	--	--	--	--	--	--	--
A cabinet mounted, single power door (vertical sliding), gravity, sterilizer with integral steam generator w/ approximately 16"H x 16"W x 26"D chamber. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 100°C to 135°C (212°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). Various electrical configurations are available for the integral steam generator, for pricing purposes 208V, 50/60HZ, 3PH, 84AMPS is used. [Chamber size for Model 1 is 17.5" x 17.5" x 26" D.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:					
EA		IN:	75	27	36	924 lb	1:	120	1	12	NO		6,050					
		CM:	190	69	91	420 kg	2:	208	3	84	DEPENDENT: YES							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
S0125	6530	Sterilizer, Stm, VAC, 1DO, CAB, 16x16x26 Chamber	A	A	A	A	--	B	F	--	A	--	--					
<p>A cabinet mounted, single power door (vertical sliding), vacuum, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110°C to 135°C (230°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). [Getting/Castle (Cage Code 32510) has a full line of sterilizers. Chamber size differs from nomenclature.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		HZ SWITCH:		BTUs / HR:					
EA		IN:	75	28	36	980 lb	1:	120	1	12	NO		4,300					
		CM:	190	71	91	445 kg	2:	--	--	--	DEPENDENT: YES							
S0127	6530	Sterilizer, Elec, VAC, 1DO, CAB, 16x16x26 Chamber	A	A	A	A	--	D	F	--	--	--						
<p>A cabinet mounted, single power door (vertical sliding), vacuum, sterilizer with integral steam generator. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110°C to 135°C (230°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). Various electrical configurations are available for the integral steam generator, for pricing purposes 208V, 50/60HZ, 3PH, 84AMPS is used.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		HZ SWITCH:		BTUs / HR:					
EA		IN:	75	39	45	1,130 lb	1:	120	1	16	NO		6,050					
		CM:	190	99	114	513 kg	2:	208	3	84	DEPENDENT: YES							
S0137	6530	Sterilizer,Stm,VAC,2DO,RCSD,1WLL,16x16x26 Chamber	A	A	A	A	--	B	F	--	A	--						
<p>A recessed mounted (through one wall), double power doors (vertical sliding), vacuum, sterilizer utilizing a remote electric steam generator. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110°C to 135°C (230°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). NOTE: For the electric steam generator, 30 kW is recommended, refer to JSN: S1815. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		HZ SWITCH:		BTUs / HR:					
EA		IN:	75	28	36	989 lb	1:	120	1	12	NO		5,100					
		CM:	191	71	91	449 kg	2:	--	--	--	DEPENDENT: YES							
S0145	6530	Sterilizer, Stm, LAB, 1DO, CAB, 16x16x26 Chamber	A	A	A	A	--	B	F	--	A	--						
<p>A cabinet mounted, single power door (vertical sliding), laboratory, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose low temperature sterilization for such laboratory processes as pasteurization, inspissation, and fractional, at temperatures in the range from 76°C to 99°C (169°F to 210°F). This sterilizer also has a liquid cycle, at temperatures in the range from 100°C to 121°C (212°F to 250°F), and can be used for general purpose gravity steam sterilization of hospital and laboratory supplies, at temperatures in the range from 110°C to 135°C (230°F to 275°F). [Getting/Castle (Cage Code 32510) has a full line of sterilizers. Chamber size differs from nomenclature.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		HZ SWITCH:		BTUs / HR:					
EA		IN:	75	28	36	980 lb	1:	120	1	12	NO		4,300					
		CM:	190	71	91	445 kg	2:	--	--	--	DEPENDENT: YES							
S0190	6530	Rack, 2SH, 16x16x26 Chamber	A	A	A	A	--	--	--	--	--	--						
<p>Rack with two extendable shelves for use with sterilizers having a 16X16X26 chamber. For use in providing loading efficiency for a wide variety of mixed or single item loads.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 0		HZ SWITCH:		BTUs / HR:					
EA		IN:	16	16	26	18 lb	1:	--	--	--	NO		--					
		CM:	41	41	66	9 kg	2:	--	--	--	DEPENDENT: NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES						
			A	N	A	V	I	1	2	3	4	5	6
S0210	6530	Sterilizer,Stm,GV,1DO,RCSD, 1WLL, 20x20x38 Chamber	A	A	A	A	--	B	F	--	A	--	--
<p>A recessed mounted (through one wall), single power door (vertical sliding), gravity, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 100°C to 135°C (212°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). [Chamber size for Model 1 is 21" x 21" x 38"D.]</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS		HZ: 50/60		BTUs / HR:			
EA		IN: 80	30	46	1,231 lb	1: 120	1	12	HZ SWITCH: NO		7,000		
		CM: 203	76	117	559 kg	2: --	--	--	DEPENDENT: YES				
S0215	6530	Sterilizer,Stm,GV,2DO,RCSD,1WLL, 20x20x38 Chamber	A	A	A	A	--	B	F	--	A	--	--
<p>A recessed mounted (through one wall), double power doors (vertical sliding), gravity, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 100°C to 135°C (212°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). [Model 1 chamber size is 21" x 21" x 38"D.]</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS		HZ: 50/60		BTUs / HR:			
EA		IN: 75	30	48	1,606 lb	1: 120	1	12	HZ SWITCH: NO		5,300		
		CM: 190	76	122	730 kg	2: --	--	--	DEPENDENT: YES				
S0220	6530	Sterilizer,Stm,GV,2DO,RCSD 2WLL, 20x20x38 Chamber	A	A	A	A	--	B	F	--	A	--	--
<p>A recessed mounted (through two walls), double power doors (vertical sliding), gravity, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 100°C to 135°C (212°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). [Chamber size for Model 1 is 21" x 21" x 38"D.]</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS		HZ: 50/60		BTUs / HR:			
EA		IN: 75	30	46	1,606 lb	1: 120	1	12	HZ SWITCH: NO		3,833		
		CM: 190	76	117	730 kg	2: --	--	--	DEPENDENT: YES				
S0225	6530	Sterilizer, Stm, VAC, 1DO, CAB, 20x20x38 Chamber	A	A	A	A	--	B	F	--	A	--	--
<p>A cabinet mounted, single power door (vertical sliding), vacuum, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110°C to 135°C (230°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). [Chamber size for Model 1 is 21" x 21" x 38"D.]</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS		HZ: 50/60		BTUs / HR:			
EA		IN: 75	30	46	1,231 lb	1: 120	1	12	HZ SWITCH: NO		7,000		
		CM: 190	76	117	559 kg	2: --	--	--	DEPENDENT: YES				
S0235	6530	Sterilizer,Stm,VAC,2DO,RCSD 1WLL, Medium Chamber	A	A	A	A	--	B	F	--	A	--	--
<p>A recessed mounted (through one wall), double power doors (vertical sliding), vacuum, sterilizer utilizing facility supplied steam w/ approximately 20"H x 20"W x 38"D chamber. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110°C to 135°C (230°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F).</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS		HZ: 50/60		BTUs / HR:			
EA		IN: 75	30	46	1,606 lb	1: 120	1	12	HZ SWITCH: NO		7,800		
		CM: 190	76	117	730 kg	2: --	--	--	DEPENDENT: YES				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES																																				
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6																									
S0237	6530	Sterilizer,ELEC,VAC,2DO,RCSD 1WLL, 20x20x38 Cham	A	A	A	A	--	D	F	--	--	--	--	--	--	--	--																										
<p>A recessed mounted (through one wall), double power doors (vertical sliding), vacuum, sterilizer with integral steam generator. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110øC to 135øC (230øF to 275øF). A liquid cycle is also provided at temperatures in the range from 100øC to 121øC (212øF to 250øF). NOTE: Various electrical configurations are available for the integral steam generator, for pricing purposes 208V, 50/60HZ, 3PH, 84AMPS is used. [No other source(s) identified with this description/specification]</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>75</td> <td>190</td> <td>30</td> <td>76</td> <td>1,726 lb 784 kg</td> <td>1:</td> <td>120</td> <td>1</td> <td>12</td> <td>NO</td> <td>YES</td> <td>9,550</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2:</td> <td>208</td> <td>3</td> <td>84</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	75	190	30	76	1,726 lb 784 kg	1:	120	1	12	NO	YES	9,550							2:	208	3	84			
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																															
EA	75	190	30	76	1,726 lb 784 kg	1:	120	1	12	NO	YES	9,550																															
						2:	208	3	84																																		
S0290	6530	Rack, 2SH, 20x20x38 CHMBR	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--																										
<p>Rack with two extendable shelves for use with sterilizers having a 20X20X38 chamber. For use in providing loading efficiency for a wide variety of mixed or single item loads. [Model 3 does not have a picture of the product, only a quote from the company.]</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>20</td> <td>51</td> <td>20</td> <td>51</td> <td>18 lb 9 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	20	51	20	51	18 lb 9 kg	1:	--	--	--	NO	NO	--							2:	--	--	--			
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																															
EA	20	51	20	51	18 lb 9 kg	1:	--	--	--	NO	NO	--																															
						2:	--	--	--																																		
S0295	6530	Loading Car & Transfer Carriage, 20x20x38 Chamber	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--																										
<p>Loading car, transfer carriage, and chamber tracks, for use with sterilizers having a 20x20x38 chamber. Loading car is a welded, CRS framework with two removable shelves of CRS welded sheet metal and wire. Transfer carriage is constructed of welded stainless steel with bottom shelf and four swivel casters. For loading and unloading 20x20x38 sterilizers and for transferring goods to and from processing areas. [No other source(s) identified with this description/specification]</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>49</td> <td>124</td> <td>20</td> <td>51</td> <td>190 lb 87 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	49	124	20	51	190 lb 87 kg	1:	--	--	--	NO	NO	--							2:	--	--	--			
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																															
EA	49	124	20	51	190 lb 87 kg	1:	--	--	--	NO	NO	--																															
						2:	--	--	--																																		
S0332	6530	Sterilizer,Stm,VAC,1DO,RCSD 1WLL,24x36x36 Chamber	A	A	A	A	--	B	F	D	A	--	--	--	--	--	--																										
<p>A recessed mounted (through one wall), single door (right or left-hinged, appropriate door configuration to be indicated on equipment elevation drawings), vacuum, sterilizer utilizing a remote electric steam generator. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110øC to 135øC (230øF to 275øF). A liquid cycle is also provided at temperatures in the range from 100øC to 121øC (212øF to 250øF). NOTE: For the electric steam generator, refer to JSN: S1830. Door may be power operated. Pricing based upon manual door operation. [Getting/Castle (Cage Code 32510) has a full line of sterilizers. Chamber size differs from nomenclature.]</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>75</td> <td>190</td> <td>45</td> <td>114</td> <td>3,800 lb 1,726 kg</td> <td>1:</td> <td>120</td> <td>1</td> <td>10</td> <td>NO</td> <td>YES</td> <td>12,500</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2:</td> <td>120</td> <td>1</td> <td>15</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	75	190	45	114	3,800 lb 1,726 kg	1:	120	1	10	NO	YES	12,500							2:	120	1	15			
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																															
EA	75	190	45	114	3,800 lb 1,726 kg	1:	120	1	10	NO	YES	12,500																															
						2:	120	1	15																																		
S0395	6530	Loading Car & Transfer Carriage, Large Chamber	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--																										
<p>Loading car and transfer carriage for use with sterilizers having a 24"W x 36"H x36"D chamber. Loading car is a welded, CRS framework with two full-length adjustable shelves of CRS welded sheet metal and wire. Transfer carriage is constructed of a welded CRS or painted for corrosion protection frame and provided two fixed and two swivel casters. Loading car is secured to the transfer carriage by a locking mechanism. For loading and unloading 24x36x36 sterilizers and for transferring goods to and from processing areas.</p>			<table border="1"> <thead> <tr> <th>UNIT OF ISSUE:</th> <th>HEIGHT IN:</th> <th>WIDTH CM:</th> <th>DEPTH IN:</th> <th>DEPTH CM:</th> <th>WEIGHT</th> <th>VOLTS</th> <th>PHASE</th> <th>AMPS</th> <th>HZ:</th> <th>HZ SWITCH:</th> <th>DEPENDENT:</th> <th>BTUs / HR:</th> </tr> </thead> <tbody> <tr> <td>EA</td> <td>58</td> <td>147</td> <td>28</td> <td>71</td> <td>218 lb 99 kg</td> <td>1:</td> <td>--</td> <td>--</td> <td>--</td> <td>NO</td> <td>NO</td> <td>--</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2:</td> <td>--</td> <td>--</td> <td>--</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:	EA	58	147	28	71	218 lb 99 kg	1:	--	--	--	NO	NO	--							2:	--	--	--			
UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH IN:	DEPTH CM:	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:																															
EA	58	147	28	71	218 lb 99 kg	1:	--	--	--	NO	NO	--																															
						2:	--	--	--																																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6		
S0405	6530	Sterilizer, STM, GV, 1DO, CAB, 24x36x48 Chamber	A	A	A	A	--	B	F	D	A	--	--							
<p>A cabinet mounted, single door (right or left-hinged, appropriate door configurations to be indicated on equipment elevation drawings), gravity, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 100°C to 138°C (212°F to 280°F). A liquid cycle is also provided at temperatures in the range from 100°C to 123°C (212°F to 254°F). One manufacturer requires air for their manual door operation only. Power door operation is available from this manufacturer. Pricing based upon manual door operation. [The Getinge chamber size is 26.5x36x53 inches.]</p>																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60				BTUs / HR:							
EA		IN:	75	59	76	3,300 lb	1:	120	1	15	HZ SWITCH: NO				14,650					
		CM:	190	150	193	1,499 kg	2:	--	--	--	DEPENDENT: YES									
S0432	6530	Sterilizer,Stm,VAC,1DO,RCSD 1WLL,24x36x48 Chamber	A	A	A	A	--	B	F	D	A	--	--							
<p>A recessed mounted (through one wall), single door (right or left-hinged, appropriate door configuration to be indicated on equipment elevation drawings), vacuum, sterilizer utilizing a remote electric steam generator. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110°C to 135°C (230°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). NOTE: For the electric steam generator, refer to JSN: S1830. Door may be power operated. Pricing based upon manual door operation. [Getting/Castle (Cage Code 32510) has a full line of sterilizers. Chamber size differs from nomenclature.]</p>																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60				BTUs / HR:							
EA		IN:	75	44	68	4,200 lb	1:	120	1	15	HZ SWITCH: NO				14,600					
		CM:	190	112	173	1,907 kg	2:	--	--	--	DEPENDENT: YES									
S0442	6530	Sterilizer,Stm,VAC,2DO,RCSD 2WLL,24x36x48 Chamber	A	A	A	A	--	B	F	D	A	--	--							
<p>A recessed mounted (through two walls), double door (right or left-hinged, appropriate door configuration to be indicated on equipment elevation drawings), vacuum, sterilizer utilizing a remote electric steam generator. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110°C to 135°C (230°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). NOTE: For the electric steam generator, refer to JSN: S1830. Door may be power operated. Pricing based upon manual door operation. [Model 1, Getting/Castle (Cage Code 32510) has a chamber size that differs from nomenclature and is 26.5" W x 36" H x 53" L.]</p>																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60				BTUs / HR:							
EA		IN:	75	59	92	3,800 lb	1:	120	1	10	HZ SWITCH: NO				13,800					
		CM:	190	150	234	1,726 kg	2:	--	--	--	DEPENDENT: YES									
S0450	6530	Sterilizer,Stm,LAB,1DO,RCSD 1WLL, 24x36x48 Chamber	A	A	A	A	--	B	F	D	A	--	--							
<p>A recessed mounted (through one wall), single door (right or left-hinged, appropriate door configuration to be indicated on equipment elevation drawings), laboratory, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose low temperature sterilization for such laboratory processes as pasteurization, inspissation, and fractional, at temperatures in the range from 76°C to 99°C (169°F to 210°F). This sterilizer also has a liquid cycle, at temperatures in the range from 100°C to 121°C (212°F to 250°F), and can be used for general purpose gravity steam sterilization of hospital and laboratory supplies, at temperatures in the range from 110°C to 135°C (230°F to 275°F). One manufacturer requires air for their manual door operation only and offers an optional power door operation. Pricing based upon manual door operation. [Model 1 chamber size is 26.5" W x 36" H x 53" D.]</p>																				
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60				BTUs / HR:							
EA		IN:	75	59	68	4,200 lb	1:	120	1	12	HZ SWITCH: NO				14,650					
		CM:	190	150	173	1,907 kg	2:	--	--	--	DEPENDENT: YES									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
S0495	6530	Loading Car & Transfer Carriage, 24x36x48 Chamber	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Loading car and transfer carriage for use with sterilizers having a 24x36x48 chamber. Loading car is a welded, CRS framework with two full-length adjustable shelves of CRS welded sheet metal and wire. Transfer carriage is constructed of a welded CRS or painted for corrosion protection frame and provided two fixed and two swivel casters. Loading car is secured to the transfer carriage by a locking mechanism. For loading and unloading 24x36x48 sterilizers and for transferring goods to and from processing areas. [No other source(s) identified with this description/specification. Getinge has increased chamber size to 26Wx36Hx50L]			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			EA	58	147	64	123 kg	270 lb	1:	--	--	--	50/60	NO	NO	--		
S0505	6530	Sterilizer, STM, GV, 1DO, CAB, 24x36x60 Chamber	A	A	A	A	--	B	F	D	A	--	--	--	--	--	--	--
A cabinet mounted, single door (right or left-hinged, appropriate door configuration to be indicated on equipment elevation drawings), gravity, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 100øC to 138øC (212øF to 280øF). A liquid cycle is also provided at temperatures in the range from 100øC to 123øC (212øF to 254øF). One manufacturer requires air for their manual door operation only. Power door operation is available from this manufacturer. Pricing based upon manual door operation.			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			EA	75	190	87	1,680 kg	3,700 lb	1:	120	1	10	50/60	NO	YES	16,800		
S0530	6530	Sterilizer,Stm,VAC,1DO,RCSD 1WLL,24x36x60 Chamber	A	A	A	A	--	B	F	D	A	--	--	--	--	--	--	--
A recessed mounted (through one wall), single door (right or left-hinged, appropriate door configurations to be indicated on equipment elevation drawings), vacuum, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110øC to 135øC (230øF to 275øF). A liquid cycle is also provided at temperatures in the range from 100øC to 121øC (212øF to 250øF). One manufacturer requires air for their manual door operation only. Power door operation is available. One manufacturer will require an additional electric service for their power door. Pricing based upon manual door operation.			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			EA	75	190	203	1,680 kg	3,700 lb	1:	120	1	12	50/60	NO	YES	16,800		
S0535	6530	Sterilizer,Stm,VAC,2DO,RCSD 1WLL, 24x36x60 Chamber	A	A	A	A	--	B	F	D	A	--	--	--	--	--	--	--
A recessed mounted (through one wall), double door (right or left-hinged, appropriate door configurations to be indicated on equipment elevation drawings), vacuum, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110øC to 135øC (230øF to 275øF). A liquid cycle is also provided at temperatures in the range from 100øC to 121øC (212øF to 250øF). Door may be power operated. Pricing based upon manual door operation.			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			EA	75	190	246	1,726 kg	3,800 lb	1:	120	1	15	50/60	NO	YES	16,500		
S0595	6530	Loading Car & Transfer Carriage, 24x36x60 Chamber	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Loading car and transfer carriage for use with sterilizers having a 24x36x60 chamber. Loading car is a welded, CRS framework with two full-length adjustable shelves of CRS welded sheet metal and wire. Transfer carriage is constructed of a welded CRS or painted for corrosion protection frame and provided two fixed and two swivel casters. Loading car is secured to the transfer carriage by a locking mechanism. For loading and unloading 24x36x60 sterilizers and for transferring goods to and from processing areas.			UNIT OF ISSUE:			HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS 1:	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:		
			EA	58	147	196	128 kg	280 lb	1:	--	--	--	0	NO	NO	--		

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
S0905	6530	Washer, Multi-Chamber (5), Automated	A	A	A	A	--	F	G	D	A	--	E					
<p>A fully automated, five multi-chamber (pre-wash, sonic cleaning, washing, rinsing, and drying), mechanical washer. The system is controlled by microcomputers that monitor and control system operations and functions and provides visual indication of deviations. A printer-recorder documents and records each cycle performance. Features an automated two rack load/indexing station and single rack unload/indexing station. Processes up to a minimum of 10 single or 40 instrument trays per hour. System designed to clean and decontaminate medical utensils and surgical instruments in a high production linear flow. Various electrical configurations are available, for pricing purposes 208V, 60HZ, 3PH, 60AMPS is used. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:			BTUs / HR:						
EA		IN:	92	45	252	6,200 lb	1:	208	3	60	60			NO		18,948		
		CM:	234	114	640	2,815 kg	2:	--	--	--	DEPENDENT:			YES				
S0910	6530	Washer, Multi-Chamber (4), Automated	C	C	C	C	--	F	G	D	A	--	E					
<p>A fully automated, four multi-chamber (pre-wash, washing, rinsing, and drying), mechanical washer. The system is controlled by microcomputers that monitor and control system operations and functions and provides visual indication of deviations. A printer-recorder documents and records each cycle performance. Features an automated two rack load/indexing station and single rack unload/indexing station. Processes up to 40 instrument trays per hour. System designed to clean and decontaminate medical utensils and surgical instruments in a high production linear flow. Various electrical configurations are available, for pricing purposes 208V, 60HZ, 3PH, 58AMPS is used. [Getting USA has discontinued their 4 chamber washer, model 7642. However, they have available Model 7662 (JSN S0905) a 5 chamber washer. No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:			BTUs / HR:						
EA		IN:	92	45	222	6,000 lb	1:	208	3	58	60			NO		14,200		
		CM:	234	114	564	2,724 kg	2:	--	--	--	DEPENDENT:			YES				
S0915	6530	Washer/Disinfector,STM,2DO,RCSD1WLL,23X19X24 Cham	C	C	C	C	--	F	G	--	A	--	E					
<p>A recessed mounted (through one wall), double doors (bottom hinged), multi-level, mechanical, washer/disinfector, minimum chamber size 23X19X24, utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Processing cycles are pre-programmed with pre-wash, wash/cleaning, rinse, thermal rinse/disinfection, instrument lubrication and drying. For use in health care facilities and laboratories where reusable items (instruments, utensils, anesthesia/respiratory goods, and glassware) are handled for decontamination purposes. This unit is not a substitute for terminal sterilization. Unit available with various electrical configurations, options, and accessories. Price based upon 208V, 3-phase, with various options. [No other source(s) identified with this description/specification. HAMO USA has been purchased by Steris but the LS 2000 is still available.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:			BTUs / HR:						
EA		IN:	76	32	28	880 lb	1:	208	3	25	50/60			NO		3,500		
		CM:	193	81	71	400 kg	2:	--	--	--	DEPENDENT:			YES				
S0920	6530	Washer/Disinfector, STM, 1DO, CAB, 26X24X24 Cham	C	C	C	C	--	F	G	D	A	--	E					
<p>A cabinet mounted, single door (vertical sliding w/ tempered glass window), multi-level, mechanical, washer/disinfector, minimum chamber size 26X24X24, utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Processing cycles are pre-programmed with pre-wash, wash/cleaning, rinse, and thermal rinse/disinfection. For use in health care facilities and laboratories where reusable items (instruments, utensils, anesthesia/respiratory goods, and glassware) are handled for decontamination purposes. This unit is not a substitute for terminal sterilization. Unit available with manual or power door, various electrical configurations, options, and accessories. Price based upon power door, 208V, 3-phase, with various options. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:			BTUs / HR:						
EA		IN:	90	44	36	1,200 lb	1:	208	3	20	50/60			NO		3,500		
		CM:	229	112	91	545 kg	2:	--	--	--	DEPENDENT:			YES				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
S0925	6530	Washer/Disinfector, STM, 1DO, CAB, 23X19X24 Cham	C	C	C	C	--	F	G	--	A	--	E					
<p>A cabinet mounted, single door (bottom hinged), multi-level, mechanical, washer/disinfector, minimum chamber size 23X19X24, utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Processing cycles are pre-programmed with pre-wash, wash/cleaning, rinse, thermal rinse/disinfection, instrument lubrication and drying. For use in health care facilities and laboratories where reusable items (instruments, utensils, anesthesia/respiratory goods, and glassware) are handled for decontamination purposes. This unit is not a substitute for terminal sterilization. Unit available with various electrical configurations, options, and accessories. Price based upon 208V, 3-phase, with various options. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN:	76	32	28	880 lb	1:	208	3	25	HZ SWITCH: NO		3,500					
		CM:	193	81	71	400 kg	2:	--	--	--	DEPENDENT: YES							
S0930	6530	Washer/Disinfector, STM, 1DO, RCSD1WLL, 23X19X24 Cham	C	C	C	C	--	F	G	--	A	--	E					
<p>A recessed mounted (through one wall), single door (bottom hinged), multi-level, mechanical, washer/disinfector, minimum chamber size 23X19X24, utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Processing cycles are pre-programmed with pre-wash, wash/cleaning, rinse, thermal rinse/disinfection, instrument lubrication and drying. For use in health care facilities and laboratories where reusable items (instruments, utensils, anesthesia/respiratory goods, and glassware) are handled for decontamination purposes. This unit is not a substitute for terminal sterilization. Unit available with various electrical configurations, options, and accessories. Price based upon 208V, 3-phase, with various options. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN:	76	32	28	880 lb	1:	208	3	25	HZ SWITCH: NO		3,500					
		CM:	193	81	71	400 kg	2:	--	--	--	DEPENDENT: YES							
S0940	6530	Washer/Disinfector, STM, 1DO, RCSD1WLL, 26X24X24 Cham	C	C	C	C	--	F	G	D	A	--	E					
<p>A recessed mounted (through one wall), single door (vertical sliding with tempered glass window), multi-level, mechanical, washer/disinfector, minimum chamber size 26X24X24, utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Processing cycles are pre-programmed with pre-wash, wash/cleaning, rinse, and thermal rinse/disinfection. For use in health care facilities and laboratories where reusable items (instruments, utensils, anesthesia/respiratory goods, and glassware) are handled for decontamination purposes. This unit is not a substitute for terminal sterilization. Unit available with manual or power door, various electrical configurations, options, and accessories. Price based upon power door, 208V, 3-phase, with various options. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN:	90	44	36	1,200 lb	1:	208	3	20	HZ SWITCH: NO		3,500					
		CM:	229	112	91	545 kg	2:	--	--	--	DEPENDENT: YES							
S0955	6530	Washer/Disinfector, STM, 2DO, RCSD1WLL, LDG/UNLDG STA	C	C	C	C	--	F	D	D	A	--	E					
<p>A recessed mounted (through one wall), power double doors (vertical sliding with tempered glass window), multi-level, mechanical, washer/disinfector, minimum chamber size 26X24X24, with automatic, two rack, load and unload stations/modules. Unit utilizes facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Processing cycles are pre-programmed with pre-wash, wash/cleaning, rinse, and thermal rinse/disinfection. For use in health care facilities and laboratories where reusable items (instruments, utensils, anesthesia/respiratory goods, and glassware) are handled for decontamination purposes. This unit is not a substitute for terminal sterilization. Unit available with various electrical configurations, options, and accessories. Price based upon 208V, 3-phase and various options. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN:	90	44	160	3,000 lb	1:	208	3	20	HZ SWITCH: NO		3,500					
		CM:	229	112	406	1,362 kg	2:	120	1	1	DEPENDENT: YES							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
S0960	6530	Washer/Disinfector,STM,2DO,RCSD1WLL,26X24X24 Cham	C	C	C	C	--	F	G	D	A	--	E					
<p>A recessed mounted (through one wall), double door (vertical sliding with tempered glass window), multi-level, mechanical, washer/disinfector, minimum chamber size 26X24X24, utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Processing cycles are pre-programmed with pre-wash, wash/cleaning, rinse, and thermal rinse/disinfection. For use in health care facilities and laboratories where reusable items (instruments, utensils, anesthesia/respiratory goods, and glassware) are handled for decontamination purposes. This unit is not a substitute for terminal sterilization. Unit available with manual or power door, various electrical configurations, options, and accessories. Price based upon power door, 208V, 3-phase, with various options. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN: 90	44	38	1,200 lb	1: 208	3	20	HZ SWITCH: NO		3,500							
		CM: 229	112	97	545 kg	2: --	--	--	DEPENDENT: YES									
S1815	6530	Generator, Steam, Electric, 30 kW	A	A	A	A	--	C	F	--	--	--	--					
<p>An approximately 30 kW electric steam generator/boiler with low water cut-off/level control, water level sight glass, main off/on switch, pilot light, lowdown/drain valves, safety valve, and steam pressure gauge. The unit can deliver steam at operating pressures up to 90 PSIG. and produce a minimum steam output of 87 lbs./hr. Unit provides condensate free steam, between 97% to 100% vapor quality, needed to power sterilizers, water stills, utensil sanitizers, and other steam powered equipment when facility supplied steam is not available. Various electrical configurations are available for the heaters, for pricing purposes 208V, 60HZ, 3PH, 84AMPS is used.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN: 54	32	43	550 lb	1: 120	1	15	HZ SWITCH: NO		1,750							
		CM: 137	81	109	250 kg	2: 208	3	84	DEPENDENT: YES									
S1830	6530	Generator, Steam, Electric, 75 KW	A	A	A	A	--	C	F	--	--	--	--					
<p>A 68 to 75 kW electric steam generator/boiler with low water cut-off/level control, water level sight glass, main off/on switch, pilot light, blowdown/drain valves, safety valve, and steam pressure gauge. The unit can deliver steam at operating pressures up to 90 PSIG and produce a minimum steam output of 205 lbs./hr. Unit provides condensate free steam, between 97% to 100% vapor quality, needed to power sterilizers, water stills, utensil sanitizers, and other steam powered equipment when facility supplied steam is not available. Various electrical configurations are available for the heaters, for pricing purposes 208V, 60HZ, 3PH, 209AMPS is used.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN: 44	31	33	468 lb	1: 208	3	209	HZ SWITCH: NO		3,500							
		CM: 112	79	84	213 kg	2: --	--	--	DEPENDENT: YES									
S2310	6530	Transporter, Rack, Horizontal, Automatic	A	A	A	A	--	--	F	D	--	--	--					
<p>An automatic horizontal rack transporter/conveyor. The unit automatically transports and transfers or accumulates racks/baskets going to or exiting from specific manufacturer's washer/sterilizers or washing equipment. Used in a facility where a high volume of processing of racks/baskets of utensils and instruments are required on a very frequent basis. The unit is sized and configured for facility specific requirements. Pricing based upon a 7' horizontal module. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:							
EA		IN: 37	120	33	400 lb	1: 120	1	30	HZ SWITCH: NO		--							
		CM: 94	305	84	182 kg	2: 208	3	30	DEPENDENT: YES									
S2620	6530	Pasteurizer, Vertical Rotation	C	C	C	C	--	C	B	--	--	--	--					
<p>A vertical rotation pasteurizer with baskets and temperature recorder. Unit features: thermostatically controlled water temperature; automatic cycles; audible and visual signal at end of cycle; power hoist; liquid level control; and a 2.5 cubic foot load capacity. Used for pasteurization (a means of high-level disinfection to kill pathogenic vegetative bacteria and viruses by total immersion in water at 160ø-170øF for 30 minutes) of breathing circuit parts used by respiratory care and anesthesia departments. [No other source(s) identified with this description/specification. Weight shown is for a full unit.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:							
EA		IN: 67	30	32	652 lb	1: 120	1	19	HZ SWITCH: NO		--							
		CM: 170	76	81	296 kg	2: --	--	--	DEPENDENT: YES									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
S2625	6530	Washer/Pasteurizer, Vertical Rotation, Combination	C	C	C	C	--	C	F	--	--	--	--	--	--	--	--	
<p>A fully automatic, compact, combination, vertical rotation, washer/pasteurizer with baskets. Unit features: 30 minute wash and pasteurizing cycles, temperature recorder for pasteurizing cycle, thermostatically controlled water temperature in pasteurizing cycle; visual signal at end of cycle; power hoist; liquid level control; and a 2.5 cubic foot load capacity. Used for washing then pasteurization (a means of high-level disinfection to kill pathogenic vegetative bacteria and viruses by total immersion in water at 160ø-170øF for 30 minutes) of breathing circuit parts used by respiratory care and anesthesia departments. For medium to low volume processing. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	67	30	32	650 lb	1:	240	1	46	DEPENDENT: YES		--					
		CM:	170	76	81	296 kg	2:	--	--	--								
S2627	6530	Washer, Fiber Scope	C	C	C	C	--	B	B	--	--	--	--	--	--	--	--	
<p>A low temperature sterile processing system for sterilizing immersible surgical and diagnostic scopes, cameras, instruments and accessories. The unit shall provide a digital display of cycle data and shall record and print a permanent record of cycles. Units are available in floor, counter top or cart models. [The dimensions for height are with the lid open. Instrument trays are purchased separately at a unit price between \$73.00 and \$582.00 according to size and style. Steris (Model 1) provides a work station cart (model: A1900) as an option for approximately \$2,995. Custom Ultrasonics Inc., (Cage Code SR325) is a fourth source.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	65	38	30	220 lb	1:	120	1	10	DEPENDENT: YES		--					
		CM:	165	97	76	100 kg	2:	--	--	--								
S2630	6530	Dryer, Cabinet, Tubing	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
<p>A bio-clean dryer available in a single or double door unit. The dryer features: tube holder; shelves; pre-filter(s); HEPA filter(s); blower(s); see through door(s); heaters, temperature selection; and automatic timer. The loading capacity of the units depend upon the items (tubes, parts or combination thereof) being dried. Used as a preferred method of drying tubes or parts following pasteurization or other methods of high level disinfection. Dimensions, utility data, and pricing based upon double door unit.</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	86	48	26	387 lb	1:	120	1	18	DEPENDENT: YES		6,800					
		CM:	218	122	66	176 kg	2:	--	--	--								
S2635	6530	Cleaner, Ultrasonic, SNGL Chamber, CAB, F/S	A	A	A	A	--	D	F	--	--	--	--	--	--	--	--	
<p>A free-standing, cabinet mounted, single stainless steel chamber (minimum size 10X24X12), ultrasonic cleaner. The cleaning unit includes the following minimum features: power lid, automatic detergent injector, automatic level controls, automatic timer, and switch fill and drain controls. Sonic cleaning energy provided to the chamber by transducers which are powered by a solid-state generator(s) at a frequency of 40 kHz. Designed for use in surgery reprocessing areas, central processing departments and laboratories to clean surgical instruments and other hardware with sonic energy. [No other source(s) identified with this description/specification]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	46	30	30	500 lb	1:	208	1	30	DEPENDENT: YES		1,400					
		CM:	117	76	76	227 kg	2:	--	--	--								
S2640	6530	Cleaner, Ultrasonic, Console, DBL CHMBR, CAB, F/S	A	A	A	A	--	F	F	--	--	--	--	--	--	--	--	
<p>A free-standing, cabinet mounted, double stainless steel chambers (minimum sizes 10X24X12), ultrasonic cleaner and rinsing and dryer. The cleaning chamber includes the following minimum features: power lid, automatic detergent injector, automatic level controls, automatic timer, and switch fill and drain controls. Sonic cleaning energy provided to the chamber by transducers which are powered by a solid-state generator(s) at a frequency of 40 kHz. The rinse/dryer chamber is of the same basic design, size, and construction as the cleaning chamber. However, the chamber has pre-positioned spray nozzles to provide complete rinse and purified-water rinse coverage and thermostatically controlled recirculated forced hot air for drying. Cleaning and rinse/drying chambers are positioned for either right-to-left or left-to-right workflow. Designed for use to clean surgical instruments and other hardware with sonic energy and effectively spray rinse and dry items after sonic cleaning. [Model 3 uses a 30 kHz frequency generator and is a 208/120V, 3 phase unit.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		HZ SWITCH: NO		BTUs / HR:					
EA		IN:	59	67	31	1,050 lb	1:	220	1	45	DEPENDENT: YES		7,000					
		CM:	150	170	79	477 kg	2:	120	1	60								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES										
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5
S3185	6530	Washer, Cart & Utensil, 2 DO, PIT MNTD, RCSD 2 WLL	A	A	A	A	--	D	G	--	A	--	E				
<p>A recessed (through two walls), pit mounted, double door (right or left-hinged, appropriate configuration to be indicated on equipment elevation drawings), cart and utensil washer (minimum chamber load capacity 78X34X76). A microprocessor-based controller monitors and controls system operations and functions. The unit provides: visual and/or audible indication of cycle operation, programmable treatment time and temperatures, and a minimum of three cycles (wash with detergent, rinse, and drying). For use in central processing to clean and decontaminate, carts, patient-care utensils (IV poles, wheel chairs, stretchers, etc.) and other bulk items. Various electrical configurations are available, for pricing 208V, 60HZ, 3-phase is used. [No other source(s) identified with this description/specification]</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	128	74	90	4,220 lb	1:	208	3	45	NO		21,500				
		CM:	325	188	228	1,916 kg	2:	--	--	--	DEPENDENT: YES						
S4300	6530	Gun, Steam	A	A	A	A	--	J	--	--	A	--	--				
<p>A wall mounted steam gun utilizing facility supplied steam. Steam gun is provided with a 10' high pressure steam hose, 10' detergent hose, detergent tank, two nylon brushes, and one stainless steel brush. Provides a choice of steam only, steam and detergent, hot water and detergent, and hot water only. For use to clean moisture resistant items (carts, racks, and other metal items) that otherwise might require hand scrubbing. [No other source(s) identified with this description/specification]</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	33	14	9	36 lb	1:	--	--	--	NO		--				
		CM:	84	36	23	17 kg	2:	--	--	--	DEPENDENT: NO						
S4800	6530	Sterilizer, SURG INSTRU & Dressing, 10" DIA CHMBR	C	C	C	C	--	--	A	--	--	--	--				
<p>A self-contained, countertop mounted, electrically heated, steam sterilizer. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides visual indication of cycle stages and deviations. A printer-recorder documents and records each cycle performance. For low volume, convenient, steam sterilization of liquids, media, instruments, glassware, and absorbent materials, in clinics and other areas of the health care facility. [Special Note for Model 3. Due to trademark requirements the Ritter M9 Ultraclave must be selected for use in a medical/surgical setting. For Dental use the Midmark M9 Ultraclave must be selected with a unit price of \$4,945. Units appear identical except for the small difference in price.]</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	17	23	25	134 lb	1:	120	1	13	NO		--				
		CM:	43	58	64	61 kg	2:	--	--	--	DEPENDENT: YES						
S4950	6530	Sterilizer, SURG INSTRU & Dressing, 16X26 CHMBR	C	C	C	C	--	--	C	--	--	--	--				
<p>A self-contained, stand mounted, electrically heated, steam sterilizer. The unit is controlled manually and provides audible and visual indication of end of cycle. Temperature ranges are between 110°C to 135°C (230°F to 275°F). Sterilizer to be provided with stand; time and temperature controls; temperature and pressure gauges; safety valve; two trays; and chart recorder. For steam sterilization of liquids, instruments, glassware, and absorbent materials, in clinics and other areas of the health care facility. Various electrical configurations are available and must be specified at the time of ordering. For pricing purposes 208V is used. [Price difference verified. Model 1 requires a dedicated 30 amp circuit. Models 2 and 3 have temperature ranges between 110-121 C.]</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	60	28	35	355 lb	1:	208	1	44	NO		10,239				
		CM:	152	71	89	162 kg	2:	--	--	--	DEPENDENT: YES						
S5500	6530	Sterilizer, Hydrogen Peroxide Gas, 1.75 cu ft Cham	C	C	C	C	--	--	B	--	--	--	--				
<p>A compact low temperature hydrogen peroxide gas plasma sterilizer mounted on a mobile cart. Sterilization chamber shall have a capacity of approximately 1.75 cubic feet. The sterilizer shall be capable of processing metal instruments, plastics, heat and moisture sensitive devices in approximately 45 minutes with no aeration required. Unit shall be equipped with a visual display and audible alarm. A built in printer will provide system performance record for each cycle. [No other source(s) identified with this description/specification. Requires a dedicated 110-120V outlet, NEMA L5-20 plug, and a minimum distance of 3 inches from walls.]</p>																	
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:				
EA		IN:	55	25	32	600 lb	1:	120	1	20	NO		--				
		CM:	140	64	81	273 kg	2:	--	--	--	DEPENDENT: YES						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
S5505	6530	Sterilizer, Hydrogen Peroxide Gas, 3.5 cu ft Cham	C	C	C	C	--	--	G	--	--	--	--	--	--	--	--	--	
A floor mounted, low temperature hydrogen peroxide gas plasma sterilizer. Sterilization chamber shall have a capacity of approximately 3.5 cubic feet (100 liters). The sterilizer shall be capable of processing metal instruments, plastics, heat and moisture sensitive devices in approximately 75 minutes with no aeration required. Unit shall be equipped with a visual display and audible alarm. A built in printer will provide system performance record for each cycle. [No other source(s) identified with this description/specification. Chamber size for Model 2 is 8.8 cubic feet.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	66	40	40	770 lb	1:	208	3	20	NO								
		CM:	168	102	102	350 kg	2:	--	--	--	DEPENDENT: YES								
S9610	6530	Station, Utility / Rack	C	C	C	A	--	--	--	--	--	--	--	--	--	--	--	--	
Rack / utility station. The station consists of a stainless steel countertop, 4-1/2" apron, legs and necessary cross-member supports. The stations are specially designed to handle loading racks or trays for use with a specific manufacturer's related equipment and accessories but may also serve a variety of general uses, such as an accumulating, sorting, inspecting, or processing station. Various station widths/lengths (25" to 126", depending upon manufacturer) are available. Pricing based upon a 50" width/length. [Mortec's unit has a 3-1/2 inch apron.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	36	50	25	160 lb	1:	--	--	--	NO								
		CM:	91	127	64	73 kg	2:	--	--	--	DEPENDENT: NO								
S9765	6530	Washer, Bedpan, CW/STM, WLL MNTD	C	C	C	C	--	B	F	--	A	--	E						
A wall mounted bedpan washer-sanitizer with cold water/steam cycle. By pushing the start button a utensil is automatically flushed with cold water for approximately 30 seconds and then sprayed with steam for approximately 30 seconds to provide through sanitizing. Used to provide a convenient, effective means of processing bedpans and urinals with minimized odors and cross-contamination. Other electrical configurations are available as special option. [1. No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	58	30	21	240 lb	1:	120	1	5	NO								
		CM:	147	76	53	109 kg	2:	--	--	--	DEPENDENT: YES								
S9770	6530	Cart, Loading, Sterilizable	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
All purpose sterilizable loading/supply cart with fixed bottom shelf, two full-length adjustable shelves, and two adjustable retaining rods. The cart is specially constructed to resist the corrosive action of high temperature steam and gas sterilization. For use with cart loading sterilizers and washers to process, transport and store goods. Cart is available in a minimum of two sizes. Dimensions and pricing based on a cart for a chamber size of 26X62X76. [No other source(s) identified with this description/specification]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	58	25	38	170 lb	1:	--	--	--	NO								
		CM:	146	64	97	78 kg	2:	--	--	--	DEPENDENT: NO								
S9800	6530	Sterilizer,Stm,VAC,1DO,RCSD1WLL,F/M, Large Chamber	A	A	A	A	--	B	F	D	A	--	--						
A floor mounted, recessed through one wall, power single door steam sterilizer, with approximately 26"W x 62"D x 42"H chamber (right or left-hinged, appropriate door configurations to be indicated on equipment elevation drawings), vacuum, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Unit provided with a hydraulic cart lift at the door to raise and lower processing carts. For high-volume sterilization of wrapped dry goods and hard goods in hospitals and laboratories. Pre-vacuum cycle temperature in the range from 110°C to 135°C (230°F to 275°F). A gravity and liquid cycle is also provided at temperatures in the range from 100°C to 135°C (212°F to 275°F). [Steris can meet the requirement using the Eagle 3000 Series FLJ unit with modifications. The product would be considered a non-standard fabrication by Steris.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:								
EA		IN:	95	58	66	5,632 lb	1:	120	1	10	NO								
		CM:	241	147	168	2,557 kg	2:	208	3	9	DEPENDENT: YES		26,800						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
S9805	6530	Sterilizer,Stm,VAC,2DO,RCSD2WLL,PIT,26x62x42 Cham	A	A	A	A	--	B	D	E	A	--	--					
		A pit mounted, recessed through two walls, power double doors (right or left-hinged, appropriate door configurations to be indicated on equipment elevation drawings), vacuum, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For high-volume sterilization of wrapped dry goods and hard goods in hospitals and laboratories. Pre-vacuum cycle temperature in the range from 110°C to 138°C (230°F to 280°F). A gravity and liquid cycle is also provided at temperatures in the range from 100°C to 138°C (212°F to 280°F).																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	50/60	HZ SWITCH:	NO	BTUs / HR:				
		EA	IN: 93	55	63	7,132 lb	1: 120	1	15	HZ SWITCH: NO		BTUs / HR: 24,620						
			CM: 236	140	160	3,238 kg	2: 208	3	9	DEPENDENT: YES								
S9810	6530	Sterilizer,Stm,VAC,1DO,RCSD1WLL,PIT,26x62x42 Cham	A	A	A	A	--	B	D	D	A	--	--					
		A pit mounted, recessed through one wall, power single door (right or left-hinged, appropriate door configurations to be indicated on equipment elevation drawings), vacuum sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For high-volume sterilization of wrapped dry goods and hard goods in hospitals and laboratories. Pre-vacuum cycle temperature in the range from 110°C to 138°C (230°F to 280°F). A gravity and liquid cycle is also provided at temperatures in the range from 100°C to 138°C (212°F to 280°F).																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	50/60	HZ SWITCH:	NO	BTUs / HR:				
		EA	IN: 95	55	66	5,632 lb	1: 120	1	15	HZ SWITCH: NO		BTUs / HR: 21,680						
			CM: 241	140	168	2,557 kg	2: 208	3	9	DEPENDENT: YES								
S9815	6530	Sterilizer,Stm,VAC,2DO,RCSD2WLL,F/M,26x62x42 Cham	A	A	A	A	--	B	F	D	A	--	--					
		A floor mounted, recessed through two walls, power double doors (right or left-hinged, appropriate door configurations to be indicated on equipment elevation drawings), vacuum, sterilizer utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Unit provided with a hydraulic cart lift at the door to raise and lower processing carts. For high-volume sterilization of wrapped dry goods and hard goods in hospitals and laboratories. Pre-vacuum cycle temperature in the range from 110°C to 135°C (230°F to 275°F). A gravity and liquid cycle is also provided at temperatures in the range from 100°C to 135°C (212°F to 275°F). [Steris can meet the requirement using the Eagle 3000 Series FLJ unit with modifications. The product would be considered a non-standard fabrication by Steris.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	50/60	HZ SWITCH:	NO	BTUs / HR:				
		EA	IN: 93	55	63	7,132 lb	1: 120	1	15	HZ SWITCH: NO		BTUs / HR: 25,300						
			CM: 236	140	160	3,238 kg	2: 208	1	9	DEPENDENT: YES								
T0005	6625	Electrical Safety Analyzer	C	C	C	C	--	--	A	--	--	--	--					
		Electrical safety analyzer. Characteristics/components include combining all lead connected ECG lead tests measuring individual lead leakage; AC/DC measurement; current consumption; automatic neutral-ground and power-ground resistance and volts. This unit is used for electrical safety testing, preventive maintenance programs and equipment repair. Battery powered models are available. [Price difference verified.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:				
		EA	IN: 5	10	11	8 lb	1: 120	1	15	HZ SWITCH: NO		BTUs / HR: --						
			CM: 13	25	28	4 kg	2: --	--	--	DEPENDENT: NO								
T0010	6525	Beam Analyzer, Radiation Therapy	C	C	C	C	--	--	A	--	--	--	--					
		Radiation Beam Analyzer This is a quality assurance system that measures therapy radiation sources, including dose and dose rates, enabling user calculation of beam constancy, flatness and symmetry.																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	YES	BTUs / HR:				
		EA	IN: 10	14	17	26 lb	1: 115	1	5	HZ SWITCH: YES		BTUs / HR: --						
			CM: 25	36	43	12 kg	2: --	--	--	DEPENDENT: NO								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
T0015	6625	Defibrillator Analyzer, Automatic, Portable	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Defibrillator analyzer. Characteristics/components include automatic and portable with direct reading; accurately verifies the output characteristics of all defibrillators while simulating the resistance of the human body; output energy measured in joules or watt seconds on two scales of 0-200.0 or 0-1000; output energy remains displayed until the reset button is depressed once the defibrillator is fired; and output jacks provided for oscilloscope connection to observe defibrillator pulse wave shape. Shall include the optional pacemaker testing module if required by the end user. Battery powered models are available.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			4	10	11	9 lb	1: 120	1	1	60	NO	NO	--					
			10	25	28	4 kg	2: --	--	--				--					
T0020	6625	Stand, Test, Radiological Compliance	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Adjustable test stand which accepts a test pattern disk for determining radiological tube focal spots. The stand can also be used to determine half layer values and light-radiation field registrations. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			18	12	9	11 lb	1: --	--	--	--	NO	NO	--					
			46	30	23	5 kg	2: --	--	--				--					
T0025	6625	Meter, Radiation Survey	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Radiation survey meter. Characteristics/components include hand held and battery operated with a built-in detector; and ability to detect alpha, beta, gamma and x-ray radiation. This unit is used for spot-checking laboratories and other work areas for contamination of equipment, counter tops and floors. The unit is also well suited for detecting accidental exposures to personnel clothes, checking x-ray equipment for possible leakage or locating small spills. [Price difference verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			9	7	9	6 lb	1: --	--	--	0	NO	NO	--					
			23	18	23	3 kg	2: --	--	--				--					
T0030	6525	Radiation-Light Field Analyzer	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Light and radiation field analyzer for quality assurance testing of radiation therapy devices. Unit is self contained and checks the coincidence of light and radiation fields, symmetry of radiation field, flatness of radiation field, and penumbra size of the radiation field. Unit has built in graphics printer for hard copy output of scanned information. [Sun Nuclear Corp. is now the sole distributor of the Profiler model analyzer. No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			16	10	2	9 lb	1: 120	1	2	60	NO	NO	--					
			40	25	4	4 kg	2: --	--	--				--					
T0090	3630	Bench, Loom	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
The loom bench shall be approximately 24Wx11Dx40L inches and made of wood. It shall have a storage area below the seat. This bench seat is used during the operation of a floor loom.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			24	14	40	35 lb	1: --	--	--	--	NO	NO	--					
			61	36	102	16 kg	2: --	--	--				--					
T0100	9195	Bench, Woodwork, Drawers, Shelves, 32x72x30	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Woodwork bench. Characteristics/components include solid maple top and open leg bench. A variety of accessories include drawers, shelves, and the overall height of the bench that varies with thickness of top. [Database price is for base unit and top only. Accessories priced separately.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			32	72	30	163 lb	1: --	--	--	--	NO	NO	--					
			81	183	76	74 kg	2: --	--	--				--					

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES									
				R	A	F	A	H		1	2	3	4	5	6				
T0105	7195	Bench, Woodwork, 4 Vises	C C C C --																
Woodwork bench approximately 32" H x 64" W x 54" D. Characteristics/components include four vise hard maple construction top laminated with steel channel end splines; leg frame that provides sturdy foundation; lower shelf that provides ample storage area; vises have heavy steel screw with double lead fast running thread; and provide maximum operating speeds. [Woodcraft (Cage Code 0J7S6) is provided as a potential alternate source They have workbench tops that can be custom built, however, their bench size is only 20" wide and comes with only 2 vises. No other source (s) identified with this description/specification.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	32	64	54	225 lb	1:	--	--	--	NO		--						
		CM:	81	163	137	103 kg	2:	--	--	--	NO		--						
T0106	7195	Bench, Work, With 4 Drawers, 1 Cabinet, 2 Shelves	C C C C --																
Workbench with 4 drawers. Characteristics/components include heavy gauge steel construction, four drawers, each, 14 3/4" W X 19 1/2" D X 5 5/8" H, on nylon rollers; each drawer includes a padlock hasp, provision for cylinder lock and pull, and a single full size door with padlock hasp.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	34	42	24	183 lb	1:	--	--	--	NO		--						
		CM:	86	107	61	83 kg	2:	--	--	--	NO		--						
T0110	7195	Bench, Work, Wood Top, With 30"Frame, 34x96x30	C C C C --																
Workbench with wood top. Characteristics/components include construction of seasoned lumber that is kiln-dried to a moisture content of 6 to 8 percent; strips of lumber 1-5/8 inch wide are electronically laminated with a special light bonding glue to create a smooth crack and warp resistant surface; and legs constructed of welded heavy gauge steel. It is used in occupational therapy.																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	34	96	36	259 lb	1:	--	--	--	NO		--						
		CM:	87	244	91	118 kg	2:	--	--	--	NO		--						
T0120	7195	Bench, Work, Wood Top, 1 Drawer, 1 Shelf, 34x72x30	C C C C --																
Workbench with wood top approximately 72" W x 30" D x 34" H. Characteristics/components include laminated wood top, 1- 5/8 inches thick; legs constructed of welded heavy gauge steel with floor feet for maximum stability; and one drawer and shelf. Workbench is used in occupational therapy. [Models priced with drawer and shelf.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	34	72	30	255 lb	1:	--	--	--	NO		--						
		CM:	87	183	76	116 kg	2:	--	--	--	NO		--						
T0125	7195	Bench, Work, Wood Top, Drawer, 31x96x36	C C C C --																
Wood top workbench. Characteristics/components include laminated wood top, 1- 5/8 inches thick; one drawer; legs constructed of welded heavy gauge steel with top span overhanging leg span 1-1/2 inches on each side. This unit is used in occupational therapy. [No other sources identified with this description/specification. Other manufacturers were located but they could not match the combination of 96 inches wide with a depth of 36 inches.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	31	96	36	269 lb	1:	--	--	--	NO		--						
		CM:	79	244	91	123 kg	2:	--	--	--	NO		--						
T0135	7195	Bench, Work, Metal Top	C C C C --																
The bench shall be a stationary workbench with a metal top approximately 60" X 30"																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	34	60	30	105 lb	1:	--	--	--	NO		--						
		CM:	86	152	76	48 kg	2:	--	--	--	NO		--						
T0175	7125	Cabinet, Storage, Tool	C C C C --																
Tool storage cabinet. This unit is mobile and has four separate areas to accept the different types of tools. Cabinet is used to provide the basic tools needed for "hands on" experience in wood, electricity, metal and power technology. [Various manufacturers who were contacted do not carry this particular cabinet in their inventory. No other manufacturers were found.]																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	66	47	22	290 lb	1:	--	--	--	NO		--						
		CM:	168	119	56	132 kg	2:	--	--	--	NO		--						

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R A F A H						1	2	3	4	5	6
T0180	7100	Cabinet, Storage, Tool, F/Mounted		A	A	A	A	--	--	--	--	--	--	--	--
The cabinet shall be designed to store and secure tools. It shall be non mobile.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA		IN:	84	61	30	551 lb	1:	--	--	--	0	NO	--		
		CM:	213	155	76	251 kg	2:	--	--	--	NO	NO	--		
T0280	3413	Drill Press, Bnch/Mntd		C	C	C	C	--	--	A	--	--	--	--	--
Shall be a bench mounted drill press with a 10 inch minimum capacity and variable speed. The motor shall have a minimum capacity of 1/3 HP.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA		IN:	34	11	21	80 lb	1:	115	1	6	60	NO	--		
		CM:	86	28	53	37 kg	2:	--	--	--	YES	YES	--		
T0285	3413	Drill Press, Floor Mounted, Tilt Table		C	C	C	C	--	--	D	--	--	--	--	--
Floor mounted drill press. Characteristics/components include 1/2 inch drill capacity; tilt table that tilts 45 degrees; 3/4 HP motor; three-spoke pilot wheel; depth stop and gauge. The unit is used for general purposes in occupational therapy.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA		IN:	67	18	28	219 lb	1:	120	1	16	60	NO	--		
		CM:	170	46	71	100 kg	2:	--	--	--	NO	NO	--		
T0400	3413	Grinder, Floor Mounted, Pedestal		C	C	C	C	--	--	D	--	--	--	--	--
Floor mounted grinder. Characteristics/components include pedestal type with a 1 HP motor; cast iron wheel guard and dust vents; large eye shields with quick adjustment levels; pre-lubricated with enclosed ball bearings; and two grinding wheels. This unit is used for general purposes in maintenance shops. Models are also available in 230 VAC, 3 phase.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA		IN:	58	24	13	176 lb	1:	120	1	13	60	NO	--		
		CM:	147	61	33	80 kg	2:	230	3	3	YES	YES	--		
T0405	3413	Grinder, Bench Mounted		C	C	C	C	--	--	A	--	--	--	--	--
Bench mounted grinder. Characteristics/components include cast iron wheel guard and dust vents; large eye shields with quick adjustment levels; pre-lubricated with enclosed ball bearings; and two grinding wheels. The unit is used for general purposes in machinist work shops. [All models have 3/4 HP motors with 8 inch diameter grinding wheels.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA		IN:	11	18	9	42 lb	1:	120	1	8	60	NO	--		
		CM:	28	46	23	19 kg	2:	--	--	--	NO	NO	--		
T0410	3415	Grinder, Keymaking, Automatic		C	C	C	C	--	--	A	--	--	--	--	--
Automatic key duplicating grinder. This unit cuts all cylinder keys from large head to small padlock and double-sided automotive keys. Characteristics/components include 1/4 HP motor; meets CSA and OSHA requirements; reversible vise that holds both single and double-sided keys; and soft touch brushes that protect fingers, will not wear keys and keeps accurate depths. The unit is used in facility maintenance shops for key duplication.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA		IN:	9	11	14	40 lb	1:	120	1	10	60	NO	--		
		CM:	23	28	36	19 kg	2:	--	--	--	NO	NO	--		
T0440	3413	Jointer, Woodworking, 6", 39x48x21		C	C	C	C	--	--	A	--	--	--	--	--
Woodworking jointer. Characteristics/components include 6 inch cutting capacity; 3/4 HP motor; set of 3 high speed steel knives; 2-way tilting fences with "dual control"; front and rear safety knife guard; push blocks; and a stand of enclosed steel. The system is used for general purposes in woodworking shops.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:				
EA		IN:	60	66	25	478 lb	1:	120	1	10	60	NO	--		
		CM:	152	168	64	217 kg	2:	--	--	--	NO	NO	--		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
T0460	3630	Kiln, Ceramic, Front Loading	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Front loading ceramic kiln. Characteristics/components include double insulation wall; chamber depth that permits placing pieces well away from the unit's door for even heating; and control wires with long life elements that are protected by durable refractory holders and are easy to replace. The unit is used for ceramic projects in occupational therapy and craft shops.																		
UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA			IN:	38	36	32	475 lb	1:	120	1	15	60	NO	--				
			CM:	97	91	81	216 kg	2:	240	1	45	NO	--					
T0465	3630	Kiln, Ceramic, Top Loading	C	C	C	C	--	--	G	--	--	--	--	--	--	--	--	--
Top loading ceramic kiln. Characteristics/components include all steel exterior construction with high gloss, heat resistant finish; firing chamber that is high temperature refractory type backed by special insulation to prevent heat loss and keep exterior heat radiation to a maximum; and 7 cubic foot capacity. The unit is used for firing clay in general ceramic shops. Requires external timer.																		
UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA			IN:	40	40	50	380 lb	1:	208	3	30	60	NO	--				
			CM:	102	102	127	173 kg	2:	--	--	--	NO	--					
T0600	7195	Workbench, 2 Drawer	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Work station workbench approximately 36"D x 72"W x 30"H. Characteristics/components include two drawers (14" W X 20" D X 5" H); master key lock; back stops; and an 18" drawer/ small parts cabinet. This unit is used in wood and metal workshops. [Only two sources were located that meet this description. Other manufacturer/vendor products could not match the combination of 72 inches wide and 36 inches deep and drawers. The Edsal Manufacturing Company (Model 2) provides the most flexibility in meeting specific workbench requirements. They provide a full range of tops, legs and other accessories to allow the design of a bench to meet any size or need.]																		
UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA			IN:	30	72	36	200 lb	1:	--	--	--	--	NO	--				
			CM:	76	183	91	91 kg	2:	--	--	--	NO	--					
T0700	7125	Rack, Bar, Wood, Pipe	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Bar, lumber and pipe rack. Characteristics/components include one plywood rack; four back panels; two divider shelves; and galvanized steel construction on these convenient racks. This rack can be used in wood or metal shops to store lumber, pipe, rod, conduit and plywood for a work project.																		
UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA			IN:	108	48	54	386 lb	1:	--	--	--	--	NO	--				
			CM:	275	122	137	176 kg	2:	--	--	--	NO	--					
T0740	5130	Sander, Disk, 12" Wheel	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Disk sander. Characteristics/components include 12 inch wheel; tilt table; stand; unit disc that is mounted to the end of motor shaft for powerful and accurate operation; scale that shows exact degree of derived table tilt; and a low 24 volt control unit at the push button station magnetic control. This unit can be used for sanding in wood shops.																		
UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA			IN:	47	19	22	206 lb	1:	120	1	7	60	NO	--				
			CM:	119	48	56	94 kg	2:	--	--	--	NO	--					
T0741	7195	Bench, Woodworking, 2 Cabinets, 31x36x21	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Woodworking bench. Two base steel constructed units placed back to back with each having full size doors; doors are fitted with master-keyed locking handles, and have an adjustable interior shelf. Characteristics/components include four vises attached to table top at corners; maple tabletop that is 2- 1/4 inches thick with natural finish laminated edge. The unit is used for work projects and storage in metal and woodwork shops. [This is a one of a kind, special made item, only one distributor was located.]																		
UNIT OF ISSUE:			HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:				
EA			IN:	31	64	54	120 lb	1:	--	--	--	--	NO	--				
			CM:	79	163	137	55 kg	2:	--	--	--	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I R A F A H						UTILITIES 1 2 3 4 5 6						
T0760	3220	Saw, Band, Woodworking	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Woodworking band saw. Characteristics/components include stand; basic 14 inch wood cutting saw; wheel; blade guards; chip chute; 6 inch arbor pulley; and a 3/4 HP motor. This saw is used for cutting wood in woodworking shops. [Model 1 has a 1 HP motor.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	68	31	89	201 lb	1:	120	1	10	60					
		CM:	173	79	226	92 kg	2:	--	--	--	NO					
		DEPENDENT: NO														
T0761	7195	Bench, Woodworking, Locker Base, 33 x 120 x 30	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Woodworking workbench. This is a locker based unit with a laminated maple top. The lockers include padlock hasp, spring hinges and provision for cylinder locks. The top is sturdy laminated maple. This unit is used in woodworking shops. It consists of base cabinets and one maple top. Final configuration to be determined by end user. [No other source(s) identified with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	33	120	30	212 lb	1:	--	--	--	--					
		CM:	84	305	76	97 kg	2:	--	--	--	NO					
		DEPENDENT: NO														
T0780	3220	Saw, Circular, Woodworking	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Circular woodworking saw. Characteristics/components include large cast iron table (22" X 37" with extension) that provides solid work support and prevents warping and distortion; capability to cut stock 2- 9/16" thick at 90 degrees and 1-13/16" at 45 degrees; rips to center of 48" panel; 1 HP motor; and 10" diameter blade. The unit is used for cutting wood in woodworking shops.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	41	57	42	282 lb	1:	120	1	10	60					
		CM:	104	145	107	128 kg	2:	--	--	--	NO					
		DEPENDENT: NO														
T0801	7195-00-057-1976	Workbench, Electric, Locker Base	C C C C --	--	B	--	--	--	--	--	--	--	--	--	--	
Electrical workbench approximately 34" H x 72" W x 36" D. Characteristics/components include removable maple top; with two locker units; and four box lockers (each 12" W X 21" D X 15" H) in each locker unit. This workbench is used in wood and metal workshops. Workbench is a mix and match construction and can be configured to end users needs.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	36	72	36	377 lb	1:	120	1	15	60					
		CM:	91	183	91	172 kg	2:	--	--	--	NO					
		DEPENDENT: NO														
T0802	7290	Jigsaw, Electric	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Electric jig saw. Characteristics/components include variable speed orbital action; Allen wrenches for shoe and blade adjustments; and two (2) metal cutting blades. This saw is used to cut metal or wood.																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	9	11	4	11 lb	1:	120	1	6	60					
		CM:	23	28	11	5 kg	2:	--	--	--	NO					
		DEPENDENT: NO														
T0810	7290	Stand, Jack, Shoe Repair	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--	
Shoe repair jack stand. Characteristics/components include five men's and women's lasts; top locks in place or spins free; top is controlled with the turn of a knob and the top section is long enough to keep boots clear of the knob. This stand is used to form and repair shoes in brace and limb shops. [Only one manufacturer found for this item. No other source(s) were found with this description/specification.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	48	10	10	88 lb	1:	--	--	--	--					
		CM:	122	25	25	40 kg	2:	--	--	--	NO					
		DEPENDENT: NO														
T0850	7290	Cutter, Sole, Bench Mounted	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--	
Bench mounted, hand operated cutter. This is a five-in-one functional machine that skives, cuts, trims, bevels edges and presses edges of bonded surfaces. Can be used on plastic, rubber and leather materials. Unit has a 9" throat clearance. Used in shoe repair and orthotic/prosthetic shops. [No other source(s) identified with this description/specification]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:						
EA		IN:	--	20	8	50 lb	1:	--	--	--	--					
		CM:	--	51	21	23 kg	2:	--	--	--	NO					
		DEPENDENT: NO														

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
T0860	7290	Machine, Sewing, Industrial, Heavy Duty	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Industrial sewing machine. Characteristics/components include heavy duty; capability to produce fine stitches on elegant ladies' shoes just as easily as it does hard-wearing stitches on heavy working boots; capability to sew in all directions; 18-1/2 inch clearance under arm; hand wheel which may be front or side mounted; and a heavy duty power stand which comes with adjustable speeds, precision motor control and 1/3 HP. This machine is used to repair and make shoes. [Model 3, Landis McKay 12K is a reconditioned machine as no new ones are built today in the US. The Landis is a household name in the shoe manufacturing industry. The reconditioned machines are considered as good as new with parts readily available.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 65	34	35	617 lb	1: 120	1	7	60	NO	--						
			CM: 165	86	89	281 kg	2: --	--	--	DEPENDENT:	NO	--						
T0870	7290	Machine, Sewing, Industrial, Medium Duty	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Industrial sewing machine. Characteristics/components include medium duty, high-speed; light harness stitcher on stand unit; 1/2 HP motor; stitch speed of 1800 stitches per minute (S.P.M.); maximum thread size of 3 cord; and adjustable stand heights. This machine is used for leather garment work, light or medium stitching at high speeds on upholstery or slip covers, etc.																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 65	24	21	330 lb	1: 120	1	7	60	NO	--						
			CM: 165	61	53	150 kg	2: --	--	--	DEPENDENT:	NO	--						
T0875	3611	Machine, Sign Making	A	A	A	A	--	--	A	--	--	--	--	--	--	--	--	--
		Sign making and engraving machine. The machine has a powering motor, moveable spindle housing, cutting bit and trays to hold the uncut stock and letter blanks. The machine has adjustable arms for making different size lettering from the same letter blank. Automated models are available. [Model 1 includes a Windows based software package for use with any computer.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 16	26	20	54 lb	1: 120	1	5	60	NO	--						
			CM: 41	66	51	25 kg	2: --	--	--	DEPENDENT:	YES	--						
T0960	3630	Wheel, Kick, Potter's, 34x30x33	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Potters' kick wheel. Characteristics/components include mechanical unit; easy foot operation that allows the potter to regulate speeds for throwing as well as quick starting and stopping; back and forth treadle motion that propels the approximately 135 pound, balanced flywheel which provides the momentum for easy throwing; precision steel shaft, mounted in ball bearing, that connects the flywheel to the wheel head; and a non-corrosive aluminum worktable shaped for a comfortable hip rest. This wheel is used in arts and craft shops and physical therapy rooms of hospitals. Unit can be ordered with the motor drive option. [Price difference verified.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 30	43	46	350 lb	1: 120	1	7	60	NO	--						
			CM: 76	109	117	159 kg	2: --	--	--	DEPENDENT:	NO	--						
T0965	7195	Workbench, Adjustable Height, Hydraulic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Hydraulic workbench. Characteristics/components include table tops that are laminated high pressure plastic or hard wood, adjustable height benches. Adjustable heights should range between 30 and 36 inches through the use of a retractable extending handle.																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 42	66	48	250 lb	1: --	--	--	--	NO	--						
			CM: 107	168	122	114 kg	2: --	--	--	DEPENDENT:	NO	--						
T0970	6530	Table, Work, Adult, Stand-In	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Adult stand-in work table. Characteristics/components include upholstered back support; adjustable knee support; cutout; and allows adults to stand. This table is used to rehabilitate the severely handicapped in hospitals and other healthcare institutions. Adjustable height from 41" to 58". Height adjustment can be manual or electric driven. [Price difference verified.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 58	41	31	285 lb	1: 115	1	4	60	NO	--						
			CM: 147	104	79	130 kg	2: --	--	--	DEPENDENT:	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
T1000	5140	Cabinet, Tool, Mobile, With Mechanics Tool Chest	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Tool cabinet and chest. Characteristics/components include: a mobile tool cabinet with 5 inch casters; shall have a minimum of 7 tamper-proof drawers; and have an internal drawer locking system that prevents unintentional drawer openings. The mechanics tool chest shall be capable of sitting on top of the mobile tool cabinet. It shall have a minimum of 10 tamper-proof drawers and have an internal drawer locking system that prevents unintentional drawer opening. All drawers shall lock automatically when the lid is closed. Shall have a partitioned top till that holds the lift-out trays equipped with socket dividers. [.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 59	36	21	295 lb	1: --	--	--	--	NO	--						
			CM: 150	91	53	134 kg	2: --	--	--	NO	--	--						
T1020	5140	Cabinet, Tool, Floor Standing, 84x60x22	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Floor standing tool cabinet. Characteristics/components include assortment of tool hangers, plastic nail and tote trays. Constructed of heavy maple framing and hardwood panels. Upper storage compartments are lined with 1/4 inch perforated pegboard. [No other source(s) identified with this description/specification. Other sources contacted that offer similar type products could not cross reference it to their inventory. They considered this product a specialty or custom made item.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 84	60	22	225 lb	1: --	--	--	--	NO	--						
			CM: 213	152	56	103 kg	2: --	--	--	NO	--	--						
T1150	7125	Cabinet, Storage, Electric Parts	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Electric parts storage cabinet. Characteristics/components include sturdy construction steel hardware; provides storage space for various items; adjustable dividers in drawers; double doors; and master-keyed lock. This cabinet can be used to store electric parts in an electrical shop.																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 85	36	18	387 lb	1: --	--	--	--	NO	--						
			CM: 216	91	46	176 kg	2: --	--	--	NO	--	--						
T1500	3520	Machine, Finishing, Shoe	C	C	C	C	--	--	--	--	C	--	--	--	--	--	--	--
		Shoe finishing machine. Characteristics/components include belts and wheels for leather finishing; two sanding belts, each 59-1/2 inches long, to cut faster, run cooler and last longer, with one belt 1-9/16 inches wide and the other at 4 inches wide; dust control system with front-access dust collection drawer; quick-adjust sole trimmer; and a 2 HP blower motor. This machine is used to manufacture and repair shoes. [No other source(s) identified with this description/specification.]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 67	30	32	750 lb	1: 220	1	13	60	NO	--						
			CM: 170	76	81	341 kg	2: --	--	--	NO	--	--						
T1510	6530	System, Vacuum Forming	C	C	C	C	--	--	--	--	A	--	--	--	--	--	--	--
		Vacuum forming system used in the production of orthotic devices. System includes 1/4 HP vacuum pump which produces 26 inches of mercury vacuum, 8 gallon holding tank, table base, and a variety of forming trays. Trays are interchangeable on the base and may be changed without the use of hand tools. Foot treadle control sets and maintains a constant vacuum. [No other source(s) could be found with this description/specification..]																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 46	33	39	322 lb	1: 120	1	10	60	NO	--						
			CM: 117	84	99	147 kg	2: --	--	--	YES	--	--						
T2050	7290	Collector, Dust, Freestanding	C	C	C	C	--	--	--	--	A	--	--	--	--	--	--	--
		Free standing dust collector for use in small shops throughout the facility. Unit includes electric power head, absolute filter system, primary paper filters, drum adapter, 55 gallon roll-top drum, hoses, and blast gates. Will support two or three collection points with three inch lines.																
		UNIT OF ISSUE:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	IN: 88	27	37	100 lb	1: 120	1	13	60	NO	--						
			CM: 224	69	94	46 kg	2: --	--	--	YES	--	--						

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I R A F A H						UTILITIES 1 2 3 4 5 6					
T3640	3413	Grinder, Pedestal/Mounted, Combination Belt/Disc	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Pedestal type grinder. Combination 6-inch abrasive belt and 12-inch abrasive disk sander with tilting table/fens assembly, disc table, belt and disc guard and dust collection shroud. This grinder is used for grinding materials in metal workshops. [Price difference verified.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA		IN:	56	32	26	160 lb	1:	120	1	13	HZ SWITCH: NO				
		CM:	142	81	66	73 kg	2:	--	--	--	DEPENDENT: NO				
T4000	3920	Hoist, Chain, 1/2 Ton Capacity, 7 Foot Lift	A A A A --	--	--	--	--	--	--	--	--	--	--	--	--
Chain hoist. Characteristics/components include minimum 1/2 ton capacity; trolley that can be used with any hook suspended hoist; and a hoist that features a hardened load chain for optimum strength, flexibility and long wear.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: --		BTUs / HR:				
EA		IN:	6	6	6	62 lb	1:	--	--	--	HZ SWITCH: NO				
		CM:	15	15	15	29 kg	2:	--	--	--	DEPENDENT: NO				
T6000	3416	Lathe, Metal, Bench/Mounted, Multi-Speed, 4 Feed	C C C C --	--	B	--	--	--	--	--	--	--	--	--	--
Metal-turning lathe. Characteristics/components include bench mounted; 12 inch swing, distance between centers 40 inches, speed range 60-1550 RPM, minimum number of speeds 8, cuts English and Metric threads, 4-way turret tool post, heavy-duty construction and 2 HP motor.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA		IN:	50	30	70	2,000 lb	1:	230	3	7	HZ SWITCH: NO				
		CM:	127	76	178	908 kg	2:	--	--	--	DEPENDENT: NO				
T7550	3405	Saw, Radial Arm	C C C C --	--	C	--	--	--	--	--	--	--	--	--	--
Radial arm saw. Characteristics/components include floor model unit; 12 inch diameter blade with an arm which permits saw blade to rotate a full 360 degrees above worktable; 1-1/2 HP motor with an automatic Electro-mechanical brake that is built into the motor and stops the blade automatically in seconds after switch is turned off; 45 degree to 90 degree level position stop; and a table size of 25-1/2 X 30" (635 X 762 mm). This unit is used for wood cutting in woodworking shops.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA		IN:	63	30	32	300 lb	1:	220	1	17	HZ SWITCH: NO				
		CM:	163	76	82	137 kg	2:	--	--	--	DEPENDENT: NO				
T7560	3220	Saw, 10 Inch, Tilting Arbor	C C C C --	--	G	--	--	--	--	--	--	--	--	--	--
Tilting arbor saw. Characteristics/components include 10 inch unit; jet-lock rip fence; combination blade; miter gauge; extension wings; motor cover; a large cast iron table at 27" X 36" with wings and an accurately ground face for precision work. This saw is used for woodwork in majority of the nations schools and in millwork furniture, cabinet and home workshops.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA		IN:	37	63	43	1,584 lb	1:	220	3	21	HZ SWITCH: NO				
		CM:	94	160	109	720 kg	2:	--	--	--	DEPENDENT: YES				
T7580	3455	Saw, Hack, Endless Blade	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Horizontal band saw. Characteristics/components include portable; true horizontal cutting performance with a 4" X 6" rectangular capacity; 1/3 HP motor with a on/off toggle switch and automatic shut-off; and capability for conversion to vertical band saw in only a few minutes. Saw is used for wood or metal work in maintenance, machine and home workshops.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA		IN:	38	41	18	150 lb	1:	120	1	7	HZ SWITCH: NO				
		CM:	97	104	46	69 kg	2:	--	--	--	DEPENDENT: NO				
T7620	3220	Saw, Scroll, With Stand	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Scroll saw with stand. Characteristics/components include capability to cut stock up to 1-3/4" thick; 24" arm to blade capacity for ripping table that measures 14" X 14" and provides ample support for large, bulky panels and other hard to handle materials; table tilt of 45 degrees right and 15 degrees left for standard bi-level cutting; and a complete set of blades which include one (1) saber blade, three (3) scroll saw blades, belt and pulley guard. This saw is used for cutting projects in woodwork shops.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:				
EA		IN:	55	20	41	75 lb	1:	120	1	7	HZ SWITCH: NO				
		CM:	140	51	104	34 kg	2:	--	--	--	DEPENDENT: NO				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
T8000	3530	Machine, Sewing/Stitching	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Industrial type sewing machine. Single needle, extra heavy duty backstitch with reverse feed. Has an extra long cylinder arm and built in bobbin winder. Also has an extra high presser lift for sewing very heavy materials. This machine is used for sewing leather, canvas, nylon and other heavy materials.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	48	122	17	210 lb 96 kg	1: 120	1	10	60	NO	NO	--					
T8005	6625	Signal - Differential Amp. Analyzer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Signal analyzer. This unit is capable of analyzing the electrical signals for distortion, networking, noise levels, and burst signals. The system can be used to determine Electro magnetic interface and many other applications. The unit is programmable to measure and analyze all aspects of signal transmission. Used in research and maintenance in a healthcare facility. [No other source(s) identified with this description/specification.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	9	23	25	81 lb 37 kg	1: 120	1	3	60	NO	NO	--					
T8015	6625	Calibrator, Audiometer	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Audiometer calibrator system. Characteristics/components include dual-frequency, dual-amplitude capacity for calibrating precision Type 1 as well as general purpose Type 2 sound level meters; generates four selectable reference outputs at 250 and 1000 Hz, each at 94 and 110 dB; and uses a single 9 volt transistor battery. This system is used for hearing tests in hospitals and clinics. [Price difference verified. Model 2 is a sophisticated, multifunction, wide frequency range calibrator. Models 1 and 3 are simple calibrators.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	4	10	11	4 lb 2 kg	1: --	--	--	0	NO	NO	--					
T8020	6625	Generator, Pulse	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Pulse generator. Characteristics/components include four output modes; and complement dual outputs that greatly increase unit applicability in logic design areas, especially interfacing within a system or to peripherals. The unique output flexibility within the normal and complement modes is particularly useful in logic design or control applications requiring simultaneous signals. [Price difference verified.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	7	18	20	22 lb 10 kg	1: 120	1	6	60	NO	NO	--					
T8025	6625	Generator, Function	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
		Function generator. Characteristics/components include generated sine, triangle and square waveforms; covers 0.2 Hz to 2.0 MHz in 7 ranges; voltage controlled amplitude output; 20 dB step attenuator; four digit frequency counter display and ability to generate low-distortion sine waves which make the unit uniquely appropriate for applications requiring audio signals. [Price difference verified.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	4	10	17	13 lb 6 kg	1: 120	1	8	60	NO	NO	--					
T8030	6625-01-042-8213	Electrosurgery Analyzer	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Electrosurgery analyzer. This is a power analyzing system that verifies electrosurgical specifications such as output power, radio frequency leakage and output waveforms. This is necessary because electrosurgical units should provide safe controlled power output at RF with a predetermined physiological load so that burns and electrical shocks are avoided.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
		EA	6	15	16	15 lb 7 kg	1: 115	1	2	60	NO	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
T8035	6625	Radiometer, Laser	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Laser radiometer. Characteristics/components include measures and displays power output from 0.1 W to 100 W in continuous wave (CW) operation and energy output from 100 milli-Joule (mJ) to 100 J in pulsed operation; portable; and has a self-calibration feature that guarantees accurate and dependable measurements. [Dimensions for each model are for display units (Nova, 3Sigma and FieldMaster-GS). Price for each model includes displays and 4 heads, probes or sensors to operate with the various display units. Model 1 Heads (F150, 3A-P, 10A & PE 50BB), Model 2 Probes (PM150, PM10V1, PM10 & J50) and Model 3 Sensors (LM-150 FS HTD, LM-30V, LM-10 HTD & LM-P10i). All displays are battery operated and come with AC adapters.]																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:	--					
			CM:	7	10	10	9 lb	1:	--	--	--	HZ SWITCH:	NO	BTUs / HR:	--				
				19	25	25	4 kg	2:	--	--	--	DEPENDENT:	NO	--					
T8040	6625	Meter, Sound Level	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Sound level meter. This is a 27-140 dB sound analyzing device. It is used to analyze precision measurement and analysis of sound levels in laboratory, industrial, community, hospitals and audiology clinics. Unit is battery powered. [On the next revision of the MIL-STD-1691 consideration should be given to combine JSN: T8015, CALIBRATOR, AUDIOMETER with JSN: T8040, METER, SOUND LEVEL. There are Audiometer Analyzer Kits available which contain both of the above, plus accessories such as cables, adapters, filters, etc. No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:	--					
			CM:	8	4	2	2 lb	1:	--	--	--	HZ SWITCH:	NO	BTUs / HR:	--				
				20	10	5	1 kg	2:	--	--	--	DEPENDENT:	NO	--					
T8045	6625	Oscilloscope, With Accessories	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Oscilloscope. Characteristics/components include 100 MHz unit; digitizing scope with a fully-functional analog scope that can control data acquisition and a switch-selectable Pre/Post/Mid-triggering with reference to a triggering event. This unit is used to evaluate electronic equipment faults.																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	BTUs / HR:	--					
			CM:	11	17	13	25 lb	1:	120	1	2	HZ SWITCH:	NO	BTUs / HR:	--				
				28	43	33	12 kg	2:	--	--	--	DEPENDENT:	NO	--					
T8050	6625	Component Analyzer, Solid State	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Solid state component analyzer. This unit is a dual wide, plug in instrument which occupies a vertical amplifier compartment and an adjacent time base compartment. This is a general purpose H/W analysis with 8-16 bit microprocessor support. The system is used to analyze solid state electronic components. [This is a component of a Tektronix analyzer JSN-T8045. No other source(s) identified with this description/specification.]																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	BTUs / HR:	--					
			CM:	9	17	17	26 lb	1:	120	1	6	HZ SWITCH:	NO	BTUs / HR:	--				
				23	43	43	12 kg	2:	--	--	--	DEPENDENT:	NO	--					
T8055	6625	Wattmeter, Ultrasonic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
Ultrasonic wattmeter. Characteristics/components include electronic and mechanical design to provide superior performance and greater durability; clear Plexiglas tubing on the front panel that allows the operator to immediately determine the liquid level within the sealed reservoir; and power measurements that can be conveniently read on the LCD display. This unit is a one-of-a-kind instrument used by biomedical repair persons who regularly test therapeutic ultrasound devices. Unit is battery powered.																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	BTUs / HR:	--					
			CM:	9	12	9	11 lb	1:	120	1	1	HZ SWITCH:	NO	BTUs / HR:	--				
				23	30	23	5 kg	2:	--	--	--	DEPENDENT:	YES	--					
T9100	3439	Torch, Welding/Cutting, W/AC	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
Shall be a welding and Cutting Outfit with a torch handle, tip mixer, check valves, cutting attachments, various cutting and welding tips, a minimum 20 foot twin hoses, and oxygen/acetylene regulator with 2-1/2 inch gauges, goggles and spar lighter.																			
UNIT OF ISSUE:		EA	IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	BTUs / HR:	--					
			CM:	--	--	--	20 lb	1:	--	--	--	HZ SWITCH:	NO	BTUs / HR:	--				
				--	--	--	9 kg	2:	--	--	--	DEPENDENT:	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
T9200	5140	Tools, Woodworking, With Cabinet	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Tool set. Characteristics/components include complete woodworking hand tool storage system and a basic starter unit; hardwood or metal construction; inside back panel and doors lined with 1/8" pegboard with ample tool storage; cabinets complete with a lower adjustable shelf, tote trays and master-keyed locking door. Set is used to store tools in woodworking shops. [No other source(s) identified with this description/specification. This is a one of a kind item and only one distributor was located. Other similar cabinets were found but not as a package that included the tools.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	84	213	22	320 lb 146 kg	1:	--	--	--	NO	--						
							2:	--	--	--	NO	--						
T9300	3439	Welder, Arc	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	--
		Arc welder. Characteristics/components include 12 position selector switch; wall plug; and input cable. This welder is used to weld carbon, low alloy, stainless steel; aluminum and copper. It brazes and solders and fabricates 16 gauge sheet steel and thick plates.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	25	64	14	81 lb 37 kg	1:	230	1	50	60 NO	--						
							2:	--	--	--	YES	--						
T9400	5120	Vise, Machinists', Swivel Base	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Machinists' vise. Characteristics/components include adjustable; back jaw stationary; pin in place; and capability to remove the pin which allows adjustment for tapered work with maximum gripping. Vise is used for a wide range of work in tool and die rooms. Available in 4 or 6 inch jaw width. [No other source(s) identified with this description/specification. The requirement for an adjustable back jaw with pin lock limits the availability of this item. General purpose machinists vises are readily available from multiple sources: Wilton, Record, Columbian]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	--	--	--	59 lb 27 kg	1:	--	--	--	NO	--						
							2:	--	--	--	NO	--						
T9420	5120	Vise, Bench/Pipe, Swivel Base, 5 Inch Jaw	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Bench and pipe vise. Characteristics/components include 6 inch opening jaw; 5 inch width jaw; holds 1/8 to 1-1/2 inch pipe. Swivel base allows full 360 degrees rotation, geared lock bolt insures positive locking against slippage.																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	13	33	15	115 lb 53 kg	1:	--	--	--	NO	--						
							2:	--	--	--	NO	--						
T9430	5120	Sweeper, Street	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Street sweeper. Unit has a liquid cooled gas, diesel or propane engine which develops 25 HP or better (15 HP for diesel) at normal working load. The unit features an electric starter, steel chassis frame, street brush, dirt holding tank, operator compartment, brakes, wrap around bumper and a dust filter/suppressor. The dust holding tank dumps hydraulically. Mechanical access panels either raise or remove easily for maintaining the engine, electrical system and hydraulics. The sweeper is designed for medium duty indoor and outdoor applications. Light duty and heavy industrial/public works duty machines are available. The database pricing reflects the manufacturers' standard configuration for the model listed with an overhead guard option. [Model 2 and 3 height includes the overhead guard. Without the guard the height is approximately 58". The height of the cab for Model 1 is 78". Price difference verified.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	82	208	123	3,390 lb 1,539 kg	1:	--	--	--	0 NO	--						
							2:	--	--	--	NO	--						
V0005	6530	Cage, Animal, Large	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
		Large animal cage. Characteristics/components include durable and reinforced fiberglass; a shell that resists stains, scratches and wear; mildew resistant; and a drain with strainer. Cage used to house large animals. Unit price is based on requester requirements. [This is a place holder for a large animal cage with unit price determined at time of construction and installation. All manufacturers offer this item. Cut sheets are provided.]																
		UNIT OF ISSUE:	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
		EA	--	--	--	-- lb -- kg	1:	--	--	--	NO	--						
							2:	--	--	--	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
V0006	6530	Kennel, Large Animal, Intensive Care, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Kennel, large animal, intensive care, mobile with CCU door. Used to transport or isolate patients in critical care situations. Stainless steel, approximately 40" W x 30" D x 37" H. CCU Door controls oxygen and temperature, provides filtered ventilation and allows humidity control, IV administration and can be fitted with a nebulizer. [Models 1 and 2 are simple cages with oxygen therapy doors and are provided for information. Model 3 is a top-of-the-line Intensive Care Unit providing a full range of supporting attributes. It is the only one that truly meets the description and is the only model requiring electrical power. Note: Adding an additional JSN to cover kennels similar to those in Models 1 and 2 should be considered.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
			67	170	87	300 lb 137 kg	1:	120	1	10								
					37		2:	--	--	--								
V0007	6530	Cage, Transport, Aluminum, Large	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Cage, transfer, aluminum, for large animals. Approximate dimensions: 28 1/2 W x 87 L x 51 H. Constructed of series 6000 aluminum alloy and other non-corrosive materials. Guillotine doors on either end, individually removable bars, and squeeze back. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
			51	130	29	450 lb 205 kg	1:	--	--	--								
					87		2:	--	--	--								
V0008	6530	Rack, 4 Each, Single Cage, Primate	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Rack, single cage, primate, 2 tiers, holds 2 cages per tier. Approximate cage dimensions: 24" W x 28" D x 34" H. Stainless steel excreta tray and horizontal water supply line are included. Other accessories such as feeders and water bottles are ordered separately. [Price difference verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
			83	211	59	-- lb -- kg	1:	--	--	--								
					35		2:	--	--	--								
V0010	6530	Cage, Animal, Small	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Small animal cage. Characteristics/components include water bottle; disposable pan liner; feeding arrangements; constructed of type 18 to 24 gauge heavy steel; corrosion resistant; separate wire floors; and smooth finish for easy cleaning. Cage used to house small animals. [Prices quoted are for cases of 10 each. Price difference verified.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:	--			
			14	36	11	15 lb 7 kg	1:	--	--	--								
					19		2:	--	--	--								
V0011	6530	Cage, Squeeze, Primate	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Cage, squeeze, primate, aluminum. Dimensions: 29" W x 45 1/2" L x 50" H. Used for transfer or restraint of large primates. Fabricated of highly corrosion resistant aluminum alloy extrusions and sheet material. Manually operated screw-type squeeze mechanism; open design for visibility; removable clear acrylic sheet side panels; and removable stainless steel excreta pan. [No other source(s) identified with this description/specification]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--			
			50	127	29	-- lb -- kg	1:	--	--	--								
					46		2:	--	--	--								
V0012	6530	Housing, Group, Exercise Unit	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Stainless steel group housing/exercise unit for small and medium primates. Approximate dimensions: 45" W x 70" L x 82-1/2" H, Floor area: +/- 17 sq. ft. Fabricated of high chrome, high nickel, and highly corrosion resistant type 304 stainless steel. Accessories items such as bowls, T-Bar dollies, watering units, water bottles, drinking tubes, etc. are ordered separately. [Model 2 is 75" deep, the others are from 58' to 62" deep.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	--			
			94	239	51	-- lb -- kg	1:	--	--	--								
					75		2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
V0015	6530	Table, Examination/Treatment, Animal, CRS,33x20x72	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Animal examination/treatment table. Characteristics/components include type 304 (corrosion resistant) stainless steel; non-magnetic; fabricated with turned down edges and fully welded corners; and stabilized with H-brace supports. Table is used for examination and treatment of animals. [Prices verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:							
EA		IN:	34	24	72	115 lb	1:	--	--	--	NO							
		CM:	86	61	183	52 kg	2:	--	--	--	NO							
V0020	6530	Clipper, Hair, Animal	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Animal hair clipper. Characteristics/components include electric; detachable head; cylindrical housing; clips area 44 mm wide; vibrationless operation; freely interchangeable blades in the head; capable of using size 10 blades for primary clipping to remove a heavier coat or size 40 blades for preparing a surgical area without abrasion. Clippers are used for clipping laboratory animal hair.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:							
EA		IN:	4	2	8	2 lb	1:	120	1	1	NO							
		CM:	10	5	19	1 kg	2:	--	--	--	NO							
V0025	6530	Scale, Weighing, Animal, Large	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Large animal weighing scale. This is a microprocessor-controlled scale with remote weighing platform on 10 feet cable. Scale reads to 100 lbs/45 kg with accuracy of (+/-) 0.02 percent of capacity. For weighing animals, samples in fume hoods or other isolated environments. [Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:							
EA		IN:	3	22	46	22 lb	1:	120	1	1	NO							
		CM:	8	56	117	10 kg	2:	--	--	--	YES							
V0026	6530	Balance, Small Animal	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Balance, small animal. Used in laboratory research for weighing small rodents, etc. Accuracy +/- .1 gram, and maximum weigh capacity of not less than 12 kg.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:							
EA		IN:	22	15	23	38 lb	1:	120	1	1	NO							
		CM:	56	38	58	18 kg	2:	--	--	--	YES							
V0030	6530	Table, Operating, Veterinary, Hydraulic	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Veterinary operating table. Characteristics/components include stainless steel; corrosion resistant construction; elevation adjustment range from approximately 36" to 49" high; sanitary design to minimize places for debris; accommodates animals weighing up to 300 pounds; and has waterproof outlets. Table is used for surgical procedures on medium to large animals.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:							
EA		IN:	43	23	58	700 lb	1:	--	--	--	NO							
		CM:	109	58	147	318 kg	2:	--	--	--	NO							
V0040	6530	Chamber, Hyperbaric, Animal	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	F
Animal hyperbaric chamber. This unit is a horizontal laminar flow exposure chamber with a unique inlet and outlet baffle-plenum configuration. The unit is designed for an even distribution of airflow across the chamber providing uniform concentrations of particulates or vapors and near uniform air conditions. The chamber is useful as an aid for providing controlled levels of contaminants to animals or plants in such a way as to be reproducible, and to minimize unwanted variables.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:							
EA		IN:	81	32	52	640 lb	1:	120	1	25	NO							
		CM:	206	81	132	291 kg	2:	--	--	--	NO							
V0045	6530	Washer, Pressure, Veterinary, Hot Water	A	A	A	A	--	--	D	A	--	--	--	--	--	--	--	--
Veterinary hot water pressure washer. This is a compact pressure washer that is easily transported and prepared for operation. Characteristics/components include trigger control that enables the operator to shut off the water flow away from the machine; a detachable power unit with built-in carrying handles; soap/ rinse cycles controlled by the nozzle on the wand; and variable pressure for different cleaning jobs. This unit is used for cleaning veterinary equipment in hospitals. [Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		BTUs / HR:							
EA		IN:	38	23	29	140 lb	1:	120	1	20	YES							
		CM:	97	58	74	64 kg	2:	--	--	--	YES							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
V0055	6640	Washer/Sanitizer, Cage, Steam	A	A	A	A	--	D	F	D	A	--	E					
		Cage washer/sanitizer. Characteristics/components include tunnel type; enclosed steam cabinet; type 304 CRS; integral 39 gallon wash and rinse tank; 36 inch wide CRS conveyer belt with speed controller; 3 HP motor-driven pumps for wash and rinse section; automatic controls in CRS switch box; operates on 115 VAC; start-stop buttons in oil-tight switch boxes at each end; thermostatically controlled heaters to provide 160-190 degrees F. wash and rinse water and 180 degrees F. sanitizing water; two vent stacks with automatic dampers; marine light in tunnel; 1 inch NPT hot water (20-60 PSIG) 1 inch NPT steam (10-60 PSIG) 3/4 inch NPT return, 8-12 inch diameter vent and 3 inch NPT drain. Unit is used for washing and processing general purpose cages, cage pans and accessory cage equipment. [A third source could not be found with 3 HP motor-driven pumps.]																
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 92 137	DEPTH 252 640	WEIGHT 12,000 lb 5,448 kg	VOLTS 1: 2:	PHASE 230 --	AMPS 3 --	AMPS 70 --	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: 24,000				
V0060	6640	Washer/Sanitizer, Cage, Large	A	A	A	A	--	D	F	D	A	--	E					
		Large cage washer/sanitizer. Characteristics/components include enclosed steam cabinet; type 304 CRS; large capacity water tank; 36 inch wide CRS conveyor belt with speed controller; 7 HP pre-wash pump motor; 7 HP pump motor for wash and rinse section; automatic controls in NEMA-12 housing; start-stop buttons in oil-tight switch boxes at each end; thermostatically controlled heaters to provide 110-120 degree F. pre-wash water, 160-170 degree F. wash water and 170-180 degree F. rinsing-sanitizing water; vent stacks with automatic dampers; marine light in tunnel; 1/2 inch NPT cold water (20-50 PSIG), 1-1/4 inch NPT hot water (20-60 PSIG), 1-1/4 inch steam (10-60 PSIG), 3/4 in NPT return, 3 inch NPT drain and 8 inch diameter vent; and capacity of 3,000 cages in 6 hours. Unit is used for processing cages and accessories. [Model 1 has a 10 HP wash pump motor and a 5 HP rinse pump motor.]																
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 96 137	DEPTH 336 853	WEIGHT 12,000 lb 5,448 kg	VOLTS 1: 2:	PHASE 230 208	AMPS 3 3	AMPS 70 60	HZ: 60	HZ SWITCH: NO	DEPENDENT: YES	BTUs / HR: 24,000				
V0065	6530	Rack, Rodent, 5 or 6 Tier, Including 30 Cages	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	
		Rodent rack. Characteristics/components include five tier high racks with nylon support rails; type 304 corrosion resistant steel construction to withstand repeated long term washing and drying by mechanical washers; brake controls on one pair of casters; and suspension design to minimize movement of individual cages. Rack used for care of rodents in research facilities.																
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 78 198	DEPTH 69 175	WEIGHT -- lb -- kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	AMPS -- --	HZ: --	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --				
V0067	6530	Rack/Shelving, Rodent, 4 or 5 Tier, 20 Cages	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	
		Rack, rodent, stainless steel, 4 or 5 tiers with 20 cages per rack (not included). Mounted on 5 inch chrome plated casters with brakes. Accessories such as cages, watering units, feeders etc. are ordered separately.																
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 72 183	DEPTH 60 152	WEIGHT -- lb -- kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	AMPS -- --	HZ: --	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --				
V0069	6530	Rack/Shelving, Mouse, 5 Tier, 25 Cages	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	
		Rack, mouse, 5 tier, stainless steel, 5 cages per tier, 25 cages per rack (not included), mounted on 5" chrome plated casters. Accessory items such as cages, feeders, water systems, etc. are ordered separately.																
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 75 190	DEPTH 70 178	WEIGHT -- lb -- kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	AMPS -- --	HZ: 0	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --				
V0070	6530	Rack, Mouse, 4/5 Tier, Incl. 20/30 Cages Per Rack	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	
		Rack, mouse, 4 or 5 tier, 5 or 6 cages per tier, includes 20 to 30 cages per rack, mounted on 5" chrome plated casters. Accessory items such as feeders, water systems, etc. are ordered separately.																
		UNIT OF ISSUE: EA	HEIGHT IN: CM	WIDTH 75 191	DEPTH 49 124	WEIGHT 175 lb 80 kg	VOLTS 1: 2:	PHASE -- --	AMPS -- --	AMPS -- --	HZ: 0	HZ SWITCH: NO	DEPENDENT: NO	BTUs / HR: --				

JSN	NSN	NOMENCLATURE	CATEGORY:	UTILITIES									
				A	N	A	V	I	1	2	3	4	5
V0072	6530	Rack, Ferret, 3 Tier, 6 Cages Per Rack	C C C C --	--	--	--	--	--	--	--	--	--	--
Rack, ferret, 3 tier, 6 cages per rack. Stainless steel cages with #2 wire mesh in the top half of cage doors. Each rack to include 6 stainless steel refuse pans and 5 square feet of animal space. Racks are mounted on 5 inch heavy duty stainless steel casters, 2 locking.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:		
EA		IN:	70	70	36	250 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	178	178	91	114 kg	2:	--	--	--	DEPENDENT:	NO	--
V0074	6530	Rack, Rabbit, 6 Cages Per Rack	C C C C --	--	--	--	--	--	--	--	--	--	--
Rack, rabbit, 3 tier, 2 cages per tier, 6 cages per rack. Racks constructed entirely of type 304 stainless steel tubing with 16 gauge wall thickness. Mounted on 5 inch heavy duty stem-type copper/nickel/chrome plated casters. Rack dimensions: 59" W x 25- 1/4" D x 71-1/2" H. Accessory items such as cages, cage floors, feeding bowls, water systems, etc. must be ordered separately. [Price difference verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:		
EA		IN:	76	58	35	-- lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	193	147	89	-- kg	2:	--	--	--	DEPENDENT:	NO	--
V0076	6530	Rack, Rabbit, 3 Cages Per Rack	C C C C --	--	--	--	--	--	--	--	--	--	--
Rack, rabbit, 3 tier, 1 cage per tier, 3 cages per rack included. Racks constructed entirely of type 304 stainless steel tubing with 16 gauge wall thickness. Mounted on 5 inch heavy duty stem-type copper/nickel/chrome plated casters. Approximate rack dimensions: 29-1/2" W x 25-1/4" D x 71-1/2" H. Accessory items such as feeding bowls, water systems, etc. must be ordered separately. [No other sources(s) identified with this description/specification.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	NO	BTUs / HR:		
EA		IN:	72	37	27	100 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	183	94	69	46 kg	2:	--	--	--	DEPENDENT:	NO	--
V0078	6530	Rack, Cat, 6 Cages Per Rack	C C C C --	--	--	--	--	--	--	--	--	--	--
Rack, cat, 6 stainless steel cages per rack. Includes resting boards, stainless steel feeders, card holders and stainless steel waste pans. Racks are mounted on 5 inch heavy duty stainless steel casters, 2 locking.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	BTUs / HR:		
EA		IN:	70	82	32	150 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	178	208	81	68 kg	2:	--	--	--	DEPENDENT:	NO	--
V0082	6530	Rack, Guinea Pig, 15 Cages Per Rack	C C C C --	--	--	--	--	--	--	--	--	--	--
Rack, guinea pig, stainless steel, 5 Tier, 3 cages per tier, 15 cages per rack. Each rack includes stainless steel refuse pans. Each cage includes stainless steel feeders. Mounted on 5 inch heavy duty stainless steel casters, 2 locking. [Model 1 and 3 are 8 cage models. A 15 cage rack is a special order item.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	BTUs / HR:		
EA		IN:	70	71	27	-- lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	178	180	69	-- kg	2:	--	--	--	DEPENDENT:	NO	--
V0084	6530	Rack, Hamster, With 20 Cages	C C C C --	--	--	--	--	--	--	--	--	--	--
Rack, hamster, at least 20 cage capacity, stainless steel, 20 cages per rack. Accessory items such as feeders, water bottles, etc. are ordered separately.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	BTUs / HR:		
EA		IN:	75	70	26	200 lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	190	178	66	91 kg	2:	--	--	--	DEPENDENT:	NO	--
V0085	6530	Shelving Unit For 20 Hamster Cages	C C C C --	--	--	--	--	--	--	--	--	--	--
Shelving rack, hamster, accommodates 20 cages per rack, stainless steel. Accessory items such as cages, feeders, water bottles, etc. are ordered separately. [Price difference verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	BTUs / HR:		
EA		IN:	75	67	26	-- lb	1:	--	--	--	HZ SWITCH:	NO	--
		CM:	191	170	66	-- kg	2:	--	--	--	DEPENDENT:	NO	--

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
V0086	6530	Rack And Cage System, Metabolism, 8 Per Unit	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Cage, metabolism, consisting of a stainless steel rack and 8 - 14 metabolic cages per rack. Cages are positioned on removable shelves. Cage size: approximately 12" W x 15" D x 25" H. Rack has four 5 inch diameter casters, 2 with brakes. [Prices differences verified. Model 1 includes 14 cages.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	75	71	25	150 lb	1:	--	--	--	NO				
		CM:	190	180	64	68 kg	2:	--	--	--	NO				
V0088	6530	Rack And Cage, Metabolism, 18 Per Unit	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Cage, metabolism, consisting of a stainless steel rack and approximately 18 metabolic cages per rack. Cage size: 12"W x 15"D x 5"H. Rack has four 5 inch diameter neoprene casters, 2 with brakes. [No other source(s) identified with this description/specification]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	68	64	18	325 lb	1:	--	--	--	NO				
		CM:	173	163	46	148 kg	2:	--	--	--	NO				
V0105	6530	Run, Modular, Stainless Steel	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Run, modular, stainless steel, includes three runs in each room, approximately 4' x 6'. Custom designed to fit rooms. Prices to be determined for each application. [Place holder only, specifications and prices to be determined for specific application.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	--	--	--	-- lb	1:	--	--	--	0				
		CM:	--	--	--	-- kg	2:	--	--	--	NO				
V0110	6530	Dispenser, Bedding, With Conveyor	C C C C --	--	D	--	--	--	--	--	--	--	--	--	E
Dispenser, bedding, with 36 inch wide conveyor. Storage-dispensing hopper, 14 gauge stainless steel, with stainless steel structure supports. Includes start/stop switch and speed control for the variable speed drive motor and start/stop switch for the drive motor that powers the cage conveyor.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	62	84	96	1,250 lb	1:	208	1	20	60				
		CM:	157	213	244	568 kg	2:	120	1	15	NO				
V0115	6530	Filler, Bottle, For Lab Animals	C C C C --	B	A	--	--	--	--	--	--	--	--	--	--
Filler, bottle, for filling laboratory animals' watering bottle. Includes interchangeable header with nozzle to fill 32 ounce bottles. Header, jets, table and frame fabricated entirely of type 304 stainless steel with brass valve. [Price difference verified. Model 3 Optional Station (part #BFS 100), left or right side, is an additional \$990.00.]															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	47	20	30	151 lb	1:	120	1	1	60				
		CM:	119	51	76	69 kg	2:	--	--	--	NO				
V0120	6530	Station, Clean/Dump, Waste, Portable	C C C C --	--	A	--	--	--	--	--	--	--	--	--	--
Waste management system for laboratory animals. Constructed of stainless steel with two lower cabinets that are designed to hold kraft bags, autoclavable poly vinyl bag, or disposable container box. Unit includes casters, with two locking.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	89	64	52	700 lb	1:	120	1	15	60				
		CM:	226	163	132	318 kg	2:	--	--	--	NO		900		
V0125	6530	Rack, Excreta Pan	C C C C --	--	--	--	--	--	--	--	--	--	--	--	--
Rack, wash, excreta pan, stainless steel. Complete with stainless steel casters, two fixed and two swivel. Approximate dimensions: 36" w x 76" D x 53" H.															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:				
EA		IN:	54	38	68	-- lb	1:	--	--	--	--				
		CM:	137	97	173	-- kg	2:	--	--	--	NO				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
V0130	6530	Workbench, Laminar Flow, Mobile, 4 Feet	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Workbench, stay-clean, with laminar flow hood, mounted on casters. Air flow is horizontal positive. Work area dimensions are approximately 46W X 22D. Other sizes available. [Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	72	53	34	560 lb	1:	120	1	20	NO							
		CM:	183	135	86	255 kg	2:	--	--	--	YES							
V0135	6650	Bio-Clean Unit, Duo-Flow	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Laminar flow bio-clean unit, duo-flow, mounted on casters. Negative or positive flow. Approximate dimensions: 72" W x 36" D x 73" H.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	80	78	46	510 lb	1:	120	1	15	NO							
		CM:	203	198	117	232 kg	2:	--	--	--	YES							
V0140	6530	Isolator, Micro, Housing Unit	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Stay-clean system; housing unit, stainless steel with three or four shelves to accommodate various cage sizes. Used to protect animals from airborne contamination. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	80	69	46	175 lb	1:	120	1	15	NO							
		CM:	203	175	117	80 kg	2:	--	--	--	NO							
V0150	6515	Anesthesia/Ventilator System, Veterinary	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Veterinary anesthesia/ventilator delivery system. Maintains independent regulation of inspiratory time, inspiratory flow, and respiratory pause. Monitors tidal volume, system leaks, and automatic overflows of high gas inflows during spontaneous manual bag or mechanical ventilation, with mounting adapter extension pipe and clamp for attachment to horizontal or vertical surface. Tidal volume range is 0-300ml or 300-1600ml. Contains an internal battery backup. [This is the only unit found that provides both anesthesia and ventilation in a single delivery system. A vaporizer, if required must be ordered as an accessory, average price \$1,000.00.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	4	10	10	10 lb	1:	--	--	--	NO							
		CM:	10	25	25	5 kg	2:	--	--	--	NO							
X0990	6525	Immobilizer, Infant, With Cassette Holder	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Infant immobilizer. This unit has a cassette holder for use in radiology for X-ray imaging of infants and toddlers. This unit is used for simple and fast immobilizing and positioning of infants for radiographic, fluoroscopic and other medical examinations. The seat platform turns on ball bearings and has horizontal movement of cassette carriers. The unit is adjustable for patients from ages infant to 3-1/2 years. The lead shield has adjustable conventional markers and adjusts up and down for various examinations.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	40	23	46	90 lb	1:	--	--	--	NO							
		CM:	102	58	117	41 kg	2:	--	--	--	NO							
X1000	6525	Benchtop, Plastic, Laminated	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Plastic laminated benchtop. This unit is custom built for all types of darkrooms and loading benches. The length, depth, and color are specifically matched to each installation. The top is 3/4 inch plywood with a 4-1/2 inch high (outside size), backsplash and end returns. Waste bin cutouts are bound with a welded stainless steel rim either 4"X16" or 7"X7" size. This unit is used on top of darkroom casement in X-ray processing rooms. is based per foot of benchtop. [The price provided is based on one linear foot of plastic laminate benchtop. The average cost of a waste bin cutout is \$55. A stainless steel rim ranges in price from \$40 to \$90. All pricing is directly dependent on quantity and size.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	5	12	24	-- lb	1:	--	--	--	NO							
		CM:	13	30	61	-- kg	2:	--	--	--	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X1020	6525	Cabinet, Wall Hung, With (3) 5 Inch Compartments	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall mounted cabinet. This is a wall hung unit with three 5 inch vertical compartments. The unit is generally used for cassette storage in hospital darkrooms. [A thorough search of vendors could not identify another source for this item. GE and Phillips both previous sources have discontinued the item.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			22	18	16	40 lb	1:	--	--	--	0	NO	--					
			56	46	41	19 kg	2:	--	--	--	NO	NO	--					
X1030	6525	Cabinet, Wall Hung, 4 Compartments, 22x24x16	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall mounted cabinet. This is a wall hung unit with (4) vertical compartments. The unit is generally used for cassette storage in hospitals and photo darkrooms. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			22	24	16	51 lb	1:	--	--	--	--	NO	--					
			56	61	41	24 kg	2:	--	--	--	NO	NO	--					
X1040	6525	Cabinet, Wall Hung, 1-2 Door, 3 Shelves, 22x18x21	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Wall mounted cabinet with 1 or 2 doors, approximately 22" H X 18" W X 21" D. This unit is designed to organize and store darkroom materials. The unit has two or three adjustable shelves. The construction is a double wall that is utilized throughout. All hardware used is of the highest quality including full length piano hinges, positive action roller latches, and brushed metal wire pulls. [No other source(s) identified with this description/specification. Model 1 has one shelf.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			22	18	16	44 lb	1:	--	--	--	--	NO	--					
			56	46	41	20 kg	2:	--	--	--	NO	NO	--					
X1050	6525	Cabinet, Base, With (3) 5 Inch Compartments	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Cassette storage base cabinet. The unit is approximately 36" H x 18" W x 22" D and is constructed with heavy gauge, rust resistant Electro-galvanized steel. It has double wall construction throughout and all hardware used is of the highest quality. The unit is designed to organize and store darkroom materials. The unit has capacity for extra large cassettes. All vertical partitions are removable. [No other source(s) identified for this item with this description/specification. GE and Philips have discontinued the item.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			36	18	22	75 lb	1:	--	--	--	0	NO	--					
			92	46	56	34 kg	2:	--	--	--	NO	NO	--					
X1060	6525	Cabinet, Base, 1 Door	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Base storage cabinet. The unit is approximately 37" H x 18" W x 22" D and is designed for X-ray department use. The unit has one hinged door (may have two doors) and two adjustable shelves. The cabinet may be constructed of steel or laminated wood. [Model 1 has two doors. A third source could not be located for this item. Both GE and Philips have discontinued the item.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			37	18	22	77 lb	1:	--	--	--	0	NO	--					
			94	46	56	35 kg	2:	--	--	--	NO	NO	--					
X1070	6525	Bin, Receptacles, Waste, 37x12x22	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Waste receptacle bin. This unit is supplied with a removable metal paper container that has handles at both ends. The waste bin is installed under centerline of 6 X 6 inches (152 X 152 mm) bench top cutout for easy access. This unit is used in X-ray darkrooms.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			37	15	22	45 lb	1:	--	--	--	--	NO	--					
			94	38	56	21 kg	2:	--	--	--	NO	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
X1080	6525	Cabinet, Base, Film Identifier	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Film identifier base cabinet approximately 36"H x 12" W x 22 "D. This cabinet is generally fabricated to meet the needs and requirements of the facility. The unit features full length, chrome plated piano hinges, touch latches, height adjustable shelves, bases and stainless steel edging on cassette storage cabinets. [No other source (s) identified with this description/specification.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	37	12	22	75 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	94	30	55	34 kg	2:	--	--	--									
X1100	6525	Bin, Loading, Film	A	A	A	A	--	--	F	--	--	--	--	--	--	--	--	--	
<p>Film loading bin, approximately 33" H x 23" W x 15" D. Double steel light trap door gives maximum protection and assures lifetime safety. All corners and seams are welded for strength and protection. The interior of the hinged bin is divided into five compartments, each capable of accepting 14" X 17" films. Adjustable inserts to accommodate smaller size films are provided. Also provided with a room light micro switch interlock. This unit is used in photo and X-ray darkrooms.</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	36	22	15	78 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	91	56	38	36 kg	2:	--	--	--									
X1160	6525	Cabinet, Filing, Film, 5 Shelves With Doors	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Film filing cabinet with 5 shelves and sliding doors approximately 87" H x 31" W x 20" D. This unit enables you to make maximum use of available floor space while providing enclosed radiographic storage for 800 film in envelopes per section. The cabinets are provided with removable partitions to hold films upright. Each cabinet has an exterior channel for inserting identification labels. Construction allows stacking up to 5 high on separate bases. Base included in unit price.</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	89	32	20	285 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	226	81	51	130 kg	2:	--	--	--									
X1170	6525	Cabinet, Filing, Film, 5 Shelves, 88x36x18	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Film filing cabinet. Open shelf system with 5 shelves. Each 36 inch shelf has three interlocking dividers for use with X-ray film jackets. The system is used to store and file X-ray film folders.</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	--	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	88	36	18	165 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	224	91	46	75 kg	2:	--	--	--									
X1171	6525	Cabinet, Filing, Film, 5 Shelves 88x48x18	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Film filing cabinet. Open shelf system with 5 shelves. Each 48 inch wide shelf has three interlocking dividers for use with X-ray film jackets. This system is used to store and file X-ray film folders.</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	88	48	18	213 lb	1:	--	--	--	DEPENDENT:	NO	--						
		CM:	224	122	46	97 kg	2:	--	--	--									
X1200	6525	Lithotripter, Extracorporeal	F	F	F	F	--	D	F	D	--	--	B						
<p>Extracorporeal Shock Wave Lithotripter (ESWL), is a multifunctional radiographic/fluoroscopic urological diagnostic and ESWL System with optional ultrasound capabilities. It is used to locate urinary stones and calculi using radiology and treating the stones and calculi using ultrasound shock waves. The equipment must be capable of full power usage and full operation with patient under full conscious sedation as opposed to anesthesia. [Recommended minimum room size: 18'-0" L x 16'-0" W. Recommended minimum ceiling height 8'-0".]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:						
EA		IN:	--	--	--	3,277 lb	1:	480	3	91	DEPENDENT:	YES	12,400						
		CM:	--	--	--	1,488 kg	2:	--	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X1360	6525	Cabinet, Filing, Film, Modular, Auto, 92x84x18	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
Film filing cabinet. This unit is a modular design cabinet for filing X-ray film. The unit is automatically movable with 5 tiers in each row. Characteristics and components include two automatically movable units and stationary units double faced. The unit is used to store and file X-ray film in hospitals and healthcare facilities. Must meet ADA Standards. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	126	84	18	--	1:	120	1	15	NO							
		CM:	320	213	46	--	2:	--	--	--	NO							
X1400	6525	Holder, Cassette, Vertical, With Bucky	F	F	F	F	--	--	D	--	--	--	--	--	--	--	--	--
Vertical cassette holder. Includes counterbalanced cabinet holder, vertical multi-sided capability with three field automatic exposure control and automatic collimation control. The unit is available in either right or left hand loading. Sturdy box girder construction, with nylon bearings and dual lock system. The unit is used in X-ray departments for holding film cassettes during radiographic procedures. Specify right or left hand cassette loading when ordering.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	88	27	27	348	1:	110	1	4	NO							
		CM:	223	69	69	158	2:	220	3	4	YES							
X1405	6525	Stand, Bucky, Vertical, Tilt, Automatic	F	F	F	F	--	--	A	--	--	--	--	--	--	--	--	--
Vertical and tilting bucky stand. This unit is mounted to the floor and wall to provide a vibration-free mounting platform for the universal bucky. The grid line free radiographs are produced at exposure times as short as two milliseconds. Characteristics and components include aluminum interspaced grid with a 36 inch (914 mm) to 40 inch (1016 mm) focal range. The unit's cassette size sensing tray accommodates all cassette sizes between 5 and 17 inches. The unit tilts at angles of +90/-20 degrees from the vertical position. The unit is used in X-ray facilities for processing radiography images.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	87	31	27	335	1:	120	1	5	NO							
		CM:	222	80	68	152	2:	--	--	--	NO							
X1415	6525	Laser Positioning System, Patient-Wall	F	F	F	F	--	--	F	--	--	--	--	--	--	--	--	--
Laser positioning system. This unit is designed for accurate patient alignment for radiation therapy. Three vertical laser beams and a horizontal beam intersect to define the iso-center to aid in patient positioning. The unit is generally supplied as a component of various radiation therapy systems.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	18	6	4	15	1:	115	1	1	NO							
		CM:	46	15	10	7	2:	--	--	--	YES							
X1416	6525	Laser Positioning System, Patient-Ceiling	F	F	F	F	--	--	F	--	--	--	--	--	--	--	--	--
Laser positioning system. This unit is designed for accurate patient alignment for radiation therapy. Three vertical laser beams and a horizontal beam intersect to define the iso-center to aid in patient positioning. The unit is generally supplied as a component of various radiation therapy systems.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	17	25	5	15	1:	120	1	1	NO							
		CM:	43	64	13	7	2:	--	--	--	YES							
X1420	6525	Imager, Laser (512x512) Din/PACS	F	F	F	F	--	--	C	--	--	--	--	--	--	--	--	--
Laser imager. An infrared laser beam is scanned across the film by a precision rotating polygon, while correcting optic focus and controlling the beam's intensity. The characteristics and components include an automatic film handling system and uses 10" X 14" IR film. It can be interfaced to additional imaging modalities with optional interface kit. For use with digital output imaging modalities.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	57	40	26	749	1:	220	1	16	YES							
		CM:	145	102	66	340	2:	--	--	--	NO							

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X1425	6525	Imager, Laser (1024 X 1024) (Din/PACS)	F	F	F	F	--	--	A	--	--	--	--	--	--	--	--	--
Laser imager. Solid state laser that provides high resolution images of superior quality and accuracy. An infrared laser beam is scanned across each film by a precision rotating polygon, while correcting optics focus and control the beam's intensity. Can be interfaced to as many as eight (8) modalities with interface kit. For use with digital output imaging modalities.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN:	60	65	31	800 lb	1:	120	1	15	HZ SWITCH: NO		--					
		CM:	152	165	79	363 kg	2:	--	--	--	DEPENDENT: NO		--					
X1426	6525	Imager, Dry Chemistry, 14" X 17"	C	C	C	C	--	--	C	--	--	--	--	--	--	--	--	--
Dry chemistry laser imager that produces high resolution, continuous-tone images that incorporate a dry developing process for ready-to-view 14" x 17" films as they exit the system. The use of wet fixer, developer and water for processing of film is not required. No hazardous wastes (as defined by the EPA) shall be produced. Shall have the options for 512, 1024 and 2048 resolutions. One or two inputs (digital or video) are standard and expandable with the optional input manager. System shall conform to DIN-PACS and DICOM V3.0 or latest version.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:							
EA		IN:	54	26	32	550 lb	1:	220	1	10	HZ SWITCH: YES		2,300					
		CM:	137	66	81	250 kg	2:	--	--	--	DEPENDENT: NO		--					
X1427	6525	Imager, Dry Chemistry, 8" X 10"	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
The imager shall produce a high resolution, continuous-tone images that incorporates a dry imaging and developing process for ready-to-view, 8" x 10" films as they exit the system. The use of wet fixer, developer and water for processing of film is not required. No hazardous wastes (as defined by the EPA) shall be produced. Shall have 2,256 X 2,676 pixels, spatial resolutions. One or two inputs (digital or video) are standard and expandable up to four with the optional input manage systems. Shall conform to DIN-PACS and DICOM V3.0 or latest version. Primary applications are C-arm, digital X-ray, nuclear medicine and ultrasound.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN:	18	21	27	165 lb	1:	120	1	7	HZ SWITCH: NO		700					
		CM:	46	53	68	75 kg	2:	--	--	--	DEPENDENT: NO		--					
X1600	6525-00-075-3294	Cabinet, Transfer, Cassette, 4 Door, 2 Compartment	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--
Cassette transfer cabinet. (X-ray pass box). This unit is a X-ray pass box with four doors and automatic interlock. There is a 1/16 inch lead lining and two compartments. The unit is fabricated from heavy gauge steel and features double wall construction throughout. With the automatic system, when one door is opened, the door on the other side is automatically locked. This device is used in darkrooms to transfer cassettes.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: --		BTUs / HR:							
EA		IN:	27	25	20	240 lb	1:	--	--	--	HZ SWITCH: NO		--					
		CM:	69	64	51	109 kg	2:	--	--	--	DEPENDENT: NO		--					
X1709	6525	Loader/Unloader, Film, Daylight, Multiple	F	F	F	F	--	--	F	--	--	--	--	--	--	--	--	--
Daylight film loader/unloader provides for up to 7 sizes of film/cassettes combinations. Device automatically unloads and loads coded cassettes or permits front panel selection of film size-type for uncoded cassettes. Loader/unloader must interface with a film processor. [This product line has been discontinued by many major manufacturers, such as Dupont Medical and Sterling Diagnostic Imaging.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN:	49	32	28	721 lb	1:	208	1	15	HZ SWITCH: YES		--					
		CM:	124	81	71	328 kg	2:	--	--	--	DEPENDENT: NO		--					
X1710	6525-01-010-8496	Processor, Film, Daylight	F	F	F	F	--	--	B	C	--	--	--	--	--	--	--	--
Processing set, radiographic film, daylight system. May be an individual component or integrated system. Cassette loader/unloader and rapid film processor provides for three integral film sizes and 80 second processing. Alternative processing cycles include 103, 137 and 244 second processing. Requires exhaust for humid air. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:							
EA		IN:	51	34	33	771 lb	1:	208	1	30	HZ SWITCH: NO		9,194					
		CM:	130	86	25	68 kg	2:	--	--	--	DEPENDENT: NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X1719	6525	Adapter, Processor, Film, Daylight	E	E	E	E	--	--	A	--	--	--	--	--	--	--	--	--
<p>Film processor adapter. This is a daylight system which fits on the feed tray of most full size processors and is designed to accept daylight transport feeder for automatic feeding in daylight. Unit can also be fed manually, under safe-light conditions, into processor with adapter in place. For Kodak processor M8, M6B, M6AW, M6A-N, M7A, and M7. Use Model RA for X-Omat processor models 460, 480, and 270RA. [No other source(s) identified with this description/specification. This item is made by Eastman Kodak for Kodak X-Omat series processors.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	50/60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			10	21	22	67 lb	1:	120	1	2								
			25	53	56	31 kg	2:	--	--	--								
X1720	6525-00-612-7650	Safe, Film, X-Ray, 2 Compartment	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>X-ray film safe. The safe has a dispenser type design and two interior compartments. It has a sensing eye which will only allow opening the cover under safe light conditions making accidental exposure of film impossible. Once opened, the unit's top automatically recloses. The safe accommodates 150 unexposed film packets and 16 exposed film packets and can be mounted on a wall or in a radiology or dental cabinet. The safe is used in film processing and film storage. [For applications where the safe light feature is not needed, Wolf X-ray (CAGE 66335) carries a 2 compartment film bin with an automatic closing top.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	YES	--	--
			12	16	19	20 lb	1:	120	1	1								
			30	41	48	9 kg	2:	--	--	--								
X1725	6525	Duplicator/Printer, Film, Table, 17x16x24	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>X-ray film duplicator and/or subtraction printer. Table top. This unit is a high-precision subtraction device that provides maximum resolution, transfer, and consequently makes subtraction of the highest diagnostic value. It is lightweight and compact, and features easy to read lighted controls, including the switch controlling both subtraction and duplication; which prevents double exposure. [No other source(s) identified with this description/specification.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			17	24	24	75 lb	1:	120	1	1								
			43	61	61	34 kg	2:	--	--	--								
X1730	6525	Duplicator, Film, Dental, 9x18x14	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Dental X-ray film duplicator. This unit copies up to 8 inch by 10 inch dental X-ray film. The entire operating mechanism is a modular assembly that can be lifted out of the housing for access to all components. The unit's construction is high-density polyethylene and coated steel. Casework is impervious to standard processing chemicals. It also has a built-in safelight for positioning of films.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			9	19	14	-- lb	1:	110	1	35								
			23	48	36	-- kg	2:	--	--	--								
X2040	6525	Processor, Film, Dental	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
<p>Processor, film dental X-ray. This unit is designed for operational simplicity. The film feed and exit are from the top as are the convenient push button controls and indicator light. Processing times are optimized at approximately 6.25 minutes. The unit requires no plumbing and includes a built-in automatic chemistry heating system. The unit is used in dental offices and facilities. [Air Techniques Incorporated, is also the manufacturer of Model A/T 2000 (Model 3) which is distributed by Sullivan-Schein Dental (CAGE 8Y961).]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	--	--
			18	18	31	90 lb	1:	120	1	8								
			46	46	79	41 kg	2:	--	--	--								
X2100	6515	Scanner, Ultrasound, General Purpose	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
<p>High definition, diagnostic ultrasound system for Radiology, Cardiology, Vascular, ob-gyn, Perinatology, and Surgical imaging applications. The unit employs curved, phased and linear array imaging technology. The system supports colorflow, pulse and continuous wave imaging modalities. On board software measurement packages available for all imaging applications. The system is DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. In addition, a full line of probes and conventional recording devices are available.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	DEPENDENT:	NO	4,788	--
			64	27	45	590 lb	1:	120	1	20								
			163	69	114	268 kg	2:	--	--	--								

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X2105	6515	Scanner, Ultrasound, Cardiac (Echo)	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
High definition, diagnostic ultrasound system for Radiology, Cardiology, Vascular, ob-gyn, Perinatology, and Surgical imaging applications. The unit employs curved, phased and linear array imaging technology. The system supports colorflow, pulse, continuous wave imaging modalities. On board software measurement packages available for all imaging applications. The system is DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. In addition, a full line of probes and conventional recording devices are available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN: 64	24	39	590 lb	1: 120	1	12	HZ SWITCH: NO		--							
		CM: 163	61	99	268 kg	2: --	--	--	DEPENDENT: NO		--							
X2107	6515	Scanner, Ultrasound, Intravascular	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
High definition, diagnostic ultrasound system for Cardiology and Vascular studies. The unit employs curved, phased and linear array imaging technology. Provides 360 degrees internal images of the coronary arteries, peripheral vessels and cardiac chambers.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:							
EA		IN: 61	25	28	450 lb	1: 120	1	13	HZ SWITCH: NO		--							
		CM: 155	64	71	205 kg	2: --	--	--	DEPENDENT: NO		--							
X2110	6515	Scanner, Ultrasound, Pulsed Doppler	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
High definition, diagnostic ultrasound system for Radiology, Cardiology, Vascular, ob-gyn, Perinatology, and Surgical imaging applications. The unit employs curved, phased and linear array imaging technology. The system supports colorflow, pulse, and continuous wave, imaging modalities. On board software measurement packages available for all imaging applications. The system is DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. In addition, a full line of probes and conventional recording devices are available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN: 64	26	42	500 lb	1: 120	1	20	HZ SWITCH: NO		4,100							
		CM: 163	66	107	227 kg	2: --	--	--	DEPENDENT: NO		--							
X2111	6515	Scanner System, Ophthalmic, Topographic	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Shall be a laser operated, multipurpose tomograph for the imaging and measurement of the retinal topography, changes of the optic nerve, macula holes, tumors and edema. Shall have the capability for ICG angiography. Shall have fast image acquisition time in the range of 940 milliseconds and be able to acquire images through undilated pupils. All standard components shall be integrated into one workstation. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN: 30	36	24	24 lb	1: 120	1	15	HZ SWITCH: NO		--							
		CM: 76	91	61	11 kg	2: --	--	--	DEPENDENT: NO		--							
X2115	6515	Scanner, Ultrasound, Obstetrical, Black & White	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
High definition, diagnostic ultrasound system for ob-gyn. The system supports black and white Doppler capability through all convex and linear sector transducers. On board software measurement packages available for all imaging applications. The system is DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. In addition, a full line of probes and conventional recording devices are available.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60		BTUs / HR:							
EA		IN: 60	22	37	441 lb	1: 120	1	20	HZ SWITCH: NO		--							
		CM: 152	56	94	201 kg	2: --	--	--	DEPENDENT: NO		--							
X2120	6525	Scanner, Bone Density, Full Body	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--
Full body scanner used to determine bone mineral density measurements and vertebral assessment associated with osteoporotic fracture risk. [Model 1 can also be procured with a 230VAC (8Amp) electrical requirement. This may be more cost efficient. Room size for Model 1 is 8' x 10'. The recommended minimum room size for Model 2 is 10' x 7'. Model 3 requires a room size of 9' x 8'. It also requires a 20Amp dedicated circuit for the computer/printer. The government price for Model 1 is \$98,000 and for Model 3 is \$65,000.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60		BTUs / HR:							
EA		IN: 51	48	104	950 lb	1: 120	1	14	HZ SWITCH: NO		3,400							
		CM: 130	122	264	432 kg	2: --	--	--	DEPENDENT: NO		--							

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES													
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
X2605	6525	Camera, Identification, Film	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--	
<p>Film identification camera for use with cassettes like the Kodak C1. Cannot be used for C2 (Windowless) cassettes. This unit works in normal room lighting, transferring patient I.D. data from a card to X-ray film. The I.D. appears as light type on a dark background; exposure time is approximately one second. [Numerous distributors found for this item, but only one manufacturer.]</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	12	12	17	20 lb	1:	120	1	1	60	NO	--						
			31	30	42	9 kg	2:	--	--	--	DEPENDENT:	NO	--						
X3145	6525-01-086-7025	Screen, X-Ray, Protective, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Mobile X-ray protective screen. The unit is a single 1/6 minimum thickness lead sheet, that is sandwiched between the formed steel shells. An 8" X 10" lead glass window is placed at a convenient height. The steel construction increases the X-ray protective value and is not X-ray transparent as are wood or wood products. The unit is used for effective radiation protection of department personnel during vascular procedures. This unit can fit any application with its mobility. [Price difference verified.]</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	75	31	2	150 lb	1:	--	--	--	0	NO	--						
			190	79	81	68 kg	2:	--	--	--	DEPENDENT:	NO	--						
X3147	6525-01-086-7025	Screen, X-Ray, Protective, Mobile, Adjustable	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Mobile X-ray protective screen. The X-ray barrier provides optically-clear visibility while shielding medical personnel from scatter radiation. Its large clear Pb lead-plastic or acrylic window offers 0.5 mm lead-equivalent protection to the user's head and upper body. The unit is used for effective radiation protection of department personnel during vascular procedures. This unit can fit any application with its mobility. [This JSN appears similar to JSN X3145, Screen, X-Ray, Protective, Mobile. Recommend the descriptions be reviewed.]</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	75	36	2	185 lb	1:	--	--	--	--	NO	--						
			190	91	6	84 kg	2:	--	--	--	DEPENDENT:	NO	--						
X3150	6525	Rack, Apron/Gloves, Wall Mounted	A	A	A	A	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Apron and gloves rack. This is a wall unit which holds aprons and gloves. The body is heavy gauge steel finish in gray or green baked enamel, glove and apron holding arms are aluminum. The unit's convenient on wall storage will prolong the useful life of your protection aprons by helping prevent damage to internal components.</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	69	30	--	25 lb	1:	--	--	--	--	NO	--						
			175	76	--	11 kg	2:	--	--	--	DEPENDENT:	NO	--						
X3155	6525	Rack, Apron/Gloves, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Apron and gloves rack. This is a mobile unit which holds aprons and gloves. The body is heavy gauge steel finish in gray or green baked enamel, glove and apron holding arms are aluminum.</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	69	30	30	108 lb	1:	--	--	--	0	NO	--						
			175	76	76	49 kg	2:	--	--	--	DEPENDENT:	NO	--						
X3830	6525	Illuminator, Film, Single, Wall Mounted	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--	
<p>Single film illuminator approximately 20"H x 17"W x 5"D. This is a single panel wall mounted unit. Characteristics and components include, two 15 watt fluorescent tubes; gravity grip film holder, constructed of corrosion resistant galvanized steel with stainless steel trim, and a clean uncluttered appearance. This unit is used to view X-ray film in hospitals and doctors offices.</p>																			
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:							
EA		CM:	21	17	5	23 lb	1:	120	1	1	60	NO	--						
			53	43	13	11 kg	2:	--	--	--	DEPENDENT:	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES							
			A	N	A	V	I	1	2	3	4	5	6
X3900	6525	Illuminator, Film, Double, Recessed	A	A	A	A	--	--	B	--	--	--	--
<p>Film illuminator double recessed, approximately 20" x 30" x 6". This unit offers completely flush recess installation that provides a clean modern appearance. The unit has two 15 watt fluorescent daylight bulbs or one 32 watt Circline lamp per section. It has a positive film holder for maximum holding capabilities. Each viewing area is controlled by an on/off rocker switch. The interior partition is removable for panoramic use. The unit is used to view radiography film in X-ray clinics and general hospital use. Specify panoramic illumination configuration when ordering.</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	20	30	6	-- lb	1:	120	1	2	60	NO	--
		CM:	51	76	16	-- kg	2:	--	--	--	NO	--	--
X3930	6525	Illuminator, Film, Double, Wall Mounted, 20x29x6	C	C	C	C	--	--	A	--	--	--	--
<p>X-ray film illuminator. This is a double, wall mounted type unit with a continuous viewing surface. The tension film grips are adjustable top and bottom with standard grip strip. The unit's balanced-light viewing is assured by the 32W circular fluorescent lamp. It provides 500 feet candles of cool operation across the entire 14" X 17" viewing surface. It is available with or without film-activated switch. The unit can be used in hospitals, examining rooms, satellite office or lab.</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	20	29	6	-- lb	1:	120	1	2	60	NO	--
		CM:	51	74	16	-- kg	2:	--	--	--	NO	--	--
X3940	6525	Illuminator, Film, 8 Panels, Wall Mounted	A	A	A	A	--	--	A	--	--	--	--
<p>Film illuminator, 8 panels, wall mounted. This unit has a stainless steel or light gray baked enamel finish. It consists of two 4-panel illuminators, with dual switches and torque grip film holders. The lower illuminator is tilted 35 degrees from the vertical while the upper illuminator is vertical (on two tier unit). It is arranged to facilitate handling of the films and especially effective for seated viewing. The unit is used to review and analyze X-ray films. [The lower illuminator on Model 2 and 3 has 20 degrees angulation from vertical as standard instead of 35 degrees.]</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	42	59	6	184 lb	1:	120	1	8	60	NO	--
		CM:	107	150	16	84 kg	2:	--	--	--	NO	--	--
X3950	6525	Illuminator, Film, Mobile, 4 Over 4	C	C	C	C	--	--	A	--	--	--	--
<p>Mobile film illuminator. This unit is manufactured of heavy gauge steel which is formed and welded into a single integral housing. It has two 4-panel illuminators with continuous film-retainer clips. The system has built-in reflectors which help provide panoramic uniform light through a 1/8" thick Plexiglas viewing panel. It is equipped with a mobile stand that allows movement of the unit where needed for use during lectures and conferences.</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	78	67	24	330 lb	1:	120	1	10	60	NO	--
		CM:	198	170	61	150 kg	2:	--	--	--	NO	--	--
X3960	6525	Illuminator, Film, 8 Panel, With Desk	C	C	C	C	--	--	A	--	--	--	--
<p>Film illuminator with desk approximately 78x66x24. This unit includes a four over four format of X-ray illuminators mounted in a high density particle board frame with walnut grain melamine high pressure laminated end panel. It shall have two remote control switches for individual light panel control. The lower tier of illuminators shall be mounted at 30 or 45 degree angle. [Model 2 base module and mounting arms are constructed of steel with the top made of wood with a Formica top. Model 3 unit is made of welded steel. Models 1 and 3 have lower tier of illuminators mounted at 20 degrees.]</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	78	66	24	335 lb	1:	120	1	10	60	NO	--
		CM:	198	168	61	152 kg	2:	--	--	--	NO	--	--
X3990	6525	Illuminator, Film, 4 Panels, Wall Mounted	C	C	C	C	--	--	A	--	--	--	--
<p>Film illuminator, 4 panels, wall mounted. This unit is designed for simple on the wall installation. It has a front-mounted switch for independent control of fluorescent lamps. The unit is used to review and analyze radiography film in hospitals and X-ray clinics.</p>													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:		
EA		IN:	23	60	6	116 lb	1:	120	1	5	60	NO	--
		CM:	58	152	16	53 kg	2:	--	--	--	NO	--	--

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X4000	6525	Illuminator, Film, 4 Panel, Recessed, 23x61x5	A	A	A	A	--	--	B	--	--	--	--	--	--	--	--	--
Film illuminator, four panels, recessed mounted. This unit has stainless steel trim, welded and ground smooth. It includes both high and standard brightness to best suit film density as well as standard film-activated switch.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	23	61	5	-- lb	1: 120	1	5	60	NO	--						
			59	155	13	-- kg	2: --	--	--	DEPENDENT:	NO	--						
X4110	6525	Console, PACS, Remote View, 512 X 512, 1 Monitor	F	F	F	F	--	--	B	--	--	--	--	--	--	--	--	--
One monitor remote viewing station for picture archiving and retrieval (PACS) system. This station is for use by providers outside of radiology to review images and results. Station includes local image storage, image manipulation, and simultaneous display of multiple images on a single 512 x 512 image display CRT. Images are stored on a resident hard disk and roll off the disk as more recent images are sent to the station by radiology. Provider may request images from the PACS. Unit must be connected to the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	20	20	10	42 lb	1: 120	1	2	50/60	NO	--						
			51	51	25	19 kg	2: --	--	--	DEPENDENT:	NO	--						
X4111	6525	Console, PACS, Remote View, 1k X 1k, 1 Monitor	F	F	F	F	--	--	A	--	--	--	--	--	--	--	--	--
One monitor remote viewing for picture archiving and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display on a 1K X 1K single CRT. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	29	48	29	350 lb	1: 120	1	9	50/60	NO	5,473						
			74	122	74	159 kg	2: --	--	--	DEPENDENT:	YES	--						
X4112	6525	Console, PACS, Remote View, 1k X 1k, 2 Monitors	F	F	F	F	--	--	B	--	--	--	--	--	--	--	--	--
Two monitor remote viewing station for picture archiving and retrieval (PACS) system. This station is for use by providers inside or outside of radiology to review images. Station includes local image storage, image manipulation, and simultaneous display of multiple images on two 1024 x 1024 image display CRT's. Images are stored on a resident hard disk and roll off the disk as more recent images are sent to the station. Provider may request images from the PACS. Unit must be connected to the PACS by LAN for image and result receipt. This station is for use in areas like radiologist's offices and the E.R. where a more comprehensive system is required. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	29	48	29	350 lb	1: 120	1	9	50/60	NO	--						
			74	122	74	159 kg	2: --	--	--	DEPENDENT:	NO	--						
X4122	6525	Console, PACS, Remote View, 2k X 2k, 2 Monitors	F	F	F	F	--	--	A	--	--	--	--	--	--	--	--	--
Two monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on a two 2058 X 2058 image display CRT's. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	29	48	29	350 lb	1: 120	1	9	50/60	NO	5,473						
			74	122	74	159 kg	2: --	--	--	DEPENDENT:	NO	--						
X4124	6525	Console, PACS, Remote View, 2k X 2k, 4 Monitors	F	F	F	F	--	--	A	--	--	--	--	--	--	--	--	--
Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 2K X 2K CRT's. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.																		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES								
			A	N	A	V	I	R	A	F	A	H	1	2	3
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	23	64	20	400 lb	120	1	10	60	NO	--		
				CM:				2:				DEPENDENT:			
			EA	58	163	51	182 kg	--	--	--		NO	--		
X4130	6525	Juke Box, Optical Disk, PACS	F	F	F	F	--	--	A	--	--	--	D		
Optical disk juke box for storage and retrieval of digital images. Device maintains on line images for the PACS system. Device includes multiple optical disk readers and stores multiple optical disks. In conjunction with the PACS processor, the correct platter is loaded into a reader, the image data is retrieved and the image is sent to the requesting location. The system shall be DICOM 3.0 or latest version compatible, for easy linkage to filmless image management systems and review stations. [No other source(s) identified with this description/specification.]															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	48	50	28	207 lb	120	1	15	50/60	NO	--		
				CM:				2:				DEPENDENT:			
			EA	122	127	71	94 kg	--	--	--		NO	--		
X4140	6525	Scanner, X-Ray Film Digitizer	F	F	F	F	--	--	A	--	--	--	D		
X-ray film scanner to permit filmed images to be converted to digital format. Device uses computer controlled laser beam to read the film data and converts the beam data to digital image data. Scan modes shall be 12-bit (4096) grayscale, 8-bit (256) grayscale or bi-level. Geometric accuracy shall be better than 1% or 2 pixels, whichever is greater, in both axes. Optical density range from 0.01 to 3.0. Shall accept all standard film sizes. Selectable scan speed for a 14" x 17" file are 11, 13, 26, and 51 seconds. Shall conform to the SCSI-2 specification. SCSI termination and ID selection are accessible on the unit. The system shall be DICOM 3.0 or latest version compatible, for easy linkage to filmless image management systems and review stations. [Model 2 comes standard with a 25 mixed size sheet feeder. Multiple sheet feeders are options for the other two models.]															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	29	26	29	90 lb	120	1	1	50/60	NO	--		
				CM:				2:				DEPENDENT:			
			EA	74	66	74	41 kg	--	--	--		NO	--		
X4150	6525	Processor, Computed Radiography Plate	F	F	F	F	--	--	C	--	--	--	D		
Computed radiography, high capacity plate reader is used to produce digital x-ray images from Imaging Plates (phosphor plates) or IP Cassettes. The system shall be DICOM 3.0 or latest version compatible for easy linkage to filmless image management systems and review stations. The x-ray images can then be processed electronically to improve diagnostic precision, film management and hard copy output quality. Requires X1420 or X1425 (Laser Imagers) for hard copy output.															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	60	33	45	705 lb	120	1	10	50/60	YES	2,630		
				CM:				2:				DEPENDENT:			
			EA	152	84	114	320 kg	240	1	16		NO			
X4160	6525	Computer, DIN/PACS System	F	F	F	F	--	--	C	--	--	--	D		
DIN/PACS central computer provides network traffic management, image processing control, and database management. It is a high-speed image and data server for medical imaging and shall support 1 to 200 workstations on a single server. Must have ACR/NEMA DICOM compliant database to ensure future compatibility. Available in four configurations: 16 GB RAID, 64GB RAID, 128 GB RAID and 256 GB RAID. Configuration is site dependent; specify configuration at the time of procurement. List price does not include networking or workstations.															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	--	--	--	250 lb	240	1	12	60	NO	--		
				CM:				2:				DEPENDENT:			
			EA	--	--	--	114 kg	--	--	--		YES	--		
X4200	6525	Stereotactic Surgical System	C	C	C	.	--	--	B	--	--	--	--		
Surgical instrument guided system used to track surgical instruments in cranial procedures. Interfacing with CT and MRI the device assists the surgeon in the cranial surgical procedure by showing the precise location of the hand instruments during a procedure. The device allows for simulation surgery prior to the actual operation. [The price for Model 1 can vary from \$400K to \$450K depending on software chosen.]															
			UNIT OF ISSUE:	HEIGHT IN:	WIDTH:	DEPTH:	WEIGHT:	VOLTS 1:	PHASE:	AMPS:	HZ:	HZ SWITCH:	BTUs / HR:		
			EA	60	32	32	250 lb	120	1	2	60	NO	--		
				CM:				2:				DEPENDENT:			
			EA	152	81	81	114 kg	--	--	--		NO	--		

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X4390	6525	Viewer, Spot, High Intensity	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
High intensity spot viewer. Unit can be desk or wall mounted with a foot switch. A swivel mount allows rotation for different angles. The illuminator is used for viewing dense films.																		
UNIT OF ISSUE:		EA	IN:	8	6	8	WEIGHT	9 lb	1:	120	1	5	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	20	15	20	4 kg	2:	--	--	--	--	--	DEPENDENT:	NO	BTUs / HR:	--	--	--
X4780	6525	Radiographic Unit, Mobile, Battery, 100 mA, 100kVp	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	--
Mobile radiographic, rechargeable battery powered x-ray unit. The unit is 100 mA, 110 kVp. For use in surgery or patient treatment areas.																		
UNIT OF ISSUE:		EA	IN:	77	29	59	WEIGHT	941 lb	1:	120	1	10	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	--
		CM:	196	74	150	428 kg	2:	--	--	--	--	--	DEPENDENT:	NO	BTUs / HR:	--	--	--
X4890	6525	Fluoroscopic, Digital, Mobile, C-Arm	C	C	C	C	--	--	F	--	--	--	--	--	--	--	--	--
This system is a high quality radiographic/fluoroscopic mobile digital C-arm for use in orthopedics, general surgery, urology, vascular, neurosurgery, neurovascular and cardiovascular procedures. This units characteristics and components include a high frequency x-ray generator with single or dual focus x-ray tube unit, 9" or 12" multi-field image intensifier, dual 16" monitors, real time digital imaging and last image hold capabilities. The system shall be DICOM 3.0 or latest version, compatible, for easy linkage to filmless image management systems and review stations.																		
UNIT OF ISSUE:		EA	IN:	87	85	34	WEIGHT	650 lb	1:	120	1	30	HZ:	60	HZ SWITCH:	YES	BTUs / HR:	--
		CM:	220	215	86	296 kg	2:	--	--	--	--	--	DEPENDENT:	NO	BTUs / HR:	--	--	--
X5100	6525	Radiographic Unit, 80 kW, Chest, Digital	F	F	F	F	--	--	F	--	--	--	--	--	--	--	--	B
Digital chest system designed solely for making x-ray exposures of the chest. Patients can be standing, seated or lying on their sides. Patient through put is approximately 60 exposures per hour. The configuration of the system consists of a detector subsystem, image processing system, 80 kW high frequency x-ray generator and ceiling suspension or floor mounted column for the x-ray tube. The system shall be DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. [Model 1 Philips (Gage Code 1CS84) is priced with a 65 KW generator. Philips usually configures this system this way due to the speed and efficiency of the detector (800 to 1600 speed equivalent). Recommended minimum room size: 16' L X 11' W, minimum ceiling height: 9'-5".]																		
UNIT OF ISSUE:		EA	IN:	--	--	--	WEIGHT	2,222 lb	1:	480	3	120	HZ:	50/60	HZ SWITCH:	YES	BTUs / HR:	7,850
		CM:	--	--	--	1,009 kg	2:	230	1	16	16	16	DEPENDENT:	NO	BTUs / HR:	7,850	7,850	7,850
X5300	6525-00-935-1006	Processor, Film, 120 Seconds	E	E	E	E	--	B	C	--	--	--	--	--	--	--	--	E
Film processor. This is a compact size, high capacity unit. The unit processes 400 mixed films per hour in 120 second processing mode. The unit should be provided with a 14 gallon external replenishment tank and standby kit. This system is used to process radiographic film in x-ray darkroom. [These models all have a choice of various preprogrammed processing cycles to provide complete versatility.]																		
UNIT OF ISSUE:		EA	IN:	45	31	31	WEIGHT	380 lb	1:	220	1	30	HZ:	60	HZ SWITCH:	YES	BTUs / HR:	--
		CM:	114	79	79	173 kg	2:	--	--	--	--	--	DEPENDENT:	NO	BTUs / HR:	--	--	--
X5310	6525-01-111-1018	Processor, Film, 150 Seconds	F	F	F	F	--	B	A	--	--	--	--	--	--	--	--	B
Automatic, compact 150 second processor unit. The unit provides processed, dry, ready-to-read radiographs in 150 seconds and has a fully automatic replenishment system. A removable dryer assembly is located behind the wet section for improved accessibility and ease of service. This tabletop unit is used in radiographic, nuclear medicine, ultrasound and radiation therapy departments. Accessories may include mounting stand and 7 gallon replenisher tanks.																		
UNIT OF ISSUE:		EA	IN:	20	26	31	WEIGHT	200 lb	1:	120	1	20	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	4,000
		CM:	51	66	79	91 kg	2:	--	--	--	--	--	DEPENDENT:	NO	BTUs / HR:	4,000	4,000	4,000

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X5320	6525-00-464-2514	Processor, Film, 90 Seconds	F	F	F	F	--	B	C	--	--	--	--	E				
<p>Film processor. This is a 90 second processor which monitors ten important processor functions, such as developer and fixer temperatures, developer and fixer recirculation, wash water flow and safety controls. The unit display is LED, and audible alarms alert the operator if any function deviates from normal operating limits.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			49	31	38	567 lb	1: 208	1	30	60	NO	NO	--					
			124	78	97	258 kg	2: --	--	--									
X5322	6525-00-464-2514	Processor, Film, 45 Second Cycle	E	E	E	E	--	B	G	--	--	--	E					
<p>Film processor. This is a 45 second processor which monitors ten important processor functions, such as developer and fixer temperatures, developer and fixer recirculation, wash water flow and safety controls. The unit display is LED, and audible alarms alert the operator if any function deviates from normal operating limits. Unit will process up to 460 films per hour. Rapid processing cycle requires use of special chemistry and films. Processor may be used as 90 second processor with standard film and chemistry. Unit can be docked to daylight loader/unloader unit. [The Fuji (Model 3) has a 50 second processing time.]</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			49	31	44	497 lb	1: 208	1	25	60	NO	YES	--					
			124	79	112	226 kg	2: --	--	--									
X5325	6525	Mixer, Chemical, Automatic	B	B	B	B	--	J	A	--	--	--	--					
<p>Automatic chemical mixer. This unit reduces chemical mixing time compared to manual methods. It indicates when more replenisher solution is needed. Once the operator inserts the needed concentrate containers, it automatically opens chemical bottles, turns on the water, mixes the solutions, turns off the water and feeds the mixed solution to the film processor. This system is used in small to medium departments.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			31	24	18	50 lb	1: 120	1	1	50/60	NO	NO	--					
			79	61	46	23 kg	2: --	--	--									
X5350	6525	Processor, Film, Dental, Automatic, Table Mounted	E	E	E	E	--	B	A	--	--	--	--					
<p>Dental film processor. This system is a table model. It is designed for operational simplicity. The film feed and exit are from the top as are convenient push button control and indicator lights. Processing times are optimized at approximately 2 minutes for extra-oral film and 4 minutes for intra-oral film. It has a solid state developer thermostat that controls the processing temperature, and individual circulation pumps ensure consistent and uniform processing. This unit is used in dental clinics and x-ray film processing facilities.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			20	25	31	90 lb	1: 120	1	6	60	NO	NO	--					
			51	64	79	41 kg	2: --	--	--									
X5414	6525	Silver Recovery System, 2 Gallon	C	C	C	C	--	--	A	--	--	--	--					
<p>This is a 2.5 gallon capacity silver recovery unit. The unit recovers approximately 0.125 troy ounces of silver per hour. This unit is designed for manual or batch recovery operations in small size labs. The controls are solid state with high quality non corrosive parts and multiple current selection controls. Must satisfy EPA standards for disposal of de-silvered fixer, developer and wash water.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			31	15	14	46 lb	1: 120	1	4	60	NO	NO	--					
			79	38	36	21 kg	2: --	--	--									
X5416	6525	Silver Recovery System, 5 Gallon	C	C	C	C	--	--	A	--	--	--	--					
<p>Five gallon silver recovery unit. This unit's recovery capacity is approximately 0.315 troy ounces per hour. The unit is perfect for small to medium sized applications. The design characteristics include a gear driven motor, non corrosive parts and a removable cathode. Must satisfy EPA Standards for disposal of de-silvered fixer, developer and wash water.</p>																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			36	19	14	62 lb	1: 120	1	4	60	NO	NO	--					
			91	48	36	29 kg	2: --	--	--									

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES						
				R	A	F	A	H		1	2	3	4	5	6	
X5420	6525	Silver Recovery System, 6 Gallon, 37x15x14	C C C C --	--	A	--	--	--	--							
Six gallon silver recovery system. The unit is designed to work with most film processors that use 0.5 to 14 gallons of fixer per day. The unit recovers from 0.25 to 3.0 troy ounces of silver per hour. This automatic unit samples the processor's silver concentration and adjusts the operating current to match actual silver recovery needs. Must satisfy EPA Standards for disposal of de-silvered fixer, developer and wash water. [.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:			
EA	CM:	37	18	15	62 lb	1:	120	1	12	60	NO	--				
		94	46	38	28 kg	2:	--	--	--	DEPENDENT:	NO	--				
X5430	6525	Radiographic Unit, Mammographic	F F F F --	--	C	--	--	--	--							
This system is specifically designed, both electronically and mechanically, to meet the recommended American College of Radiology (ACR) "Specifications for New Mammography Equipment". The system is a computer controlled, menu-driven unit for exclusive use in mammography examination procedures. The examination can be performed on standing, seated or recumbent patients. Shall have stereotactic biopsy capability if this option is selected. [Recommended minimum room size: 12'-6" L x 14 W, ceiling height 8'-0". Full field digital mammography systems have recently become available. Prices are considerably higher and range from \$470K to \$630K. The Lorad M-IV Platinum unit and the GE Seonraphe DMR + can be upgraded. Consideration should be given to adding a new JSN for the full field digital mammography systems.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:			
EA	CM:	--	--	--	1,073 lb	1:	208	1	41	50/60	YES	4,952				
		--	--	--	488 kg	2:	--	--	--	DEPENDENT:	NO	--				
X5435	6525	Breast Biopsy System, Stereotactic	F F F F --	--	F	--	--	--	--							
System used for performing breast biopsies using x-ray and computer imaging. [Model 1 can also be purchased with digital spot mammography (DSM). Model 2 & 3 have numerous options available.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:			
EA	CM:	72	109	61	1,722 lb	1:	240	1	35	0	NO	6,037				
		183	277	155	782 kg	2:	208	1	35	DEPENDENT:	NO	--				
X5440	6525	Table, Breast Biopsy, Floating Top	C C C C --	--	A	--	--	--	--							
Decubitus breast imaging table used in performing core breast biopsies. Table provides 360 degree access to the breast. Table is used for stereotactic breast biopsy procedures, as well as for stretcher mammography, ultrasound guided biopsy, needle location and can be used as a flat exam table. This table includes patient positioning system, 4 way float top, 4" longitudinal travel, 4" transverse travel, linear bearings, and electromagnetic lock. [No other source (s) identified with this description/specification. See X5435, Breast Biopsy System, Stereotactic. This system includes a table.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:			
EA	CM:	38	27	72	315 lb	1:	120	1	2	60	NO	--				
		97	69	183	143 kg	2:	--	--	--	DEPENDENT:	NO	--				
X5445	6525	Table, Breast Biopsy	C C C C --	--	A	--	--	--	--							
Decubitus breast imaging table used in performing core breast biopsies. Table provides 360 degree access to the breast. Table is used for stereotactic breast biopsy procedures, as well as for stretcher mammography, ultrasound guided biopsy, needle location and can be used as a flat exam table. [No other source (s) identified with this description/specification. See X5435, Breast Biopsy System, Stereotactic. This system includes a table.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:			
EA	CM:	38	27	72	315 lb	1:	120	1	2	60	NO	--				
		97	69	183	143 kg	2:	--	--	--	DEPENDENT:	NO	--				
X5500	6525	Radiographic Unit, Cephalometric	F F F F --	--	G	--	--	--	--							
Cephalometric radiographic unit. This unit shall have electronic timing with automatic reset timing capability and a main correction unit to adjust for line voltage fluctuations. Tube head shall be of the oil immersed shield-type with a total inherent filtration of 3.3 mm A1 and a focal spot of 0.9. [Model 1 can be upgraded to a clinical correct direct digital imaging system with an approximate cost of \$47,305. Model 2 can also be upgraded by adding part numbers 5450 260 and 918 672 at a cost of \$33,495.]																
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		HZ SWITCH:		BTUs / HR:			
EA	CM:	90	59	47	308 lb	1:	220	3	16	60	NO	--				
		229	150	119	140 kg	2:	--	--	--	DEPENDENT:	YES	--				

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X5700	6525	Radiographic Unit, 65 kW, Non-Tilt Table	F	F	F	F	--	--	F	--	--	--	--	B				
<p>This system is specifically designed to perform radiographic examinations in the Radiology Department. This units characteristics and components include, 65 kW micro-processor controlled X-ray generator, non-tilting table with a horizontally adjustable bucky and floating table top, ceiling suspended 0.6/1.0 mm tube unit and vertical bucky stand. [Recommended minimum room size: 17'-0" L X 13'-0" W. Minimum ceiling height 8'-6".]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA	CM:	--	--	--	1,820 lb	1: 480	3	120	NO		10,027							
		--	--	--	827 kg	2: --	--	--	DEPENDENT: YES									
X5900	6525	Radiographic Unit, 80 kW, 90/45 or 90/90 Table	F	F	F	F	--	--	F	--	--	--	B					
<p>This system is specifically designed to perform radiographic examinations in the Radiology Department. This units characteristics and components include a ceiling suspended 0.6/1.0 mm tube unit, 80kW micro-processor controlled X-ray generator, 90/45 or 90/90 table and wall mounted cassette holder. [No other source(s) identified with this description/specification. Recommended minimum room size: 17'-0" L x 13'-0" W. Minimum ceiling height 9'-6".]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60		BTUs / HR:							
EA	CM:	--	--	--	5,716 lb	1: 480	3	***	YES		10,027							
		--	--	--	2,595 kg	2: --	--	--	DEPENDENT: NO									
X6175	6525	Radiographic/Fluoro Unit, Angio, Biplane, Digital	F	F	F	F	--	--	F	--	--	--	B					
<p>This system is specifically designed to perform biplane radiographic/fluoroscopic examinations in the Special Procedures Department. On-line digital angio image processing will provide instant availability of images for review. This units characteristics and components include: 100 kW micro-processor controlled X-ray generators, C-arm and U arm with 9" multi-field Image Intensifier, integrated X-ray tube unit. The Digital Spot Imaging for both the AP and Lateral planes shall consist of a computer, keyboard with acquisition and viewing monitor and a slave monitor. The system shall be DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. It is recommended that the TV monitors be ceiling suspended. [Recommended minimum room size: 35'-0"L x 22'-6" W. Minimum ceiling height 9'-6.5". Price can vary based on specific clinical and site requirements.]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60		BTUs / HR:							
EA	CM:	--	--	--	17,455 lb	1: 480	3	271	YES		46,758							
		--	--	--	7,925 kg	2: --	--	--	DEPENDENT: NO									
X6185	6525	Rad/Fluoro Unit, Remote, 80 kW, 90/90 Table	F	F	F	F	--	--	E	--	--	--	B					
<p>This system is specifically designed to perform radiographic/fluoroscopic examinations in the Radiology Department. On-line digital image processing will provide instant availability of images for review via infrared remote control. This units characteristics and components include, 80 kW micro-processor controlled X-ray generator, remote-controlled 90/90 table with 15" multi-field Image Intensifier and integrated tube support. The Digital Spot Imaging consists of a computer, keyboard with acquisition, viewing monitor and a slave monitor. The system shall be DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. It is recommended that the TV monitors be ceiling suspended. [Recommended minimum room size: 20'-0" L X 18'-0" W. Minimum ceiling height 10'-10".]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 60		BTUs / HR:							
EA	CM:	--	--	--	5,898 lb	1: 480	3	181	NO		15,332							
		--	--	--	2,678 kg	2: --	--	--	DEPENDENT: YES									
X6190	6525	Radiographic/Fluoro Unit, Cardiac, 100 kW, Digital	F	F	F	F	--	--	F	--	--	--	B					
<p>This system is specifically designed to perform biplane radiographic/fluoroscopic examinations in the Cardiology Department. On-line digital cardiac image processing will provide instant availability of images for review. This units characteristics and components include 100 kW micro-processor controlled X-ray generators, C-arm and U arm with 9" multi-field Image Intensifier, integrated X-ray tube unit and cine camera. The Digital Imaging for both the AP and Lateral planes shall consists of a computer, keyboard with acquisition, viewing monitor, and slave monitor. The system shall be DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. It is recommended that the TV monitors be ceiling suspended. System to be procured with Cardiac Cath Lab computerized analysis/monitoring system. [Recommended minimum room size: 35'L x 22'-6" W. Minimum ceiling height 9'-6.5".]</p>																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ: 50/60		BTUs / HR:							
EA	CM:	--	--	--	10,736 lb	1: 480	3	271	YES		28,500							
		--	--	--	4,874 kg	2: --	--	--	DEPENDENT: NO									

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
X6195	6525	Injector, Angiographic	F	F	F	F	--	--	B	--	--	--	--	--	--	--	--	--	
<p>Angiographic injector. This unit is a specialized radiographic procedure that provides sharp, well-defined visual images of the vascular anatomy. The injector introduces a vision radiopaque fluid (contrast medium) into an artery or vein through a small catheter, making vessels contrast with their more radiolucent surrounding. The unit incorporates an electromechanical or pneumatic driven syringe to deliver the contrast medium. The syringe assemblies consist of an electric motor connected to a jackscrew that moves the syringe piston into or out of the syringe barrel. The unit is used in hospitals with radiographic procedures. Specify if unit is to be pedestal, ceiling, wall or table mounted when ordering. [Price for all models based on pedestal mounted unit.]</p>			UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
			EA	CM:	55	26	53	128 lb	1:	120	1	10	60	NO	--				
					140	66	135	58 kg	2:	--	--	--	NO	--					
X6196	6525	Injector, CT	F	F	F	F	--	--	B	--	--	--	--	--	--	--	--	--	
<p>CT injector. This unit is a specialized radiographic system that provides sharp, well-defined visual images of the vascular anatomy. The injector introduces a vision radiopaque fluid (contrast medium) into an artery or vein through a small catheter, making vessels contrast with their more radiolucent surrounding. The unit incorporates an electromechanical or pneumatically driven syringe to deliver the contrast medium. The syringe assemblies consist of an electric motor connected to a jackscrew that moves the syringe piston into or out of the syringe barrel. The unit is used in hospitals with radiographic procedures. The unit can be ceiling, wall, or remote stand mounted. [All models are priced for the remote stand mounted unit. All three manufacturers/vendors have available ceiling and wall mount accessories or options.]</p>			UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
			EA	CM:	55	26	53	125 lb	1:	120	1	3	50/60	NO	--				
					140	66	135	57 kg	2:	--	--	--	NO	--					
X6240	6525	Radiographic Unit, Computerized Tomography (CT)	F	F	F	F	--	--	F	--	--	--	--	--	--	--	--	B	
<p>The CT Scanner System is a noninvasive radiographic technique that involves the reconstruction of a tomographic plane of the body (four slices per revolution) from a large number of collected x-ray absorption measurements taken during a scan around the body's periphery. The CT System shall be a single gantry, whole body scanning system appropriate to support tertiary care facilities with an annual projected workload of less than 5,500 separate studies. System includes DICOM 3.0 or latest version software protocol. System to be procured with turnkey installation. [Prices are estimates only and will vary based on specific configurations. Turnkey installation can vary between \$50K to \$150K depending on the site. Minimum room size for Model 1 is 22'-0" L x 19'-0" W with a ceiling height of 8'-6". Model 2 recommended minimum room size is 19'-8" L x 16'-9" W with a ceiling height 9'. Model 3 minimum room size is 22' L x 12' W with a ceiling height of 9'.]</p>			UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
			EA	CM:	--	--	--	8,518 lb	1:	480	3	97	60	NO	36,542				
					--	--	--	3,868 kg	2:	--	--	--	YES	--					
X6245	6525	Rad Unit, Computerized Tomography, (CT), HP	F	F	F	F	--	--	F	--	--	--	--	--	--	--	--	B	
<p>The CT High Performance (HP) Scanner System is a noninvasive radiographic technique that involves the reconstruction of a tomographic plane of the body (a slice) from a large number of collected x-ray absorption measurements taken during a scan around the body's periphery. The CT System shall be a single gantry, whole body scanning system appropriate to support tertiary care facilities with an annual projected workload of 5,500 to 7,500 separate studies. System to be procured with turnkey installation. [Prices are estimates only and will vary based on specific configurations. Turnkey installation can vary between \$50K to \$150K depending on the site. Recommended minimum room size for Model 1 is 22' L x 19' W with a ceiling height of 8'-6". Model 2 minimum room size is 19'-8" by 16'-9". Model 3 minimum room size is 19' x 25' with a 9' ceiling height.]</p>			UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
			EA	CM:	--	--	--	8,546 lb	1:	480	3	110	60	NO	48,761				
					--	--	--	3,880 kg	2:	--	--	--	YES	--					
X6320	6525	Rad Unit, 60 kW, 90/45 or 90/90 Table, Wall Casset	F	F	F	F	--	--	F	--	--	--	--	--	--	--	--	B	
<p>This system is specifically designed to perform radiographic examinations in the Radiology Department. This units characteristics and components include a ceiling suspended 0.6/1.0 mm tube unit, 60kW micro-processor controlled x-ray generator, 90/45 or 90/90 table and wall mounted cassette holder. [Recommended minimum room size: 17'-0" L x 13'-0" W. Minimum ceiling height 9'-6". No other source(s) identified with this description/specification.]</p>			UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:					
			EA	CM:	--	--	--	3,581 lb	1:	480	3	137	0	YES	2,270				
					--	--	--	1,626 kg	2:	--	--	--	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X6340	6525	Rad/Fluoro Unit, 65 kW, 12" I.I., 90/15 Table	F	F	F	F	--	--	F	--	--	--	--	B				
<p>This system is specifically designed to perform radiographic/fluoroscopic examinations in the Radiology Department. The characteristics and components include a ceiling suspended 0.6/1.0 mm tube unit, 65 kW micro-processor controlled X-ray generator, 90/15 table with 12" multi-field Image Intensifier (I.I.) and bucky wall stand. The digital upgrade option will be required to make the system DICOM 3.0 or latest version, compatible, for easy linkage to filmless image management systems and review stations. It is recommended that the TV monitor be ceiling suspended. [Minimum room size for Model 1 is 16'-6" L X 12'-6" W and a minimum ceiling height of 9'-0" (recommended ceiling height is 9'-6"). Recommended room size for Model 2 is 19'-8" L x 13'-4" W and a minimum ceiling height of 9'-0". Recommended room size for Model 3 is 20'-0" L x 18'-0" W with a minimum of 9'-3" ceiling height.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	--	--	--	6,421 lb	1:	480	3	117	60	YES	14,441					
			--	--	--	2,915 kg	2:	400	3	140	NO							
X6400	6525	Rad/Fluoro Unit, 80 kW, 15" I.I., 90/90 Table, DIG	F	F	F	F	--	--	F	--	--	--	B					
<p>This system is specifically designed to perform radiographic/fluoroscopic examinations in the Radiology Department. On-line digital image processing will provide instant availability of images for review via infrared remote control. The characteristics and components include a ceiling suspended 0.6/1.0 mm tube unit, 80 kW micro-processor controlled X-ray generator, 90/90 table with 15" multi-field Image Intensifier (I.I.). The Digital Spot Imaging consists of a computer, keyboard with acquisition and viewing monitor, a slave monitor and a view pad integrating both RF and angio functions. The system shall be DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. It is recommended that the TV monitors be ceiling suspended. [Recommended room size for Model 1 is 19'-8" L x 13'-4" W and a minimum ceiling height of 9'-0". Minimum room size for Model 2 is 16'-6" L X 12'-6" W and a minimum ceiling height of 9'-0" (recommended ceiling height is 9'-6"). Model 3 recommended room size is 20'-0" L x 18'-0" W with a minimum ceiling height of 9'-3".]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	--	--	--	6,855 lb	1:	400	3	142	60	YES	82,340					
			--	--	--	3,113 kg	2:	480	3	117	NO							
X6450	6525-01-007-6058	Radiographic Unit, Dental, Wall Mounted, 15 mA	F	F	F	F	--	--	B	--	--	--	B					
<p>Dental radiographic unit. This is a wall mounted 7-15 mA intra-oral x-ray system. The unit performs a wide range of diagnostic surveys from caries detection to periodontal loss using long cone paralleling technique. This unit has 60 & 90 fixed kVp settings at 15 mA. This device is used in dental clinics.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	48	33	10	75 lb	1:	120	1	15	50/60	NO	--					
			122	84	25	34 kg	2:	--	--	--	NO		--					
X6500	6525-00-222-1340	Radiographic Unit, Dental, Panographic	F	F	F	F	--	--	F	--	--	--	B					
<p>Full mouth dental panographic radiographic unit. The unit includes teleradiographic capability, dental readout, and automatic exposure timer. Wheelchair patient compatible. [Price difference verified.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	92	48	45	520 lb	1:	120	1	20	50/60	NO	--					
			234	122	114	236 kg	2:	--	--	--	NO		--					
X6505	6525	Radiographic Unit, Dental, Panographic & Cephalo.	F	F	F	F	--	--	F	--	--	--	B					
<p>Dental panographic and Cephalometric radiographic unit. This is a radiographic system for routine intra-oral examination. This unit shall provide radiographs of the maxillary sinus and the entire jawbone including temporomandibular joints. The unit shall be complete with control panel and mounting hardware.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
EA		CM:	92	77	50	450 lb	1:	120	1	20	50/60	YES	--					
			234	196	127	205 kg	2:	208	1	10	NO		--					

JSN	NSN	NOMENCLATURE	CATEGORY:	A N A V I						UTILITIES					
				R	A	F	A	H		1	2	3	4	5	6
X6535	6525	Rad/Fluoro/Tomo Unit, Urologic, Digital		F	F	F	F	--		--	F	--	--	--	B
<p>This system is specifically designed to perform digital radiographic/fluoroscopic examinations in the Urology Department. The characteristics and components include a 80 kW micro-processor controlled x-ray generator, urological table with integrated tube stand, 16 inch multi-field Image Intensifier (I.I.), video chain, disc recorder and required accessories. The Digital Spot Imaging consists of a computer, keyboard with acquisition and viewing monitor and a slave monitor. The system shall be DICOM 3.0 compatible or latest version, for easy linkage to filmless image management systems and review stations. TV monitors shall be tower mounted or suspended from the ceiling. [Recommended minimum room size: 16'-6"L x 13'-0"W. Minimum ceiling height 9'-6".]</p>															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 50/60			BTUs / HR:			
EA		IN:	--	--	3,200 lb	1:	240	3	20	HZ SWITCH: YES			11,000		
		CM:	--	--	1,453 kg	2:	380	3	30	DEPENDENT: NO					
X6600	6525	Radiographic Unit, Dental, Wall Mounted, 7 mA		F	F	F	F	--		--	A	--	--	--	B
<p>Dental radiographic unit. Wall mounted, 7 mA, 70 kVp, 120 VAC, electronic remote exposure control unit. The unit shall have electronic timing with automatic reset timing capability and main power correction unit to adjust for line voltage fluctuations. Tube head shall be of the oil immersed, shield type with total inherent filtration of 1.5 mm AL , with a focal spot of 0.6. [Maximum reach of Model 2 is 85" from wall.]</p>															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60			BTUs / HR:			
EA		IN:	96	59	66 lb	1:	120	1	20	HZ SWITCH: NO			--		
		CM:	244	150	30 kg	2:	--	--	--	DEPENDENT: NO					
X6605	6525	Imager, Dental, Digital Image		C	C	C	C	--		--	A	--	--	--	--
<p>Dental imaging system. Used in intra oral x-ray imaging. Computer-aided to enhance image. Storage and printing capabilities for the image. System includes, CPU, CRT, active surface sensor, 120MB HD storage, thermal printer, mobile workstation, and is compatible with any intra oral x-ray system. [Price difference verified.]</p>															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60			BTUs / HR:			
EA		IN:	33	24	50 lb	1:	120	1	5	HZ SWITCH: NO			--		
		CM:	84	61	23 kg	2:	--	--	--	DEPENDENT: YES					
X6650	6525-00-612-7840	Safelight, Darkroom, Wall or Bench Mounted		A	A	A	A	--		--	A	--	--	--	--
<p>Darkroom safelight. This unit is suitable for direct or indirect lighting. This unit can be mounted on the wall, ceiling or counter top. The unit includes a 8 X 10 inch lens size, stainless steel trim, and gray baked enamel finish.</p>															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60			BTUs / HR:			
EA		IN:	16	12	8 lb	1:	120	1	--	HZ SWITCH: NO			--		
		CM:	41	30	4 kg	2:	--	--	--	DEPENDENT: NO					
X6660	6525-00-612-7825	Safelight, Darkroom, Ceiling Mounted		A	A	A	A	--		--	A	--	--	--	--
<p>Ceiling mounted darkroom safelight. This unit features a 5-1/2 inch diameter lens. It can be mounted on the wall (when ordered with the fully adjustable tilt bracket) or suspended from the ceiling. The unit has a gray baked enamel finish. It provides either direct or indirect illumination.</p>															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60			BTUs / HR:			
EA		IN:	--	6	5 lb	1:	120	1	--	HZ SWITCH: NO			--		
		CM:	--	15	3 kg	2:	--	--	--	DEPENDENT: NO					
X6800	6525-LL-000-0151	Rad/Fluoro Unit, 80 kW, 9" I.I., 90/45 Table, DIG		F	F	F	F	--		--	F	--	--	--	B
<p>This system is specifically designed to perform radiographic/fluoroscopic examinations in the Radiology Department. The characteristics and components include a ceiling suspended 0.6/1.0 mm tube unit, 80 kW micro-processor controlled X-ray generator, 90/45 table with 9" multi-field Image Intensifier (I.I.). The digital option is required to make the system DICOM 3.0 or latest version, compatible, for easy linkage to filmless image management systems and review stations. It is recommended that the TV monitor be ceiling suspended. System may include a video tape recorder (VTR). [Recommended room size for Model 1 is 19'-8" L x 13'-4" W and a minimum ceiling height of 9'-0". Minimum room size for Model 2 is 16'-6" L X 12'-6" W and a minimum ceiling height of 9'-0" (recommended ceiling height is 9'-6"). Model 3 recommended room size is 20'-0" L x 18'-0" W. Minimum ceiling height is 9'-3" (recommended ceiling height is 9'-6").]</p>															
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ: 60			BTUs / HR:			
EA		IN:	--	--	6,855 lb	1:	480	3	117	HZ SWITCH: YES			82,340		
		CM:	--	--	3,113 kg	2:	400	3	142	DEPENDENT: NO					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X7000	6525	Center, Mixing, Barium	A	A	A	A	--	D	A	--	--	--	--	--	--	--	--	
Barium mixing center for Radiology. The mixing container is made of glass or stainless steel with handles. The two speed model is available with or without a 60-second timer and has speeds of 18,000 or 22,000 RPM. The unit is equipped with a two piece vinyl/styrene lid and include either a 1.2L glass or 1L stainless steel container. The unit has surgical steel mixing blades and a snug fitting lid. The controls are two toggle switches mounted on the front. The unit is equipped with a heavy duty three foot (910 mm) cord and a 3-wire ground plug. The unit is a mixer for barium which is used in x-ray medical photography of the alimentary canal.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	15	7	8	10 lb	1:	120	1	3	60		NO					
		CM:	38	17	20	5 kg	2:	--	--	--	NO		--					
X7950	6525	Tank, Replenishing	E	E	E	E	--	--	--	--	--	--	--	--	--	--	--	
Replenishing tank. Molded in round or square polyethylene. Tank has dust cover, floating lid, grab handles and dispensers. It is used in x-ray department darkrooms for holding film processing chemicals. Quantity of two per darkroom required.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	29	19	19	-- lb	1:	--	--	--	--		NO					
		CM:	74	48	48	-- kg	2:	--	--	--	NO		--					
X8010	6525	Cutter, Block, Beam, Radiotherapy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Radiotherapy beam block cutter. The unit is used to create blanks to cast a shielding block for radiation therapy use. The system consists of a lighted work table for the positioning of an x-ray of the area to be treated. The treatment height is determined by adjusting a column; then a stylus is used to trace the area to be shielded while a heated wire cuts a foam block. [Price difference verified. Model 3 includes an auto-indexing feature that the other models do not.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	105	34	24	-- lb	1:	120	1	3	60		NO					
		CM:	267	86	61	-- kg	2:	--	--	--	NO		--					
X8011	6525	Dispenser, Lead Alloy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Lead alloy dispenser used to heat and dispense the lead alloy "CERROBLEND." This alloy is used to manufacture beam blocks used in radiation therapy. Three (3) gallon capacity.																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	18	15	15	37 lb	1:	120	1	7	60		NO					
		CM:	46	38	38	17 kg	2:	--	--	--	NO		--					
X8015	6525	Cutter, Compensator, Radiotherapy	C	C	C	C	--	--	A	--	--	--	--	--	--	--	--	
Radiotherapy compensator cutter. The system includes a three axis milling machine and a computer to obtain patient information and control the milling process. The system is used to prepare tissue compensation beam blocks for radiation therapy patients. [Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	52	36	35	250 lb	1:	120	1	10	60		NO					
		CM:	132	91	89	114 kg	2:	--	--	--	NO		--					
X8501	6525	Simulator, Therapy, X-Ray	F	F	F	F	--	--	F	--	--	--	--	--	--	--	B	
This system is specifically designed to simulate radiotherapy treatment plans in the Oncology Department. The characteristics and components include a precise mechanical system including digital fluoroscopic and radiographic x-ray capabilities and a flexible computer system. It shall have the capability to simulate any linear accelerator. Shall include a couch, collimator and accessories. Movements and scales shall be a match to other treatment machines to maintain their integrity of simulation for all cancer treatments. The system shall be DICOM RT compatible, for easy linkage to film-less image management systems and review stations. [Recommended minimum room size for Model 1 is 24'-2" L x 19'-6" W. Minimum ceiling height 8'-6". Model 2 recommended room size is 17'-1" L x 16'-2" W with a ceiling height of 10'-0" (Note:These dimensions are exclusive of the Control Room). Model 2 requires a dedicated 230V 10Amp circuit for the Flat Panel Imager. Price difference verified.]																		
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:							
EA		IN:	--	--	--	11,326 lb	1:	480	3	120	50/60		YES					
		CM:	--	--	--	5,142 kg	2:	120	1	50	NO		14,336					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X8700	6525	Accelerator, Linear, 18 MeV	F	F	F	F	--	B	F	D	--	--	A					
<p>This is a multi-energy linear accelerator. This unit is an isocentrally-mounted, Mega-voltage therapy machine which provides electron therapy in the range 4 to 18 MeV and x-ray therapy at 6 MV and 15 MV. The system consists of the following items: radio frequency (RF), power source (magnetron) and (RF) circuit (isolator, directional coupler, RF load and phase shifter). It also includes an accelerating structure and automatic frequency control system (AFC). The units applications are radiation therapy. [No other source(s) identified with this description/specification. Typical room size is 41'-6" L x 36'-0" W. Minimum ceiling height 10'-0". Special radiation shielding construction required.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	--	--	--	-- lb	1: 440	3	40	60	NO	--						
			--	--	--	-- kg	2: 240	3	45	DEPENDENT:	YES	--						
X8710	6525	Accelerator, Linear, 6 MeV	F	F	F	F	--	E	F	D	--	--						
<p>This system is a 6 MeV linear accelerator. The linear accelerator consists of four major components: a modulator, an electron gun, a radio frequency (RF) power source and an accelerator gun. The system emits a well-defined beam of uniformly intense radiation energy used to treat deep seated neoplasms and tumors. [No other source(s) identified with this description/specification. Recommended minimum room size: 37'-0" L x 33'-0" W. Minimum ceiling height 9'-6". Special radiation shielding required.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	103	48	140	20,555 lb	1: 208	3	181	50/60	YES	20,000						
			262	122	356	9,332 kg	2: 120	1	20	DEPENDENT:	NO	--						
X8740	6525	Accelerator, Linear, 6-10 MeV, Dual Energy	F	F	F	F	--	E	F	D	--	--	B					
<p>Dual energy linear accelerator used for external beam radiation therapy in treating cancer. X-ray energy range of 6-10 MV. Shall employ high energy modulated pulses of direct current with a peak power of a few megawatts to produce the microwave energy that accelerates the electron beam produced by the electron gun. Used in hospitals for cancer treatments. [No other source(s) identified with this description/specification. Recommended room size: 41'-6" L x 36'-0" W. Minimum ceiling height 10'-0". Special radiation shielding construction required.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	253	137	200	31,025 lb	1: 208	3	150	50/60	YES	27,313						
			643	348	508	14,086 kg	2: 120	1	20	DEPENDENT:	NO	--						
X8750	6525	Accelerator, Linear, 5-22 MeV, Dual Energy	F	F	F	F	--	B	D	A	D	--	B					
<p>Dual energy linear accelerator used for external beam radiation therapy in treating cancer. X-ray energy range of 5-22 MV. Shall employ high-energy modulated pulses of direct current (DC) electricity with a peak power of a few megawatts to produce the microwave energy that accelerates the electron produced by the electron gun. This unit is used in hospitals for cancer treatments. [No other source(s) identified with this description/specification. Recommended minimum room size is 41'-6" L x 36'-0" W. Minimum ceiling height 10'-0". Special radiation shielding construction required.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	--	--	--	31,025 lb	1: 208	3	150	50/60	YES	3,554						
			--	--	--	14,086 kg	2: 120	1	20	DEPENDENT:	NO	--						
X8800	6525-00-455-9947	Illuminator, Film, Dental, Portable	C	C	C	C	--	--	A	--	--	--	--					
<p>Portable dental film illuminator. The unit is made for desk or shelf viewing, and designed to handle oblong mounts including large 18-window dental mounts. It features a 4-3/4 X 13-3/4 inch viewing area of shatterproof, translucent Plexiglas. This system is used in dental offices to view dental x-rays. [Model 1 price includes 2X magnification. With 2X magnification, Model 3 price is \$122.00.]</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	8	17	6	8 lb	1: 120	1	1	60	NO	--						
			20	43	15	4 kg	2: --	--	--	DEPENDENT:	NO	--						
X9305	6525	Cabinet, Storage, Lead Lined	C	C	C	C	--	--	--	--	--	--	--					
<p>Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.</p>																		
UNIT OF ISSUE:		IN:	HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	BTUs / HR:						
EA		CM:	25	20	12	125 lb	1: --	--	--	0	NO	--						
			64	51	30	57 kg	2: --	--	--	DEPENDENT:	NO	--						

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X9310	6525	Cart, Transport, Radium	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Radium transport cart. The cart is a rugged, enameled-steel and equipped with two wheels, a caster and a long handle. It is designed for safety and convenience when transporting radioactive material between a permanent storage safe and the patient's bedside. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			42	20	20	14 lb	1:	--	--	--	NO	NO	--					
			107	51	51	7 kg	2:	--	--	--	NO	NO	--					
X9315	6525	Safe, Storage, Radium	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Radium storage safe. The unit assures optimum shielding against exposure to radioisotopes. It is made of steel (CRS) with a minimum of 2 inches of lead lining, has a door key-lock and is fire-proof.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			19	18	17	1,150 lb	1:	--	--	--	0	NO	--					
			48	46	43	522 kg	2:	--	--	--	NO	NO	--					
X9320	6525	Shield, L Block, Radium Handling	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
L-block solid lead shield. 5 cm thick shield to protect the head and torso from radiation while working with radium and other implant seeds. Provides tilted 5 cm thick leaded glass window which is at least 10 cm high by 20 cm wide with a density of 6.2 gm per cubic cm. Overall size is 22 inches high, 14 inches wide and 16.5 inches deep. Designed to sit on a work table in front of a radium safe to provide protection while working with the seeds.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			29	20	18	550 lb	1:	--	--	--	0	NO	--					
			74	51	46	250 kg	2:	--	--	--	NO	NO	--					
X9340	6525	Phantom, CT, Head	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
CT head phantom for 10 cm probe. Used for testing of computed tomography devices. Must meet the BRH (21 CFR 1020.33) "Computed Tomography Test Phantoms and Measurement Protocol" requirements. Provides measurement of dose at nine locations in a plane parallel to the slice plane. Eight acrylic rods provided to fill unused ion chamber bores. Available in 5 or 17 hole configuration and alternate 14 cm probe configuration. Specify requirement at time of procurement. [Model 1 has a carrying case #20V60 with a price of \$475.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			6	--	7	8 lb	1:	--	--	--	NO	NO	--					
			16	--	18	4 kg	2:	--	--	--	NO	NO	--					
X9345	6525	Phantom, CT, Body	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
CT body phantom for 10 cm probe. Used for the testing of computed tomography devices. Must meet the BRH (21 CFR 1020.33) "Computed Tomography Test Phantoms and Measurement Protocol" requirements. Provides measurement of dose at nine locations in a plane parallel to the slice plane. Eight acrylic rods provided to fill unused ion chamber bores. Available in 5 or 17 hole configuration and also for 14 cm probe option. Specify requirement at time of procurement.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			6	--	13	-- lb	1:	--	--	--	NO	NO	--					
			16	--	33	-- kg	2:	--	--	--	NO	NO	--					
X9346	6525	Phantom, CT Performance	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Meets guidelines in AAPM Report #1 For Performance Evaluation and Quality Assurance of CT Scanners. Consists of an 8.5" diameter acrylic tank that contains a beam width insert, a spatial resolution and linespread block, a high-contrast insert and a means for inserting alignment pins and/or TLD holders. Measures nine separate performance parameters: routine standardization of alignment, beam width, spatial uniformity, linearity/contrast, spatial resolution, linespread, noise, size independence and adsorbed dose. All components of the phantom are housed in a compact, transparent tank which holds the system together in the correct orientation.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	HZ SWITCH:	DEPENDENT:	BTUs / HR:					
			9	--	16	18 lb	1:	--	--	--	0	NO	--					
			23	--	41	9 kg	2:	--	--	--	NO	NO	--					

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES											
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6
X9500	6525	System, Uptake, Thyroid, Mobile	C	C	C	C	--	--	B	--	--	--	--	--	--	--	--	--
Mobile thyroid uptake system. The characteristics and components include; amplifier tube assembly and base, uptake stand and collimated shield. This is a mobile unit with arm medical stand, 2 inch probe with I.A.E.A. flat field collimator and thyroid positioner, neck phantom, and analyzer/scaler/timer with automatic background subtract and automatic % readout.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	50/60	HZ SWITCH:	YES	BTUs / HR:	NO	--	--	--
			64	163	32	44	450 lb	1:	120	1	6	DEPENDENT:	NO	--				
					81	112	205 kg	2:	--	--	--							
X9705	6525	Stretcher, MRI Compatible	F	F	F	F	--	--	--	--	--	--	--	--	--	--	--	--
MRI compatible stretcher. This unit is used to prepare and transport patients in a magnetic resonance imaging area. It is a non ferrous, fixed height unit and is equipped with four locking casters and a MRI compatible pad.																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	NO	--	--	--
			33	84	73	25	75 lb	1:	--	--	--	DEPENDENT:	NO	--				
					185	64	34 kg	2:	--	--	--							
X9805	6530	Stand, Injection, Nuclear Medicine	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
An injection stand designed for arm positioning for radionuclide injections. The arm rest holds the patient's arm firmly in place. A utility tray sits adjacent to the armrest to hold supplies and includes a lead-lined multi syringe holder. The stand height is adjustable approximately from 29" to 44." Casters allow the stand to be rolled into position or out of the way for storage. It is structurally balanced so that it won't tip over. [No other source(s) identified with this description/specification.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	0	HZ SWITCH:	NO	BTUs / HR:	NO	--	--	--
			44	112	28	28	210 lb	1:	--	--	--	DEPENDENT:	NO	--				
					71	71	96 kg	2:	--	--	--							
X9810	6525	System, Camera, Gamma, Mobile	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
Mobile gamma camera system. This unit is a compact scintillation camera system. The characteristics and components include a detector, electronics and a console mounted on a mobile base. The console contains all operating controls and the image display. This unit is used for bedside evaluation of critically ill patients. [No other source found for this item. ADAC Laboratories, now part of Philips Medical, discontinued the TransCam model. They were the last of the major manufacturers to make a mobile gamma camera.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	NO	--	--	--
			50	127	30	46	425 lb	1:	115	1	10	DEPENDENT:	NO	--				
					76	117	193 kg	2:	--	--	--							
X9825	6525	Nuclear Imaging System	F	F	F	F	--	--	--	--	--	--	--	--	--	--	--	--
A system that combines the functionality of PET and SPECT with the anatomical landmarks of CT to perform Functional Anatomic Mapping. [Minimum room dimensions are 15'-0" x 16'-6" with a ceiling height of 7'-6". No other source provides a unit that combines PET and SPECT with CT. Philips and CTI Molecular Imaging have units that combine PET and CT.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	60	HZ SWITCH:	NO	BTUs / HR:	NO	9,556	--	--
			--	--	--	8,503 lb	1:	208	3	20	DEPENDENT:	NO	9,556					
					--	3,861 kg	2:	--	--	--								
X9830	6625	Scanner, Nuclear, SPECT, Dual Head	C	C	C	C	--	--	--	--	--	--	--	--	--	--	--	--
The system shall be a single plane or variable angle dual detector emission system, designed for fast data acquisition and high patient throughput for Single Photo Emission Computed Tomography (SPECT), whole body and general purpose nuclear medicine procedures. It shall be designed to image at any energy range for any procedures. The unit detects and counts photons emanating from radiopharmaceuticals. Collimators available to suit full range applications. The system shall be DICOM 3.0 or latest version, compatible, for easy linkage to filmless image management systems and review stations. [Recommended room size for Model 1 is 18'-0" L x 12'-0" W. Minimum room size for model 2 is 14'-0" L x 11'-4" W. Minimum room size for Model 3 is 18'-6" L x 14'-6" W and a ceiling height of 7'-6" (Recommended ceiling height is 8'-0"). Philips Medical Systems also makes several types of gamma cameras.]																		
UNIT OF ISSUE:		EA	HEIGHT IN:	WIDTH CM:	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	50/60	HZ SWITCH:	YES	BTUs / HR:	NO	6,800	--	--
			76	194	66	62	4,791 lb	1:	220	1	30	DEPENDENT:	NO	6,800				
					168	157	2,176 kg	2:	--	--	--							

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES							
			A	N	A	V	I	1	2	3	4	5	6
X9835	6625	Counter, Gamma, Multichannel	C	C	C	C	--	--	A	--	--	--	--
Multi-channel gamma counter. This unit measures trace quantities (10-9 to 10-12 gm) of many diagnostically significant substances found in patient samples (serum, urine or other body fluids). Substances routinely measured by radio-assay techniques include hormones, vitamins, drugs, cancer antigen, and other proteins. Characteristics and components include personal computer data acquisition and analysis system (PC-DAAS); disk store, constant quanta detector, built-in dedicated computer. This system is used in clinical laboratory. [Model 1 price can vary from \$16k for a 10 well detector to \$55K for a 50 well detector. Price shown is for the most common 20 well detector.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	28	28	32	400 lb	1:	115	1	3	60		--
		CM:	71	71	81	182 kg	2:	--	--	--	YES		
DEPENDENT: YES													
X9836	6625	Counter, Gamma, Multichannel	C	C	C	C	--	--	A	--	--	--	--
Multi-channel gamma counter. This unit measures trace quantities (10-9 to 10-12 gm) of many diagnostically significant substances found in patient samples (serum, urine or other body fluids). Substances routinely measured by radio-assay techniques include hormones, vitamins, drugs, cancer antigen, and other proteins. Characteristics and components include personal computer data acquisition and analysis system (PC-DAAS); disk store, constant quanta detector, built-in dedicated computer. This system is used in radiation safety department. Unit to be supplied with appropriate shields and collimators for high level whole body counting.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	28	27	33	540 lb	1:	120	1	3	60		--
		CM:	71	69	84	246 kg	2:	--	--	--	YES		
DEPENDENT: NO													
X9840	6525	Computer, Clinical, Nuclear Medicine	C	C	C	C	--	--	F	--	--	--	D
Nuclear medicine clinical computer. The computer is a complete system for managing the nuclear medicine department. The unit is used to acquire images from multiple equipment systems and process with a single computer system for enhancement and manipulation. Accessories and components include laser printers, remote consoles and dry lasers. [Price difference verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	21	24	22	75 lb	1:	120	1	15	60		3,800
		CM:	53	61	56	34 kg	2:	--	--	--	YES		
DEPENDENT: YES													
X9841	7120	Computer, Radio Therapy, Record/Verify	C	C	C	C	--	--	B	--	--	--	D
This is a treatment management system that has been specifically designed for the Oncology Department. Its unique features provide the tools for the department to handle standard and exceptional clinical routines, optimizing machine and staff resources. It shall enable management to track and report patient prescriptions and treatments, machine treatment schedules and billing charges for work. Interface kits must be procured for each LINAC system. The system shall be DICOM 3.0 or latest version compatible, for easy linkage to filmless image management systems and review stations. [The prices shown are representative only. Individual system configuration at time of purchase will impact the price. The amount of hardware a department needs depends upon its electronic information processes and how it plans to use the system. These systems will have better response times if they use a dedicated server.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	--	--	--	-- lb	1:	120	1	10	50/60		--
		CM:	--	--	--	-- kg	2:	--	--	--	NO		
DEPENDENT: NO													
X9842	7120	Computer, Rad Therapy Treatment Planning	C	C	C	C	--	--	A	--	--	--	--
The treatment planning computer must provide a total system three dimensional configuration that provides enhanced visualization of the radiation beam target volume, patient anatomy, treatment beam data and dose distribution. The system must be capable of brachytherapy treatment planning, using both linear and seed source. As a minimum shall include the optional CT/MR interface via Ethernet, a second remote work station and graphic work station. [The prices shown should be considered rough budget figures only. The configuration of these systems may vary significantly based on clinical and hardware requirements.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:	BTUs / HR:			
EA		IN:	--	--	--	-- lb	1:	120	1	10	50/60		--
		CM:	--	--	--	-- kg	2:	--	--	--	NO		
DEPENDENT: NO													

JSN	NSN	NOMENCLATURE	CATEGORY:			UTILITIES							
			A	N	A	V	I	1	2	3	4	5	6
X9845	6625	Monitor, Radiation, Area	C	C	C	C	--	--	A	--	--	--	--
Area radiation monitor. This unit has a 3 decade logarithmic meter ranging from 0.1 mR/hr to 100 mR/hr. When the radiation dose rate exceeds the predetermined alarm level, a loud two-tone alarm and a flashing red light are activated. The detector and circuitry can withstand high levels of radiation. The unit assures that persons working in and around radiation areas are adequately alerted to hazardous levels of gamma- and x-rays.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		IN: 10 CM: 25	10 25	5 13	7 lb 4 kg	1: 120 2: --	1 --	1 --	60 NO	NO --			
X9847	6525	Monitor, Radiation, Portable	C	C	C	C	--	--	A	--	--	--	--
Portable radiation monitor used in the quality assurance testing of radiology and radiation therapy equipment. Unit to include automatic barometric pressure compensation and RS-232 digital output. Shall be battery powered and shall use air equivalent ion chambers. Unit measures exposure rate, exposure, pulse exposure and pulse duration. Monitor to have a range of 0.01 mR per hour to 200 kR per hour. Instrument should be purchased with appropriate ion chambers.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		IN: 10 CM: 25	13 33	9 23	15 lb 12 kg	1: -- 2: --	-- --	-- --	0 NO	NO --			
X9850	6525	System, Thermoluminescence Dosimetry	C	C	C	C	--	--	B	--	--	--	--
Thermoluminescence measuring system. This unit can be used for personnel dosimetry, environmental surveys, beam profiling or reactor site monitoring. The system processes, reads and records results. [Price difference verified.]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		IN: 12 CM: 30	22 57	18 45	88 lb 40 kg	1: 120 2: --	1 --	3 --	60 NO	NO --			
X9870	6625	Densitometer, Film, Radiographic	C	C	C	C	--	--	A	--	--	--	--
Radiographic film densitometer. This unit is a precision instrument that quickly measures the optical density of film to an accuracy of +/- 0.02 optical density. The unit provides the capability to automatically transfer the data to a computer for storage and retrieval. This unit is used in hospitals and health clinics for X-ray quality control.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		IN: 6 CM: 15	11 28	15 38	9 lb 4 kg	1: 120 2: --	1 --	1 --	60 NO	YES --			
X9875	6525	Sensitometer	C	C	C	C	--	--	A	--	--	--	--
Unit provides consistent and calibrated step wedge images on x-ray film. The film is processed in the processor being tested and is then read on a densitometer for results. Results are checked against the standard and prior period readings to determine if the processor is functioning properly.													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		IN: 4 CM: 10	7 18	9 23	3 lb 2 kg	1: 120 2: --	1 --	2 --	60 NO	YES --			
X9900	6525	MRI System, Open	F	F	F	F	--	J	F	--	--	--	--
Open Magnetic Resonance Imaging (MRI) System that uses magnetic fields in the range of 0.2 to 0.5 tesla and radio-frequency (RF) radiation to translate hydrogen nuclei distribution in body tissues into computer-generated images of anatomic structures. MRI is primarily used to identify diseases of the central nervous system, brain, and spine and to detect musculoskeletal disorders. System includes DICOM 3.0 or latest version software protocol. System to be procured with turnkey installation. [Recommended minimum room size is approximately 425 sq. ft. Recommended ceiling height is 9'-0".]													
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS PHASE AMPS			HZ:		BTUs / HR:		
EA		IN: 86 CM: 218	124 315	124 315	70,000 lb 31,780 kg	1: 480 2: 240	3 1	79 79	60 NO	YES 38,251			

JSN	NSN	NOMENCLATURE	CATEGORY:				UTILITIES												
			A	N	A	V	I	R	A	F	A	H	1	2	3	4	5	6	
X9905	6525	MRI System, Super Conductive	F	F	F	F	--	--	F	--	--	--	--	H					
<p>Magnetic Resonance Imaging Units (MRI) use Superconducting strong magnetic fields (between 0.5 and 1.5 tesla) and radio-frequency (RF) radiation to translate hydrogen nuclei distribution in body tissues into computer-generated images of anatomic structures. MRI is primarily used to identify diseases of the central nervous system, brain, and spine and to detect musculoskeletal disorders. It includes DICOM 3.0 or latest version software protocol. The unit is to be procured with turnkey installation. [Recommended minimum room size: 50'-0" L x 30'-0" W. Minimum ceiling height 10'-8" Note: Room design should insure the 5 gauss line is contained within the magnet room and does not extend into the operator console area. Model 3 requires only 325 sq. ft. of floor space.]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	--	--	--	28,380 lb	1:	480	3	121	YES		110,656						
		CM:	--	--	--	12,885 kg	2:	--	--	--	YES								
X9910	6525	Wheelchair, MRI	C	C	C	C	--	--	--	--	--	--	--	--					
<p>MRI wheelchair. This unit accommodates any size patient, with 19" wide seat, yet it is compact enough to slip through narrow doorways and over thresholds. The chair easily locks for stable positioning and patient transfer and features a non-corrosive, lightweight but strong tubular frame. Non-magnetic, non-ferrous wheelchair is for use in the MRI environment. [Uninterruptable Power Supply, Approximately 2200VA/1600W, Rack Mount with extendable Run Time. Unit must incorporate hot user swappable batteries and must have an overload indicator, replace battery indicator, audible alarm, automatic voltage regulation and include Smart Slot card and software. It must use RS232 DB-9 interface for communication. NEMA L5-30P power connector, and (8) NEMA 5-15R outlets. [This item is a component of a Server/Networking system to be used in conjunction with JSN A0912. No other source(s) identified with this description/specification]]</p>																			
UNIT OF ISSUE:		HEIGHT	WIDTH	DEPTH	WEIGHT	VOLTS	PHASE	AMPS	HZ:		HZ SWITCH:		BTUs / HR:						
EA		IN:	20	26	28	37 lb	1:	--	--	--	NO		--						
		CM:	51	66	71	17 kg	2:	--	--	--	NO		--						

NOMENCLATURE	PAGE
A	
Accelerator, Linear, 18 MeV	385
Accelerator, Linear, 5-22 MeV, Dual Energy	385
Accelerator, Linear, 6 MeV	385
Accelerator, Linear, 6-10 MeV, Dual Energy	385
Adapter Panel With Couplers, Blue, 6 Port, SM/MM	21
Adapter Panel With Couplers, Yellow, 6 Port, SM/MM	21
Adapter, Processor, Film, Daylight	371
Altar	147
Amalgamator, Dental	72
Analgesia Unit, Inhalation, Central Gases/Vacuum	55
Analgesia Unit, Inhalation, Central Vacuum Only	55
Analyzer, Auditory, Evoked Potential	240
Analyzer, BUN, Discrete	215
Analyzer, Blood Chem, Auto, 60 Samples/Hour	213
Analyzer, Blood Gas	221
Analyzer, Chemistry, Drug Screening	214
Analyzer, Chemistry, Multichannel	216
Analyzer, Chemistry, Stat	214
Analyzer, Chemistry, Stat, High Capacity	214
Analyzer, Coagulation, Automatic	216
Analyzer, Glucose	218
Analyzer, Hematology, Differential, Automatic	217
Analyzer, Hydrogen, Breath	314
Analyzer, Lead	221
Analyzer, Pulmonary Function, w/Computer	246
Analyzer, Urine, Advanced	213
Analyzer, Urine, Basic	213
Analyzer, pH/Blood Gas	221
Anesthesia Apparatus, 3 Gas	245
Anesthesia/Ventilator System, Veterinary	366
Apparatus, Culture, Anaerobic	228
Ark w/External Light	147
Armed Forces Vision Tester	279
Armoire, Resuscitation	157
Arthroscope, Dental, TMJ	71
Artwork, Decorative, With Frame	37
Artwork, Mural, Wall	37
Aspirator, Low Pressure/High Volume, Chest/Abdomen	315
Aspirator, Low Pressure/Low Volume, Surgical	315
Aspirator, Uterine, Mobile	315
Aspirator/Pressure Unit, General Purpose	315
Assembly Line, Tray, Custom	206
Assembly, Boilout/Curing, Double	58
Audiometer, Diagnostic	240
Audiometer, Diagnostic, Middle Ear, Impedance	240
Audiometer, Screening, Group	239
Autorefractor, Ophthalmic	276
B	
Baker, Waffle, Dual Plate	175
Balance, Analytical, Laboratory/Pharmacy	250
Balance, Electronic, Laboratory/Pharmacy	250
Balance, Mechanical Torsion, Enclosed	251
Balance, Prescription, 10 mg Sensitivity	250
Balance, Small Animal	362
Balance, Trip, 2 Beam, 2kg Capacity, .1gm Division	251
Bar, Chinning, Wall Mount	170
Bar, Towel, 1" Diameter, SS, Surface Mntd, Psych	35
Bar, Towel, 1" Diameter, SS, Surface Mounted	35
Bar, Weightlifting	174
Basket, Wastepaper, Executive, Wood, 15 x 13 x 13	162
Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	163
Basket, Wastepaper, Round, Metal	162

NOMENCLATURE	PAGE
Basket, Wastepaper, Step-On	162
Bassinet, w/Cart	261
Bath, Cryoprecipitate Thawing (+4 Deg C)	215
Bath, Hydrotherapy, Body, 34x106x78	295
Bath, Hydrotherapy, Burn, w/Lift	296
Bath, Hydrotherapy, Sitting	295
Bath, Hydrotherapy, w/Elevating Tub	296
Bath, Paraffin, Hand/Foot	298
Bath, Water, Impression	70
Bath, Water, Refrigerated, Circulating	230
Bath, Water, Serology, Electric	230
Bath, Water, Tissue Processing	230
Bath/Shower, Nursing Table, Freestanding	327
Bathtub, Patient	321
Battery Pack, Extended for use with UPS (A0911)	22
Beam Analyzer, Radiation Therapy	349
Bed, Air-Fluidized	261
Bed, Birthing, Electric	283
Bed, Bunk, Watchroom	165
Bed, Hi-Low, Manual	283
Bed, Non-medical, Single	165
Bed, Patient, Electric	283
Bed, Patient, Electric, Special Care	283
Bed, Platform, Without Visible Legs, Psychiatric	284
Bench, Decline	170
Bench, Locker Room, Floor Mounted	30
Bench, Locker Room, Portable	30
Bench, Loom	350
Bench, Stall, Shower, Built In	31
Bench, Weightlifting, Incline Press, Fixed Height	170
Bench, Weightlifting, Supine	169
Bench, Weightlifting, Utility, Adjustable	169
Bench, Woodwork, 4 Vises	351
Bench, Woodwork, Drawers, Shelves, 32x72x30	350
Bench, Woodworking, 2 Cabinets, 31x36x21	353
Bench, Woodworking, Locker Base, 33 x 120 x 30	354
Bench, Work, Metal Top	351
Bench, Work, With 4 Drawers, 1 Cabinet, 2 Shelves	351
Bench, Work, Wood Top, 1 Drawer, 1 Shelf, 34x72x30	351
Bench, Work, Wood Top, Drawer, 31x96x36	351
Bench, Work, Wood Top, With 30"Frame, 34x96x30	351
Benchtop, Plastic, Laminated	366
Bilirubinometer	230
Bin, Ingredient, Mobile, 150 Lb. Capacity	175
Bin, Ingredient, Mobile, 250 Lb. Capacity	176
Bin, Loading, Film	368
Bin, Mail Sorting, Table Mounted	150
Bin, Plaster, 3 Compartment	72
Bin, Receptacles, Waste, 37x12x22	367
Bio-Clean Unit, Duo-Flow	366
Biofeedback Analysis System	301
Blast Gate, Vacuum System	60
Blender, Heavy Duty, 1 Gal, CRS Bowl	176
Blender, Heavy Duty, 1/2 Gal, CRS Bowl	176
Blinds, Window, Mini w/Brackets	39
Blowgun, Air, Lever Type, With 10 Foot Hose	74
Board, Abdominal Exercise	169
Board, Bulletin, 48 x 48	167
Board, Bulletin, Wood Framed, 36 x 24	167
Board, Copy, Electronic Facsimile	256
Board, Scheduling, Magnetic, 36 X 48	167
Bookcase, 3 Shelf	150
Bookcase, Executive, 3 Shelf, Wood	150
Bookcase, Open, 5 Shelf	150

NOMENCLATURE	PAGE
Bookstack, Single	151
Booth, Audio, Dbl Wall, Definitive Test, 1 Person	241
Booth, Audio, Double Wall, 6 Person	241
Booth, Audio, Double Wall, Suite	241
Booth, Audio, Single Wall, 1 Person	241
Booth, Treatment, Ultraviolet	301
Booth, Treatment, Ultraviolet, Hand-Foot	301
Bracket, Support	77
Bracket, Television, Ceiling Mounted	36
Bracket, Television, Wall Backing	36
Bracket, Television, Wall Mounted, w/Adjust Arm	35
Breader, Mobile, Manual	176
Breader, Table Mounted, Automatic	176
Breast Biopsy System, Stereotactic	379
Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	180
Brewer, Coffee, Auto, Elect, 3 Burner, Side/Side	180
Broiler, Char-Broiler, 1 Grid	177
Broiler, Char-Broiler, 2 Grid	177
Broiler, Infrared, Electric, Double	177
Broiler, Infrared, Gas, Dual	176
Bronchoscope, Fiberoptic, Adult	308
Bronchoscope, Fiberoptic, Adult, Large Channel	307
Bronchoscope, Fiberoptic, Adult, Slim Casing	307
Bronchoscope, Fiberoptic, Examination Only	306
Bronchoscope, Fiberoptic, Pediatric	307
Bronchoscope, Fiberoptic, Therapeutic	307
Bronchoscope, Video, Therapeutic	307
Bucket, Mop, With Wringer, 26 Quart	156
Bumper, Dock	38
Bumper, Wall, Bed	36
Burnisher, Floor	166
C	
Cabinet, Base, 1 Door	367
Cabinet, Base, 1-2 Door, 37x20x19	75
Cabinet, Base, 2 Door, 36x36x24	57
Cabinet, Base, 4 Drawer, 32x20x18	56
Cabinet, Base, 4 Drawer, 36x18x24	56
Cabinet, Base, 5 Drawer	75
Cabinet, Base, 7 Drawers, 37Hx20Wx18D	78
Cabinet, Base, Bin Drawer, 2 Drawer, 36x24x24	56
Cabinet, Base, Casting Machine, 36x24x24	57
Cabinet, Base, Door, 36x24x24	57
Cabinet, Base, Drop Door, Door, 36x24x24	57
Cabinet, Base, Film Identifier	368
Cabinet, Base, Sink, Angle Corner, 36x53x24	56
Cabinet, Base, Sink, Wall Hung, 2 Doors, 18x27x17	76
Cabinet, Base, Wall Hung, 2 Doors	76
Cabinet, Base, Wall Hung, 3 Drawers, 22x20x18	76
Cabinet, Base, Wall Hung, 4 Drawers	76
Cabinet, Base, With (3) 5 Inch Compartments	367
Cabinet, Base, With Sink, 1 Door, 37x20x18	75
Cabinet, Base, With Sink, 2 Doors	76
Cabinet, Bedside, Door, Drawer	154
Cabinet, Bio Safety Class II/B2, 6 ft, Bench Top	226
Cabinet, Bio Safety, Class II/A, Bench, Vert, 4ft	224
Cabinet, Bio Safety, Class II/A, F/S, Vert, 4ft	224
Cabinet, Bio Safety, Class II/B1, F/S, Vert, 4ft	225
Cabinet, Bio Safety, Class II/B1, F/S, Vert, 6ft	225
Cabinet, Bio Safety, Class II/B2, Bench Top, 4ft	225
Cabinet, Bio Safety, Class II/B2, F/S, 4ft	225
Cabinet, Bio Safety, Class III	225
Cabinet, Blanket, Fire, Wall Mounted	36
Cabinet, Blast Cleaning, F/S	73
Cabinet, Catheter Storage	264

NOMENCLATURE	PAGE
Cabinet, Control, Nitrogen	28
Cabinet, Desk, Wall Hung, 1-2 Drawers, 6.5x20x18	76
Cabinet, Desk, Wall Hung, 2 Drawers, 6.5x27x17	76
Cabinet, Distribution, Mail	150
Cabinet, Exam Room, 1 Door, 1 Drawer	263
Cabinet, F/S, 5 Shelf, 1 DO, Sloping Top, 92x24x13	49
Cabinet, F/S, 5 Shelf, 1 DO, Sloping Top, 95x24x16	50
Cabinet, Filing, Cardex	155
Cabinet, Filing, Film, 5 Shelves 88x48x18	368
Cabinet, Filing, Film, 5 Shelves With Doors	368
Cabinet, Filing, Film, 5 Shelves, 88x36x18	368
Cabinet, Filing, Film, Modular, Auto, 92x84x18	369
Cabinet, Filing, Full Height, 4-5 Drawer	155
Cabinet, Filing, Half Height, 2 Drawer	155
Cabinet, Filing, Lateral, Full Height, 5 Drawer	155
Cabinet, Filing, Lateral, Half Height	155
Cabinet, Filing, Security, Full Height	155
Cabinet, Floor Stand, 5 SH, 2 SGDO, ST, 95x36x16	55
Cabinet, Floor Stand, 5 SH, 2 SGDO, ST, 98x48x22	55
Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 92"x30"	54
Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 92"x36"	54
Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 92x48x13	54
Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95"x36"	54
Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95x30x16	54
Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95x48x16	54
Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 98"x48"	55
Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 98x30x22	54
Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 98x36x22	55
Cabinet, Floor Standing, 5 SH, 2 SDO, ST, 92"x36"	55
Cabinet, Food, Heated, Mbl, 2 Compartment, Counter Ht	203
Cabinet, Heated, Food, Mobile, Large	177
Cabinet, Heated, Service Pan/Tray, Mobile	195
Cabinet, Hot/Cold, Food, Mobile, Counter Height	178
Cabinet, Ice Cream, Mobile, Self-Service	195
Cabinet, Ice Cream, Mobile, Storage	195
Cabinet, Instrument	263
Cabinet, Instrument, CRS, 2 Glass Door, 6 Shelf	263
Cabinet, Instrument, Lens Measuring	274
Cabinet, Keys	156
Cabinet, Medicine	31
Cabinet, Microscope Slide	236
Cabinet, Mobile, Storage/Assistant, Dental	64
Cabinet, Narcotic, U/C or Ctr, With Safe, 24x24x12	31
Cabinet, Open, W/H, 2 Shelf, Sloping Top, 38x24x13	47
Cabinet, Open, W/H, 2 Shelf, Sloping Top, 38x36x13	47
Cabinet, Open, W/H, 2 Shelf, Sloping Top, 41x36x16	47
Cabinet, Open, W/H, 2 Shelf, Sloping Top, 41x48x16	47
Cabinet, Paraffin Block	236
Cabinet, Pastry, Mobile, Large	177
Cabinet, Pastry, Mobile, Medium	177
Cabinet, Pedestal Base, W/Dust Collector, 25x42x20	56
Cabinet, Proofing, Counter Top	178
Cabinet, Proofing, Mobile	178
Cabinet, Refrigerated, Mobile	178
Cabinet, Sink, U/C/B, 1 Door, 36x18x22	42
Cabinet, Sink, U/C/B, 1 Door, 36x24x22	43
Cabinet, Sink, U/C/B, 2 Door, 30" W	44
Cabinet, Sink, U/C/B, 2 Door, 36x36x22	45
Cabinet, Sink, U/C/B, 2 Door, 36x48x22	46
Cabinet, Specimen, Pass Thru, CRS	219
Cabinet, Storage, 2 Door, 5 Shelf	156
Cabinet, Storage, Acid, Floor Standing, Shelves	256
Cabinet, Storage, Acid, Freestanding	257
Cabinet, Storage, Acid, Undercounter	256

NOMENCLATURE	PAGE	NOMENCLATURE	PAGE
Cabinet, Storage, Data Processing	156	Cabinet, Wall Hung, 2 Sliding Doors, 23Hx38Wx8D	77
Cabinet, Storage, Electric Parts	356	Cabinet, Wall Hung, 2 Sliding Doors, 30Hx38Wx14D	77
Cabinet, Storage, Flammable, Freestanding	257	Cabinet, Wall Hung, 2 Sliding Doors, 30x36x12	75
Cabinet, Storage, Hanging Scopes	264	Cabinet, Wall Hung, 4 Compartments, 22x24x16	367
Cabinet, Storage, Lead Lined	385	Cabinet, Wall Hung, With (3) 5 Inch Compartments	367
Cabinet, Storage, Photographic Slides	156	Cabinet, Wardrobe, 1 Door, 84x15x22	39
Cabinet, Storage, Safety, Built-In, Vented	257	Cabinet, Wardrobe, 1 Door, 84x24x22	40
Cabinet, Storage, Tool	351	Cabinet, Warming, F/S, 1 Heated Compartment, Elect	263
Cabinet, Storage, Tool, F/Mounted	352	Cabinet, Warming, F/S, 2 Heated Compartment, Elect	264
Cabinet, Storage, Video Tape	155	Cabinet, Warming, Pass-Thru, CRS	178
Cabinet, Television / Video Recorder	156	Cabinet, w/Sink, O/H Cab, Free Standing, 48"Wx24"D	107
Cabinet, Tool, Floor Standing, 84x60x22	356	Cabinet, w/Sink, O/H Cab, Free Standing, 60"Wx24"D	107
Cabinet, Tool, Mobile, With Mechanics Tool Chest	356	Cabinet/Server, Heated, 2 Drawer/Compartment	203
Cabinet, Transfer, Cassette, 4 Door, 2 Compartment	370	Cabinet/Server, Heated, Mbl, 3 Drawer/Compartment	203
Cabinet, Treatment, 2 Door, 2 Drawer, Single Shelf	263	Cable Management, Horizontal Base Unit	21
Cabinet, U/C/B, 1 DR, 3 Half DR, 1 Door, 30" W	44	Cage, Animal, Large	360
Cabinet, U/C/B, 1 DR, 3 Half DR, 1 Door, 36" W	45	Cage, Animal, Small	361
Cabinet, U/C/B, 1 DR, 3 Half DR, 1 Door, 36x48x22	46	Cage, Security, Heavy Duty	38
Cabinet, U/C/B, 1 PBD, 2 DR, 1 File DR, 30x18x22	47	Cage, Squeeze, Primate	361
Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x18x22	42	Cage, Transport, Aluminum, Large	361
Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	42	Calibrator, Audiometer	358
Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x30x22	43	Calibrator, Radioisotope	222
Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	44	Camera, Fundus, Digital	276
Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x48x22	45	Camera, Fundus, Flash, Automatic	276
Cabinet, U/C/B, 1 Shelf, 2 Door, 30x36x22	47	Camera, Identification, Film	373
Cabinet, U/C/B, 1 Shelf, 2 Door, 30x48x22	47	Camera, Photo Identification Card System	256
Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x30x22	43	Camera, Portable, CCTV, With Recorder	164
Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x36x22	44	Can, Trash, 44 Gallon	163
Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x48x22	45	Canopy, Hood, Exhaust Stack, Individual	223
Cabinet, U/C/B, 1 Shelf, 6 Half DR, 1 DO, 36x36x22	45	Canopy, Hood, Fume, 6 foot	226
Cabinet, U/C/B, 1 Shelf, 6 Half DR, 1 DO, 36x48x22	46	Carrel, Study Table	159
Cabinet, U/C/B, 2 Half Drawer, 2 Door, 30" W	47	Carriage, Pail, CRS, Without Pail	316
Cabinet, U/C/B, 2 Half Drawer, 3 Drawer, 36x36x22	45	Cart, Anesthesia	315
Cabinet, U/C/B, 2 Half Drawer, 3 Drawer, 36x48x22	46	Cart, Anesthesia, Mobile	143
Cabinet, U/C/B, 2 Half Drawers, 3 DR, 36x30x22	43	Cart, Buffet, Medium	179
Cabinet, U/C/B, 2 Shelf, 2 Door, 36x30x22	43	Cart, Bulk Supply, Mobile, 74"H x 51"W x 22"D	145
Cabinet, U/C/B, 2 Shelf, 2 Door, 36x36x22	44	Cart, Cast, Mobile, 36"H x 46"W x 22"D	143
Cabinet, U/C/B, 2 Shelf, 2 Door, 36x48x22	46	Cart, Closed, w/Shelves, Mobile, 72"Hx48"Wx22"D	147
Cabinet, U/C/B, 2 Shelves, 1 Door, 36x24x22	42	Cart, Closed, w/Totes, Mobile, 72"H x 48"W x 22"D	147
Cabinet, U/C/B, 4 Drawer, 30x18x22	46	Cart, Computer, Mobile, 48"H x 54"W x 22"D	143
Cabinet, U/C/B, 4 Drawer, 36x18x22	42	Cart, Emergency, Mobile, 66"H x 52"W x 22"D	144
Cabinet, U/C/B, 4 Drawer, 36x24x22	43	Cart, Endoscopy, Mobile, 78"H x 62"W x 24"D	145
Cabinet, U/C/B, 8 Half Drawer, 36x36x22	45	Cart, Fetal Monitoring, Birthing Room	318
Cabinet, U/C/B, 8 Half Drawer, 36x48x22	46	Cart, General Storage, Mobile	145
Cabinet, U/C/B, 8 Half Drawers, 36x30x22	44	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	144
Cabinet, U/C/B, Open, 2 Shelf, 36x30x22	43	Cart, Janitor's	156
Cabinet, U/C/B, Open, 2 Shelf, 36x36x22	44	Cart, Library, Mobile	157
Cabinet, W/H, 2 SH, 1 GDO, Sloping Top, 38x18x13	48	Cart, Linen, Soiled	156
Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	48	Cart, Loading, Sterilizable	348
Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x36x13	48	Cart, Lockable, Mobile, 42"H x 49"W x 22"D	145
Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x48x13	49	Cart, Machine, Mobile, 36"H x 32"W x 22"D	143
Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 41x30x16	49	Cart, Medication, Mobile, 68"H x 54"W x 22"D	144
Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 41x36x16	49	Cart, Medication, Unit Dose	284
Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x36x13	49	Cart, Metabolic	247
Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x48x13	49	Cart, Plaster	262
Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 41x36x16	49	Cart, Proctology Treatment, Mobile	144
Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 31x18x16	48	Cart, Shelving, Storage, Mobile, SS	259
Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	48	Cart, Storage, Dbl Width, Mbl, 74"H x 51"W x 22"D	145
Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x30x13	48	Cart, Supply	157
Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	48	Cart, Supply, Linen	157
Cabinet, Wall Hanging, Dental Laboratory, 30x24x12	57	Cart, Surgical Case	316
Cabinet, Wall Hanging, Dental Laboratory, 30x48x12	57	Cart, Surgical Case, Birthing Room	317
Cabinet, Wall Hung, 1-2 Door, 3 Shelves, 22x18x21	367	Cart, Surgical Dressing, CRS, Mobile	317
Cabinet, Wall Hung, 2 Sliding Door, 23x38x14	78	Cart, Traction Appliances, Mobile	262

NOMENCLATURE	PAGE	NOMENCLATURE	PAGE
Cart, Transport, Radium	386	Chair, Sleeper	154
Cart, Trash	157	Chair, Stacking	153
Cart, Utility	157	Chair, Swivel, High Back	153
Cart, Weight, Physical Therapy, w/Weights	302	Chair, Swivel, Low Back	153
Cart, Wire, Mobile	146	Chair, Task, Swivel, With Arms	153
Cart, Wire, Mobile, 61"W x 48"H x 24"D	146	Chair, Waiting Room, Single	154
Cart, Wire, Mobile, 72"H x 42"W x 24"D	146	Chair, Waiting Room, Tandem	154
Cart, Wire, Mobile, 72"H x 61"W x 24"D	146	Chair, Whirlpool, Adjustable	297
Case, Display	168	Chair/Table, Combination Unit	319
Cash Register, With Locking Drawer	164	Chalkboard	167
Casting Machine, Electric, Chrome/Cobalt	64	Chamber, Hyperbaric, Animal	362
Casting Machine, Induction, Bench Mounted	64	Chisel, Dental, Pneumatic	69
Casting Machine, Induction, Free Standing	64	Chromatograph, Gas, General	213
Casting Machine, Manual, Broken Arm	64	Chromatograph, Gas, Mass Spectrometer	213
Cell Saver, Autologous Blood Recovery	216	Chromatograph, Ion	214
Cell Washer, Frozen Blood Deglycerolizer	216	Chromatograph, Liquid	214
Cell Washer/Centrifuge	220	Chute, Waste, Plaster, Counter Mounted	72
Center, Infant Care	247	Cleaner, Carpet / Floor, Vacuum, Portable	166
Center, Mixing, Barium	384	Cleaner, Carpet, Vacuum, Industrial	165
Centrifuge, Cytology	221	Cleaner, Steam, Dental	67
Centrifuge, Heavy Duty, Floor Model, Refrigerated	220	Cleaner, Ultrasonic, 10-12 Quart Capacity	73
Centrifuge, Medium Duty, Refrigerated, Floor Model	219	Cleaner, Ultrasonic, 6 Quart Capacity	59
Centrifuge, Microhematocrit, 24 Tube	219	Cleaner, Ultrasonic, Console, DBL CHMBR, CAB, F/S	346
Centrifuge, Refrigerated, Benchtop	220	Cleaner, Ultrasonic, SNGL Chamber, CAB, F/S	346
Centrifuge, Refrigerated, Floor Model	220	Clipper, Hair, Animal	362
Centrifuge, Serological, Multi Speed, Benchtop	220	Clock, Battery, 12" Diameter	168
Centrifuge, Small, Blood Typing, Variable Speed	219	Clock, Elapsed Time, Electric	30
Centrifuge, Table, Small, 3200 RPM, 6 Place	219	Clock, Ship's, With Barometer	168
Centrifuge, Tabletop	219	Co-Oximeter	217
Chair, Arm Writing	151	Coagulator, Infrared	265
Chair, Arm, Lounge Type	152	Collector, Dust, Freestanding	356
Chair, Auditorium, With Tablet Arm	151	Colonoscope, Fiberoptic, Therapeutic	308
Chair, Blood Donor, Recliner, Manual or Pneumatic	251	Colonoscope, Video, Therapeutic	308
Chair, Blood Donor, Recliner, w/Motor, Armrest	252	Colposcope System, Mobile, w/Accessories	289
Chair, Chancel, Chapel	149	Column, Service, Prefab, Surgical, Ceiling Mounted	28
Chair, Chapel, w/ Kneeler	147	Column, Service, Prefabricated, ICU	27
Chair, Child's	151	Commode Chair	270
Chair, Conference	151	Compactor, 1.5 - 6 CuYd, Receiver 15 - 40 CuYd Cap	260
Chair, Dialysis	273	Compactor, VERT, Freestanding, Front Door Loading	260
Chair, Dining Room	151	Component Analyzer, Solid State	359
Chair, Drafting, Rotary	152	Compressor, Air, Dental, 6 Operatories	75
Chair, Easy	152	Compressor, Dental Air, System	66
Chair, Exam, Vestibular	274	Computer Assisted Cardiology Management System.	292
Chair, Exam/Treatment, ENT, w/Adjustable Light	274	Computer, Clinical, Nuclear Medicine	388
Chair, Exam/Treatment, Podiatry, w/Motor	274	Computer, DIN/PACS System	376
Chair, Exam/Treatment, With Motor	274	Computer, Holter Monitor Analysis System	292
Chair, Examination/Treatment, Surgical, ENT	319	Computer, Mean Cell Volume	228
Chair, Executive, Rotary, Highback	152	Computer, Microprocessing, w/CRT Monitor	253
Chair, Executive, Side	152	Computer, Microprocessing, w/Flat Panel Monitor	253
Chair, Executive, Swivel	152	Computer, Rad Therapy Treatment Planning	388
Chair, High Back, Patient	152	Computer, Radio Therapy, Record/Verify	388
Chair, Laboratory, Blood Drawing, w/Storage	252	Conditioner, Cold Treatment Pack	298
Chair, Operating, Dental	65	Console, PACS, Remote View, 1k X 1k, 1 Monitor	375
Chair, Operating, Dental, With Unit Mount, Light	71	Console, PACS, Remote View, 1k X 1k, 2 Monitors	375
Chair, Operating, Dental, Without Unit Mount	65	Console, PACS, Remote View, 2k X 2k, 2 Monitors	375
Chair, Procedure, Dental	65	Console, PACS, Remote View, 2k X 2k, 4 Monitors	375
Chair, Radiographic, Dental	65	Console, PACS, Remote View, 512 X 512, 1 Monitor	375
Chair, Recliner	152	Console, Service, Infant, Prefabricated	28
Chair, Rocking, High Back	153	Container, Recycling, Large	163
Chair, Rotary, Laboratory, Dental	65	Container, Recycling, Small	163
Chair, Secretarial, Executive	153	Controller, Flow, Infusion, 5-60 DPM	267
Chair, Secretarial, Tilt Back, Adjustable Height	153	Conveyor, Clothing, On Hangers	166
Chair, Side With Arms	151	Conveyor, Meal Tray Makeup, CRS	180
Chair, Side, Without Arms	151	Conveyor, Meal Tray Return	182

NOMENCLATURE	PAGE
Conveyor, Tray, Electric, Moveable	181
Cooker, Pressure, Gas, Dual	204
Copier, Desk Top	254
Copier, Floor Standing, Digital	254
Corneal Topography Unit	283
Costumer, Wall, Executive	33
Counter, Reception Control, Built-In	37
Counter, Bacteria	228
Counter, Cafeteria, Cold Food, Mobile, 4-Pan	180
Counter, Cafeteria, Cold Food, Mobile, 5-Pan	180
Counter, Cafeteria, Filler, Approximately 36x80x32	181
Counter, Cafeteria, Filler, Approximately 39x74x33	181
Counter, Cafeteria, Filler, Approximately 52x50x30	181
Counter, Cafeteria, Hot Food, Mobile, 5-Pan	181
Counter, Cafeteria, Mbl, Util, W/Power 36x39x28	183
Counter, Cafeteria, Mobile, Utility	183
Counter, Cafeteria, Utility, W/ Power 57x50x40	182
Counter, Cafeteria, Utility, W/Power 36x50x40	182
Counter, Cafeteria, Utility, W/Power 48x64x32	182
Counter, Cafeteria, Utility, W/Power 57x50x42	183
Counter, Cafeteria, Utility, W/Power 61x80x42	182
Counter, Cell, Auto	227
Counter, Cleanup, With 2 or 3 Sinks	30
Counter, Console, Communications	37
Counter, Gamma, Multichannel	388
Counter, Gamma, Multichannel	388
Counter, Gamma, RIA, Manual	239
Counter, Pill/Tablet, Automated, Counter Mounted	285
Counter, Radioimmunoassay, Multi Det	239
Counter, Radioimmunoassay, Single Det	239
Counter, Work, w/Storage, Cab, Pharm, Wall Mtd,48"	121
Counter, Work, w/Storage, Cab, Pharm, Wall Mtd,72"	122
Counter, Work, w/Storage, Pharm, Wall Mtd, 48"W	121
Counter, Work, w/Storage, Pharm, Wall Mtd, 96"W	122
Counter, w/Sink, Storage, Pharm, Wall Mtd, 66"W	122
Counter/Dispenser, Pill/Tablet	285
Counter/Timer, Digital	227
Countertop, Epoxy Resin	58
Countertop, High Pressure Laminate	53
Countertop, Laminated, 1" or 1-1/4"x W x D	77
Countertop, Laminated, 3/4" Thick	77
Countertop, Modified Epoxy Resin	53
Countertop, Stainless Steel	53
Coupler, Quick Disconnect	74
Credenza, Executive, Wood	158
Crib	284
Cross, Chapel	148
Crucifix, Chapel	148
Cryosurgical Unit, Mobile	271
Cupsink	52
Curing Unit, Denture, 2 Stage	66
Curing Unit, Denture, 3 Stage	66
Curtain, Air	175
Cutter, Block, Beam, Radiotherapy	384
Cutter, Cast, w/Vacuum	272
Cutter, Compensator, Radiotherapy	384
Cutter, Food, Electric, Bench Mounted	184
Cutter, Sole, Bench Mounted	354
Cutter/Mixer, Electric, 10-15 Qt Capacity	184
Cutter/Mixer, Electric, 40 Quart	184
Cutter/Slicer, Vegetable	185
Cytometer, Flow, Advanced Laboratory	215
Cytometer, Flow, Clinical Laboratory	215

NOMENCLATURE	PAGE
D	
Defibrillator Analyzer, Automatic, Portable	350
Defibrillator/Cardioscope, 5-Lead	290
Defibrillator/Monitor, Acute Care	289
Defibrillator/Monitor/Recorder Automatic	290
Defibrillator/Monitor/Recorder, Portable	290
Delivery System, Dental Operating	71
Deminalizer, Water, Floor Mounted, 1/2-3 GPM	221
Densitometer, Blood	218
Densitometer, Film, Radiographic	389
Densitometer, Scanning	217
Desk, Double Pedestal, 30 x 60 x 30	158
Desk, Executive, Wood	158
Desk, Fitting/Dispensing, Optical	274
Desk, Folding, W/M	158
Desk, Refraction w/console, w/o Sink	275
Desk, Refraction, w/Sink, 33x92x25	274
Desk, Secretary, Executive	158
Desk, Single Pedestal	158
Detector, Mercury	231
Dewar, Liquid Nitrogen	251
Dialysis Box, Recessed, Single Valve	326
Diathermy Treatment Unit	301
Dilutor, 1:25,000 Dilution	218
Dishwasher, Conveyor, Steam, 1 Tank	189
Dishwasher, Conveyor, Steam, 2 Tank	189
Dishwasher, Conveyor, Steam, 3 Tank	190
Dishwasher, Household	190
Dispenser, Bedding, With Conveyor	365
Dispenser, Bowl/Plate, Mobile, Heated, 2 Stack	188
Dispenser, Bowl/Plate, Mobile, Unheated, 2 Stack	188
Dispenser, Bowl/Plate, Mobile, Unheated, 4 Stack	188
Dispenser, Bread, CRS, 2 Compartment	185
Dispenser, Coffee, Freeze Dried	187
Dispenser, Cream, Eutectic, 2 Quart	186
Dispenser, Cup/Saucer, Unheated, Mobile, 4 Stack	186
Dispenser, Detergent, Automatic	185
Dispenser, Drink, Carbonated	186
Dispenser, Drink, Non-Carbonated	186
Dispenser, Drink, Non-Carbonated w/Refrigeration	186
Dispenser, Drinking Glass, Mobile	187
Dispenser, Flatware, 8-12 Basket, Counter Mounted	188
Dispenser, Glove, Surgical/Examination, Wall Mntd	32
Dispenser, Hot Chocolate, Counter Mounted	189
Dispenser, Ice Cream, Soft, Freestanding	189
Dispenser, Iced Tea	185
Dispenser, Lead Alloy	384
Dispenser, Liquid Soap, SS, Surface Mounted	31
Dispenser, Meal Tray, Mobile	188
Dispenser, Meal Tray, w/Flatware Cylinders	187
Dispenser, Milk Shake, 8 Gal	189
Dispenser, Milk, Bulk, Double	186
Dispenser, Milk, Bulk, Single	185
Dispenser, Milk, Mobile, Individual Container	185
Dispenser, Paper Cup, SS, Surface Mounted	31
Dispenser, Paper Towel, SS, Surface Mounted	31
Dispenser, Plate, Mobile, Heated, 2 Stack	187
Dispenser, Plate, Mobile, Heated, 4 Stack	187
Dispenser, Plate, Mobile, Unheated, 4 Stack	187
Dispenser, Reagent, Phenolic	233
Dispenser, Soap, Disposable	31
Dispenser, Toilet Tissue, SS, 1-Roll, Surface MNTD	35
Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	35
Dispenser, Tray/Flatware, 2 Stacks, 8-12 Cylinder	189

NOMENCLATURE	PAGE
Dispenser, Water Metering, Automatic, Electric	209
Dispenser, Toilet Paper w/Utility Shelf, SS, 2-Roll	35
Dispensing System, Prescription, Robotic	285
Display, Tackboard & Markerboard, Wall Mtd	140
Disposal, Garbage, 2 HP Motor	323
Disposal, Sanitary Napkin, SS, Surface Mounted	32
Disposal, Waste, Heavy Duty	190
Distilling Apparatus, Xylene Recovery	221
Distribution System, Medication, Automatic	264
Divider, Dough, Roll	190
Drapes, Blackout	39
Drapes, Pair	39
Dresser, 6 Drawer	158
Drill Press, Bnch/Mntd	352
Drill Press, Floor Mounted, Tilt Table	352
Drill System, Surgical, Oral, Electric Drive	67
Drill System, Surgical, Oral, Nitrogen Drive	67
Drill, Paper	166
Drill, Surgical, Air Drive	272
Drill, Surgical, Electric Drive	272
Driver, Model Indexing Pins	73
Dryer, Cabinet, Tubing	346
Dryer, Clothes, Automatic, Electric, Household	260
Dryer, Film/Print	242
Dryer, Film/Print, High Capacity	242
Dryer, Glassware, Electric	222
Dryer, Vegetable, CRS	190
Duodeno/Cholechoscope System, Mother/Daughter	309
Duodenoscope, Fiberoptic, Therapeutic	308
Duodenoscope, Video, w/Accessories	308
Duplicator, Film, Dental, 9x18x14	371
Duplicator/Printer, Film, Table, 17x16x24	371

E

E.I.A. Analysis System, Advanced	212
E.I.A. Analysis System, Basic	212
E.I.A. Plate Washer System	213
ENT Unit, w/Air, Electric Power, Suction, Pressure	272
Edger, Lens, Automatic Beveling	282
Edger, Lens, Automatic Beveling, Cabinet Mounted	282
Electrical Safety Analyzer	349
Electrocardiograph, 12 Lead, Portable	290
Electrocardiograph, 3 Channel Display/Printout	290
Electrocardiograph, 3 Channel, CAPOC Compatible	291
Electrocardiograph, Portable, Single Channel	290
Electroencephalograph, 32 Channel	291
Electromyograph	291
Electronystagmograph w/Accessories	291
Electrophoresis, General	217
Electrophoresis, Thin Layer	217
Electrosurgery Analyzer	358
Electrosurgical Unit, Dual Output	264
Electrosurgical Unit, Endoscopy	312
Electrosurgical Unit, Mobile, Unblended	263
Electrosurgical Unit, Monopolar, Wall Mounted	265
Embedder, Tissue	237
Embosser, Compact, Plastic Card	254
Embosser, Metal Tag	254
Endoscopy Cart, Fiberoptic, Basic	313
Endoscopy Cart, Fiberoptic, w/Video Accessories	313
Endoscopy Cart, Fiberoptic, w/Video, Info. Mgmt.	313
Endoscopy Cart, Video (CCD) Scope	313
Endoscopy Cart, Video (CCD) Scope, with Info. Mgmt	314
Engine, Dental, Bench, Electric	69
Enlarger/Printer, Photographic, 3 Lens	242

NOMENCLATURE	PAGE
Enteroscope, Fiberoptic, Therapeutic	309
Enteroscope, Video, Therapeutic	310
Ergometer, Bicycle, Mobile	298
Ergometer, Bicycle, Stationary	298
Ergometer, Bicycle, Testing/Evaluation	299
Ergometer, Recumbent Bicycle, Computer Assisted	175
Ergometer, Recumbent Stepper	169
Ergometer, Stationary, Stair	170
Ergometer, Upper Body	299
Evacuation System, Laboratory, Dental	66
Evaluator, Hand Impairment, Computer Assisted	304
Exam, Workstation & Cart, Free Standing, 84" W	95
Exam, Workstation & Markerboard, Wall Mtd, 48" W	94
Exam, Workstation & Sink, Wall Mtd, 48" W	94
Exam, Workstation & Storage, Wall Mtd, 3 Walls	94
Exercise Apparatus, Weight Training, Multi-Station	172
Exercise Board, Abdominal, Raised and Bent Leg	170
Exercise Machine, Rotary Shoulder	172
Exercise Machine, Abdominal	171
Exercise Machine, Back Extension	173
Exercise Machine, Biceps	171
Exercise Machine, Chest	171
Exercise Machine, Closed Chain	173
Exercise Machine, Hip Abduction	172
Exercise Machine, Hip Adduction	172
Exercise Machine, Leg Curl	175
Exercise Machine, Leg Extension	175
Exercise Machine, Leg Press/Squat	171
Exercise Machine, Neck	171
Exercise Machine, Pullover	172
Exercise Machine, Rowing	172
Exercise Machine, Shoulder	174
Exercise Machine, Triceps	171
Exerciser, Continuous Passive Motion (CPM)	306
Exerciser, Ladder	299
Exerciser, Ramp and Curbs	299
Exerciser, Staircase, Convertible	299
Exerciser, Upper Body, Weight Assisted	170
Exhaust System, Welding	37
Extinguisher, Fire	24
Eyewash, Counter Top	322
Eyewash, Eye/Face, Deck Mounted w/Squeeze Handle	323
Eyewash, Eye/Face, Sink Mounted, Hands-free	322
Eyewash, Floor Mounted	322
Eyewash, Wall Mounted, Hands-Free	322

F

Facsimile Machine	256
Fiber Optic Cabinet, 36 Port, Rack Mounted	21
Fibrometer, Auto	227
Filler, Bottle, For Lab Animals	365
Flags, Command & Staff	169
Floor Cover, Rubber, Interlock	173
Flowmeter, Air, Connect w/50 PSI Supply	247
Flowmeter, Oxygen, Low Flow	247
Fluoroscopic, Digital, Mobile, C-Arm	377
Flushing Unit, Renal Dialysis Cartridge	272
Font, Baptismal	148
Font, Holy Water	149
Footstool, Straight	154
Former, Vacuum, With Motor, Vacuum Pump, Heater	71
Fountain, Water	329
Fountain, Water, CRS, Wall Mounted, 2 Level	329
Fountain, Water, CRS, Wall Mounted, Handicap	329
Fountain, Water, CRS, Wall Mounted, Recessed	329

NOMENCLATURE	PAGE
Frame Set, Lens, Trial	280
Frame, Apron, 1 Drawer, 4x24x22	41
Frame, Apron, 1 Drawer, 4x30x22	41
Frame, Apron, 1 Drawer, 4x36x22	41
Frame, Apron, 2 Drawer, 4x48x22	41
Frame, Apron, 3 Drawer, 4x60x22	41
Frame, Bed, Overhead, Balkan	262
Frame, Infectious Waste Bag w/Lid	262
Frame, Table, 2 Drawer, 1-2 Half Drawer, 36x42x24	57
Frame, Table, 2 Drawer, 36x40x24	56
Freeze-Dryer, Tissue	237
Freezer, 2 Section, CRS	328
Freezer, Biological, Chest, -70c, 12 Cubic Feet	332
Freezer, Blood, Chest, Double Compartment	331
Freezer, Blood/Platelet,Upright, -85C, 20-30 Cu Ft	331
Freezer, CRS, Prefabricated -20 F	329
Freezer, Counter High, -70 C, 5 CUFT	331
Freezer, Cryogenic, Chest	333
Freezer, Drawer, Undercounter	329
Freezer, Food, Upright, CRS, 23 Cu Ft, 84x27x37	333
Freezer, Ice Cream, 15 Gallon	328
Freezer, Ice Cream, 25 Gallon	328
Freezer, Ice Cream, 35 Gallon	328
Freezer, Ice Cream, 45 Gallon	328
Freezer, Ice Cream, Chest, 5 Cubic Foot	328
Freezer, Plasma, Upright, -35c, 20 Cubic Feet	331
Freezer, Rapid, Blood/Plasma, 4 Cubic Feet	330
Freezer, Undercounter, 5 Cubic Feet	331
Freezer,Biological, -85, 19-25 Cubic Feet, Upright	330
Fryer, 30 Lb. Capacity, Electric, Counter Mounted	191
Fryer, Electric, 15 Lb. Capacity, Counter Mounted	191
Fryer, Electric, 30 Lb. Capacity, Free Standing	191
Fryer, Electric, 50-70 Lb. Capacity, Free Standing	192
Fryer, Electric, 85 Lb. Capacity, Freestanding	192
Fryer, Fat, Deep, 50 Lb. Capacity, Gas	191
Fryer, Gas, 30-40 Lb. Capacity, Free Standing	191
Fryer, Pressure, 70 Lb. Capacity, Electric	192
Furnace, Laboratory, Dental, Burnout	68
Furnace, Laboratory, Porcelain Glazing	69
Furnace, Porcelain, Vacuum	71
Furniture, Playroom, Assorted	163

G

Gastroscope, Fiberoptic, Therapeutic	309
Gastroscope, Video, Therapeutic	309
Gauge, Distance, Pupillary	281
Generator, Function	358
Generator, Lens	282
Generator, Pulse	358
Generator, Steam, Electric, 30 kW	345
Generator, Steam, Electric, 75 KW	345
Gonioscope, Lens, Contact	280
Grab Bar, 1-1/4" Dia., SS, 2 Wall, Shower Use	32
Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	32
Griddle, Electric, Counter Mounted, 36" Wide	193
Griddle, Gas, Counter Mounted, 36" Wide	193
Griddle, Gas, Mobile Stand Mounted, 48" Wide	193
Griddle, Gas, Stand Mounted, 36" Wide	193
Grinder, Bench Mounted	352
Grinder, Floor Mounted, Pedestal	352
Grinder, Keymaking, Automatic	352
Grinder, Meat, 20 Lb./Minute Capacity, Electric	193
Grinder, Meat, 40-50 Lb./Minute Capacity, Mobile	193
Grinder, Meat, 80 Lb./Minute Capacity	194
Grinder, Pedestal/Mounted, Combination Belt/Disc	357

NOMENCLATURE	PAGE
Grinder/Polisher, Bench Mounted, High Speed	70
Guard, Casting Machine	58
Gun, Steam	347
H	
Hamper, Linen, Mobile, w/Lid	262
Handpiece, Laboratory, Dental	67
Handpiece, Laboratory, Dental, Electric	67
Headwall, Prefabricated, General, 1-2 bed	27
Headwall, Prefabricated, ICU, With Equipment	27
Hearing Aid Analyzer	240
Heart/Lung Machine, Bypass, Modular	271
Heat Probe Unit, Endoscopic	309
Heater, Duplicating Colloid	68
Heater, Duplicating Colloid, Automatic	68
Hematocrit Accessory, Automatic	228
Hemodialysis Unit, Hollow Fiber or Plate	253
Hemodialysis Unit, Mbl, w/Reverse Osmosis System	271
Hemoglobin Analysis System	213
Hemoglobinometer	218
Hoist, Chain, 1/2 Ton Capacity, 7 Foot Lift	357
Holder, Candle, Altar	149
Holder, Cassette, Vertical, With Bucky	369
Holder, Chart, 20 Each	252
Holder, Chart, Mobile, 30 Each	252
Holder, Chart, Mobile, 45 Each	252
Holder, Chart, Patient, Wall or Door Mounted	253
Homogenizer, Tissue	237
Hood, Collecting, Dust, 17x29x21	60
Hood, Exhaust, Kitchen	194
Hood, Exhaust, Non-Commercial	194
Hood, Fishmouth	60
Hood, Fume, Bench	223
Hood, Fume, Dental Acrylic, Floor Standing	61
Hood, Fume, Floor Standing	222
Hood, Fume, Floor Standing, Explosion Proof	223
Hood, Fume, Floor Standing, Perchloric	223
Hood, Fume, Histopathology Staining	226
Hood, Fume, Radioisotope	223
Hood, Fume, Radioisotope, Bench, w/Glovebox	224
Hood, Laminar Flow, Horizontal, Bench Top, 4ft	224
Hood, Laminar Flow, Horizontal, Free Standing, 6ft	224
Hook, Garment, Double, SS, Surface Mounted	33
Hook, Garment, Triple, Surface Mounted	33
Hooks, Mat, Gym	303
Horizontal Exerciser, Upper and Lower Extremities	299
Hose, Retractable, Wall Mounted	195
Hose, Spray, Pre-Rinse	208
Housing, Group, Exercise Unit	361
Hypo/Hyperthermia Unit, Automatic/Manual, Mobile	271

I

Ice Maker, 500 Pound	330
Ice Maker, Cubes (approx 400lbs/24hrs)	330
Ice Maker, Cubes, 250 Pound, 39x29x26	330
Ice Maker, Cubes, Undercounter	330
Ice Maker, Flaked, With Dispenser, 71x19x24	330
Illuminator, Film, 4 Panel, Recessed, 23x61x5	375
Illuminator, Film, 4 Panels, Wall Mounted	374
Illuminator, Film, 8 Panel, With Desk	374
Illuminator, Film, 8 Panels, Wall Mounted	374
Illuminator, Film, Dental, Portable	385
Illuminator, Film, Double, Recessed	374
Illuminator, Film, Double, Wall Mounted, 20x29x6	374
Illuminator, Film, Mobile, 4 Over 4	374

NOMENCLATURE	PAGE
Illuminator, Film, Single, Wall Mounted	373
Imager, Dental, Digital Image	383
Imager, Dry Chemistry, 14" X 17"	370
Imager, Dry Chemistry, 8" X 10"	370
Imager, Laser (1024 X 1024) (Din/PACS)	370
Imager, Laser (512x512) Din/PACS	369
Immobilizer, Infant, With Cassette Holder	366
Imprinter, Clock, Day / Date / Time	166
Imprinter, Data Record, Electric	254
Imprinter, Data Record, Manual	254
Incubator, Blood Bank, Tabletop	234
Incubator, Anaerobic, Vacuum	234
Incubator, Bacteriological, 2 Compartment	234
Incubator, Bacteriological, 34x37x25	227
Incubator, Bacteriological, Dry Block	229
Incubator, Bacteriological, Single	227
Incubator, Co2, 2 Chamber	227
Incubator, Infant, ICU, Mobile	248
Incubator, Infant, ICU, Mobile/Transport	248
Incubator, Infant, Mobile, Isolation	248
Incubator, Multipurpose, Dry Block	230
Incubator, Paraffin, +/- 10 Cubic Foot	234
Incubator, Platelet, Freestanding, w/Rotator	227
Infuser, Rapid, Blood	267
Injector, Angiographic	381
Injector, CT	381
Inner Ear (Cochlear) Analyzer, Screen	241
Insufflator, Automatic Controls	312
Interceptor, Solids, Large Capacity, Floor Type	326
Intercom - Room To Room	39
Irradiator, Blood	216
Isokinetic Unit, Testing and Treatment	299
Isolator, Micro, Housing Unit	366

J

Jigsaw, Electric	354
Jointer, Woodworking, 6", 39x48x21	352
Juke Box, Optical Disk, PACS	376

K

Kennel, Large Animal, Intensive Care, Mobile	361
Kettle, Cabinet, 2 Unit, Tilting, Steam, 20 Qt Ea.	198
Kettle, Jacketed, 20 Gal Cap, Elect, Freestanding	196
Kettle, Jacketed, 40 Gal Cap, Gas, Freestanding	196
Kettle, Jacketed, Gas, 20 Gallon Capacity	196
Kettle, Jacketed, Steam, 60 Gallon Capacity	197
Kettle, Jacketed, Steam, Fixed, 40 Gallon Capacity	196
Kettle, Jacketed, Steam, Tilt, 10 Gal, Table Mtd	197
Kettle, Jacketed, Steam, Tilting, 20 Gal Capacity	196
Kettle, Jacketed, Steam, Tilting, 40 Gal Capacity	196
Kettle, Jacketed, Steam, Tilting, 5 GAL, Table MTD	195
Kettle, Jacketed, Tilting, 60 Gallon Capacity, Gas	197
Kettle/Mixer, Jacketed, Tilting, Steam, 40 Gal Cap	198
Kettle/Mixer, Jacketed, Tilting, Steam, 60 Gal Cap	197
Kettle/Mixer, Jacketed, Tilting, Steam, 80 GAL Cap	198
Kettle/Mixer, Tilting, Table Mtd, Electric, 20 Qt	198
Kiln, Ceramic, Front Loading	353
Kiln, Ceramic, Top Loading	353
Kit, Wallyball	174

L

Ladder, Platform, Mobile	259
Lamp, Desk, Fluorescent	165
Lamp, Slit, Photographic w/Tonometer	277
Lamp, Slit, w/Applanation Tonometer	277
Lamp, Table, With Shade	165

NOMENCLATURE	PAGE
Lantern, Perception, Color	280
Laparoscope	310
Laser Positioning System, Patient-Ceiling	369
Laser Positioning System, Patient-Wall	369
Laser System w/Slit Lamp or Ophthalmoscope	276
Laser, Corneal Surgery	277
Laser, Ophthalmic, Semiconductor Diode	276
Laser, Photocoagulation, Dual Fiber, Ophthalmology	277
Laser, Pulsed Dye	310
Laser, Smoke Evacuator	276
Laser, Surgical, CO2, Mobile	310
Laser, Surgical, KTP	310
Lathe, Dental, Bench Mounted	70
Lathe, Metal, Bench/Mounted, Multi-Speed, 4 Feed	357
Lavatory, China, for Disturbed Patient	327
Lavatory, Vitreous China, Slab Type	323
Lavatory, Vitreous China, Slab Type w/Sens Op Fauc	323
Lavatory, Vitreous China, Straight Back	323
Lavatory, Vitreous China, Under or Counter Top Mtd	323
Lavatory, Wheelchair, 7x20x27	327
Lectern, Mobile, With Reading Light	163
Lectern, Mobile, With Self Contained Audio	164
Legs, Rail, Apron	75
Lensometer	277
Lensometer, Soft Contact	277
Leveler, Dock	37
Lift, Cadaver	265
Lift, Manual, Mortuary, 300 Lb. Capacity (Minimum)	238
Lift, Patient, Hydraulic, 350 Lb. Cap, Adj U-Base	298
Lift, Patient, Physical Therapy	297
Light Grp, Surg, Ceiling, 2 Light, Parallel Track	287
Light Source, Fiberoptic Headlamp	312
Light Source, Fiberoptic, Endoscopy	311
Light, Bench, Dental	60
Light, Corneal Microscope, Circular	289
Light, Dental Operating, Chair Mounted	69
Light, Dental, Operating, Ceiling, Column	70
Light, Dental, Operating, Ceiling, Track	69
Light, Dental, Operating, Dual, Ceiling, Track	70
Light, Exam, Ceiling Mounted	286
Light, Exam, Mobile	286
Light, Exam, Mobile, Spotlight, Mobile Stand	286
Light, Exam, Table Mounted, Spotlight	286
Light, Exam, Ultraviolet (Woods)	286
Light, Exam, Wall Mounted	286
Light, Infrared	303
Light, Infrared/Ultraviolet Combination	302
Light, Overbed, Direct And Indirect	287
Light, Phototherapy, Mobile	302
Light, Surg, Ceiling Mtd, Dual, Equal Dia Heads	288
Light, Surg, Ceiling Mtd, Dual, Unequal Dia Heads	288
Light, Surgical, Ceiling Mounted, 1 Light, Camera	289
Light, Surgical, Ceiling Mounted, Single, Large	288
Light, Surgical, Ceiling Mounted, Single, Medium	288
Light, Surgical, Ceiling Mounted, Single, Track	287
Light, Surgical, Ceiling Mtd, Birthing/Retractable	289
Light, Surgical, Ceiling, Single, Small	288
Light, Surgical, Dual, LDR/LDRP, In-Ceiling	287
Light, Surgical, Single, LDR/LDRP, In-Ceiling	287
Light, Ultraviolet, Mobile	303
Lithotripter, Extracorporeal	368
Lithotripter, Ultrasound	270
Loader/Unloader, Film, Daylight, Multiple	370
Loading Car & Transfer Carriage, 20x20x38 Chamber	340

NOMENCLATURE	PAGE
Loading Car & Transfer Carriage, 24x36x48 Chamber	342
Loading Car & Transfer Carriage, 24x36x60 Chamber	342
Loading Car & Transfer Carriage, Large Chamber	340
Locker, 2 Person, Over/Under	25
Locker, 2 Person, Side by Side, 72x15x18	25
Locker, Box, Personal Effects	25
Locker, Single Tier, 72x12x18	25
Locker, Supply, 6 Drawers, Mobile, 29"W x 20"D	142
Locker, Supply, Cassette, Wall Mtd, 23"W x 20"D	141
Locker, Supply, Endoscopy, Wall Mtd, 24"W x 14"D	142
Locker, Supply, General, Wall Mtd, 23"W x 20"D	141
Locker, Supply, Med Surg, Wall Mtd	141
Locker, Supply, Medication, Wall Mtd, 23"W x 20"D	142
Locker, Supply, Shelf & Drawer, Mbl, 29"W x 20"D	143
Locker, Supply, Wire Shelves, Mobile	142
Locker, Supply, w/Shelves, Wall Mtd, 23"W x 20"D	141

M

MRI System, Open	389
MRI System, Super Conductive	390
Machine, Finishing, Shoe	356
Machine, Sewing, Industrial, Heavy Duty	355
Machine, Sewing, Industrial, Medium Duty	355
Machine, Sewing/Stitching	358
Machine, Sign Making	355
Machine, Vending	36
Magnet, Eye, Electric	280
Mailbox, Horizontal, Rear Loading	26
Management Processor Module for LAN Switch	23
Manikin, Training, ACLS/CPR	256
Marker, Linen	260
Mat, Exercise	303
Mattress, Bed, Hospital	284
Mattress, Pressure Reduction	262
Medical Gas Outlet Location - In OR Wall	27
Message Board, Digital	27
Meter, Radiation Survey	350
Meter, Sound Level	359
Meter, pH	216
Microbiological Identification System	228
Microbiological Susceptibility/ID System	228
Microfinisher, Dental, Counter Mounted	73
Microscope, Binocular	210
Microscope, Binocular, Phase Contrast	211
Microscope, Fluorescence	211
Microscope, Fluorescent, Photographic	212
Microscope, Inverted, Tissue Culture	210
Microscope, Karyotyping, Digital Image	210
Microscope, Operating, Ceiling Mounted	310
Microscope, Operating, Portable	311
Microscope, Operating, Portable, General Use	311
Microscope, Operating, Wall Mounted	311
Microscope, Photographic	211
Microscope, Projection / Video System	211
Microscope, Stereo, Photographic, Desk Top	209
Microscope, Teaching, Multiple Head	212
Microscope, Teaching, Multiple Head (18)	212
Microscope, Trinocular	211
Microtome, Rotary, Tilt, Bench Mounted	229
Microtome, Rotary, Tilt, Refrigerated	229
Mirror, Float Glass, With SS Frame	26
Mirror, Float Glass, With SS Frame & Shelf	26
Mirror, Float Glass, With SS Frame, 36 x Required	26
Mirror, Front Surface Reflector, Eye Exam	281
Mirror, Posture, Wall Mounted	26

NOMENCLATURE	PAGE
Mirror, SS, With SS Frame, 36x18	26
Mirror, Safety, Convex	36
Mixer / Investor, With Vacuum	70
Mixer, Chemical, Automatic	378
Mixer, Free Standing, 30 Quart	199
Mixer, Free Standing, 60 Quart	199
Mixer, Free Standing, 80 Quart	199
Mixer, Table Mounted, 10 Qt.	199
Mixer, Table Mounted, 20 Quart	199
Mixer, Table Mounted, 5 Quart	199
Mixer, Vortex, Test Tube	233
Module, Lab, Dbl Side, w/Sink, Lockers, 192"Wx72"D	107
Module, Lab, Dbl, w/End, Lockr, Shelf, 192"Wx60"D	107
Module, Lab, End Panel, 60" W	107
Module, Lab, Work Surf, O/H Cab, Cabinet, 30" W	106
Module, Lab, Work Surf, O/H Cab, Cabinet, 48" W	106
Module, Lab, Work Surf, O/H Cab, Cabinets, 48" W	106
Module, Lab, Work Surf, O/H Cab, Hvy Storage, 48"W	105
Module, Lab, Work Surf, O/H Cab, Hvy Storage, 72"W	105
Module, Lab, Work Surface, O/H Cab, 24" W	101
Module, Lab, Work Surface, O/H Cab, 30" W	102
Module, Lab, Work Surface, O/H Cab, 48" W	102
Module, Lab, Work Surface, O/H Cab, 60" W	102
Module, Lab, Work Surface, O/H Cab, 72" W	102
Module, Lab, Work Surface, O/H Cab, Drwrs, 24" W	103
Module, Lab, Work Surface, O/H Cab, Drwrs, 30" W	103
Module, Lab, Work Surface, O/H Cab, Drwrs, 48" W	104
Module, Lab, Work Surface, O/H Cab, Drwrs, 60" W	104
Module, Lab, Work Surface, O/H Cab, Drwrs, 72" W	104
Module, Preventive Dentistry, 1 Station	69
Module, Storage, File/Cabinet, Free Std, 48"x16"	140
Module, Storage, File/Cabinet, Wall Mtd, 30"x16"	139
Module, Storage, File/Cabinet, Wall Mtd, 48"x16"	139
Module, Storage, Files/Shelves, Wall Mtd	140
Module, Storage, Files/Shelves, Wall Mtd, 48"x16"	140
Module, Storage, Pharm, Straight, F/S, 154"Wx21"D	123
Module, Storage, Pharm, U-Shape, F/S, 155x55	123
Module, Storage, Shelves, Wall Mtd, 72"W x 16"D	140
Module, Storage, Shelves, Wall Mtd, 96"W x 16"D	140
Monitor, 4 Channels, Telemetry, Bedside	292
Monitor, Anesthesia/Respiratory Gas	294
Monitor, CCTV, Small, 9" (Color)	244
Monitor, ECG/Respiration, Infant (Apnea)	292
Monitor, Fetal, Bedside/Stand Alone	293
Monitor, Fetal, Central	293
Monitor, Physiologic, Respiratory Gas	294
Monitor, Physiological, Bedside, 4 Channel	293
Monitor, Physiological, Central, 8 Bed, Color	293
Monitor, Physiological, Infant.	293
Monitor, Radiation, Area	389
Monitor, Radiation, Portable	389
Monitor, Television	243
Monitor, Vital Signs	266
Monitoring System, Cardiac Catheterization Lab	293

N

Nasopharyngoscope, Fiberoptic, Examination Only	306
Nasopharyngoscope, Fiberoptic, Therapeutic	306
Nebulizer, Ultrasonic	248
Nephelometer, Fluorescence	232
Net, Volleyball w/Stanchions & Wires	173
Nourishment Station, Freestanding	264
Nuclear Imaging System	387
Nurse Station, Accessible w/Angle, Free Std, 96" W	98
Nurse Station, Admitting, Free Standing, 72" W	99

NOMENCLATURE	PAGE
Nurse Station, Angle, Free Standing, 96" W	99
Nurse Station, Large, Free Standing	101
Nurse Station, Medium, Free Standing	100
Nurse Station, Recept, L-Shaped, Free Std, 96 x 96	100
Nurse Station, Recept, Straight, Free Std, 96" W	99
O	
Office, Provider, L-Shaped, Wall Mtd, 102"W x 96"D	93
Office, Provider, L-Shaped, Wall Mtd, 110"W x 72"D	93
Office, Provider, L-Shaped, Wall Mtd, 120"W x 48"D	93
Ophthalmometer/Keratometer	278
Ophthalmoscope, Binocular, Indirect	278
Ophthalmoscope, Direct	278
Oral Surgery System, Mobile	72
Organ, Chapel	148
Oscilloscope, With Accessories	359
Osmometer	218
Otoscope/Ophthalmoscope, Wall Mounted	267
Oven, Convection, Double, Electric, Free Standing	200
Oven, Convection, Double, Gas, Free Standing	200
Oven, Curing, Dental	68
Oven, Drying, Dental	71
Oven, Drying, Large, 2 Door	235
Oven, Drying, Medium, 2 Cubic Foot	234
Oven, Drying, Medium, 3 Cubic Foot	235
Oven, Drying, Small, w/Timer	234
Oven, Microwave, Consumer	201
Oven, Microwave, Heavy Duty, 1000 Watts	201
Oven, Microwave, Heavy Duty, 1500 Watts	201
Oven, Microwave, Over-the Range w/ Hood	194
Oven, Triple, Modular Deck, Gas	201
Oximeter, Pulse	294
Oxygen Analyzer, 0-100%	245
Oxygen Analyzer, Battery or Rechargeable	245
P	
Pachymeter, Ultrasound, Corneal	283
Packager, Unit Dose, Liquid	285
Packager, Unit Dose, Solids	285
Pail, Utility, CRS, Without Carriage	316
Pallet Lift, Hydraulic, Manual, 48" Pallet	259
Pan, Frying, Tilting, Elect, 30 Gal, Free Standing	192
Pan, Frying, Tilting, Gas, 30 Gal, Floor Mounted	192
Parallel Bars, Physical Therapy	303
Pasteurizer, Vertical Rotation	345
Patch Panel, 110 Block/RJ-45, Cat 5E, 48 Port,568A	22
Patch Panel, 110 Block/RJ-45, Cat 5E, 64 Port,568A	22
Patch Panel, 110 Block/RJ-45, Cat 5E, 96 Port,568A	22
Patch Panel, Copper, UTP	22
Patching Machine, Linen, Thermal	260
Peeler, Vegetable, 15 Lb. Capacity, Portable	202
Peeler, Vegetable, 30 Lb. Capacity, Free Standing	202
Peeler, Vegetable, 50 Lb. Capacity, Free Standing	202
Pegboard, Glassware, 30x30x6	41
Pegboard, Glassware, 30x36x6	42
Perimeter	278
Perimeter, Automated	278
Peritoneal Dialysis Unit, Hollow	272
Pew, Chapel w/Fold Up Kneeler	148
Phantom, CT Performance	386
Phantom, CT, Body	386
Phantom, CT, Head	386
Pharmacy Bulk Storage High Volume	131
Pharmacy Bulk Storage Low Volume	123
Pharmacy Bulk Storage Medium Volume	125

NOMENCLATURE	PAGE
Pharmacy Dispensing & Storage High Volume	133
Pharmacy Dispensing & Storage Low Volume	124
Pharmacy Dispensing & Storage Medium Volume	127
Pharmacy IV Admixture High Volume	136
Pharmacy IV Admixture Low Volume	125
Pharmacy IV Admixture Medium Volume	130
Pharmacy Manuf & Prepack High Volume	132
Pharmacy Manuf & Prepack Medium Volume	127
Pharmacy Manufacturing & Prepack Low Volume	124
Pharmacy Offsite Satellite High Volume	134
Pharmacy Offsite Satellite Medium Volume	128
Pheresis Unit	217
Phlebotomy Arm, Wheelchair Accessible	252
Photographic Optical Printer System	164
Photometer, Flame	229
Phototherapy Unit, Fiberoptic w/ Bili-Lite Pad,	302
Piano, Upright w/Bench	149
Pipettor, 20-100 Micro Liter	231
Pipettor, Micro, 3 Range	231
Plaster Dispensing System, Dental Lab, Power, W/M	63
Platform, Exercise, w/Mat	303
Platform, Exercise, w/Mat, Powered	305
Platform, Referee, Volleyball w/Pads	173
Plethysmograph System, Vascular	245
Plotter/Printer, Large Format, Digital	255
Polisher, Electrochemical	72
Polisher, Lens	282
Pool, Hydrotherapy, Tank	295
Power Supply, 725 W, for LAN Switch	23
Power Supply, Ophthalmoscope	278
Power Supply, Uninterruptable, Rack Mounted	22
Press, Flask, Hydraulic, Single Flask	68
Press, Flask, Pneumatic	68
Printer, Cassette Label, Laboratory	235
Printer, Color Laser, Large	255
Printer, Color, Small	255
Printer, Computer	254
Printer, Label, Pharmacy	255
Printer, Slide, Laboratory	235
Printer/Copier/Fax Combination	255
Prism Set, Square, w/Case	281
Processor, Black/White Slide Film, High Capacity	242
Processor, Color Film, High Capacity	242
Processor, Color Slide Film, High Capacity	241
Processor, Computed Radiography Plate	376
Processor, Film, 120 Seconds	377
Processor, Film, 150 Seconds	377
Processor, Film, 45 Second Cycle	378
Processor, Film, 90 Seconds	378
Processor, Film, Daylight	370
Processor, Film, Dental	371
Processor, Film, Dental, Automatic, Table Mounted	378
Processor, Photo Film/Prints, Automated	242
Projector, Acuity w/Stand, Wall Mounted Screen	279
Projector, Multimedia/Data	243
Projector, Overhead	164
Projector, Slide, Carousel	243
Projector, Video	244
Prophylaxis Unit, Ultrasonic	74
Proportioner (Blender), Oxygen/Air	247
Protein Analysis System	212
Public Address System	30
Pulley, Triplex	304
Pulmonary Function Analyzer, Portable	246

NOMENCLATURE	PAGE
Pulper/Grinder, Water Fed, Freestanding	194
Pulpit, Chapel	148
Pump, Breast	261
Pump, Continuous, Analgesia (PCA)	268
Pump, Embalming	239
Pump, Enteral Feeding	268
Pump, Intra-Aortic, Balloon	271
Pump, Pneumatic Stocking/Cuff	268
Pump, Pneumatic Tourniquet	268
Pump, Syringe, Infusion	267
Pump, Vacuum, Dental Oven	68
Pump, Vacuum, Laboratory Oven	238
Pump, Volumetric, Infusion, Multiple Line	268
Pump, Volumetric, Infusion, Single Line	268
Purification System, Water	222
Purifier, Air	222

R

Rack And Cage System, Metabolism, 8 Per Unit	365
Rack And Cage, Metabolism, 18 Per Unit	365
Rack, 2SH, 16x16x26 Chamber	338
Rack, 2SH, 20x20x38 CHMBR	340
Rack, 4 Each, Single Cage, Primate	361
Rack, Apron/Gloves, Mobile	373
Rack, Apron/Gloves, Wall Mounted	373
Rack, Bar, Wood, Pipe	353
Rack, Barbell Weight	173
Rack, Cat, 6 Cages Per Rack	364
Rack, Chart, Desk/Table Mounted	253
Rack, Crutch, Wall Mounted	33
Rack, Dumbbell	174
Rack, Excreta Pan	365
Rack, Ferret, 3 Tier, 6 Cages Per Rack	364
Rack, Guinea Pig, 15 Cages Per Rack	364
Rack, Hamster, With 20 Cages	364
Rack, Hat / Coat, Floor Standing	169
Rack, Hat / Coat, Wall Mounted	169
Rack, Magazine, F/S	164
Rack, Magazine, Wall Mounted	164
Rack, Mail Bag	165
Rack, Mobile, Refrigerator/Freezer/Transport	202
Rack, Mortuary, Mobile, Four Tray	270
Rack, Mouse, 4/5 Tier, Incl. 20/30 Cages Per Rack	363
Rack, Pack, Hot/Cold, Wall Mounted	304
Rack, Pamphlet, Wall Mounted	165
Rack, Rabbit, 3 Cages Per Rack	364
Rack, Rabbit, 6 Cages Per Rack	364
Rack, Rodent, 5 or 6 Tier, Including 30 Cages	363
Rack, Storage, Cylinder, Gas	257
Rack, Storage, Food, CRS	203
Rack, Storage, Mobile, Wire, CRS	257
Rack, Tray/Pan, Mobile, CRS, Light/Medium Duty	207
Rack, Wash, Pan/Utensil	206
Rack/Shelving, Mouse, 5 Tier, 25 Cages	363
Rack/Shelving, Rodent, 4 or 5 Tier, 20 Cages	363
Rad Unit, 60 kW, 90/45 or 90/90 Table, Wall Casset	381
Rad Unit, Computerized Tomography, (CT), HP	381
Rad/Fluoro Unit, 65 kW, 12" I.I., 90/15 Table	382
Rad/Fluoro Unit, 80 kW, 15" I.I., 90/90 Table, DIG	382
Rad/Fluoro Unit, 80 kW, 9" I.I., 90/45 Table, DIG	383
Rad/Fluoro Unit, Remote, 80 kW, 90/90 Table	380
Rad/Fluoro/Tomo Unit, Urologic, Digital	383
Radiation-Light Field Analyzer	350
Radio Communication System	267
Radiographic Unit, 65 kW, Non-Tilt Table	380

NOMENCLATURE	PAGE
Radiographic Unit, 80 kW, 90/45 or 90/90 Table	380
Radiographic Unit, 80 kW, Chest, Digital	377
Radiographic Unit, Cephalometric	379
Radiographic Unit, Computerized Tomography (CT)	381
Radiographic Unit, Dental, Panographic	382
Radiographic Unit, Dental, Panographic & Cephalo.	382
Radiographic Unit, Dental, Wall Mounted, 15 mA	382
Radiographic Unit, Dental, Wall Mounted, 7 mA	383
Radiographic Unit, Mammographic	379
Radiographic Unit, Mobile, Battery, 100 mA, 100kVp	377
Radiographic/Fluoro Unit, Angio, Biplane, Digital	380
Radiographic/Fluoro Unit, Cardiac, 100 kW, Digital	380
Radiometer, Laser	359
Radiuscope	279
Rail System , Utility, Gas and Electric	27
Rail, Accessory Mounting, Length As Required	28
Rail, Apron, 4.5" H x W x 2" D	75
Rail, Apron, 4x24x1	40
Rail, Apron, 4x30x1	40
Rail, Apron, 4x36x1	40
Rail, Apron, 4x42x1	40
Rail, Apron, 4x48x1	40
Rail, Apron, 4x54x1	40
Rail, Apron, 4x60x1	41
Rail, MOD, W/MNTD, HX144XD	147
Range, w/Oven, Gas	201
Reader / Printer, Microfilm	162
Reader, Bar Code, Hand Held, With Interface	167
Reader, Microfilm	162
Rear Hinged Cover, for LAN Rack	21
Rear Wire Frame	21
Recorder / Player, Cassette, Video	244
Recorder, Cassette Tape, Audio	163
Recorder, ECG, Long Term, Portable, w/Case	291
Recorder, Esophageal Motility, Ambulator	314
Recorder, Tape, w/Delayed Audio Feedback	240
Recycling System, Formalin	221
Refractometer	218
Refrigerated Room, Mortuary, 3 Cart	336
Refrigerated Room, Mortuary, 4 Cart	336
Refrigerated Room, Mortuary, 5 Cart	336
Refrigerated Room, Mortuary, 6 Cart	336
Refrigerator, 50 Cubic Feet	334
Refrigerator, 14 Cubic Feet	334
Refrigerator, 2 Swing Doors, Shelves, 40 CUFT	333
Refrigerator, 20 Cubic Feet, 70x32x27	334
Refrigerator, 25 Cubic Feet	334
Refrigerator, 45 Cubic Feet, 84x55x35	335
Refrigerator, 5 CUFT	334
Refrigerator, 65 CUFT	335
Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	334
Refrigerator, Biological, SS, 2 Door, 40 Cu Ft	332
Refrigerator, Blood Bank, 2 Glass Do, Dr, 48 Cu Ft	332
Refrigerator, Blood Bank, Glass Do, Dr, 25 Cu Ft	331
Refrigerator, Blood Bank, Undercounter, Drawer	332
Refrigerator, Lab, SS, 2 Door, 6 Shelves	333
Refrigerator, Morgue, 2 Cadaver	335
Refrigerator, Morgue, 4 Cadaver, 76x73x96	335
Refrigerator, Morgue, Side Opening, 3 Cadaver	335
Refrigerator, Passthru, 50 Cubic Feet, 84x53x40	336
Refrigerator, Passthru, 75 Cubic Feet, 84x78x40	336
Refrigerator, Prefab, 320 Cubic Feet, 108x108x108	337
Refrigerator, Rollthru, 40 Cubic Feet	337
Refrigerator, Rollthru, 75 Cubic Feet, 89x67x40	337

NOMENCLATURE	PAGE
Refrigerator, U/C or F/S, 5 Cu Ft	333
Refrigerator/Freezer, 2 Door, 10 Cubic Feet	334
Refrigerator/Freezer, 20 Cubic Feet	335
Refrigerator/Freezer, 40 Cubic Feet	335
Refrigerator/Freezer, Biological, 1 Door	332
Refrigerator/Freezer, Biological, SS, 2 Door	332
Refrigerator/Freezer, Biological,Upright, 18 Cu Ft	332
Refrigerator/Freezer, Explosion Proof, 13 Cu Ft	333
Regulator, Vacuum	247
Relay Rack, Aluminum	21
Repository, Night, With Safe	36
Reprocessor, Renal Dialyzer Cartridge	273
Resin Curing Unit, Visible Light	66
Resuscitator, Bag-Mask, Hand Op, Infant	250
Resuscitator, Bag-Mask, Hand Operated	250
Retinal Imaging System, Fluorosecin/Indocyanine	283
Retinoscope, Streak	280
Rod, Shower Curtain, 1"Diameter, W/Curtain & Hooks	34
Roller, Dough, Pie, Counter Mounted	198
Room, Controlled Environment	233
Room, Controlled Environment, Small	226
Rotator, Mixer	233
Run, Modular, Stainless Steel	365

S

Safe, Collection Agent	168
Safe, F/S, Class 5	168
Safe, Film, X-Ray, 2 Compartment	371
Safe, Storage, Radium	386
Safelight, Darkroom, Ceiling Mounted	383
Safelight, Darkroom, Wall or Bench Mounted	383
Sampler, Air Particulate (Pollen)	245
Sandblaster, Complete	72
Sander, Disk, 12" Wheel	353
Saw, 10 Inch, Tilting Arbor	357
Saw, Band, Meat Cutting	202
Saw, Band, Woodworking	354
Saw, Circular, Woodworking	354
Saw, Hack, Endless Blade	357
Saw, Radial Arm	357
Saw, Scroll, With Stand	357
Scale, Autopsy	231
Scale, Dial or Digital, Benchtop, 250 Lb. Capacity	205
Scale, In-Bed, 400 Pound Capacity	265
Scale, Infant, 0-35 Pounds	265
Scale, Infant, for Incubator	265
Scale, Ingredient, Dial Or Digital	204
Scale, Person Weighing, High Capacity	266
Scale, Roll On, Built In, 2000 Pound Capacity	29
Scale, Roll On, Freestanding, 2000 Pound Capacity	266
Scale, Sit/Stand	266
Scale, Sling Type, Digital Read-Out	266
Scale, Weighing, 300 Pound Capacity	266
Scale, Weighing, Animal, Large	362
Scanner System, Ophthalmic, Topographic	372
Scanner, Bone Density, Full Body	372
Scanner, Document	292
Scanner, Nuclear, SPECT, Dual Head	387
Scanner, Ultrasound, Cardiac (Echo)	372
Scanner, Ultrasound, General Purpose	371
Scanner, Ultrasound, Intravascular	372
Scanner, Ultrasound, Obstetrical, Black & White	372
Scanner, Ultrasound, Pulsed Doppler	372
Scanner, X-Ray Film Digitizer	376
Screen, Privacy, Freestanding	34

NOMENCLATURE	PAGE
Screen, Confessional, Portable	150
Screen, Projection, 144x144, Remote Control	243
Screen, Projection, 50 X 50	243
Screen, Projection, 70x70	243
Screen, Projection, 84x84	243
Screen, Projection, Eye Exam	281
Screen, X-Ray, Protective, Mobile	373
Screen, X-Ray, Protective, Mobile, Adjustable	373
Screening Device, Cystic Fibrosis	215
Screening Device, Newborn Hearing	240
Scrubber, Floor, Automatic, Rechargeable	261
Sealer, Electronic, Blood Bag	252
Sealer, Heat, Plastic Bag, w/Motor, Portable	261
Seat, Toilet, Child, Fold-Down	327
Sensitometer	389
Set, Stations Of The Cross	149
Set, Statue, Chapel	149
Shaker, Platform, Frozen Blood Processing	235
Shaker, Reciprocating	235
Shaker, Rotating, 12 Standard Tubes	235
Shaker, Rotating, 15 Slides	236
Sharpener, Blade, Microtome	237
Sheeter/Moulder, Dough	203
Shelf Unit, Pharmacy, Wall Mtd, 88"Hx24"Wx16"D	120
Shelf Unit, Pharmacy, Wall Mtd, 88"Hx30"Wx16"D	121
Shelf Unit, Pharmacy, Wall Mtd, 88"Hx48"Wx16"D	121
Shelf Unit, Pharmacy, Wall Mtd, 88"Hx48"Wx9"D	120
Shelf, 5" Depth, SS, Surface Mounted	34
Shelf, 8" Depth, SS, Surface Mounted	33
Shelf, Fold Down, Stainless Steel	34
Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	33
Shelves, Pharmacy, Wall Mtd, 88"Hx48"Wx13"D	121
Shelves, Pharmacy, Wall Mtd, Tall, 88"Hx48"Wx16"D	121
Shelving Unit For 20 Hamster Cages	364
Shelving, File, Open, Patient Records	29
Shelving, Storage, 75"H X 36"W X 14"D	258
Shelving, Storage, 77hx36wx18d	258
Shelving, Storage, Beam Block Tray	257
Shelving, Storage, Enclosed	258
Shelving, Storage, Movable Aisle, Manual	28
Shelving, Storage, Movable Aisle, Powered	29
Shelving, Storage, Pallet	258
Shelving, Storage, Solid, CRS,w/Adjustable Shelves	258
Shelving, Storage, Warehouse	258
Shelving, Storage, Wire, CRS, w/Adjustable Shelves	258
Shelving, Wire, Chrome, Mobile, 65x25x26	337
Shield, L Block, Radium Handling	386
Shower Cabinet, Complete	295
Shower Trolley System, Complete	294
Shower, Patient, Psychiatric	324
Shower, Safety, Freestanding, With Eye/Face Wash	324
Shower, Single, Hand-Held	324
Shredder, Paper Heavy Duty	166
Shredder, Paper, Security	166
Shutter, Roll, CRS, With Hood	38
Sigmoidoscope, Fiberoptic, Therapeutic	311
Sigmoidoscope, Video, Therapeutic	311
Signal - Differential Amp. Analyzer	358
Silver Recovery System, 2 Gallon	378
Silver Recovery System, 5 Gallon	378
Silver Recovery System, 6 Gallon, 37x15x14	379
Simulator, Driving, Work Therapy	304
Simulator, Therapy, X-Ray	384
Sink & Locker, Clean Utility, Wall Mtd, 121" W	98

NOMENCLATURE	PAGE	NOMENCLATURE	PAGE
Sink & Locker, Soiled Utility, Wall Mtd, 78"W	97	Spectrophotometer, Fluorescence	232
Sink & Storage, Clean Utility, Wall Mtd, 72" W	97	Spectrophotometer, Infrared, Two Beam	231
Sink & Storage, Soiled Utility, Wall Mtd, 72" W	97	Spectrophotometer, UV/Vis, Basic	232
Sink & Storage, Soiled Utility, Wall Mtd, 96" W	97	Sphygmomanometer, Aneroid, Wall Mounted	266
Sink Area, Staff Lounge, Wall Mtd, 72" W	98	Spirometer, Diagnostic	246
Sink, CRS, 18 Gauge, With Faucet, 11x18x14	59	Spirometer, Monitoring, Hand Held	246
Sink, CRS, 6x12x9	77	Spirometer, Therapeutic	246
Sink, CRS, Drop-In, 7.5hx16wx16d or 7.5hx18wx14d	77	Stacker, Straddle, 127" Lift, 2000 lb Capacity	259
Sink, Cage Washing, SS, Single Compartment, F/S	325	Stainer, Immunostaining System	236
Sink, Cantilevered, Wall Mtd	138	Stainer, Slide, Automatic, Hematology	236
Sink, Cantilevered, Wall Mtd, 24"W x 24"D	138	Stainer, Slide, Batch, Histological	236
Sink, Cook's, 1 Compartment	203	Stand, Basin, CRS, Mobile, Double	317
Sink, Cook's, 2 Compartment	203	Stand, Basin, CRS, Mobile, Single	317
Sink, Cup, Raceway	231	Stand, Bucky, Vertical, Tilt, Automatic	369
Sink, Epoxy Resin, 10x25x15 ID	53	Stand, Dictionary	162
Sink, Epoxy Resin, 11x18x15 ID	53	Stand, IV, Adjustable	267
Sink, Flushing Rim, China, 18x26x22	325	Stand, Injection, Nuclear Medicine	387
Sink, Lead Lined, With Decay Storage	53	Stand, Instrument, Ophthalmic	281
Sink, Mop, Molded Stone, 10x36x24	324	Stand, Jack, Shoe Repair	354
Sink, Plaster, China	324	Stand, Mayo	315
Sink, Pot, Double Compartment, w/Drainboards	183	Stand, Mixer, CRS, 2 Shelf, w/Attachment Pole	200
Sink, Pot, Triple Compartment, w/Drainboards	184	Stand, Projection	161
Sink, Processing, Film, Color, E-6 Type	321	Stand, Test, Radiological Compliance	350
Sink, Processing, Film, Color/Black & White	321	Star Of David, Chapel	149
Sink, Processing, Photographic Print	321	Starter Unit, Meal Tray Assembly Line, CRS	207
Sink, SS, 10x14x10	59	Station, Clean/Dump, Waste, Portable	365
Sink, SS, 18 Gauge, 11x14x14	58	Station, Pathology, Gross	238
Sink, SS, Double Compartment, 10x14x16 ID	52	Station, Picking, Pharm, Straight, Wall Mtd, 144"W	122
Sink, SS, Single Compartment, 10x14x16 ID	51	Station, Picking, Pharm, U-Shape, Free Std, 144x72	123
Sink, SS, Single Compartment, 10x19x16 ID	51	Station, Picking, Pharm, U-Shape, Stor, F/S	123
Sink, SS, Single Compartment, 12x14x16 ID	52	Station, Pneumatic Tube System	38
Sink, SS, Single Compartment, 12x22x16 ID	51	Station, Utility / Rack	348
Sink, SS, Single Compartment, 12x28x16 ID	51	Steamer, Stack, 2 Compartments, Gas Boiler	195
Sink, SS, Single Compartment, 6x12x9 ID	52	Stereotactic Surgical System	376
Sink, SS, Single Compartment, 7.5x12x12 ID	50	Sterilizer, Elec, GV, 1DO, CAB, Small Chamber	337
Sink, SS, Single Compartment, 7.5x14x14 ID	50	Sterilizer, Elec, VAC, 1DO, CAB, 16x16x26 Chamber	338
Sink, SS, Single Compartment, 7.5x16x16 ID	50	Sterilizer, Hydrogen Peroxide Gas, 1.75 cu ft Cham	347
Sink, SS, Single Compartment, 7.5x18x14 ID	50	Sterilizer, Hydrogen Peroxide Gas, 3.5 cu ft Cham	348
Sink, SS, Single Compartment, 7.5x19x16 ID	51	Sterilizer, STM, GV, 1DO, CAB, 16x16x26 Chamber	337
Sink, SS, With Faucet, Standpipe	59	Sterilizer, STM, GV, 1DO, CAB, 24x36x48 Chamber	341
Sink, SS, Without Faucet, 8x14x10	59	Sterilizer, STM, GV, 1DO, CAB, 24x36x60 Chamber	342
Sink, Scrub, Double, Automatic	326	Sterilizer, SURG INSTRU & Dressing, 10" DIA CHMBR	347
Sink, Scrub, SS, 1-3 Bay, With Knee Valve	325	Sterilizer, SURG INSTRU & Dressing, 16X26 CHMBR	347
Sink, Scrub, With Knee Valve, 13.5x22x19	325	Sterilizer, Stm, LAB, 1DO, CAB, 16x16x26 Chamber	338
Sink, Scullery, Triple Compartment	204	Sterilizer, Stm, VAC, 1DO, CAB, 16x16x26 Chamber	338
Sink, Service, Cast Iron	325	Sterilizer, Stm, VAC, 1DO, CAB, 20x20x38 Chamber	339
Sink, Soak, Mobile, 1 Compartment	204	Sterilizer,ELEC,VAC,2DO,RCSD 1WLL, 20x20x38 Cham	340
Sink, Surgeon's Scrub, Vitreous China	325	Sterilizer,Stm,GV,1DO,RCSD, 1WLL, 20x20x38 Chamber	339
Sink, Vegetable Preparation, 2 Compartment	204	Sterilizer,Stm,GV,2DO,RCSD 2WLL, 20x20x38 Chamber	339
Sink, w/Cabinet, Free Standing, 24"W x 24"D	139	Sterilizer,Stm,GV,2DO,RCSD,1WLL, 20x20x38 Chamber	339
Sink, w/Cabinet, Free Standing, 30"W x 24"D	139	Sterilizer,Stm,LAB,1DO,RCSD 1WLL, 24x36x48 Chamber	341
Sink, w/Cabinet, Free Standing, 48"W x 24"D	139	Sterilizer,Stm,VAC,1DO,RCSD 1WLL,24x36x36 Chamber	340
Sink, w/Cabinet, Free Standing, 60"W x 24"D	139	Sterilizer,Stm,VAC,1DO,RCSD 1WLL,24x36x48 Chamber	341
Sink/Drainboard, Dishwashing, Triple Bowl	183	Sterilizer,Stm,VAC,1DO,RCSD 1WLL,24x36x60 Chamber	342
Slicer, Meat, Table	204	Sterilizer,Stm,VAC,1DO,RCSD1WLL,F/M, Large Chamber	348
Slide Cover, Automated	236	Sterilizer,Stm,VAC,1DO,RCSD1WLL,PIT,26x62x42 Cham	349
Soap Dish, With Bar, SS, Recessed	34	Sterilizer,Stm,VAC,2DO,RCSD 1WLL, 24x36x60 Chamber	342
Sofa, Upholstered	154	Sterilizer,Stm,VAC,2DO,RCSD 1WLL, Medium Chamber	339
Soldering Unit, Precision	65	Sterilizer,Stm,VAC,2DO,RCSD 2WLL,24x36x48 Chamber	341
Source,Light, Fiberoptic Headlamp w/Camera Control	312	Sterilizer,Stm,VAC,2DO,RCSD,1WLL, 16x16x26 Chamber	338
Spectrometer, Atomic Absorption, Double Beam	232	Sterilizer,Stm,VAC,2DO,RCSD2WLL,F/M,26x62x42 Cham	349
Spectrometer, Infrared, Single Beam	214	Sterilizer,Stm,VAC,2DO,RCSD2WLL,PIT,26x62x42 Cham	349
Spectrophotometer, Atomic Absorption	232	Stimulator, Neuromuscular	300
Spectrophotometer, Atomic Absorption, Computerized	232	Stimulator, Neuromuscular, Interferential	300

NOMENCLATURE	PAGE	NOMENCLATURE	PAGE
Stimulator, Neuromuscular, Multi-Channel	300	Table, Examination, Proctology, Electro/Hydraulic	320
Stimulator, Neuromuscular, Portable	300	Table, Examination, Treatment, Electro/Hydraulic	320
Stimulator, Transcutaneous Electric Nerve	300	Table, Examination/Treatment, Animal, CRS,33x20x72	362
Stirrer, Hot Plate, Magnetic	233	Table, Examination/Treatment, With Cabinet	318
Stool, Anesthesia, With Back	317	Table, Examination/Treatment, Wood	304
Stool, Operating, Dental, Assistant	66	Table, Food Preparation, CRS, Mobile	205
Stool, Operating, Dental, Doctor	65	Table, Inspection, Linen	161
Stool, Self Adjusting	154	Table, Instrument, Ophthalmic, Adjustable	275
Stool, Step, Retractable Caster	154	Table, Instrument, Straddle	315
Stool, Surgeon, Revolving	275	Table, Instrument/Dressing, Angular	316
Stove, 4 Burner, w/Oven, Microwave	200	Table, Instrument/Dressing, CRS	316
Stove, Household, 4 Burner, w/Oven, Electric	200	Table, Instrument/Dressing, CRS, approx. 36x20x34	316
Stretcher, MRI Compatible	387	Table, Instrument/Dressing, Mobile	316
Stretcher, Mobile, CRS, 9 Position	269	Table, Machine, CRS	205
Stretcher, Mobile, CRS, Tapered Head Section	269	Table, Microscope, 1-2 Person	210
Stretcher, Recovery, Labor	269	Table, Microscope, Teaching, 3-5 Person	210
Stretcher, Recovery, Surgical	269	Table, Minor Surgery, Pedestal, 4 Section, Mobile	319
Stretcher, Transport, Cadaver	269	Table, Mobile	162
Suction Apparatus, Dental	67	Table, Multiple Instrument, Ophthalmologic, Revolv	275
Suction Unit, Endoscopy	312	Table, Occasional, Executive, Wood	159
Surfacer, Lens, Cylinder, 2 Spindle, Automatic	282	Table, Occasional, Lamp, 20 x 27 x 27	160
Suspension Unit, Utility, Ceiling, Microsurgery	317	Table, Office, (size as required)	160
Sweeper, Street	360	Table, Office, Round	161
Switch, Local Area Network (LAN)	23	Table, Operating, 5 or 6 Section, Trauma	321
Switching Module, Desktop, Fast Ethernet	23	Table, Operating, Fracture, Orthopedic	320
Switching Module, MM Fiber,Gigabit Ethernet Server	23	Table, Operating, Pedestal, 5 Section	320
Switching Module, SM, Gigabit Ethernet Server	23	Table, Operating, Remote Control	320
System, Camera, Gamma, Mobile	387	Table, Operating, Spinal	321
System, Esophageal Motility Recording	314	Table, Operating, Veterinary, Hydraulic	362
System, Phacofragmentation (Cusa)	281	Table, Overbed	284
System, Reverse Osmosis, Water	273	Table, Ping Pong, Folding	161
System, Reverse Osmosis, Water, Mobile	273	Table, Pool	161
System, Stress Exercise, w/Treadmill	301	Table, Procedure, Urological	320
System, Thermoluminescence Dosimetry	389	Table, Process, Adj Height, 10 Drawer, 60"W x 24"D	137
System, Uptake, Thyroid, Mobile	387	Table, Process, Adj Height, 15 Drawer, 72"W x 24"D	138
System, Vacuum Forming	356	Table, Process, Adj Height, 20 Drawer, 72"W x 36"D	138
		Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	137
		Table, Process, Adj Height, 5 Drawer, 60"W x 24"D	137
		Table, Process, Adj Height, 9 Drawer	138
		Table, Process, Adj Height, Mbl, 10 Drwr,60"Wx24"D	137
		Table, Sacrament	148
		Table, Tilt	305
		Table, Traction, Physical Therapy	305
		Table, Treatment, Hi/Lo	305
		Table, Treatment/Casting, Heavy Duty	318
		Table, Typing, Mobile	162
		Table, Work, 2 Drawer	160
		Table, Work, 60W x 30D	160
		Table, Work, 60W x 48D	161
		Table, Work, Adult, Stand-In	355
		Table, Work, Stainless Steel	184
		Table, Work, Standup, 37 X 60 X 30	161
		Table, Work, w/Storage, Pharm, Wall Mtd, 48"W	122
		Table, Writing	159
		Tabletop, Decontamination	269
		Tank Assembly, Boilout	58
		Tank Assembly, Curing	58
		Tank Assembly, Washout/Boilout	59
		Tank, Replenishing	384
		Telecommunication Outlet	24
		Telemetry System, ECG	292
		Telemetry System, ECG, Ambulatory, Multi-Channel	273
		Telephone, Desk, 1 Line	24
		Telephone, Desk, Multiple Line	24
T			
TV/VCR Combination	245		
Tabernacle, Chapel	148		
Table, Autopsy, Mbl, w/Stationary Service Center	238		
Table, Autopsy, Stationary-Elevating	238		
Table, Autopsy, Stationary-Fixed-Height	238		
Table, Autopsy/Dissecting, Tank, CRS	238		
Table, Bakers, w/Shelf	205		
Table, Balance, Marble	251		
Table, Breast Biopsy	379		
Table, Breast Biopsy, Floating Top	379		
Table, Casting	318		
Table, Child's	160		
Table, Chiropratic	319		
Table, Coffee	160		
Table, Computer, Medium Size	159		
Table, Computer, Small	159		
Table, Computer, With Print Shelf	159		
Table, Conference, Wood	160		
Table, Cook's, w/Pan Rack, 96x36x36	205		
Table, Cook's, w/Pan Rack, 96x72x36	205		
Table, Cutting, Meat	205		
Table, Diaper Changing, Wall Mounted	30		
Table, Dining	161		
Table, Drafting	160		
Table, Exam, CRS, 2 Section	319		
Table, Exam, Orthopedic	319		
Table, Exam, Pediatric, With Scale	318		

NOMENCLATURE	PAGE
Telephone, Desk, With Speaker	24
Telephone, Wall Mounted, 1 Line	24
Telephone, Wall Mounted, 1 Line, With Speaker	24
Telephone, Wall Mounted, Multi-Line, Cordless	25
Telephone, Wall Mounted, Multi-Line, With Speaker	25
Telephone, Wall Mounted, Multiple Line	24
Telephone, Wall Mounted, Waterproof	25
Television, Color, 20" Diagonal	244
Television, Color, 27", w/stand	164
Television, Color, Bedside	244
Television, Plasma	245
Tempering Unit, Heat, Lens	282
Tenderizer, Meat, Electric	206
Tent, Mist, Aerosol or Oxygen	250
Test Set, Vision, Worth, Binocular	280
Tester, Visual Acuity, Video/Microprocessor Based	279
Therapy Feedback Unit	301
Therapy Unit, Hydroculator	298
Thermometer, Electronic	294
Tissue Processor, Automatic, 2 Level	237
Tissue Processor, Electron Microscopy	237
Tissue Processor, Vacuum	212
Toaster, Conveyor, 1000 Slices/Hr, Gas	206
Toaster, Conveyor, 480 Slices/Hr, Electric	206
Toaster, Conveyor, 600 Slices/Hr, Electric	206
Toaster, Pop-Up, 4 Slice, Electric	206
Toilet, Wall Hung, Siphon Jet	327
Toilet, Wall Hung, Siphon Jet, Psychiatric	328
Tonometer, Applanation	279
Tonometer, Noncontact	279
Tools, Woodworking, With Cabinet	360
Top, Crib, Safety	284
Torch, Casting/Soldering, Dental	72
Torch, Welding/Cutting, W/Ac	359
Track, Cubicle, Surface Mounted, With Curtain	34
Track, Drapery, Ceil/Wall Mntd, Sngl Channel Cord	34
Track, IV, Ceiling Mounted, 4 Foot	29
Track, IV, Ceiling Mounted, 7 Foot	29
Track, IV, Oval, Ceiling Mounted, 4' x 7'	29
Traction Unit, Hydraulic, Low Back	305
Traction Unit, Portable	305
Transcription Unit, Standalone	165
Transilluminator, Neonatal	248
Transport Cart, Meal Tray, 2 Door, Standard Height	179
Transport Cart, Meal Tray, 3 Door, Standard Height	179
Transport Cart, Meal Tray, Heated, Large	178
Transport Cart, Meal Tray, Low Profile	207
Transport Cart, Meal Tray, w/Beverages	179
Transporter, Locker, Supply, 27"W x 25"D	142
Transporter, Rack, Horizontal, Automatic	345
Trap, Plaster, Small	326
Tray, Body, Fiberglass or Plastic	270
Treadmill, Electric	306
Treadmill, Weight Bearing System	306
Treatment System, Occup/Phys Ther, Computer Assist	304
Treatment, Sink, Workcenter, Cart, Wall Mtd, 105"W	96
Treatment, Sink, Workcenter, Wall Mtd, 120" W	95
Trimmer, Model, Dental, 1/4 HP	73
Trimmer, Model, Dental, Dual Wheel	74
Truck, Hand, 2 Wheel	259
Truck, Hydraulic Lift, Electric	259
Truck, Platform, 4 Wheel	259
Tub/Shower, Combination, Pediatric	322
Tympanograph, w/X-Y Recorder	240

NOMENCLATURE	PAGE
Typewriter, Electric	255
U	
Ultracentrifuge	220
Ultrasonic Treatment Unit	302
Ultrasonic Unit, Patient Treatment	302
Ultrasonic Unit, Treatment	302
Ultrasound/Neuromuscular Stimulation Combo Unit	300
Uninterruptible Power Supply, Single Phase	39
Uninterruptible Power Supply, Three Phase	38
Unit, Exam, Eye, w/Motor Chair, Phoropter	280
Urinal, Wall Hung	326
Urn, Coffee, 2 Section, 10 Gallons Each, Gas	208
Urn, Coffee, 2 Section, 10-15 Gallons Ea, Electric	208
Urn, Coffee, 2 Section, 10-15 Gallons Each, Steam	208
Urn, Coffee, 2 Section, 3 Gallons Each, Electric	207
Urn, Coffee, 2 Section, 6 Gallons Each, Steam	207
Urn, Coffee, 2 Sections, 6 Gallons Each, Electric	207
Urodynamic Measurement System w/Video	270
Utility Center, Dental, Wall or Floor Mounted	71
Utility Center, Plumbing Connection	326
V	
Vacuum, Wet/Dry, HEPA Filtration	261
Valve, Air, Needle Control	74
Valve, Control, Water	74
Valve, Gas, Needle Control	74
Valve, Mixing, Thermostatic	323
Valve, Rinse, Bedpan, With Disinfectant Injector	322
Valve, Water, Foot, With Faucet	59
Vault, With Day Gate, Built In	29
Ventilator, High Frequency, Adult	249
Ventilator, High Frequency, Infant	249
Ventilator, High Frequency, Transport	249
Ventilator, ICU, Adult	249
Ventilator, ICU, Neonatal/Pediatric	249
Ventilator, Portable	249
Ventilator, Transport	250
Vibrator, Dental, Heavy Duty	73
Vibrator, Dental, Standard Duty	73
Video Conferencing System	244
View Box, RH Typing	230
Viewer, Spot, High Intensity	377
Viscometer	233
Vise, Bench/Pipe, Swivel Base, 5 Inch Jaw	360
Vise, Machinists', Swivel Base	360
W	
Wardrobe, Patient Clothing	157
Wardrobe, Television	158
Wardrobe, Vestment, Built In	150
Warmer, Blood	317
Warmer, Blood, High Volume	318
Warmer, Infant, Mobile	248
Warmer, Slide	231
Warmer, Spectacle, Plastic	281
Warming Unit, Patient, Automatic/Manual, Air	271
Washer, Bedpan, CW/STM, WLL MNTD	348
Washer, Cart & Utensil, 2 DO, PIT MNTD, RCSD 2 WLL	347
Washer, Cart, Automatic, Electric And Steam	209
Washer, Clothes, Automatic	260
Washer, Fiber Scope	346
Washer, Garbage Can, Pedestal, Steam	209
Washer, Labware, Electric, Under Counter	229
Washer, Labware, Steam, approx. 80x39x31	229
Washer, Multi-Chamber (4), Automated	343

NOMENCLATURE	PAGE	NOMENCLATURE	PAGE
Washer, Multi-Chamber (5), Automated	343	Workstation, Corner Work Surf, Free Stand, 72x72	83
Washer, Pipette, Automatic, 22-1/4hx10-3/8dia	229	Workstation, Corner Work Surf, Free Stand, 72x96	85
Washer, Pot/Pan, Electric	209	Workstation, Corner Work Surface, Wall Mtd, 72x48	79
Washer, Pot/Pan, Steam And Electric	209	Workstation, Corner Work Surface, Wall Mtd, 72x72	80
Washer, Pressure w/Sanitizer	208	Workstation, Corner Work Surface, Wall Mtd, 72x96	81
Washer, Pressure, Mobile w/Sanitizer	179	Workstation, Corner w/Peds, Free Standing, 72x72	83
Washer, Pressure, Veterinary, Hot Water	362	Workstation, Dental Lab, Acrylic Curing	63
Washer, Print, Automatic, Drum or Tilt/Rock	242	Workstation, Dental Lab, Acrylic Processing	62
Washer, Tray, Automatic Stacking, Electric	208	Workstation, Dental Lab, Casting	62
Washer/Disinfecter, STM, 1DO, CAB, 23X19X24 Cham	344	Workstation, Dental Lab, Ceramic, Modular	61
Washer/Disinfecter, STM, 1DO, CAB, 26X24X24 Cham	343	Workstation, Dental Lab, Die Trimming	63
Washer/Disinfecter,STM,1DO,RCSD1WLL,23X19X24 Cham	344	Workstation, Dental Lab, Equipment Bench	62
Washer/Disinfecter,STM,1DO,RSCD1WLL,26X24X24 Cham	344	Workstation, Dental Lab, Floor Standing	61
Washer/Disinfecter,STM,2DO,RCSD1WLL,23X19X24 Cham	343	Workstation, Dental Lab, Four Station	61
Washer/Disinfecter,STM,2DO,RCSD1WLL,26X24X24 Cham	345	Workstation, Dental Lab, Investment	62
Washer/Disinfecter,STM,2DO,RCSD1WLL,LDG/UNLDG STA	344	Workstation, Dental Lab, Metal Grinding	61
Washer/Pasteurizer, Vertical Rotation, Combination	346	Workstation, Dental Lab, Microblasting	62
Washer/Sanitizer, Cage, Large	363	Workstation, Dental Lab, Plaster	63
Washer/Sanitizer, Cage, Steam	363	Workstation, Dental Lab, Polishing, 2 Station	63
Waste Disposal Unit, Sharps	32	Workstation, Dental Lab, Polishing, Single	64
Waste Disposal Unit, Sharps w/Glove Dispenser	32	Workstation, Dental Lab, Receiving	60
Water Closet, Lavatory, Combination, Module	327	Workstation, Dental Lab, Surveying / Milling	62
Wattmeter, Ultrasonic	359	Workstation, Endoscopy Video Documentation	312
Weight Set, Calibration, 1 mg to 100 gm	251	Workstation, Hematology Lab, Medium	116
Weight Set, Calibration, 100 gm to 1 kg	251	Workstation, Hematology Lab, Minimal	109
Weight Set, Exercise, Barbell Plate	174	Workstation, Hematology Lab, Small	112
Weight Set, Exercise, Dumbbell	174	Workstation, Histopathology Lab, Medium	118
Welder, Arc	360	Workstation, L-Shaped w/Files, Free Stand, 72x120	85
Welder, PVC Blood Tubing, Sterile Process	217	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	82
Welder, Tack, Orthodontic	64	Workstation, L-Shaped w/Peninsula, Wall Mtd, 72x72	80
Wheel, Kick, Potter's, 34x30x33	355	Workstation, L-Shaped w/Table, Wall Mounted, 72x60	79
Wheel, Potters	303	Workstation, L-Shaped, Free Standing, 72x72	84
Wheelchair, MRI	390	Workstation, L-Shaped, Freestanding, 72x48	82
Wheelchair, Patient Transport, Folding	270	Workstation, L-Shaped, Wall & Panel Mounted, 72x90	81
Whirlpool, Arm, Pedestal Mounted	296	Workstation, L-Shaped, Wall Mounted, 72x60	79
Whirlpool, Extremity, Floor Mounted	296	Workstation, L-Shaped, Wall Mounted, 72x72	80
Whirlpool, Extremity, Mobile, Large	297	Workstation, L-Transaction 48, Free Stand, 96x72	84
Whirlpool, Full Body, Mobile	297	Workstation, L-Transaction 72, Free Stand, 72x96	84
Whirlpool, Leg, CRS, Floor Mounted	297	Workstation, L-Transaction 72, Free Std, 72x72	82
Whirlpool, Leg, Floor Mounted	297	Workstation, Microbiology Lab, Medium	119
Whirlpool, Mobile, Extremity, Medium	296	Workstation, Microbiology Lab, Small	113
Whiteboard / Projection Screen, Cabinet	167	Workstation, Shipping/Receiving Lab, Medium	117
Whiteboard, Dry Erase	167	Workstation, Shipping/Receiving Lab, Minimal	109
Whiteboard, Projection Screen Combination	168	Workstation, Shipping/Receiving Lab, Small	112
Whiteboard, With Sliding Panels.	168	Workstation, Straight, Dbl Sided, Free Std, 75" W	89
Window, Observation, One Way	33	Workstation, Straight, Free Standing, 48" W	88
Work Station, Computer, Retractable, Wall Mounted	253	Workstation, Straight, Free Standing, 60" W	88
Workbench, 2 Drawer	353	Workstation, Straight, Free Standing, 72" W	88
Workbench, Adjustable Height, Hydraulic	355	Workstation, Tech, Dental, Lab, Single Station	60
Workbench, Electric, Locker Base	354	Workstation, U-Shaped Peninsula, Free Stand, 72x96	87
Workbench, Fabrication/Maintenance	275	Workstation, U-Shaped, Free Standing, 108x72	86
Workbench, Laminar Flow, Mobile, 4 Feet	366	Workstation, U-Transact 72 w/Cab, Free Std, 72x84	87
Workcenter, Computer, Free Standing, 48" W	78	Workstation, U-Transaction 72, Free Stand, 108x72	86
Workcenter, Computer, Free Standing, 60" W	78	Workstation, Urinalysis Lab, Medium	116
Workcenter, Computer, Free Standing, 72" W	78	Workstation, Urinalysis Lab, Minimal	108
Workcenter, Med Prep, w/Sink, Wall Mtd, 117"W	96	Workstation, Urinalysis Lab, Small	111
Workcenter, Trauma, w/Sink, Wall Mtd, 171" W	96	Workstation, Microbiology Lab, Minimal	110
Workstation Blood Bank/Serology Lab, Small	114	Worksurface, Computer, O/H Cab, Wall Mtd, 48" W	92
Workstation, Blood Bank Lab, Medium	119	Worksurface, Computer, O/H Cab, Wall Mtd, 72" W	92
Workstation, Chemistry Lab, Medium	115	Worksurface, Computer, O/H Cab, Wall Mtd, 60" W	92
Workstation, Chemistry Lab, Minimal	108	Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 24" W	89
Workstation, Chemistry Lab, Small	110	Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 30" W	90
Workstation, Computer, Enclosed, With Lock	159	Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 48" W	90
Workstation, Computer, Open	159	Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 60" W	91

NOMENCLATURE	PAGE
Worksurface, w/Overhd Cab & Drwrs, Wall Mtd, 72" W	91
Worksurface, w/Overhead Cab, Wall Mtd, 24" W	89
Worksurface, w/Overhead Cab, Wall Mtd, 30" W	90
Worksurface, w/Overhead Cab, Wall Mtd, 48" W	90
Worksurface, w/Overhead Cab, Wall Mtd, 60" W	91
Worksurface, w/Overhead Cab, Wall Mtd, 72" W	91