

**NOT MEASUREMENT
SENSITIVE**

**MIL-STD-1901
22 JANUARY 1992**

MILITARY STANDARD

MUNITION ROCKET AND MISSILE MOTOR IGNITION SYSTEM DESIGN, SAFETY CRITERIA FOR



AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 13GP

MIL-STD-1901

CONTENTS

		Page
Paragraph 1.0	SCOPE	1
1.1	Scope	1
1.2	Applicability	1
1.3	Excluded munitions.	1
2.0	REFERENCED DOCUMENTS	2
2.1	Government documents.	2
2.2	Order of precedence	3
3.0	DEFINITIONS	4
3.1	Sources and interpretation.	4
4.0	GENERAL REQUIREMENTS	6
4.1	Ignition system design.	6
4.2	Hazard analyses	6
4.3	Ignition system	6
4.4	Manual arming	7
4.5	Ignition system safety failure rate	7
4.6	Documentation	7
4.7	Electromagnetic environments	7
4.8	Electronic logic functions	7
4.9	Fail-safe features	7
4.10	Explosive ordnance disposal	8
4.11	Armed or non-armed condition	8
4.12	Design for quality control, inspection & maintenance	9
4.13	Design approval	9
4.14	Reviewing activity	9
5.0	DETAILED REQUIREMENTS	11
5.1	Application guidance	11
5.2	Pyrotechnic trains	11
6.0	NOTES	14
6.1	Intended use.	14
6.2	Additional criteria	14
6.3	Acquisition requirements	14
6.4	Custodian of service-approvals for lead & booster explosives & pyrotechnic materials which are acceptable in-line prior to ignition system arming	14
6.5	Hazard analyses	14
6.6	Subject term (key word) listing	14
6.7	International standardization agreements	15

MIL-STD-1901

1.0 SCOPE

1.1 Scope. This standard establishes design safety criteria for ignition systems used to arm and fire munition propulsion systems.

1.2 Applicability. This standard applies to the design of ignition systems in new exploratory, advanced, engineering and operational system developments. Ignition systems incorporating one or more explosive components shall be subjected to the requirements of this standard in the same manner as those incorporating only pyrotechnic devices unless otherwise noted.

1.3 Excluded munitions. This standard does not apply to the following:

- a. Nuclear weapons systems and trainers.
- b. Flares and signals dispensed by hand held devices.
- c. Pyrotechnic countermeasure devices.

MIL-STD-1901

2.0 REFERENCED DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.3).

SPECIFICATIONS

MILITARY

MIL-I-23659	Initiators, Electric, Design and Evaluation of
MIL-P-46994	Pellets/Granules, Boron/Potassium Nitrate

STANDARDS

FEDERAL

FED-STD-595	Color.
-------------	--------

MILITARY

MIL-STD-331	Fuze and Fuze Components, Environmental and Performance Tests for.
MIL-STD-444	Nomenclature and Definitions in the Ammunition Area.
MIL-STD-461	Electromagnetic Interference Characteristics, Requirements for.
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement of.
MIL-STD-882	System Safety Program Requirements.
MIL-STD-1316	Fuze Design, Safety Criteria for.
MIL-STD-1385	Preclusion of Ordnance Hazards in Electromagnetic Fields, General Requirements for.
MIL-STD-1512	Electroexplosive Subsystems, Electrically Initiated, Design Requirements and Test Methods.

MIL-STD-1901

MIL-STD-1751	Safety and Performance Tests for Qualification of Explosives
MIL-STD-1757	Lightning Qualification Test Techniques for Aerospace Vehicles and Hardware.
DOD-STD-1795	Lightning Qualification of Aerospace Vehicles and Equipment.
DOD-STD-2167	Defense System Software Development.
DOD-STD-2169	High Altitude Electromagnetic Pulse (HEMP) Environment.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia PA 19120-5099.)

2.1.2 Other Government documents. The following other Government documents form a part of this standard to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ADA-086259, Vol 4	Joint Services Safety and Performance Manual for Qualification of Explosives for Military Use.
AFSC DH 1-6	Design Handbook, System Safety.
NAVORD OD 44942	Weapon System Safety Guidelines Handbook.

(Copies of specifications, standards, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

MIL-STD-1901

3.0 DEFINITIONS

3.1 Sources and interpretation. The definitions of MIL-STD-444 generally apply to the ammunition terms used in this standard and the definitions of ADA-086259, Vol. 4 apply to the explosive terms. For interpretation of this standard, the following specific definitions apply:

3.1.1 Armed. An ignition system is armed when the output of a primary explosive, a sensitive pyrotechnic or a firing stimulus can produce ignition system function.

a. An ignition system employing pyrotechnic train interruption (see 5.2.2) is considered armed when the interrupter(s) position (or condition) is ineffective in preventing propagation of the pyrotechnic train at a rate equal to or exceeding 0.5 percent at a confidence level of 95 percent.

b. An ignition system employing a non-interrupted pyrotechnic train (see 5.2.3) is considered armed when the stimulus available for delivery to the initiator equals or exceeds the initiator's maximum no-fire stimulus.

3.1.2 Electric ignition - The activation of the initiator in the pyrotechnic train by direct application of electrical energy.

3.1.3 Enabling. The act of removing or activating one or more safety features which prevent arming, thus permitting arming to occur subsequently.

3.1.4 Environment. A specific physical condition to which the ignition system may be exposed.

3.1.5 Environmental stimulus. A specific stimulus obtained from an environment.

3.1.6 Fail-safe design. A characteristic of an ignition system or part thereof designed to preclude ignition of the propulsion system or hazard to personnel when safety features malfunction.

3.1.7 Firmware. The combination of a hardware device and computer instructions or computer data that reside as read only software on the hardware device. The software cannot be readily modified under program control.

3.1.8 Igniter charge. A source of heat and pressure that actually ignites the motor propellant.

3.1.9 Initiator. The first component used in an explosive/pyrotechnic train.

3.1.10 Ignition safety device (ISD). A device whose purpose is to prevent an unintended functioning of the rocket or missile motor by interruption of the ignition train, interruption of the laser energy or disconnection of the operating circuit.

MIL-STD-1901

3.1.11 Ignition system (IS). The aggregate of devices in a weapon system, including those in the munition, launcher and munition launch platform, which generate and control the operating signal to cause the rocket or missile motor to function.

3.1.12 Independent safety feature. A safety feature is independent if its integrity is not affected by the functioning or malfunctioning of the other safety features.

3.1.13 Interrupted firing train. A pyrotechnic train (see 3.1.21) with elements of the train functionally separated until arming to interrupt the firing path and thus prevent ignition of the motor propellant in the event of unintended initiation of one of the elements upstream.

3.1.14 Laser Ignition. The activation of the initiator by laser energy.

3.1.15 Launch cycle. The sequence of events necessary for normal launch, that occurs between committing the system to launch and the time the system leaves the launcher or launch platform.

3.1.16 Maximum no-fire stimulus (MNFS). The stimulus level at which the initiator will not fire or unsafely degrade with a probability of 0.995 at a confidence level of 95 percent. Stimulus refers to the characteristic(s) such as current, rate of change of current (di/dt), power, voltage, or energy which is (are) most critical in defining the no-fire performance of the initiator.

3.1.17 Pyrotechnic materials. Those energetic materials or compounds which do not ordinarily detonate in their intended function but rather burn or deflagrate. Typical examples include boron potassium nitrate (BKNO₃), black powder, and many metal/oxidant combinations.

3.1.18 Pyrotechnic train. The deflagration train beginning with the initiator and terminating in the motor propellant. For the purposes of this standard, the term pyrotechnic train is used also for those incorporating one or more detonating components in the train.

3.1.19 Safety feature. An element or combination of elements that prevents unintentional arming or functioning.

3.1.20 Safety system failure. A failure of the ignition system to prevent unintentional arming or functioning.

3.1.21 Sensitive pyrotechnics. Sensitive pyrotechnics are used to initiate or ignite other, less sensitive, materials in the firing train. They are used in primers or squibs of ignition systems and are sensitive to ESD, heat, impact, or friction and undergo a rapid exothermic reaction upon initiation.

3.1.22 Sensor, environmental. A component or series of components designed to detect and respond to a specific environment.

MIL-STD-1901

4.0 GENERAL REQUIREMENTS

4.1 Ignition system design. The design of the ignition system shall take into account the aggregate of devices in the weapon system (munition, launcher, and munition launch platform) which generate and control the operating signal to cause the rocket or missile motor to function.

4.2 Analyses. The following analyses shall be performed to identify hazardous conditions for the purpose of their elimination or control.

a. A preliminary hazard analysis shall be conducted to identify and classify, per MIL-STD-882, hazards of normal and abnormal environments, as well as conditions and personnel actions that may occur in the phases before intentional arming of the IS. This analysis shall be used in the preparation of system design, test and evaluation requirements, and in combination with the system hazard analyses and detailed analyses (4.2.b) below, to determine the need to incorporate an Ignition Safety Device (ISD). An ISD shall be incorporated where the design of the pyrotechnic train dictates (see 5.2.2) or when its incorporation is necessary to meet the IS safety failure rate (see 4.5).

b. System hazard analyses and detailed analyses, such as fault tree analyses, and failure mode effects and criticality analyses, shall be conducted to arrive at an estimate of the safety system failure rate and to identify any single point or credible failure modes. These analyses shall include an assessment of the relative sensitiveness of each component in the pyrotechnic train.

c. For the IS containing an embedded microprocessor, controller or other computing device, the analyses shall include a determination of the contribution of the software (see 4.8) to the enabling of a safety feature.

d. Where the software is shown to directly control or remove one or more safety features, a detailed analysis and testing of the applicable software shall be performed to assure that no design weaknesses, credible software failures, or credible hardware failures propagating through the software can result in compromise of the safety features.

4.3 Ignition system. In order to preclude unintended ignition system arming or initiation, the ignition system shall:

a. inhibit the arming sequence except as a consequence of a valid launch or confirmation of launch intent.

b. not be susceptible to common-mode failures.

c. not contain any single-point failure mode prior to or at the initiation of the arming cycle.

d. delay, based on the overall ignition system firing timeline, initiation of the arming cycle within appropriate operational tolerances.

MIL-STD-1901

e. utilize environmental forces, whenever possible, to enable safety feature(s). When the IS utilizes stored energy to enable the safety feature(s), the stored energy source shall not be integral to the IS unless it can be demonstrated that it is impractical to do otherwise and that the required safety failure rate (see 4.5) can be achieved.

4.4 Manual arming. The ignition system shall not be capable of being armed manually unless such capability is required by operational conditions and is specifically approved by the responsible reviewing activity of 4.14. Such systems shall be capable of being easily returned to a safe condition under the conditions of deployment.

4.5 Ignition system safety failure rate. The safety failure rate of the IS shall be calculated by performing a safety analysis (see 4.2) and shall be verified to the extent practicable by test and analysis. As a minimum requirement, the safety failure rate shall not exceed one failure in one million prior to intentional initiation of the arming sequence.

4.6 Documentation. The evaluation program used as the basis of the safety assessment which is prepared by the developing agency shall be documented in both detail and summary form.

4.7 Electromagnetic environments. ISs, in their normal life cycle configurations, shall not inadvertently arm or function during and after exposure to: electromagnetic radiation (EMR), electrostatic discharge (ESD), electromagnetic pulse (EMP), electromagnetic interference (EMI), lightning effects (LE), or power supply transients (PST). In addition, ISs shall not exhibit unsafe operation during and after exposure to the above environments. ISs shall be tested or evaluated for:

- a. EMR - per MIL-STD-1385 and MIL-STD-1512
- b. ESD - per MIL-STD-331
- c. EMP - per DOD-STD-2169
- d. EMI - per MIL-STD-461 and MIL-STD-462
- e. LE - per DOD-STD-1795 and MIL-STD-1757
- f. PST - per appropriate test and analysis

4.8. Electronic logic functions. Any electronic logic related to safety functions performed by the IS shall be embedded as firmware or hardware. Firmware devices shall not be erasable or alterable by credible environments which the IS would otherwise survive.

4.9 Fail-safe features. ISs shall incorporate fail-safe features based on munition requirements.

MIL-STD-1901

4.10 Explosive ordnance disposal. The IS shall incorporate Explosive Ordnance Disposal (EOD) features which insure that, in the event of accidents, extreme/hostile situations, or dud ordnance; EOD personnel can either return the munition to a safe to handle condition or, where necessary, implement field expedient disposal.

4.10.1 EOD reviewing authority. All new or altered designs, or new applications of existing designs shall be presented to the appropriate service's EOD research, development, test and evaluation (RDT&E) authority for technical advice and assistance in determining viable design approaches or trade-offs for EOD as follows:

- a. For Army: Commander
 US Army ARDEC
 ATTN: SMCAR-FSM-E
 Picatinny Arsenal, NJ 07806-5000

- b. For Navy and Commanding Officer
 Marine Corps: Naval Explosive Ordnance
 Disposal Technology Center
 Code 60
 Indian Head, MD 20640-5070

- c. For Air Force Commanding Officer
 ATTN: Detachment 63 AFLC LOC
 Indian Head, MD 20640-5070

4.11 Armed or non-armed condition.

4.11.1 Non-armed condition assurance. The IS design shall incorporate one or more of the following:

- a. A feature that prevents assembly of the IS in an armed condition.

- b. A feature that provides a positive means of determining that the IS is not armed during and after its assembly and during installation into the munition.

- c. A feature that prevents installation of an armed, assembled IS into a munition.

If arming and reset of the assembled IS in tests is a normal procedure in manufacturing, inspection, or at any time prior to its installation into a munition, subparagraph a is not sufficient and either subparagraph b or c must also be met.

4.11.2 Visual indication. If visual indication of the non-armed or armed condition is employed in the IS, visible indicators shall be designed to provide a positive, unambiguous indication of condition. Indicator failure shall not result in a false non-armed indication. If color coding is used to represent condition, the colors and coding shall be as follows:

MIL-STD-1901

a. Non-armed condition. Fluorescent green background with the letter S or word SAFE superimposed thereon in white. Colors shall be nonspecular.

b. Armed condition. Fluorescent red or fluorescent orange background with the letter A or the word ARMED superimposed thereon in black. Colors shall be nonspecular.

c. Suggested color specification.

- 1) Fluorescent green, Color No. 38901 per FED-STD-595
- 2) Fluorescent red, Color No. 38905 per FED-STD-595
- 3) Fluorescent orange, Color No. 38903 per FED-STD-595

4.11.3 Return to non-armed condition. Where arming of the IS is recyclable, the armed IS shall return to the non-armed condition upon removal of the arming energy.

4.11.4 Electrical firing energy dissipation. For electrically initiated pyrotechnic trains, the IS design shall include a feature to dissipate the firing energy whenever an armed IS is returned to the non-armed condition. The dissipation means shall be designed to prevent common mode failures.

4.12 Design for quality control, inspection, and maintenance.

a. The IS shall be designed and documented to facilitate application of effective quality control and inspection procedures. Design characteristics critical to safety shall be identified to assure that the designed safety is maintained.

b. The design of the IS shall facilitate the use of inspection and test equipment for monitoring all characteristics which assure the safety and intended functioning of the fuze at all appropriate stages. The IS design should facilitate the use of automatic inspection equipment.

c. Embedded computing systems and their associated software (firmware) shall be designed and documented for ease of future maintenance. Software development shall be in accordance with accepted high quality software development procedures, such as DOD-STD-2167.

4.13 Design approval. At the inception of engineering development, the developing activity should obtain approval from the cognizant safety authority of both the design concept and the methodology for assuring compliance with safety requirements. At the completion of engineering development, the developing activity shall present a safety assessment to the cognizant safety authority (see 4.14) for review to obtain approval of the design.

4.14 Reviewing activity. New or altered designs, or new applications of approved designs shall be presented to the appropriate service safety review board for a safety evaluation and certification of compliance with this standard:

MIL-STD-1901

- a. Army: Commander
US Army Missile Command
ATTN: AMSMI-SF
Redstone Arsenal, AL 35898

- b. Navy: Chairman, Weapon System Explosives
Safety Review Board
US Naval Sea Systems Command
Washington DC 20362-5101

- c. Air Force: USAF Nonnuclear Munitions Safety Board
ATTN: AFDTC/SES
Eglin Air Force Base FL 32542-5000

MIL-STD-1901

5.0 DETAILED REQUIREMENTS.

5.1 Application guidance. The following detailed requirements shall apply for specific IS designs.

5.2 Pyrotechnic trains.5.2.1 Pyrotechnic or explosive sensitivity (transfer charge-and-igniter pyrotechnics).

a. Only pyrotechnic materials listed in Table I herein and those explosive materials listed in Table I of MIL-STD-1316 are approved by all services for use in a position leading to the initiation of a rocket or missile motor without interruption.

b. Approval by all services must be received by the Chairman, DOD Fuze Engineering Standardization Working Group (see 6.4) before a new material can be added to these tables or before a listed material can be deleted. Approved pyrotechnic and explosive materials shall be qualified in the IS and certified by the associated safety board of 4.14 as acceptable for that IS.

c. The material used in ISs shall not be altered by any means (precipitation, recrystallization, grinding, density changes, etc.) likely to increase its sensitivity beyond that at which the material was qualified and at which it is customarily used, unless it is requalified.

d. Pyrotechnic materials which do not appear in Table I may be utilized physically in-line with the rocket motor prior to IS arming if:

(1) The material is qualified to MIL-STD-1751, as determined by testing, to the requirements of paragraph 5.4 therein, with the exception of paragraph 5.4.5, "Hot Wire Ignition Test," or

(2) For material that does not meet the test requirements of MIL-STD-1751 above, the material shall demonstrate, in comparative tests, sensitivity values equal to or less than Boron Potassium Nitrate (BKNO₃). BKNO₃ shall be tested alongside the proposed material to obtain the comparative values.

TABLE I. Approved Pyrotechnics

<u>Pyrotechnic</u>	<u>Specification</u>
BKNO ₃	MIL-P-46994

MIL-STD-1901

5.2.2 Pyrotechnic train interruption. When the pyrotechnic train contains material(s) other than those allowed by 5.2.1, at least one interrupter (shutter, slider, rotor, for example) shall separate these materials from the balance of the pyrotechnic train until it is removed during ISD arming as a consequence of an intentional initiation of the launch sequence.

5.2.2.1 Methods of restraint. The interrupter(s) shall comply with one of the following methods of restraint.

a. The interrupter(s) shall be directly locked mechanically in the safe position by at least one safety feature. The safety feature shall not be removed prior to intentional initiation of the arming sequence.

b. The interrupter(s) shall be directly restrained mechanically in the safe position by at least one safety feature. The safety feature shall be overcome by the arming energy and shall automatically return the interrupter to a safe position upon removal of the arming energy.

5.2.2.2 Interruption position. If the sensitive element is positioned such that safety is dependent upon the presence of an interrupter, the design shall include positive means to prevent the ISD from being assembled without the properly positioned interrupter. If the sensitive element is positioned such that omission of the interrupter will prohibit pyrotechnic train transfer, a single interrupter is acceptable.

5.2.2.3 Interruption effectiveness. The effectiveness of interruption prior to initiation of the arming sequence shall be determined numerically in accordance with MIL-STD-331, Primary Explosive Component Safety Test or by similar methodologies. The results shall be presented and justified to the appropriate service safety authority.

5.2.3 Noninterrupted pyrotechnic train control. When the pyrotechnic train contains only those materials allowed by 5.2.1, no train interruption is required. Where pyrotechnic train interruption is not incorporated, function energy shall be controlled to preclude unintentional arming and firing. For ignition systems containing function energy prior to intentional arming, at least two energy interrupters, each controlled by an independent safety feature, shall prevent the flow of energy to the initiator until the intent to launch the munition is verified by the IS. Where the design includes energy interrupters, the IS shall not be capable of functioning in the absence of the interrupter(s). The combined probability of having function energy in the IS, having a failure of the energy control feature(s) and firing the initiator with the available function energy shall be compatible with the allowable IS safety system failure rate (see 4.5).

5.2.4 Initiator electrical sensitivity.

5.2.4.1 Noninterrupted pyrotechnic train. The initiator for an electrically fired non-interrupted train shall:

MIL-STD-1901

a. meet the appropriate characteristics listed for Class B initiators of MIL-I-23659.

b. not exhibit unsafe degradation when tested in accordance with MIL-STD-1512.

c. not be capable of being initiated by any electrical potential of less than 500 volts. Deflagration of the initiator is acceptable provided that initiator detonation is required to propagate the pyrotechnic train.

d. Not be capable of being initiated by any electrical potential of less than 500 volts, when applied to any accessible part of the IS after installation into the munition or any munition subsystem.

5.2.4.2 Interrupted pyrotechnic train. Unless otherwise specified, the initiator for an electrically fired interrupted pyrotechnic train shall be qualified to the requirements listed for Class A initiators in MIL-I-23659.

MIL-STD-1901

6. NOTES

This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.

- 6.1 Intended use. This standard establishes specific design safety criteria for ignition systems and ignition safety devices.
- 6.2 Additional criteria. Individual services and service components may issue regulations or instructions which impose additional design safety criteria or add clarifying guidelines (e.g. U.S. Army Fuze Safety Review Board Guidelines for Evaluation of Electronic Safety & Arming Systems, WSESRB Technical Manual for Electronic Safety and Arming Devices with Non-Interrupted Explosive Trains).
- 6.3 Acquisition requirements. Acquisition documents should specify the following:
- a. TITLE, NUMBER and DATE of this standard.
 - b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2).
- 6.4 Custodian of service-approvals for lead and booster explosives and pyrotechnic materials which are acceptable in-line prior to ignition system arming.

Chairman
 DOD Fuze Engineering Standardization Working Group
 U.S. Army Armament Research, Development and Engineering Center
 Attn: SMCAR-AEF-C
 Picatinny Arsenal NJ 07806-5000

- 6.5 Hazard analyses. Techniques for conducting hazard analyses are described in NAVSEA OD44942, AFSC Design Handbook DH 1-6, and Nuc Reg 0492.
- 6.6 Subject term (key word) listing.

Arming, control
 Explosive ordnance disposal
 Explosive train
 Explosive train interruption
 Fail-safe
 Function, premature
 Fuze
 Fuze design, safety criteria for
 Ignition safety device
 Ignition system
 Pyrotechnic train
 Safety and arming device

MIL-STD-1901

6.7 International Standardization Agreements. Certain provisions of this standard are the subject of International Standardization Agreements (ASCC-AIR-STD-20/9, Design Safety Principles for Airborne Weapon Fuzing Systems, STANAG 4187, Fuzing Systems; Safety Design Requirements, and STANAG 3525, Design Safety Principles and General Design Criteria for Airborne Weapon Fuzing Systems, and STANAG 4368, Electric and Laser Ignition Systems for Rockets and Guided Missile Motors - Safety Design Requirements). When change notice, revision or cancellation of this document is proposed which affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels, including departmental standardization offices, if required.

Custodians:

Army-AR
Navy-OS
Air Force-11

Preparing Activity:

Army-AR

Review activities:

Army-MI
Navy-AS
Air Force-18,99

Project 13GP-0016

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

1 RECOMMEND A CHANGE:

1. DOCUMENT NUMBER
MIL-STD-1901

2. DOCUMENT DATE (YYMMDD)
920122

3. DOCUMENT TITLE
MUNITION ROCKET AND MISSILE MOTOR IGNITION SYSTEM DESIGN, SAFETY CRITERIA FOR

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)

b. ORGANIZATION

c. ADDRESS (Include Zip Code)

d. TELEPHONE (Include Area Code)

7. DATE SUBMITTED (YYMMDD)

(1) Commercial

(2) AUTOVON (if applicable)

8. PREPARING ACTIVITY

a. NAME **US ARMY ARDEC
STANDARDIZATION OFFICE**

b. TELEPHONE (Include Area Code)

(1) Commercial
(201) 724-6671

(2) AUTOVON
880-6671

c. ADDRESS (Include Zip Code)

**ATTN: SMCAR-BAC-S
PICATINNY ARSENAL, NJ 07806-5000**

IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:

Defense Quality and Standardization Office
5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466
Telephone (703) 756-2340 AUTOVON 289-2340