

This Military Standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

REVIEW INTEREST:
NAVY - YD
MC
ARMY - MO

		FED. SUP. CLASS 2920
<p>THESE FACES MUST BE IN THE SAME PLANE WITHIN .003 T.I.R.</p> <p>SECTION</p> <p>NOTES:</p> <ol style="list-style-type: none"> MATERIAL: GRAY IRON CASTING, QQ-I-652, CLASS 20 PAINT EXCEPT ON MACHINED SURFACES. ZINC CHROMATE PRIMER AS PER SPEC. TT-P-666 OR TT-P-636 BLACK ENAMEL FINISH AS PER SPEC. TT-E-489 MODIFICATIONS IN OUTSIDE APPEARANCE AND CONSTRUCTION ARE ACCEPTABLE IF UNIT INTERCHANGEABILITY IS NOT AFFECTED REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. ALL DIMENSIONS ARE IN INCHES. 		8 November 1982 24 JUNE 1965 12 SEPTEMBER 1962 29 NOVEMBER 1956 REVISED
<p>P.A. MO ERDL Other Cust N YD</p> <p>TITLE END BELL, ELECTRICAL ROTATING EQUIPMENT, DRIVE END, (GENERATOR, ENGINE-ACCESSORY, 28-VOLT, 18-AMP)</p> <p>PROCUREMENT SPECIFICATION MIL-G-12604</p> <p>SUPERSEDES</p>		<p>MS PART NO. 13819-1</p> <p>MILITARY STANDARD</p> <p>MS13819</p> <p>SHEET 1 OF 1</p>

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.