

REVIEW ACTIVITY : DCSC, 69
USER ACTIVITY : YD, ATAC

		FED. SUP CLASS 2805
<p>NOTES:</p> <ol style="list-style-type: none"> 1. MATERIAL: COPPER-LEAD LINING, S.A.E. NO. 49 ON STEEL, S.A.E. NO. 1008 OR 1010 2. PLATING: LEAD-TIN PLATE I.D. (6% MIN. TIN) TO A THICKNESS .001 NOMINAL. FLASH-TIN PLATE ALL OVER AFTER LEAD-TIN PLATE. 3. IN 2.901 DIA. INSPECTION BLOCK WITH ONE PARTING LINE FACE AGAINST A STOP AT HORIZONTAL CENTER LINE OF BLOCK AND A PRESSURE OF 2020 LBS. ON OTHER P.L. FACE. HEIGHT WILL BE 1.4515-1.4525 ON SIDE OPPOSITE STOP. 4. REMOVE ALL BURRS. 5. MS PART NUMBER AND PART MANUFACTURER'S IDENTIFICATION TO BE CLEARLY MARKED WITHOUT INTERFERING WITH THE FUNCTION OF THE PART. 6. TOLERANCES: UNLESS OTHERWISE SPECIFIED, LINEAR MACHINED DIMENSIONS $\pm .010$; ANGULAR MACHINED DIMENSIONS $\pm 30^\circ$. DO NOT SCALE DRAWING. 7. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. 8. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID. 9. ALL DIMENSIONS IN INCHES. 		
<p>P.A. ARMY MO(ERDL) Other Cust A.F. - 69 NAVY - YD</p>		<p>APPROVED 24 OCTOBER 1955 REVISED 7 MAR 1966 15 APRIL 1982</p>
<p>TITLE BEARING, SLEEVE: ENGINE, PLAIN, 2-3/4" X 1-1/2"</p>		<p>PART NO. MS 13922-1</p>
<p>PROCUREMENT SPECIFICATION MIL-E-11275</p>		<p>SHEET 1 OF 1</p>
<p>DD FORM 672-1 (Coordinated)</p>		<p>PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.</p>

This Military Standard has been approved by the Department of Defense and is mandatory use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.