



This military standard is approved by NAVAL AIR SYSTEMS COMMAND.
 Dead weight of the Navy and still be used by
 the military. All other military ac. are required
 to 4- day this standard who is suitable

DD FORM 672-1 (Limited circulation)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PROJECT NO 5975-5532

PLATE NO 28811

 22 AUG 1972
 REVISED (A) 8 SEP 1972 (B) 2 JAN 1973 (C) 17 JUNE 1973 (D) 31 JANUARY 1975 (E) 18 FEB 77

FED SUP CLASS
5075**NOTES:**

1. MATERIAL- 16 GAUGE CRS.
2. DOOR SHALL HAVE 2 DOUBLE ROWS OF LOUVERS, 6 INCHES WIDE, 3/4 INCH HIGH WITH 1 INCH SPACE BETWEEN LOUVERS. EACH LOUVER SHALL HAVE APPROXIMATELY 1 3/4 SQUARE INCHES OF OPENING
3. FINISH- SHALL BE IN ACCORDANCE WITH MIL-STD-808 AND COLOR PER FED-STD-595, GREEN COLOR NO 24300. HARDWARE SHALL BE IN ACCORDANCE WITH QQ-P-416, TYPE II, CLASS 1, CADMIUM PLATE UNLESS OTHERWISE NOTED
4. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES.
5. DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED, TOLERANCES FRACTIONS $\pm 1/32$
6. DOOR SHALL BE OF WELDED CONSTRUCTION.
ALL WELDING SHALL BE IN ACCORDANCE WITH MIL-W-8811
7. DOOR SHALL BE SUPPLIED COMPLETELY ASSEMBLED WITH HANDLE, LOCK, HINGE PIN BRACKET, LATCH, WEATHERSTRIP, LATCH PLATE AND ALL NECESSARY HARDWARE, TO INSTALL ON VERTICAL AND TURRET PROJECTED TOP RACKS.
8. EXAMPLE OF PART NUMBER

MS 14127 -1 L

LEFT HAND HINGED DOOR

SIZE DASH NUMBER

BASIC PART NUMBER

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

22 AUG 1972
REVISED (A) 8 SEP 1972 (E) FOR CHANGES SEE SHEET 1

P A NAVY - AS Other Code	TITLE DOOR, FACE MOUNTED	MILITARY STANDARD
		MS 14127(AS)
PROCUREMENT SPECIFICATION	SUPERSEDES	SHEET 2 OF 2

DD FORM 672-1 (Limited circulation)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PLATE NO. 32071

This military standard is governed by MIL-STD-883C, and SYSTEMS STANDARD, Department of the Navy and shall be used by that activity. All other military activities are required to employ this standard where applicable.