

INCH-POUND

MS14181C
AMENDMENT 1
19 JUNE 1998

MILITARY SPECIFICATION SHEET

BOLT, TENSION, NICKEL ALLOY 718, 220 KSI Ft_u,
EXTERNAL WRENCHING, SPLINE DRIVE, FLANGED HEAD

This amendment forms a part of MS14181C, dated 30 January 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

NOTE 7. Fourth sentence, after "PASSIVATION" add: "WITH DRY FILM LUBRICANT."

NOTE 7. After last sentence, add: "NO CODE AFTER GRIP LENGTH DASH NUMBERS INDICATES PASSIVATION ONLY."

NOTE 8. In third example of part number, after "UNDRILLED HEAD" add: ",PASSIVATED." Delete: "(INACTIVE FOR NEW DESIGN)"

NOTE 8. In fourth example of part number, after "DRILLED HEAD" add: ",PASSIVATED." Delete: "(INACTIVE FOR NEW DESIGN)"

Custodians:

Army - AV
Navy - AS
Air Force - 99

Preparing Activity:

DLA-IS

(Project 5306-2050)

AMSC N/A

FSC 5306

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.