

USER ACTIVITIES
NAVY-OS, SH

REVIEWED ACTIVITIES
AIR FORCE - 84
DLA-15

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for replacement use shall be made from this document.




TABLE I. DASH NUMBERS.

DASH NO	A	TEMPER
001	.034	0
003	.034	15
005	.109	0
007	.109	15
009	.125	0
011	.125	15
013	.141	0
015	.141	15
017	.156	0
019	.156	15
021	.172	0
023	.172	15
025	.188	0
027	.188	15
029	.203	0
031	.203	15
033	.219	0
035	.219	15
037	.234	0
039	.234	15
041	.250	0

DASH NO	A	TEMPER
043	.250	15
045	.266	0
047	.266	15
049	.281	0
051	.281	15
053	.297	0
055	.297	15
057	.313	0
059	.313	15
061	.328	0
063	.328	15
065	.344	0
067	.344	15
069	.359	0
071	.359	15

FED. SPEC CLASS
9525

APPROVED 29 Feb 1984 REVISED

P. A. Other Cost	AS MR 99	INTERNATIONAL INTEREST	TITLE WIRE, ROUND, NONELECTRICAL ALUMINUM ALLOY 7075	MILITARY STANDARD MSI4275
PROCUREMENT SPECIFICATION QQ-A-225			SUPRESEDED	PAGE 1 OF 2

DD FORM 672-1 (COORDINATED)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

9525-0084

USER ACTIVITIES:
NAVY-OS, SH

REVIEWER ACTIVITIES
AIR FORCE-84
DLA-IS


This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

FED. SUP CLASS
9525

REQUIREMENTS:

1. MATERIAL. ALUMINUM ALLOY 7075, (UNS A97075), AS SPECIFIED IN QQ-A-225/a.
2. FORMING PROCESS. DRAWN.
3. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS14275D001



4. MARKING. ALUMINUM AND ALUMINUM ALLOYS SHALL BE MARKED WITH THE PRODUCER'S NAME OR REGISTERED TRADE MARK, THE PART NUMBER (MILITARY STANDARD (MS) NUMBER PLUS THE APPLICABLE DASH NUMBER), AND THE LOT NUMBER, AND THIS MARKING SHALL BE APPLIED IN ACCORDANCE WITH FED-STD-184.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. STANDARD LENGTH OF WIRE FOR TEMPER "T4" AND "T6" IS 12 FEET NOMINAL, STANDARD LENGTH OF WIRE FOR TEMPER "O" IS 200 LB SPOOLS NOMINAL.
3. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
4. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

APPROVED 29 Feb 1984 REVISED

P. A. Other Cost	AS MR 99	INTERNATIONAL INTEREST	TITLE WIRE, ROUND, NONELECTRICAL ALUMINUM ALLOY 7075	MILITARY STANDARD MS14275
PROCUREMENT SPECIFICATION QQ-A-225			SUPERSEDES:	PAGE 2 OF 2