

USER ACTIVITIES:
NAVY- MC, OS, SH

REVIEWER ACTIVITIES:
AIR FORCE -84
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.





TABLE I. DASH NUMBERS.

DASH NO	A	B	C	TEMPER	FORMING PROCESS
001	144	48	.160	T6	R
003	144	48	.056	T6	R
005	144	48	.036	T6	R
007	144	48	.112	T6	R

REQUIREMENTS:

- MATERIAL. ALUMINUM ALLOY 7075, (UNS A97075) AS SPECIFIED IN QQ-A-250/13.
- FORMING PROCESS. ROLLED (CODE R).
- PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS14359R001



- MARKING. ALUMINUM AND ALUMINUM ALLOYS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-184 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

- ALL DIMENSIONS ARE IN INCHES.
- REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
- FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

APPROVED 22 May 1984 REVISED

P. A. Other Cust	AS MR 99	INTERNATIONAL INTEREST	TITLE SHEET, ALUMINUM ALLOY ALCLAD 7075	MILITARY STANDARD MSI4359
PROCUREMENT SPECIFICATION QQ-A-250		SUPERSEDES:		PAGE 1 OF 1