

USER ACTIVITIES  
ARMY - ME


TABLE I. DASH NUMBERS AND DIMENSIONS.

DASH NUMBER	A NOMINAL SIZE INCHES	B NOMINAL SIZE INCHES	C NOMINAL SIZE FEET	CONDITION	ADDITIONAL <sup>1/</sup> REQUIREMENTS
-001	.188	48	8	ANNEALED	po or sb
-003	.281	48	8	ANNEALED	af
-005	.312	48	8	ANNEALED	po or sb
-007	.750	36	10	ANNEALED	af
-009	1.250	48	8	ANNEALED	po or sb

<sup>1/</sup> SEE REQUIREMENT 3

REQUIREMENTS:

- MATERIAL. STEEL, CORROSION RESISTANT, TYPE 302 (UNS S30200) AS SPECIFIED IN PROCUREMENT DOCUMENT.
- FORMING PROCESS. HOT ROLLED
- ADDITIONAL REQUIREMENTS.  
AS FABRICATED - CODE "af"  
PICKLED OVERALL OR SANDBLASTED - CODE "po" or "sb"
- PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A DASH NUMBER FROM TABLE I.



- MARKING. IRON AND STEEL PRODUCTS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-183 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

- IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
- REFERENCED GOVERNMENT (OR NONGOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

REVIEWER ACTIVITIES:  
DLA - IS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.  
This military standard is approved for use by all Departments and Agencies of the Department of Defense.  
Selection for all new engineering and design applications and for repetitive use shall be made from this document, when applicable.

APPROVED 12 OCT 87 REVISED

P. A. NAVY-AS Other Cost ARMY-AR AIR FORCE-99	INTERNATIONAL INTEREST	TITLE PLATE, METAL, CORROSION RESISTANT, TYPE 302	MILITARY STANDARD	
			MSI4504	
PROCUREMENT SPECIFICATION MIL-S-5059	SUPERSEDES:	PAGE   OF		

AMSC N/A

DD FORM 1 MAY 73 672-1 (COORDINATED)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

9515-0641