

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This standard has been approved by the Bureau of Ships Department of the Navy and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

		FED. SUP CLASS 2040	
Requirements			
<p>(A) 1. Halyard cleat shall be commercial bronze with a tensile strength of not less than 30,000 pounds per square inch.</p> <p>2. Drill 1/4 inch diameter holes and countersink for number 12 wood screws.</p> <p>3. Allowable tolerances shall be plus 1/16 inch, minus 0, except that the overall length may be plus or minus 1/2 inch.</p> <p>4. Remove all burrs and sharp edges and finish as indicated on detail.</p> <p>5. To be fitted to ensign and jackstaves for belaying halyards.</p>			
<p>(A) MS Part No.</p> <p>MS15173-1</p>		<p>(A) FIN</p>	
<p>P.A. Ships</p> <p>Other Cust</p>		<p>TITLE</p> <p>(A) CLEAT, ROPE (HALYARD), 4-1/2 INCH, MARINE HARDWARE</p>	
<p>Procurement Specification</p> <p>NONE</p>		<p>MILITARY STANDARD</p> <p>MS 15173 (SHIPS)</p>	
<p>SUPERSEDES:</p>		<p>SHEET 1 OF 1</p>	

DD FORM 1 SEP 57 672N

LIMITED COORDINATION PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Project 2040-0012Sh

APPROVED 9 JULY 1952 REVISED (A) 2 JUN 1959