


FED. SUP CLASS
6240



Characteristic

(B) Industry No. Amperes Volts Bulb Finish Base Filaments Light center length (inches) ^{1/} Hours life (approximate) Lumen output (approximate)	(B) BGB/BGK 0.75 4 S-8 Clear Candelabra, prefocusing, double contact C-6 1-1/8 50 28
---	--

^{1/} Distance from center of light source to plane of locating bosses of prefocusing collar.

(B) Deleted use, type number, and FIIN number.

**(C) CANCELED AFTER 28 MAY 1987.
NO SUPERSEDING STANDARD.**

This military standard is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

Project 6240-N387

MS part number
MS15532-1

(B) Denotes changes

P. A. SH <small>Other Cust</small>	INTERNATIONAL INTEREST	TITLE LAMP, INCANDESCENT, S-8, CANDELABRA, PREFOCUSING, DOUBLE CONTACT	MILITARY STANDARD
PROCUREMENT SPECIFICATION None			MS15532(SH)
SUPERSEDES:		Page 1 of 1	

DD FORM 672-1 (LIMITED COORDINATION)
MAY 73

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

AMSC N/A

DISTRIBUTION STATEMENT A

Approved for public release; distribution unlimited

★U.S. GOVERNMENT PRINTING OFFICE: 1978-703-122/1753

FSC 6240

APPROVED 2 AUG 1954 REVISED (A) 27 JUN 1956 (B) 3 APR 1978 (C) 28 MAY 1987