



STYLE 1

STYLE 2

| DASH NO. | THICKNESS OF MOUNTING | L ±.005 | STYLE | SUPERSEDES |
|----------|-----------------------|------------|-------|------------|
| -5 | 3/32 | 1/8 | 1 | -1 |
| -6 | | | 2 | -2 |
| -7 | 5/32 | 3/16 | 1 | -3 |
| -8 | | | 2 | -4 |
| -9 | 7/32 | 1/4 | 1 | |
| -10 | | | 2 | |
| -11 | 9/32 | 3/8 | 2 | |

NOTES:

- MATERIAL: BRASS, QQ-B-626, COMP. 22, 1/2 HARD.
- FINISH: (a) TIN PLATED IN ACCORDANCE WITH MIL-T-10727, TYPE I, .0003 MIN. THICKNESS OR TYPE II, .0001 MIN. THICKNESS.
OR
(b) TIN-LEAD PLATED IN ACCORDANCE WITH MIL-P-81728, .0003 MIN. THICKNESS (COPPER UNDERPLATE NOT REQUIRED).
- THREADS SHALL BE IN ACCORDANCE WITH HANDBOOK H28.
- DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, DECIMALS SHALL HAVE A TOLERANCE OF $\pm .005$. INTERPRET IN ACCORDANCE WITH USASI Y14.5-1966 (ANSI).
- FOR MOUNTING NUT SEE MS35649.
- REMOVE ALL BURRS AND BREAK ALL SHARP EDGES.

FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS.

(B) ENTIRE STANDARD REVISED

| | | |
|-----------------------------------|--|-------------------|
| P.A. NAVY - AS | TITLE | MILITARY STANDARD |
| Other Cust | TERMINAL, STUD THREADED DOUBLE TURRET | MS17172 (AS) |
| PROCUREMENT SPECIFICATION NONE | SUPERSEDES: MS17172 (WEP) | SHEET 1 OF 1 |

DD FORM 672-1 (Limited coordination)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PLATE NO. 22071

This military standard is approved by NAVAL AIR SYSTEMS COMMAND, Department of the Navy and shall be used by that activity. All other military activities are required to employ this standard where suitable.

APPROVED 21 JUNE 1960 REVISED (A) 6 MARCH 1963 (B) 12 Oct 1972