


FED. SUP CLASS
6680User
CSReview
MD

CS

ARMY

DSA

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.



DASH NO. ①	FORMER PART NO. ①	TYPE	SIZE	"A" DIMENSION ± 3/4 INCH	"B" DIMENSION ± 1 INCH
-3F	MS -7	I	3/8	3	
-4F	MS -8	I	1/2	3 1/2	
-5F	MS -9	I	5/8	3 3/4	
-3S	MS -10	II	3/8		5 1/2
-4S	MS -11	II	1/2		5 1/2
-5S	MS -12	II	5/8		5 3/4

CONNECTION END

TYPE I - EXTERNAL FLARE, REFRIGERATION, DIMENSIONS SPECIFIED ON MS 35873.

TYPE II - SOLDER JOINT, FEMALE, REFRIGERATION, DIMENSIONS SPECIFIED ON MS 35925.

NOTES

- INDICATORS SHALL BE SUITABLE FOR REFRIGERANT TYPE 12 OR TYPE 22 OF DB-F-1421.
- PROTECTIVE SIGHT GLASS CAPS OR COVERS ARE ACCEPTABLE IF INTEGRAL PART OF MANUFACTURER'S DESIGN.
- FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
- REFERENCES DOCUMENTS SHALL BE THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BIDS OR REQUEST FOR PROPOSAL.
- PART NUMBERS: THE MS PART NUMBER CONSISTS OF THE MS NUMBER, PLUS THE DASH NUMBER. EXAMPLE: MS 17798-3F. THE DASH NUMERAL INDICATES END CONNECTION SIZE IN 1/8 INCH INCREMENTS. THE DASH LETTER INDICATES TYPE OF END CONNECTION, I.E., "F" EQUALS FLARE END, "S" EQUALS SOLDER END.

P.A. ARMY OTHER CUST NAVY	GL YD	TITLE INDICATOR, SIGHT, LIQUID REFRIGERANT	MILITARY STANDARD
			MS 17798
Procurement Specification MIL-I-23208		SUPERSEDES:	SHEET 1 OF 1