



FED. SUP CLASS
2925

NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.



PART NO.	A DIA +.020	B DIA +.003	C +.004	USE WITH SPARK PLUG THREAD
MS17840-1	.970	.718	.081	18 mm
MS17840-2	.810	.560	.057	14 mm

MATERIAL: COPPER, AMS 4500
HARDNESS: ROCKWELL F 15 MAX
BREAK SHARP EDGES .015 MAX RADIUS
DIMENSIONS IN INCHES

**(A) CANCELLED AFTER 15 SEPT 1981.
NO SUPERSEDING STANDARD.**

(B) REINSTATED 15 JUNE 1983.

(B) DENOTES CHANGES

P.A. AS	TITLE	MILITARY STANDARD
Other Cust AV	GASKET-SPARK PLUG	MS17840
Procurement Specification CORE	SUPERSEDES:	SHEET 1 OF 1

This standard has been approved by the NAVAL AIR SYSTEMS COMMAND Department of the NAVY and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

APPROVED 8 May 1962 REVISED (A) 15 September 1981 (B) 15 June 1983