

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS (FSC listing).
AF 14, 19+11, 17, 85 Army MO+EL, MI, MU Navy MC, CG+SH₂AS, OS
military standard has been approved by the Department of Defense and is mandatory for all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

<p>STAMP PART NUMBER AND MANUFACTURER'S IDENTIFICATION</p> <p>SEE REQUIREMENT I</p>		<p>FED SUP CLASS 5935</p>	
<p>APPROVED 1 JULY 1963 REVISED (A) 1 MAY 1964 (B) 1 JUNE 1966</p>			
<p>(B) ENTIRE STANDARD REVISED (Project 5935-1355-13)</p>			
<p>PA NAVY-SH Other Cust ARMY-EL AF-11</p>		<p>International Interest</p>	
<p>Procurement Specification MIL-C-22992</p>		<p>TITLE CONNECTOR, RECEPTACLE, DUMMY STOWAGE SUPERSEDES</p>	
<p>MILITARY STANDARD MS18062</p>		<p>SHEET 1 OF 2</p>	

Reviewer/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS (FSC listing).

Navy

Army

AF


Military standard has been approved by the Department of Defense and is mandatory for all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

FED SUP CLASS
5935

SIZE	A THREAD (PLATED) CLASS 2A	D DIA +005 -010	K ±021 -010	M +010 -000	R (TP)	S +021 -020	T DIA ±005 +010 -006	YY DIA +010 -006	AAA	BBB	CCC
12	8750-0 IP-0 2L-DS	.567	.938	.797	.906	1.188	.150	.647	.126 +.007 -.001	.063 +.007 -.001	.0035
14	1.0000-0 IP-0 2L-DS	.692	.938		.969	1.281	.150	.772	.126 +.007 -.001	.063 +.007 -.001	.0035
16	1.1250-0 IP-0 2L-DS	.817	.938		1.062	1.375	.150	.897	.182 +.010 -.001	.108 +.010 -.001	.0070
18	1.2500-0 IP-0 2L-DS	.942	.953		1.156	1.500	.177	1.022			
20	1.3750-0 IP-0 2L-DS	1.068	.953		1.250	1.625		1.148			
22	1.5000-0 IP-0 2L-DS	1.192	.953	.797	1.375	1.750		1.272	.182 +.010 -.001	.108 +.010 -.001	
24	1.7500-0 IP-0 2L-DS	1.317	1.047	.859	1.562	2.000		1.473	.260 +.010 -.001	.155 +.010 -.001	
28	2.0000-0 IP-0 2L-DS	1.536	1.047	.859	1.750	2.250	.177	1.692			
32	2.2500-0 IP-0 2L-DS	1.786	1.110	.922	1.938	2.500	.209	1.942			
36	2.5000-0 IP-0 2L-DS	2.005	1.110	.922	2.188	2.750	.209	2.161			
40	2.7500-0 IP-0 2L-DS	2.255	1.110	.922	2.375	3.000	.209	2.411	.260 +.010 -.001	.155 +.010 -.001	.0070

REQUIREMENTS:

1. Mates with plug shown on standard MS17344.
2. Shell finish shall be designated by the letter C (conductive) or N (non-conductive).
3. The part number shall include finish and size as shown in the example below.



NOTES:

1. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
2. Referenced documents shall be of the issue in effect on date of invitations for bid.
3. All dimensions are in inches. Unless otherwise specified, tolerance is $\pm .016$.

APPROVED 1 JULY 1963 REVISED (B) ENTIRE STANDARD REVISED

P A NAVY-SH	International Interest	TITLE CONNECTOR, RECEPTACLE DUMMY STOWAGE	MILITARY STANDARD
Other Cust ARMY-EL AF-II			MS 18062
Procurement Specification MIL-C-22992		SUPERSEDES:	SHEET 2