



NOTES:

- | | | |
|--|-------|-------|
| 1. Dimensions are in inches. | .603 | 15.32 |
| 2. Unless otherwise specified, tolerance is $\pm .015$ (.38 mm). | 1.002 | 25.45 |
| 3. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm. | 1.317 | 33.45 |
| 4. Tolerance between any two adjacent contact centers shall be $\pm .004$ (.10 mm). Tolerance between any two contact centers, other than adjacent contacts, shall be $\pm .006$ (.15 mm). | | |
| 5. Contact identification may be located on either side of the contact hole but shall appear on the front and rear of each insert. | | |
| 6. For design feature purposes, this standard takes precedence over procurement documents referenced herein. | | |
| 7. Referenced documents shall be of the issue in effect on date of invitation for bid. | | |

DESIGN STANDARD FOR USE WITH MIL-C-28748/2.

ⓑ denotes changes

P.A. Navy - EC	International interest	TITLE CONNECTOR, RECTANGULAR, ELECTRICAL, RACK AND PANEL 9, SIZE 16 SOLDER SOCKET CONTACTS	MILITARY STANDARD
Other Cust AF-80 Army - EL			MS18239
Procurement Specification MIL-C-28748		SUPERSEDES:	Page 1 OF 1