

FED SUP CLASS
8935

SHELL SIZE	GG DIA MIN	HH DIA MAX	JJ MAX	RECOMMENDED PACKING "O" RING
9	317	625		MS 9021-019
11	434	750		-022
13	548	875	688	-024
15	673	1000		-026
17	798	1125		-028
19	899	1250	719	-128
21	1024	1375		-130
23	1149	1500	812	-132
25	1274	1625		-134

- 9 THE POINT AT WHICH A GAGE PIN HAVING THE SAME BASIC DIAMETER AS THE MATING CONTACT AND A SQUARE FACE TOUCHES SOCKET CONTACT SPRING
- 10 RECOMMENDED PACKING IS FOR DIMENSIONS ONLY MATERIAL IS OPTIONAL
- 11 THE GAGE FEATURES FOR GG SHALL BE CC SMALLER THAN THEIR MMC SIZE AT BASIC LOCATION

APPROVED 22 JAN 65 REVISED 11 JAN 66 (C) ENTIRE STD REDRAWN 1 FEB 67 (E) FOR CHANGES SEE SHTS 1 & 2

This standard has been approved by the Department of the USAF and is mandatory for use by that activity. All other military activities are required to employ this standard where applicable.

P A Other Cust (E)	15	TITLE CONNECTOR, RECEPTACLE, ELECTRIC, JAM NUT MOUNTING, SOLDER TYPE, BAYONET COUPLING	MILITARY STANDARD MS 20029
PROCUREMENT SPECIFICATION MIL-C-27599 (USAF)	SUPERSEDES		SHEET 2 OF 2

DD FORM 1 SEP 53 672-1 (Limited coordination)

EDITION OF 1 SEP 57 MAY BE USED