

FED. SUP CLASS  
4760DRILL NO 50  
(.065 - .075)  
CSINK 90° X .094BREAK CORNERS  
DIM N

THREAD T

BREAK CORNERS  
DIM N  
.047 RAD, OPTIONALFITTING END IN ACCORDANCE  
WITH MS33677, STYLE A,  
FOR APPLICABLE PIPE THREAD.

DASH NO	THREAD T NPT	A +.002 -.010	B	C	E MAX	K MAX DIA	L	M RAD	N MAX
0	1/16-27	.188	.188	.094			.312	.031	.010
1	1/8-27	.281	.250				.328		
2	1/4-18	.375	.281				.484		
3	3/8-18	.438	.312		.359	.375			
4	1/2-14	.563	.375		.500	.531	.625		
6	3/4-14	.625	.438			.719	.641		
8	1-11-1/2	.813	.500	.125	.656	.938	.797	.062	.047
10	1-1/4-11-1/2	.938	.562		.672	1.250	.828		
12	1-1/2-11-1/2	1.125	.625			1.469			
16	2-11-1/2	1.313	.688		.688	1.906	.859		
20	2-1/2-8	1.500	.750		1.125	2.031	1.297		

P.A. AIR FORCE-82

TITLE

Other  
ARMY-AR  
NAVY-AS  
AIR FORCE-99

PLUG, PIPE

MILITARY STANDARD

MS20913

PROCUREMENT SPECIFICATION  
MIL-F-5509

SUPERSEDES:

AN913

SHEET 1 OF 2

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PROJECT NO. 4730-0608 19 Jul 1

Review activities: ARMY-NE, MI, GL  
DLA-CS  
User activities: ARMY-AVThis military standard is approved by the Department and Agencies of the  
Department of Defense. Selection for all new engineering and design  
applications and for repetitive use shall be made from this document.

APPROVED 10 JAN 57 REVISED (A) 24 MAY 57 (B) 10 FEB 67 (C) 25 FEB 77 (D) 16 JUN 78 (E) 21 MAR 79 (F) 2 SEP 82 (G) 19 JUL 84

FED. SUP CLASS  
4730

MATERIAL: ALUMINUM ALLOY; COPPER ALLOY; STEEL; CORROSION RESISTANT STEEL (CRES);  
(SEE PROCUREMENT SPECIFICATION).

FINISH: SEE PROCUREMENT SPECIFICATION.

NO GUE LETTER IN PART NUMBER FOR COPPER ALLOY.

ADD D AFTER DASH NO. FOR ALUMINUM ALLOY (EXCEPT 7075-T73).

ADD S AFTER DASH NO. FOR STEEL.

ADD J AFTER DASH NO. FOR CRES, TYPE 304.

ADD K AFTER DASH NO. FOR CRES, TYPE 316.

ADD W AFTER DASH NO. FOR 7075-T73 ALUMINUM ALLOY.

EXAMPLE OF PART NUMBERS:

MS20913-6 - PLUG, 3/4 PIPE THREAD, COPPER ALLOY.

MS20913-6D - PLUG, 3/4 PIPE THREAD, ALUMINUM ALLOY (EXCEPT 7075-T73).

MS20913-6J - PLUG, 3/4 PIPE THREAD, CRES, TYPE 304.

MS20913-6K - PLUG, 3/4 PIPE THREAD, CRES, TYPE 316.

MS20913-6S - PLUG, 3/4 PIPE THREAD, STEEL.

MS20913-6W - PLUG, 3/4 PIPE THREAD, 7075-T73 ALUMINUM ALLOY.

BREAK ALL SHARP EDGES AND REMOVE ALL HANGING BURRS AND SLIVERS WHICH MIGHT BECOME DISLODGED UNDER USAGE.

- (G) AT OPTION OF MANUFACTURER, THE DASH 0 AND DASH 1 SIZES MAY BE FURNISHED WITHOUT MARKING.  
DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS  $\pm .016$ , ANGLES  $\pm 5^\circ$ .  
THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.  
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

Review activities: ARMY - ME, MT, GL User activities: ARMY - AV

DLA - CS

APPROVED 10 JAN 67 REVISED (E) FOR CHANGES SEE PAGES 1 & 2. 21 MAR 79 (F) 2 SEP 82 (G)

P.A. AIR FORCE - 82 Other: ARMY - AR NAVY - AS AIR FORCE - 99	TITLE  PLUG, PIPE	MILITARY STANDARD  MS20913
PROCUREMENT SPECIFICATION MIL - F - 5509	SUPERSEDES: AN913	SHEET 2 OF 2

DD FORM 672-1 (Coordinated)

PROVIDES REVISIONS OF THIS FORM ARE DELETED.

PROJECT NO. 4730-0608

This military standard is approved by the Department and Agencies of the Department of Defense. Sections for all new engineering and design applications and for repetitive use shall be made from this document.